# A Two Level Linear Dependent Type Theory

Qiancheng  $Fu^1$  and Hongwei  $Xi^1$ 

<sup>1</sup>Boston University

November 6, 2022

# 1 Syntax

#### 2 Static Fragment

### Sort Order

$$\overline{\mathbf{U} \sqsubseteq s}$$
  $\overline{\mathbf{L} \sqsubseteq \mathbf{L}}$ 

# Static Context

$$\frac{\Gamma \vdash \qquad \Gamma \vdash A : s \qquad x \in \mathit{fresh}(\Gamma)}{\Gamma, x : A \vdash}$$

# Static Typing

$$\frac{\Gamma \vdash \Gamma}{\Gamma \vdash s : \mathsf{U}} \qquad \frac{\Gamma, x : A \vdash \Gamma}{\Gamma, x : A \vdash x : A} \qquad \frac{\Gamma \vdash A : s \quad \Gamma, x : A \vdash B : r}{\Gamma \vdash \Pi_t(x : A).B : t} \qquad \frac{\Gamma \vdash A : s \quad \Gamma, x : A \vdash B : r}{\Gamma \vdash \Pi_t\{x : A\}.B : t}$$

$$\frac{\Gamma, x : A \vdash m : B}{\Gamma \vdash \lambda_t(x : A).m : \Pi_t(x : A).B} \qquad \frac{\Gamma, x : A \vdash m : B}{\Gamma \vdash \lambda_t\{x : A\}.m : \Pi_t\{x : A\}.B} \qquad \frac{\Gamma \vdash m : \Pi_t(x : A).B \quad \Gamma \vdash n : A}{\Gamma \vdash m \ n : B[n/x]}$$

$$\frac{\Gamma \vdash m : \Pi_t\{x : A\}.B \quad \Gamma \vdash n : A}{\Gamma \vdash m \ n : B[n/x]} \qquad \frac{s \sqsubseteq t \quad r \sqsubseteq t \quad \Gamma \vdash A : s \quad \Gamma, x : A \vdash B : r}{\Gamma \vdash \Sigma_t(x : A).B : t}$$

$$\frac{s \sqsubseteq t \quad \Gamma \vdash A : s \quad \Gamma, x : A \vdash B : r}{\Gamma \vdash \Sigma_t\{x : A\}.B : t} \qquad \frac{\Gamma \vdash \Sigma_t(x : A).B \quad \Gamma \vdash m : A \quad \Gamma \vdash n : B[m/x]}{\Gamma \vdash (m, n)_t : \Sigma_t(x : A).B}$$

$$\frac{\Gamma \vdash \Sigma_t\{x : A\}.B \quad \Gamma \vdash m : A \quad \Gamma \vdash n : B[m/x]}{\Gamma \vdash \{m, n\}_t : \Sigma_t\{x : A\}.B}$$

$$\frac{\Gamma, z : \Sigma_t(x : A).B \vdash C : s \quad \Gamma \vdash m : \Sigma_t(x : A).B \quad \Gamma, x : A, y : B \vdash n : C[\langle x, y \rangle_t/z]}{\Gamma \vdash R^\Sigma}$$

$$\frac{\Gamma, z : \Sigma_t(x : A).B \vdash C : s \qquad \Gamma \vdash m : \Sigma_t(x : A).B \qquad \Gamma, x : A, y : B \vdash n : C[\langle x, y \rangle_t/z]}{\Gamma \vdash \mathbf{R}^{\Sigma}_{[z]C}(m, [x, y]n) : C[m/z]}$$

$$\frac{\Gamma,z:\Sigma_t\{x:A\}.B\vdash C:s\qquad \Gamma\vdash m:\Sigma_t\{x:A\}.B\qquad \Gamma,x:A,y:B\vdash n:C[\{x,y\}_t/z]}{\Gamma\vdash \mathbf{R}^\Sigma_{[z]C}(m,[x,y]n):C[m/z]}$$

$$\frac{\Gamma, x: A, y: A, p: x \equiv_A y \vdash B: s \qquad \Gamma, z: A \vdash H: B[z/x, z/y, \operatorname{refl} z/p] \qquad \Gamma \vdash P: m \equiv_A n}{\Gamma \vdash \mathbf{R}^{\equiv}_{[x,y,p]B}([z]H, P): B[m/x, n/y, P/p]}$$

$$\frac{\Gamma \vdash B : s \qquad \Gamma \vdash m : A \qquad A \simeq B}{\Gamma \vdash m : B}$$

# 3 Dynamic Fragment

# **Dynamic Context**

$$\frac{\Gamma;\Delta \vdash \qquad \Gamma \vdash A:s \qquad x \in \mathit{fresh}(\Gamma)}{\Gamma,x:A;\Delta,x:_s A \vdash} \qquad \qquad \frac{\Gamma;\Delta \vdash \qquad \Gamma \vdash A:s \qquad x \in \mathit{fresh}(\Gamma)}{\Gamma,x:A;\Delta \vdash}$$

# Context Merge

$$\frac{\Delta_1 \cup \Delta_2 = \Delta \quad x \in \mathit{fresh}(\Delta)}{(\Delta_1, x :_U A) \cup (\Delta_2, x :_U A) = (\Delta, x :_U A)}$$
 
$$\frac{\Delta_1 \cup \Delta_2 = \Delta \quad x \in \mathit{fresh}(\Delta)}{(\Delta_1, x :_L A) \cup \Delta_2 = (\Delta, x :_L A)}$$
 
$$\frac{\Delta_1 \cup \Delta_2 = \Delta \quad x \in \mathit{fresh}(\Delta)}{\Delta_1 \cup (\Delta_2, x :_L A) = (\Delta, x :_L A)}$$

# Context Constraint

$$\frac{\Delta \triangleright \mathbf{U}}{\Delta, x :_{\mathbf{U}} A \triangleright \mathbf{U}} \qquad \qquad \frac{\Delta \triangleright \mathbf{L}}{\Delta, x :_{s} A \triangleright \mathbf{L}}$$

# **Dynamic Typing**

### 4 Erasure

# **Erasure Relation**

$$\frac{\Gamma, x : A; \Delta, x :_s A \vdash \Delta \rhd \cup}{\Gamma, x : A; \Delta, x :_s A \vdash x \sim x : A} \qquad \frac{\Gamma, x : A; \Delta, x :_s A \vdash m \sim m' : B}{\Gamma; \Delta \vdash \lambda_t(x : A).m \sim \lambda_t(x : \Box).m' : \Pi_t(x : A).B}$$

$$\frac{\Gamma, x : A; \Delta, h = m \sim m' : B}{\Gamma; \Delta \vdash \lambda_t(x : A).m \sim \lambda_t(x : \Box).m' : \Pi_t(x : A).B} \qquad \frac{\Gamma; \Delta \vdash m \sim m' : \Pi_t(x : A).B}{\Gamma; \Delta \vdash \lambda_t(x : A).m \sim m' : n' : B[n/x]}$$

$$\frac{\Gamma; \Delta \vdash m \sim m' : \Pi_t(x : A).B}{\Gamma; \Delta \vdash m \sim m' : B[n/x]} \qquad \frac{\Gamma; \Delta \vdash m \sim m' : \Pi_t(x : A).B}{\Gamma; \Delta \vdash m \sim m' : B[n/x]}$$

$$\frac{\Gamma \vdash \Sigma_t(x : A).B : t}{\Gamma; \Delta \vdash m \sim m' : A} \qquad \frac{\Gamma; \Delta_t \vdash m \sim m' : B[m/x]}{\Gamma; \Delta_t \vdash m \sim m' : A} \qquad \frac{\Gamma; \Delta_t \vdash m \sim m' : B[m/x]}{\Gamma; \Delta_t \vdash m \sim m' : A}$$

$$\frac{\Gamma \vdash \Sigma_t(x : A).B : t}{\Gamma; \Delta \vdash m \sim m' : A} \qquad \frac{\Gamma; \Delta_t \vdash n : B[m/x]}{\Gamma; \Delta \vdash \{m, n\}_t \sim \{m', n'\}_t : \Sigma_t(x : A).B}$$

$$\frac{\Gamma; \Delta \vdash m \sim m' : \Sigma_t(x : A).B}{\Gamma; \Delta_t \vdash m \sim m' : \Sigma_t(x : A).B} \qquad \frac{\Gamma, x : A, y : B; \Delta_t(x : A).B}{\Gamma; \Delta_t \vdash m \sim m' : \Sigma_t(x : A).B}$$

$$\frac{\Gamma; \Sigma \vdash \Sigma_t(x : A).B \vdash C : s}{\Gamma; \Delta_t \vdash m \sim m' : \Sigma_t(x : A).B} \qquad \Gamma, x : A, y : B; \Delta_t(x : A).B \vdash C : S$$

$$\frac{\Gamma; \Delta \vdash m \sim m' : \Sigma_t(x : A).B}{\Gamma; \Delta_t \vdash m \sim m' : \Sigma_t(x : A).B} \qquad \Gamma, x : A, y : B; \Delta_t(x : x) \vdash C[\{x, y\}_t/z]$$

$$\frac{\Gamma; \Delta \vdash m \sim m' : A}{\Gamma; \Delta \vdash m \sim m' : A} \qquad \frac{\Gamma; \Delta \vdash m \sim m' : A \&_t B}{\Gamma; \Delta \vdash m \sim m' : A} \qquad \frac{\Gamma; \Delta \vdash m \sim m' : A \&_t B}{\Gamma; \Delta \vdash m \sim m' : B}$$

$$\frac{\Gamma \vdash B : s}{\Gamma; \Delta \vdash m \sim m' : A} \qquad \frac{\Gamma; \Delta \vdash m \sim m' : A}{\Gamma; \Delta \vdash m \sim m' : B}$$

# 5 Static Semantics

# Static Reduction

$$\begin{array}{c} A \hookrightarrow A' \\ \hline \Pi_t(x:A).B \leadsto \Pi_t(x:A').B \\ \hline \Pi_t(x:A).B \leadsto \Pi_t(x:A').B \\ \hline \Pi_t(x:A).B \leadsto \Pi_t(x:A).B' \\ \hline \Pi_t\{x:A).B \leadsto \Pi_t(x:A).B' \\ \hline \Pi_t\{x:A).B \leadsto \Pi_t\{x:A).B' \\ \hline \Pi_t\{x:A).B \leadsto \Pi_t\{x:A).B' \\ \hline \Lambda_t(x:A).M \leadsto \Lambda_t(x:A').m \\ \hline \Lambda_t(x:A).M \leadsto \Lambda_t(x:A).M' \\ \hline \Lambda_t(x:A).M \leadsto \Lambda_t(x:A).M' \\ \hline \Lambda_t(x:A).M \leadsto \Lambda_t(x:A).M' \\ \hline \Lambda_t\{x:A\}.M \leadsto \Lambda_t\{x:A'\}.M \\ \hline \Lambda_t\{x:A\}.M \leadsto \Lambda_t\{x:A'\}.M \\ \hline \Lambda_t\{x:A\}.M \leadsto \Lambda_t\{x:A\}.M' \\ \hline \Lambda_t\{x:A\}.M \leadsto \Lambda_t\{x:A'\}.M \\ \hline \Lambda_t\{x:A\}.M \leadsto \Lambda_t\{x:A\}.M' \\ \hline \Lambda_t\{x:A\}.M \leadsto \Lambda_t\{x:A\}.M \\ \hline \Lambda_t\{x:A\}.M \Longrightarrow \Lambda_t\{x$$

#### Conversion

$$\frac{A \simeq B \qquad B \leadsto C}{A \simeq A} \qquad \frac{A \simeq B \qquad C \leadsto B}{A \simeq C}$$

# 6 Dynamic Semantics

### Value

$$\frac{1}{x \text{ value}} \quad \frac{1}{\lambda_t(x:A).m \text{ value}} \quad \frac{u \text{ value}}{\lambda_t(x:A).m \text{ value}} \quad \frac{u \text{ value}}{\langle u,v\rangle_t \text{ value}} \quad \frac{v \text{ value}}{\{v,m\}_t \text{ value}} \quad \frac{v \text{ value}}{(m,n)_t \text{ value}}$$

# Dynamic Reduction

$$\frac{m \rightsquigarrow m'}{m \ n \rightsquigarrow m' \ n} \qquad \frac{n \rightsquigarrow n'}{m \ n \rightsquigarrow m \ n'} \qquad \frac{v \text{ value}}{(\lambda_t(x:A).m) \ v \rightsquigarrow m[v/x]} \qquad \overline{(\lambda_t\{x:A\}.m) \ n \rightsquigarrow m[n/x]}$$

$$\frac{m \rightsquigarrow m'}{\langle m, n \rangle_t \rightsquigarrow \langle m', n \rangle_t} \qquad \frac{n \rightsquigarrow n'}{\langle m, n \rangle_t \rightsquigarrow \langle m, n' \rangle_t} \qquad \frac{m \rightsquigarrow m'}{\{m, n\}_t \rightsquigarrow \{m', n\}_t} \qquad \frac{m \rightsquigarrow m'}{R^{\Sigma}_{[z]A}(m, [x, y]n) \rightsquigarrow R^{\Sigma}_{[z]A}(m', [x, y]n)}$$

$$\frac{u \text{ value} \qquad v \text{ value}}{R^{\Sigma}_{[z]A}(\langle u, v \rangle_t, [x, y]n) \rightsquigarrow n[u/x, v/y]} \qquad \frac{v \text{ value}}{R^{\Sigma}_{[z]A}(\{v, m\}_t, [x, y]n) \rightsquigarrow n[v/x, m/y]} \qquad \frac{m \rightsquigarrow m'}{\pi_1 m \rightsquigarrow \pi_1 m'}$$

$$\frac{m \rightsquigarrow m'}{\pi_2 m \rightsquigarrow \pi_2 m'} \qquad \overline{\pi_1 (m, n)_t \rightsquigarrow m} \qquad \overline{\pi_2 (m, n)_t \rightsquigarrow n}$$

### **Erasure-Dynamic Reduction**

**Theorem 1.** For any dynamic typing  $\Gamma$ ;  $\Delta \vdash m : A$ , there exists m' such that  $\Gamma$ ;  $\Delta \vdash m \sim m' : A$ .

**Theorem 2.** For any erasure relation  $\Gamma$ ;  $\Delta \vdash m \sim m'$ : A and dynamic reduction  $m' \rightsquigarrow n'$ , there exists n such that the following diagram commutes.

**Theorem 3.** For any erasure relation  $\epsilon$ ;  $\epsilon \vdash m \sim m' : A$ , then m' is a value or there exists n' such that  $m' \rightsquigarrow n'$ .