

EAS 5830: BLOCKCHAINS

WETH

Professor Brett Hemenway Falk



Penn
Engineering
UNIVERSITY of PENNSYLVANIA

Wrapped Ether

- o Problem:
 - ETH is transferred differently than ERC-20s
- o Solution
 - Make an ERC-20 version of ETH



```
function buyPunk(uint punkIndex) payable {
    if (!allPunksAssigned) throw;
    Offer offer = punksOfferedForSale[punkIndex];
    if (punkIndex >= 10000) throw;
    if (!offer.isForSale) throw;           // punk not actually for sale
    if (offer.onlySellTo != 0x0 && offer.onlySellTo != msg.sender) throw; // punk not supposed to be sold to this user
    if (msg.value < offer.minValue) throw; // Didn't send enough ETH
    if (offer.seller != punkIndexToAddress[punkIndex]) throw; // Seller no longer owner of punk
}
```

```
function buyPunk(uint punkIndex) payable {  
    if (!allPunksAssigned) throw;  
    Offer offer = punksOfferedForSale[punkIndex];  
    if (punkIndex >= 10000) throw;  
    if (!offer.isForSale) throw;           // punk not actually for sale  
    if (offer.onlySellTo != 0x0 && offer.onlySellTo != msg.sender) throw; // punk not supposed to be sold to this user  
    if (msg.value < offer.minValue) throw; // Didn't send enough ETH  
    if (offer.seller != punkIndexToAddress[punkIndex]) throw; // Seller no longer owner of punk
```





```
function buyPunk(uint punkIndex) payable {  
    if (!allPunksAssigned) throw;  
    Offer offer = punksOfferedForSale[punkIndex];  
    if (punkIndex >= 10000) throw;  
    if (!offer.isForSale) throw; // punk not actually for sale  
    if (offer.onlySellTo != 0x0 && offer.onlySellTo != msg.sender) throw; // punk not supposed to be sold to this user  
    if (msg.value < offer.minValue) throw; // Didn't send enough ETH  
    if (offer.seller != punkIndexToAddress[punkIndex]) throw; // Seller no longer owner of punk
```



```
function withdraw() {  
    if (!allPunksAssigned) throw;  
    uint amount = pendingWithdrawals[msg.sender];  
    // Remember to zero the pending refund before  
    // sending to prevent re-entrancy attacks  
    pendingWithdrawals[msg.sender] = 0;  
    msg.sender.transfer(amount);  
}
```



```
function withdraw() {  
    if (!allPunksAssigned) throw;  
    uint amount = pendingWithdrawals[msg.sender];  
    // Remember to zero the pending refund before  
    // sending to prevent re-entrancy attacks  
    pendingWithdrawals[msg.sender] = 0;  
    msg.sender.transfer(amount);  
}
```

Stop Using Solidity's transfer() Now

SEPTEMBER 02, 2019 BY STEVE MARX

Transferring ETH


- o `receivingAddress.transfer(amount);`
 - Reverts on fail
 - Only sends 2300 gas
- o `receivingAddress.send(amount);`
 - Returns false on fail
 - Only sends 2300 gas
- o `(bool success, bytes memory data) = receivingAddress.call{value: amount}("");`
 - Allows for re-entrancy
 - Transfer all gas to receiving contract

ERC20s transfer differently

```
397     function transferToUser(address _reserve, address payable _user, uint256 _amount)
398         external
399         onlyLendingPool
400     {
401         if (_reserve != EthAddressLib.ethAddress()) {
402             ERC20(_reserve).safeTransfer(_user, _amount);
403         } else {
404             //solium-disable-next-line
405             (bool result, ) = _user.call.value(_amount).gas(50000)("");
406             require(result, "Transfer of ETH failed");
407         }
408     }
409
```

ERC20s transfer differently

```
397     function transferToUser(address _reserve, address payable _user, uint256 _amount)
398         external
399         onlyLendingPool
400     {
401         if (_reserve != EthAddressLib.ethAddress()) {
402             ERC20(_reserve).safeTransfer(_user, _amount);
403         } else {
404             //solium-disable-next-line
405             (bool result, ) = _user.call.value(_amount).gas(50000)("");
406             require(result, "Transfer of ETH failed");
407         }
408     }
409
```



ERC20s transfer differently

```
397     function transferToUser(address _reserve, address payable _user, uint256 _amount)
398         external
399         onlyLendingPool
400     {
401         if (_reserve != EthAddressLib.ethAddress()) {
402             ERC20(_reserve).safeTransfer(_user, _amount);
403         } else {
404             //solium-disable-next-line
405             (bool result, ) = _user.call.value(_amount).gas(50000)("");
406             require(result, "Transfer of ETH failed");
407         }
408     }
409
```

Handling ETH and ERC-20s

- o Uniswap v1 only allowed ETH \leftrightarrow ERC-20
 - No ERC-20 \leftrightarrow ERC-20 trades
- o Uniswap v2 only allows ERC-20 \leftrightarrow ERC-20
 - No ETH on the platform



Alice

Deposit 5 ETH



ERC20

Alice	5
Bob	11
Charlie	8

Deployed by
[OxLabs](#) in 2017

```
contract WETH9 {
    string public name      = "Wrapped Ether";
    string public symbol    = "WETH";
    uint8 public decimals = 18;

    event Approval(address indexed src, address indexed guy, uint wad);
    event Transfer(address indexed src, address indexed dst, uint wad);
    event Deposit(address indexed dst, uint wad);
    event Withdrawal(address indexed src, uint wad);

    mapping (address => uint) public balanceOf;
    mapping (address => mapping (address => uint)) public allowance;

    function() public payable {
        deposit();
    }
    function deposit() public payable {
        balanceOf[msg.sender] += msg.value;
        Deposit(msg.sender, msg.value);
    }
    function withdraw(uint wad) public {
        require(balanceOf[msg.sender] >= wad);
        balanceOf[msg.sender] -= wad;
        msg.sender.transfer(wad);
        Withdrawal(msg.sender, wad);
    }

    function totalSupply() public view returns (uint) {
        return this.balance;
    }
}
```

```
contract WETH9 {
    string public name      = "Wrapped Ether";
    string public symbol    = "WETH";
    uint8  public decimals = 18;

    event Approval(address indexed src, address indexed guy, uint wad);
    event Transfer(address indexed src, address indexed dst, uint wad);
    event Deposit(address indexed dst, uint wad);
    event Withdrawal(address indexed src, uint wad);

    mapping (address => uint)      public balanceOf;
    mapping (address => mapping (address => uint)) public allowance;

    function() public payable {
        deposit();
    }
    function deposit() public payable {
        balanceOf[msg.sender] += msg.value;
        Deposit(msg.sender, msg.value);
    }
    function withdraw(uint wad) public {
        require(balanceOf[msg.sender] >= wad);
        balanceOf[msg.sender] -= wad;
        msg.sender.transfer(wad);
        Withdrawal(msg.sender, wad);
    }

    function totalSupply() public view returns (uint) {
        return this.balance;
    }
}
```



```
contract WETH9 {
    string public name      = "Wrapped Ether";
    string public symbol    = "WETH";
    uint8 public decimals = 18;

    event Approval(address indexed src, address indexed guy, uint wad);
    event Transfer(address indexed src, address indexed dst, uint wad);
    event Deposit(address indexed dst, uint wad);
    event Withdrawal(address indexed src, uint wad);

    mapping (address => uint) public balanceOf;
    mapping (address => mapping (address => uint)) public allowance;

    function() public payable {
        deposit();
    }
    function deposit() public payable {
        balanceOf[msg.sender] += msg.value;
        Deposit(msg.sender, msg.value);
    }
    function withdraw(uint wad) public {
        require(balanceOf[msg.sender] >= wad);
        balanceOf[msg.sender] -= wad;
        msg.sender.transfer(wad);
        Withdrawal(msg.sender, wad);
    }

    function totalSupply() public view returns (uint) {
        return this.balance;
    }
}
```

```
contract WETH9 {
    string public name      = "Wrapped Ether";
    string public symbol    = "WETH";
    uint8  public decimals = 18;

    event Approval(address indexed src, address indexed guy, uint wad);
    event Transfer(address indexed src, address indexed dst, uint wad);
    event Deposit(address indexed dst, uint wad);
    event Withdrawal(address indexed src, uint wad);

    mapping (address => uint)      public balanceOf;
    mapping (address => mapping (address => uint)) public allowance;

    function() public payable {
        deposit();
    }
    function deposit() public payable {
        balanceOf[msg.sender] += msg.value;
        Deposit(msg.sender, msg.value);
    }
    function withdraw(uint wad) public {
        require(balanceOf[msg.sender] >= wad);
        balanceOf[msg.sender] -= wad;
        msg.sender.transfer(wad);
        Withdrawal(msg.sender, wad);
    }

    function totalSupply() public view returns (uint) {
        return this.balance;
    }
}
```

Overview

ETH BALANCE

◆ 3,073,678.730047328926764941 ETH

ETH VALUE

\$5,155,050,929.90 (@ \$1,677.16/ETH)

TOKEN HOLDINGS

>\$1,293,863.61 (>120 Tokens)



Overview

ETH BALANCE

3,073,678.730047328926764941 ETH

ETH VALUE

\$5,155,050,929.90 (@ \$1,677.16/ETH)

TOKEN HOLDINGS

>\$1,293,863.61 (>120 Tokens)



ERC-20 Tokens (>100)



Wrapped Ether (WETH)

743.19536996 WETH

\$1,246,457.53

@1,677.16



Tether USD (USDT)

20,231.102208 USDT

\$20,227.89

@0.9998



SHIBA INU (SHIB)

1,465,516,633.86828 SHIB

\$10,786.20

@0.00



USDC (USDC)

5,282.268984 USDC

\$5,279.86

@0.9995