
EAS 5830: BLOCKCHAINS

The EVM

Professor Brett Hemenway Falk



 The Ethereum Virtual Machine determines how programs (contracts) are executed


- The Ethereum Virtual Machine determines how programs (contracts) are executed
- The EVM is the blockchain's Operating System

- The Ethereum Virtual Machine determines how programs (contracts) are executed
- The EVM is the blockchain's Operating System
- The EVM is single threaded

- The Ethereum Virtual Machine determines how programs (contracts) are executed
- The EVM is the blockchain's Operating System
- The EVM is single threaded
 - No parallelism

- The Ethereum Virtual Machine determines how programs (contracts) are executed
- The EVM is the blockchain's Operating System
- The EVM is single threaded
 - No parallelism
 - Transactions are executed one at a time and in order

Riskless arbitrage




Exchange 2

ETH - \$2100

Riskless arbitrage

Exchange 1


ETH - \$1900







EVM Bytecode


EVM OpCodes



EVM Precompiles







Contract Source Code Verified (Exact Match)

Contract Name:	BoredApeYachtClub	Optimization Enabled:
Compiler Version	v0.7.0+commit.9e61f92b	Other Settings:

Contract Source Code (Solidity)

```
*Submitted for verification at Etherscan.io on 2021-04-22
 3
    */
    // File: @openzeppelin/contracts/utils/Context.sol
    // SPDX-License-Identifier: MIT
    pragma solidity >=0.6.0 <0.8.0;
10
11 - /*
12 * @dev Provides information about the current execution context, including the
* sender of the transaction and its data. While these are generally available
   * via msg.sender and msg.data, they should not be accessed in such a direct
    * manner, since when dealing with GSN meta-transactions the account sending and
     * paying for execution may not be the actual sender (as far as an application
17
     * is concerned).
18
     * This contract is only required for intermediate, library-like contracts.
20
```

forge verify-contract

NAME

forge-verify-contract - Verify smart contracts on a chosen verification provider.

SYNOPSIS

forge verify-contract [options] address contract

DESCRIPTION

Verifies a smart contract on a chosen verification provider.

You must provide:

- The contract address
- The contract name or the path to the contract (read below) In case of Etherscan verification, you must also provide:
- Your Etherscan API key, either by passing it as an argument or setting ETHERSCAN_API_KEY



• Address is 20 bytes

- Address is 20 bytes
 - 40 hex digits

- Address is 20 bytes
 - 40 hex digits
- Two types of accounts

- Address is 20 bytes
 - 40 hex digits
- Two types of accounts
 - Contracts

- Address is 20 bytes
 - 40 hex digits
- Two types of accounts
 - Contracts
 - No private key

- Address is 20 bytes
 - 40 hex digits
- Two types of accounts
 - Contracts
 - No private key
 - Cannot initiate transactions

- Address is 20 bytes
 - 40 hex digits
- Two types of accounts
 - Contracts
 - No private key
 - Cannot initiate transactions
 - Address is last 20 bytes of (Keccak) hash of sender address + nonce

- Address is 20 bytes
 - 40 hex digits
- Two types of accounts
 - Contracts
 - No private key
 - Cannot initiate transactions
 - Address is last 20 bytes of (Keccak) hash of sender address + nonce
 - Externally Owned Accounts (EOAs)

- Address is 20 bytes
 - 40 hex digits
- Two types of accounts
 - Contracts
 - No private key
 - Cannot initiate transactions
 - Address is last 20 bytes of (Keccak) hash of sender address + nonce
 - Externally Owned Accounts (EOAs)
 - Address is last 20 bytes of (Keccak) hash of public key

• It's hard to distinguish whether an account is an EOA or contract

- It's hard to distinguish whether an account is an EOA or contract
- if web3.eth.get code returns nonzero, then it's a contract

- It's hard to distinguish whether an account is an EOA or contract
- if <u>web3.eth.get_code</u> returns nonzero, then it's a contract
 - o if it returns 0, it may still be a contract

- It's hard to distinguish whether an account is an EOA or contract
- if <u>web3.eth.get_code</u> returns nonzero, then it's a contract
 - o if it returns 0, it may still be a contract
- If you can find a public key corresponding to the account, then it's an EOA

- It's hard to distinguish whether an account is an EOA or contract
- if <u>web3.eth.get_code</u> returns nonzero, then it's a contract
 - if it returns 0, it may still be a contract
- If you can find a public key corresponding to the account, then it's an EOA
 - Transactions originating from the account will have a signature

- It's hard to distinguish whether an account is an EOA or contract
- if <u>web3.eth.get_code</u> returns nonzero, then it's a contract
 - if it returns 0, it may still be a contract
- If you can find a public key corresponding to the account, then it's an EOA
 - Transactions originating from the account will have a signature
- Some accounts cannot be distinguished:

- It's hard to distinguish whether an account is an EOA or contract
- if <u>web3.eth.get_code</u> returns nonzero, then it's a contract
 - if it returns 0, it may still be a contract
- If you can find a public key corresponding to the account, then it's an EOA
 - Transactions originating from the account will have a signature
- Some accounts cannot be distinguished:
 - Find an address where you could deploy a contract

- It's hard to distinguish whether an account is an EOA or contract
- if <u>web3.eth.get_code</u> returns nonzero, then it's a contract
 - if it returns 0, it may still be a contract
- If you can find a public key corresponding to the account, then it's an EOA
 - Transactions originating from the account will have a signature
- Some accounts cannot be distinguished:
 - Find an address where you could deploy a contract
 - Send ETH to that address (that address will be created)

- It's hard to distinguish whether an account is an EOA or contract
- if <u>web3.eth.get_code</u> returns nonzero, then it's a contract
 - if it returns 0, it may still be a contract
- If you can find a public key corresponding to the account, then it's an EOA
 - Transactions originating from the account will have a signature
- Some accounts cannot be distinguished:
 - Find an address where you could deploy a contract
 - Send ETH to that address (that address will be created)
 - At that point, it looks like an EOA (no TXs originating from the address)

- It's hard to distinguish whether an account is an EOA or contract
- if <u>web3.eth.get_code</u> returns nonzero, then it's a contract
 - if it returns 0, it may still be a contract
- If you can find a public key corresponding to the account, then it's an EOA
 - Transactions originating from the account will have a signature
- Some accounts cannot be distinguished:
 - Find an address where you could deploy a contract
 - Send ETH to that address (that address will be created)
 - At that point, it looks like an EOA (no TXs originating from the address)
 - You can later deploy a contract to that address

The EVM is not Ethereum

• The EVM is completely separate from the consensus mechanism

EVM chains





Copyright 2020 University of Pennsylvania No reproduction or distribution without permission.