

Presentation Title

Gang Li
Deakin University

(None)






Table of Content



Background



TULIP

Team for Universal Learning and Intelligent Processing



Pause longer

■ A



Pause longer

- A
- B





Pause longer

- A
- B





Pause longer

- A
- B
- C





Aggregation Functions



TULIP

Team for Universal Learning and Intelligent Processing



Multi-Criteria Decision Making

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	?
P_2	0.1	0.6	0.5	?
P_3	0.6	0.4	0.3	?



Multi-Criteria Decision Making

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	?
P_2	0.1	0.6	0.5	?
P_3	0.6	0.4	0.3	?



Multi-Criteria Decision Making

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	?
P_2	0.1	0.6	0.5	?
P_3	0.6	0.4	0.3	?



Multi-Criteria Decision Making

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	?
P_2	0.1	0.6	0.5	?
P_3	0.6	0.4	0.3	?



Multi-Criteria Decision Making

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	?
P_2	0.1	0.6	0.5	?
P_3	0.6	0.4	0.3	?

? Which is the *best* product



Aggregation Functions — WAM

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	
P_2	0.1	0.6	0.5	
P_3	0.6	0.4	0.3	



Aggregation Functions — WAM

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	
P_2	0.1	0.6	0.5	
P_3	0.6	0.4	0.3	
Weights	0.5	0.25	0.25	

■ Weighted Arithmetic Mean



Aggregation Functions — WAM

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	?
P_2	0.1	0.6	0.5	
P_3	0.6	0.4	0.3	
Weights	0.5	0.25	0.25	

■ Weighted Arithmetic Mean

$P_1 \quad 0.5(0.4) + 0.25(0.3) + 0.25(0.8) = 0.475$



Aggregation Functions — WAM

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	0.475
P_2	0.1	0.6	0.5	?
P_3	0.6	0.4	0.3	
Weights	0.5	0.25	0.25	

■ Weighted Arithmetic Mean

$$\begin{aligned} P_1 & 0.5(0.4) + 0.25(0.3) + 0.25(0.8) = 0.475 \\ P_2 & 0.5(0.1) + 0.25(0.6) + 0.25(0.5) = 0.325 \end{aligned}$$



Aggregation Functions — WAM

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	0.475
P_2	0.1	0.6	0.5	0.325
P_3	0.6	0.4	0.3	?
Weights	0.5	0.25	0.25	

■ Weighted Arithmetic Mean

$P_1 \quad 0.5(0.4) + 0.25(0.3) + 0.25(0.8) = 0.475$
 $P_2 \quad 0.5(0.1) + 0.25(0.6) + 0.25(0.5) = 0.325$
 $P_3 \quad 0.5(0.6) + 0.25(0.4) + 0.25(0.3) = 0.950$



Aggregation Functions — WAM

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	0.475
P_2	0.1	0.6	0.5	0.325
P_3	0.6	0.4	0.3	0.950
Weights	0.5	0.25	0.25	

■ Weighted Arithmetic Mean

$P_1 \quad 0.5(0.4) + 0.25(0.3) + 0.25(0.8) = 0.475$
 $P_2 \quad 0.5(0.1) + 0.25(0.6) + 0.25(0.5) = 0.325$
 $P_3 \quad 0.5(0.6) + 0.25(0.4) + 0.25(0.3) = 0.950$



Aggregation Functions — WAM

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	0.475
P_2	0.1	0.6	0.5	0.325
P_3	0.6	0.4	0.3	0.950
Weights	0.5	0.25	0.25	

■ Weighted Arithmetic Mean

$P_1 \quad 0.5(0.4) + 0.25(0.3) + 0.25(0.8) = 0.475$
 $P_2 \quad 0.5(0.1) + 0.25(0.6) + 0.25(0.5) = 0.325$
 $P_3 \quad 0.5(0.6) + 0.25(0.4) + 0.25(0.3) = 0.950$

? *the **best** product*



Aggregation Functions — WAM

Problem A customer wants to select a product that is *inexpensive*, *good quality*, and with *good service*. Choices have been narrowed down to three products with following utility values:

Product	Price	Quality	Service	Overall Rating
P_1	0.4	0.3	0.8	0.475
P_2	0.1	0.6	0.5	0.325
P_3	0.6	0.4	0.3	0.950
Weights	0.5	0.25	0.25	

■ Weighted Arithmetic Mean

$P_1 \quad 0.5(0.4) + 0.25(0.3) + 0.25(0.8) = 0.475$
 $P_2 \quad 0.5(0.1) + 0.25(0.6) + 0.25(0.5) = 0.325$
 $P_3 \quad 0.5(0.6) + 0.25(0.4) + 0.25(0.3) = 0.950$

? *the best product*



Fuzzy Measure

Definition

A *fuzzy measure* is a set of functions $v : 2^N \rightarrow [0, 1]$ on all possible combinations of n criteria, which satisfies:

- $v(A) \leq v(B)$ whenever $A \subset B$;
- $v(\emptyset) = 0$ and $v(N) = 1$.





Fuzzy Measure

Definition

A *fuzzy measure* is a set of functions $v : 2^N \rightarrow [0, 1]$ on all possible combinations of n criteria, which satisfies:

- $v(A) \leq v(B)$ whenever $A \subset B$;
 - $v(\emptyset) = 0$ and $v(N) = 1$.
-
- Since $A \subseteq N$ is a *coalition* of criteria, $v(A)$ represents the importance of this coalition.





Choquet Integral — Summary

- The Choquet Integral generalises many important aggregation functions including the *mean*, *weighted arithmetic mean*, *maximum*, *minimum* and *ordered weighted average*.
 - ◆ Unlike WAM which allocates a weight to each input, it assigns a weight to all the subsets of inputs, hence 2^n parameters.
- *K-Additivity*: k -additive fuzzy measures model no interaction of groups with more than k criteria
 - ◆ It allows an arbitrary reduction in complexity at the expense of modelling ability.
 - ◆ In the case of 3-additivity, we can model the interactions of pairs and triples, but not of larger groups.





Choquet Integral — Summary

- The Choquet Integral generalises many important aggregation functions including the *mean*, *weighted arithmetic mean*, *maximum*, *minimum* and *ordered weighted average*.
 - ◆ Unlike WAM which allocates a weight to each input, it assigns a weight to all the subsets of inputs, hence 2^n parameters.
- *K-Additivity*: k -additive fuzzy measures model no interaction of groups with more than k criteria
 - ◆ It allows an arbitrary reduction in complexity at the expense of modelling ability.
 - ◆ In the case of 3-additivity, we can model the interactions of pairs and triples, but not of larger groups.



Choquet Integral — Summary

- The Choquet Integral generalises many important aggregation functions including the *mean*, *weighted arithmetic mean*, *maximum*, *minimum* and *ordered weighted average*.
 - ◆ Unlike WAM which allocates a weight to each input, it assigns a weight to all the subsets of inputs, hence 2^n parameters.
- *K-Additivity*: k -additive fuzzy measures model no interaction of groups with more than k criteria
 - ◆ It allows an arbitrary reduction in complexity at the expense of modelling ability.
 - ◆ In the case of 3-additivity, we can model the interactions of pairs and triples, but not of larger groups.





Choquet Integral — Summary

- The Choquet Integral generalises many important aggregation functions including the *mean*, *weighted arithmetic mean*, *maximum*, *minimum* and *ordered weighted average*.
 - ◆ Unlike WAM which allocates a weight to each input, it assigns a weight to all the subsets of inputs, hence 2^n parameters.
- *K-Additivity*: k -additive fuzzy measures model no interaction of groups with more than k criteria
 - ◆ It allows an arbitrary reduction in complexity at the expense of modelling ability.
 - ◆ In the case of 3-additivity, we can model the interactions of pairs and triples, but not of larger groups.





Choquet Integral — Summary

- The Choquet Integral generalises many important aggregation functions including the *mean*, *weighted arithmetic mean*, *maximum*, *minimum* and *ordered weighted average*.
 - ◆ Unlike WAM which allocates a weight to each input, it assigns a weight to all the subsets of inputs, hence 2^n parameters.
- *K-Additivity*: k -additive fuzzy measures model no interaction of groups with more than k criteria
 - ◆ It allows an arbitrary reduction in complexity at the expense of modelling ability.
 - ◆ In the case of 3-additivity, we can model the interactions of pairs and triples, but not of larger groups.



Application and Analysis



TULIP

Team for Universal Learning and Intelligent Processing

Presentation Title

Last Changed by: (NONE) (None)-(None) ((None)) – 10 / ??



Data Collection

Source *Tripadvisor* website (www.tripadvisor.com)

Extractor *Visual Web Ripper*

Data

- 8561 records about ratings on *Singapore* hotel *features* and overall *ratings*;
- *Demographic, Region, Travel Types*, etc



TULIP

Team for Universal Learning and Intelligent Processing



Data Collection

Source *Tripadvisor* website (www.tripadvisor.com)

Extractor *Visual Web Ripper*

Data

- 8561 records about ratings on *Singapore* hotel *features* and overall *ratings*;
- *Demographic, Region, Travel Types*, etc



TULIP

Team for Universal Learning and Intelligent Processing



Data Collection

Source *Tripadvisor* website (www.tripadvisor.com)

Extractor *Visual Web Ripper*

Data

- 8561 records about ratings on *Singapore* hotel *features* and overall *ratings*;
- *Demographic, Region, Travel Types*, etc





Data Collection

Source *Tripadvisor* website (www.tripadvisor.com)

Extractor *Visual Web Ripper*

Data

- 8561 records about ratings on *Singapore* hotel *features* and overall *ratings*;
- *Demographic, Region, Travel Types*, etc





Data Collection

Source *Tripadvisor* website (www.tripadvisor.com)

Extractor *Visual Web Ripper*

Data

- 8561 records about ratings on *Singapore* hotel *features* and overall *ratings*;
- *Demographic, Region, Travel Types*, etc





Data Collection

- Hotel Rating Data Collections:





Data Collection

■ Hotel Rating Data Collections:

Travel Type	Region	Size
Business	Asia	1210 instances
	Europe	581 instances
	North America	407 instances
	Oceania	381 instances
Couple	Asia	1169 instances
	Europe	1389 instances
	North America	320 instances
	Oceania	1188 instances
Family	Asia	951 instances
	Europe	309 instances
	North America	131 instances
	Oceania	525 instances
Total:		8561 instances



Model Evaluation

- *Choquet Integral* is evaluated against typical aggregation methods such as AM, WAM and OWA;





Model Evaluation

- *Choquet Integral* is evaluated against typical aggregation methods such as AM, WAM and OWA;
- Evaluation using the *mean absolute error* (MAE) based on 10-fold cross validation.

Algorithms	Data Sets		
	Business	Couple	Family
AM	0.0757	0.0689	0.0706
OWA	0.0718	0.0666	0.0682
WAM	0.0701	0.0633	0.0665
CI	<i>kadd</i> = 1	0.0701	0.0633
	<i>kadd</i> = 2	0.0661	0.0614
	<i>kadd</i> = 3	0.0618	0.0556
	<i>kadd</i> = 4	0.0619	0.0561
	<i>kadd</i> = 5	0.0579	0.0541
	<i>kadd</i> = 6	<u>0.0576</u>	<u>0.0540</u>



Conclusion



TULIP

Team for Universal Learning and Intelligent Processing



Related Resources

- [1] Gang Li, Rob Law, Huy Quan Vu, Jia Rong. Discovering the Hotel Selection Preferences of Hong Kong Inbound Travelers Using the Choquet Integral, *Tourism Management*, Accepted on 21/10/2012 ¹
- [2] Huy Quan Vu, Gleb Beliakov, Gang Li. A Choquet Ingtegral Toolbox and its Application in Customer's Preference Analysis, in *Data Mining Applications with R*, Book Chapter, *Elsevier* 2013 ^{2 3}

¹An extensive invesigation on *HK* hotels preferences.

²RFMTool usage and a case study on *Singapore* hotels preferences.

³RFMTool: A R toolbox package publically available at TULIP Portal: <http://www.tulip.org.au/resources/rfmtree>



Conclusion

- This work has extended practical capability of feature-based sentiment mining;





Conclusion

- This work has extended practical capability of feature-based sentiment mining;
- introduced a new aggregation techniques for effective MCMD modeling;





Conclusion

- This work has extended practical capability of feature-based sentiment mining;
- introduced a new aggregation techniques for effective MCMD modeling;
- constructed a hotel preference profile for travels from different areas and under different travel modes. This will be also helpful for hotel managers in strategic planning and decision making.





Conclusion


- This work has extended practical capability of feature-based sentiment mining;
- introduced a new aggregation techniques for effective MCMD modeling;
- constructed a hotel preference profile for travels from different areas and under different travel modes. This will be also helpful for hotel managers in strategic planning and decision making.

Questions?





Contact Information



Associate Professor *Gang Li*
School of Information Technology
Deakin University, Geelong, Australia
Email GANGLI@ACM.ORG
Lab TEAM FOR UNIVERSAL LEARNING AND INTELLIGENT PROCESSING