NYU

Midterm Presentation

WebDev_Spring 2026

PRESENTED BY Ding, Andy

03/24/2026

Demo & Progress

A Demo of the Site and the Progress I Have Made

01

NYU

Demo Of the Site

- This set of code is overall building a personal calligraphy showcase website.
- The website includes Navigation, the Home hero section, About Me, Five Calligraphy Styles, Four Treasures, Works Showcase, Get in Touch, as well as two pop-up functions.
- The code is divided into three parts: HTML is responsible for the structure, CSS is responsible for the styling and animations, and JavaScript is responsible for the interactions.

Demo Of the Site

- https://qd2156-hash.github.io/AndyWeb_DevMid/

Snippet of Code

A Snippet of Code I Figured out

02

NYU

Snippet of Code

One piece of code I figured out is the ink motion animation on the homepage. I wanted the opening section of my website to feel more connected to the theme of Chinese calligraphy, so I designed a simple animated ink effect using HTML and CSS. The animation is made of a horizontal ink line and a small moving dot, which together suggest the feeling of a brushstroke in motion.

Snippet of Code

HTML

```html
<section class="hero-section">
  <div class="container hero-content">
    <div class="ink-motion-box">
      <div class="ink-line">
        <span class="ink-dot"></span>
      </div>
      <p>Ink Motion</p>
    </div>
    <h1>Brushstrokes in Motion, Seasons in Ink</h1>
    <p class="hero-text">Welcome to my personal calligraphy showcase</p>
    <button id="learn-more">Learn More</button>
  </div>
</section>
```

NYU

Snippet of Code

HTML

```html
<section class="hero-section">
  <div class="container hero-content">
    <div class="ink-motion-box">
      <div class="ink-line">
        <span class="ink-dot"></span>
      </div>
      <p>Ink Motion</p>
    </div>
```

This line creates an outer container that wraps the entire “ink animation” area. I named it `ink-motion-box` because it is essentially a small box used to display the dynamic ink effect.

Snippet of Code

HTML

```html
<section class="hero-section">
  <div class="container hero-content">
    <div class="ink-motion-box">
      <div class="ink-line">
        <span class="ink-dot"></span>
      </div>
```

This line creates a horizontal line.

This line is the main part of the animation and looks like a smear of ink pulled out by a brush.

Snippet of Code

HTML

```html
<section class="hero-section">
  <div class="container hero-content">
    <div class="ink-motion-box">
      <div class="ink-line">
        <span class="ink-dot"></span>
      </div>
      <p>Ink Motion</p>
    </div>
```

A small dot was added inside the black line of this section.

This dot will move during the animation, so it resembles a pen tip or ink droplet, which makes the entire line appear more "handwritten".

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

```
@keyframes huabi {
  0% {
    width: 20px;
  }
  50% {
    width: 180px;
  }
  100% {
    width: 20px;
  }
}

@keyframes inkdotmove {
  0% {
    left: 0;
  }
  50% {
    left: 160px;
  }
  100% {
    left: 0;
  }
}
```

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

This line begins to set the style of the outer box.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Set the width of this box to 280px.

This line is for setting the margin. "auto" makes the box horizontally centered, while the 30px at the bottom ensures a certain distance between it and the following title.

This line sets the inner padding of the box at the top and bottom to 30px.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

A light brown dotted border was added around this box.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Set the background color to a very light beige shade.
This will make the dark ink lines stand out more.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Set the background color to a very light beige shade.
This will make the dark ink lines stand out more.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Start setting the style of the text "Ink Motion" in the box.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Add an upper margin of 18px to the text.
Set the text size to 24px and set the letter spacing to 6px.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Start setting the style of that "black line".

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Start setting the style of that "black line".

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

This line is extremely important. It indicates that this element is using relative positioning, so the absolutely positioned .ink-dot inside can move relative to it.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Set the line height to 4px.
Set the initial width of the lines to 180px.
Make this line horizontally centered inside the box.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Set the line color to a dark brown shade that is close to black.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

This line adds animation to the lines.

"huabi" is the name of the animation, 2.2s indicates that the animation lasts for 2.2 seconds each time, and "infinite" means it will loop infinitely.

This enables the lines to continuously stretch and retract, simulating the process of generating strokes.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Start setting the style of the ink dots.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

This line indicates that this dot is positioned absolutely.

Its position will be based on the relative positioning area of the preceding .ink-line.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Set the dot distance above to -8px.

Place the dot at the very left end initially.

Set the dot width to 20px.

Set the height of the dots to 20px.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Turn the elements into circles.

If there is no such row, it will just be a square.

NYU

Snippet of Code

CSS

```
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Set the dot color to a slightly lighter brown.

This way, it will have a color gradient from the main line, and won't be exactly the same.

NYU

Snippet of Code

CSS

```css
.ink-motion-box {
  width: 280px;
  margin: 0 auto 30px auto;
  padding: 30px 0;
  border: 1px dashed #c1b4a1;
  background-color: #fcfaf6;
}

.ink-motion-box p {
  margin: 18px 0 0 0;
  font-size: 24px;
  letter-spacing: 6px;
}

.ink-line {
  position: relative;
  width: 180px;
  height: 4px;
  margin: 0 auto;
  background-color: #2a241d;
  animation: huabi 2.2s infinite;
}

.ink-dot {
  position: absolute;
  top: -8px;
  left: 0;
  width: 20px;
  height: 20px;
  border-radius: 50%;
  background-color: #8d775d;
  animation: inkdotmove 2.2s infinite;
}
```

Add animation to the dots.

They will move synchronously with the lines, giving the impression that the ink dots are driving the entire stroke forward.

NYU

Snippet of Code

CSS

(Keyframes animation)

```
@keyframes huabi {
  0% {
    width: 20px;
  }
  50% {
    width: 180px;
  }
  100% {
    width: 20px;
  }
}

@keyframes inkdotmove {
  0% {
    left: 0;
  }
  50% {
    left: 160px;
  }
  100% {
    left: 0;
  }
}
```

This line defines a keyframe animation called "huabi".

NYU

Snippet of Code

CSS

(Keyframes animation)

```
@keyframes huabi {
  0% {
    width: 20px;
  }
  50% {
    width: 180px;
  }
  100% {
    width: 20px;
  }
}

@keyframes inkdotmove {
  0% {
    left: 0;
  }
  50% {
    left: 160px;
  }
  100% {
    left: 0;
  }
}
```

When the animation reached halfway, the line extended to 180px.

At the beginning of the animation, the line width was only 20px.

When the animation ends, the line size returns to 20px.

NYU

Snippet of Code

CSS

(Keyframes animation)

```
@keyframes huabi {
  0% {
    width: 20px;
  }
  50% {
    width: 180px;
  }
  100% {
    width: 20px;
  }
}

@keyframes inkdotmove {
  0% {
    left: 0;
  }
  50% {
    left: 160px;
  }
  100% {
    left: 0;
  }
}
```

This line defines the second animation, named "inkdotmove", which is specifically responsible for controlling the movement of the small dots.

NYU

Snippet of Code

CSS

(Keyframes animation)

```
@keyframes huabi {
  0% {
    width: 20px;
  }
  50% {
    width: 180px;
  }
  100% {
    width: 20px;
  }
}

@keyframes inkdotmove {
  0% {
    left: 0;
  }
  50% {
    left: 160px;
  }
  100% {
    left: 0;
  }
}
```

At the beginning, the dot was on the far left.

Halfway through the animation, the dot moves to the right by 160 pixels. Since the line itself is approximately 180 pixels long, this value allows the dot to approach the end of the line.

When the animation ends, the dot returns to the left, creating a circular back-and-forth motion.

NYU

Media Query

03

Include at Least One Media Query In My Site

NYU

Next Steps

What I Plan on Continuing to Add Functionally For My Final

04

NYU

Next Steps

If I had more time, I would like to continue improving both the content and the interactive features of this website. Next, I want to add more calligraphy works to make the site feel richer and more complete. I would also like to refine the animations and visual details so the overall design feels smoother and more connected to the atmosphere of Chinese calligraphy. In addition, I hope to improve the contact form so that it can provide a more complete user interaction beyond the current pop-up feedback.

Thanks for Visiting Andy’s Calligraphy Website

NYU