Contents

command	hotkey	comment
backward-sexp	C-M-b	sexp: symbolic expression
balance-windows	C-x +	
beginning-of-buffer	M-<	
capitalize-word	M-c	
comint-next-input	M-n	
comint-previous-input	M-p	
delete-char	C-d	
delete-other-windows	C-x 1	
delete-rectangle	C-x r d	
delete-window	C-x 0	
describe-command	C-h x	
describe-function	C-h f	
describe-key	C-h k	
describe-mode	C-h m	
downcase-region	C-x C-l	
downcase-word	M-l	
execute-extended-command	M-x	
end-of-buffer	M->	
enlarge-window	C-x ^	
enlarge-window-horizontally	C-x }	
eval-expression	M-:	
find-file	C-x C-f	
forward-sexp	C-M-f	sexp: symbolic expression
isearch-backward	C-r	i: incremental
isearch-repeat-forward	C-s	i: incremental
keyboard-quit	C-g	
kill-buffer	C-x k	
kill-line	C-k	
kill-region	C-w	
kill-ring-save	M-w	
list-buffers	C-x C-b	
magit-status	C-x g	
mark-whole-buffer	C-x h	
move-beginning-of-line	C-a	
move-end-of-line	C-e	
next-line	C-n	
open-line	C-o	
other-window	C-x o	
previous-line	C-p	
query-replace	M-%	
quoted-insert	C-q	
recenter-top-bottom	C-l	
rectangle-mark-mode	C-x SPC	
rename-buffer	C-x x r	
repeat	C-x z	
save-buffer	C-x C-s	
save-buffers-kill-terminal	C-x C-c	
set-mark-command	C-SPC	