Linux Root Filesystem



© Copyright 2004-2026, Bootlin
Creative Commons BY-SA 3.0
Corrections, suggestions, contributions and translations are welcome!



Principle and solutions



Filesystems

- Filesystems are used to organize data in directories and files on storage devices or on the network. The directories and files are organized as a hierarchy
- In UNIX systems, applications and users see a **single global hierarchy** of files and directories, which can be composed of several filesystems.
- Filesystems are **mounted** in a specific location in this hierarchy of directories
  - When a filesystem is mounted in a directory (called *mount point*), the contents of this directory reflect the contents of this filesystem.
  - When the filesystem is unmounted, the *mount point* is empty again.
- This allows applications to access files and directories easily, regardless of their exact storage location



Filesystems (2)

- Create a mount point, which is just a directory

```
$ sudo mkdir /mnt/usbkey
```

- It is empty

```
$ ls /mnt/usbkey
$
```

- Mount a storage device in this mount point

```
$ sudo mount -t vfat /dev/sda1 /mnt/usbkey
$
```

- You can access the contents of the USB key

```
$ ls /mnt/usbkey
docs prog.c picture.png movie.avi
$
```



mount / umount

- `mount` allows to mount filesystems
  - `mount -t type device mountpoint`
  - `type` is the type of filesystem (optional for non-virtual filesystems)
  - `device` is the storage device, or network location to mount
  - `mountpoint` is the directory where files of the storage device or network location will be accessible
  - `mount` with no arguments shows the currently mounted filesystems
- `umount` allows to unmount filesystems
  - This is needed before rebooting, or before unplugging a USB key, because the Linux kernel caches writes in memory to increase performance. `umount` makes sure that these writes are committed to the storage.



Root filesystem

- A particular filesystem is mounted at the root of the hierarchy, identified by `/`
- This filesystem is called the **root filesystem**
- As `mount` and `umount` are programs, they are files inside a filesystem.
  - They are not accessible before mounting at least one filesystem.
- As the root filesystem is the first mounted filesystem, it cannot be mounted with the normal `mount` command
- It is mounted directly by the kernel, according to the `root=` kernel option
- When no root filesystem is available, the kernel panics:

```
Please append a correct "root=" boot option Kernel panic - not syncing:
VFS: Unable to mount root fs on unknown block(0,0)
```



Location of the root filesystem

- It can be mounted from different locations
  - From the partition of a hard disk
  - From the partition of a USB key
  - From the partition of an SD card
  - From the partition of a NAND flash chip or similar type of storage device
  - From the network, using the NFS protocol
  - From memory, using a pre-loaded filesystem (by the bootloader)
  - etc.
- It is up to the system designer to choose the configuration for the system, and configure the kernel behavior with `root=`



Mounting rootfs from storage devices


- Partitions of a hard disk or USB key
  - `root=/dev/sdXY`, where `X` is a letter indicating the device, and `Y` a number indicating the partition
  - `/dev/sdb2` is the second partition of the second disk drive (either USB key or ATA hard drive)
- Partitions of an SD card
  - `root=/dev/mmcblkXpY`, where `X` is a number indicating the device and `Y` a number indicating the partition
  - `/dev/mmcblk0p2` is the second partition of the first device
- Partitions of flash storage
  - `root=/dev/mtdblockX`, where `X` is the partition number
  - `/dev/mtdblock3` is the fourth enumerated flash partition in the system (there could be multiple flash chips)



Mounting rootfs over the network (1)

Once networking works, your root filesystem could be a directory on your GNU/Linux development host, exported by NFS (Network File System). This is very convenient for system development:

- Makes it very easy to update files on the root filesystem, without rebooting.
- Can have a big root filesystem even if you don't have support for internal or external storage yet.
- The root filesystem can be huge. You can even build native compiler tools and build all the tools you need on the target itself (better to cross-compile though).





Mounting rootfs over the network (2)

On the development workstation side, a NFS server is needed


- Install an NFS server (example: Debian, Ubuntu)
  `sudo apt install nfs-kernel-server`
- Add the exported directory to your `/etc/exports` file:
  `/home/tux/rootfs 192.168.1.111(rw,no_root_squash,no_subtree_check)`
  - `192.168.1.111` is the client IP address
  - `rw,no_root_squash,no_subtree_check` are the NFS server options for this directory export.
- Ask your NFS server to reload this file:
  `sudo exportfs -r`



Mounting rootfs over the network (3)

- On the target system
- The kernel must be compiled with
  - CONFIG_NFS_FS=y (NFS **client** support)
  - CONFIG_ROOT_NFS=y (support for NFS as rootfs)
  - CONFIG_IP_PNP=y (configure IP at boot time)
- The kernel must be booted with the following parameters:
  - `root=/dev/nfs` (we want rootfs over NFS)
  - `ip=192.168.1.111` (target IP address)
  - `nfsroot=192.168.1.110:/home/tux/rootfs/` (NFS server details)
  - You may need to add "`,nfsvers=3,tcp`" to the `nfsroot` setting, as an NFS version 2 client and UDP may be rejected by the NFS server in recent GNU/Linux distributions.

Mounting rootfs over the network (4)





Root filesystem in memory: initramfs

It is also possible to boot the system with a filesystem in memory: *initramfs*

- Either from a compressed CPIO archive integrated into the kernel image
- Or from such an archive loaded by the bootloader into memory
- At boot time, this archive is extracted into the Linux file cache
- It is useful for two cases:
  - Fast booting of very small root filesystems. As the filesystem is completely loaded at boot time, application startup is very fast.
  - As an intermediate step before switching to a real root filesystem, located on devices for which drivers are not part of the kernel image (storage drivers, filesystem drivers, network drivers). This is always used on the kernel of desktop/server distributions to keep the kernel image size reasonable.
- Details (in kernel documentation): filesystems/ramfs-rootfs-initramfs



External initramfs

- To create one, first create a compressed CPIO archive:

```
cd rootfs/
find . | cpio -H newc -o > ../initramfs.cpio
cd ..
gzip initramfs.cpio
```

- If you're using U-Boot, you'll need to include your archive in a U-Boot container:

```
mkimage -n 'Ramdisk Image' -A arm -O linux -T ramdisk -C gzip
        -d initramfs.cpio.gz uInitramfs
```

- Then, in the bootloader, load the kernel binary, DTB and `uInitramfs` in RAM and boot the kernel as follows:

```
bootz kernel-addr initramfs-addr dtb-addr
```




Built-in initramfs

To have the kernel Makefile include an initramfs archive in the kernel image: use the CONFIG_INITRAMFS_SOURCE option.

- It can be the path to a directory containing the root filesystem contents
- It can be the path to a ready made cpio archive
- It can be a text file describing the contents of the initramfs

See the kernel documentation for details:
driver-api/early-userspace/early_userspace_support

WARNING: only binaries from GPLv2 compatible code are allowed to be included in the kernel binary using this technique. Otherwise, use an external initramfs.





Contents



Root filesystem organization

- The organization of a Linux root filesystem in terms of directories is well-defined by the **Filesystem Hierarchy Standard**
- https://refspecs.linuxfoundation.org/fhs.shtml
- Most Linux systems conform to this specification
  - Applications expect this organization
  - It makes it easier for developers and users as the filesystem organization is similar in all systems



Important directories (1)

/bin	Basic programs
/boot	Kernel images, configurations and initramfs (only when the kernel is loaded from a filesystem, not common on non-x86 architectures)
/dev	Device files (covered later)
/etc	System-wide configuration
/home	Directory for the users home directories
/lib	Basic libraries
/media	Mount points for removable media
/mnt	Mount point for a temporarily mounted filesystem
/proc	Mount point for the proc virtual filesystem



Important directories (2)

/root	Home directory of the `root` user
/run	Run-time variable data (previously `/var/run`)
/sbin	Basic system programs
/sys	Mount point of the sysfs virtual filesystem
/tmp	Temporary files
/usr	
/usr/bin	Non-basic programs
/usr/lib	Non-basic libraries
/usr/sbin	Non-basic system programs
/var	Variable data files, for system services. This includes spool directories and files, administrative and logging data, and transient and temporary files



Separation of programs and libraries

- Basic programs are installed in `/bin` and `/sbin` and basic libraries in `/lib`
- All other programs are installed in `/usr/bin` and `/usr/sbin` and all other libraries in `/usr/lib`
- In the past, on UNIX systems, `/usr` was very often mounted over the network, through NFS
- In order to allow the system to boot when the network was down, some binaries and libraries are stored in `/bin`, `/sbin` and `/lib`
- `/bin` and `/sbin` contain programs like `ls`, `ip`, `cp`, `bash`, etc.
- `/lib` contains the C library and sometimes a few other basic libraries
- All other programs and libraries are in `/usr`
- Update: distributions are now making `/bin` link to `/usr/bin`, `/lib` to `/usr/lib` and `/sbin` to `/usr/sbin`. Details here: The Case for the /usr Merge.



Pseudo Filesystems



proc virtual filesystem

- The `proc` virtual filesystem exists since the beginning of Linux
- It allows
  - The kernel to expose statistics about running processes in the system
  - The user to adjust at runtime various system parameters about process management, memory management, etc.
- The `proc` filesystem is used by many standard user space applications, and they expect it to be mounted in `/proc`
- Applications such as `ps` or `top` would not work without the `proc` filesystem
- Command to mount `proc`:
  `mount -t proc nodev /proc`
- See filesystems/proc in kernel documentation or `man proc`



proc contents

- One directory for each running process in the system
  - `/proc/<pid>`
  - `cat /proc/3840/cmdline`
  - It contains details about the files opened by the process, the CPU and memory usage, etc.
- `/proc/interrupts`, `/proc/iomem`, `/proc/cpuinfo` contain general device-related information
- `/proc/cmdline` contains the kernel command line
- `/proc/sys` contains many files that can be written to adjust kernel parameters
  - They are called *sysctl*. See admin-guide/sysctl/ in kernel documentation.
  - Example (free the page cache and slab objects):
    `echo 3 > /proc/sys/vm/drop_caches`



sysfs filesystem

- It allows to represent in user space the vision that the kernel has of the buses, devices and drivers in the system
- It is useful for various user space applications that need to list and query the available hardware, for example `udev` or `mdev` (see later)
- All applications using sysfs expect it to be mounted in the `/sys` directory
- Command to mount `/sys`: `mount -t sysfs nodev /sys`
-
```
$ ls /sys/
block bus class dev devices firmware fs kernel module power
```



Minimal filesystem




Basic applications

- In order to work, a Linux system needs at least a few applications
- An `init` application, which is the first user space application started by the kernel after mounting the root filesystem (see https://en.wikipedia.org/wiki/Init):
  - The kernel tries to run the command specified by the `init=` command line parameter if available.
  - Otherwise, it tries to run `/sbin/init`, `/etc/init`, `/bin/init` and `/bin/sh`.
  - In the case of an initramfs, it will only look for `/init`. Another path can be supplied by the `rdinit=` kernel argument.
  - If none of this works, the kernel panics and the boot process is stopped.
  - The `init` application is responsible for starting all other user space applications and services, and for acting as a universal parent for processes whose parent terminate before they do.
- A shell, to implement scripts, automate tasks, and allow a user to interact with the system
- Basic UNIX executables, for use in system scripts or in interactive shells: `mv`, `cp`, `mkdir`, `cat`, `modprobe`, `mount`, `ip`, etc.
- These basic components have to be integrated into the root filesystem to make it usable



Overall booting process





Overall booting process with initramfs

