

Functional Programming in Education

George Wilson

Data61/CSIRO

george.wilson@data61.csiro.au

22nd May 2018



University

First year, first semester

Which language?

```
class Hello {  
  
    public static void main(String[] args) {  
        System.out.println("Hello, world!");  
    }  
  
}
```

	Content
Week 1	Basic expressions
Week 2	procedure declarations
Week 3	if-statement
Week 4	while-statement
Week 5	for-statement
...	

Structure and Interpretation of Computer Programs

Second Edition



Harold Abelson and
Gerald Jay Sussman
with Julie Sussman

```
(define (factorial n)
  (cond (<= n 1)
        1
        (* n (factorial (- n 1)))))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

```
=> (+ (* 3 3) (sqr 4))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

```
=> (+ (* 3 3) (sqr 4))
```

```
=> (+ 9 (sqr 4))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

```
=> (+ (* 3 3) (sqr 4))
```

```
=> (+ 9 (sqr 4))
```

```
=> (+ 9 (* 4 4))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

```
=> (+ (* 3 3) (sqr 4))
```

```
=> (+ 9 (sqr 4))
```

```
=> (+ 9 (* 4 4))
```

```
=> (+ 9 16)
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

```
=> (+ (* 3 3) (sqr 4))
```


```
=> (+ 9 (sqr 4))
```

```
=> (+ 9 (* 4 4))
```

```
=> (+ 9 16)
```

```
=> 25
```

```
{factorial 6}  
(* 6 {factorial 5})  
(* 6 (* 5 {factorial 4}))  
(* 6 (* 5 (* 4 {factorial 3})))  
(* 6 (* 5 (* 4 (* 3 {factorial 2}))))  
(* 6 (* 5 (* 4 (* 3 (* 2 {factorial 1}))))))  
(* 6 (* 5 (* 4 (* 3 (* 2 1)))))  
(* 6 (* 5 (* 4 (* 3 2))))  
(* 6 (* 5 (* 4 6)))  
(* 6 (* 5 24))  
(* 6 120)  
720
```



Incredible breadth of content

complexity analysis

symbolic computation with quotation

interpreters


object-oriented programming

logic programming

many other concepts

A critique of Abelson and Sussman
- or -
Why calculating is better than scheming

Philip Wadler
Programming Research Group
11 Keble Road
Oxford, OX1 3QD


received April 1980



(or similar)

```
data List a
  = Nil
  | Cons a (List a)
```

```
(define (sum items)
  (cond ((null? items) 0)
        (else (+ (car items) (sum (cdr items))))))
```

```
(define (sum items)
  (cond ((null? items) 0)
        (else (+ (car items) (sum (cdr items))))))
```

```
sum items = case items of
  Nil      -> 0
  Cons x xs -> x + sum xs
```

```
(define (new-if predicate then-clause else-clause)
  (cond (predicate then-clause)
        (else else-clause)))
```

```
(define (new-if predicate then-clause else-clause)
  (cond (predicate then-clause)
        (else else-clause)))
```

`newIf` **True** `t f` `=` `t`

`newIf` **False** `t f` `=` `f`

The Structure and Interpretation of the Computer Science Curriculum

Matthias Felleisen, Northeastern University, Boston, MA, USA

Robert Bruce Findler, University of Chicago, Chicago, IL, USA

Matthew Flatt, University of Utah, Salt Lake City, UT, USA

Shriram Krishnamurthi, Brown University, Providence, RI, USA

Email: {matthias,robby,mflatt,shriram}@plt-scheme.org

Criticisms

Examples are drawn from overly-technical domains

```
(define (deriv exp var)
  (cond ((number? exp) 0)
        ((variable? exp)
         (if (same-variable? exp var) 1 0))
        ((sum? exp)
         (make-sum (deriv (addend exp) var)
                     (deriv (augend exp) var)))
        ((product? exp)
         (make-sum
          (make-product (multiplier exp)
                        (deriv (multiplicand exp) var))
          (make-product (deriv (multiplier exp) var)
                        (multiplicand exp))))
        (else
         (error "unknown expression type -- DERIV" exp))))
```

Criticisms

Lacking coverage of foundational problem-solving techniques

From an educational point of view, our experience suggests that undergraduate computer science courses should emphasize basic notions of modularity, specification, and data abstraction, and should not let these be displaced by more advanced topics, such as design patterns, object-oriented methods, concurrency, functional languages, and so on.

— Jackson and Chapin, 2000 (emphasis mine)

HOW TO DESIGN PROGRAMS

Second Edition

An Introduction to Programming and Computing

Matthias Felleisen

Robert Bruce Findler

Matthew Flatt

Shriram
Krishnamurthi

Choose Language



☐ The Racket Language (ctl-R)

Start your program with `#lang` to specify the desired dialect. For example:

```
#lang racket           [docs]
#lang racket/base      [docs]
#lang typed/racket     [docs]
#lang scribble/base    [docs]
```

... and many more

☒ Teaching Languages (ctl-T)

How to Design Programs

Beginning Student

Beginning Student with List Abbreviations

Intermediate Student

Intermediate Student with `lambda`

Advanced Student

DeinProgramm

Die Macht der Abstraktion - Anfänger

Die Macht der Abstraktion

Die Macht der Abstraktion mit Zuweisungen

Die Macht der Abstraktion - fortgeschritten

☐ Other Languages (ctl-O)

...

Show Details

OK

Cancel

```
(require 2htdp/image)
(require 2htdp/universe)
```



```
(define rocket )

(define (picture-of-rocket height)
  (place-image rocket 50 height (empty-scene 100 60)))

(define (sign x)
  (cond ((> x 0) 1)
        ((= x 0) 0)
        ((< x 0) -1)))

(define (picture-of-rocket.v2 height)
  (cond
    [(<= height 60)
     (place-image 50 height
                  (empty-scene 100 60))]
    [(> height 60)
     (place-image 50 60
                  (empty-scene 100 60))]))
```


Welcome to [DrRacket](#), version 7.2 [3m].

Language: **Beginning Student**; memory limit: 128 MB.

> (picture-of-rocket.v2 5555)

place-image: expects 4 arguments, but found only 3

> |



Strings aren't compared with `=` and its relatives. Instead, you must use `string=?` or `string<=?` or `string>=?` if you ever need to compare strings. While it is obvious that `string=?` checks whether the two given strings are equal, the other two primitives are open to interpretation. **Look up their documentation.** Or, experiment, guess a general law, and then check in the documentation whether you guessed right.

If the documentation in HelpDesk appears confusing, experiment with the functions in the interactions area. Give them appropriate arguments, and find out what they compute. Also use **inappropriate** arguments for some operations just to find out how BSL reacts:

```
> (string-length 42)  
string-length:expects a string, given 42
```

1. From Problem Analysis to Data Definitions

Identify the information that must be represented and how it is represented in the chosen programming language. Formulate data definitions and illustrate them with examples.

2. Signature, Purpose Statement, Header

State what kind of data the desired function consumes and produces. Formulate a concise answer to the question *what* the function computes. Define a stub that lives up to the signature.

3. Functional Examples

Work through examples that illustrate the function's purpose.

4. Function Template

Translate the data definitions into an outline of the function.


5. Function Definition


Fill in the gaps in the function template. Exploit the purpose statement and the examples.

6. Testing

Articulate the examples as tests and ensure that the function passes all. Doing so discovers mistakes. Tests also supplement examples in that they help others read and understand the definition when the need arises—and it will arise for any serious program.

Figure 1: The basic steps of a function design recipe





Language Choice in Introductory Programming Courses at Australasian and UK Universities

Simon
University of Newcastle
Australia
simon@newcastle.edu.au

Raina Mason
Southern Cross University
Australia
raina.mason@scu.edu.au

Tom Crick
Cardiff Metropolitan University
United Kingdom
tcrick@cardiffmet.ac.uk

James H. Davenport
University of Bath
United Kingdom
j.h.davenport@bath.ac.uk

Ellen Murphy
University of Bath
United Kingdom
e.murphy@bath.ac.uk




Figure 3: Prevalence of reasons for choice of language

3 + False

```
<interactive>:1:1: error:
```

- No instance for (Num Bool) arising from a use of `+'
- In the expression: 3 + False
In an equation for `it': it = 3 + False

GHC custom type errors

```
{-# language DataKinds, TypeFamilies, TypeOperators #-}  
{-# language UndecidableInstances #-}
```

```
import GHC.TypeLits
```

```
instance TypeError (Text "Booleans are not numbers" :$$:  
                    Text "so we cannot add or multiply them")  
  => Num Bool where
```


3 + False

```
<interactive>:1:1: error:
```

- Booleans are not numbers
so we cannot add or multiply them
- In the expression: 3 + False
In an equation for 'it': it = 3 + False

Custom preludes for a staged introduction

Prelude.hs

```
module Prelude
  ( N.Integer, (+)
  )
where

import GHC.Num (Integer)
import qualified GHC.Num as N

(+) :: Integer -> Integer -> Integer
(+) = (N.+)
```

Helium4Haskell / helium

Watch 2 Star 15 Fork 6

Code Issues 2 Pull requests 1 Projects 0 Wiki Insights

The Helium compiler, Helium-as-a-library, and the texthint interpreter

606 commits

13 branches

0 releases

7 contributors

GPL-3.0

Branch: master

New pull request

Create new file

Upload files

Find File

Clone or download

serras Add Git ignore

Latest commit e0d9c33 on Apr 9, 2018

demo	Initial revision	17 years ago
docs	Test harness is working again. All .out files modified to also say "P...	3 years ago
lib	.lvm files (for Prelude.hs and .core) will be compiled on demand. No ...	5 years ago
src	Add named holes to parser	a year ago
test	Whatever	2 years ago
.gitignore	Add Git ignore	a year ago

A brief personal anecdote. . .

Thanks for listening!