

Functional Programming in Education

George Wilson

Data61/CSIRO

`george.wilson@data61.csiro.au`

22nd May 2018



University

First year, first semester

Which language?

```
class Hello {  
  
    public static void main(String[] args) {  
        System.out.println("Hello, world!");  
    }  
  
}
```

	Content
Week 1	Basic expressions
Week 2	procedure declarations
Week 3	if-statement
Week 4	while-statement
Week 5	for-statement
...	

Structure and Interpretation of Computer Programs

Second Edition



Harold Abelson and
Gerald Jay Sussman
with Julie Sussman

```
(define (factorial n)
  (cond (<= n 1)
        1
        (* n (factorial (- n 1))))))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)  
=> (+ (sqr 3) (sqr 4))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

```
=> (+ (* 3 3) (sqr 4))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

```
=> (+ (* 3 3) (sqr 4))
```

```
=> (+ 9 (sqr 4))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

```
=> (+ (* 3 3) (sqr 4))
```

```
=> (+ 9 (sqr 4))
```

```
=> (+ 9 (* 4 4))
```

Evaluation by substitution

```
(define (sum-of-squares x y)  
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

```
=> (+ (* 3 3) (sqr 4))
```

```
=> (+ 9 (sqr 4))
```

```
=> (+ 9 (* 4 4))
```

```
=> (+ 9 16)
```

Evaluation by substitution

```
(define (sum-of-squares x y)
  (+ (sqr x) (sqr y)))
```

```
(sum-of-squares 3 4)
```

```
=> (+ (sqr 3) (sqr 4))
```

```
=> (+ (* 3 3) (sqr 4))
```


```
=> (+ 9 (sqr 4))
```

```
=> (+ 9 (* 4 4))
```

```
=> (+ 9 16)
```

```
=> 25
```

```
{factorial 6}  
(* 6 {factorial 5})  
(* 6 (* 5 {factorial 4}))  
(* 6 (* 5 (* 4 {factorial 3})))  
(* 6 (* 5 (* 4 (* 3 {factorial 2}))))  
(* 6 (* 5 (* 4 (* 3 (* 2 {factorial 1}))))))  
(* 6 (* 5 (* 4 (* 3 (* 2 1)))))  
(* 6 (* 5 (* 4 (* 3 2))))  
(* 6 (* 5 (* 4 6)))  
(* 6 (* 5 24))  
(* 6 120)  
720
```



Incredible breadth of content

complexity analysis

symbolic computation with quotation

interpreters

object-oriented programming

logic programming

many other concepts

A critique of Abelson and Sussman
- or -
Why calculating is better than scheming

Philip Wadler
Programming Research Group
11 Keble Road
Oxford, OX1 3QD


received April 1980



(or similar)

```
data List a
  = Nil
  | Cons a (List a)
```

```
(define (sum items)
  (cond ((null? items) 0)
        (else (+ (car items) (sum (cdr items))))))
```

```
(define (sum items)
  (cond ((null? items) 0)
        (else (+ (car items) (sum (cdr items))))))
```

```
sum items = case items of
  Nil      -> 0
  Cons x xs -> x + sum xs
```

```
(define (new-if predicate then-clause else-clause)
  (cond (predicate then-clause)
        (else else-clause)))
```

```
(define (new-if predicate then-clause else-clause)
  (cond (predicate then-clause)
        (else else-clause)))
```

newIf **True** t f = t

newIf **False** t f = f

others criticised the content

Criticisms

Examples are drawn from overly-technical domains

```
(define (deriv exp var)
  (cond ((number? exp) 0)
        ((variable? exp)
         (if (same-variable? exp var) 1 0))
        ((sum? exp)
         (make-sum (deriv (addend exp) var)
                     (deriv (augend exp) var)))
        ((product? exp)
         (make-sum
          (make-product (multiplier exp)
                        (deriv (multiplicand exp) var))
          (make-product (deriv (multiplier exp) var)
                        (multiplicand exp))))
        (else
         (error "unknown expression type -- DERIV" exp))))
```

Criticisms

Lacking coverage of foundational problem-solving techniques

From an educational point of view, our experience suggests that undergraduate computer science courses should emphasize basic notions of modularity, specification, and data abstraction, and should not let these be displaced by more advanced topics, such as design patterns, object-oriented methods, concurrency, functional languages, and so on.

— Jackson and Chapin, 2000 (emphasis mine)



HOW TO DESIGN PROGRAMS

Second Edition

An Introduction to Programming and Computing


Matthias
Felleisen

Robert Bruce
Findler

Matthew
Flatt

Shriram
Krishnamurthi

```
(require 2htdp/image)
(require 2htdp/universe)

(define rocket )

(define (picture-of-rocket height)
  (place-image rocket 50 height (empty-scene 100 60)))

(define (sign x)
  (cond ((> x 0) 1)
        ((= x 0) 0)
        ((< x 0) -1)))

(define (picture-of-rocket.v2 height)
  (cond
    [(<= height 60)
     (place-image 50 height
                  (empty-scene 100 60))]
    [(> height 60)
     (place-image 50 60
                  (empty-scene 100 60))]))
```

Welcome to [DrRacket](#), version 7.2 [3m].

Language: **Beginning Student**; memory limit: 128 MB.

> (picture-of-rocket.v2 5555)

place-image: expects 4 arguments, but found only 3

> |

Choose Language

☐ The Racket Language (ctl-R)

Start your program with #lang to specify the desired dialect. For example:

```
#lang racket           [docs]
#lang racket/base      [docs]
#lang typed/racket     [docs]
#lang scribble/base    [docs]
```

... and many more

☒ Teaching Languages (ctl-T)

How to Design Programs
Beginning Student
Beginning Student with List Abbreviations
Intermediate Student
Intermediate Student with lambda
Advanced Student

DeinProgramm
Die Macht der Abstraktion - Anfänger
Die Macht der Abstraktion
Die Macht der Abstraktion mit Zuweisungen
Die Macht der Abstraktion - fortgeschritten

☐ Other Languages (ctl-O)

...

Show DetailsOKCancel

1. From Problem Analysis to Data Definitions

Identify the information that must be represented and how it is represented in the chosen programming language. Formulate data definitions and illustrate them with examples.

2. Signature, Purpose Statement, Header

State what kind of data the desired function consumes and produces. Formulate a concise answer to the question *what* the function computes. Define a stub that lives up to the signature.

3. Functional Examples

Work through examples that illustrate the function's purpose.

4. Function Template

Translate the data definitions into an outline of the function.

5. Function Definition

Fill in the gaps in the function template. Exploit the purpose statement and the examples.

6. Testing


Articulate the examples as tests and ensure that the function passes all. Doing so discovers mistakes. Tests also supplement examples in that they help others read and understand the definition when the need arises—and it will arise for any serious program.


Figure 1: The basic steps of a function design recipe

Strings aren't compared with `=` and its relatives. Instead, you must use `string=?` or `string<=?` or `string>=?` if you ever need to compare strings. While it is obvious that `string=?` checks whether the two given strings are equal, the other two primitives are open to interpretation. [Look up their documentation.](#) Or, experiment, guess a general law, and then check in the documentation whether you guessed right.

If the documentation in HelpDesk appears confusing, experiment with the functions in the interactions area. Give them appropriate arguments, and find out what they compute. Also use **inappropriate** arguments for some operations just to find out how BSL reacts:

```
> (string-length 42)  
string-length:expects a string, given 42
```





haskell for mac screenshot

3 + False

```
<interactive>:1:1: error:
```

- No instance for (Num Bool) arising from a use of `+'
- In the expression: 3 + False
In an equation for `it': it = 3 + False

Prelude.hs

```
module Prelude
  ( N.Integer,  (+)
  )
where

import GHC.Num (Integer)
import qualified GHC.Num as N

(+)  :: Integer -> Integer -> Integer
(+)  = (N.+)
```

Helium4Haskell/helium: The H

+

→

↺

🏠

🔒

GitHub, Inc. (US)

https://github.com/Helium4Haskell/helium

⋮

🔒

☆

↓


🔍

📄

📺

1

☰



Search or jump to...

/

Pull requests


Issues

Marketplace

Explore

🔔

+



▼

📄 Helium4Haskell / helium

👁 Watch

▼

2

★ Star

15

🍴 Fork

6

↔ Code

🔔 Issues 2

🔗 Pull requests 1

📁 Projects 0

📖 Wiki

📊 Insights

The Helium compiler, Helium-as-a-library, and the texthint interpreter

📄 606 commits

🌿 13 branches

📦 0 releases

👤 7 contributors

📄 GPL-3.0

Branch: master ▼


New pull request

Create new file

Upload files

Find File

Clone or download ▼

 serras Add Git ignore

Latest commit e0d9c33 on Apr 9, 2018

📁 demo	Initial revision	17 years ago
📁 docs	Test harness is working again. All .out files modified to also say "P...	3 years ago
📁 lib	.lvm files (for Prelude.hs and .core) will be compiled on demand. No ...	5 years ago
📁 src	Add named holes to parser	a year ago
📁 test	Whatever	2 years ago
📄 .gitignore	Add Git ignore	a year ago

custom type error machinery in GHC

Thanks for listening!