An Intuition for Propagators

George Wilson


CSIRO's Data61


george.wilson@data61.csiro.au

2nd September 2019




1970s, MIT











+














-- types data Cell a

data Par a
instance Monad Par

```
-- types
data Cell a
```

data Par a instance Monad Par

```
-- Creating a cell cell :: Par (Cell a)
```

```
-- types
data Cell a
data Par a
instance Monad Par
-- Creating a cell
cell :: Par (Cell a)
-- Working with Cells
content :: Cell a -> Par (Maybe a)
```


write :: Cell a -> a -> Par ()

```
-- types
data Cell a
data Par a
instance Monad Par
-- Creating a cell
cell :: Par (Cell a)
-- Working with Cells
content :: Cell a -> Par (Maybe a)
write :: Cell a -> a -> Par ()
-- Creating a propagator
watch :: Cell a -> (a -> Par ()) -> Par ()
```




do


input <- cell




```
do
  input <- cell
  output <- cell</pre>
```



```
input <- cell
output <- cell
watch input (\c ->
write output (toUpper c))
```




```
do
 input <- cell
 output <- cell
 watch input (\c ->
   write output (toUpper c))
 write input 'q'
 content output -- Just 'O'
```



```
do
 input <- cell
 output <- cell
 watch input (\c ->
   write output (toUpper c))
 write input 'q'
 content output -- Just 'Q'
```

```
lift :: (a -> b) -> Cell a -> Cell b -> Par ()
lift f input output =
  watch input (\a ->
```

write output (f a))



```
input <- cell
output <- cell
lift toUpper input output

write input 'q'
content output -- Just '0'</pre>
```

Thanks for listening!