

An Intuition for Propagators

George Wilson

CSIRO's Data61


george.wilson@data61.csiro.au


2nd September 2019



1970s, MIT

a model of computation for **highly concurrent** machines








"Hello"





"Compose"

















```
-- types
```

```
data Cell a
```

```
data Par a
```

```
instance Monad Par
```

```
-- types
```

```
data Cell a
```

```
data Par a
```

```
instance Monad Par
```

```
-- Creating a cell
```

```
cell      :: Par (Cell a)
```

```
-- types
```

```
data Cell a
```

```
data Par a
```

```
instance Monad Par
```

```
-- Creating a cell
```

```
cell      :: Par (Cell a)
```

```
-- Working with Cells
```

```
content  :: Cell a -> Par (Maybe a)
```

```
write    :: Cell a -> a -> Par ()
```


-- types

data Cell a

data Par a

instance Monad Par

-- Creating a cell

cell :: **Par** (**Cell** a)


-- Working with Cells

content :: **Cell** a -> **Par** (**Maybe** a)

write :: **Cell** a -> a -> **Par** ()



-- Creating a propagator

watch :: **Cell** a -> (a -> **Par** ()) -> **Par** ()



do


input <- cell



do

input <- cell

output <- cell




do

```
input  <- cell
```

```
output <- cell
```

```
watch input (\c ->
```

```
  write output (toUpper c))
```



do

```
input  <- cell
```


```
output <- cell
```

```
watch input (\c ->
```

```
  write output (toUpper c))
```

```
write input 'q'
```

```
content output  -- Just 'Q'
```



do

```
input  <- cell
```

```
output <- cell
```

```
watch input (\c ->
```

```
  write output (toUpper c))
```

```
write input 'q'
```

```
content output  -- Just 'Q'
```

Thanks for listening!