

Propagators: An Introduction

George Wilson

Data61/CSIRO


george.wilson@data61.csiro.au

November 8, 2017





What?




Why?

Roots as early as the 1970's at MIT

- Guy L. Steele Jr.
- Gerald J. Sussman
- Richard Stallman

More recently:


- Alexey Radul



```
(define (map f xs)
  (cond ((null? xs) '())
        (else (cons (f (car xs))
                      (map f (cdr xs)))))))
```

And then

- Edward Kmett



$$x \leq y \implies f(x) \leq f(y)$$

Propagators

The *propagator model* is a model of computation
We model computations as *propagator networks*


The *propagator model* is a model of computation
We model computations as *propagator networks*

Propagator networks:

- are extremely expressive
- lend themselves to parallel and distributed evaluation
- allow different strategies of problem-solving to seamlessly cooperate


A propagator network comprises


- cells
- propagators
- connections between cells and propagators





3


toUpper

















$$z \leftarrow x + y$$

$$z = x + y$$

$$7 = x + 4$$


$$7 = 3 + 4$$


$$z = x + y$$


$$z \leftarrow x + y$$


$$x \leftarrow z - y$$

$$y \leftarrow z - x$$











Propagators let us express multi-directional relationships!


$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$



$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$


$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$





$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$


$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$
















We can combine networks into larger networks!

?

What types are the values of the cells?


'c'








Cells store *information about a value*


```
data Maybe a = Nothing | Just a
```











:(

Contradiction

data Perhaps a = Unknown | Known a | Contradiction

```
data Perhaps a = Unknown | Known a | Contradiction
```

```
instance Eq a => Monoid (Perhaps a) where
```

```
    mempty = Unknown
```

```
    mappend Unknown x           = x
```

```
    mappend x      Unknown      = x
```

```
    mappend Contradiction _      = Contradiction
```


```
    mappend _      Contradiction = Contradiction
```


```
    mappend (Known a) (Known b) =
```


```
        if a == b
```


```
        then Known a
```


```
        else Contradiction
```














Will other monoids work?

Will other monoids work?


What about List?











Looking good?











We need commutativity!

$$x \oplus y = y \oplus x$$

We need commutativity!

$$x \oplus y = y \oplus x$$


List append is not commutative!


`[1, 2, 3] <> [4, 5, 6] == [1, 2, 3, 4, 5, 6]`


`[4, 5, 6] <> [1, 2, 3] == [4, 5, 6, 1, 2, 3]`


We need a commutative monoid
What about addition?


$$x + y = y + x$$


























We need idempotence!

$$x \oplus x = x$$

We need an idempotent, commutative monoid.

This structure is called a *join-semilattice*

Associativity

$$(x \vee y) \vee z = x \vee (y \vee z)$$

Commutativity

$$x \vee y = y \vee x$$

Idempotence

$$x \vee x = x$$

Partial information that supports merging!

Other examples?

$$[1, 5]$$

$$[1, 5] \langle \rangle [2, 7] = [2, 5]$$

$\{True, False\}$

TODO set intersection examples