

Propagators: An Introduction

George Wilson

Data61/CSIRO


george.wilson@data61.csiro.au

November 11, 2017





What?




Why?

Beginnings as early as the 1970's at MIT

- Guy L. Steele Jr.
- Gerald J. Sussman
- Richard Stallman

More recently:


- Alexey Radul



```
(define (map f xs)
  (cond ((null? xs) '())
        (else (cons (f (car xs))
                      (map f (cdr xs)))))))
```

And then

- Edward Kmett



$$x \leq y \implies f(x) \leq f(y)$$

Propagators

The *propagator model* is a model of computation
We model computations as *propagator networks*


The *propagator model* is a model of computation
We model computations as *propagator networks*

Propagator networks:

- are extremely expressive
- lend themselves to parallel and distributed evaluation
- allow different strategies of problem-solving to seamlessly cooperate


A propagator network comprises


- cells
- propagators
- connections between cells and propagators





3


toUpper

















$$z \leftarrow x + y$$

$$z = x + y$$

$$7 = x + 4$$


$$7 = 3 + 4$$


$$z = x + y$$


$$z \leftarrow x + y$$


$$x \leftarrow z - y$$

$$y \leftarrow z - x$$











Propagators let us express multi-directional relationships!


$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$



$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$


$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$





$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$


$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$














We can combine networks into larger networks!

?

Cells *accumulate information* about a value

data Perhaps a = Unknown | Known a | Contradiction

```
data Perhaps a = Unknown | Known a | Contradiction
```

```
instance Eq a => Monoid (Perhaps a) where
```

```
    mempty = Unknown
```

```
    mappend Unknown x           = x
```

```
    mappend x      Unknown      = x
```

```
    mappend Contradiction _      = Contradiction
```


```
    mappend _      Contradiction = Contradiction
```


```
    mappend (Known a) (Known b) =
```


```
        if a == b
```


```
        then Known a
```


```
        else Contradiction
```




































3			2
	4	1	
	3	2	
4			1

3			2
	4	1	
	3	2	
4			1


3			2
	4	1	
	3	2	
4			1

3			2
	4	1	
	3	2	
4			1

3			2
	4	1	
	3	2	
4			1

3			2
	4	1	
	3	2	
4			1

$\{1,2,3,4\}$



A 4x4 grid with a yellow cell at (1,3) and a pointer from the set {1,2,3,4} to it.

3			2
	4	1	
	3	2	
4			1

$\{1,3,4\}$

3			2
	4	1	
	3	2	
4			1

3			2
	4	1	
	3	2	
4			1

$\{2,3,4\}$

$\{1,2,4\}$



A 4x4 grid with a red cell containing the number 3 and a yellow cell. An arrow points from the set $\{1,2,4\}$ to the red cell. The grid contains the following numbers:

3			2
	4	1	
	3	2	
4			1


$$\{2,3,4\} \cap \{1,3,4\} \cap \\ \{1,2,4\} \cap \{1,2,3\}$$

3			2
	4	1	
	3	2	
4			1

{4}

3			2
	4	1	
	3	2	
4			1

3		4	2
	4	1	
	3	2	
4			1





$$[1, 5]$$

$$[1, 5] \cup [2, 7] = [2, 5]$$


$$[1, 5] \cup [2, 7] = [2, 5]$$


$$[2, 5] + [9, 10] = [11, 15]$$





What types are the values of the cells?






'c'


Contradiction


Is this the only type propagator cells can contain?
Will other monoids work?

Is this the only type propagator cells can contain?
Will other monoids work?


What about List?











Looking good?











We need commutativity!

$$x \oplus y = y \oplus x$$

We need commutativity!

$$x \oplus y = y \oplus x$$


List append is not commutative!


`[1, 2, 3] <> [4, 5, 6] == [1, 2, 3, 4, 5, 6]`


`[4, 5, 6] <> [1, 2, 3] == [4, 5, 6, 1, 2, 3]`

We need a commutative monoid
What about addition?

$$x + y = y + x$$







We need idempotence!

$$x \oplus x = x$$

We need an idempotent, commutative monoid.
This structure is called a *join-semilattice*

Associativity

$$(x \vee y) \vee z = x \vee (y \vee z)$$

Commutativity

$$x \vee y = y \vee x$$

Idempotence

$$x \vee x = x$$

Other examples?

TODO point to Alexey's stuff here

Edward Kmett has worked on:

- Making it go fast
- Scheduling strategies and garbage collection
- Relaxing requirements (Eg. not requiring a full join-semilattice, admitting non-monotone functions)

TODO finish this slide

TODO expand this

In conclusion, propagator networks:

- Are parallelisable and distributable
- Admit any Haskell function you can write today ...
- ...and more functions!
- compute bidirectionally
- give us constraint solving

TODO expand on all this

Things we could build with propagators:

The best spreadsheet