

Propagators: An Introduction

George Wilson

Data61/CSIRO


george.wilson@data61.csiro.au

November 14, 2017





What?




Why?

Beginnings as early as the 1970's at MIT

- Guy L. Steele Jr.
- Gerald J. Sussman
- Richard Stallman

More recently:


- Alexey Radul



```
(define (map f xs)
  (cond ((null? xs) '())
        (else (cons (f (car xs))
                      (map f (cdr xs)))))))
```

And then

- Edward Kmett



$$x \leq y \implies f(x) \leq f(y)$$

They're related to many areas of research, including:

- Logic programming (particularly Datalog)
- Constraint solvers
- Conflict-Free Replicated Datatypes
- LVars
- Programming language theory
- And Spreadsheets!

They have advantages:

- are extremely expressive
- lend themselves to parallel and distributed evaluation
- allow different strategies of problem-solving to cooperate


Propagators

The *propagator model* is a model of computation
We model computations as *propagator networks*

The *propagator model* is a model of computation
We model computations as *propagator networks*


A propagator network comprises


- cells
- propagators
- connections between cells and propagators





3


toUpper

















$$z \leftarrow x + y$$

$$z = x + y$$

$$7 = x + 4$$


$$7 = 3 + 4$$


$$z = x + y$$


$$z \leftarrow x + y$$


$$x \leftarrow z - y$$

$$y \leftarrow z - x$$











Propagators let us express multi-directional relationships!


$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$



$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$

$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$




$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$


$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$





$$^{\circ}F = ^{\circ}C \times \frac{9}{5} + 32$$


$$^{\circ}C = (^{\circ}F - 32) \div \frac{9}{5}$$














We can combine networks into larger networks!

?

Cells *accumulate information* about a value

3			2
	4	1	
	3	2	
4			1

3			2
	4	1	
	3	2	
4			1


3			2
	4	1	
	3	2	
4			1

3			2
	4	1	
	3	2	
4			1

3			2
	4	1	
	3	2	
4			1

3			2
	4	1	
	3	2	
4			1

$\{1,2,3,4\}$



A 4x4 grid with a yellow cell at (1,3) and a pointer from the set {1,2,3,4} to it.

3			2
	4	1	
	3	2	
4			1


$\{1,3,4\}$

3			2
	4	1	
	3	2	
4			1

3			2
	4	1	
	3	2	
4			1

$\{2,3,4\}$

$\{1,2,4\}$



A 4x4 grid with a red cell containing the number 3 and a yellow cell. An arrow points from the set $\{1,2,4\}$ to the red cell.

3			2
	4	1	
	3	2	
4			1

$$\{2,3,4\} \cap \{1,3,4\} \cap \\ \{1,2,4\} \cap \{1,2,3\}$$

3			2
	4	1	
	3	2	
4			1

{4}

3			2
	4	1	
	3	2	
4			1

3		4	2
	4	1	
	3	2	
4			1

Cells accumulate information in a *bounded join-semilattice*

Cells accumulate information in a *bounded join-semilattice*

A bounded join-semilattice is:


- A *partially ordered set*
- with a least element
- such that any set of elements has a *least upper bound*



Cells accumulate information in a *bounded join-semilattice*



A bounded join-semilattice is:



- A *partially ordered set*
- with a least element
- such that any set of elements has a *least upper bound*



“Least upper bound” is denoted as \vee and is usually pronounced “join”


























$\{1,2,4\} < \{1,4\}$




$$\{1,2,4\} < \{1,4\} < \{1\}$$









$$\{1, 2, 3\} \cup \{1, 4\}$$





$$\{1,2,3\} \vee \{1,4\} = \{1\}$$

\vee has useful algebraic properties. It is:

- A monoid
- that's commutative
- and idempotent

Left identity

$$\epsilon \vee x = x$$

Right identity

$$x \vee \epsilon = x$$

Associativity

$$(x \vee y) \vee z = x \vee (y \vee z)$$

Commutative

$$x \vee y = y \vee x$$

Idempotent

$$x \vee x = x$$

```
class BoundedJoinSemilattice a where
  bottom :: a
  (\\) :: a -> a -> a
```



```
class BoundedJoinSemilattice a where
```

```
  bottom :: a
```

```
  (\/) :: a -> a -> a
```

```
data SudokuVal = One | Two | Three | Four
               deriving (Eq, Ord, Show)
```

```
class BoundedJoinSemilattice a where
  bottom :: a
  (\\) :: a -> a -> a
```

```
data SudokuVal = One | Two | Three | Four
               deriving (Eq, Ord, Show)
```

```
newtype SudokuSet = S (Set SudokuVal)
```

```
class BoundedJoinSemilattice a where
```

```
  bottom :: a
```

```
  (\\) :: a -> a -> a
```

```
data SudokuVal = One | Two | Three | Four
               deriving (Eq, Ord, Show)
```

```
newtype SudokuSet = S (Set SudokuVal)
```

```
instance BoundedJoinSemilattice SudokuSet where
```

```
  bottom      = S (Set.fromList [One, Two, Three, Four])
```

```
  S a \\ S b = S (Set.intersection a b)
```

We don't write values directly to cells
Instead we *join information in*

We don't write values directly to cells
Instead we *join information in*

This makes our propagators *monotone*, meaning that as the input cells gain information, the output cells gain information (or don't change)

We don't write values directly to cells
Instead we *join information in*

This makes our propagators *monotone*, meaning that as the input cells gain information, the output cells gain information (or don't change)

A function $f : A \rightarrow B$ where A and B are partially ordered sets is **monotone** if and only if, for all $x, y \in A$. $x \leq y \implies f(x) \leq f(y)$

The bounded join-semilattice laws and monotonicity, combined with the finiteness of our lattices, make propagator networks deterministic, even in the face of parallelism and distribution

The bounded join-semilattice laws and monotonicity, combined with the finiteness of our lattices, make propagator networks deterministic, even in the face of parallelism and distribution


Bounded join-semilattices are already popular in the distributed systems world
See: Conflict Free Replicated Datatypes

The bounded join-semilattice laws and monotonicity, combined with the finiteness of our lattices, make propagator networks deterministic, even in the face of parallelism and distribution

Bounded join-semilattices are already popular in the distributed systems world
See: Conflict Free Replicated Datatypes

We can relax these constraints in a few different directions

?



data Perhaps $a =$ Unknown | Known a | Contradiction

```
data Perhaps a = Unknown | Known a | Contradiction
```

```
instance Eq a => BoundedJoinSemiLattice (Perhaps a) where
```

```
    bottom = Unknown
```

```
    (\\) Unknown x           = x
```

```
    (\\) x           Unknown = x
```

```
    (\\) Contradiction _      = Contradiction
```


```
    (\\) _      Contradiction = Contradiction
```



```
    (\\) (Known a) (Known b) =
```


```
        if a == b
```


```
            then Known a
```


```
            else Contradiction
```
























There are loads of other bounded join-semilattices too!


$$[1, 5]$$

$$[1, 5] \cap [2, 7] = [2, 5]$$

$$[1, 5] \cap [2, 7] = [2, 5]$$


$$[2, 5] + [9, 10] = [11, 15]$$






We can use this to combine multiple imprecise measurements

What other bounded join-semilattices are there?





- Set intersection
- Set union
- Interval arithmetic
- Perhaps

And so many more!

- Set intersection
- Set union
- Interval arithmetic
- Perhaps

And so many more!

?

What happens when we hit contradiction?

What happens when we hit contradiction?

: (

What happens when we hit contradiction?

: (

Monotonicity means that contradiction propagators all over the place

If we track the provenance of information,
we can help identify the source of contradiction

If we track the provenance of information,
we can help identify the source of contradiction

Then we can keep track of which subsets of the information are consistent
and which are inconsistent

$$[2, 5] \cap [3, 7] \cap [6, 9] = []$$

$$[2, 5] \cap [3, 7] \cap [6, 9] = \emptyset$$

$$[2, 5] \cap [3, 7] = [3, 5]$$

$$[2, 5] \cap [3, 7] \cap [6, 9] = []$$

$$[2, 5] \cap [3, 7] = [3, 5]$$

$$[3, 7] \cap [6, 9] = [6, 7]$$

$$[2, 5] \cap [3, 7] \cap [6, 9] = []$$

$$[2, 5] \cap [3, 7] = [3, 5]$$

$$[3, 7] \cap [6, 9] = [6, 7]$$

$$[2, 5] \cap [6, 9] = []$$

$$[2, 5] \cap [3, 7] \cap [6, 9] = \emptyset$$

$$[2, 5] \cap [3, 7] = [3, 5]$$

$$[3, 7] \cap [6, 9] = [6, 7]$$

$$[2, 5] \cap [6, 9] = \emptyset$$

Consistent subsets:

$$\{\}$$

$$\{[2, 5]\}$$

$$\{[3, 7]\}$$

$$\{[6, 7]\}$$

$$\{[2, 5], [3, 7]\}$$

$$\{[3, 7], [6, 9]\}$$

Maximal consistent subsets:

$$\{[2, 5], [3, 7]\}$$

$$\{[3, 7], [6, 9]\}$$

$$[2, 5] \cap [3, 7] \cap [6, 9] = []$$

$$[2, 5] \cap [3, 7] = [3, 5]$$

$$[3, 7] \cap [6, 9] = [6, 7]$$

$$[2, 5] \cap [6, 9] = []$$

Consistent subsets:

$$\{\}$$

$$\{[2, 5]\}$$

$$\{[3, 7]\}$$

$$\{[6, 7]\}$$

$$\{[2, 5], [3, 7]\}$$

$$\{[3, 7], [6, 9]\}$$

Inconsistent subsets:

$$\{[2, 5], [6, 9]\}$$

$$\{[2, 5], [3, 7], [6, 9]\}$$

Minimal inconsistent
subsets:

$$\{[2, 5], [6, 9]\}$$


Maximal consistent subsets:

$$\{[2, 5], [3, 7]\}$$

$$\{[3, 7], [6, 9]\}$$

This concept is something called a *Truth Management System*

Now that we can handle contradiction, we can make guesses!
This lets us encode search problems easily



?

Alexey Radul's work on propagators:

- Art of the Propagator

<http://web.mit.edu/~axch/www/art.pdf>

- Propagation Networks: A Flexible and Expressive Substrate for Computation

<http://web.mit.edu/~axch/www/phd-thesis.pdf>

Lindsey Kuper's work on LVars is closely related, and works today:

- Lattice-Based Data Structures for Deterministic Parallel and Distributed Programming
<https://www.cs.indiana.edu/~lkuper/papers/lindsey-kuper-dissertation.pdf>
- lvish library
<https://hackage.haskell.org/package/lvish>

Edward Kmett has worked on:

- Making propagators go fast
- Scheduling strategies and garbage collection
- Relaxing requirements (Eg. not requiring a full join-semilattice, admitting non-monotone functions)

Ed's stuff:

- <http://github.com/ekmett/propagators>
- <http://github.com/ekmett/concurrent>
- Lambda Jam talk (Easy mode):
<https://www.youtube.com/watch?v=acZkF6Q2XKs>
- Boston Haskell talk (Hard mode):
<https://www.youtube.com/watch?v=DyPzPeOPgUE>

In conclusion, propagator networks:

- Admit any Haskell function you can write today ...
- ... and more functions!
- compute bidirectionally
- give us constraint solving and search
- parallelise and distribute

Thanks for listening!