

Title:	QFSAE Q20 Final Harness Design
Part Number:	Q20 Harness
Description:	Car Harness Design for QFSAE Q20 Car



From	То	Conductor	Conductor PN	Twisted With	Gauge	Length	From Contact PN	Notes
AFR.2	ECU D.22	W10.White	22 AWG White		22 AWG	≥ 12 in		AV8, AFR Signal
AFR.3	GND	W12.Black	20 AWG Black		20 AWG	≥ 12 in		Car GND -> AFR
BSPD.1	TPS1	W123.White	22 AWG White		22 AWG	≥ 7 in		BSPD TPS1 Splice
BSPD.3	BSE1	W125.White	22 AWG White		22 AWG	≥ 7 in		BSE1
BSPD.4	BSE2	W126.White	22 AWG White		22 AWG	≥ 7 in		BSE2
BSPD.5	PCB_12V	W127.Red	20 AWG Red		20 AWG	≥ 7 in		BSPD 12V
BSPD.6	GND	W128.Black	20 AWG Black		20 AWG	≥ 6 in		BSPD Ground
BSPD.7	PDM_A.A30	W49.White	22 AWG White		22 AWG	≥ 10 in		BSPD Flag Input
Battery.1	GND	W129.Black	M22759/8-8-0		8 AWG	≥ 15 in		Battery Ground
BrakeLight.1	BrakePressureSwitch.2	W40.Red	20 AWG Red		20 AWG	≥ 18 in		
BrakeLight.2	GND	W71.Black	20 AWG Black		20 AWG	≥ 6 in		Brake Light GND
BrakeOT.1	DashMasterSwitch.1	W41.Red	20 AWG Red		20 AWG	≥ 54 in		Dash -> Brake OT
CAN_COMM	COMM.9	COMM_CAN.Black	2 Wire 22 AWG shielded		22 AWG	≥ 1 in		Comm CAN Lo
CAN_COMM	COMM.10	COMM_CAN.Brown	2 Wire 22 AWG shielded		22 AWG	≥ 1 in		Comm CAN Hi
CAN_PDM	CAN_COMM	CAN3.Black	2 Wire 22 AWG shielded		22 AWG	≥ 2 in		
CAN_PDM	CAN_COMM	CAN3.Brown	2 Wire 22 AWG shielded		22 AWG	≥ 2 in		
CAN_PDM	PDM_B.B25	PDM_CAN.Black	2 Wire 22 AWG shielded twisted	Brown	22 AWG	≥ 5 in		
CAN_PDM	PDM_B.B26	PDM_CAN.Brown	2 Wire 22 AWG shielded twisted	Black	22 AWG	≥ 5 in		
DashMasterSwitch.2	PDM_A.A27	☐ W9.White	20 AWG White		20 AWG	≥ 45 in		Master Switch Input
Datalogger.8	PDM_A.A06	W30.Red	20 AWG Red		20 AWG	≥ 14 in		Datalogger Pwr
Datalogger.15	GPS.3	☐ W62.White	22 AWG White		22 AWG	≥ 10 in		GPS RX
Datalogger.16	GPS.2	W61.White	22 AWG White		22 AWG	≥ 10 in		GPS TX
Datalogger.19	FL_Damper.2	W14.White	22 AWG White		22 AWG	≥ 51 in		FL Damper
Datalogger.20	FR_Damper.2	W15.White	22 AWG White		22 AWG	≥ 51 in		FR Damper
Datalogger.21	SteeringAngle.2	W16.White	22 AWG White		22 AWG	≥ 45 in		Steering Potentiometer
Datalogger.22	FrontBrakePres.2	W19.White	22 AWG White		22 AWG	≥ 45 in		
Datalogger.27	GPS.1	W63.Black	20 AWG Black		20 AWG	≥ 10 in		GPS GND
Datalogger.28	GPS.4	W64.Red	20 AWG Red		20 AWG	≥ 10 in		GPS 5V
Datalogger.34	OilTemp.2	W45.White	22 AWG White		22 AWG	≥ 22 in		Oil Temp
Datalogger.45	RL_Damper.2	W21.White	22 AWG White		22 AWG	≥ 16 in		RL Damper
Datalogger.46	RR_Damper.2	W22.White	22 AWG White		22 AWG	≥ 16 in		RR Damper
Datalogger.47	RearBrakePres.2	W23.White	22 AWG White		22 AWG	≥ 45 in		Rear Brake Pressure
Datalogger.67	COMM.1	L180_Comm.Orange	4 Wire 22 AWG shielded		22 AWG	≥ 10 in		Ethernet Transmit +
Datalogger.68	COMM.2	L180_Comm.Brown	4 Wire 22 AWG shielded		22 AWG	≥ 10 in		Ethernet Transmit -
Datalogger.77	COMM.3	L180_Comm.Red	4 Wire 22 AWG shielded		22 AWG	≥ 10 in		Ethernet Receive +
Datalogger.78	COMM.4	L180_Comm.Black	4 Wire 22 AWG shielded		22 AWG	≥ 10 in		Ethernet Receive -
ECU_A.3	APPS1.2	W110.White	22 AWG White		22 AWG	≥ 20 in		APPS1
ECU_A.5	APPS2.2	W18.White	22 AWG White		22 AWG	≥ 18 in		APPS2 Signal
ECU_A.10	5V_C	W84.Orange	22 AWG Orange		22 AWG			ECU->5V Splice C
ECU_A.15	FL_Speed.2	W44.White	22 AWG White		22 AWG	≥ 34 in		FL Speed Signal
ECU_A.16	RR_Speed.2	W59.White	22 AWG White		22 AWG			RL Speed Signal

Wiring Table 1 of 3 Page 2 of 8

Title:	QFSAE Q20 Final Harness Design
Part Number:	Q20 Harness
Description:	Car Harness Design for QFSAE Q20 Car



From	То	Conductor	Conductor PN	Twisted With	Gauge	Length	From Contact PN	Notes
ECU_A.17	RL_Speed.2	W13.White	24 AWG White		24 AWG			RL Speed Input Signal
ECU_A.18	5V_C							<u> </u>
ECU_A.23	FR_Speed.2	W43.White	22 AWG White		22 AWG	≥ 6 in		FR Speed Signal
ECU_A.24	GND	W38.Black	20 AWG Black		20 AWG			ECU BATT -
ECU_A.25	GND	W53.Black	20 AWG Black		20 AWG			ECU BATT -
ECU_A.26	0V_C	W87.Orange	22 AWG Orange		22 AWG			ECU -> 0V C
ECU_A.27	0V_C	W88.Orange	22 AWG Orange		22 AWG			
ECU_A.32	GND	W54.Black	20 AWG Black		20 AWG			ECU BATT -
ECU_B.13	ECU_PWR	W2.Red	20 AWG Red		20 AWG			ECU 12V
ECU_B.19	ECU_PWR	W4.Red	20 AWG Red		20 AWG			ECU 12V
ECU_C.1	ETB_PWR.2	W104.Red	20 AWG Red		20 AWG	≥ 6 in		Motor +
ECU_C.3	Coil.2	W47.White	22 AWG White		22 AWG			Coil Signal
ECU_C.4	TPS2	W150.White	22 AWG White		22 AWG			TPS2
ECU_C.10	GND	W33.Black	20 AWG Black		20 AWG			ECU BATT -
ECU_C.11	GND	W34.Black	20 AWG Black		20 AWG			ECU Batt -
ECU_C.14	ThrottlePosition.2	W114.White	22 AWG White		22 AWG	≥ 6 in		TPS2
ECU_C.15	MATP.3	W52.White	22 AWG White		22 AWG	≥ 18 in		MAP Signal
ECU_C.16	GearPosition.2	W130.White	22 AWG White		22 AWG	≥ 12 in		Gear Pos Signal
ECU_C.17	OilPressure.2	W149.White	22 AWG White		22 AWG			AV4, Oil Pressure
ECU_C.18	ETB_PWR.1	W102.Black	20 AWG Black		20 AWG	≥ 6 in		Motor -
ECU_C.19	Injector.2	W75.Black	20 AWG Black		20 AWG	≥ 10 in		Injector Signal
ECU_C.20	Shifting.2	W103.Black	20 AWG Black		20 AWG			Upshift Actuator
ECU_C.21	Shifting.3	W111.Black	20 AWG Black		20 AWG			Downshift Actuator
ECU_C.25	FuelPres.2	W50.White	22 AWG White		22 AWG			Fuel Pressure
ECU_C.26	ECU_PWR	W5.Red	20 AWG Red		20 AWG			ECU 12V
ECU_D.1	CamCrank.1	CRANK.Brown	2 Wire (1 twisted pair), 24 AWG Shielded	Black	24 AWG			Crank Signal
ECU_D.3	MATP.2	W25.White	22 AWG White		22 AWG	≥ 18 in		MAT Sensor
ECU_D.4	CoolantTemp.2	W24.White	22 AWG White		22 AWG			Coolant Temp Signal
ECU_D.15	CamCrank.2	CRANK.Black	2 Wire (1 twisted pair), 24 AWG Shielded	Brown	24 AWG			Crank Ground, Sensor 0V A
ECU_D.16	ThrottlePosition.3					≥ 6 in		TPS 0V B
ECU_D.20	TPS1	W57.White	22 AWG White		22 AWG			TPS1
ECU_D.21	SteeringWheel.1	W51.White	22 AWG White		22 AWG	≥ 26 in		Rotary Switch 1, Fuel Map Toggle
ECU_D.23	COMM.5	ECU_Comm.Black	4 Wire 24 AWG shielded		24 AWG			
ECU_D.24	COMM.6	ECU_Comm.Brown	4 Wire 24 AWG shielded		24 AWG			
ECU_D.25	COMM.7	ECU_Comm.Red	4 Wire 24 AWG shielded		24 AWG			
ECU_D.26	COMM.8		4 Wire 24 AWG shielded		24 AWG			
FL_Speed.1	GND	W70.Black	20 AWG Black		20 AWG			FL Speed GND
FL_Speed.3	12V_Sensors	W99.Red	20 AWG Red		20 AWG			12V Sensor Supply
FR_Speed.1	GND	W69.Black	20 AWG Black		20 AWG			FR Speed GND
FR_Speed.3		W100.Red	20 AWG Red		20 AWG			
FanSwitch.1	PDM_A.A28	W1.Black	20 AWG Black		20 AWG	≥ 36 in		Fan GND

Wiring Table 2 of 3 Page 3 of 8

Title:	QFSAE Q20 Final Harness Design
Part Number:	Q20 Harness
Description:	Car Harness Design for QFSAE Q20 Car



From	То	Conductor	Conductor PN	Twisted With	Gauge	Length	From Contact PN	Notes
FanSwitch.2	PDM_A.A29	W35.White	20 AWG White		20 AWG	≥ 36 in		Fan Input
FuelPump.3	GND	W97.Black	20 AWG Black		20 AWG	≥ 6 in		Fuel Pump GND
GND	Fan_R.2	W68.Black	20 AWG Black		20 AWG	≥ 6 in		Right Fan Ground
GearPosition.1	0V_C	W90.Brown	22 AWG Brown		22 AWG	≥ 12 in		Gear Position GND C
GearPosition.3	5V_C	W89.Orange	22 AWG Orange		22 AWG	≥ 12 in		Gear Position 5V C
MATP.1	0V_C	W91.Brown	22 AWG Brown		22 AWG	≥ 18 in		MATP 0V C
MATP.4	5V_C	W92.Brown	22 AWG Brown		22 AWG	≥ 18 in		MATP 5V C
MasterSwitch.1	Battery.1	W65.Black	M22759/8-8-0		8 AWG	35 in		
OilPressure.1	0V_C	W93.Brown	22 AWG Brown		22 AWG			Oil Pressure 0V C
OilPressure.3	5V_C	W151.Orange	22 AWG Orange		22 AWG			Oil Pressure 5V C
OilTemp.1	0V_C	W133.Brown	22 AWG Brown		22 AWG	≥ 12 in		Oil Temp 0V C
OilTemp.3	5V_C	W132.Orange	22 AWG Orange		22 AWG	≥ 12 in		Oil Temp 5V C
PDM_A.A02	Transponder.1	W27.Red	20 AWG Red		20 AWG	≥ 23 in		Transponder
PDM_A.A03	FAN_L.1	W148.Red	20 AWG Red		20 AWG	≥ 20 in		Left Fan 12V
PDM_A.A04	Dash_MCU.1	W3.Red	20 AWG Red		20 AWG	≥ 45 in		Dash Power
PDM_A.A07	AFR.1	W31.Red	20 AWG Red		20 AWG	≥ 16 in		AFR PWR
PDM_A.A09	ECU_PWR	W26.Red	22 AWG Red		22 AWG			PDM -> ECU 12V Splice
PDM_A.A10	BrakePressureSwitch.1	W6.Red	20 AWG Red		20 AWG	≥ 16 in		PDM->Brake Switch
PDM_A.A11	Coil.1	W7.Red	20 AWG Red		20 AWG	≥ 4 in		Coil Circuit
PDM_A.A13	Injector.1	W8.Red	20 AWG Red		20 AWG	≥ 14 in		Injector
PDM_A.A15	BrakeOT.2	W42.Red	20 AWG Red		20 AWG	≥ 47 in		Master Switch Out
PDM_A.A17	ECU_PWR	W32.Red	20 AWG Red		20 AWG			PDM -> ECU 12V
PDM_B.B03	FuelPump.1	W36.Red	20 AWG Red		20 AWG	≥ 10 in		Fuel Pump PWR
PDM_B.B05	Fan_R.1	W147.Red	20 AWG Red		20 AWG	≥ 10 in		
PDM_B.B07	Shifting.1	W11.Red	20 AWG Red		20 AWG	≥ 4 in		Shifting 12V
PDM_C	MasterSwitch.2	W56.Red	M22759/87-8-2		8 AWG	≥ 24 in		
PDM_C	StarterRelay.1	W145.Red	M22759/8-8-2		8 AWG	12 in		PDM -> Starter Relay
RL_Damper.1	GND	W72.Black	20 AWG Black		20 AWG	≥ 6 in		
RL_Damper.3	12V_Sensors	W121.Red	20 AWG Red		20 AWG	≥ 6 in		
RL_Speed.1	GND	W20.Black	22 AWG Black		22 AWG			RL Speed GND
RL_Speed.3	12V_Sensors	W101.Red	20 AWG Red		20 AWG			
RR_Damper.1	GND	W122.Black	20 AWG Black		20 AWG	≥ 6 in		
RR_Damper.3	12V_Sensors	W135.Red	20 AWG Red		20 AWG	≥ 6 in		
RR_Speed.1	GND	W67.Black	20 AWG Black		20 AWG			RR Speed GND
RR_Speed.3	12V_Sensors	W 112.Red	20 AWG Red		20 AWG			12V Sensor Supply
Starter	StarterRelay.2	W 146.Red	M22759/8-8-2		8 AWG	≥ 2.67 ft		Starter Relay -> Starter
ThrottlePosition.1	TPS1	W136.White	22 AWG White		22 AWG	≥ 7 in		ETB TPS1

Wiring Table 3 of 3 Page 4 of 8

Title:	
Part Number:	Q20 Harness
Description:	Car Harness Design for QFSAE Q20 Car



#	Туре	Reference Designator	Manufacturer	Part Number	Color	Gauge	Length	Twisted With
1	Cable	CAN1		2 Wire 22 AWG shielded	☐☐ White		0 in	
2	Cable	CAN2		2 Wire 22 AWG shielded	☐☐ White		0 in	
3	Cable	CAN3		2 Wire 22 AWG shielded	☐☐ White		≥ 2 in	
4	Cable	COMM_CAN		2 Wire 22 AWG shielded	☐☐ White		≥ 1 in	
5	Cable	CRANK		2 Wire (1 twisted pair), 24 AWG Shielded	☐☐ White			
6	Cable	ECU_Comm		4 Wire 24 AWG shielded	☐☐ White			
7	Cable	L180_Comm		4 Wire 22 AWG shielded	☐☐ White		≥ 10 in	
8	Cable	MCU_CAN		2 Wire 22 AWG shielded	☐☐ White		0 in	
9	Cable	PDM_CAN		2 Wire 22 AWG shielded twisted	☐☐ White		≥ 5 in	
10	Wire	W1		20 AWG Black	Black	20 AWG	≥ 36 in	
11	Wire	W2		20 AWG Red	Red	20 AWG		
12	Wire	W3		20 AWG Red	Red	20 AWG	≥ 45 in	
13	Wire	W4		20 AWG Red	Red	20 AWG		
14	Wire	W5		20 AWG Red	Red	20 AWG		
15	Wire	W6		20 AWG Red	Red	20 AWG	≥ 16 in	
16	Wire	W7		20 AWG Red	Red	20 AWG	≥ 4 in	
17	Wire	W8		20 AWG Red	Red	20 AWG	≥ 14 in	
	Wire	W9		20 AWG White	☐☐ White	20 AWG	≥ 45 in	
	Wire	W10		22 AWG White	☐☐ White	22 AWG	≥ 12 in	
20	Wire	W11		20 AWG Red	Red	20 AWG	≥ 4 in	
21	Wire	W12		20 AWG Black	Black	20 AWG	≥ 12 in	
	Wire	W13		24 AWG White	☐☐ White	24 AWG		
	Wire	W14		22 AWG White	☐☐ White	22 AWG	≥ 51 in	
24	Wire	W15		22 AWG White	☐☐ White	22 AWG	≥ 51 in	
	Wire	W16		22 AWG White	☐☐ White	22 AWG	≥ 45 in	
	Wire	W17		22 AWG White	☐☐ White	22 AWG	0 in	
27	Wire	W18		22 AWG White	☐☐ White	22 AWG	≥ 18 in	
28	Wire	W19		22 AWG White	☐☐ White	22 AWG	≥ 45 in	
	Wire	W20		22 AWG Black	Black	22 AWG		
30	Wire	W21		22 AWG White	☐☐ White	22 AWG	≥ 16 in	
	Wire	W22		22 AWG White	☐☐ White	22 AWG	≥ 16 in	
	Wire	W23		22 AWG White	☐☐ White	22 AWG	≥ 45 in	
	Wire	W24		22 AWG White	☐☐ White	22 AWG		
	Wire	W25		22 AWG White	☐☐ White	22 AWG	≥ 18 in	
	Wire	W26		22 AWG Red	Red	22 AWG		
	Wire	W27		20 AWG Red	Red	20 AWG	≥ 23 in	
	Wire	W28		22 AWG White	☐ White	22 AWG	0 in	
	Wire	W29		22 AWG White	☐ White	22 AWG	0 in	
	Wire	W30		20 AWG Red	Red	20 AWG	≥ 14 in	
	Wire	W31		20 AWG Red	Red	20 AWG	≥ 16 in	
	Wire	W32		20 AWG Red	Red	20 AWG		

Cutlist 1 of 4 Page 5 of 8

Title:	
Part Number:	Q20 Harness
Description:	Car Harness Design for QFSAE Q20 Car



#	Туре	Reference Designator	Manufacturer	Part Number	Color	Gauge	Length	Twisted With
	42 Wire	W33		20 AWG Black	■ Black	20 AWG		
	43 Wire	W34		20 AWG Black	Black	20 AWG		
	44 Wire	W35		20 AWG White	☐☐ White	20 AWG	≥ 36 in	
	45 Wire	W36		20 AWG Red	Red	20 AWG	≥ 10 in	
	46 Wire	W37		20 AWG Red	Red	20 AWG	0 in	
	47 Wire	W38		20 AWG Black	Black	20 AWG		
	48 Wire	W39		22 AWG White	☐☐ White	22 AWG	0 in	
	49 Wire	W40		20 AWG Red	Red	20 AWG	≥ 18 in	
	50 Wire	W41		20 AWG Red	Red	20 AWG	≥ 54 in	
	51 Wire	W42		20 AWG Red	Red	20 AWG	≥ 47 in	
	52 Wire	W43		22 AWG White	☐☐ White	22 AWG	≥ 6 in	
	53 Wire	W44		22 AWG White	☐☐ White	22 AWG	≥ 34 in	
	54 Wire	W45		22 AWG White	☐☐ White	22 AWG	≥ 22 in	
	55 Wire	W46		22 AWG White	☐☐ White	22 AWG	0 in	
	56 Wire	W47		22 AWG White	☐☐ White	22 AWG		
	57 Wire	W48		22 AWG White	☐☐ White	22 AWG	0 in	
	58 Wire	W49		22 AWG White	☐☐ White	22 AWG	≥ 10 in	
	59 Wire	W50		22 AWG White	☐☐ White	22 AWG		
	60 Wire	W51		22 AWG White	☐☐ White	22 AWG	≥ 26 in	
	61 Wire	W52		22 AWG White	☐☐ White	22 AWG	≥ 18 in	
	62 Wire	W53		20 AWG Black	Black	20 AWG		
	63 Wire	W54		20 AWG Black	Black	20 AWG		
	64 Wire	W55		22 AWG White	☐☐ White	22 AWG	0 in	
	65 Wire	W56		M22759/87-8-2	Red	8 AWG	≥ 24 in	
	66 Wire	W57		22 AWG White	☐☐ White	22 AWG		
	67 Wire	W58		22 AWG White	☐☐ White	22 AWG	0 in	
	68 Wire	W59		22 AWG White	☐☐ White	22 AWG		
	69 Wire	W60		22 AWG White	☐☐ White	22 AWG	0 in	
	70 Wire	W61		22 AWG White	☐☐ White	22 AWG	≥ 10 in	
	71 Wire	W62		22 AWG White	☐☐ White	22 AWG	≥ 10 in	
	72 Wire	W63		20 AWG Black	Black	20 AWG	≥ 10 in	
	73 Wire	W64		20 AWG Red	Red	20 AWG	≥ 10 in	
	74 Wire	W65		M22759/8-8-0	Black	8 AWG	35 in	
	75 Wire	W66		20 AWG Red	Red	20 AWG	0 in	
	76 Wire	W67		20 AWG Black	Black	20 AWG		
	77 Wire	W68		20 AWG Black	Black	20 AWG	≥ 6 in	
	78 Wire	W69		20 AWG Black	Black	20 AWG	≥ 6 in	
	79 Wire	W70		20 AWG Black	Black	20 AWG	≥ 34 in	
	80 Wire	W71		20 AWG Black	Black	20 AWG	≥ 6 in	
	81 Wire	W72		20 AWG Black	Black	20 AWG	≥ 6 in	
	82 Wire	W73		20 AWG Black	Black	20 AWG	0 in	

Cutlist 2 of 4 Page 6 of 8

Title:	
Part Number:	Q20 Harness
Description:	Car Harness Design for QFSAE Q20 Car



#	Туре	Reference Designator	Manufacturer	Part Number	Color	Gauge	Length	Twisted With
83	Wire	W74		20 AWG Black	Black	20 AWG	0 in	
84	Wire	W75		20 AWG Black	■ Black	20 AWG	≥ 10 in	
85	Wire	W76		20 AWG Black	Black	20 AWG	0 in	
86	Wire	W77		20 AWG Black	Black	20 AWG	0 in	
87	Wire	W78		20 AWG Black	Black	20 AWG	0 in	
88	Wire	W79		20 AWG Black	Black	20 AWG	0 in	
89	Wire	W80		20 AWG Black	Black	20 AWG	0 in	
90	Wire	W81		20 AWG Black	Black	20 AWG	0 in	
91	Wire	W82		20 AWG Black	Black	20 AWG	0 in	
92	Wire	W83		22 AWG Orange	Orange	22 AWG	0 in	
93	Wire	W84		22 AWG Orange	Orange	22 AWG		
94	Wire	W85		22 AWG Orange	Orange	22 AWG	0 in	
95	Wire	W86		22 AWG Orange	Orange	22 AWG	0 in	
96	Wire	W87		22 AWG Orange	Orange	22 AWG		
97	Wire	W88		22 AWG Orange	Orange	22 AWG		
98	Wire	W89		22 AWG Orange	Orange	22 AWG	≥ 12 in	
99	Wire	W90		22 AWG Brown	Brown	22 AWG	≥ 12 in	
100	Wire	W91		22 AWG Brown	Brown	22 AWG	≥ 18 in	
101	Wire	W92		22 AWG Brown	Brown	22 AWG	≥ 18 in	
102	Wire	W93		22 AWG Brown	Brown	22 AWG		
103	Wire	W94		22 AWG Brown	Brown	22 AWG	0 in	
104	Wire	W95		22 AWG Brown	Brown	22 AWG	0 in	
105	Wire	W96		22 AWG Brown	Brown	22 AWG	0 in	
106	Wire	W97		20 AWG Black	Black	20 AWG	≥ 6 in	
107	Wire	W98		22 AWG White	☐☐ White	22 AWG	0 in	
108	Wire	W99		20 AWG Red	Red	20 AWG	≥ 34 in	
109	Wire	W100		20 AWG Red	Red	20 AWG	≥ 6 in	
110	Wire	W101		20 AWG Red	Red	20 AWG		
111	Wire	W102		20 AWG Black	Black	20 AWG	≥ 6 in	
112	Wire	W103		20 AWG Black	Black	20 AWG		
113	Wire	W104		20 AWG Red	Red	20 AWG	≥ 6 in	
114	Wire	W105		22 AWG White	☐☐ White	22 AWG	0 in	
115	Wire	W106		22 AWG White	☐☐ White	22 AWG	0 in	
116	Wire	W107		22 AWG White	☐☐ White	22 AWG	0 in	
117	Wire	W108		22 AWG White	☐ White	22 AWG	0 in	
118	Wire	W109		22 AWG White	☐☐ White	22 AWG	0 in	
119	Wire	W110		22 AWG White	☐☐ White	22 AWG	≥ 20 in	
120	Wire	W111		20 AWG Black	Black	20 AWG		
121	Wire	W112		20 AWG Red	Red	20 AWG		
	Wire	W113		22 AWG White	☐☐ White	22 AWG	0 in	
123	Wire	W114		22 AWG White	☐☐ White	22 AWG	≥ 6 in	

Cutlist 3 of 4 Page 7 of 8

Title:		
Part Number:	Q20 Harness	
Description:	Car Harness Design for QFSAE Q20 Car	



#	Туре	Reference Designator	Manufacturer	Part Number	Color	Gauge	Length	Twisted With
124	Wire	W115		22 AWG White	☐☐ White	22 AWG	0 in	
125	Wire	W116		22 AWG White	☐☐ White	22 AWG	0 in	
126	Wire	W117		22 AWG White	☐☐ White	22 AWG	0 in	
127	Wire	W118		22 AWG White	☐☐ White	22 AWG	0 in	
128	Wire	W119		22 AWG White	☐☐ White	22 AWG	0 in	
129	Wire	W120		22 AWG White	☐☐ White	22 AWG	0 in	
130	Wire	W121		20 AWG Red	Red	20 AWG	≥ 6 in	
131	Wire	W122		20 AWG Black	Black	20 AWG	≥ 6 in	
132	Wire	W123		22 AWG White	☐☐ White	22 AWG	≥ 7 in	
133	Wire	W124		22 AWG White	☐☐ White	22 AWG	0 in	
134	Wire	W125		22 AWG White	☐☐ White	22 AWG	≥ 7 in	
135	Wire	W126		22 AWG White	☐☐ White	22 AWG	≥ 7 in	
136	Wire	W127		20 AWG Red	Red	20 AWG	≥ 7 in	
137	Wire	W128		20 AWG Black	Black	20 AWG	≥ 6 in	
138	Wire	W129		M22759/8-8-0	Black	8 AWG	≥ 15 in	
139	Wire	W130		22 AWG White	☐☐ White	22 AWG	≥ 12 in	
140	Wire	W131		22 AWG Brown	Brown	22 AWG	0 in	
141	Wire	W132		22 AWG Orange	Orange	22 AWG	≥ 12 in	
142	Wire	W133		22 AWG Brown	Brown	22 AWG	≥ 12 in	
143	Wire	W134		20 AWG Black	Black	20 AWG	0 in	
144	Wire	W135		20 AWG Red	Red	20 AWG	≥ 6 in	
145	Wire	W136		22 AWG White	☐☐ White	22 AWG	≥ 7 in	
146	Wire	W137		20 AWG Red	Red	20 AWG	0 in	
147	Wire	W138		20 AWG Red	Red	20 AWG	0 in	
148	Wire	W139		20 AWG Red	Red	20 AWG	0 in	
149	Wire	W140		20 AWG Red	Red	20 AWG	0 in	
150	Wire	W141		20 AWG Red	Red	20 AWG	0 in	
151	Wire	W142		20 AWG Red	Red	20 AWG	0 in	
152	Wire	W143		20 AWG Red	Red	20 AWG	0 in	
153	Wire	W144		20 AWG Red	Red	20 AWG	0 in	
154	Wire	W145		M22759/8-8-2	Red	8 AWG	12 in	
155	Wire	W146		M22759/8-8-2	Red	8 AWG	≥ 2.67 ft	
	Wire	W147		20 AWG Red	Red	20 AWG	≥ 10 in	
157	Wire	W148		20 AWG Red	Red	20 AWG	≥ 20 in	
158	Wire	W149		22 AWG White	☐☐ White	22 AWG		
159	Wire	W150		22 AWG White	☐☐ White	22 AWG		
160	Wire	W151		22 AWG Orange	Orange	22 AWG		
161		ECU_A.18 - 5V_C						
162		ECU_D.16 - ThrottlePosition.3					≥ 6 in	

Cutlist 4 of 4 Page 8 of 8