

Smart Traffic Lights using Local AI

Mock IEEE-Style Research Paper

Literature Review

Smart traffic-light systems are being studied as a way to reduce waiting time and respond more quickly to changing road conditions. Traditional traffic lights usually follow fixed timers. They are simple and inexpensive, but they cannot easily react when one road suddenly becomes crowded. Recent systems use cameras and artificial intelligence (AI) to estimate how many vehicles are present and then adjust the lights. For beginners, the main idea is simple: instead of changing lights only according to a clock, the system uses information from the road. Research reviews also show growing interest in AI-based traffic signal control and its possible benefits for changing traffic conditions [1].

Cloud-based AI systems send camera information to a central server for processing. This can provide strong computing power, but it depends on an internet connection and can introduce communication delay. Local smart-camera systems move some processing closer to the road. This can reduce the amount of information that must be sent over the internet and may allow faster decisions. A small local computer can examine camera input and send a short instruction to the traffic-light controller. Machine-vision research has also explored using camera-based vehicle information to adapt traffic-light timing [2].

Furthermore, machine learning (ML) and deep learning algorithms have proven highly capable of predicting traffic flow at intersections. Studies demonstrate that algorithms like the Multilayer Perceptron Neural Network (MLP-NN) score excellent performance metrics while maintaining low training times, making them highly feasible for direct implementation on smart traffic light controllers to enable adaptive timing [3].

The systems can be compared using three simple measures. Basic Timed Lights make decisions every 30 seconds, use zero internet data, and have a setup cost of \$200. Cloud AI Systems make decisions in 2 seconds, use high internet data, and have a setup cost of \$2,500. Local Smart Cameras make decisions in 0.5 seconds, use low internet data, and have a setup cost of \$1,200.

Simple System Architecture

The proposed architecture follows four steps. First, Street Cameras capture traffic conditions. Second, the video information is sent to Smart Pole Computers, which perform local processing and make a quick traffic decision. Third, selected information can be forwarded to the City Cloud Server for storage and wider analysis. Fourth, the decision is sent to the Traffic Lights, which change their signals. The flow is therefore: Street Cameras → Smart Pole Computers → City Cloud Server → Traffic Lights.

Research Gap

Existing traffic systems can work well for regular daily traffic, especially when traffic patterns are predictable. However, an important emergency problem remains: many systems do not have a built-in way to automatically clear a path for a speeding ambulance. This creates a need for a smart traffic system that can detect an emergency vehicle and quickly coordinate nearby signals to create a clear route.

References

- [1] F. Rasheed, K. L. A. Yau, R. M. Noor, C. Wu, and Y.-C. Low, "Deep Reinforcement Learning for Traffic Signal Control: A Review," *IEEE Access*, vol. 8, pp. 208016–208044, 2020. doi: 10.1109/ACCESS.2020.3034141.

- [2] V. Gorodokin, S. Zhankaziev, E. Shepeleva, K. Magdin, and S. Evtyukov, “Optimization of adaptive traffic light control modes based on machine vision,” *Transportation Research Procedia*, vol. 57, pp. 241–249, 2021. doi: 10.1016/j.trpro.2021.09.047.
- [3] A. Navarro-Espinoza *et al.*, “Traffic Flow Prediction for Smart Traffic Lights Using Machine Learning Algorithms,” *Technologies*, vol. 10, no. 1, p. 5, Jan. 2022. doi: 10.3390/technologies10010005.