Virtual Memory: Systems

15-213: Introduction to Computer Systems
18th Lecture, March 27, 2018

Instructor:

Franz Franchetti, Seth Copen Goldstein, and Brian Railing

Recap: Hmmm, How Does This Work?!



VM as a Tool for Memory Management

- Simplifying memory allocation
- Sharing code and data among processes



Review: Virtual Memory & Physical Memory



- A *page table* contains page table entries (PTEs) that map virtual pages to physical pages.

Translating with a k-level Page Table

- **Having multiple levels greatly reduces page table size**



Translation Lookaside Buffer (TLB)

- A small cache of page table entries with fast access by MMU



Typically, a TLB hit eliminates the k memory accesses required to do a page table lookup.

Set Associative Cache: Read

- *Locate set*
- *Check if any line in set has matching tag*
- *Yes + line valid: hit*
- *Locate data starting at offset*



Review of Symbols

- **Basic Parameters**
  - **$N = 2^n$** : Number of addresses in virtual address space
  - **$M = 2^m$** : Number of addresses in physical address space
  - **$P = 2^p$** : Page size (bytes)



- **Components of the *virtual address* (VA)**
  - **TLBI**: TLB index
  - **TLBT**: TLB tag
  - **VPO**: Virtual page offset
  - **VPN**: Virtual page number



- **Components of the *physical address* (PA)**
  - **PPO**: Physical page offset (same as VPO)
  - **PPN:** Physical page number
  - **CO**: Byte offset within cache line
  - **CI:** Cache index
  - **CT**: Cache tag

(bits per field for our simple example)



Today

- **Simple memory system example**
- Case study: Core i7/Linux memory system
- Memory mapping

Simple Memory System Example

- **Addressing**
  - 14-bit virtual addresses
  - 12-bit physical address
  - Page size = 64 bytes



Simple Memory System TLB

- 16 entries
- 4-way associative

TLBT | TLBI

13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	0	0	1	1	0	1						

VPN | VPO

VPN = 0b1101 = 0x0D

Translation Lookaside Buffer (TLB)

Set	Tag	PPN	Valid	Tag	PPN	Valid	Tag	PPN	Valid	Tag	PPN	Valid
0	03	–	0	09	0D	1	00	–	0	07	02	1
1	03	2D	1	02	–	0	04	–	0	0A	–	0
2	02	–	0	08	–	0	06	–	0	03	–	0
3	07	–	0	03	0D	1	0A	34	1	02	–	0

Simple Memory System Page Table

Only showing the first 16 entries (out of 256)

VPN	PPN	Valid
00	28	1
01	–	0
02	33	1
03	02	1
04	–	0
05	16	1
06	–	0
07	–	0

VPN	PPN	Valid
08	13	1
09	17	1
0A	09	1
0B	–	0
0C	–	0
0D	2D	1
0E	11	1
0F	0D	1

0x0D → 0x2D



Simple Memory System Cache

- 16 lines, 4-byte block size
- Physically addressed
- Direct mapped

V[0b00001101101001] = V[0x369]

P[0b101101101001] = P[0xB69] = ?



Idx	Tag	Valid	B0	B1	B2	B3
0	19	1	99	11	23	11
1	15	0	–	–	–	–
2	1B	1	00	02	04	08
3	36	0	–	–	–	–
4	32	1	43	6D	8F	09
5	0D	1	36	72	F0	1D
6	31	0	–	–	–	–
7	16	1	11	C2	DF	03

Idx	Tag	Valid	B0	B1	B2	B3
8	24	1	3A	00	51	89
9	2D	0	–	–	–	–
A	2D	1	93	15	DA	3B
B	0B	0	–	–	–	–
C	12	0	–	–	–	–
D	16	1	04	96	34	15
E	13	1	83	77	1B	D3
F	14	0	–	–	–	–

Simple Memory System Cache

- 16 lines, 4-byte block size
- Physically addressed
- Direct mapped

V[0b00001101101001] = V[0x369]

P[0b101101101001] = P[0xB69] = 0x15

CT						CI				CO	
11	10	9	8	7	6	5	4	3	2	1	0
1	0	1	1	0	1	1	0	1	0	0	1
PPN						PPO					

Idx	Tag	Valid	B0	B1	B2	B3
0	19	1	99	11	23	11
1	15	0	–	–	–	–
2	1B	1	00	02	04	08
3	36	0	–	–	–	–
4	32	1	43	6D	8F	09
5	0D	1	36	72	F0	1D
6	31	0	–	–	–	–
7	16	1	11	C2	DF	03

Idx	Tag	Valid	B0	B1	B2	B3
8	24	1	3A	00	51	89
9	2D	0	–	–	–	–
A	2D	1	93	15	DA	3B
B	0B	0	–	–	–	–
C	12	0	–	–	–	–
D	16	1	04	96	34	15
E	13	1	83	77	1B	D3
F	14	0	–	–	–	–

Address Translation Example

Idx	Tag	Valid	B0	B1	B2	B3
0	19	1	99	11	23	11
1	15	0	–	–	–	–
2	1B	1	00	02	04	08
3	36	0	–	–	–	–
4	32	1	43	6D	8F	09
5	0D	1	36	72	F0	1D
6	31	0	–	–	–	–
7	16	1	11	C2	DF	03

Idx	Tag	Valid	B0	B1	B2	B3
8	24	1	3A	00	51	89
9	2D	0	–	–	–	–
A	2D	1	93	15	DA	3B
B	0B	0	–	–	–	–
C	12	0	–	–	–	–
D	16	1	04	96	34	15
E	13	1	83	77	1B	D3
F	14	0	–	–	–	–

Physical Address

CT CI CO

Set	Tag	PPN	Valid	Tag	PPN	Valid	Tag	PPN	Valid	Tag	PPN	Valid
0	03	–	0	09	0D	1	00	–	0	07	02	1
1	03	2D	1	02	–	0	04	–	0	0A	–	0
2	02	–	0	08	–	0	06	–	0	03	–	0
3	07	–	0	03	0D	1	0A	34	1	02	–	0

Address Translation Example: TLB/Cache Miss

Idx	Tag	Valid	B0	B1	B2	B3
0	19	1	99	11	23	11
1	15	0	–	–	–	–
2	1B	1	00	02	04	08
3	36	0	–	–	–	–
4	32	1	43	6D	8F	09
5	0D	1	36	72	F0	1D
6	31	0	–	–	–	–
7	16	1	11	C2	DF	03

Idx	Tag	Valid	B0	B1	B2	B3
8	24	1	3A	00	51	89
9	2D	0	–	–	–	–
A	2D	1	93	15	DA	3B
B	0B	0	–	–	–	–
C	12	0	–	–	–	–
D	16	1	04	96	34	15
E	13	1	83	77	1B	D3
F	14	0	–	–	–	–

Physical Address

CT						CI				CO	
11	10	9	8	7	6	5	4	3	2	1	0
1	0	1	0	0	0	1	0	0	0	0	0
PPN						PPO					

CO 0 CI 0x8 CT 0x28 Hit? N Byte: Mem

Page table

VPN	PPN	Valid
00	28	1
01	–	0
02	33	1
03	02	1
04	–	0
05	16	1
06	–	0
07	–	0

Virtual Memory Exam Question

Problem 5. (10 points):

Assume a System that has

1. A two way set associative TLB
2. A TLB with 8 total entries
3. 2^8 byte page size
4. 2^{16} bytes of virtual memory
5. one (or more) boats

Hex	Decimal	Binary
0	0	0000
1	1	0001
2	2	0010
3	3	0011
4	4	0100
5	5	0101
6	6	0110
7	7	0111
8	8	1000
9	9	1001
A	10	1010
B	11	1011
C	12	1100
D	13	1101
E	14	1110
F	15	1111

TLB

Index	Tag	Frame Number	Valid
0	0x13	0x30	1
	0x34	0x58	0
1	0x1F	0x80	0
	0x2A	0x72	1
2	0x1F	0x95	1
	0x20	0xAA	0
3	0x3F	0x20	1
	0x3E	0xFF	0

TLBT | TLBI

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	1	1	1	1	0	1	0	0	0	0	1	0	1

A. Use the TLB to fill in the table. Strike out anything that you don't have enough information to fill in.

Virtual Address	Physical Address
0x7E85	0x9585
0xD301	------
0x4C20	0x3020
0xD040	------
------	0x5830

0x7E85 = 0x0111111010000101 → TLBI = 0x2, TLBT = 0x1F

0x7E85 → 0x9585

Exam: http://www.cs.cmu.edu/~213/oldexams/exam2b-s11.pdf (solution)

Break Time!

flummox: “To confuse (a lot)"

Check out:

Quiz: day 18: VM

https://canvas.cmu.edu/courses/3822

Today

- Simple memory system example
- **Case study: Core i7/Linux memory system**
- Memory mapping

Intel Core i7 Memory System



End-to-end Core i7 Address Translation



Core i7 Level 1-3 Page Table Entries

63	62–52	51–12	11–9	8	7	6	5	4	3	2	1	0
XD	Unused	Page table physical base address	Unused	G	PS		A	CD	WT	U/S	R/W	P=1

Available for OS (page table location on disk)	P=0

Each entry references a 4K child page table. Significant fields:

P: Child page table present in physical memory (1) or not (0).

R/W: Read-only or read-write access access permission for all reachable pages.

U/S: user or supervisor (kernel) mode access permission for all reachable pages.

WT: Write-through or write-back cache policy for the child page table.

A: Reference bit (set by MMU on reads and writes, cleared by software).

PS: Page size either 4 KB or 4 MB (defined for Level 1 PTEs only).

Page table physical base address: 40 most significant bits of physical page table address (forces page tables to be 4KB aligned)

XD: Disable or enable instruction fetches from all pages reachable from this PTE.

Core i7 Level 4 Page Table Entries

63	62 52	51 12	11 9	8	7	6	5	4	3	2	1	0
XD	Unused	Page physical base address	Unused	G		D	A	CD	WT	U/S	R/W	P=1

Available for OS (page location on disk)	P=0

Each entry references a 4K child page. Significant fields:

P: Child page is present in memory (1) or not (0)

R/W: Read-only or read-write access permission for child page

U/S: User or supervisor mode access

WT: Write-through or write-back cache policy for this page

A: Reference bit (set by MMU on reads and writes, cleared by software)

D: Dirty bit (set by MMU on writes, cleared by software)

Page physical base address: 40 most significant bits of physical page address
(forces pages to be 4KB aligned)

XD: Disable or enable instruction fetches from this page.

Core i7 Page Table Translation



Cute Trick for Speeding Up L1 Access



- **Observation**
  - Bits that determine CI identical in virtual and physical address
  - Can index into cache while address translation taking place
  - Generally we hit in TLB, so PPN bits (CT bits) available next
  - ***"Virtually indexed, physically tagged"***
  - Cache carefully sized to make this possible

Virtual Address Space of a Linux Process



Linux Organizes VM as Collection of "Areas"



- **pgd:**
  - Page global directory address
  - Points to L1 page table
- **vm_prot:**
  - Read/write permissions for this area
- **vm_flags**
  - Pages **shared** with other processes or **private** to this process

Each process has own **`task_struct`**, etc

Linux Page Fault Handling



Segmentation fault:
accessing a non-existing page

Normal page fault

Protection exception:
e.g., violating permission by writing to a read-only page (Linux reports as Segmentation fault)

Today

- Simple memory system example
- Case study: Core i7/Linux memory system
- **Memory mapping**

Memory Mapping

- **VM areas initialized by associating them with disk objects.**
  - Called ***memory mapping***

- **Area can be *backed by* (i.e., get its initial values from) :**
  - ***Regular file*** on disk (e.g., an executable object file)
    - Initial page bytes come from a section of a file
  - ***Anonymous file*** (e.g., nothing)
    - First fault will allocate a physical page full of 0's (***demand-zero page***)
    - Once the page is written to (***dirtied***), it is like any other page

- **Dirty pages are copied back and forth between memory and a special *swap file*.**

Review: Memory Management & Protection

- Code and data can be isolated or shared among processes



Sharing Revisited: Shared Objects



- **Process 1 maps the shared object (on disk).**

Sharing Revisited: Shared Objects



- **Process 2 maps the same shared object.**
- **Notice how the virtual addresses can be different.**

Sharing Revisited: Private Copy-on-write (COW) Objects



- Two processes mapping a ***private copy-on-write (COW)*** object
- Area flagged as private copy-on-write
- PTEs in private areas are flagged as read-only

Sharing Revisited:
Private Copy-on-write (COW) Objects



- **Instruction writing to private page triggers protection fault.**
- **Handler creates new R/W page.**
- **Instruction restarts upon handler return.**
- **Copying deferred as long as possible!**

The `fork` Function Revisited

- **VM and memory mapping explain how `fork` provides private address space for each process.**

- **To create virtual address for new process:**
  - Create exact copies of current **`mm_struct`**, **`vm_area_struct`**, and page tables.
  - Flag each page in both processes as read-only
  - Flag each **`vm_area_struct`** in both processes as private COW

- **On return, each process has exact copy of virtual memory.**

- **Subsequent writes create new pages using COW mechanism.**

The execve Function Revisited



- **To load and run a new program `a.out` in the current process using `execve`:**
- **Free `vm_area_struct`'s and page tables for old areas**
- **Create `vm_area_struct`'s and page tables for new areas**
  - Programs and initialized data backed by object files.
  - `.bss` and stack backed by anonymous files.
- **Set PC to entry point in `.text`**
  - Linux will fault in code and data pages as needed.

Finding More Shareable Pages

- **Easy places to identify shareable pages**
  - Child created via `fork`
  - Processes loading the same binary file
    - E.g., bash or python interpreters, web browsers, ...
  - Processes loading the same library file
- **What about others?**
  - Kernel Same-Page Merging
  - OS scans through all of physical memory, looking for duplicate pages
  - When found, merge into single copy, marked as copy-on-write
  - Implemented in Linux kernel in 2009
  - Limited to pages marked as likely candidates
  - Especially useful when processor running many virtual machines

User-Level Memory Mapping

```
void *mmap(void *start, int len,
           int prot, int flags, int fd, int offset)
```

- **Map `len` bytes starting at offset `offset` of the file specified by file description `fd`, preferably at address `start`**
  - `start`: may be 0 for "pick an address"
  - `prot`: PROT_READ, PROT_WRITE, PROT_EXEC, ...
  - `flags`: MAP_ANON, MAP_PRIVATE, MAP_SHARED, ...

- **Return a pointer to start of mapped area (may not be `start`)**

User-Level Memory Mapping

```
void *mmap(void *start, int len,
           int prot, int flags, int fd, int offset)
```



Example: Using mmap to Copy Files

- Copying a file to `stdout` without transferring data to user space

```c
#include "csapp.h"

void mmapcopy(int fd, int size)
{

    /* Ptr to memory mapped area */
    char *bufp;

    bufp = mmap(NULL, size,
                PROT_READ,
                MAP_PRIVATE,
                fd, 0);
    write(1, bufp, size);
    return;
}
```

mmapcopy.c

```c
/* mmapcopy driver */
int main(int argc, char **argv)
{
    struct stat stat;
    int fd;

    /* Check for required cmd line arg */
    if (argc != 2) {
        printf("usage: %s <filename>\n",
               argv[0]);
        exit(0);
    }

    /* Copy input file to stdout */
    fd = Open(argv[1], O_RDONLY, 0);
    fstat(fd, &stat);
    mmapcopy(fd, stat.st_size);
    exit(0);
}
```

mmapcopy.c

Some Uses of mmap

- **Reading big files**
  - Uses paging mechanism to bring files into memory
- **Shared data structures**
  - When call with **`MAP_SHARED`** flag
    - Multiple processes have access to same region of memory
    - Risky!
- **File-based data structures**
  - E.g., database
  - Give **`prot`** argument **`PROT_READ | PROT_WRITE`**
  - When unmap region, file will be updated via write-back
  - Can implement load from file / update / write back to file

Summary

- **VM requires hardware support**
  - Exception handling mechanism
  - TLB
  - Various control registers
- **VM requires OS support**
  - Managing page tables
  - Implementing page replacement policies
  - Managing file system
- **VM enables many capabilities**
  - Loading programs from memory
  - Forking processes
  - Providing memory protection

Today: Virtual Memory Systems

- Simple memory system example
- Case study: Core i7/Linux memory system
- Memory mapping

Next Lecture

- **Dynamic Memory Allocation**