ISO 20022

Account Switching - ISO - Latest version

Message Definition Report - Part 2

Approved by the Payments SEG on 19 March 2018.

This document provides details of the Message Definitions for Account Switching - ISO - Latest version.

March 2018

Table of Contents

1 Message Set Overview 4
1.1 List of MessageDefinitions 4
2 acmt.027.001.01 AccountSwitchInformationRequestV01 6
2.1 MessageDefinition Functionality 6
2.2 Structure 7
2.3 Constraints 7
2.4 Message Building Blocks 8
3 acmt.028.001.01 AccountSwitchInformationResponseV01 17
3.1 MessageDefinition Functionality 17
3.2 Structure 18
3.3 Constraints 18
3.4 Message Building Blocks 21
4 acmt.029.001.01 AccountSwitchCancelExistingPaymentV01 35
4.1 MessageDefinition Functionality 35
4.2 Structure 36
4.3 Constraints 36
4.4 Message Building Blocks 39
5 acmt.030.001.01 AccountSwitchRequestRedirectionV01 52
5.1 MessageDefinition Functionality 52
5.2 Structure 53
5.3 Constraints 53
5.4 Message Building Blocks 54
6 acmt.031.001.01 AccountSwitchRequestBalanceTransferV01 60
6.1 MessageDefinition Functionality 60
6.2 Structure 61
6.3 Constraints 61
6.4 Message Building Blocks 62
7 acmt.032.001.01 AccountSwitchBalanceTransferAcknowledgementV01 69
7.1 MessageDefinition Functionality 69
7.2 Structure 70
7.3 Constraints 70
7.4 Message Building Blocks 71
8 acmt.033.001.01 AccountSwitchNotifyAccountSwitchCompleteV01 77
8.1 MessageDefinition Functionality 77
8.2 Structure 78
8.3 Constraints 78
8.4 Message Building Blocks 78

9 acmt.034.001.01 AccountSwitchRequestPaymentV01 83
9.1 MessageDefinition Functionality 83
9.2 Structure 84
9.3 Constraints 87
9.4 Message Building Blocks 89
10 acmt.035.001.01 AccountSwitchPaymentResponseV01 128
10.1 MessageDefinition Functionality 128
10.2 Structure 128
10.3 Constraints 129
10.4 Message Building Blocks 129
11 acmt.036.001.01 AccountSwitchTerminationSwitchV01 134
11.1 MessageDefinition Functionality 134
11.2 Structure 134
11.3 Constraints 135
11.4 Message Building Blocks 135
12 acmt.037.001.01 AccountSwitchTechnicalRejectionV01 140
12.1 MessageDefinition Functionality 140
12.2 Structure 140
12.3 Constraints 141
12.4 Message Building Blocks 141
13 Message Items Types 146
13.1 MessageComponents 146
13.2 Message Datatypes 359

1 Message Set Overview

Introduction

The Account Switch Service provides the central functions required to support the guaranteed switch of a customer's account and the transfer of payments arrangements associated with the account from one payment institution to another payment institution in seven working days. Payment institutions may use some of the central functions to provide a partial account switch.

1.1 List of MessageDefinitions

The following table lists all MessageDefinitions described in this book.

MessageDefinition	Definition
acmt.027.001.01 AccountSwitchInformationRequestV01	The AccountSwitchInformationRequest message is sent by the new account servicer to the account servicer which previously held the account to initiate the account switch process. It provides information sufficient for the old account servicer to identify the old account and validate the account parties. The new account servicer is able to inform the old bank of the maximum funding the new account will provide to settle a negative closing balance and the proposed balance transfer window.
acmt.028.001.01 AccountSwitchInformationResponseV01	The AccountSwitchInformationResponse message is sent by the account servicer that previously held the account to the new account servicer to signal whether the account owner's account can be switched and to pass details of payment arrangements to be transferred to the new account servicer if the account may be switched. Confirmation of the balance transfer window is permitted by the old account servicer.
acmt.029.001.01 AccountSwitchCancelExistingPaymentV01	The AccountSwitchCancelExistingPayment message is sent by the new account servicer to the previous account servicer to identify which payment arrangements are to be cancelled on the account owner's account and when they are to be cancelled. This message is used during a partial switch of the account and may be sent multiple times to allow for the account parties to transfer different payment arrangements at different times during the switch.
acmt.030.001.01 AccountSwitchRequestRedirectionV01	The AccountSwitchRequestRedirection message is sent by the new account servicer to a central account switch servicer to set up the redirection of payment and collection transactions that are processed after completion of the account switch. It is routed to the previous account servicer to signal that it should schedule the cancellation of all payment arrangements on the old account. This message may also be used by the new bank to amend the new account details, if the details previously provided were incorrect.
acmt.031.001.01 AccountSwitchRequestBalanceTransferV01	The AccountSwitchRequestBalanceTransfer message is sent by the new account servicer to the account servicer which previously held the account to request the transfer of the closing balance. This may be addressed to the new account or an alternate account nominated by the new account servicer.

MessageDefinition	Definition
acmt.032.001.01 AccountSwitchBalanceTransferAcknowledgementV01	The AccountSwitchBalanceTransferAcknowledgement message is sent by the previous account servicer to the new account servicer in response to the AccountSwitchRequestBalanceTransfer message. It confirms the status of the old account and the balance of the account on closure. In the case of a negative closing balance, the old account servicer provides details of the nominated account to which payment should be made from the new account servicer.
acmt.033.001.01 AccountSwitchNotifyAccountSwitchCompleteV01	The AccountSwitchNotifyAccountSwitchComplete message is sent by the new account servicer to a central account switch servicer to signal that it has completed the account switch.
acmt.034.001.01 AccountSwitchRequestPaymentV01	The AccountSwitchRequestPayment message is sent by the old account servicer to the new account servicer after the completion of the account switch to request the transfer of funds for a payment that the previous account servicer has had to make from the old account (for example: the settlement of a card transaction that was authorised offline).
acmt.035.001.01 AccountSwitchPaymentResponseV01	The AccountSwitchPaymentResponse message is sent by the new account servicer to the old account servicer to confirm whether it will make the requested payment in a request payment message. The AccountSwitchPaymentResponse message is only used to respond to a AccountSwitchRequestPayment message.
acmt.036.001.01 AccountSwitchTerminationSwitchV01	The AccountSwitchTerminationSwitch message is sent by the new account servicer to the account switch servicer to signal that the account switch must be stopped. The AccountSwitchTerminationSwitch message is only used in exception after the new account servicer has received an AccountSwitchInformationResponse message.
acmt.037.001.01 AccountSwitchTechnicalRejectionV01	The AccountSwitchTechnicalRejection message is sent by the account switch servicer to the new account servicer when it has not been able to validate a previously sent message.

2 acmt.027.001.01 AccountSwitchInformationRequestV01

2.1 MessageDefinition Functionality

The AccountSwitchInformationRequest message is sent by the new account servicer to the account servicer which previously held the account to initiate the account switch process. It provides information sufficient for the old account servicer to identify the old account and validate the account parties. The new account servicer is able to inform the old bank of the maximum funding the new account will provide to settle a negative closing balance and the proposed balance transfer window.

Outline

The AccountSwitchInformationRequestV01 MessageDefinition is composed of 6 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the details of the account switch.

C. NewAccount

   Account servicer holding the account to which the switch will be made. That is, the acquiring account servicer.

D. OldAccount

   Account held at the old account servicer being switched to the new account servicer.

E. BalanceTransfer

   Information that enables the receiving account servicer to reconcile the payment with the request.

F. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

2.2 Structure

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Message root <*Document*> <*AcctSwtchInfReq*>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		9
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			9
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		9
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		9
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		10
	SwitchDate <*SwtchDt*>	[0..1]	Date		10
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		10
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		10
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		11
	Response <*Rspn*>	[0..*]	±		12
	NewAccount <*NewAcct*>	[1..1]	±		12
	OldAccount <*OdAcct*>	[1..1]	±		15
	BalanceTransfer <*BalTrf*>	[0..*]	±		15
	SupplementaryData <*SplmtryData*>	[0..*]	±	C13	16

2.3 Constraints

C1 ActiveCurrency

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

C2 ActiveOrHistoricCurrency

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

C3 AnyBIC

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

C4 BICFI

Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

C5 ChequeMaturityDateRule

If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

C6 Country

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

C7 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C8 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C9 IBAN

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

C10 InstructionForCreditorAgentRule

If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

C11 IntermediaryAgent2Rule

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

C12 IntermediaryAgent3Rule

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

C13 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

C14 UltimateCreditorGuideline

UltimateCreditor may only be present if different from Creditor.

C15 UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

C16 ValidationByTable

Must be a valid terrestrial language.

C17 ValidationByTable

Must be a valid nationality.

2.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

2.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

2.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the details of the account switch.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		9
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		9
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		10
	SwitchDate <*SwtchDt*>	[0..1]	Date		10
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		10
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		10
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		11
	Response <*Rspn*>	[0..*]	±		12

2.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

2.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

2.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

2.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

2.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

2.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted. Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded.

CodeName	Name	Definition
		Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection. Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

2.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

2.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

2.4.3 NewAccount <NewAcct>

Presence: [1..1]

Definition: Account servicer holding the account to which the switch will be made. That is, the acquiring account servicer.

NewAccount <NewAcct> contains the following elements (see "NewAccount1" on page 186 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Account <*Acct*>	[1..1]	±		189
	AccountParty <*AcctPty*>	[1..*]			189
	CurrentName <*CurNm*>	[1..1]			191
	NamePrefix <*NmPrfx*>	[0..1]			192
{Or	NamePrefix <*NmPrfx*>	[1..1]	CodeSet		192
Or}	ExtendedNamePrefix <*XtndedNmPrfx*>	[1..1]	Text		192
	Surname <*Srnm*>	[1..1]	Text		193
	GivenName <*GvnNm*>	[0..1]	Text		193
	MiddleName <*MddlNm*>	[0..1]	Text		193
	Initials <*Initls*>	[0..1]	Text		193
	NameSuffix <*NmSfx*>	[0..1]	Text		193
	Name <*Nm*>	[0..1]	Text		193
	StartDate <*StartDt*>	[0..1]	Date		193
	EndDate <*EndDt*>	[0..1]	Date		193
	PreviousName <*PrvsNm*>	[0..*]			194
	NamePrefix <*NmPrfx*>	[0..1]			194
{Or	NamePrefix <*NmPrfx*>	[1..1]	CodeSet		194
Or}	ExtendedNamePrefix <*XtndedNmPrfx*>	[1..1]	Text		195
	Surname <*Srnm*>	[1..1]	Text		195
	GivenName <*GvnNm*>	[0..1]	Text		195
	MiddleName <*MddlNm*>	[0..1]	Text		195
	Initials <*Initls*>	[0..1]	Text		195
	NameSuffix <*NmSfx*>	[0..1]	Text		195
	Name <*Nm*>	[0..1]	Text		195
	StartDate <*StartDt*>	[0..1]	Date		195
	EndDate <*EndDt*>	[0..1]	Date		195
	Gender <*Gndr*>	[0..1]	CodeSet		196
	Language <*Lang*>	[0..1]	CodeSet	C16	196
	BirthDate <*BirthDt*>	[0..1]	Date		196
	CountryOfBirth <*CtryOfBirth*>	[0..1]	CodeSet	C18	196

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ProvinceOfBirth <*PrvcOfBirth*>	[0..1]	Text		196
	CityOfBirth <*CityOfBirth*>	[0..1]	Text		197
	TaxationCountry <*TaxtnCtry*>	[0..1]	CodeSet	C18	197
	CountryAndResidentialStatus <*CtryAndResdtlSts*>	[0..1]	±		197
	SocialSecurityNumber <*SclSctyNb*>	[0..1]	Text		197
	PostalAddress <*PstlAdr*>	[0..*]	±		197
	CitizenshipInformation <*CtznshInf*>	[0..*]			198
	Nationality <*Ntlty*>	[1..1]	CodeSet	C17	198
	MinorIndicator <*MnrInd*>	[0..1]	Indicator		198
	StartDate <*StartDt*>	[0..1]	Date		199
	EndDate <*EndDt*>	[0..1]	Date		199
	PrimaryCommunicationAddress <*PmryComAdr*>	[0..1]	±		199
	SecondaryCommunicationAddress <*ScndryComAdr*>	[0..1]	±		199
	OtherIdentification <*OthrId*>	[0..*]	±		200
	OtherDetails <*OthrDtls*>	[0..*]			200
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		201
	Code <*Cd*>	[1..1]	Text		201
	Proprietary <*Prtry*>	[0..1]	Text		201
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		201
	StartDate <*StartDt*>	[0..1]	Date		201
	Description <*Desc*>	[0..1]	Text		202
	Organisation <*Org*>	[0..1]			202
	FullLegalName <*FullLglNm*>	[1..1]	Text		202
	TradingName <*TradgNm*>	[0..1]	Text		203
	OrganisationLegalStatus <*OrgLglSts*>	[0..1]	CodeSet		203
	EstablishedDate <*EstblishdDt*>	[0..1]	Date		203
	RegistrationNumber <*RegnNb*>	[0..1]	Text		203
	RegistrationCountry <*RegnCtry*>	[0..1]	CodeSet	C18	203
	RegistrationDate <*RegnDt*>	[0..1]	Date		204
	TaxationIdentificationNumber <*TaxtnIdNb*>	[0..1]	Text		204
	TaxationCountry <*TaxtnCtry*>	[0..1]	CodeSet	C18	204

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CountryOfOperation <*CtryOfOpr*>	[0..1]	CodeSet	C18	204
	BoardResolutionIndicator <*BrdRsltnInd*>	[0..1]	Indicator		204
	BusinessAddress <*BizAdr*>	[0..1]	±		205
	OperationalAddress <*OprlAdr*>	[0..1]	±		205
	LegalAddress <*LglAdr*>	[0..1]	±		206
	RepresentativeOfficer <*RprtvOffcr*>	[0..*]	±		206
	TreasuryManager <*TrsrMgr*>	[0..1]	±		207
	MainMandateHolder <*MainMndtHldr*>	[0..*]	±		207
	Sender <*Sndr*>	[0..*]	±		208

2.4.4 OldAccount <OdAcct>

Presence: [1..1]

Definition: Account held at the old account servicer being switched to the new account servicer.

OldAccount <OdAcct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

2.4.5 BalanceTransfer <BalTrf>

Presence: [0..*]

Definition: Information that enables the receiving account servicer to reconcile the payment with the request.

BalanceTransfer <BalTrf> contains the following elements (see "BalanceTransfer1" on page 350 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	BalanceTransferReference <*BalTrfRef*>	[0..1]			350
	BalanceTransferReference <*BalTrfRef*>	[1..1]	Text		351
	BalanceTransferMethod <*BalTrfMtd*>	[0..1]	±		351
	BalanceTransferFundingLimit <*BalTrfFndgLmt*>	[0..1]			358
	CurrencyAmount <*CcyAmt*>	[1..1]	Amount	C1, C19	358

2.4.6 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C13 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

3 acmt.028.001.01 AccountSwitchInformationResponseV01

3.1 MessageDefinition Functionality

The AccountSwitchInformationResponse message is sent by the account servicer that previously held the account to the new account servicer to signal whether the account owner's account can be switched and to pass details of payment arrangements to be transferred to the new account servicer if the account may be switched. Confirmation of the balance transfer window is permitted by the old account servicer.

Outline

The AccountSwitchInformationResponseV01 MessageDefinition is composed of 7 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the details of the account switch.

C. NewAccount

   New account to which the switch will be made (destination account).

D. OldAccount

   Account held at the old account servicer being switched to the new account servicer.

E. PaymentInstruction

   Details of debit payment arrangements associated with the old account. For example the payment may be a standing order, a bill payment arrangement or a future dated payment.

F. DirectDebitInstruction

   Details of a direct debit instruction associated with the old account.

G. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

3.2 Structure

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Message root <Document> <AcctSwtchInfRspn>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		21
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			22
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		22
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		22
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		22
	SwitchDate <*SwtchDt*>	[0..1]	Date		23
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		23
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		23
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		24
	Response <*Rspn*>	[0..*]	±		25
	NewAccount <*NewAcct*>	[1..1]	±		25
	OldAccount <*OdAcct*>	[1..1]	±		25
	PaymentInstruction <*PmtInstr*>	[0..*]	±	C5, C6, C7, C8, C9, C10, C15, C17, C25, C26, C31, C11, C12, C13, C14, C29	26
	DirectDebitInstruction <*DrctDbtInstr*>	[0..*]	±		33
	SupplementaryData <*SplmtryData*>	[0..*]	±	C27	34

3.3 Constraints

C1 ActiveCurrency

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

C2 ActiveOrHistoricCurrency

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3)

contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

C3 AnyBIC

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

C4 BICFI

Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

C5 ChargeBearerRule

If ChargeBearer is present, then CreditTransferTransactionInformation/ChargeBearer is not allowed.

If CreditTransferTransactionInformation/ChargeBearer is present, then ChargeBearer is not allowed.

CreditTransferTransactionInformation/ChargeBearer and ChargeBearer may both be absent.

C6 ChargesAccountAgentRule

If ChargesAccountAgent is present, then it must contain a branch of the DebtorAgent. It must not contain a completely different agent.

C7 ChargesAccountRule

If ChargesAccountAgent is present, then ChargesAccount must be present.

C8 ChequeAndCreditorAccountRule

If PaymentMethod is CHK (Cheque), then CreditTransferTransactionInformation/ CreditorAccount is not allowed.

C9 ChequeDeliveryAndCreditorAgentRule

If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ ChequeInstruction/DeliveryMethod/Code is present and is equal to MLFA (MailToFinalAgent), CRFA (CourierToFinalAgent), RGFA (RegisteredMailToFinalAgent) or PUFA (PickUpByFinalAgent), then CreditTransferTransactionInformation/CreditorAgent must be present.

C10 ChequeDeliveryAndNoCreditorAgentRule

If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ ChequeInstruction/DeliveryMethod/Code is present and different from MLFA (MailToFinalAgent), CRFA (CourierToFinalAgent), RGFA (RegisteredMailToFinalAgent) or PUFA (PickUpByFinalAgent), then CreditTransferTransactionInformation/CreditorAgent is not allowed.

C11 ChequeFromGuideline

CreditTransferTransactionInformation/ChequeInstruction/ChequeFrom may only be present if different from CreditTransferTransactionInformation/UltimateDebtor or Debtor.

C12 ChequeInstructionDeliverToCreditorAgentGuideline

If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRFA (CourierToFinalAgent), MLFA (MailToFinalAgent), PUFA (PickUpByFinalAgent) or

RGFA (RegisteredMailToFinalAgent), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

C13 ChequeInstructionDeliverToCreditorGuideline

If PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRCD (CourierToCreditor), MLCD (MailToCreditor), PUCD (PickUpByCreditor) or RGCD (RegisteredMailToCreditor), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

C14 ChequeInstructionDeliverToDebtorGuideline

If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and if CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is CRDB (CourierToDebtor), MLDB (MailToDebtor), PUDB (PickUpByDebtor) or RGDB (RegisteredMailToDebtor), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from Debtor.

C15 ChequeInstructionRule

If PaymentMethod is different from CHK (Cheque), then CreditTransferTransactionInformation/ChequeInstruction is not allowed.

C16 ChequeMaturityDateRule

If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

C17 ChequeNoDeliveryAndNoCreditorAgentRule

If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is not present, then CreditTransferTransactionInformation/CreditorAgent is not allowed.

C18 Country

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

C19 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C20 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C21 IBAN

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

C22 InstructionForCreditorAgentRule

If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

C23 IntermediaryAgent2Rule

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

C24 IntermediaryAgent3Rule

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

C25 NonChequePaymentMethodRule

If PaymentMethod is different from CHK (Cheque) and CreditTransferTransactionInformation/Creditor is not present, then CreditTransferTransactionInformation/CreditorAccount must be present.

C26 PaymentTypeInformationRule

If PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed.

C27 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

C28 UltimateCreditorGuideline

UltimateCreditor may only be present if different from Creditor.

C29 UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

C30 UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

C31 UltimateDebtorRule

If UltimateDebtor is present, then CreditTransferTransactionInformation/UltimateDebtor is not allowed.

If CreditTransferTransactionInformation/UltimateDebtor is present, then UltimateDebtor is not allowed.

CreditTransferTransactionInformation/UltimateDebtor and UltimateDebtor may both be absent.

3.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

3.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

3.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the details of the account switch.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		22
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		22
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		22
	SwitchDate <*SwtchDt*>	[0..1]	Date		23
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		23
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		23
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		24
	Response <*Rspn*>	[0..*]	±		25

3.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

3.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

3.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

3.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

3.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

3.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted. Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.

CodeName	Name	Definition
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection. Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

3.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

3.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

3.4.3 NewAccount <NewAcct>

Presence: [1..1]

Definition: New account to which the switch will be made (destination account).

NewAccount <NewAcct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

3.4.4 OldAccount <OdAcct>

Presence: [1..1]

Definition: Account held at the old account servicer being switched to the new account servicer.

OldAccount <OdAcct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

3.4.5 PaymentInstruction <PmtInstr>

Presence: [0..*]

Definition: Details of debit payment arrangements associated with the old account. For example the payment may be a standing order, a bill payment arrangement or a future dated payment.

Impacted by: C5 "ChargeBearerRule", C6 "ChargesAccountAgentRule", C7 "ChargesAccountRule", C8 "ChequeAndCreditorAccountRule", C9 "ChequeDeliveryAndCreditorAgentRule", C10 "ChequeDeliveryAndNoCreditorAgentRule", C15 "ChequeInstructionRule", C17 "ChequeNoDeliveryAndNoCreditorAgentRule", C25 "NonChequePaymentMethodRule", C26 "PaymentTypeInformationRule", C31 "UltimateDebtorRule", C11 "ChequeFromGuideline", C12 "ChequeInstructionDeliverToCreditorAgentGuideline", C13 "ChequeInstructionDeliverToCreditorGuideline", C14 "ChequeInstructionDeliverToDebtorGuideline", C29 "UltimateDebtorGuideline"

PaymentInstruction <PmtInstr> contains the following elements (see "PaymentInstruction24" on page 213 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PaymentInformationIdentification <*PmtInfId*>	[1..1]	Text		220
	PaymentMethod <*PmtMtd*>	[1..1]	CodeSet		220
	BatchBooking <*BtchBookg*>	[0..1]	Indicator		220
	NumberOfTransactions <*NbOfTxs*>	[0..1]	Text		221
	ControlSum <*CtrlSum*>	[0..1]	Quantity		221
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		221
	RequestedExecutionDate <*ReqdExctnDt*>	[1..1]	Date		221
	PoolingAdjustmentDate <*PoolgAdjstmntDt*>	[0..1]	Date		222
	Debtor <*Dbtr*>	[1..1]	±		222
	DebtorAccount <*DbtrAcct*>	[1..1]	±		222
	DebtorAgent <*DbtrAgt*>	[1..1]	±		222
	DebtorAgentAccount <*DbtrAgtAcct*>	[0..1]	±		223
	InstructionForDebtorAgent <*InstrForDbtrAgt*>	[0..1]	Text		223
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		223
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		224
	ChargesAccount <*ChrgsAcct*>	[0..1]	±		224
	ChargesAccountAgent <*ChrgsAcctAgt*>	[0..1]	±		225
	CreditTransferTransactionInformation <*CdtTrfTxInf*>	[1..*]		C22, C23, C24, C28, C30	225
	PaymentIdentification <*PmtId*>	[1..1]	±		229
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		230
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		230
	Amount <*Amt*>	[1..1]	Amount	C1, C19	230
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		231
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C16	231
	Frequency <*Frqcy*>	[0..1]			232
	Sequence <*Seq*>	[0..1]	Text		233
	StartDate <*StartDt*>	[1..1]	Date		233
	EndPointChoice <*EndPtChc*>	[1..1]			233

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		233
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		233
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		234
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		234
	TransferInstruction <*TrfInstr*>	[0..1]			234
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		234
	Code <*Cd*>	[1..1]	Text		235
	Proprietary <*Prtry*>	[0..1]	Text		235
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		235
	StartDate <*StartDt*>	[0..1]	Date		235
	Description <*Desc*>	[0..1]	Text		235
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		235
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		236
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		236
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		236
	CreditorAgent <*CdtrAgt*>	[1..1]	±		237
	Creditor <*Cdtr*>	[0..1]	±		237
	CreditorAccount <*CdtrAcct*>	[0..1]	±		237
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		238
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		238
	Purpose <*Purp*>	[0..1]			238
{Or	Code <*Cd*>	[1..1]	CodeSet		239
Or}	Proprietary <*Prtry*>	[1..1]	Text		239
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		239
	Tax <*Tax*>	[0..1]			240
	Creditor <*Cdtr*>	[0..1]			242
	TaxIdentification <*TaxId*>	[0..1]	Text		242
	RegistrationIdentification <*RegnId*>	[0..1]	Text		242
	TaxType <*TaxTp*>	[0..1]	Text		242
	Debtor <*Dbtr*>	[0..1]			243
	TaxIdentification <*TaxId*>	[0..1]	Text		243

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	RegistrationIdentification <*RegnId*>	[0..1]	Text		243
	TaxType <*TaxTp*>	[0..1]	Text		243
	Authorisation <*Authstn*>	[0..1]			243
	Title <*Titl*>	[0..1]	Text		244
	Name <*Nm*>	[0..1]	Text		244
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		244
	ReferenceNumber <*RefNb*>	[0..1]	Text		244
	Method <*Mtd*>	[0..1]	Text		244
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	244
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	245
	Date <*Dt*>	[0..1]	Date		245
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		245
	Record <*Rcrd*>	[0..*]			245
	Type <*Tp*>	[0..1]	Text		246
	Category <*Ctgy*>	[0..1]	Text		246
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		247
	DebtorStatus <*DbtrSts*>	[0..1]	Text		247
	CertificateIdentification <*CertId*>	[0..1]	Text		247
	FormsCode <*FrmsCd*>	[0..1]	Text		247
	Period <*Prd*>	[0..1]			247
	Year <*Yr*>	[0..1]	Date		247
	Type <*Tp*>	[0..1]	CodeSet		248
	FromToDate <*FrToDt*>	[0..1]			248
	FromDate <*FrDt*>	[1..1]	Date		249
	ToDate <*ToDt*>	[1..1]	Date		249
	TaxAmount <*TaxAmt*>	[0..1]			249
	Rate <*Rate*>	[0..1]	Rate		249
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	250
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	250
	Details <*Dtls*>	[0..*]			250
	Period <*Prd*>	[0..1]			251

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		251
	Type <*Tp*>	[0..1]	CodeSet		251
	FromToDate <*FrToDt*>	[0..1]			252
	FromDate <*FrDt*>	[1..1]	Date		252
	ToDate <*ToDt*>	[1..1]	Date		253
	Amount <*Amt*>	[1..1]	Amount	C2, C20	253
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		253
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		253
	RemittanceInformation <*RmtInf*>	[0..1]			254
	Unstructured <*Ustrd*>	[0..*]	Text		254
	Structured <*Strd*>	[0..*]			254
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			255
	Type <*Tp*>	[0..1]			255
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			256
{Or	Code <*Cd*>	[1..1]	CodeSet		256
Or}	Proprietary <*Prtry*>	[1..1]	Text		257
	Issuer <*Issr*>	[0..1]	Text		257
	Number <*Nb*>	[0..1]	Text		257
	RelatedDate <*RltdDt*>	[0..1]	Date		257
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		257
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		258
	Invoicer <*Invcr*>	[0..1]	±		259
	Invoicee <*Invcee*>	[0..1]	±		259
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		260

Constraints

- **ChargeBearerRule**

  If ChargeBearer is present, then CreditTransferTransactionInformation/ChargeBearer is not allowed.

  If CreditTransferTransactionInformation/ChargeBearer is present, then ChargeBearer is not allowed.

  CreditTransferTransactionInformation/ChargeBearer and ChargeBearer may both be absent.

```
Following Must be True
    /ChargeBearer Must be absent
 Or    /CreditTransferTransactionInformation[*]/ChargeBearer Must be absent
```

- **ChargesAccountAgentRule**

  If ChargesAccountAgent is present, then it must contain a branch of the DebtorAgent. It must not contain a completely different agent.

```
On Condition
    /ChargesAccountAgent is present
Following Must be True
    /ChargesAccountAgent/FinancialInstitutionIdentification/Name Must be equal to
value 'Branch of DebtorAgent'
```

- **ChargesAccountRule**

  If ChargesAccountAgent is present, then ChargesAccount must be present.

```
On Condition
    /ChargesAccountAgent is present
Following Must be True
    /ChargesAccount Must be present
```

- **ChequeAndCreditorAccountRule**

  If PaymentMethod is CHK (Cheque), then CreditTransferTransactionInformation/CreditorAccount is not allowed.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAccount Must be absent
```

- **ChequeDeliveryAndCreditorAgentRule**

  If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is present and is equal to MLFA (MailToFinalAgent), CRFA (CourierToFinalAgent), RGFA (RegisteredMailToFinalAgent) or PUFA (PickUpByFinalAgent), then CreditTransferTransactionInformation/CreditorAgent must be present.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod
is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is within DataType <<Code>> ChequeDelivery2Code
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAgent Must be present
```

- **ChequeDeliveryAndNoCreditorAgentRule**

  If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is present and different from MLFA (MailToFinalAgent), CRFA (CourierToFinalAgent), RGFA (RegisteredMailToFinalAgent) or PUFA (PickUpByFinalAgent), then CreditTransferTransactionInformation/CreditorAgent is not allowed.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod
is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is not within DataType <<Code>> ChequeDelivery2Code
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAgent Must be absent
```

- **ChequeFromGuideline**

  CreditTransferTransactionInformation/ChequeInstruction/ChequeFrom may only be present if different from CreditTransferTransactionInformation/UltimateDebtor or Debtor.

- **ChequeInstructionDeliverToCreditorAgentGuideline**

  If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRFA (CourierToFinalAgent), MLFA (MailToFinalAgent), PUFA (PickUpByFinalAgent) or RGFA (RegisteredMailToFinalAgent), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

- **ChequeInstructionDeliverToCreditorGuideline**

  If PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRCD (CourierToCreditor), MLCD (MailToCreditor), PUCD (PickUpByCreditor) or RGCD (RegisteredMailToCreditor), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

- **ChequeInstructionDeliverToDebtorGuideline**

  If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and if CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is CRDB (CourierToDebtor), MLDB (MailToDebtor), PUDB (PickUpByDebtor) or RGDB (RegisteredMailToDebtor), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from Debtor.

- **ChequeInstructionRule**

  If PaymentMethod is different from CHK (Cheque), then CreditTransferTransactionInformation/ChequeInstruction is not allowed.

```
On Condition
    /PaymentMethod is present
 And    /PaymentMethod is different from value 'Cheque'
Following Must be True
    /CreditTransferTransactionInformation[*]/ChequeInstruction Must be absent
```

- **ChequeNoDeliveryAndNoCreditorAgentRule**

  If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is not present, then CreditTransferTransactionInformation/CreditorAgent is not allowed.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod
is absent
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAgent Must be absent
```

- **NonChequePaymentMethodRule**

  If PaymentMethod is different from CHK (Cheque) and CreditTransferTransactionInformation/Creditor is not present, then CreditTransferTransactionInformation/CreditorAccount must be present.

```
On Condition
    /PaymentMethod is different from value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/Creditor is absent
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAccount Must be present
```

- **PaymentTypeInformationRule**

  If PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed.

```
On Condition
    /PaymentTypeInformation is present
Following Must be True
    /CreditTransferTransactionInformation[*]/PaymentTypeInformation Must be absent
```

- **UltimateDebtorGuideline**

  UltimateDebtor may only be present if different from Debtor.

- **UltimateDebtorRule**

  If UltimateDebtor is present, then CreditTransferTransactionInformation/UltimateDebtor is not allowed.

  If CreditTransferTransactionInformation/UltimateDebtor is present, then UltimateDebtor is not allowed.

  CreditTransferTransactionInformation/UltimateDebtor and UltimateDebtor may both be absent.

```
Following Must be True
    /UltimateDebtor Must be absent
 Or    /CreditTransferTransactionInformation[*]/UltimateDebtor Must be absent
```

3.4.6 DirectDebitInstruction <DrctDbtInstr>

Presence: [0..*]

Definition: Details of a direct debit instruction associated with the old account.

DirectDebitInstruction <DrctDbtInstr> contains the following elements (see "DirectDebitInstructionDetails1" on page 158 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	MandateIdentification <*MndtId*>	[1..1]	Text		159
	AutomatedDirectDebitInstructionIndicator <*AutomtdDrctDbtInstrInd*>	[0..1]	Indicator		159
	DirectDebitTransferableIndicator <*DrctDbtTrfblInd*>	[0..1]	Indicator		159
	Creditor <*Cdtr*>	[1..1]	±		160
	LastCollectionCurrencyAmount <*LastColltnCcyAmt*>	[0..1]	Amount	C2, C20	160
	LastCollectionDate <*LastColltnDt*>	[0..1]	Date		160
	OtherDetails <*OthrDtls*>	[0..*]			161
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		161
	Code <*Cd*>	[1..1]	Text		161
	Proprietary <*Prtry*>	[0..1]	Text		161
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		161
	StartDate <*StartDt*>	[0..1]	Date		162
	Description <*Desc*>	[0..1]	Text		162

3.4.7 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C27 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

4 acmt.029.001.01 AccountSwitchCancelExistingPaymentV01

4.1 MessageDefinition Functionality

The AccountSwitchCancelExistingPayment message is sent by the new account servicer to the previous account servicer to identify which payment arrangements are to be cancelled on the account owner's account and when they are to be cancelled. This message is used during a partial switch of the account and may be sent multiple times to allow for the account parties to transfer different payment arrangements at different times during the switch.

Outline

The AccountSwitchCancelExistingPaymentV01 MessageDefinition is composed of 6 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the details of the account switch.

C. OldAccount

   Details of the old account.

D. PaymentInstruction

   Details of a debit payment arrangement associated with the old account. The payment may be a standing order, a bill payment arrangement or a future dated payment.

E. DirectDebitInstruction

   Details of a direct debit Instruction associated with the old account.

F. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

4.2 Structure

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Message root <Document> <AcctSwtchCclExstgPmt>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		39
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			40
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		40
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		40
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		40
	SwitchDate <*SwtchDt*>	[0..1]	Date		40
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		41
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		41
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		42
	Response <*Rspn*>	[0..*]	±		42
	OldAccount <*OdAcct*>	[1..1]	±		43
	PaymentInstruction <*PmtInstr*>	[0..*]	±	C5, C6, C7, C8, C9, C10, C15, C17, C25, C26, C31, C11, C12, C13, C14, C29	43
	DirectDebitInstruction <*DrctDbtInstr*>	[0..*]	±		50
	SupplementaryData <*SplmtryData*>	[0..*]	±	C27	51

4.3 Constraints

C1 ActiveCurrency

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

C2 ActiveOrHistoricCurrency

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

C3 AnyBIC

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

C4 BICFI

Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

C5 ChargeBearerRule

If ChargeBearer is present, then CreditTransferTransactionInformation/ChargeBearer is not allowed.

If CreditTransferTransactionInformation/ChargeBearer is present, then ChargeBearer is not allowed.

CreditTransferTransactionInformation/ChargeBearer and ChargeBearer may both be absent.

C6 ChargesAccountAgentRule

If ChargesAccountAgent is present, then it must contain a branch of the DebtorAgent. It must not contain a completely different agent.

C7 ChargesAccountRule

If ChargesAccountAgent is present, then ChargesAccount must be present.

C8 ChequeAndCreditorAccountRule

If PaymentMethod is CHK (Cheque), then CreditTransferTransactionInformation/ CreditorAccount is not allowed.

C9 ChequeDeliveryAndCreditorAgentRule

If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ ChequeInstruction/DeliveryMethod/Code is present and is equal to MLFA (MailToFinalAgent), CRFA (CourierToFinalAgent), RGFA (RegisteredMailToFinalAgent) or PUFA (PickUpByFinalAgent), then CreditTransferTransactionInformation/CreditorAgent must be present.

C10 ChequeDeliveryAndNoCreditorAgentRule

If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ ChequeInstruction/DeliveryMethod/Code is present and different from MLFA (MailToFinalAgent), CRFA (CourierToFinalAgent), RGFA (RegisteredMailToFinalAgent) or PUFA (PickUpByFinalAgent), then CreditTransferTransactionInformation/CreditorAgent is not allowed.

C11 ChequeFromGuideline

CreditTransferTransactionInformation/ChequeInstruction/ChequeFrom may only be present if different from CreditTransferTransactionInformation/UltimateDebtor or Debtor.

C12 ChequeInstructionDeliverToCreditorAgentGuideline

If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRFA (CourierToFinalAgent), MLFA (MailToFinalAgent), PUFA (PickUpByFinalAgent) or RGFA (RegisteredMailToFinalAgent), then CreditTransferTransactionInformation/ ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

C13 ChequeInstructionDeliverToCreditorGuideline

If PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRCD (CourierToCreditor), MLCD (MailToCreditor), PUCD (PickUpByCreditor) or RGCD (RegisteredMailToCreditor), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

C14 ChequeInstructionDeliverToDebtorGuideline

If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and if CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is CRDB (CourierToDebtor), MLDB (MailToDebtor), PUDB (PickUpByDebtor) or RGDB (RegisteredMailToDebtor), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from Debtor.

C15 ChequeInstructionRule

If PaymentMethod is different from CHK (Cheque), then CreditTransferTransactionInformation/ChequeInstruction is not allowed.

C16 ChequeMaturityDateRule

If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

C17 ChequeNoDeliveryAndNoCreditorAgentRule

If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is not present, then CreditTransferTransactionInformation/CreditorAgent is not allowed.

C18 Country

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

C19 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C20 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C21 IBAN

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

C22 InstructionForCreditorAgentRule

If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

C23 IntermediaryAgent2Rule

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

C24 IntermediaryAgent3Rule

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

C25 NonChequePaymentMethodRule

If PaymentMethod is different from CHK (Cheque) and CreditTransferTransactionInformation/Creditor is not present, then CreditTransferTransactionInformation/CreditorAccount must be present.

C26 PaymentTypeInformationRule

If PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed.

C27 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

C28 UltimateCreditorGuideline

UltimateCreditor may only be present if different from Creditor.

C29 UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

C30 UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

C31 UltimateDebtorRule

If UltimateDebtor is present, then CreditTransferTransactionInformation/UltimateDebtor is not allowed.

If CreditTransferTransactionInformation/UltimateDebtor is present, then UltimateDebtor is not allowed.

CreditTransferTransactionInformation/UltimateDebtor and UltimateDebtor may both be absent.

4.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

4.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

4.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the details of the account switch.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		40
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		40
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		40
	SwitchDate <*SwtchDt*>	[0..1]	Date		40
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		41
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		41
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		42
	Response <*Rspn*>	[0..*]	±		42

4.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

4.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

4.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

4.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

4.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

4.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted. Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection.

CodeName	Name	Definition
		Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

4.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

4.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

4.4.3 OldAccount <OdAcct>

Presence: [1..1]

Definition: Details of the old account.

OldAccount <OdAcct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

4.4.4 PaymentInstruction <PmtInstr>

Presence: [0..*]

Definition: Details of a debit payment arrangement associated with the old account. The payment may be a standing order, a bill payment arrangement or a future dated payment.

Impacted by: C5 "ChargeBearerRule", C6 "ChargesAccountAgentRule", C7 "ChargesAccountRule", C8 "ChequeAndCreditorAccountRule", C9 "ChequeDeliveryAndCreditorAgentRule", C10 "ChequeDeliveryAndNoCreditorAgentRule", C15 "ChequeInstructionRule", C17 "ChequeNoDeliveryAndNoCreditorAgentRule", C25 "NonChequePaymentMethodRule", C26 "PaymentTypeInformationRule", C31 "UltimateDebtorRule", C11 "ChequeFromGuideline", C12 "ChequeInstructionDeliverToCreditorAgentGuideline", C13 "ChequeInstructionDeliverToCreditorGuideline", C14 "ChequeInstructionDeliverToDebtorGuideline", C29 "UltimateDebtorGuideline"

PaymentInstruction <PmtInstr> contains the following elements (see "PaymentInstruction24" on page 213 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PaymentInformationIdentification <*PmtInfId*>	[1..1]	Text		220
	PaymentMethod <*PmtMtd*>	[1..1]	CodeSet		220
	BatchBooking <*BtchBookg*>	[0..1]	Indicator		220
	NumberOfTransactions <*NbOfTxs*>	[0..1]	Text		221
	ControlSum <*CtrlSum*>	[0..1]	Quantity		221
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		221
	RequestedExecutionDate <*ReqdExctnDt*>	[1..1]	Date		221
	PoolingAdjustmentDate <*PoolgAdjstmntDt*>	[0..1]	Date		222
	Debtor <*Dbtr*>	[1..1]	±		222
	DebtorAccount <*DbtrAcct*>	[1..1]	±		222
	DebtorAgent <*DbtrAgt*>	[1..1]	±		222
	DebtorAgentAccount <*DbtrAgtAcct*>	[0..1]	±		223
	InstructionForDebtorAgent <*InstrForDbtrAgt*>	[0..1]	Text		223
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		223
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		224
	ChargesAccount <*ChrgsAcct*>	[0..1]	±		224
	ChargesAccountAgent <*ChrgsAcctAgt*>	[0..1]	±		225
	CreditTransferTransactionInformation <*CdtTrfTxInf*>	[1..*]		C22, C23, C24, C28, C30	225
	PaymentIdentification <*PmtId*>	[1..1]	±		229
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		230
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		230
	Amount <*Amt*>	[1..1]	Amount	C1, C19	230
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		231
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C16	231
	Frequency <*Frqcy*>	[0..1]			232
	Sequence <*Seq*>	[0..1]	Text		233
	StartDate <*StartDt*>	[1..1]	Date		233
	EndPointChoice <*EndPtChc*>	[1..1]			233

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		233
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		233
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		234
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		234
	TransferInstruction <*TrfInstr*>	[0..1]			234
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		234
	Code <*Cd*>	[1..1]	Text		235
	Proprietary <*Prtry*>	[0..1]	Text		235
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		235
	StartDate <*StartDt*>	[0..1]	Date		235
	Description <*Desc*>	[0..1]	Text		235
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		235
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		236
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		236
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		236
	CreditorAgent <*CdtrAgt*>	[1..1]	±		237
	Creditor <*Cdtr*>	[0..1]	±		237
	CreditorAccount <*CdtrAcct*>	[0..1]	±		237
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		238
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		238
	Purpose <*Purp*>	[0..1]			238
{Or	Code <*Cd*>	[1..1]	CodeSet		239
Or}	Proprietary <*Prtry*>	[1..1]	Text		239
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		239
	Tax <*Tax*>	[0..1]			240
	Creditor <*Cdtr*>	[0..1]			242
	TaxIdentification <*TaxId*>	[0..1]	Text		242
	RegistrationIdentification <*RegnId*>	[0..1]	Text		242
	TaxType <*TaxTp*>	[0..1]	Text		242
	Debtor <*Dbtr*>	[0..1]			243
	TaxIdentification <*TaxId*>	[0..1]	Text		243

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	RegistrationIdentification <*RegnId*>	[0..1]	Text		243
	TaxType <*TaxTp*>	[0..1]	Text		243
	Authorisation <*Authstn*>	[0..1]			243
	Title <*Titl*>	[0..1]	Text		244
	Name <*Nm*>	[0..1]	Text		244
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		244
	ReferenceNumber <*RefNb*>	[0..1]	Text		244
	Method <*Mtd*>	[0..1]	Text		244
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	244
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	245
	Date <*Dt*>	[0..1]	Date		245
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		245
	Record <*Rcrd*>	[0..*]			245
	Type <*Tp*>	[0..1]	Text		246
	Category <*Ctgy*>	[0..1]	Text		246
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		247
	DebtorStatus <*DbtrSts*>	[0..1]	Text		247
	CertificateIdentification <*CertId*>	[0..1]	Text		247
	FormsCode <*FrmsCd*>	[0..1]	Text		247
	Period <*Prd*>	[0..1]			247
	Year <*Yr*>	[0..1]	Date		247
	Type <*Tp*>	[0..1]	CodeSet		248
	FromToDate <*FrToDt*>	[0..1]			248
	FromDate <*FrDt*>	[1..1]	Date		249
	ToDate <*ToDt*>	[1..1]	Date		249
	TaxAmount <*TaxAmt*>	[0..1]			249
	Rate <*Rate*>	[0..1]	Rate		249
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	250
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	250
	Details <*Dtls*>	[0..*]			250
	Period <*Prd*>	[0..1]			251

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		251
	Type <*Tp*>	[0..1]	CodeSet		251
	FromToDate <*FrToDt*>	[0..1]			252
	FromDate <*FrDt*>	[1..1]	Date		252
	ToDate <*ToDt*>	[1..1]	Date		253
	Amount <*Amt*>	[1..1]	Amount	C2, C20	253
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		253
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		253
	RemittanceInformation <*RmtInf*>	[0..1]			254
	Unstructured <*Ustrd*>	[0..*]	Text		254
	Structured <*Strd*>	[0..*]			254
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			255
	Type <*Tp*>	[0..1]			255
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			256
{Or	Code <*Cd*>	[1..1]	CodeSet		256
Or}	Proprietary <*Prtry*>	[1..1]	Text		257
	Issuer <*Issr*>	[0..1]	Text		257
	Number <*Nb*>	[0..1]	Text		257
	RelatedDate <*RltdDt*>	[0..1]	Date		257
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		257
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		258
	Invoicer <*Invcr*>	[0..1]	±		259
	Invoicee <*Invcee*>	[0..1]	±		259
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		260

Constraints

- **ChargeBearerRule**

  If ChargeBearer is present, then CreditTransferTransactionInformation/ChargeBearer is not allowed.

  If CreditTransferTransactionInformation/ChargeBearer is present, then ChargeBearer is not allowed.

  CreditTransferTransactionInformation/ChargeBearer and ChargeBearer may both be absent.

```
Following Must be True
    /ChargeBearer Must be absent
 Or    /CreditTransferTransactionInformation[*]/ChargeBearer Must be absent
```

- **ChargesAccountAgentRule**

  If ChargesAccountAgent is present, then it must contain a branch of the DebtorAgent. It must not contain a completely different agent.

```
On Condition
    /ChargesAccountAgent is present
Following Must be True
    /ChargesAccountAgent/FinancialInstitutionIdentification/Name Must be equal to
value 'Branch of DebtorAgent'
```

- **ChargesAccountRule**

  If ChargesAccountAgent is present, then ChargesAccount must be present.

```
On Condition
    /ChargesAccountAgent is present
Following Must be True
    /ChargesAccount Must be present
```

- **ChequeAndCreditorAccountRule**

  If PaymentMethod is CHK (Cheque), then CreditTransferTransactionInformation/CreditorAccount is not allowed.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAccount Must be absent
```

- **ChequeDeliveryAndCreditorAgentRule**

  If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is present and is equal to MLFA (MailToFinalAgent), CRFA (CourierToFinalAgent), RGFA (RegisteredMailToFinalAgent) or PUFA (PickUpByFinalAgent), then CreditTransferTransactionInformation/CreditorAgent must be present.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod
is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is within DataType <<Code>> ChequeDelivery2Code
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAgent Must be present
```

- **ChequeDeliveryAndNoCreditorAgentRule**

  If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is present and different from MLFA (MailToFinalAgent), CRFA (CourierToFinalAgent), RGFA (RegisteredMailToFinalAgent) or PUFA (PickUpByFinalAgent), then CreditTransferTransactionInformation/CreditorAgent is not allowed.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod
is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is not within DataType <<Code>> ChequeDelivery2Code
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAgent Must be absent
```

- **ChequeFromGuideline**

  CreditTransferTransactionInformation/ChequeInstruction/ChequeFrom may only be present if different from CreditTransferTransactionInformation/UltimateDebtor or Debtor.

- **ChequeInstructionDeliverToCreditorAgentGuideline**

  If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRFA (CourierToFinalAgent), MLFA (MailToFinalAgent), PUFA (PickUpByFinalAgent) or RGFA (RegisteredMailToFinalAgent), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

- **ChequeInstructionDeliverToCreditorGuideline**

  If PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRCD (CourierToCreditor), MLCD (MailToCreditor), PUCD (PickUpByCreditor) or RGCD (RegisteredMailToCreditor), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

- **ChequeInstructionDeliverToDebtorGuideline**

  If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and if CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is CRDB (CourierToDebtor), MLDB (MailToDebtor), PUDB (PickUpByDebtor) or RGDB (RegisteredMailToDebtor), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from Debtor.

- **ChequeInstructionRule**

  If PaymentMethod is different from CHK (Cheque), then CreditTransferTransactionInformation/ChequeInstruction is not allowed.

```
On Condition
    /PaymentMethod is present
 And    /PaymentMethod is different from value 'Cheque'
Following Must be True
    /CreditTransferTransactionInformation[*]/ChequeInstruction Must be absent
```

- **ChequeNoDeliveryAndNoCreditorAgentRule**

  If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is not present, then CreditTransferTransactionInformation/CreditorAgent is not allowed.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod
is absent
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAgent Must be absent
```

- **NonChequePaymentMethodRule**

  If PaymentMethod is different from CHK (Cheque) and CreditTransferTransactionInformation/Creditor is not present, then CreditTransferTransactionInformation/CreditorAccount must be present.

```
On Condition
    /PaymentMethod is different from value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/Creditor is absent
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAccount Must be present
```

- **PaymentTypeInformationRule**

  If PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed.

```
On Condition
    /PaymentTypeInformation is present
Following Must be True
    /CreditTransferTransactionInformation[*]/PaymentTypeInformation Must be absent
```

- **UltimateDebtorGuideline**

  UltimateDebtor may only be present if different from Debtor.

- **UltimateDebtorRule**

  If UltimateDebtor is present, then CreditTransferTransactionInformation/UltimateDebtor is not allowed.

  If CreditTransferTransactionInformation/UltimateDebtor is present, then UltimateDebtor is not allowed.

  CreditTransferTransactionInformation/UltimateDebtor and UltimateDebtor may both be absent.

```
Following Must be True
    /UltimateDebtor Must be absent
 Or    /CreditTransferTransactionInformation[*]/UltimateDebtor Must be absent
```

4.4.5 DirectDebitInstruction <DrctDbtInstr>

Presence: [0..*]

Definition: Details of a direct debit Instruction associated with the old account.

DirectDebitInstruction <DrctDbtInstr> contains the following elements (see "DirectDebitInstructionDetails1" on page 158 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	MandateIdentification <*MndtId*>	[1..1]	Text		159
	AutomatedDirectDebitInstructionIndicator <*AutomtdDrctDbtInstrInd*>	[0..1]	Indicator		159
	DirectDebitTransferableIndicator <*DrctDbtTrfblInd*>	[0..1]	Indicator		159
	Creditor <*Cdtr*>	[1..1]	±		160
	LastCollectionCurrencyAmount <*LastColltnCcyAmt*>	[0..1]	Amount	C2, C20	160
	LastCollectionDate <*LastColltnDt*>	[0..1]	Date		160
	OtherDetails <*OthrDtls*>	[0..*]			161
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		161
	Code <*Cd*>	[1..1]	Text		161
	Proprietary <*Prtry*>	[0..1]	Text		161
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		161
	StartDate <*StartDt*>	[0..1]	Date		162
	Description <*Desc*>	[0..1]	Text		162

4.4.6 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C27 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

5 acmt.030.001.01 AccountSwitchRequestRedirectionV01

5.1 MessageDefinition Functionality

The AccountSwitchRequestRedirection message is sent by the new account servicer to a central account switch servicer to set up the redirection of payment and collection transactions that are processed after completion of the account switch. It is routed to the previous account servicer to signal that it should schedule the cancellation of all payment arrangements on the old account. This message may also be used by the new bank to amend the new account details, if the details previously provided were incorrect.

Outline

The AccountSwitchRequestRedirectionV01 MessageDefinition is composed of 5 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the details of the account switch.

C. NewAccount

   Account servicer holding the account to which the switch will be made for example the acquiring account servicer.

D. OldAccount

   Account held at the old account servicer being switched to the new account servicer.

E. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

5.2 Structure

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Message root <Document> <AcctSwtchReqRdrctn>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		54
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			54
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		54
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		55
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		55
	SwitchDate <*SwtchDt*>	[0..1]	Date		55
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		55
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		55
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		57
	Response <*Rspn*>	[0..*]	±		57
	NewAccount <*NewAcct*>	[1..1]	±		57
	OldAccount <*OdAcct*>	[1..1]	±		58
	SupplementaryData <*SplmtryData*>	[0..*]	±	C6	58

5.3 Constraints

C1 ActiveOrHistoricCurrency

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

C2 AnyBIC

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

C3 BICFI

Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

C4 Country

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

C5 **IBAN**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

C6 **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

5.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

5.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

5.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the details of the account switch.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		54
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		55
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		55
	SwitchDate <*SwtchDt*>	[0..1]	Date		55
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		55
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		55
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		57
	Response <*Rspn*>	[0..*]	±		57

5.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

5.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

5.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

5.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

5.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

5.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted.

CodeName	Name	Definition
		Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection. Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.

CodeName	Name	Definition
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

5.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

5.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

5.4.3 NewAccount <NewAcct>

Presence: [1..1]

Definition: Account servicer holding the account to which the switch will be made for example the acquiring account servicer.

NewAccount <NewAcct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

5.4.4 OldAccount <OdAcct>

Presence: [1..1]

Definition: Account held at the old account servicer being switched to the new account servicer.

OldAccount <OdAcct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

5.4.5 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C6 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

6 acmt.031.001.01 AccountSwitchRequestBalanceTransferV01

6.1 MessageDefinition Functionality

The AccountSwitchRequestBalanceTransfer message is sent by the new account servicer to the account servicer which previously held the account to request the transfer of the closing balance. This may be addressed to the new account or an alternate account nominated by the new account servicer.

Outline

The AccountSwitchRequestBalanceTransferV01 MessageDefinition is composed of 6 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the details of the account switch.

C. NewAccount

   Details of the new account set up with the new account servicer.

   Usage: If an Alternate Credit Account is not specified and the closing balance of the old account was positive then the payment of the outstanding balance should be made to this account.

D. NominatedAccount

   Alternate beneficiary account for a payment made from the old account servicer to the new account servicer in the case of a positive closing balance of the old bank.

E. BalanceTransfer

   Information that enables the receiving bank to reconcile the payment with the request.

F. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

6.2 Structure

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Message root <Document> <AcctSwtchReqBalTrf>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		62
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			63
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		63
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		63
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		63
	SwitchDate <*SwtchDt*>	[0..1]	Date		64
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		64
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		64
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		65
	Response <*Rspn*>	[0..*]	±		66
	NewAccount <*NewAcct*>	[1..1]	±		66
	NominatedAccount <*NmntdAcct*>	[0..1]	±		66
	BalanceTransfer <*BalTrf*>	[0..*]	±		67
	SupplementaryData <*SplmtryData*>	[0..*]	±	C13	67

6.3 Constraints

C1 ActiveCurrency

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

C2 ActiveOrHistoricCurrency

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

C3 AnyBIC

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

C4 BICFI

Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

C5 **ChequeMaturityDateRule**

If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

C6 **Country**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

C7 **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C8 **CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C9 **IBAN**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

C10 **InstructionForCreditorAgentRule**

If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

C11 **IntermediaryAgent2Rule**

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

C12 **IntermediaryAgent3Rule**

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

C13 **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

C14 **UltimateCreditorGuideline**

UltimateCreditor may only be present if different from Creditor.

C15 **UltimateDebtorGuideline**

UltimateDebtor may only be present if different from Debtor.

6.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

6.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

6.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the details of the account switch.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		63
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		63
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		63
	SwitchDate <*SwtchDt*>	[0..1]	Date		64
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		64
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		64
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		65
	Response <*Rspn*>	[0..*]	±		66

6.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

6.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

6.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

6.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

6.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

6.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted. Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.

CodeName	Name	Definition
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection. Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

6.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

6.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

6.4.3 NewAccount <NewAcct>

Presence: [1..1]

Definition: Details of the new account set up with the new account servicer.

Usage: If an Alternate Credit Account is not specified and the closing balance of the old account was positive then the payment of the outstanding balance should be made to this account.

NewAccount <NewAcct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

6.4.4 NominatedAccount <NmntdAcct>

Presence: [0..1]

Definition: Alternate beneficiary account for a payment made from the old account servicer to the new account servicer in the case of a positive closing balance of the old bank.

NominatedAccount <NmntdAcct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

6.4.5 BalanceTransfer <BalTrf>

Presence: [0..*]

Definition: Information that enables the receiving bank to reconcile the payment with the request.

BalanceTransfer <BalTrf> contains the following elements (see "BalanceTransfer1" on page 350 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	BalanceTransferReference <*BalTrfRef*>	[0..1]			350
	BalanceTransferReference <*BalTrfRef*>	[1..1]	Text		351
	BalanceTransferMethod <*BalTrfMtd*>	[0..1]	±		351
	BalanceTransferFundingLimit <*BalTrfFndgLmt*>	[0..1]			358
	CurrencyAmount <*CcyAmt*>	[1..1]	Amount	C1, C19	358

6.4.6 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C13 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

7 acmt.032.001.01 AccountSwitchBalanceTransferAcknowledgementV01

7.1 MessageDefinition Functionality

The AccountSwitchBalanceTransferAcknowledgement message is sent by the previous account servicer to the new account servicer in response to the AccountSwitchRequestBalanceTransfer message. It confirms the status of the old account and the balance of the account on closure. In the case of a negative closing balance, the old account servicer provides details of the nominated account to which payment should be made from the new account servicer.

Outline

The AccountSwitchBalanceTransferAcknowledgementV01 MessageDefinition is composed of 6 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the details of the account switch.

C. OldAccount

   Account held at the old Account Servicer being switched to the new Account Servicer.

D. OldAccountBalance

   Balance of the old account.

E. BalanceTransfer

   Information that enables any payments made in connection with the fulfilment of an account switch to be reconciled by the relevant account servicer with the associated request.

   Usage: In the case of a negative closing balance of the old account, and where the old account servicer wishes any payment from the new account servicer to be addressed to an alternate account, this will be specified here.

F. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

7.2 Structure

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Message root <Document> <AcctSwtchBalTrfAck>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		71
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			72
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		72
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		72
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		72
	SwitchDate <*SwtchDt*>	[0..1]	Date		73
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		73
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		73
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		74
	Response <*Rspn*>	[0..*]	±		75
	OldAccount <*OdAcct*>	[1..1]	±		75
	OldAccountBalance <*OdAcctBal*>	[1..1]	±		75
	BalanceTransfer <*BalTrf*>	[0..*]	±		75
	SupplementaryData <*SplmtryData*>	[0..*]	±	C13	76

7.3 Constraints

C1 ActiveCurrency

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

C2 ActiveOrHistoricCurrency

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

C3 AnyBIC

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

C4 BICFI

Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

C5 ChequeMaturityDateRule

If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

C6 Country

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

C7 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C8 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C9 IBAN

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

C10 InstructionForCreditorAgentRule

If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

C11 IntermediaryAgent2Rule

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

C12 IntermediaryAgent3Rule

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

C13 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

C14 UltimateCreditorGuideline

UltimateCreditor may only be present if different from Creditor.

C15 UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

7.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

7.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

7.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the details of the account switch.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		72
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		72
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		72
	SwitchDate <*SwtchDt*>	[0..1]	Date		73
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		73
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		73
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		74
	Response <*Rspn*>	[0..*]	±		75

7.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

7.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

7.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

7.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

7.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

7.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted. Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.

CodeName	Name	Definition
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection. Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

7.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

7.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

7.4.3 OldAccount <OdAcct>

Presence: [1..1]

Definition: Account held at the old Account Servicer being switched to the new Account Servicer.

OldAccount <OdAcct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

7.4.4 OldAccountBalance <OdAcctBal>

Presence: [1..1]

Definition: Balance of the old account.

OldAccountBalance <OdAcctBal> contains the following elements (see "AmountAndDirection5" on page 152 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Amount <*Amt*>	[1..1]	Amount	C1, C19	152
	CreditDebit <*CdtDbt*>	[0..1]	CodeSet		153

7.4.5 BalanceTransfer <BalTrf>

Presence: [0..*]

Definition: Information that enables any payments made in connection with the fulfilment of an account switch to be reconciled by the relevant account servicer with the associated request.

Usage: In the case of a negative closing balance of the old account, and where the old account servicer wishes any payment from the new account servicer to be addressed to an alternate account, this will be specified here.

BalanceTransfer <BalTrf> contains the following elements (see "BalanceTransfer1" on page 350 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	BalanceTransferReference <*BalTrfRef*>	[0..1]			350
	BalanceTransferReference <*BalTrfRef*>	[1..1]	Text		351
	BalanceTransferMethod <*BalTrfMtd*>	[0..1]	±		351
	BalanceTransferFundingLimit <*BalTrfFndgLmt*>	[0..1]			358
	CurrencyAmount <*CcyAmt*>	[1..1]	Amount	C1, C19	358

7.4.6 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C13 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

8 acmt.033.001.01 AccountSwitchNotifyAccountSwitchCompleteV01

8.1 MessageDefinition Functionality

The AccountSwitchNotifyAccountSwitchComplete message is sent by the new account servicer to a central account switch servicer to signal that it has completed the account switch.

Outline

The AccountSwitchNotifyAccountSwitchCompleteV01 MessageDefinition is composed of 3 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the account switch.

   Usage: This element is used to communicate confirmation of the account switch.

C. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

8.2 Structure

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Message root <Document> <AcctSwtchNtfyAcctSwtchCmplt>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		78
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			79
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		79
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		79
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		79
	SwitchDate <*SwtchDt*>	[0..1]	Date		79
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		80
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		80
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		81
	Response <*Rspn*>	[0..*]	±		81
	SupplementaryData <*SplmtryData*>	[0..*]	±	C1	82

8.3 Constraints

C1 **SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

8.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

8.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

8.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the account switch.

Usage: This element is used to communicate confirmation of the account switch.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		79
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		79
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		79
	SwitchDate <*SwtchDt*>	[0..1]	Date		79
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		80
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		80
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		81
	Response <*Rspn*>	[0..*]	±		81

8.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

8.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

8.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

8.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

8.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

8.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted. Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection.

CodeName	Name	Definition
		Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

8.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

8.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

8.4.3 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C1 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

9 acmt.034.001.01 AccountSwitchRequestPaymentV01

9.1 MessageDefinition Functionality

The AccountSwitchRequestPayment message is sent by the old account servicer to the new account servicer after the completion of the account switch to request the transfer of funds for a payment that the previous account servicer has had to make from the old account (for example: the settlement of a card transaction that was authorised offline).

Outline

The AccountSwitchRequestPaymentV01 MessageDefinition is composed of 5 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the details of the account switch and a response code to the original payment request.

C. OldAccount

   Account held at the old account servicer being switched to the new account servicer.

D. CreditInstructions

   Specific information relating to a request for payment, including details that enable the receiving account servicer to reconcile the payment to be received with the original payment request.

E. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

9.2 Structure

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Message root <Document> <AcctSwtchReqPmt>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		89
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			89
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		89
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		89
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		90
	SwitchDate <*SwtchDt*>	[0..1]	Date		90
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		90
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		90
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		91
	Response <*Rspn*>	[0..*]	±		92
	OldAccount <*OdAcct*>	[1..1]	±		92
	CreditInstructions <*CdtInstrs*>	[1..1]		C10, C11, C12, C14, C15	92
	PaymentIdentification <*PmtId*>	[1..1]	±		96
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		97
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		97
	Amount <*Amt*>	[1..1]	Amount	C1, C7	97
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		98
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C5	98
	Frequency <*Frqcy*>	[0..1]			99
	Sequence <*Seq*>	[0..1]	Text		100
	StartDate <*StartDt*>	[1..1]	Date		100
	EndPointChoice <*EndPtChc*>	[1..1]			100
{Or	**NumberOfPayments** <*NbOfPmts*>	[0..1]	Text		100
Or}	**LastPaymentDate** <*LastPmtDt*>	[0..1]	Date		100
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		101
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		101
	TransferInstruction <*TrfInstr*>	[0..1]			101

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		101
	Code <*Cd*>	[1..1]	Text		102
	Proprietary <*Prtry*>	[0..1]	Text		102
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		102
	StartDate <*StartDt*>	[0..1]	Date		102
	Description <*Desc*>	[0..1]	Text		102
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		102
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		103
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		103
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		103
	CreditorAgent <*CdtrAgt*>	[1..1]	±		104
	Creditor <*Cdtr*>	[0..1]	±		104
	CreditorAccount <*CdtrAcct*>	[0..1]	±		104
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		105
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		105
	Purpose <*Purp*>	[0..1]			105
{Or	**Code** <*Cd*>	[1..1]	CodeSet		106
Or}	**Proprietary** <*Prtry*>	[1..1]	Text		106
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		106
	Tax <*Tax*>	[0..1]			107
	Creditor <*Cdtr*>	[0..1]			109
	TaxIdentification <*TaxId*>	[0..1]	Text		109
	RegistrationIdentification <*RegnId*>	[0..1]	Text		109
	TaxType <*TaxTp*>	[0..1]	Text		109
	Debtor <*Dbtr*>	[0..1]			110
	TaxIdentification <*TaxId*>	[0..1]	Text		110
	RegistrationIdentification <*RegnId*>	[0..1]	Text		110
	TaxType <*TaxTp*>	[0..1]	Text		110
	Authorisation <*Authstn*>	[0..1]			110
	Title <*Titl*>	[0..1]	Text		111
	Name <*Nm*>	[0..1]	Text		111

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		111
	ReferenceNumber <*RefNb*>	[0..1]	Text		111
	Method <*Mtd*>	[0..1]	Text		111
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C8	111
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C8	112
	Date <*Dt*>	[0..1]	Date		112
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		112
	Record <*Rcrd*>	[0..*]			112
	Type <*Tp*>	[0..1]	Text		113
	Category <*Ctgy*>	[0..1]	Text		113
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		114
	DebtorStatus <*DbtrSts*>	[0..1]	Text		114
	CertificateIdentification <*CertId*>	[0..1]	Text		114
	FormsCode <*FrmsCd*>	[0..1]	Text		114
	Period <*Prd*>	[0..1]			114
	Year <*Yr*>	[0..1]	Date		114
	Type <*Tp*>	[0..1]	CodeSet		115
	FromToDate <*FrToDt*>	[0..1]			115
	FromDate <*FrDt*>	[1..1]	Date		116
	ToDate <*ToDt*>	[1..1]	Date		116
	TaxAmount <*TaxAmt*>	[0..1]			116
	Rate <*Rate*>	[0..1]	Rate		116
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C8	117
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C8	117
	Details <*Dtls*>	[0..*]			117
	Period <*Prd*>	[0..1]			118
	Year <*Yr*>	[0..1]	Date		118
	Type <*Tp*>	[0..1]	CodeSet		118
	FromToDate <*FrToDt*>	[0..1]			119
	FromDate <*FrDt*>	[1..1]	Date		119
	ToDate <*ToDt*>	[1..1]	Date		120

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Amount <*Amt*>	[1..1]	Amount	C2, C8	120
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		120
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		120
	RemittanceInformation <*RmtInf*>	[0..1]			121
	Unstructured <*Ustrd*>	[0..*]	Text		121
	Structured <*Strd*>	[0..*]			122
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			122
	Type <*Tp*>	[0..1]			123
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			123
{Or	**Code** <*Cd*>	[1..1]	CodeSet		123
Or}	**Proprietary** <*Prtry*>	[1..1]	Text		124
	Issuer <*Issr*>	[0..1]	Text		124
	Number <*Nb*>	[0..1]	Text		124
	RelatedDate <*RltdDt*>	[0..1]	Date		125
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		125
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		125
	Invoicer <*Invcr*>	[0..1]	±		126
	Invoicee <*Invcee*>	[0..1]	±		126
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		127
	SupplementaryData <*SplmtryData*>	[0..*]	±	C13	127

9.3 Constraints

C1 ActiveCurrency

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

C2 ActiveOrHistoricCurrency

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

C3 AnyBIC

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

C4 BICFI

Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

C5 ChequeMaturityDateRule

If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

C6 Country

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

C7 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C8 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

C9 IBAN

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

C10 InstructionForCreditorAgentRule

If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

C11 IntermediaryAgent2Rule

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

C12 IntermediaryAgent3Rule

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

C13 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

C14 UltimateCreditorGuideline

UltimateCreditor may only be present if different from Creditor.

C15 UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

9.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

9.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

9.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the details of the account switch and a response code to the original payment request.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		89
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		89
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		90
	SwitchDate <*SwtchDt*>	[0..1]	Date		90
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		90
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		90
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		91
	Response <*Rspn*>	[0..*]	±		92

9.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

9.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

9.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

9.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

9.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

9.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted. Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested.

CodeName	Name	Definition
		Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection. Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

9.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

9.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

9.4.3 OldAccount <OdAcct>

Presence: [1..1]

Definition: Account held at the old account servicer being switched to the new account servicer.

OldAccount <OdAcct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

9.4.4 CreditInstructions <CdtInstrs>

Presence: [1..1]

Definition: Specific information relating to a request for payment, including details that enable the receiving account servicer to reconcile the payment to be received with the original payment request.

Impacted by: C10 "InstructionForCreditorAgentRule", C11 "IntermediaryAgent2Rule", C12 "IntermediaryAgent3Rule", C14 "UltimateCreditorGuideline", C15 "UltimateDebtorGuideline"

CreditInstructions <CdtInstrs> contains the following **CreditTransferTransaction27** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PaymentIdentification <*PmtId*>	[1..1]	±		96
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		97
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		97
	Amount <*Amt*>	[1..1]	Amount	C1, C7	97
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		98
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C5	98
	Frequency <*Frqcy*>	[0..1]			99
	Sequence <*Seq*>	[0..1]	Text		100
	StartDate <*StartDt*>	[1..1]	Date		100
	EndPointChoice <*EndPtChc*>	[1..1]			100
{Or	**NumberOfPayments** <*NbOfPmts*>	[0..1]	Text		100
Or}	**LastPaymentDate** <*LastPmtDt*>	[0..1]	Date		100
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		101
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		101
	TransferInstruction <*TrfInstr*>	[0..1]			101
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		101
	Code <*Cd*>	[1..1]	Text		102
	Proprietary <*Prtry*>	[0..1]	Text		102
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		102
	StartDate <*StartDt*>	[0..1]	Date		102
	Description <*Desc*>	[0..1]	Text		102
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		102
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		103
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		103
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		103
	CreditorAgent <*CdtrAgt*>	[1..1]	±		104
	Creditor <*Cdtr*>	[0..1]	±		104
	CreditorAccount <*CdtrAcct*>	[0..1]	±		104
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		105
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		105

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Purpose <*Purp*>	[0..1]			105
{Or	**Code** <*Cd*>	[1..1]	CodeSet		106
Or}	**Proprietary** <*Prtry*>	[1..1]	Text		106
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		106
	Tax <*Tax*>	[0..1]			107
	Creditor <*Cdtr*>	[0..1]			109
	TaxIdentification <*TaxId*>	[0..1]	Text		109
	RegistrationIdentification <*RegnId*>	[0..1]	Text		109
	TaxType <*TaxTp*>	[0..1]	Text		109
	Debtor <*Dbtr*>	[0..1]			110
	TaxIdentification <*TaxId*>	[0..1]	Text		110
	RegistrationIdentification <*RegnId*>	[0..1]	Text		110
	TaxType <*TaxTp*>	[0..1]	Text		110
	Authorisation <*Authstn*>	[0..1]			110
	Title <*Titl*>	[0..1]	Text		111
	Name <*Nm*>	[0..1]	Text		111
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		111
	ReferenceNumber <*RefNb*>	[0..1]	Text		111
	Method <*Mtd*>	[0..1]	Text		111
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C8	111
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C8	112
	Date <*Dt*>	[0..1]	Date		112
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		112
	Record <*Rcrd*>	[0..*]			112
	Type <*Tp*>	[0..1]	Text		113
	Category <*Ctgy*>	[0..1]	Text		113
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		114
	DebtorStatus <*DbtrSts*>	[0..1]	Text		114
	CertificateIdentification <*CertId*>	[0..1]	Text		114
	FormsCode <*FrmsCd*>	[0..1]	Text		114
	Period <*Prd*>	[0..1]			114

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		114
	Type <*Tp*>	[0..1]	CodeSet		115
	FromToDate <*FrToDt*>	[0..1]			115
	FromDate <*FrDt*>	[1..1]	Date		116
	ToDate <*ToDt*>	[1..1]	Date		116
	TaxAmount <*TaxAmt*>	[0..1]			116
	Rate <*Rate*>	[0..1]	Rate		116
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C8	117
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C8	117
	Details <*Dtls*>	[0..*]			117
	Period <*Prd*>	[0..1]			118
	Year <*Yr*>	[0..1]	Date		118
	Type <*Tp*>	[0..1]	CodeSet		118
	FromToDate <*FrToDt*>	[0..1]			119
	FromDate <*FrDt*>	[1..1]	Date		119
	ToDate <*ToDt*>	[1..1]	Date		120
	Amount <*Amt*>	[1..1]	Amount	C2, C8	120
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		120
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		120
	RemittanceInformation <*RmtInf*>	[0..1]			121
	Unstructured <*Ustrd*>	[0..*]	Text		121
	Structured <*Strd*>	[0..*]			122
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			122
	Type <*Tp*>	[0..1]			123
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			123
{Or	**Code** <*Cd*>	[1..1]	CodeSet		123
Or}	**Proprietary** <*Prtry*>	[1..1]	Text		124
	Issuer <*Issr*>	[0..1]	Text		124
	Number <*Nb*>	[0..1]	Text		124
	RelatedDate <*RltdDt*>	[0..1]	Date		125
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		125

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		125
	Invoicer <*Invcr*>	[0..1]	±		126
	Invoicee <*Invcee*>	[0..1]	±		126
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		127

Constraints

- **InstructionForCreditorAgentRule**

  If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

```
On Condition
    /CreditorAccount is present
 And    /InstructionForCreditorAgent[1] is present
Following Must be True
    /InstructionForCreditorAgent[*]/Code Must be within DataType <<Code>>
PartialInstruction3Code
```

- **IntermediaryAgent2Rule**

  If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

```
On Condition
    /IntermediaryAgent2 is present
Following Must be True
    /IntermediaryAgent1 Must be present
```

- **IntermediaryAgent3Rule**

  If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

```
On Condition
    /IntermediaryAgent3 is present
Following Must be True
    /IntermediaryAgent2 Must be present
```

- **UltimateCreditorGuideline**

  UltimateCreditor may only be present if different from Creditor.

- **UltimateDebtorGuideline**

  UltimateDebtor may only be present if different from Debtor.

9.4.4.1 PaymentIdentification <PmtId>

Presence: [1..1]

Definition: Set of elements used to reference a payment instruction.

PaymentIdentification <PmtId> contains the following elements (see "PaymentIdentification1" on page 173 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionIdentification <*InstrId*>	[0..1]	Text		173
	EndToEndIdentification <*EndToEndId*>	[1..1]	Text		173

9.4.4.2 PaymentTypeInformation <PmtTpInf>

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

PaymentTypeInformation <PmtTpInf> contains the following elements (see "PaymentTypeInformation19" on page 260 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		260
	ServiceLevel <*SvcLvl*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		261
	LocalInstrument <*LclInstrm*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		262
	CategoryPurpose <*CtgyPurp*>	[0..1]			262
{Or	Code <*Cd*>	[1..1]	CodeSet		262
Or}	Proprietary <*Prtry*>	[1..1]	Text		262

9.4.4.3 TaxRateMarker <TaxRateMrkr>

Presence: [0..1]

Definition: Specifies the rate of tax levied.

Datatype: "TaxRateMarker1Code" on page 374

CodeName	Name	Definition
ALPR	AmountQuotedLessLifeAssurance	Specifies the amount quoted less life assurance premium rate income tax.
ALIT	AmountQuotedLessStandardRate	Specifies the amount quoted less standard rate income tax.
GRSS	GrossAmount	Specifies an amount before the deduction of tax.

9.4.4.4 Amount <Amt>

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Impacted by: C1 "ActiveCurrency", C7 "CurrencyAmount"

Datatype: "ActiveCurrencyAndAmount" on page 359

Constraints

- **ActiveCurrency**

  The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

9.4.4.5 ChargeBearer <ChrgBr>

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: "ChargeBearerType1Code" on page 362

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

9.4.4.6 ChequeInstruction <ChqInstr>

Presence: [0..1]

Definition: Set of elements needed to issue a cheque.

Impacted by: C5 "ChequeMaturityDateRule"

ChequeInstruction <ChqInstr> contains the following elements (see "Cheque7" on page 153 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ChequeType <*ChqTp*>	[0..1]	CodeSet		154
	ChequeNumber <*ChqNb*>	[0..1]	Text		154
	ChequeFrom <*ChqFr*>	[0..1]			155
	Name <*Nm*>	[1..1]	Text		155
	Address <*Adr*>	[1..1]	±		155
	DeliveryMethod <*DlvryMtd*>	[0..1]			155
{Or	Code <*Cd*>	[1..1]	CodeSet		156
Or}	Proprietary <*Prtry*>	[1..1]	Text		156
	DeliverTo <*DlvrTo*>	[0..1]			156
	Name <*Nm*>	[1..1]	Text		157
	Address <*Adr*>	[1..1]	±		157
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		157
	ChequeMaturityDate <*ChqMtrtyDt*>	[0..1]	Date		158
	FormsCode <*FrmsCd*>	[0..1]	Text		158
	MemoField <*MemoFld*>	[0..2]	Text		158
	RegionalClearingZone <*RgnlClrZone*>	[0..1]	Text		158
	PrintLocation <*PrtLctn*>	[0..1]	Text		158
	Signature <*Sgntr*>	[0..5]	Text		158

Constraints

- **ChequeMaturityDateRule**

  If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

```
On Condition
    /ChequeType is present
 And    /ChequeType is within DataType <<Code>> ChequeType3Code
Following Must be True
    /ChequeMaturityDate Must be absent
```

9.4.4.7 Frequency <Frqcy>

Presence: [0..1]

Definition: The schedule for a credit payment arrangement.

Frequency <Frqcy> contains the following **Frequency1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Sequence <*Seq*>	[0..1]	Text		100
	StartDate <*StartDt*>	[1..1]	Date		100
	EndPointChoice <*EndPtChc*>	[1..1]			100
{Or	**NumberOfPayments** <*NbOfPmts*>	[0..1]	Text		100
Or}	**LastPaymentDate** <*LastPmtDt*>	[0..1]	Date		100
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		101
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		101

9.4.4.7.1 Sequence <Seq>

Presence: [0..1]

Definition: Technical identifier of a Credit Transfer as part of a series of Credit Transfers within a single Payment Instruction. Assists the transfer of complex variable future payment schedules, associated with a single act of customer consent, within a single Payment Instruction.

Datatype: "Max3NumericText" on page 381

9.4.4.7.2 StartDate <StartDt>

Presence: [1..1]

Definition: The date of the first payment to be made for this payment schedule.

Datatype: "ISODate" on page 376

9.4.4.7.3 EndPointChoice <EndPtChc>

Presence: [1..1]

Definition: Information about when the payment arrangement will end.

EndPointChoice <EndPtChc> contains one of the following **EndPoint1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	**NumberOfPayments** <*NbOfPmts*>	[0..1]	Text		100
Or}	**LastPaymentDate** <*LastPmtDt*>	[0..1]	Date		100

9.4.4.7.3.1 NumberOfPayments <NbOfPmts>

Presence: [0..1]

Definition: Number of the payments that will be made in completing this frequency sequence including any executed since the sequence start date.

Datatype: "Max35Text" on page 381

9.4.4.7.3.2 LastPaymentDate <LastPmtDt>

Presence: [0..1]

Definition: Final payment of the standing order due.

Datatype: "ISODate" on page 376

9.4.4.7.4 RequestedFrequencyPattern <ReqdFrqcyPttrn>

Presence: [0..1]

Definition: Payment schedule frequency pattern which indicates how frequently a payment is made.

RequestedFrequencyPattern <ReqdFrqcyPttrn> contains one of the following elements (see "Frequency37Choice" on page 175 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		175
Or}	Proprietary <*Prtry*>	[1..1]	Text		176

9.4.4.7.5 NonWorkingDayAdjustment <NonWorkgDayAdjstmnt>

Presence: [0..1]

Definition: Adjustment indicator for a non-working day to enable payment to be made on the next working day.

Datatype: "BusinessDayConvention1Code" on page 361

CodeName	Name	Definition
FWNG	Following	The date will be the first following day that is a business day.
PREC	Preceding	The date will be the first preceding day that is a business day.

9.4.4.8 TransferInstruction <TrfInstr>

Presence: [0..1]

Definition: Provides further information about the status of transferred scheduled payment(s).

TransferInstruction <TrfInstr> contains the following **TransferInstruction1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		101
	Code <*Cd*>	[1..1]	Text		102
	Proprietary <*Prtry*>	[0..1]	Text		102
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		102
	StartDate <*StartDt*>	[0..1]	Date		102
	Description <*Desc*>	[0..1]	Text		102

9.4.4.8.1 TransferIndicator <TrfInd>

Presence: [0..1]

Definition: Indicates whether a payment arrangement is transferable.

Usage: Default value for TransferIndicator is false.

Datatype: One of the following values must be used (see "YesNoIndicator" on page 378):

- *Meaning When True:* Yes
- *Meaning When False:* No

9.4.4.8.2 Code <Cd>

Presence: [1..1]

Definition: Specifies an additional parameter to be applied to the requested transaction schedule.

Datatype: "Max35Text" on page 381

9.4.4.8.3 Proprietary <Prtry>

Presence: [0..1]

Definition: Specifies an additional parameter to be applied to the transaction schedule in a proprietary format.

Datatype: "Max256Text" on page 380

9.4.4.8.4 StartDateTime <StartDtTm>

Presence: [0..1]

Definition: The date and time at which the event specified by Code commences.

Datatype: "ISODateTime" on page 376

9.4.4.8.5 StartDate <StartDt>

Presence: [0..1]

Definition: The date on which the event specified by Code commences.

Datatype: "ISODate" on page 376

9.4.4.8.6 Description <Desc>

Presence: [0..1]

Definition: Additional switch parameters in a free text format.

Datatype: "Max350Text" on page 380

9.4.4.9 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

UltimateDebtor <UltmtDbtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

9.4.4.10 IntermediaryAgent1 <IntrmyAgt1>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

IntermediaryAgent1 <IntrmyAgt1> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

9.4.4.11 IntermediaryAgent2 <IntrmyAgt2>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

IntermediaryAgent2 <IntrmyAgt2> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

9.4.4.12 IntermediaryAgent3 <IntrmyAgt3>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

IntermediaryAgent3 <IntrmyAgt3> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

9.4.4.13 CreditorAgent <CdtrAgt>

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

CreditorAgent <CdtrAgt> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

9.4.4.14 Creditor <Cdtr>

Presence: [0..1]

Definition: Party to which an amount of money is due.

Creditor <Cdtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

9.4.4.15 CreditorAccount <CdtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

CreditorAccount <CdtrAcct> contains the following elements (see "CashAccount24" on page 146 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		146
	Type <*Tp*>	[0..1]	±		146
	Currency <*Ccy*>	[0..1]	CodeSet	C2	147
	Name <*Nm*>	[0..1]	Text		147

9.4.4.16 UltimateCreditor <UltmtCdtr>

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

UltimateCreditor <UltmtCdtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

9.4.4.17 InstructionForCreditorAgent <InstrForCdtrAgt>

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

InstructionForCreditorAgent <InstrForCdtrAgt> contains the following elements (see "InstructionForCreditorAgent1" on page 212 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Code <*Cd*>	[0..1]	CodeSet		212
	InstructionInformation <*InstrInf*>	[0..1]	Text		213

9.4.4.18 Purpose <Purp>

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

Purpose <Purp> contains one of the following **Purpose2Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	**Code** <*Cd*>	[1..1]	CodeSet		106
Or}	**Proprietary** <*Prtry*>	[1..1]	Text		106

9.4.4.18.1 Code <Cd>

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: "ExternalPurpose1Code" on page 368

9.4.4.18.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: "Max35Text" on page 381

9.4.4.19 RegulatoryReporting <RgltryRptg>

Presence: [0..10]

Definition: Information needed due to regulatory and statutory requirements.

RegulatoryReporting <RgltryRptg> contains the following elements (see "RegulatoryReporting3" on page 269 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DebitCreditReportingIndicator <*DbtCdtRptgInd*>	[0..1]	CodeSet		269
	Authority <*Authrty*>	[0..1]			270
	Name <*Nm*>	[0..1]	Text		270
	Country <*Ctry*>	[0..1]	CodeSet	C18	270
	Details <*Dtls*>	[0..*]			270
	Type <*Tp*>	[0..1]	Text		271
	Date <*Dt*>	[0..1]	Date		271
	Country <*Ctry*>	[0..1]	CodeSet	C18	271
	Code <*Cd*>	[0..1]	Text		271
	Amount <*Amt*>	[0..1]	Amount	C2, C20	271
	Information <*Inf*>	[0..*]	Text		272

9.4.4.20 Tax <Tax>

Presence: [0..1]

Definition: Provides details on the tax.

Tax <Tax> contains the following **TaxInformation6** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Creditor <*Cdtr*>	[0..1]			109
	TaxIdentification <*TaxId*>	[0..1]	Text		109
	RegistrationIdentification <*RegnId*>	[0..1]	Text		109
	TaxType <*TaxTp*>	[0..1]	Text		109
	Debtor <*Dbtr*>	[0..1]			110
	TaxIdentification <*TaxId*>	[0..1]	Text		110
	RegistrationIdentification <*RegnId*>	[0..1]	Text		110
	TaxType <*TaxTp*>	[0..1]	Text		110
	Authorisation <*Authstn*>	[0..1]			110
	Title <*Titl*>	[0..1]	Text		111
	Name <*Nm*>	[0..1]	Text		111
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		111
	ReferenceNumber <*RefNb*>	[0..1]	Text		111
	Method <*Mtd*>	[0..1]	Text		111
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C8	111
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C8	112
	Date <*Dt*>	[0..1]	Date		112
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		112
	Record <*Rcrd*>	[0..*]			112
	Type <*Tp*>	[0..1]	Text		113
	Category <*Ctgy*>	[0..1]	Text		113
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		114
	DebtorStatus <*DbtrSts*>	[0..1]	Text		114
	CertificateIdentification <*CertId*>	[0..1]	Text		114
	FormsCode <*FrmsCd*>	[0..1]	Text		114
	Period <*Prd*>	[0..1]			114
	Year <*Yr*>	[0..1]	Date		114
	Type <*Tp*>	[0..1]	CodeSet		115
	FromToDate <*FrToDt*>	[0..1]			115
	FromDate <*FrDt*>	[1..1]	Date		116
	ToDate <*ToDt*>	[1..1]	Date		116

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxAmount <*TaxAmt*>	[0..1]			116
	Rate <*Rate*>	[0..1]	Rate		116
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C8	117
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C8	117
	Details <*Dtls*>	[0..*]			117
	Period <*Prd*>	[0..1]			118
	Year <*Yr*>	[0..1]	Date		118
	Type <*Tp*>	[0..1]	CodeSet		118
	FromToDate <*FrToDt*>	[0..1]			119
	FromDate <*FrDt*>	[1..1]	Date		119
	ToDate <*ToDt*>	[1..1]	Date		120
	Amount <*Amt*>	[1..1]	Amount	C2, C8	120
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		120

9.4.4.20.1 Creditor <Cdtr>

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

Creditor <Cdtr> contains the following **TaxParty1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxIdentification <*TaxId*>	[0..1]	Text		109
	RegistrationIdentification <*RegnId*>	[0..1]	Text		109
	TaxType <*TaxTp*>	[0..1]	Text		109

9.4.4.20.1.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: "Max35Text" on page 381

9.4.4.20.1.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 381

9.4.4.20.1.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 381

9.4.4.20.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Set of elements used to identify the party on the debit side of the transaction to which the tax applies.

Debtor <Dbtr> contains the following **TaxParty2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxIdentification <*TaxId*>	[0..1]	Text		110
	RegistrationIdentification <*RegnId*>	[0..1]	Text		110
	TaxType <*TaxTp*>	[0..1]	Text		110
	Authorisation <*Authstn*>	[0..1]			110
	Title <*Titl*>	[0..1]	Text		111
	Name <*Nm*>	[0..1]	Text		111

9.4.4.20.2.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: "Max35Text" on page 381

9.4.4.20.2.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 381

9.4.4.20.2.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 381

9.4.4.20.2.4 Authorisation <Authstn>

Presence: [0..1]

Definition: Details of the authorised tax paying party.

Authorisation <Authstn> contains the following **TaxAuthorisation1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Title <*Titl*>	[0..1]	Text		111
	Name <*Nm*>	[0..1]	Text		111

9.4.4.20.2.4.1 Title <Titl>

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: "Max35Text" on page 381

9.4.4.20.2.4.2 Name <Nm>

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: "Max140Text" on page 379

9.4.4.20.3 AdministrationZone <AdmstnZn>

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "Max35Text" on page 381

9.4.4.20.4 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "Max140Text" on page 379

9.4.4.20.5 Method <Mtd>

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: "Max35Text" on page 381

9.4.4.20.6 TotalTaxableBaseAmount <TtlTaxblBaseAmt>

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Impacted by: C2 "ActiveOrHistoricCurrency", C8 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

9.4.4.20.7 TotalTaxAmount <TtlTaxAmt>

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Impacted by: C2 "ActiveOrHistoricCurrency", C8 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

9.4.4.20.8 Date <Dt>

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: "ISODate" on page 376

9.4.4.20.9 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: "Number" on page 378

9.4.4.20.10 Record <Rcrd>

Presence: [0..*]

Definition: Record of tax details.

Record <Rcrd> contains the following **TaxRecord2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]	Text		113
	Category <*Ctgy*>	[0..1]	Text		113
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		114
	DebtorStatus <*DbtrSts*>	[0..1]	Text		114
	CertificateIdentification <*CertId*>	[0..1]	Text		114
	FormsCode <*FrmsCd*>	[0..1]	Text		114
	Period <*Prd*>	[0..1]			114
	Year <*Yr*>	[0..1]	Date		114
	Type <*Tp*>	[0..1]	CodeSet		115
	FromToDate <*FrToDt*>	[0..1]			115
	FromDate <*FrDt*>	[1..1]	Date		116
	ToDate <*ToDt*>	[1..1]	Date		116
	TaxAmount <*TaxAmt*>	[0..1]			116
	Rate <*Rate*>	[0..1]	Rate		116
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C8	117
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C8	117
	Details <*Dtls*>	[0..*]			117
	Period <*Prd*>	[0..1]			118
	Year <*Yr*>	[0..1]	Date		118
	Type <*Tp*>	[0..1]	CodeSet		118
	FromToDate <*FrToDt*>	[0..1]			119
	FromDate <*FrDt*>	[1..1]	Date		119
	ToDate <*ToDt*>	[1..1]	Date		120
	Amount <*Amt*>	[1..1]	Amount	C2, C8	120
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		120

9.4.4.20.10.1 Type <Tp>

Presence: [0..1]

Definition: High level code to identify the type of tax details.

Datatype: "Max35Text" on page 381

9.4.4.20.10.2 Category <Ctgy>

Presence: [0..1]

Definition: Specifies the tax code as published by the tax authority.

Datatype: "Max35Text" on page 381

9.4.4.20.10.3 CategoryDetails <CtgyDtls>

Presence: [0..1]

Definition: Provides further details of the category tax code.

Datatype: "Max35Text" on page 381

9.4.4.20.10.4 DebtorStatus <DbtrSts>

Presence: [0..1]

Definition: Code provided by local authority to identify the status of the party that has drawn up the settlement document.

Datatype: "Max35Text" on page 381

9.4.4.20.10.5 CertificateIdentification <CertId>

Presence: [0..1]

Definition: Identification number of the tax report as assigned by the taxing authority.

Datatype: "Max35Text" on page 381

9.4.4.20.10.6 FormsCode <FrmsCd>

Presence: [0..1]

Definition: Identifies, in a coded form, on which template the tax report is to be provided.

Datatype: "Max35Text" on page 381

9.4.4.20.10.7 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following **TaxPeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		114
	Type <*Tp*>	[0..1]	CodeSet		115
	FromToDate <*FrToDt*>	[0..1]			115
	FromDate <*FrDt*>	[1..1]	Date		116
	ToDate <*ToDt*>	[1..1]	Date		116

9.4.4.20.10.7.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 376

9.4.4.20.10.7.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 375

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

9.4.4.20.10.7.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following **DatePeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FromDate <*FrDt*>	[1..1]	Date		116
	ToDate <*ToDt*>	[1..1]	Date		116

9.4.4.20.10.7.3.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: "ISODate" on page 376

9.4.4.20.10.7.3.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: "ISODate" on page 376

9.4.4.20.10.8 TaxAmount <TaxAmt>

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

TaxAmount <TaxAmt> contains the following **TaxAmount2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Rate <*Rate*>	[0..1]	Rate		116
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C8	117
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C8	117
	Details <*Dtls*>	[0..*]			117
	Period <*Prd*>	[0..1]			118
	Year <*Yr*>	[0..1]	Date		118
	Type <*Tp*>	[0..1]	CodeSet		118
	FromToDate <*FrToDt*>	[0..1]			119
	FromDate <*FrDt*>	[1..1]	Date		119
	ToDate <*ToDt*>	[1..1]	Date		120
	Amount <*Amt*>	[1..1]	Amount	C2, C8	120

9.4.4.20.10.8.1 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: "PercentageRate" on page 378

9.4.4.20.10.8.2 TaxableBaseAmount <TaxblBaseAmt>

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Impacted by: C2 "ActiveOrHistoricCurrency", C8 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

9.4.4.20.10.8.3 TotalAmount <TtlAmt>

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Impacted by: C2 "ActiveOrHistoricCurrency", C8 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

9.4.4.20.10.8.4 Details <Dtls>

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

Details <Dtls> contains the following **TaxRecordDetails2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Period <*Prd*>	[0..1]			118
	Year <*Yr*>	[0..1]	Date		118
	Type <*Tp*>	[0..1]	CodeSet		118
	FromToDate <*FrToDt*>	[0..1]			119
	FromDate <*FrDt*>	[1..1]	Date		119
	ToDate <*ToDt*>	[1..1]	Date		120
	Amount <*Amt*>	[1..1]	Amount	C2, C8	120

9.4.4.20.10.8.4.1 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following **TaxPeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		118
	Type <*Tp*>	[0..1]	CodeSet		118
	FromToDate <*FrToDt*>	[0..1]			119
	FromDate <*FrDt*>	[1..1]	Date		119
	ToDate <*ToDt*>	[1..1]	Date		120

9.4.4.20.10.8.4.1.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 376

9.4.4.20.10.8.4.1.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 375

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.

CodeName	Name	Definition
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

9.4.4.20.10.8.4.1.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following **DatePeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FromDate <*FrDt*>	[1..1]	Date		119
	ToDate <*ToDt*>	[1..1]	Date		120

9.4.4.20.10.8.4.1.3.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: "ISODate" on page 376

9.4.4.20.10.8.4.1.3.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: "ISODate" on page 376

9.4.4.20.10.8.4.2 Amount <Amt>

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Impacted by: C2 "ActiveOrHistoricCurrency", C8 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

9.4.4.20.10.9 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: "Max140Text" on page 379

9.4.4.21 RelatedRemittanceInformation <RltdRmtInf>

Presence: [0..10]

Definition: Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain.

RelatedRemittanceInformation <RltdRmtInf> contains the following elements (see "RemittanceLocation2" on page 173 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	RemittanceIdentification <*RmtId*>	[0..1]	Text		174
	RemittanceLocationMethod <*RmtLctnMtd*>	[0..1]	CodeSet		174
	RemittanceLocationElectronicAddress <*RmtLctnElctrncAdr*>	[0..1]	Text		174
	RemittanceLocationPostalAddress <*RmtLctnPstlAdr*>	[0..1]			174
	Name <*Nm*>	[1..1]	Text		175
	Address <*Adr*>	[1..1]	±		175

9.4.4.22 RemittanceInformation <RmtInf>

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

RemittanceInformation <RmtInf> contains the following **RemittanceInformation14** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Unstructured <*Ustrd*>	[0..*]	Text		121
	Structured <*Strd*>	[0..*]			122
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			122
	Type <*Tp*>	[0..1]			123
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			123
{Or	**Code** <*Cd*>	[1..1]	CodeSet		123
Or}	**Proprietary** <*Prtry*>	[1..1]	Text		124
	Issuer <*Issr*>	[0..1]	Text		124
	Number <*Nb*>	[0..1]	Text		124
	RelatedDate <*RltdDt*>	[0..1]	Date		125
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		125
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		125
	Invoicer <*Invcr*>	[0..1]	±		126
	Invoicee <*Invcee*>	[0..1]	±		126
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		127

9.4.4.22.1 Unstructured <Ustrd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: "Max140Text" on page 379

9.4.4.22.2 Structured <Strd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

Structured <Strd> contains the following **StructuredRemittanceInformation14** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			122
	Type <*Tp*>	[0..1]			123
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			123
{Or	**Code** <*Cd*>	[1..1]	CodeSet		123
Or}	**Proprietary** <*Prtry*>	[1..1]	Text		124
	Issuer <*Issr*>	[0..1]	Text		124
	Number <*Nb*>	[0..1]	Text		124
	RelatedDate <*RltdDt*>	[0..1]	Date		125
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		125
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		125
	Invoicer <*Invcr*>	[0..1]	±		126
	Invoicee <*Invcee*>	[0..1]	±		126
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		127

9.4.4.22.2.1 ReferredDocumentInformation <RfrdDocInf>

Presence: [0..*]

Definition: Set of elements used to identify the documents referred to in the remittance information.

ReferredDocumentInformation <RfrdDocInf> contains the following **ReferredDocumentInformation3** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			123
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			123
{Or	**Code** <*Cd*>	[1..1]	CodeSet		123
Or}	**Proprietary** <*Prtry*>	[1..1]	Text		124
	Issuer <*Issr*>	[0..1]	Text		124
	Number <*Nb*>	[0..1]	Text		124
	RelatedDate <*RltdDt*>	[0..1]	Date		125

9.4.4.22.2.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of referred document.

Type <Tp> contains the following **ReferredDocumentType2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			123
{Or	**Code** <*Cd*>	[1..1]	CodeSet		123
Or}	**Proprietary** <*Prtry*>	[1..1]	Text		124
	Issuer <*Issr*>	[0..1]	Text		124

9.4.4.22.2.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the referred document.

CodeOrProprietary <CdOrPrtry> contains one of the following **ReferredDocumentType1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	**Code** <*Cd*>	[1..1]	CodeSet		123
Or}	**Proprietary** <*Prtry*>	[1..1]	Text		124

9.4.4.22.2.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: "DocumentType5Code" on page 364

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.

9.4.4.22.2.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: "Max35Text" on page 381

9.4.4.22.2.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "Max35Text" on page 381

9.4.4.22.2.1.2 Number <Nb>

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: "Max35Text" on page 381

9.4.4.22.2.1.3 RelatedDate <RltdDt>

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: "ISODate" on page 376

9.4.4.22.2.2 ReferredDocumentAmount <RfrdDocAmt>

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

ReferredDocumentAmount <RfrdDocAmt> contains the following elements (see "RemittanceAmount2" on page 177 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DuePayableAmount <*DuePyblAmt*>	[0..1]	Amount	C2, C20	178
	DiscountAppliedAmount <*DscntApldAmt*>	[0..*]			179
	Type <*Tp*>	[0..1]			179
{Or	Code <*Cd*>	[1..1]	CodeSet		179
Or}	Proprietary <*Prtry*>	[1..1]	Text		179
	Amount <*Amt*>	[1..1]	Amount	C2, C20	179
	CreditNoteAmount <*CdtNoteAmt*>	[0..1]	Amount	C2, C20	180
	TaxAmount <*TaxAmt*>	[0..*]			180
	Type <*Tp*>	[0..1]			180
{Or	Code <*Cd*>	[1..1]	CodeSet		181
Or}	Proprietary <*Prtry*>	[1..1]	Text		181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	181
	AdjustmentAmountAndReason <*AdjstmntAmtAndRsn*>	[0..*]			181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	182
	CreditDebitIndicator <*CdtDbtInd*>	[0..1]	CodeSet		182
	Reason <*Rsn*>	[0..1]	Text		182
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		182
	RemittedAmount <*RmtdAmt*>	[0..1]	Amount	C2, C20	183

9.4.4.22.2.3 CreditorReferenceInformation <CdtrRefInf>

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

CreditorReferenceInformation <CdtrRefInf> contains the following elements (see "CreditorReferenceInformation2" on page 162 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			162
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			162
{Or	Code <*Cd*>	[1..1]	CodeSet		163
Or}	Proprietary <*Prtry*>	[1..1]	Text		163
	Issuer <*Issr*>	[0..1]	Text		163
	Reference <*Ref*>	[0..1]	Text		163

9.4.4.22.2.4 Invoicer <Invcr>

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

Invoicer <Invcr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

9.4.4.22.2.5 Invoicee <Invcee>

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

Invoicee <Invcee> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

9.4.4.22.2.6 AdditionalRemittanceInformation <AddtlRmtInf>

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: "Max140Text" on page 379

9.4.5 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C13 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

10 acmt.035.001.01 AccountSwitchPaymentResponseV01

10.1 MessageDefinition Functionality

The AccountSwitchPaymentResponse message is sent by the new account servicer to the old account servicer to confirm whether it will make the requested payment in a request payment message. The AccountSwitchPaymentResponse message is only used to respond to a AccountSwitchRequestPayment message.

Outline

The AccountSwitchPaymentResponseV01 MessageDefinition is composed of 3 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the details of the account switch.

C. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

10.2 Structure

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Message root <*Document*> <*AcctSwtchPmtRspn*>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		129
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			129
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		129
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		130
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		130
	SwitchDate <*SwtchDt*>	[0..1]	Date		130
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		130
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		130
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		132
	Response <*Rspn*>	[0..*]	±		132
	SupplementaryData <*SplmtryData*>	[0..*]	±	C1	132

10.3 Constraints

C1 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

10.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

10.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

10.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the details of the account switch.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		129
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		130
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		130
	SwitchDate <*SwtchDt*>	[0..1]	Date		130
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		130
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		130
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		132
	Response <*Rspn*>	[0..*]	±		132

10.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

10.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

10.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

10.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

10.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

10.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted. Usage: Accepted status should be used when account switch service receives

CodeName	Name	Definition
		and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection. Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.

CodeName	Name	Definition
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

10.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

10.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

10.4.3 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C1 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

11 acmt.036.001.01 AccountSwitchTerminationSwitchV01

11.1 MessageDefinition Functionality

The AccountSwitchTerminationSwitch message is sent by the new account servicer to the account switch servicer to signal that the account switch must be stopped. The AccountSwitchTerminationSwitch message is only used in exception after the new account servicer has received an AccountSwitchInformationResponse message.

Outline

The AccountSwitchTerminationSwitchV01 MessageDefinition is composed of 3 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the details of the account switch, including reasons for the termination of the account switch.

C. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

11.2 Structure

Or	MessageElement/BuildingBlock*<XML Tag>*	Mult.	Type	Constr. No.	Page
	Message root <Document> <AcctSwtchTermntnSwtch>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		135
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			135
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		135
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		136
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		136
	SwitchDate <*SwtchDt*>	[0..1]	Date		136
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		136
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		136
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		138
	Response <*Rspn*>	[0..*]	±		138
	SupplementaryData <*SplmtryData*>	[0..*]	±	C1	138

11.3 Constraints

C1 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

11.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

11.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

11.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the details of the account switch, including reasons for the termination of the account switch.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		135
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		136
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		136
	SwitchDate <*SwtchDt*>	[0..1]	Date		136
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		136
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		136
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		138
	Response <*Rspn*>	[0..*]	±		138

11.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

11.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

11.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

11.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

11.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

11.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted.

CodeName	Name	Definition
		Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection. Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.

CodeName	Name	Definition
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

11.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

11.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

11.4.3 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C1 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

12 acmt.037.001.01 AccountSwitchTechnicalRejectionV01

12.1 MessageDefinition Functionality

The AccountSwitchTechnicalRejection message is sent by the account switch servicer to the new account servicer when it has not been able to validate a previously sent message.

Outline

The AccountSwitchTechnicalRejectionV01 MessageDefinition is composed of 3 MessageBuildingBlocks:

A. MessageIdentification

   Unique identification for the message.

B. AccountSwitchDetails

   Contains information about the details of the account switch, including reasons for the technical rejection of the account switch.

C. SupplementaryData

   Additional information that cannot be captured in the structured elements and/or any other specific block.

12.2 Structure

Or	MessageElement/BuildingBlock<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Message root <*Document*> <*AcctSwtchTechRjctn*>	[1..1]			
	MessageIdentification <*MsgId*>	[1..1]	±		141
	AccountSwitchDetails <*AcctSwtchDtls*>	[1..1]			141
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		141
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		142
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		142
	SwitchDate <*SwtchDt*>	[0..1]	Date		142
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		142
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		142
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		144
	Response <*Rspn*>	[0..*]	±		144
	SupplementaryData <*SplmtryData*>	[0..*]	±	C1	144

12.3 Constraints

C1 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

12.4 Message Building Blocks

This chapter describes the MessageBuildingBlocks of this MessageDefinition.

12.4.1 MessageIdentification <MsgId>

Presence: [1..1]

Definition: Unique identification for the message.

MessageIdentification <MsgId> contains the following elements (see "MessageIdentification1" on page 169 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

12.4.2 AccountSwitchDetails <AcctSwtchDtls>

Presence: [1..1]

Definition: Contains information about the details of the account switch, including reasons for the technical rejection of the account switch.

AccountSwitchDetails <AcctSwtchDtls> contains the following **AccountSwitchDetails1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	UniqueReferenceNumber <*UnqRefNb*>	[1..1]	Text		141
	RoutingUniqueReferenceNumber <*RtgUnqRefNb*>	[1..1]	Text		142
	SwitchReceivedDateTime <*SwtchRcvdDtTm*>	[0..1]	DateTime		142
	SwitchDate <*SwtchDt*>	[0..1]	Date		142
	SwitchType <*SwtchTp*>	[1..1]	CodeSet		142
	SwitchStatus <*SwtchSts*>	[0..1]	CodeSet		142
	BalanceTransferWindow <*BalTrfWndw*>	[0..1]	CodeSet		144
	Response <*Rspn*>	[0..*]	±		144

12.4.2.1 UniqueReferenceNumber <UnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Datatype: "Max35Text" on page 381

12.4.2.2 RoutingUniqueReferenceNumber <RtgUnqRefNb>

Presence: [1..1]

Definition: Unique number that provides unique and unambiguous identification of the account switch.

Usage: Where one or more account switches have taken place since the original account switch this field contains the unique number that relates to the switch that transferred the account to the latest new account servicer.

Datatype: "Max35Text" on page 381

12.4.2.3 SwitchReceivedDateTime <SwtchRcvdDtTm>

Presence: [0..1]

Definition: Date and time that the request was received by the central switch service, populated by the central switch service only.

Datatype: "ISODateTime" on page 376

12.4.2.4 SwitchDate <SwtchDt>

Presence: [0..1]

Definition: Date on which the account switch is expected to have completed. The value is the same as the targeted switch date if the switch completes in the expected timeline.

Datatype: "ISODate" on page 376

12.4.2.5 SwitchType <SwtchTp>

Presence: [1..1]

Definition: Indicates whether the account switch is a full switch or a partial switch.

Usage: A full switch indicates the transfer of the full balance of the account and associated payment mandates. A partial switch indicates the transfer of certain payment mandates to a new account.

Datatype: "SwitchType1Code" on page 374

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

12.4.2.6 SwitchStatus <SwtchSts>

Presence: [0..1]

Definition: State of the account switch at the time the message is sent.

Datatype: "SwitchStatus1Code" on page 373

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted.

CodeName	Name	Definition
		Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection. Usage: Redirection status should be used when the account switch service receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.

CodeName	Name	Definition
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

12.4.2.7 BalanceTransferWindow <BalTrfWndw>

Presence: [0..1]

Definition: Identifies the processing window in which the balance transfer will be processed on the day of the account switch.

Datatype: "BalanceTransferWindow1Code" on page 361

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

12.4.2.8 Response <Rspn>

Presence: [0..*]

Definition: Response code and additional information.

Response <Rspn> contains the following elements (see "ResponseDetails1" on page 349 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

12.4.3 SupplementaryData <SplmtryData>

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

Impacted by: C1 "SupplementaryDataRule"

SupplementaryData <SplmtryData> contains the following elements (see "SupplementaryData1" on page 183 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

13 Message Items Types

13.1 MessageComponents

13.1.1 Account

13.1.1.1 CashAccount24

Definition: Provides the details to identify an account.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		146
	Type <*Tp*>	[0..1]	±		146
	Currency <*Ccy*>	[0..1]	CodeSet	C2	147
	Name <*Nm*>	[0..1]	Text		147

13.1.1.1.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

Identification <Id> contains one of the following elements (see "AccountIdentification4Choice" on page 150 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	IBAN <*IBAN*>	[1..1]	IdentifierSet	C21	151
Or}	Other <*Othr*>	[1..1]			151
	Identification <*Id*>	[1..1]	Text		151
	SchemeName <*SchmeNm*>	[0..1]			151
{Or	Code <*Cd*>	[1..1]	CodeSet		152
Or}	Proprietary <*Prtry*>	[1..1]	Text		152
	Issuer <*Issr*>	[0..1]	Text		152

13.1.1.1.2 Type <Tp>

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

Type <Tp> contains one of the following elements (see "CashAccountType2Choice" on page 150 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		150
Or}	Proprietary <*Prtry*>	[1..1]	Text		150

13.1.1.1.3 Currency <Ccy>

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Impacted by: C2 "ActiveOrHistoricCurrency"

Datatype: "ActiveOrHistoricCurrencyCode" on page 360

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

13.1.1.1.4 Name <Nm>

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "Max70Text" on page 382

13.1.1.2 CashAccount36

Definition: Provides the details to identify an account.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

13.1.1.2.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

Identification <Id> contains one of the following elements (see "AccountIdentification4Choice" on page 150 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	IBAN <*IBAN*>	[1..1]	IdentifierSet	C21	151
Or}	Other <*Othr*>	[1..1]			151
	Identification <*Id*>	[1..1]	Text		151
	SchemeName <*SchmeNm*>	[0..1]			151
{Or	Code <*Cd*>	[1..1]	CodeSet		152
Or}	Proprietary <*Prtry*>	[1..1]	Text		152
	Issuer <*Issr*>	[0..1]	Text		152

13.1.1.2.2 Type <Tp>

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

Type <Tp> contains one of the following elements (see "CashAccountType2Choice" on page 150 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		150
Or}	Proprietary <*Prtry*>	[1..1]	Text		150

13.1.1.2.3 Currency <Ccy>

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Impacted by: C2 "ActiveOrHistoricCurrency"

Datatype: "ActiveOrHistoricCurrencyCode" on page 360

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

13.1.1.2.4 Name <Nm>

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "Max70Text" on page 382

13.1.1.2.5 Owner <Ownr>

Presence: [0..1]

Definition: Party that legally owns the account.

Owner <Ownr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.1.2.6 Servicer <Svcr>

Presence: [0..1]

Definition: Party that manages the account on behalf of the account owner, that is manages the registration and booking of entries on the account, calculates balances on the account and provides information about the account.

Servicer <Svcr> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.1.3 CashAccountType2Choice

Definition: Nature or use of the account.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		150
Or}	Proprietary <*Prtry*>	[1..1]	Text		150

13.1.1.3.1 Code <Cd>

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: "ExternalCashAccountType1Code" on page 365

13.1.1.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: "Max35Text" on page 381

13.1.2 Account Identification

13.1.2.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	IBAN <*IBAN*>	[1..1]	IdentifierSet	C21	151
Or}	Other <*Othr*>	[1..1]			151
	Identification <*Id*>	[1..1]	Text		151
	SchemeName <*SchmeNm*>	[0..1]			151
{Or	Code <*Cd*>	[1..1]	CodeSet		152
Or}	Proprietary <*Prtry*>	[1..1]	Text		152
	Issuer <*Issr*>	[0..1]	Text		152

13.1.2.1.1 IBAN <IBAN>

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Impacted by: C21 "IBAN"

Datatype: "IBAN2007Identifier" on page 377

Constraints

- **IBAN**

  A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

13.1.2.1.2 Other <Othr>

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

Other <Othr> contains the following **GenericAccountIdentification1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		151
	SchemeName <*SchmeNm*>	[0..1]			151
{Or	Code <*Cd*>	[1..1]	CodeSet		152
Or}	Proprietary <*Prtry*>	[1..1]	Text		152
	Issuer <*Issr*>	[0..1]	Text		152

13.1.2.1.2.1 Identification <Id>

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max34Text" on page 380

13.1.2.1.2.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **AccountSchemeName1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		152
Or}	Proprietary <*Prtry*>	[1..1]	Text		152

13.1.2.1.2.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 365

13.1.2.1.2.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 381

13.1.2.1.2.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 381

13.1.3 Amount

13.1.3.1 AmountAndDirection5

Definition: Amount of money debited or credited on the books of an account servicer.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Amount <*Amt*>	[1..1]	Amount	C1, C19	152
	CreditDebit <*CdtDbt*>	[0..1]	CodeSet		153

13.1.3.1.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money that is debited or credited.

Impacted by: C1 "ActiveCurrency", C19 "CurrencyAmount"

Datatype: "ActiveCurrencyAndAmount" on page 359

Constraints

- **ActiveCurrency**

  The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.3.1.2 CreditDebit <CdtDbt>

Presence: [0..1]

Definition: Indicates if the amount is a debited or a credited.

Datatype: "CreditDebitCode" on page 364

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

13.1.4 Cheque

13.1.4.1 Cheque7

Definition: Set of characteristics related to a cheque instruction, such as cheque type or cheque number.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ChequeType <*ChqTp*>	[0..1]	CodeSet		154
	ChequeNumber <*ChqNb*>	[0..1]	Text		154
	ChequeFrom <*ChqFr*>	[0..1]			155
	Name <*Nm*>	[1..1]	Text		155
	Address <*Adr*>	[1..1]	±		155
	DeliveryMethod <*DlvryMtd*>	[0..1]			155
{Or	Code <*Cd*>	[1..1]	CodeSet		156
Or}	Proprietary <*Prtry*>	[1..1]	Text		156
	DeliverTo <*DlvrTo*>	[0..1]			156
	Name <*Nm*>	[1..1]	Text		157
	Address <*Adr*>	[1..1]	±		157
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		157
	ChequeMaturityDate <*ChqMtrtyDt*>	[0..1]	Date		158
	FormsCode <*FrmsCd*>	[0..1]	Text		158
	MemoField <*MemoFld*>	[0..2]	Text		158
	RegionalClearingZone <*RgnlClrZone*>	[0..1]	Text		158
	PrintLocation <*PrtLctn*>	[0..1]	Text		158
	Signature <*Sgntr*>	[0..5]	Text		158

Constraints

- **ChequeMaturityDateRule**

  If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

```
On Condition
    /ChequeType is present
 And    /ChequeType is within DataType <<Code>> ChequeType3Code
Following Must be True
    /ChequeMaturityDate Must be absent
```

13.1.4.1.1 ChequeType <ChqTp>

Presence: [0..1]

Definition: Specifies the type of cheque to be issued.

Datatype: "ChequeType2Code" on page 363

CodeName	Name	Definition
CCHQ	CustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. Synonym is 'corporate cheque'.
CCCH	CertifiedCustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. The financial institution prints and certifies the cheque, guaranteeing the payment.
BCHQ	BankCheque	Cheque drawn on the account of the debtor's financial institution, which is debited on the debtor's account when the cheque is issued.These cheques are printed by the debtor's financial institution and payment is guaranteed by the financial institution. Synonym is 'cashier's cheque'.
DRFT	Draft	A guaranteed bank cheque with a future value date (do not pay before], which in commercial terms is a 'negotiatable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.
ELDR	ElectronicDraft	An instrument with a future value date (do not pay before], which in commercial terms is a 'negotiatable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.

13.1.4.1.2 ChequeNumber <ChqNb>

Presence: [0..1]

Definition: Unique and unambiguous identifier for a cheque as assigned by the agent.

Datatype: "Max35Text" on page 381

13.1.4.1.3 ChequeFrom <ChqFr>

Presence: [0..1]

Definition: Identifies the party that ordered the issuance of the cheque.

ChequeFrom <ChqFr> contains the following **NameAndAddress10** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[1..1]	Text		155
	Address <*Adr*>	[1..1]	±		155

13.1.4.1.3.1 Name <Nm>

Presence: [1..1]

Definition: Name by which a party is known and is usually used to identify that party.

Datatype: "Max140Text" on page 379

13.1.4.1.3.2 Address <Adr>

Presence: [1..1]

Definition: Postal address of a party.

Address <Adr> contains the following elements (see "PostalAddress6" on page 267 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.4.1.4 DeliveryMethod <DlvryMtd>

Presence: [0..1]

Definition: Specifies the delivery method of the cheque by the debtor's agent.

DeliveryMethod <DlvryMtd> contains one of the following **ChequeDeliveryMethod1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		156
Or}	Proprietary <*Prtry*>	[1..1]	Text		156

13.1.4.1.4.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the delivery method of the cheque by the debtor's agent.

Datatype: "ChequeDelivery1Code" on page 362

CodeName	Name	Definition
MLDB	MailToDebtor	Cheque is to be sent through mail services to debtor.
MLCD	MailToCreditor	Cheque is to be sent through mail services to creditor.
MLFA	MailToFinalAgent	Cheque is to be sent through mail services to creditor agent.
CRDB	CourierToDebtor	Cheque is to be sent through courier services to debtor.
CRCD	CourierToCreditor	Cheque is to be sent through courier services to creditor.
CRFA	CourierToFinalAgent	Cheque is to be sent through courier services to creditor agent.
PUDB	PickUpByDebtor	Cheque will be picked up by the debtor.
PUCD	PickUpByCreditor	Cheque will be picked up by the creditor.
PUFA	PickUpByFinalAgent	Cheque will be picked up by the creditor agent.
RGDB	RegisteredMailToDebtor	Cheque is to be sent through registered mail services to debtor.
RGCD	RegisteredMailToCreditor	Cheque is to be sent through registered mail services to creditor.
RGFA	RegisteredMailToFinalAgent	Cheque is to be sent through registered mail services to creditor agent.

13.1.4.1.4.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies a proprietary delivery method of the cheque by the debtor's agent.

Datatype: "Max35Text" on page 381

13.1.4.1.5 DeliverTo <DlvrTo>

Presence: [0..1]

Definition: Party to whom the debtor's agent needs to send the cheque.

DeliverTo <DlvrTo> contains the following **NameAndAddress10** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[1..1]	Text		157
	Address <*Adr*>	[1..1]	±		157

13.1.4.1.5.1 Name <Nm>

Presence: [1..1]

Definition: Name by which a party is known and is usually used to identify that party.

Datatype: "Max140Text" on page 379

13.1.4.1.5.2 Address <Adr>

Presence: [1..1]

Definition: Postal address of a party.

Address <Adr> contains the following elements (see "PostalAddress6" on page 267 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.4.1.6 InstructionPriority <InstrPrty>

Presence: [0..1]

Definition: Urgency or order of importance that the originator would like the recipient of the payment instruction to apply to the processing of the payment instruction.

Datatype: "Priority2Code" on page 372

CodeName	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

13.1.4.1.7 ChequeMaturityDate <ChqMtrtyDt>

Presence: [0..1]

Definition: Date when the draft becomes payable and the debtor's account is debited.

Datatype: "ISODate" on page 376

13.1.4.1.8 FormsCode <FrmsCd>

Presence: [0..1]

Definition: Identifies, in a coded form, the cheque layout, company logo and digitised signature to be used to print the cheque, as agreed between the initiating party and the debtor's agent.

Datatype: "Max35Text" on page 381

13.1.4.1.9 MemoField <MemoFld>

Presence: [0..2]

Definition: Information that needs to be printed on a cheque, used by the payer to add miscellaneous information.

Datatype: "Max35Text" on page 381

13.1.4.1.10 RegionalClearingZone <RgnlClrZone>

Presence: [0..1]

Definition: Regional area in which the cheque can be cleared, when a country has no nation-wide cheque clearing organisation.

Datatype: "Max35Text" on page 381

13.1.4.1.11 PrintLocation <PrtLctn>

Presence: [0..1]

Definition: Specifies the print location of the cheque.

Datatype: "Max35Text" on page 381

13.1.4.1.12 Signature <Sgntr>

Presence: [0..5]

Definition: Signature to be used by the cheque servicer on a specific cheque to be printed.

Datatype: "Max70Text" on page 382

13.1.5 Direct Debit

13.1.5.1 DirectDebitInstructionDetails1

Definition: Instructions, initiated by the creditor, to debit a debtor's account in favour of the creditor.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	MandateIdentification <*MndtId*>	[1..1]	Text		159
	AutomatedDirectDebitInstructionIndicator <*AutomtdDrctDbtInstrInd*>	[0..1]	Indicator		159
	DirectDebitTransferableIndicator <*DrctDbtTrfblInd*>	[0..1]	Indicator		159
	Creditor <*Cdtr*>	[1..1]	±		160
	LastCollectionCurrencyAmount <*LastColltnCcyAmt*>	[0..1]	Amount	C2, C20	160
	LastCollectionDate <*LastColltnDt*>	[0..1]	Date		160
	OtherDetails <*OthrDtls*>	[0..*]			161
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		161
	Code <*Cd*>	[1..1]	Text		161
	Proprietary <*Prtry*>	[0..1]	Text		161
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		161
	StartDate <*StartDt*>	[0..1]	Date		162
	Description <*Desc*>	[0..1]	Text		162

13.1.5.1.1 MandateIdentification <MndtId>

Presence: [1..1]

Definition: Identification of the mandate for a direct debit instruction.

Datatype: "Max35Text" on page 381

13.1.5.1.2 AutomatedDirectDebitInstructionIndicator <AutomtdDrctDbtInstrInd>

Presence: [0..1]

Definition: Indicates whether the instruction is an automated direct debit instruction.

Usage: Default value for AutomatedDirectDebitInstructionIndicator is false.

Datatype: One of the following values must be used (see "YesNoIndicator" on page 378):

- *Meaning When True:* Yes
- *Meaning When False:* No

13.1.5.1.3 DirectDebitTransferableIndicator <DrctDbtTrfblInd>

Presence: [0..1]

Definition: Indicates whether the direct debit instruction is transferable.

Usage: Default value for DirectDebitTransferableIndicator is false.

Datatype: One of the following values must be used (see "YesNoIndicator" on page 378):

- *Meaning When True:* Yes
- *Meaning When False:* No

13.1.5.1.4 Creditor <Cdtr>

Presence: [1..1]

Definition: Party to which an amount of money is due.

Creditor <Cdtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.5.1.5 LastCollectionCurrencyAmount <LastColltnCcyAmt>

Presence: [0..1]

Definition: Amount of the last debit made for the direct debit mandate.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.5.1.6 LastCollectionDate <LastColltnDt>

Presence: [0..1]

Definition: Date on which the last debit for the direct debit mandate may be made.

Usage: Not included if all limits to the validity of the direct debit mandate have already been specified or if there are no time limits on the validity of the direct debit.

Datatype: "ISODate" on page 376

13.1.5.1.7 OtherDetails <OthrDtls>

Presence: [0..*]

Definition: Provides further information about the status of a requested transaction schedule transfer.

OtherDetails <OthrDtls> contains the following **TransferInstruction1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		161
	Code <*Cd*>	[1..1]	Text		161
	Proprietary <*Prtry*>	[0..1]	Text		161
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		161
	StartDate <*StartDt*>	[0..1]	Date		162
	Description <*Desc*>	[0..1]	Text		162

13.1.5.1.7.1 TransferIndicator <TrfInd>

Presence: [0..1]

Definition: Indicates whether a payment arrangement is transferable.

Usage: Default value for TransferIndicator is false.

Datatype: One of the following values must be used (see "YesNoIndicator" on page 378):

- *Meaning When True:* Yes
- *Meaning When False:* No

13.1.5.1.7.2 Code <Cd>

Presence: [1..1]

Definition: Specifies an additional parameter to be applied to the requested transaction schedule.

Datatype: "Max35Text" on page 381

13.1.5.1.7.3 Proprietary <Prtry>

Presence: [0..1]

Definition: Specifies an additional parameter to be applied to the transaction schedule in a proprietary format.

Datatype: "Max256Text" on page 380

13.1.5.1.7.4 StartDateTime <StartDtTm>

Presence: [0..1]

Definition: The date and time at which the event specified by Code commences.

Datatype: "ISODateTime" on page 376

13.1.5.1.7.5 StartDate <StartDt>

Presence: [0..1]

Definition: The date on which the event specified by Code commences.

Datatype: "ISODate" on page 376

13.1.5.1.7.6 Description <Desc>

Presence: [0..1]

Definition: Additional switch parameters in a free text format.

Datatype: "Max350Text" on page 380

13.1.6 Document

13.1.6.1 CreditorReferenceInformation2

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			162
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			162
{Or	Code <*Cd*>	[1..1]	CodeSet		163
Or}	Proprietary <*Prtry*>	[1..1]	Text		163
	Issuer <*Issr*>	[0..1]	Text		163
	Reference <*Ref*>	[0..1]	Text		163

13.1.6.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of creditor reference.

Type <Tp> contains the following **CreditorReferenceType2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			162
{Or	Code <*Cd*>	[1..1]	CodeSet		163
Or}	Proprietary <*Prtry*>	[1..1]	Text		163
	Issuer <*Issr*>	[0..1]	Text		163

13.1.6.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Coded or proprietary format creditor reference type.

CodeOrProprietary <CdOrPrtry> contains one of the following **CreditorReferenceType1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		163
Or}	Proprietary <*Prtry*>	[1..1]	Text		163

13.1.6.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Type of creditor reference, in a coded form.

Datatype: "DocumentType3Code" on page 364

CodeName	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, eg, in a cover scenario.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

13.1.6.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Creditor reference type, in a proprietary form.

Datatype: "Max35Text" on page 381

13.1.6.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the credit reference type.

Datatype: "Max35Text" on page 381

13.1.6.1.2 Reference <Ref>

Presence: [0..1]

Definition: Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.

Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

Datatype: "Max35Text" on page 381

13.1.7 Financial Institution Identification

13.1.7.1 BranchAndFinancialInstitutionIdentification5

Definition: Set of elements used to uniquely and unambiguously identify a financial institution or a branch of a financial institution.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.7.1.1 FinancialInstitutionIdentification <FinInstnId>

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

FinancialInstitutionIdentification <FinInstnId> contains the following elements (see "FinancialInstitutionIdentification8" on page 166 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	BICFI <*BICFI*>	[0..1]	IdentifierSet	C4	167
	ClearingSystemMemberIdentification <*ClrSysMmbId*>	[0..1]	±		167
	Name <*Nm*>	[0..1]	Text		167
	PostalAddress <*PstlAdr*>	[0..1]	±		167
	Other <*Othr*>	[0..1]	±		168

13.1.7.1.2 BranchIdentification <BrnchId>

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

BranchIdentification <BrnchId> contains the following elements (see "BranchData2" on page 168 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[0..1]	Text		169
	Name <*Nm*>	[0..1]	Text		169
	PostalAddress <*PstlAdr*>	[0..1]	±		169

13.1.7.2 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		165
	SchemeName <*SchmeNm*>	[0..1]			165
{Or	Code <*Cd*>	[1..1]	CodeSet		165
Or}	Proprietary <*Prtry*>	[1..1]	Text		165
	Issuer <*Issr*>	[0..1]	Text		166

13.1.7.2.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 381

13.1.7.2.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **FinancialIdentificationSchemeName1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		165
Or}	Proprietary <*Prtry*>	[1..1]	Text		165

13.1.7.2.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalFinancialInstitutionIdentification1Code" on page 366

13.1.7.2.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 381

13.1.7.2.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 381

13.1.7.3 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ClearingSystemIdentification <*ClrSysId*>	[0..1]	±		166
	MemberIdentification <*MmbId*>	[1..1]	Text		166

13.1.7.3.1 ClearingSystemIdentification <ClrSysId>

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

ClearingSystemIdentification <ClrSysId> contains one of the following elements (see "ClearingSystemIdentification2Choice" on page 350 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		350
Or}	Proprietary <*Prtry*>	[1..1]	Text		350

13.1.7.3.2 MemberIdentification <MmbId>

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "Max35Text" on page 381

13.1.7.4 FinancialInstitutionIdentification8

Definition: Set of elements used to identify a financial institution.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	BICFI <*BICFI*>	[0..1]	IdentifierSet	C4	167
	ClearingSystemMemberIdentification <*ClrSysMmbId*>	[0..1]	±		167
	Name <*Nm*>	[0..1]	Text		167
	PostalAddress <*PstlAdr*>	[0..1]	±		167
	Other <*Othr*>	[0..1]	±		168

13.1.7.4.1 BICFI <BICFI>

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Impacted by: C4 "BICFI"

Datatype: "BICFIIdentifier" on page 377

Constraints

- **BICFI**

  Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

13.1.7.4.2 ClearingSystemMemberIdentification <ClrSysMmbId>

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

ClearingSystemMemberIdentification <ClrSysMmbId> contains the following elements (see "ClearingSystemMemberIdentification2" on page 166 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ClearingSystemIdentification <*ClrSysId*>	[0..1]	±		166
	MemberIdentification <*MmbId*>	[1..1]	Text		166

13.1.7.4.3 Name <Nm>

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 379

13.1.7.4.4 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see "PostalAddress6" on page 267 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.7.4.5 Other <Othr>

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following elements (see "GenericFinancialIdentification1" on page 165 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		165
	SchemeName <*SchmeNm*>	[0..1]			165
{Or	Code <*Cd*>	[1..1]	CodeSet		165
Or}	Proprietary <*Prtry*>	[1..1]	Text		165
	Issuer <*Issr*>	[0..1]	Text		166

13.1.7.5 BranchData2

Definition: Information that locates and identifies a specific branch of a financial institution.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[0..1]	Text		169
	Name <*Nm*>	[0..1]	Text		169
	PostalAddress <*PstlAdr*>	[0..1]	±		169

13.1.7.5.1 Identification <Id>

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: "Max35Text" on page 381

13.1.7.5.2 Name <Nm>

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 379

13.1.7.5.3 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see "PostalAddress6" on page 267 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.8 Identification Information

13.1.8.1 MessageIdentification1

Definition: Identifies a message by a unique identifier and the date and time when the message was created by the sender.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	CreationDateTime <*CreDtTm*>	[1..1]	DateTime		170

13.1.8.1.1 Identification <Id>

Presence: [1..1]

Definition: Identification of the message.

Datatype: "Max35Text" on page 381

13.1.8.1.2 CreationDateTime <CreDtTm>

Presence: [1..1]

Definition: Date of creation of the message.

Datatype: "ISODateTime" on page 376

13.1.8.2 GenericIdentification47

Definition: Information related to an identification, for example, party identification or account identification.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	Issuer <*Issr*>	[1..1]	Text		170
	SchemeName <*SchmeNm*>	[0..1]	Text		170

13.1.8.2.1 Identification <Id>

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 379

13.1.8.2.2 Issuer <Issr>

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max4AlphaNumericText" on page 381

13.1.8.2.3 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: "Max4AlphaNumericText" on page 381

13.1.8.3 GenericIdentification44

Definition: Information related to the identification of an individual person.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		171
	Type <*Tp*>	[1..1]			171
{Or	Code <*Cd*>	[1..1]	CodeSet		171
Or}	Proprietary <*Prtry*>	[1..1]	±		172
	Issuer <*Issr*>	[0..1]	Text		172
	IssueDate <*IsseDt*>	[0..1]	Date		172
	ExpiryDate <*XpryDt*>	[0..1]	Date		172

13.1.8.3.1 Identification <Id>

Presence: [1..1]

Definition: Name or number assigned by an entity to enable recognition of that entity, eg, account identifier.

Datatype: "Max35Text" on page 381

13.1.8.3.2 Type <Tp>

Presence: [1..1]

Definition: Specifies the nature of the identification.

Type <Tp> contains one of the following **OtherIdentification1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		171
Or}	Proprietary <*Prtry*>	[1..1]	±		172

13.1.8.3.2.1 Code <Cd>

Presence: [1..1]

Definition: Other identification expressed as a code.

Datatype: "PersonIdentificationType5Code" on page 371

CodeName	Name	Definition
AREG	AlienRegistrationNumber	Number assigned by a government agency to identify foreign nationals.
CPFA	CPFAccountNumber	Account issued by the Central Provident Fund Board (Singapore).
DRLC	DriversLicenseNumber	Number assigned by a license authority to a driver's license.
EMID	EmployerIdentificationNumber	Number assigned to an employer by a registration authority.
IDCD	IdentityCardNumber	Number assigned by a national authority to an identity card.

CodeName	Name	Definition
NRIN	NationalRegistrationIdentificationNumber	National registration identification number. In Singapore this is known as the NRIC.
OTHR	Other	Another type of identification type.
PASS	PassportNumber	Number assigned by a passport authority to a passport.
POCD	PostOfficeCardNumber	Post office card number as assigned by a national post office.
SOCS	SocialSecurityNumber	Number assigned by a social security agency.
SRSA	SRSAccountNumber	Supplementary retirement scheme account number.
GUNL	GunLicenseNumber	Gun license number as assigned by a gun licensing authority.

13.1.8.3.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Other identification expressed as a proprietary code.

Proprietary <Prtry> contains the following elements (see "GenericIdentification47" on page 170 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		170
	Issuer <*Issr*>	[1..1]	Text		170
	SchemeName <*SchmeNm*>	[0..1]	Text		170

13.1.8.3.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identifier.

Datatype: "Max35Text" on page 381

13.1.8.3.4 IssueDate <IsseDt>

Presence: [0..1]

Definition: Date at which the identification was issued.

Datatype: "ISODate" on page 376

13.1.8.3.5 ExpiryDate <XpryDt>

Presence: [0..1]

Definition: Date at which the identification expires.

Datatype: "ISODate" on page 376

13.1.8.4 PaymentIdentification1

Definition: Set of elements used to provide further means of referencing a payment transaction.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionIdentification <*InstrId*>	[0..1]	Text		173
	EndToEndIdentification <*EndToEndId*>	[1..1]	Text		173

13.1.8.4.1 InstructionIdentification <InstrId>

Presence: [0..1]

Definition: Unique identification as assigned by an instructing party for an instructed party to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "Max35Text" on page 381

13.1.8.4.2 EndToEndIdentification <EndToEndId>

Presence: [1..1]

Definition: Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Datatype: "Max35Text" on page 381

13.1.9 Miscellaneous

13.1.9.1 RemittanceLocation2

Definition: Set of elements used to provide information on the remittance advice.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	RemittanceIdentification <*RmtId*>	[0..1]	Text		174
	RemittanceLocationMethod <*RmtLctnMtd*>	[0..1]	CodeSet		174
	RemittanceLocationElectronicAddress <*RmtLctnElctrncAdr*>	[0..1]	Text		174
	RemittanceLocationPostalAddress <*RmtLctnPstlAdr*>	[0..1]			174
	Name <*Nm*>	[1..1]	Text		175
	Address <*Adr*>	[1..1]	±		175

13.1.9.1.1 RemittanceIdentification <RmtId>

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the remittance information sent separately from the payment instruction, such as a remittance advice.

Datatype: "Max35Text" on page 381

13.1.9.1.2 RemittanceLocationMethod <RmtLctnMtd>

Presence: [0..1]

Definition: Method used to deliver the remittance advice information.

Datatype: "RemittanceLocationMethod2Code" on page 372

CodeName	Name	Definition
FAXI	Fax	Remittance advice information must be faxed.
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.
EMAL	EMail	Remittance advice information must be sent through e-mail.
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).

13.1.9.1.3 RemittanceLocationElectronicAddress <RmtLctnElctrncAdr>

Presence: [0..1]

Definition: Electronic address to which an agent is to send the remittance information.

Datatype: "Max2048Text" on page 380

13.1.9.1.4 RemittanceLocationPostalAddress <RmtLctnPstlAdr>

Presence: [0..1]

Definition: Postal address to which an agent is to send the remittance information.

RemittanceLocationPostalAddress <RmtLctnPstlAdr> contains the following **NameAndAddress10** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[1..1]	Text		175
	Address <*Adr*>	[1..1]	±		175

13.1.9.1.4.1 Name <Nm>

Presence: [1..1]

Definition: Name by which a party is known and is usually used to identify that party.

Datatype: "Max140Text" on page 379

13.1.9.1.4.2 Address <Adr>

Presence: [1..1]

Definition: Postal address of a party.

Address <Adr> contains the following elements (see "PostalAddress6" on page 267 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.9.2 Frequency37Choice

Definition: Choice of format for a frequency, for example, the frequency of payment.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		175
Or}	Proprietary <*Prtry*>	[1..1]	Text		176

13.1.9.2.1 Code <Cd>

Presence: [1..1]

Definition: Frequency expressed as an ISO 20022 code.

Datatype: "Frequency10Code" on page 369

CodeName	Name	Definition
NEVR	Never	Event does never take place.
YEAR	Annual	Event takes place every year or once a year.
RATE	Rate	Event takes place based on a change of a rate.
MIAN	SemiAnnual	Event takes place every six months or two times a year.
QURT	Quarterly	Event takes place every three months or four times a year.

13.1.9.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Frequency expressed as a proprietary code.

Datatype: "Max35Text" on page 381

13.1.9.3 ContactDetails2

Definition: Communication device number or electronic address used for communication.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	NamePrefix <*NmPrfx*>	[0..1]	CodeSet		176
	Name <*Nm*>	[0..1]	Text		177
	PhoneNumber <*PhneNb*>	[0..1]	Text		177
	MobileNumber <*MobNb*>	[0..1]	Text		177
	FaxNumber <*FaxNb*>	[0..1]	Text		177
	EmailAddress <*EmailAdr*>	[0..1]	Text		177
	Other <*Othr*>	[0..1]	Text		177

13.1.9.3.1 NamePrefix <NmPrfx>

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix1Code" on page 370

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MIST	Mister	Title of the person is Mister or Mr.
MISS	Miss	Title of the person is Miss.
MADM	Madam	Title of the person is Madam.

13.1.9.3.2 Name <Nm>

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 379

13.1.9.3.3 PhoneNumber <PhneNb>

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 382

13.1.9.3.4 MobileNumber <MobNb>

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 382

13.1.9.3.5 FaxNumber <FaxNb>

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: "PhoneNumber" on page 382

13.1.9.3.6 EmailAddress <EmailAdr>

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: "Max2048Text" on page 380

13.1.9.3.7 Other <Othr>

Presence: [0..1]

Definition: Contact details in another form.

Datatype: "Max35Text" on page 381

13.1.9.4 RemittanceAmount2

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DuePayableAmount <*DuePyblAmt*>	[0..1]	Amount	C2, C20	178
	DiscountAppliedAmount <*DscntApldAmt*>	[0..*]			179
	Type <*Tp*>	[0..1]			179
{Or	Code <*Cd*>	[1..1]	CodeSet		179
Or}	Proprietary <*Prtry*>	[1..1]	Text		179
	Amount <*Amt*>	[1..1]	Amount	C2, C20	179
	CreditNoteAmount <*CdtNoteAmt*>	[0..1]	Amount	C2, C20	180
	TaxAmount <*TaxAmt*>	[0..*]			180
	Type <*Tp*>	[0..1]			180
{Or	Code <*Cd*>	[1..1]	CodeSet		181
Or}	Proprietary <*Prtry*>	[1..1]	Text		181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	181
	AdjustmentAmountAndReason <*AdjstmntAmtAndRsn*>	[0..*]			181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	182
	CreditDebitIndicator <*CdtDbtInd*>	[0..1]	CodeSet		182
	Reason <*Rsn*>	[0..1]	Text		182
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		182
	RemittedAmount <*RmtdAmt*>	[0..1]	Amount	C2, C20	183

13.1.9.4.1 DuePayableAmount <DuePyblAmt>

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.9.4.2 DiscountAppliedAmount <DscntApldAmt>

Presence: [0..*]

Definition: Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor.

DiscountAppliedAmount <DscntApldAmt> contains the following **DiscountAmountAndType1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			179
{Or	Code <*Cd*>	[1..1]	CodeSet		179
Or}	Proprietary <*Prtry*>	[1..1]	Text		179
	Amount <*Amt*>	[1..1]	Amount	C2, C20	179

13.1.9.4.2.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **DiscountAmountType1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		179
Or}	Proprietary <*Prtry*>	[1..1]	Text		179

13.1.9.4.2.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: "ExternalDiscountAmountType1Code" on page 366

13.1.9.4.2.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: "Max35Text" on page 381

13.1.9.4.2.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.9.4.3 CreditNoteAmount <CdtNoteAmt>

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.9.4.4 TaxAmount <TaxAmt>

Presence: [0..*]

Definition: Quantity of cash resulting from the calculation of the tax.

TaxAmount <TaxAmt> contains the following **TaxAmountAndType1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			180
{Or	Code <*Cd*>	[1..1]	CodeSet		181
Or}	Proprietary <*Prtry*>	[1..1]	Text		181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	181

13.1.9.4.4.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the amount.

Type <Tp> contains one of the following **TaxAmountType1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		181
Or}	Proprietary <*Prtry*>	[1..1]	Text		181

13.1.9.4.4.1.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: "ExternalTaxAmountType1Code" on page 368

13.1.9.4.4.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: "Max35Text" on page 381

13.1.9.4.4.2 Amount <Amt>

Presence: [1..1]

Definition: Amount of money, which has been typed.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.9.4.5 AdjustmentAmountAndReason <AdjstmntAmtAndRsn>

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the document adjustment.

AdjustmentAmountAndReason <AdjstmntAmtAndRsn> contains the following **DocumentAdjustment1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Amount <*Amt*>	[1..1]	Amount	C2, C20	182
	CreditDebitIndicator <*CdtDbtInd*>	[0..1]	CodeSet		182
	Reason <*Rsn*>	[0..1]	Text		182
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		182

13.1.9.4.5.1 Amount <Amt>

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.9.4.5.2 CreditDebitIndicator <CdtDbtInd>

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: "CreditDebitCode" on page 364

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

13.1.9.4.5.3 Reason <Rsn>

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: "Max4Text" on page 381

13.1.9.4.5.4 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: "Max140Text" on page 379

13.1.9.4.6 RemittedAmount <RmtdAmt>

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.9.5 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PlaceAndName <*PlcAndNm*>	[0..1]	Text		183
	Envelope <*Envlp*>	[1..1]	(External Schema)		183

Constraints

- **SupplementaryDataRule**

  This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

13.1.9.5.1 PlaceAndName <PlcAndNm>

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 380

13.1.9.5.2 Envelope <Envlp>

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

Type: (External Schema)

Technical component that contains the validated supplementary data information. This technical envelope allows to segregate the supplementary data information from any other information.

13.1.10 Organisation Identification

13.1.10.1 OrganisationIdentification8

Definition: Unique and unambiguous way to identify an organisation.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AnyBIC <*AnyBIC*>	[0..1]	IdentifierSet	C3	184
	Other <*Othr*>	[0..*]			184
	Identification <*Id*>	[1..1]	Text		185
	SchemeName <*SchmeNm*>	[0..1]			185
{Or	Code <*Cd*>	[1..1]	CodeSet		185
Or}	Proprietary <*Prtry*>	[1..1]	Text		185
	Issuer <*Issr*>	[0..1]	Text		185

13.1.10.1.1 AnyBIC <AnyBIC>

Presence: [0..1]

Definition: Code allocated to a financial institution or non financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Impacted by: C3 "AnyBIC"

Datatype: "AnyBICIdentifier" on page 376

Constraints

- **AnyBIC**

  Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

13.1.10.1.2 Other <Othr>

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following **GenericOrganisationIdentification1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		185
	SchemeName <*SchmeNm*>	[0..1]			185
{Or	Code <*Cd*>	[1..1]	CodeSet		185
Or}	Proprietary <*Prtry*>	[1..1]	Text		185
	Issuer <*Issr*>	[0..1]	Text		185

13.1.10.1.2.1 Identification <Id>

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 381

13.1.10.1.2.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **OrganisationIdentificationSchemeName1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		185
Or}	Proprietary <*Prtry*>	[1..1]	Text		185

13.1.10.1.2.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalOrganisationIdentification1Code" on page 367

13.1.10.1.2.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 381

13.1.10.1.2.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 381

13.1.11 Party Identification

13.1.11.1 NewAccount1

Definition: Information about the new account.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Account <*Acct*>	[1..1]	±		189
	AccountParty <*AcctPty*>	[1..*]			189
	CurrentName <*CurNm*>	[1..1]			191
	NamePrefix <*NmPrfx*>	[0..1]			192
{Or	NamePrefix <*NmPrfx*>	[1..1]	CodeSet		192
Or}	ExtendedNamePrefix <*XtndedNmPrfx*>	[1..1]	Text		192
	Surname <*Srnm*>	[1..1]	Text		193
	GivenName <*GvnNm*>	[0..1]	Text		193
	MiddleName <*MddlNm*>	[0..1]	Text		193
	Initials <*Initls*>	[0..1]	Text		193
	NameSuffix <*NmSfx*>	[0..1]	Text		193
	Name <*Nm*>	[0..1]	Text		193
	StartDate <*StartDt*>	[0..1]	Date		193
	EndDate <*EndDt*>	[0..1]	Date		193
	PreviousName <*PrvsNm*>	[0..*]			194
	NamePrefix <*NmPrfx*>	[0..1]			194
{Or	NamePrefix <*NmPrfx*>	[1..1]	CodeSet		194
Or}	ExtendedNamePrefix <*XtndedNmPrfx*>	[1..1]	Text		195
	Surname <*Srnm*>	[1..1]	Text		195
	GivenName <*GvnNm*>	[0..1]	Text		195
	MiddleName <*MddlNm*>	[0..1]	Text		195
	Initials <*Initls*>	[0..1]	Text		195
	NameSuffix <*NmSfx*>	[0..1]	Text		195
	Name <*Nm*>	[0..1]	Text		195
	StartDate <*StartDt*>	[0..1]	Date		195
	EndDate <*EndDt*>	[0..1]	Date		195
	Gender <*Gndr*>	[0..1]	CodeSet		196
	Language <*Lang*>	[0..1]	CodeSet	C16	196
	BirthDate <*BirthDt*>	[0..1]	Date		196
	CountryOfBirth <*CtryOfBirth*>	[0..1]	CodeSet	C18	196
	ProvinceOfBirth <*PrvcOfBirth*>	[0..1]	Text		196

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CityOfBirth <*CityOfBirth*>	[0..1]	Text		197
	TaxationCountry <*TaxtnCtry*>	[0..1]	CodeSet	C18	197
	CountryAndResidentialStatus <*CtryAndResdtlSts*>	[0..1]	±		197
	SocialSecurityNumber <*SclSctyNb*>	[0..1]	Text		197
	PostalAddress <*PstlAdr*>	[0..*]	±		197
	CitizenshipInformation <*CtznshInf*>	[0..*]			198
	Nationality <*Ntlty*>	[1..1]	CodeSet	C17	198
	MinorIndicator <*MnrInd*>	[0..1]	Indicator		198
	StartDate <*StartDt*>	[0..1]	Date		199
	EndDate <*EndDt*>	[0..1]	Date		199
	PrimaryCommunicationAddress <*PmryComAdr*>	[0..1]	±		199
	SecondaryCommunicationAddress <*ScndryComAdr*>	[0..1]	±		199
	OtherIdentification <*OthrId*>	[0..*]	±		200
	OtherDetails <*OthrDtls*>	[0..*]			200
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		201
	Code <*Cd*>	[1..1]	Text		201
	Proprietary <*Prtry*>	[0..1]	Text		201
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		201
	StartDate <*StartDt*>	[0..1]	Date		201
	Description <*Desc*>	[0..1]	Text		202
	Organisation <*Org*>	[0..1]			202
	FullLegalName <*FullLglNm*>	[1..1]	Text		202
	TradingName <*TradgNm*>	[0..1]	Text		203
	OrganisationLegalStatus <*OrgLglSts*>	[0..1]	CodeSet		203
	EstablishedDate <*EstblishdDt*>	[0..1]	Date		203
	RegistrationNumber <*RegnNb*>	[0..1]	Text		203
	RegistrationCountry <*RegnCtry*>	[0..1]	CodeSet	C18	203
	RegistrationDate <*RegnDt*>	[0..1]	Date		204
	TaxationIdentificationNumber <*TaxtnIdNb*>	[0..1]	Text		204
	TaxationCountry <*TaxtnCtry*>	[0..1]	CodeSet	C18	204
	CountryOfOperation <*CtryOfOpr*>	[0..1]	CodeSet	C18	204

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	BoardResolutionIndicator <*BrdRsltnInd*>	[0..1]	Indicator		204
	BusinessAddress <*BizAdr*>	[0..1]	±		205
	OperationalAddress <*OprlAdr*>	[0..1]	±		205
	LegalAddress <*LglAdr*>	[0..1]	±		206
	RepresentativeOfficer <*RprtvOffcr*>	[0..*]	±		206
	TreasuryManager <*TrsrMgr*>	[0..1]	±		207
	MainMandateHolder <*MainMndtHldr*>	[0..*]	±		207
	Sender <*Sndr*>	[0..*]	±		208

13.1.11.1.1 Account <Acct>

Presence: [1..1]

Definition: Details of the new account.

Account <Acct> contains the following elements (see "CashAccount36" on page 147 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		148
	Type <*Tp*>	[0..1]	±		148
	Currency <*Ccy*>	[0..1]	CodeSet	C2	148
	Name <*Nm*>	[0..1]	Text		149
	Owner <*Ownr*>	[0..1]	±		149
	Servicer <*Svcr*>	[0..1]	±		149

13.1.11.1.2 AccountParty <AcctPty>

Presence: [1..*]

Definition: Party or parties to be identified in the context of account operations.

AccountParty <AcctPty> contains the following **IndividualPerson19** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CurrentName <*CurNm*>	[1..1]			191
	NamePrefix <*NmPrfx*>	[0..1]			192
{Or	NamePrefix <*NmPrfx*>	[1..1]	CodeSet		192
Or}	ExtendedNamePrefix <*XtndedNmPrfx*>	[1..1]	Text		192
	Surname <*Srnm*>	[1..1]	Text		193
	GivenName <*GvnNm*>	[0..1]	Text		193
	MiddleName <*MddlNm*>	[0..1]	Text		193
	Initials <*Initls*>	[0..1]	Text		193
	NameSuffix <*NmSfx*>	[0..1]	Text		193
	Name <*Nm*>	[0..1]	Text		193
	StartDate <*StartDt*>	[0..1]	Date		193
	EndDate <*EndDt*>	[0..1]	Date		193
	PreviousName <*PrvsNm*>	[0..*]			194
	NamePrefix <*NmPrfx*>	[0..1]			194
{Or	NamePrefix <*NmPrfx*>	[1..1]	CodeSet		194
Or}	ExtendedNamePrefix <*XtndedNmPrfx*>	[1..1]	Text		195
	Surname <*Srnm*>	[1..1]	Text		195
	GivenName <*GvnNm*>	[0..1]	Text		195
	MiddleName <*MddlNm*>	[0..1]	Text		195
	Initials <*Initls*>	[0..1]	Text		195
	NameSuffix <*NmSfx*>	[0..1]	Text		195
	Name <*Nm*>	[0..1]	Text		195
	StartDate <*StartDt*>	[0..1]	Date		195
	EndDate <*EndDt*>	[0..1]	Date		195
	Gender <*Gndr*>	[0..1]	CodeSet		196
	Language <*Lang*>	[0..1]	CodeSet	C16	196
	BirthDate <*BirthDt*>	[0..1]	Date		196
	CountryOfBirth <*CtryOfBirth*>	[0..1]	CodeSet	C18	196
	ProvinceOfBirth <*PrvcOfBirth*>	[0..1]	Text		196
	CityOfBirth <*CityOfBirth*>	[0..1]	Text		197
	TaxationCountry <*TaxtnCtry*>	[0..1]	CodeSet	C18	197

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CountryAndResidentialStatus <*CtryAndResdtlSts*>	[0..1]	±		197
	SocialSecurityNumber <*SclSctyNb*>	[0..1]	Text		197
	PostalAddress <*PstlAdr*>	[0..*]	±		197
	CitizenshipInformation <*CtznshInf*>	[0..*]			198
	Nationality <*Ntlty*>	[1..1]	CodeSet	C17	198
	MinorIndicator <*MnrInd*>	[0..1]	Indicator		198
	StartDate <*StartDt*>	[0..1]	Date		199
	EndDate <*EndDt*>	[0..1]	Date		199
	PrimaryCommunicationAddress <*PmryComAdr*>	[0..1]	±		199
	SecondaryCommunicationAddress <*ScndryComAdr*>	[0..1]	±		199
	OtherIdentification <*OthrId*>	[0..*]	±		200
	OtherDetails <*OthrDtls*>	[0..*]			200
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		201
	Code <*Cd*>	[1..1]	Text		201
	Proprietary <*Prtry*>	[0..1]	Text		201
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		201
	StartDate <*StartDt*>	[0..1]	Date		201
	Description <*Desc*>	[0..1]	Text		202

13.1.11.1.2.1 CurrentName <CurNm>

Presence: [1..1]

Definition: Current name used.

CurrentName <CurNm> contains the following **IndividualPersonNameLong1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	NamePrefix <*NmPrfx*>	[0..1]			192
{Or	NamePrefix <*NmPrfx*>	[1..1]	CodeSet		192
Or}	ExtendedNamePrefix <*XtndedNmPrfx*>	[1..1]	Text		192
	Surname <*Srnm*>	[1..1]	Text		193
	GivenName <*GvnNm*>	[0..1]	Text		193
	MiddleName <*MddlNm*>	[0..1]	Text		193
	Initials <*Initls*>	[0..1]	Text		193
	NameSuffix <*NmSfx*>	[0..1]	Text		193
	Name <*Nm*>	[0..1]	Text		193
	StartDate <*StartDt*>	[0..1]	Date		193
	EndDate <*EndDt*>	[0..1]	Date		193

13.1.11.1.2.1.1 NamePrefix <NmPrfx>

Presence: [0..1]

Definition: Prefix, as a title before a person's name.

NamePrefix <NmPrfx> contains one of the following **NamePrefix2Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	NamePrefix <*NmPrfx*>	[1..1]	CodeSet		192
Or}	ExtendedNamePrefix <*XtndedNmPrfx*>	[1..1]	Text		192

13.1.11.1.2.1.1.1 NamePrefix <NmPrfx>

Presence: [1..1]

Definition: Prefix for name.

Datatype: "NamePrefix1Code" on page 370

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MIST	Mister	Title of the person is Mister or Mr.
MISS	Miss	Title of the person is Miss.
MADM	Madam	Title of the person is Madam.

13.1.11.1.2.1.1.2 ExtendedNamePrefix <XtndedNmPrfx>

Presence: [1..1]

Definition: Name prefix that is extended.

Datatype: "Extended350Code" on page 379

13.1.11.1.2.1.2 Surname <Srnm>

Presence: [1..1]

Definition: Surname is a name added to a given name and is part of a personal name. In many cases, a surname is a family name.

Datatype: "Max35Text" on page 381

13.1.11.1.2.1.3 GivenName <GvnNm>

Presence: [0..1]

Definition: Name given at birth.

Datatype: "Max35Text" on page 381

13.1.11.1.2.1.4 MiddleName <MddlNm>

Presence: [0..1]

Definition: Second name of a person.

Datatype: "Max35Text" on page 381

13.1.11.1.2.1.5 Initials <Initls>

Presence: [0..1]

Definition: Initial prefix for name.

Datatype: "Max6Text" on page 381

13.1.11.1.2.1.6 NameSuffix <NmSfx>

Presence: [0..1]

Definition: Suffix for name.

Datatype: "Max350Text" on page 380

13.1.11.1.2.1.7 Name <Nm>

Presence: [0..1]

Definition: Full legal name.

Datatype: "Max350Text" on page 380

13.1.11.1.2.1.8 StartDate <StartDt>

Presence: [0..1]

Definition: Date that the name was assigned.

Datatype: "ISODate" on page 376

13.1.11.1.2.1.9 EndDate <EndDt>

Presence: [0..1]

Definition: Date that name changed.

Datatype: "ISODate" on page 376

13.1.11.1.2.2 PreviousName <PrvsNm>

Presence: [0..*]

Definition: Previous name used.

PreviousName <PrvsNm> contains the following **IndividualPersonNameLong1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	NamePrefix <*NmPrfx*>	[0..1]			194
{Or	NamePrefix <*NmPrfx*>	[1..1]	CodeSet		194
Or}	ExtendedNamePrefix <*XtndedNmPrfx*>	[1..1]	Text		195
	Surname <*Srnm*>	[1..1]	Text		195
	GivenName <*GvnNm*>	[0..1]	Text		195
	MiddleName <*MddlNm*>	[0..1]	Text		195
	Initials <*Initls*>	[0..1]	Text		195
	NameSuffix <*NmSfx*>	[0..1]	Text		195
	Name <*Nm*>	[0..1]	Text		195
	StartDate <*StartDt*>	[0..1]	Date		195
	EndDate <*EndDt*>	[0..1]	Date		195

13.1.11.1.2.2.1 NamePrefix <NmPrfx>

Presence: [0..1]

Definition: Prefix, as a title before a person's name.

NamePrefix <NmPrfx> contains one of the following **NamePrefix2Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	NamePrefix <*NmPrfx*>	[1..1]	CodeSet		194
Or}	ExtendedNamePrefix <*XtndedNmPrfx*>	[1..1]	Text		195

13.1.11.1.2.2.1.1 NamePrefix <NmPrfx>

Presence: [1..1]

Definition: Prefix for name.

Datatype: "NamePrefix1Code" on page 370

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MIST	Mister	Title of the person is Mister or Mr.
MISS	Miss	Title of the person is Miss.
MADM	Madam	Title of the person is Madam.

13.1.11.1.2.2.1.2 ExtendedNamePrefix <XtndedNmPrfx>

Presence: [1..1]

Definition: Name prefix that is extended.

Datatype: "Extended350Code" on page 379

13.1.11.1.2.2.2 Surname <Srnm>

Presence: [1..1]

Definition: Surname is a name added to a given name and is part of a personal name. In many cases, a surname is a family name.

Datatype: "Max35Text" on page 381

13.1.11.1.2.2.3 GivenName <GvnNm>

Presence: [0..1]

Definition: Name given at birth.

Datatype: "Max35Text" on page 381

13.1.11.1.2.2.4 MiddleName <MddlNm>

Presence: [0..1]

Definition: Second name of a person.

Datatype: "Max35Text" on page 381

13.1.11.1.2.2.5 Initials <Initls>

Presence: [0..1]

Definition: Initial prefix for name.

Datatype: "Max6Text" on page 381

13.1.11.1.2.2.6 NameSuffix <NmSfx>

Presence: [0..1]

Definition: Suffix for name.

Datatype: "Max350Text" on page 380

13.1.11.1.2.2.7 Name <Nm>

Presence: [0..1]

Definition: Full legal name.

Datatype: "Max350Text" on page 380

13.1.11.1.2.2.8 StartDate <StartDt>

Presence: [0..1]

Definition: Date that the name was assigned.

Datatype: "ISODate" on page 376

13.1.11.1.2.2.9 EndDate <EndDt>

Presence: [0..1]

Definition: Date that name changed.

Datatype: "ISODate" on page 376

13.1.11.1.2.3 Gender <Gndr>

Presence: [0..1]

Definition: Specifies the gender of the person.

Datatype: "Gender1Code" on page 369

CodeName	Name	Definition
FEMA	Female	Individual is a female.
MALE	Male	Individual is a male.

13.1.11.1.2.4 Language <Lang>

Presence: [0..1]

Definition: Language in which a person communicates.

Impacted by: C16 "ValidationByTable"

Datatype: "LanguageCode" on page 369

Constraints

- **ValidationByTable**

  Must be a valid terrestrial language.

13.1.11.1.2.5 BirthDate <BirthDt>

Presence: [0..1]

Definition: Date on which a person is born.

Datatype: "ISODate" on page 376

13.1.11.1.2.6 CountryOfBirth <CtryOfBirth>

Presence: [0..1]

Definition: Country where a person was born.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.11.1.2.7 ProvinceOfBirth <PrvcOfBirth>

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "Max35Text" on page 381

13.1.11.1.2.8 CityOfBirth <CityOfBirth>

Presence: [0..1]

Definition: City where a person was born.

Datatype: "Max35Text" on page 381

13.1.11.1.2.9 TaxationCountry <TaxtnCtry>

Presence: [0..1]

Definition: Country of taxation of an individual person.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.11.1.2.10 CountryAndResidentialStatus <CtryAndResdtlSts>

Presence: [0..1]

Definition: Country and residential status of an individual, for example, non-pernament resident.

CountryAndResidentialStatus <CtryAndResdtlSts> contains the following elements (see "CountryAndResidentialStatusType1" on page 262 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Country <*Ctry*>	[1..1]	CodeSet	C18	262
	ResidentialStatus <*ResdtlSts*>	[1..1]	CodeSet		263

13.1.11.1.2.11 SocialSecurityNumber <SclSctyNb>

Presence: [0..1]

Definition: Government identification for its citizens.

Datatype: "Max35Text" on page 381

13.1.11.1.2.12 PostalAddress <PstlAdr>

Presence: [0..*]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see "PostalAddress6" on page 267 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.11.1.2.13 CitizenshipInformation <CtznshInf>

Presence: [0..*]

Definition: Information about a citizen.

CitizenshipInformation <CtznshInf> contains the following **CitizenshipInformation1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Nationality <*Ntlty*>	[1..1]	CodeSet	C17	198
	MinorIndicator <*MnrInd*>	[0..1]	Indicator		198
	StartDate <*StartDt*>	[0..1]	Date		199
	EndDate <*EndDt*>	[0..1]	Date		199

13.1.11.1.2.13.1 Nationality <Ntlty>

Presence: [1..1]

Definition: Specifies the country where a person was born or is legally accepted as belonging to the country.

Impacted by: C17 "ValidationByTable"

Datatype: "NationalityCode" on page 370

Constraints

- **ValidationByTable**

  Must be a valid nationality.

13.1.11.1.2.13.2 MinorIndicator <MnrInd>

Presence: [0..1]

Definition: Indicates whether the person is a legal minor. It may depend on the nationality, the domicile country or the transaction in which the person is involved.

Datatype: One of the following values must be used (see "YesNoIndicator" on page 378):

- *Meaning When True:* Yes
- *Meaning When False:* No

13.1.11.1.2.13.3 StartDate <StartDt>

Presence: [0..1]

Definition: Date of the commencement of citizenship.

Datatype: "ISODate" on page 376

13.1.11.1.2.13.4 EndDate <EndDt>

Presence: [0..1]

Definition: Date of the end of citizenship.

Datatype: "ISODate" on page 376

13.1.11.1.2.14 PrimaryCommunicationAddress <PmryComAdr>

Presence: [0..1]

Definition: Address for the primary contact.

PrimaryCommunicationAddress <PmryComAdr> contains the following elements (see "CommunicationAddress3" on page 266 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Email <*Email*>	[0..1]	Text		266
	Phone <*Phne*>	[0..1]	Text		266
	Mobile <*Mob*>	[0..1]	Text		266
	FaxNumber <*FaxNb*>	[0..1]	Text		266
	TelexAddress <*TlxAdr*>	[0..1]	Text		266
	URLAddress <*URLAdr*>	[0..1]	Text		267

13.1.11.1.2.15 SecondaryCommunicationAddress <ScndryComAdr>

Presence: [0..1]

Definition: Communication device number or electronic address used for communication to an alternate address.

SecondaryCommunicationAddress <ScndryComAdr> contains the following elements (see "CommunicationAddress3" on page 266 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Email <*Email*>	[0..1]	Text		266
	Phone <*Phne*>	[0..1]	Text		266
	Mobile <*Mob*>	[0..1]	Text		266
	FaxNumber <*FaxNb*>	[0..1]	Text		266
	TelexAddress <*TlxAdr*>	[0..1]	Text		266
	URLAddress <*URLAdr*>	[0..1]	Text		267

13.1.11.1.2.16 OtherIdentification <OthrId>

Presence: [0..*]

Definition: Other type of identification.

OtherIdentification <OthrId> contains the following elements (see "GenericIdentification44" on page 170 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		171
	Type <*Tp*>	[1..1]			171
{Or	Code <*Cd*>	[1..1]	CodeSet		171
Or}	Proprietary <*Prtry*>	[1..1]	±		172
	Issuer <*Issr*>	[0..1]	Text		172
	IssueDate <*IsseDt*>	[0..1]	Date		172
	ExpiryDate <*XpryDt*>	[0..1]	Date		172

13.1.11.1.2.17 OtherDetails <OthrDtls>

Presence: [0..*]

Definition: Additonal information required for the account switch.

OtherDetails <OthrDtls> contains the following **TransferInstruction1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		201
	Code <*Cd*>	[1..1]	Text		201
	Proprietary <*Prtry*>	[0..1]	Text		201
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		201
	StartDate <*StartDt*>	[0..1]	Date		201
	Description <*Desc*>	[0..1]	Text		202

13.1.11.1.2.17.1 TransferIndicator <TrfInd>

Presence: [0..1]

Definition: Indicates whether a payment arrangement is transferable.

Usage: Default value for TransferIndicator is false.

Datatype: One of the following values must be used (see "YesNoIndicator" on page 378):

- *Meaning When True:* Yes
- *Meaning When False:* No

13.1.11.1.2.17.2 Code <Cd>

Presence: [1..1]

Definition: Specifies an additional parameter to be applied to the requested transaction schedule.

Datatype: "Max35Text" on page 381

13.1.11.1.2.17.3 Proprietary <Prtry>

Presence: [0..1]

Definition: Specifies an additional parameter to be applied to the transaction schedule in a proprietary format.

Datatype: "Max256Text" on page 380

13.1.11.1.2.17.4 StartDateTime <StartDtTm>

Presence: [0..1]

Definition: The date and time at which the event specified by Code commences.

Datatype: "ISODateTime" on page 376

13.1.11.1.2.17.5 StartDate <StartDt>

Presence: [0..1]

Definition: The date on which the event specified by Code commences.

Datatype: "ISODate" on page 376

13.1.11.1.2.17.6 Description <Desc>

Presence: [0..1]

Definition: Additional switch parameters in a free text format.

Datatype: "Max350Text" on page 380

13.1.11.1.3 Organisation <Org>

Presence: [0..1]

Definition: Organised structure that is set up for a particular purpose, for example, a business, government body, department, charity, or financial institution.

Organisation <Org> contains the following **Organisation20** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FullLegalName <*FullLglNm*>	[1..1]	Text		202
	TradingName <*TradgNm*>	[0..1]	Text		203
	OrganisationLegalStatus <*OrgLglSts*>	[0..1]	CodeSet		203
	EstablishedDate <*EstblishdDt*>	[0..1]	Date		203
	RegistrationNumber <*RegnNb*>	[0..1]	Text		203
	RegistrationCountry <*RegnCtry*>	[0..1]	CodeSet	C18	203
	RegistrationDate <*RegnDt*>	[0..1]	Date		204
	TaxationIdentificationNumber <*TaxtnIdNb*>	[0..1]	Text		204
	TaxationCountry <*TaxtnCtry*>	[0..1]	CodeSet	C18	204
	CountryOfOperation <*CtryOfOpr*>	[0..1]	CodeSet	C18	204
	BoardResolutionIndicator <*BrdRsltnInd*>	[0..1]	Indicator		204
	BusinessAddress <*BizAdr*>	[0..1]	±		205
	OperationalAddress <*OprlAdr*>	[0..1]	±		205
	LegalAddress <*LglAdr*>	[0..1]	±		206
	RepresentativeOfficer <*RprtvOffcr*>	[0..*]	±		206
	TreasuryManager <*TrsrMgr*>	[0..1]	±		207
	MainMandateHolder <*MainMndtHldr*>	[0..*]	±		207
	Sender <*Sndr*>	[0..*]	±		208

13.1.11.1.3.1 FullLegalName <FullLglNm>

Presence: [1..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max350Text" on page 380

13.1.11.1.3.2 TradingName <TradgNm>

Presence: [0..1]

Definition: Name used by a business for commercial purposes, although its registered legal name, used for contracts and other formal situations, may be another.

Datatype: "Max350Text" on page 380

13.1.11.1.3.3 OrganisationLegalStatus <OrgLglSts>

Presence: [0..1]

Definition: Status of a legal entity.

Datatype: "OrganisationLegalStatus1Code" on page 370

CodeName	Name	Definition
CIOC	CharitableIncorporatedOrganisation	Charitable incorporated organisation (CIO)
CHAR	Charity	Charity
CICC	CommunityInterestCompany	Community Interest Company (CIC)
GENP	GeneralPartnership	General partnership
IAPS	IndustrialAndProvidentSociety	For example a co-operative, which does include Ltd. or charity.
LLPP	LimitedLiabilityPartnership	Limited liability partnership (LLP)
PCLG	PrivateCompanyLimitedByGuarantee	Private company limited by guarantee (Ltd.)
LIMP	LimitedPartnership	Limited partnership (LP)
PCLS	PrivateCompanyLimitedByShares	Private company limited by shares (Ltd.)
PCLC	PublicLimitedCompany	Public limited company (Plc.)
SOLE	SoleProprietorship	Sole proprietorship/Sole trader
UNLC	UnlimitedCompany	Unlimited company
UNLT	UnlimitedTrust	Unlimited trust

13.1.11.1.3.4 EstablishedDate <EstblishdDt>

Presence: [0..1]

Definition: Date of establishment or date of founding of an institution is the date on which that institution chooses to claim as its starting point.

Datatype: "ISODate" on page 376

13.1.11.1.3.5 RegistrationNumber <RegnNb>

Presence: [0..1]

Definition: Registration number for the organisation.

Datatype: "Max70Text" on page 382

13.1.11.1.3.6 RegistrationCountry <RegnCtry>

Presence: [0..1]

Definition: Country in which the organisation is registered.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.11.1.3.7 RegistrationDate <RegnDt>

Presence: [0..1]

Definition: Date a given organisation was officially registered.

Datatype: "ISODate" on page 376

13.1.11.1.3.8 TaxationIdentificationNumber <TaxtnIdNb>

Presence: [0..1]

Definition: Taxation unique reference number.

Datatype: "Max35Text" on page 381

13.1.11.1.3.9 TaxationCountry <TaxtnCtry>

Presence: [0..1]

Definition: Country of taxation of an individual person or an organisation.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.11.1.3.10 CountryOfOperation <CtryOfOpr>

Presence: [0..1]

Definition: Country in which the organisation has its business activity.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.11.1.3.11 BoardResolutionIndicator <BrdRsltnInd>

Presence: [0..1]

Definition: Indicates that the new bank holds a copy of a registered company's board resolution for the account switch.

Datatype: One of the following values must be used (see "TrueFalseIndicator" on page 378):

- *Meaning When True:* True
- *Meaning When False:* False

13.1.11.1.3.12 BusinessAddress <BizAdr>

Presence: [0..1]

Definition: Address where the business activity is taking place.

BusinessAddress <BizAdr> contains the following elements (see "PostalAddress6" on page 267 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.11.1.3.13 OperationalAddress <OprlAdr>

Presence: [0..1]

Definition: Address, for example, of a shared services centre.

OperationalAddress <OprlAdr> contains the following elements (see "PostalAddress6" on page 267 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.11.1.3.14 LegalAddress <LglAdr>

Presence: [0..1]

Definition: Address where the entity resides and is registered. More generically, it is the home address (residential address).

LegalAddress <LglAdr> contains the following elements (see "PostalAddress6" on page 267 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.11.1.3.15 RepresentativeOfficer <RprtvOffcr>

Presence: [0..*]

Definition: Person in the customer's organisation who can be contacted by the account servicer.

RepresentativeOfficer <RprtvOffcr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.11.1.3.16 TreasuryManager <TrsrMgr>

Presence: [0..1]

Definition: Person responsible of the treasury department within an organisation.

TreasuryManager <TrsrMgr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.11.1.3.17 MainMandateHolder <MainMndtHldr>

Presence: [0..*]

Definition: Person who will delegate some authority to other individuals (mandate holders) to perform some specific bank operations on the account.

MainMandateHolder <MainMndtHldr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.11.1.3.18 Sender <Sndr>

Presence: [0..*]

Definition: Sender of a message related to the life cyle of an account.

Sender <Sndr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.11.2 PartyIdentification125

Definition: Set of elements used to identify a person or an organisation.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.11.2.1 Name <Nm>

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 379

13.1.11.2.2 PostalAddress <PstlAdr>

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

PostalAddress <PstlAdr> contains the following elements (see "PostalAddress6" on page 267 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.11.2.3 Identification <Id>

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

Identification <Id> contains one of the following **Party34Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210

13.1.11.2.3.1 OrganisationIdentification <OrgId>

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

OrganisationIdentification <OrgId> contains the following elements (see "OrganisationIdentification8" on page 184 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AnyBIC <*AnyBIC*>	[0..1]	IdentifierSet	C3	184
	Other <*Othr*>	[0..*]			184
	Identification <*Id*>	[1..1]	Text		185
	SchemeName <*SchmeNm*>	[0..1]			185
{Or	Code <*Cd*>	[1..1]	CodeSet		185
Or}	Proprietary <*Prtry*>	[1..1]	Text		185
	Issuer <*Issr*>	[0..1]	Text		185

13.1.11.2.3.2 PrivateIdentification <PrvtId>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

PrivateIdentification <PrvtId> contains the following elements (see "PersonIdentification13" on page 263 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DateAndPlaceOfBirth <*DtAndPlcOfBirth*>	[0..1]			263
	BirthDate <*BirthDt*>	[1..1]	Date		264
	ProvinceOfBirth <*PrvcOfBirth*>	[0..1]	Text		264
	CityOfBirth <*CityOfBirth*>	[1..1]	Text		264
	CountryOfBirth <*CtryOfBirth*>	[1..1]	CodeSet	C18	264
	Other <*Othr*>	[0..*]			264
	Identification <*Id*>	[1..1]	Text		265
	SchemeName <*SchmeNm*>	[0..1]			265
{Or	Code <*Cd*>	[1..1]	CodeSet		265
Or}	Proprietary <*Prtry*>	[1..1]	Text		265
	Issuer <*Issr*>	[0..1]	Text		265

13.1.11.2.4 CountryOfResidence <CtryOfRes>

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.11.2.5 ContactDetails <CtctDtls>

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

ContactDetails <CtctDtls> contains the following elements (see "ContactDetails2" on page 176 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	NamePrefix <*NmPrfx*>	[0..1]	CodeSet		176
	Name <*Nm*>	[0..1]	Text		177
	PhoneNumber <*PhneNb*>	[0..1]	Text		177
	MobileNumber <*MobNb*>	[0..1]	Text		177
	FaxNumber <*FaxNb*>	[0..1]	Text		177
	EmailAddress <*EmailAdr*>	[0..1]	Text		177
	Other <*Othr*>	[0..1]	Text		177

13.1.12 Payment

13.1.12.1 InstructionForCreditorAgent1

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the creditor's agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the creditor's agent.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Code <*Cd*>	[0..1]	CodeSet		212
	InstructionInformation <*InstrInf*>	[0..1]	Text		213

13.1.12.1.1 Code <Cd>

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor's agent.

Datatype: "Instruction3Code" on page 369

CodeName	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/ claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/ claimant by the most efficient means of telecommunication.

13.1.12.1.2 InstructionInformation <InstrInf>

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the creditor's agent that is bilaterally agreed or specific to a user community.

Datatype: "Max140Text" on page 379

13.1.12.2 PaymentInstruction24

Definition: Characteristics that apply to the debit side of the payment transactions included in the credit transfer initiation.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PaymentInformationIdentification <*PmtInfId*>	[1..1]	Text		220
	PaymentMethod <*PmtMtd*>	[1..1]	CodeSet		220
	BatchBooking <*BtchBookg*>	[0..1]	Indicator		220
	NumberOfTransactions <*NbOfTxs*>	[0..1]	Text		221
	ControlSum <*CtrlSum*>	[0..1]	Quantity		221
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		221
	RequestedExecutionDate <*ReqdExctnDt*>	[1..1]	Date		221
	PoolingAdjustmentDate <*PoolgAdjstmntDt*>	[0..1]	Date		222
	Debtor <*Dbtr*>	[1..1]	±		222
	DebtorAccount <*DbtrAcct*>	[1..1]	±		222
	DebtorAgent <*DbtrAgt*>	[1..1]	±		222
	DebtorAgentAccount <*DbtrAgtAcct*>	[0..1]	±		223
	InstructionForDebtorAgent <*InstrForDbtrAgt*>	[0..1]	Text		223
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		223
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		224
	ChargesAccount <*ChrgsAcct*>	[0..1]	±		224
	ChargesAccountAgent <*ChrgsAcctAgt*>	[0..1]	±		225
	CreditTransferTransactionInformation <*CdtTrfTxInf*>	[1..*]		C22, C23, C24, C28, C30	225
	PaymentIdentification <*PmtId*>	[1..1]	±		229
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		230
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		230
	Amount <*Amt*>	[1..1]	Amount	C1, C19	230
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		231
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C16	231
	Frequency <*Frqcy*>	[0..1]			232
	Sequence <*Seq*>	[0..1]	Text		233
	StartDate <*StartDt*>	[1..1]	Date		233
	EndPointChoice <*EndPtChc*>	[1..1]			233
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		233
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		233

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		234
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		234
	TransferInstruction <*TrfInstr*>	[0..1]			234
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		234
	Code <*Cd*>	[1..1]	Text		235
	Proprietary <*Prtry*>	[0..1]	Text		235
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		235
	StartDate <*StartDt*>	[0..1]	Date		235
	Description <*Desc*>	[0..1]	Text		235
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		235
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		236
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		236
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		236
	CreditorAgent <*CdtrAgt*>	[1..1]	±		237
	Creditor <*Cdtr*>	[0..1]	±		237
	CreditorAccount <*CdtrAcct*>	[0..1]	±		237
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		238
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		238
	Purpose <*Purp*>	[0..1]			238
{Or	Code <*Cd*>	[1..1]	CodeSet		239
Or}	Proprietary <*Prtry*>	[1..1]	Text		239
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		239
	Tax <*Tax*>	[0..1]			240
	Creditor <*Cdtr*>	[0..1]			242
	TaxIdentification <*TaxId*>	[0..1]	Text		242
	RegistrationIdentification <*RegnId*>	[0..1]	Text		242
	TaxType <*TaxTp*>	[0..1]	Text		242
	Debtor <*Dbtr*>	[0..1]			243
	TaxIdentification <*TaxId*>	[0..1]	Text		243
	RegistrationIdentification <*RegnId*>	[0..1]	Text		243
	TaxType <*TaxTp*>	[0..1]	Text		243

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Authorisation <*Authstn*>	[0..1]			243
	Title <*Titl*>	[0..1]	Text		244
	Name <*Nm*>	[0..1]	Text		244
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		244
	ReferenceNumber <*RefNb*>	[0..1]	Text		244
	Method <*Mtd*>	[0..1]	Text		244
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	244
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	245
	Date <*Dt*>	[0..1]	Date		245
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		245
	Record <*Rcrd*>	[0..*]			245
	Type <*Tp*>	[0..1]	Text		246
	Category <*Ctgy*>	[0..1]	Text		246
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		247
	DebtorStatus <*DbtrSts*>	[0..1]	Text		247
	CertificateIdentification <*CertId*>	[0..1]	Text		247
	FormsCode <*FrmsCd*>	[0..1]	Text		247
	Period <*Prd*>	[0..1]			247
	Year <*Yr*>	[0..1]	Date		247
	Type <*Tp*>	[0..1]	CodeSet		248
	FromToDate <*FrToDt*>	[0..1]			248
	FromDate <*FrDt*>	[1..1]	Date		249
	ToDate <*ToDt*>	[1..1]	Date		249
	TaxAmount <*TaxAmt*>	[0..1]			249
	Rate <*Rate*>	[0..1]	Rate		249
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	250
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	250
	Details <*Dtls*>	[0..*]			250
	Period <*Prd*>	[0..1]			251
	Year <*Yr*>	[0..1]	Date		251
	Type <*Tp*>	[0..1]	CodeSet		251

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FromToDate <*FrToDt*>	[0..1]			252
	FromDate <*FrDt*>	[1..1]	Date		252
	ToDate <*ToDt*>	[1..1]	Date		253
	Amount <*Amt*>	[1..1]	Amount	C2, C20	253
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		253
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		253
	RemittanceInformation <*RmtInf*>	[0..1]			254
	Unstructured <*Ustrd*>	[0..*]	Text		254
	Structured <*Strd*>	[0..*]			254
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			255
	Type <*Tp*>	[0..1]			255
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			256
{Or	Code <*Cd*>	[1..1]	CodeSet		256
Or}	Proprietary <*Prtry*>	[1..1]	Text		257
	Issuer <*Issr*>	[0..1]	Text		257
	Number <*Nb*>	[0..1]	Text		257
	RelatedDate <*RltdDt*>	[0..1]	Date		257
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		257
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		258
	Invoicer <*Invcr*>	[0..1]	±		259
	Invoicee <*Invcee*>	[0..1]	±		259
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		260

Constraints

- **ChargeBearerRule**

  If ChargeBearer is present, then CreditTransferTransactionInformation/ChargeBearer is not allowed.

  If CreditTransferTransactionInformation/ChargeBearer is present, then ChargeBearer is not allowed.

  CreditTransferTransactionInformation/ChargeBearer and ChargeBearer may both be absent.

```
Following Must be True
    /ChargeBearer Must be absent
 Or    /CreditTransferTransactionInformation[*]/ChargeBearer Must be absent
```

- **ChargesAccountAgentRule**

  If ChargesAccountAgent is present, then it must contain a branch of the DebtorAgent. It must not contain a completely different agent.

```
On Condition
    /ChargesAccountAgent is present
Following Must be True
    /ChargesAccountAgent/FinancialInstitutionIdentification/Name Must be equal to
value 'Branch of DebtorAgent'
```

- **ChargesAccountRule**

  If ChargesAccountAgent is present, then ChargesAccount must be present.

```
On Condition
    /ChargesAccountAgent is present
Following Must be True
    /ChargesAccount Must be present
```

- **ChequeAndCreditorAccountRule**

  If PaymentMethod is CHK (Cheque), then CreditTransferTransactionInformation/CreditorAccount is not allowed.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAccount Must be absent
```

- **ChequeDeliveryAndCreditorAgentRule**

  If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is present and is equal to MLFA (MailToFinalAgent), CRFA (CourierToFinalAgent), RGFA (RegisteredMailToFinalAgent) or PUFA (PickUpByFinalAgent), then CreditTransferTransactionInformation/CreditorAgent must be present.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod
is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is within DataType <<Code>> ChequeDelivery2Code
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAgent Must be present
```

- **ChequeDeliveryAndNoCreditorAgentRule**

  If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is present and different from MLFA (MailToFinalAgent), CRFA (CourierToFinalAgent), RGFA (RegisteredMailToFinalAgent) or PUFA (PickUpByFinalAgent), then CreditTransferTransactionInformation/CreditorAgent is not allowed.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod
is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod/
Code is not within DataType <<Code>> ChequeDelivery2Code
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAgent Must be absent
```

- **ChequeFromGuideline**

  CreditTransferTransactionInformation/ChequeInstruction/ChequeFrom may only be present if different from CreditTransferTransactionInformation/UltimateDebtor or Debtor.

- **ChequeInstructionDeliverToCreditorAgentGuideline**

  If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRFA (CourierToFinalAgent), MLFA (MailToFinalAgent), PUFA (PickUpByFinalAgent) or RGFA (RegisteredMailToFinalAgent), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

- **ChequeInstructionDeliverToCreditorGuideline**

  If PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRCD (CourierToCreditor), MLCD (MailToCreditor), PUCD (PickUpByCreditor) or RGCD (RegisteredMailToCreditor), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

- **ChequeInstructionDeliverToDebtorGuideline**

  If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and if CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is CRDB (CourierToDebtor), MLDB (MailToDebtor), PUDB (PickUpByDebtor) or RGDB (RegisteredMailToDebtor), then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from Debtor.

- **ChequeInstructionRule**

  If PaymentMethod is different from CHK (Cheque), then CreditTransferTransactionInformation/ChequeInstruction is not allowed.

```
On Condition
    /PaymentMethod is present
 And    /PaymentMethod is different from value 'Cheque'
Following Must be True
    /CreditTransferTransactionInformation[*]/ChequeInstruction Must be absent
```

- **ChequeNoDeliveryAndNoCreditorAgentRule**

  If PaymentMethod is CHK (Cheque) and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is not present, then CreditTransferTransactionInformation/CreditorAgent is not allowed.

```
On Condition
    /PaymentMethod is equal to value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction is present
 And    /CreditTransferTransactionInformation[*]/ChequeInstruction/DeliveryMethod
is absent
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAgent Must be absent
```

- **NonChequePaymentMethodRule**

  If PaymentMethod is different from CHK (Cheque) and CreditTransferTransactionInformation/Creditor is not present, then CreditTransferTransactionInformation/CreditorAccount must be present.

```
On Condition
    /PaymentMethod is different from value 'Cheque'
 And    /CreditTransferTransactionInformation[*]/Creditor is absent
Following Must be True
    /CreditTransferTransactionInformation[*]/CreditorAccount Must be present
```

- **PaymentTypeInformationRule**

  If PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed.

```
On Condition
    /PaymentTypeInformation is present
```

```
Following Must be True
    /CreditTransferTransactionInformation[*]/PaymentTypeInformation Must be absent
```

- **UltimateDebtorGuideline**

  UltimateDebtor may only be present if different from Debtor.

- **UltimateDebtorRule**

  If UltimateDebtor is present, then CreditTransferTransactionInformation/UltimateDebtor is not allowed.

  If CreditTransferTransactionInformation/UltimateDebtor is present, then UltimateDebtor is not allowed.

  CreditTransferTransactionInformation/UltimateDebtor and UltimateDebtor may both be absent.

```
Following Must be True
    /UltimateDebtor Must be absent
 Or    /CreditTransferTransactionInformation[*]/UltimateDebtor Must be absent
```

13.1.12.2.1 PaymentInformationIdentification <PmtInfId>

Presence: [1..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

Datatype: "Max35Text" on page 381

13.1.12.2.2 PaymentMethod <PmtMtd>

Presence: [1..1]

Definition: Specifies the means of payment that will be used to move the amount of money.

Datatype: "PaymentMethod3Code" on page 371

CodeName	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.

13.1.12.2.3 BatchBooking <BtchBookg>

Presence: [0..1]

Definition: Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.

Usage:

-Batch booking is used to request and not order a possible batch booking.

-Default value for BatchBookingIndicator is false.

Datatype: One of the following values must be used (see "BatchBookingIndicator" on page 377):

- *Meaning When True:* Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.
- *Meaning When False:* Identifies that a single entry for each of the transactions in the batch or message is requested.

13.1.12.2.4 NumberOfTransactions <NbOfTxs>

Presence: [0..1]

Definition: Number of individual transactions contained in the payment information group.

Datatype: "Max15NumericText" on page 379

13.1.12.2.5 ControlSum <CtrlSum>

Presence: [0..1]

Definition: Total of all individual amounts included in the group, irrespective of currencies.

Datatype: "DecimalNumber" on page 378

13.1.12.2.6 PaymentTypeInformation <PmtTpInf>

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

PaymentTypeInformation <PmtTpInf> contains the following elements (see "PaymentTypeInformation19" on page 260 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		260
	ServiceLevel <*SvcLvl*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		261
	LocalInstrument <*LclInstrm*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		262
	CategoryPurpose <*CtgyPurp*>	[0..1]			262
{Or	Code <*Cd*>	[1..1]	CodeSet		262
Or}	Proprietary <*Prtry*>	[1..1]	Text		262

13.1.12.2.7 RequestedExecutionDate <ReqdExctnDt>

Presence: [1..1]

Definition: Date at which the initiating party requests the clearing agent to process the payment.

Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.

Datatype: "ISODate" on page 376

13.1.12.2.8 PoolingAdjustmentDate <PoolgAdjstmntDt>

Presence: [0..1]

Definition: Date used for the correction of the value date of a cash pool movement that has been posted with a different value date.

Datatype: "ISODate" on page 376

13.1.12.2.9 Debtor <Dbtr>

Presence: [1..1]

Definition: Party that owes an amount of money to the (ultimate) creditor.

Debtor <Dbtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.12.2.10 DebtorAccount <DbtrAcct>

Presence: [1..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

DebtorAccount <DbtrAcct> contains the following elements (see "CashAccount24" on page 146 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		146
	Type <*Tp*>	[0..1]	±		146
	Currency <*Ccy*>	[0..1]	CodeSet	C2	147
	Name <*Nm*>	[0..1]	Text		147

13.1.12.2.11 DebtorAgent <DbtrAgt>

Presence: [1..1]

Definition: Financial institution servicing an account for the debtor.

DebtorAgent <DbtrAgt> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.12.2.12 DebtorAgentAccount <DbtrAgtAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

DebtorAgentAccount <DbtrAgtAcct> contains the following elements (see "CashAccount24" on page 146 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		146
	Type <*Tp*>	[0..1]	±		146
	Currency <*Ccy*>	[0..1]	CodeSet	C2	147
	Name <*Nm*>	[0..1]	Text		147

13.1.12.2.13 InstructionForDebtorAgent <InstrForDbtrAgt>

Presence: [0..1]

Definition: Further information related to the processing of the payment instruction, that may need to be acted upon by the debtor agent, depending on agreement between debtor and the debtor agent.

Usage: when present, then the instructions for the debtor agent apply for all credit transfer transaction information occurrences, present in the payment information.

Datatype: "Max140Text" on page 379

13.1.12.2.14 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

UltimateDebtor <UltmtDbtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.12.2.15 ChargeBearer <ChrgBr>

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: "ChargeBearerType1Code" on page 362

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

13.1.12.2.16 ChargesAccount <ChrgsAcct>

Presence: [0..1]

Definition: Account used to process charges associated with a transaction.

Usage: Charges account should be used when charges have to be booked to an account different from the account identified in debtor's account.

ChargesAccount <ChrgsAcct> contains the following elements (see "CashAccount24" on page 146 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		146
	Type <*Tp*>	[0..1]	±		146
	Currency <*Ccy*>	[0..1]	CodeSet	C2	147
	Name <*Nm*>	[0..1]	Text		147

13.1.12.2.17 ChargesAccountAgent <ChrgsAcctAgt>

Presence: [0..1]

Definition: Agent that services a charges account.

Usage: Charges account agent should only be used when the charges account agent is different from the debtor agent.

ChargesAccountAgent <ChrgsAcctAgt> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.12.2.18 CreditTransferTransactionInformation <CdtTrfTxInf>

Presence: [1..*]

Definition: Provides information on the individual transaction(s) included in the message.

Impacted by: C22 "InstructionForCreditorAgentRule", C23 "IntermediaryAgent2Rule", C24 "IntermediaryAgent3Rule", C28 "UltimateCreditorGuideline", C30 "UltimateDebtorGuideline"

CreditTransferTransactionInformation <CdtTrfTxInf> contains the following **CreditTransferTransaction27** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PaymentIdentification <*PmtId*>	[1..1]	±		229
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		230
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		230
	Amount <*Amt*>	[1..1]	Amount	C1, C19	230
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		231
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C16	231
	Frequency <*Frqcy*>	[0..1]			232
	Sequence <*Seq*>	[0..1]	Text		233
	StartDate <*StartDt*>	[1..1]	Date		233
	EndPointChoice <*EndPtChc*>	[1..1]			233
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		233
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		233
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		234
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		234
	TransferInstruction <*TrfInstr*>	[0..1]			234
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		234
	Code <*Cd*>	[1..1]	Text		235
	Proprietary <*Prtry*>	[0..1]	Text		235
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		235
	StartDate <*StartDt*>	[0..1]	Date		235
	Description <*Desc*>	[0..1]	Text		235
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		235
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		236
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		236
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		236
	CreditorAgent <*CdtrAgt*>	[1..1]	±		237
	Creditor <*Cdtr*>	[0..1]	±		237
	CreditorAccount <*CdtrAcct*>	[0..1]	±		237
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		238
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		238

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Purpose <*Purp*>	[0..1]			238
{Or	Code <*Cd*>	[1..1]	CodeSet		239
Or}	Proprietary <*Prtry*>	[1..1]	Text		239
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		239
	Tax <*Tax*>	[0..1]			240
	Creditor <*Cdtr*>	[0..1]			242
	TaxIdentification <*TaxId*>	[0..1]	Text		242
	RegistrationIdentification <*RegnId*>	[0..1]	Text		242
	TaxType <*TaxTp*>	[0..1]	Text		242
	Debtor <*Dbtr*>	[0..1]			243
	TaxIdentification <*TaxId*>	[0..1]	Text		243
	RegistrationIdentification <*RegnId*>	[0..1]	Text		243
	TaxType <*TaxTp*>	[0..1]	Text		243
	Authorisation <*Authstn*>	[0..1]			243
	Title <*Titl*>	[0..1]	Text		244
	Name <*Nm*>	[0..1]	Text		244
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		244
	ReferenceNumber <*RefNb*>	[0..1]	Text		244
	Method <*Mtd*>	[0..1]	Text		244
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	244
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	245
	Date <*Dt*>	[0..1]	Date		245
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		245
	Record <*Rcrd*>	[0..*]			245
	Type <*Tp*>	[0..1]	Text		246
	Category <*Ctgy*>	[0..1]	Text		246
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		247
	DebtorStatus <*DbtrSts*>	[0..1]	Text		247
	CertificateIdentification <*CertId*>	[0..1]	Text		247
	FormsCode <*FrmsCd*>	[0..1]	Text		247
	Period <*Prd*>	[0..1]			247

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		247
	Type <*Tp*>	[0..1]	CodeSet		248
	FromToDate <*FrToDt*>	[0..1]			248
	FromDate <*FrDt*>	[1..1]	Date		249
	ToDate <*ToDt*>	[1..1]	Date		249
	TaxAmount <*TaxAmt*>	[0..1]			249
	Rate <*Rate*>	[0..1]	Rate		249
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	250
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	250
	Details <*Dtls*>	[0..*]			250
	Period <*Prd*>	[0..1]			251
	Year <*Yr*>	[0..1]	Date		251
	Type <*Tp*>	[0..1]	CodeSet		251
	FromToDate <*FrToDt*>	[0..1]			252
	FromDate <*FrDt*>	[1..1]	Date		252
	ToDate <*ToDt*>	[1..1]	Date		253
	Amount <*Amt*>	[1..1]	Amount	C2, C20	253
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		253
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		253
	RemittanceInformation <*RmtInf*>	[0..1]			254
	Unstructured <*Ustrd*>	[0..*]	Text		254
	Structured <*Strd*>	[0..*]			254
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			255
	Type <*Tp*>	[0..1]			255
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			256
{Or	Code <*Cd*>	[1..1]	CodeSet		256
Or}	Proprietary <*Prtry*>	[1..1]	Text		257
	Issuer <*Issr*>	[0..1]	Text		257
	Number <*Nb*>	[0..1]	Text		257
	RelatedDate <*RltdDt*>	[0..1]	Date		257
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		257

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		258
	Invoicer <*Invcr*>	[0..1]	±		259
	Invoicee <*Invcee*>	[0..1]	±		259
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		260

Constraints

- **InstructionForCreditorAgentRule**

  If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

```
On Condition
    /CreditorAccount is present
 And    /InstructionForCreditorAgent[1] is present
Following Must be True
    /InstructionForCreditorAgent[*]/Code Must be within DataType <<Code>>
PartialInstruction3Code
```

- **IntermediaryAgent2Rule**

  If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

```
On Condition
    /IntermediaryAgent2 is present
Following Must be True
    /IntermediaryAgent1 Must be present
```

- **IntermediaryAgent3Rule**

  If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

```
On Condition
    /IntermediaryAgent3 is present
Following Must be True
    /IntermediaryAgent2 Must be present
```

- **UltimateCreditorGuideline**

  UltimateCreditor may only be present if different from Creditor.

- **UltimateDebtorGuideline**

  UltimateDebtor may only be present if different from Debtor.

13.1.12.2.18.1 PaymentIdentification <PmtId>

Presence: [1..1]

Definition: Set of elements used to reference a payment instruction.

PaymentIdentification <PmtId> contains the following elements (see "PaymentIdentification1" on page 173 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionIdentification <*InstrId*>	[0..1]	Text		173
	EndToEndIdentification <*EndToEndId*>	[1..1]	Text		173

13.1.12.2.18.2 PaymentTypeInformation <PmtTpInf>

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

PaymentTypeInformation <PmtTpInf> contains the following elements (see "PaymentTypeInformation19" on page 260 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		260
	ServiceLevel <*SvcLvl*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		261
	LocalInstrument <*LclInstrm*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		262
	CategoryPurpose <*CtgyPurp*>	[0..1]			262
{Or	Code <*Cd*>	[1..1]	CodeSet		262
Or}	Proprietary <*Prtry*>	[1..1]	Text		262

13.1.12.2.18.3 TaxRateMarker <TaxRateMrkr>

Presence: [0..1]

Definition: Specifies the rate of tax levied.

Datatype: "TaxRateMarker1Code" on page 374

CodeName	Name	Definition
ALPR	AmountQuotedLessLifeAssurance	Specifies the amount quoted less life assurance premium rate income tax.
ALIT	AmountQuotedLessStandardRate	Specifies the amount quoted less standard rate income tax.
GRSS	GrossAmount	Specifies an amount before the deduction of tax.

13.1.12.2.18.4 Amount <Amt>

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Impacted by: C1 "ActiveCurrency", C19 "CurrencyAmount"

Datatype: "ActiveCurrencyAndAmount" on page 359

Constraints

- **ActiveCurrency**

  The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.12.2.18.5 ChargeBearer <ChrgBr>

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: "ChargeBearerType1Code" on page 362

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

13.1.12.2.18.6 ChequeInstruction <ChqInstr>

Presence: [0..1]

Definition: Set of elements needed to issue a cheque.

Impacted by: C16 "ChequeMaturityDateRule"

ChequeInstruction <ChqInstr> contains the following elements (see "Cheque7" on page 153 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ChequeType <*ChqTp*>	[0..1]	CodeSet		154
	ChequeNumber <*ChqNb*>	[0..1]	Text		154
	ChequeFrom <*ChqFr*>	[0..1]			155
	Name <*Nm*>	[1..1]	Text		155
	Address <*Adr*>	[1..1]	±		155
	DeliveryMethod <*DlvryMtd*>	[0..1]			155
{Or	Code <*Cd*>	[1..1]	CodeSet		156
Or}	Proprietary <*Prtry*>	[1..1]	Text		156
	DeliverTo <*DlvrTo*>	[0..1]			156
	Name <*Nm*>	[1..1]	Text		157
	Address <*Adr*>	[1..1]	±		157
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		157
	ChequeMaturityDate <*ChqMtrtyDt*>	[0..1]	Date		158
	FormsCode <*FrmsCd*>	[0..1]	Text		158
	MemoField <*MemoFld*>	[0..2]	Text		158
	RegionalClearingZone <*RgnlClrZone*>	[0..1]	Text		158
	PrintLocation <*PrtLctn*>	[0..1]	Text		158
	Signature <*Sgntr*>	[0..5]	Text		158

Constraints

- **ChequeMaturityDateRule**

  If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

```
On Condition
    /ChequeType is present
 And    /ChequeType is within DataType <<Code>> ChequeType3Code
Following Must be True
    /ChequeMaturityDate Must be absent
```

13.1.12.2.18.7 Frequency <Frqcy>

Presence: [0..1]

Definition: The schedule for a credit payment arrangement.

Frequency <Frqcy> contains the following **Frequency1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Sequence <*Seq*>	[0..1]	Text		233
	StartDate <*StartDt*>	[1..1]	Date		233
	EndPointChoice <*EndPtChc*>	[1..1]			233
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		233
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		233
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		234
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		234

13.1.12.2.18.7.1 Sequence <Seq>

Presence: [0..1]

Definition: Technical identifier of a Credit Transfer as part of a series of Credit Transfers within a single Payment Instruction. Assists the transfer of complex variable future payment schedules, associated with a single act of customer consent, within a single Payment Instruction.

Datatype: "Max3NumericText" on page 381

13.1.12.2.18.7.2 StartDate <StartDt>

Presence: [1..1]

Definition: The date of the first payment to be made for this payment schedule.

Datatype: "ISODate" on page 376

13.1.12.2.18.7.3 EndPointChoice <EndPtChc>

Presence: [1..1]

Definition: Information about when the payment arrangement will end.

EndPointChoice <EndPtChc> contains one of the following **EndPoint1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		233
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		233

13.1.12.2.18.7.3.1 NumberOfPayments <NbOfPmts>

Presence: [0..1]

Definition: Number of the payments that will be made in completing this frequency sequence including any executed since the sequence start date.

Datatype: "Max35Text" on page 381

13.1.12.2.18.7.3.2 LastPaymentDate <LastPmtDt>

Presence: [0..1]

Definition: Final payment of the standing order due.

Datatype: "ISODate" on page 376

13.1.12.2.18.7.4 RequestedFrequencyPattern <ReqdFrqcyPttrn>

Presence: [0..1]

Definition: Payment schedule frequency pattern which indicates how frequently a payment is made.

RequestedFrequencyPattern <ReqdFrqcyPttrn> contains one of the following elements (see "Frequency37Choice" on page 175 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		175
Or}	Proprietary <*Prtry*>	[1..1]	Text		176

13.1.12.2.18.7.5 NonWorkingDayAdjustment <NonWorkgDayAdjstmnt>

Presence: [0..1]

Definition: Adjustment indicator for a non-working day to enable payment to be made on the next working day.

Datatype: "BusinessDayConvention1Code" on page 361

CodeName	Name	Definition
FWNG	Following	The date will be the first following day that is a business day.
PREC	Preceding	The date will be the first preceding day that is a business day.

13.1.12.2.18.8 TransferInstruction <TrfInstr>

Presence: [0..1]

Definition: Provides further information about the status of transferred scheduled payment(s).

TransferInstruction <TrfInstr> contains the following **TransferInstruction1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		234
	Code <*Cd*>	[1..1]	Text		235
	Proprietary <*Prtry*>	[0..1]	Text		235
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		235
	StartDate <*StartDt*>	[0..1]	Date		235
	Description <*Desc*>	[0..1]	Text		235

13.1.12.2.18.8.1 TransferIndicator <TrfInd>

Presence: [0..1]

Definition: Indicates whether a payment arrangement is transferable.

Usage: Default value for TransferIndicator is false.

Datatype: One of the following values must be used (see "YesNoIndicator" on page 378):

- *Meaning When True:* Yes
- *Meaning When False:* No

13.1.12.2.18.8.2 Code <Cd>

Presence: [1..1]

Definition: Specifies an additional parameter to be applied to the requested transaction schedule.

Datatype: "Max35Text" on page 381

13.1.12.2.18.8.3 Proprietary <Prtry>

Presence: [0..1]

Definition: Specifies an additional parameter to be applied to the transaction schedule in a proprietary format.

Datatype: "Max256Text" on page 380

13.1.12.2.18.8.4 StartDateTime <StartDtTm>

Presence: [0..1]

Definition: The date and time at which the event specified by Code commences.

Datatype: "ISODateTime" on page 376

13.1.12.2.18.8.5 StartDate <StartDt>

Presence: [0..1]

Definition: The date on which the event specified by Code commences.

Datatype: "ISODate" on page 376

13.1.12.2.18.8.6 Description <Desc>

Presence: [0..1]

Definition: Additional switch parameters in a free text format.

Datatype: "Max350Text" on page 380

13.1.12.2.18.9 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

UltimateDebtor <UltmtDbtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.12.2.18.10 IntermediaryAgent1 <IntrmyAgt1>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

IntermediaryAgent1 <IntrmyAgt1> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.12.2.18.11 IntermediaryAgent2 <IntrmyAgt2>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

IntermediaryAgent2 <IntrmyAgt2> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.12.2.18.12 IntermediaryAgent3 <IntrmyAgt3>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

IntermediaryAgent3 <IntrmyAgt3> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.12.2.18.13 CreditorAgent <CdtrAgt>

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

CreditorAgent <CdtrAgt> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.12.2.18.14 Creditor <Cdtr>

Presence: [0..1]

Definition: Party to which an amount of money is due.

Creditor <Cdtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.12.2.18.15 CreditorAccount <CdtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

CreditorAccount <CdtrAcct> contains the following elements (see "CashAccount24" on page 146 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		146
	Type <*Tp*>	[0..1]	±		146
	Currency <*Ccy*>	[0..1]	CodeSet	C2	147
	Name <*Nm*>	[0..1]	Text		147

13.1.12.2.18.16 UltimateCreditor <UltmtCdtr>

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

UltimateCreditor <UltmtCdtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.12.2.18.17 InstructionForCreditorAgent <InstrForCdtrAgt>

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

InstructionForCreditorAgent <InstrForCdtrAgt> contains the following elements (see "InstructionForCreditorAgent1" on page 212 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Code <*Cd*>	[0..1]	CodeSet		212
	InstructionInformation <*InstrInf*>	[0..1]	Text		213

13.1.12.2.18.18 Purpose <Purp>

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

Purpose <Purp> contains one of the following **Purpose2Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		239
Or}	Proprietary <*Prtry*>	[1..1]	Text		239

13.1.12.2.18.18.1 Code <Cd>

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: "ExternalPurpose1Code" on page 368

13.1.12.2.18.18.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: "Max35Text" on page 381

13.1.12.2.18.19 RegulatoryReporting <RgltryRptg>

Presence: [0..10]

Definition: Information needed due to regulatory and statutory requirements.

RegulatoryReporting <RgltryRptg> contains the following elements (see "RegulatoryReporting3" on page 269 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DebitCreditReportingIndicator <*DbtCdtRptgInd*>	[0..1]	CodeSet		269
	Authority <*Authrty*>	[0..1]			270
	Name <*Nm*>	[0..1]	Text		270
	Country <*Ctry*>	[0..1]	CodeSet	C18	270
	Details <*Dtls*>	[0..*]			270
	Type <*Tp*>	[0..1]	Text		271
	Date <*Dt*>	[0..1]	Date		271
	Country <*Ctry*>	[0..1]	CodeSet	C18	271
	Code <*Cd*>	[0..1]	Text		271
	Amount <*Amt*>	[0..1]	Amount	C2, C20	271
	Information <*Inf*>	[0..*]	Text		272

13.1.12.2.18.20 Tax <Tax>

Presence: [0..1]

Definition: Provides details on the tax.

Tax <Tax> contains the following **TaxInformation6** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Creditor <*Cdtr*>	[0..1]			242
	TaxIdentification <*TaxId*>	[0..1]	Text		242
	RegistrationIdentification <*RegnId*>	[0..1]	Text		242
	TaxType <*TaxTp*>	[0..1]	Text		242
	Debtor <*Dbtr*>	[0..1]			243
	TaxIdentification <*TaxId*>	[0..1]	Text		243
	RegistrationIdentification <*RegnId*>	[0..1]	Text		243
	TaxType <*TaxTp*>	[0..1]	Text		243
	Authorisation <*Authstn*>	[0..1]			243
	Title <*Titl*>	[0..1]	Text		244
	Name <*Nm*>	[0..1]	Text		244
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		244
	ReferenceNumber <*RefNb*>	[0..1]	Text		244
	Method <*Mtd*>	[0..1]	Text		244
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	244
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	245
	Date <*Dt*>	[0..1]	Date		245
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		245
	Record <*Rcrd*>	[0..*]			245
	Type <*Tp*>	[0..1]	Text		246
	Category <*Ctgy*>	[0..1]	Text		246
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		247
	DebtorStatus <*DbtrSts*>	[0..1]	Text		247
	CertificateIdentification <*CertId*>	[0..1]	Text		247
	FormsCode <*FrmsCd*>	[0..1]	Text		247
	Period <*Prd*>	[0..1]			247
	Year <*Yr*>	[0..1]	Date		247
	Type <*Tp*>	[0..1]	CodeSet		248
	FromToDate <*FrToDt*>	[0..1]			248
	FromDate <*FrDt*>	[1..1]	Date		249
	ToDate <*ToDt*>	[1..1]	Date		249

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxAmount <*TaxAmt*>	[0..1]			249
	Rate <*Rate*>	[0..1]	Rate		249
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	250
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	250
	Details <*Dtls*>	[0..*]			250
	Period <*Prd*>	[0..1]			251
	Year <*Yr*>	[0..1]	Date		251
	Type <*Tp*>	[0..1]	CodeSet		251
	FromToDate <*FrToDt*>	[0..1]			252
	FromDate <*FrDt*>	[1..1]	Date		252
	ToDate <*ToDt*>	[1..1]	Date		253
	Amount <*Amt*>	[1..1]	Amount	C2, C20	253
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		253

13.1.12.2.18.20.1 Creditor <Cdtr>

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

Creditor <Cdtr> contains the following **TaxParty1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxIdentification <*TaxId*>	[0..1]	Text		242
	RegistrationIdentification <*RegnId*>	[0..1]	Text		242
	TaxType <*TaxTp*>	[0..1]	Text		242

13.1.12.2.18.20.1.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.1.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.1.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Set of elements used to identify the party on the debit side of the transaction to which the tax applies.

Debtor <Dbtr> contains the following **TaxParty2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxIdentification <*TaxId*>	[0..1]	Text		243
	RegistrationIdentification <*RegnId*>	[0..1]	Text		243
	TaxType <*TaxTp*>	[0..1]	Text		243
	Authorisation <*Authstn*>	[0..1]			243
	Title <*Titl*>	[0..1]	Text		244
	Name <*Nm*>	[0..1]	Text		244

13.1.12.2.18.20.2.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.2.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.2.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.2.4 Authorisation <Authstn>

Presence: [0..1]

Definition: Details of the authorised tax paying party.

Authorisation <Authstn> contains the following **TaxAuthorisation1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Title <*Titl*>	[0..1]	Text		244
	Name <*Nm*>	[0..1]	Text		244

13.1.12.2.18.20.2.4.1 Title <Titl>

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.2.4.2 Name <Nm>

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: "Max140Text" on page 379

13.1.12.2.18.20.3 AdministrationZone <AdmstnZn>

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.4 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "Max140Text" on page 379

13.1.12.2.18.20.5 Method <Mtd>

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.6 TotalTaxableBaseAmount <TtlTaxblBaseAmt>

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.12.2.18.20.7 TotalTaxAmount <TtlTaxAmt>

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.12.2.18.20.8 Date <Dt>

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: "ISODate" on page 376

13.1.12.2.18.20.9 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: "Number" on page 378

13.1.12.2.18.20.10 Record <Rcrd>

Presence: [0..*]

Definition: Record of tax details.

Record <Rcrd> contains the following **TaxRecord2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]	Text		246
	Category <*Ctgy*>	[0..1]	Text		246
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		247
	DebtorStatus <*DbtrSts*>	[0..1]	Text		247
	CertificateIdentification <*CertId*>	[0..1]	Text		247
	FormsCode <*FrmsCd*>	[0..1]	Text		247
	Period <*Prd*>	[0..1]			247
	Year <*Yr*>	[0..1]	Date		247
	Type <*Tp*>	[0..1]	CodeSet		248
	FromToDate <*FrToDt*>	[0..1]			248
	FromDate <*FrDt*>	[1..1]	Date		249
	ToDate <*ToDt*>	[1..1]	Date		249
	TaxAmount <*TaxAmt*>	[0..1]			249
	Rate <*Rate*>	[0..1]	Rate		249
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	250
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	250
	Details <*Dtls*>	[0..*]			250
	Period <*Prd*>	[0..1]			251
	Year <*Yr*>	[0..1]	Date		251
	Type <*Tp*>	[0..1]	CodeSet		251
	FromToDate <*FrToDt*>	[0..1]			252
	FromDate <*FrDt*>	[1..1]	Date		252
	ToDate <*ToDt*>	[1..1]	Date		253
	Amount <*Amt*>	[1..1]	Amount	C2, C20	253
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		253

13.1.12.2.18.20.10.1 Type <Tp>

Presence: [0..1]

Definition: High level code to identify the type of tax details.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.10.2 Category <Ctgy>

Presence: [0..1]

Definition: Specifies the tax code as published by the tax authority.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.10.3 CategoryDetails <CtgyDtls>

Presence: [0..1]

Definition: Provides further details of the category tax code.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.10.4 DebtorStatus <DbtrSts>

Presence: [0..1]

Definition: Code provided by local authority to identify the status of the party that has drawn up the settlement document.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.10.5 CertificateIdentification <CertId>

Presence: [0..1]

Definition: Identification number of the tax report as assigned by the taxing authority.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.10.6 FormsCode <FrmsCd>

Presence: [0..1]

Definition: Identifies, in a coded form, on which template the tax report is to be provided.

Datatype: "Max35Text" on page 381

13.1.12.2.18.20.10.7 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following **TaxPeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		247
	Type <*Tp*>	[0..1]	CodeSet		248
	FromToDate <*FrToDt*>	[0..1]			248
	FromDate <*FrDt*>	[1..1]	Date		249
	ToDate <*ToDt*>	[1..1]	Date		249

13.1.12.2.18.20.10.7.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 376

13.1.12.2.18.20.10.7.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 375

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

13.1.12.2.18.20.10.7.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following **DatePeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FromDate <*FrDt*>	[1..1]	Date		249
	ToDate <*ToDt*>	[1..1]	Date		249

13.1.12.2.18.20.10.7.3.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: "ISODate" on page 376

13.1.12.2.18.20.10.7.3.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: "ISODate" on page 376

13.1.12.2.18.20.10.8 TaxAmount <TaxAmt>

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

TaxAmount <TaxAmt> contains the following **TaxAmount2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Rate <*Rate*>	[0..1]	Rate		249
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	250
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	250
	Details <*Dtls*>	[0..*]			250
	Period <*Prd*>	[0..1]			251
	Year <*Yr*>	[0..1]	Date		251
	Type <*Tp*>	[0..1]	CodeSet		251
	FromToDate <*FrToDt*>	[0..1]			252
	FromDate <*FrDt*>	[1..1]	Date		252
	ToDate <*ToDt*>	[1..1]	Date		253
	Amount <*Amt*>	[1..1]	Amount	C2, C20	253

13.1.12.2.18.20.10.8.1 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: "PercentageRate" on page 378

13.1.12.2.18.20.10.8.2 TaxableBaseAmount <TaxblBaseAmt>

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.12.2.18.20.10.8.3 TotalAmount <TtlAmt>

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.12.2.18.20.10.8.4 Details <Dtls>

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

Details <Dtls> contains the following **TaxRecordDetails2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Period <*Prd*>	[0..1]			251
	Year <*Yr*>	[0..1]	Date		251
	Type <*Tp*>	[0..1]	CodeSet		251
	FromToDate <*FrToDt*>	[0..1]			252
	FromDate <*FrDt*>	[1..1]	Date		252
	ToDate <*ToDt*>	[1..1]	Date		253
	Amount <*Amt*>	[1..1]	Amount	C2, C20	253

13.1.12.2.18.20.10.8.4.1 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following **TaxPeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		251
	Type <*Tp*>	[0..1]	CodeSet		251
	FromToDate <*FrToDt*>	[0..1]			252
	FromDate <*FrDt*>	[1..1]	Date		252
	ToDate <*ToDt*>	[1..1]	Date		253

13.1.12.2.18.20.10.8.4.1.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 376

13.1.12.2.18.20.10.8.4.1.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 375

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.

CodeName	Name	Definition
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

13.1.12.2.18.20.10.8.4.1.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following **DatePeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FromDate <*FrDt*>	[1..1]	Date		252
	ToDate <*ToDt*>	[1..1]	Date		253

13.1.12.2.18.20.10.8.4.1.3.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: "ISODate" on page 376

13.1.12.2.18.20.10.8.4.1.3.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: "ISODate" on page 376

13.1.12.2.18.20.10.8.4.2 Amount <Amt>

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.12.2.18.20.10.9 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: "Max140Text" on page 379

13.1.12.2.18.21 RelatedRemittanceInformation <RltdRmtInf>

Presence: [0..10]

Definition: Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain.

RelatedRemittanceInformation <RltdRmtInf> contains the following elements (see "RemittanceLocation2" on page 173 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	RemittanceIdentification <*RmtId*>	[0..1]	Text		174
	RemittanceLocationMethod <*RmtLctnMtd*>	[0..1]	CodeSet		174
	RemittanceLocationElectronicAddress <*RmtLctnElctrncAdr*>	[0..1]	Text		174
	RemittanceLocationPostalAddress <*RmtLctnPstlAdr*>	[0..1]			174
	Name <*Nm*>	[1..1]	Text		175
	Address <*Adr*>	[1..1]	±		175

13.1.12.2.18.22 RemittanceInformation <RmtInf>

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

RemittanceInformation <RmtInf> contains the following **RemittanceInformation14** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Unstructured <*Ustrd*>	[0..*]	Text		254
	Structured <*Strd*>	[0..*]			254
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			255
	Type <*Tp*>	[0..1]			255
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			256
{Or	Code <*Cd*>	[1..1]	CodeSet		256
Or}	Proprietary <*Prtry*>	[1..1]	Text		257
	Issuer <*Issr*>	[0..1]	Text		257
	Number <*Nb*>	[0..1]	Text		257
	RelatedDate <*RltdDt*>	[0..1]	Date		257
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		257
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		258
	Invoicer <*Invcr*>	[0..1]	±		259
	Invoicee <*Invcee*>	[0..1]	±		259
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		260

13.1.12.2.18.22.1 Unstructured <Ustrd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: "Max140Text" on page 379

13.1.12.2.18.22.2 Structured <Strd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

Structured <Strd> contains the following **StructuredRemittanceInformation14** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			255
	Type <*Tp*>	[0..1]			255
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			256
{Or	Code <*Cd*>	[1..1]	CodeSet		256
Or}	Proprietary <*Prtry*>	[1..1]	Text		257
	Issuer <*Issr*>	[0..1]	Text		257
	Number <*Nb*>	[0..1]	Text		257
	RelatedDate <*RltdDt*>	[0..1]	Date		257
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		257
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		258
	Invoicer <*Invcr*>	[0..1]	±		259
	Invoicee <*Invcee*>	[0..1]	±		259
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		260

13.1.12.2.18.22.2.1 ReferredDocumentInformation <RfrdDocInf>

Presence: [0..*]

Definition: Set of elements used to identify the documents referred to in the remittance information.

ReferredDocumentInformation <RfrdDocInf> contains the following **ReferredDocumentInformation3** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			255
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			256
{Or	Code <*Cd*>	[1..1]	CodeSet		256
Or}	Proprietary <*Prtry*>	[1..1]	Text		257
	Issuer <*Issr*>	[0..1]	Text		257
	Number <*Nb*>	[0..1]	Text		257
	RelatedDate <*RltdDt*>	[0..1]	Date		257

13.1.12.2.18.22.2.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of referred document.

Type <Tp> contains the following **ReferredDocumentType2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			256
{Or	Code <*Cd*>	[1..1]	CodeSet		256
Or}	Proprietary <*Prtry*>	[1..1]	Text		257
	Issuer <*Issr*>	[0..1]	Text		257

13.1.12.2.18.22.2.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the referred document.

CodeOrProprietary <CdOrPrtry> contains one of the following **ReferredDocumentType1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		256
Or}	Proprietary <*Prtry*>	[1..1]	Text		257

13.1.12.2.18.22.2.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: "DocumentType5Code" on page 364

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and

CodeName	Name	Definition
		conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.

13.1.12.2.18.22.2.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: "Max35Text" on page 381

13.1.12.2.18.22.2.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "Max35Text" on page 381

13.1.12.2.18.22.2.1.2 Number <Nb>

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: "Max35Text" on page 381

13.1.12.2.18.22.2.1.3 RelatedDate <RltdDt>

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: "ISODate" on page 376

13.1.12.2.18.22.2.2 ReferredDocumentAmount <RfrdDocAmt>

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

ReferredDocumentAmount <RfrdDocAmt> contains the following elements (see "RemittanceAmount2" on page 177 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DuePayableAmount <*DuePyblAmt*>	[0..1]	Amount	C2, C20	178
	DiscountAppliedAmount <*DscntApldAmt*>	[0..*]			179
	Type <*Tp*>	[0..1]			179
{Or	Code <*Cd*>	[1..1]	CodeSet		179
Or}	Proprietary <*Prtry*>	[1..1]	Text		179
	Amount <*Amt*>	[1..1]	Amount	C2, C20	179
	CreditNoteAmount <*CdtNoteAmt*>	[0..1]	Amount	C2, C20	180
	TaxAmount <*TaxAmt*>	[0..*]			180
	Type <*Tp*>	[0..1]			180
{Or	Code <*Cd*>	[1..1]	CodeSet		181
Or}	Proprietary <*Prtry*>	[1..1]	Text		181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	181
	AdjustmentAmountAndReason <*AdjstmntAmtAndRsn*>	[0..*]			181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	182
	CreditDebitIndicator <*CdtDbtInd*>	[0..1]	CodeSet		182
	Reason <*Rsn*>	[0..1]	Text		182
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		182
	RemittedAmount <*RmtdAmt*>	[0..1]	Amount	C2, C20	183

13.1.12.2.18.22.2.3 CreditorReferenceInformation <CdtrRefInf>

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

CreditorReferenceInformation <CdtrRefInf> contains the following elements (see "CreditorReferenceInformation2" on page 162 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			162
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			162
{Or	Code <*Cd*>	[1..1]	CodeSet		163
Or}	Proprietary <*Prtry*>	[1..1]	Text		163
	Issuer <*Issr*>	[0..1]	Text		163
	Reference <*Ref*>	[0..1]	Text		163

13.1.12.2.18.22.2.4 Invoicer <Invcr>

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

Invoicer <Invcr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.12.2.18.22.2.5 Invoicee <Invcee>

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

Invoicee <Invcee> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.12.2.18.22.2.6 AdditionalRemittanceInformation <AddtlRmtInf>

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: "Max140Text" on page 379

13.1.13 Payment Type

13.1.13.1 PaymentTypeInformation19

Definition: Set of elements used to provide further details of the type of payment.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		260
	ServiceLevel <*SvcLvl*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		261
	LocalInstrument <*LclInstrm*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		262
	CategoryPurpose <*CtgyPurp*>	[0..1]			262
{Or	Code <*Cd*>	[1..1]	CodeSet		262
Or}	Proprietary <*Prtry*>	[1..1]	Text		262

13.1.13.1.1 InstructionPriority <InstrPrty>

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: "Priority2Code" on page 372

CodeName	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

13.1.13.1.2 ServiceLevel <SvcLvl>

Presence: [0..1]

Definition: Agreement under which or rules under which the transaction should be processed.

ServiceLevel <SvcLvl> contains one of the following **ServiceLevel8Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		261

13.1.13.1.2.1 Code <Cd>

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: "ExternalServiceLevel1Code" on page 368

13.1.13.1.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: "Max35Text" on page 381

13.1.13.1.3 LocalInstrument <LclInstrm>

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

LocalInstrument <LclInstrm> contains one of the following **LocalInstrument2Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		262

13.1.13.1.3.1 Code <Cd>

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: "ExternalLocalInstrument1Code" on page 367

13.1.13.1.3.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: "Max35Text" on page 381

13.1.13.1.4 CategoryPurpose <CtgyPurp>

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

CategoryPurpose <CtgyPurp> contains one of the following **CategoryPurpose1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		262
Or}	Proprietary <*Prtry*>	[1..1]	Text		262

13.1.13.1.4.1 Code <Cd>

Presence: [1..1]

Definition: Category purpose, as published in an external category purpose code list.

Datatype: "ExternalCategoryPurpose1Code" on page 366

13.1.13.1.4.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Category purpose, in a proprietary form.

Datatype: "Max35Text" on page 381

13.1.14 Person Identification

13.1.14.1 CountryAndResidentialStatusType1

Definition: Country and residential status.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Country <*Ctry*>	[1..1]	CodeSet	C18	262
	ResidentialStatus <*ResdtlSts*>	[1..1]	CodeSet		263

13.1.14.1.1 Country <Ctry>

Presence: [1..1]

Definition: Country to which the residential status is applicable.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.14.1.2 ResidentialStatus <ResdtlSts>

Presence: [1..1]

Definition: Residential status of an individual, for example, non-permanent resident.

Datatype: "ResidentialStatus1Code" on page 373

CodeName	Name	Definition
RESI	Resident	Resident.
PRES	PermanentResident	Permanent resident.
NRES	NonResident	Non-resident.

13.1.14.2 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DateAndPlaceOfBirth <*DtAndPlcOfBirth*>	[0..1]			263
	BirthDate <*BirthDt*>	[1..1]	Date		264
	ProvinceOfBirth <*PrvcOfBirth*>	[0..1]	Text		264
	CityOfBirth <*CityOfBirth*>	[1..1]	Text		264
	CountryOfBirth <*CtryOfBirth*>	[1..1]	CodeSet	C18	264
	Other <*Othr*>	[0..*]			264
	Identification <*Id*>	[1..1]	Text		265
	SchemeName <*SchmeNm*>	[0..1]			265
{Or	Code <*Cd*>	[1..1]	CodeSet		265
Or}	Proprietary <*Prtry*>	[1..1]	Text		265
	Issuer <*Issr*>	[0..1]	Text		265

13.1.14.2.1 DateAndPlaceOfBirth <DtAndPlcOfBirth>

Presence: [0..1]

Definition: Date and place of birth of a person.

DateAndPlaceOfBirth <DtAndPlcOfBirth> contains the following **DateAndPlaceOfBirth1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	BirthDate <*BirthDt*>	[1..1]	Date		264
	ProvinceOfBirth <*PrvcOfBirth*>	[0..1]	Text		264
	CityOfBirth <*CityOfBirth*>	[1..1]	Text		264
	CountryOfBirth <*CtryOfBirth*>	[1..1]	CodeSet	C18	264

13.1.14.2.1.1 BirthDate <BirthDt>

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "ISODate" on page 376

13.1.14.2.1.2 ProvinceOfBirth <PrvcOfBirth>

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "Max35Text" on page 381

13.1.14.2.1.3 CityOfBirth <CityOfBirth>

Presence: [1..1]

Definition: City where a person was born.

Datatype: "Max35Text" on page 381

13.1.14.2.1.4 CountryOfBirth <CtryOfBirth>

Presence: [1..1]

Definition: Country where a person was born.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.14.2.2 Other <Othr>

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

Other <Othr> contains the following **GenericPersonIdentification1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	Text		265
	SchemeName <*SchmeNm*>	[0..1]			265
{Or	Code <*Cd*>	[1..1]	CodeSet		265
Or}	Proprietary <*Prtry*>	[1..1]	Text		265
	Issuer <*Issr*>	[0..1]	Text		265

13.1.14.2.2.1 Identification <Id>

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 381

13.1.14.2.2.2 SchemeName <SchmeNm>

Presence: [0..1]

Definition: Name of the identification scheme.

SchemeName <SchmeNm> contains one of the following **PersonIdentificationSchemeName1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		265
Or}	Proprietary <*Prtry*>	[1..1]	Text		265

13.1.14.2.2.2.1 Code <Cd>

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 367

13.1.14.2.2.2.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 381

13.1.14.2.2.3 Issuer <Issr>

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 381

13.1.15 Postal Address

13.1.15.1 CommunicationAddress3

Definition: Communication device number or electronic address used for communication.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Email <*Email*>	[0..1]	Text		266
	Phone <*Phne*>	[0..1]	Text		266
	Mobile <*Mob*>	[0..1]	Text		266
	FaxNumber <*FaxNb*>	[0..1]	Text		266
	TelexAddress <*TlxAdr*>	[0..1]	Text		266
	URLAddress <*URLAdr*>	[0..1]	Text		267

13.1.15.1.1 Email <Email>

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: "Max256Text" on page 380

13.1.15.1.2 Phone <Phne>

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 382

13.1.15.1.3 Mobile <Mob>

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 382

13.1.15.1.4 FaxNumber <FaxNb>

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: "PhoneNumber" on page 382

13.1.15.1.5 TelexAddress <TlxAdr>

Presence: [0..1]

Definition: Address for a telex machine.

Datatype: "Max35Text" on page 381

13.1.15.1.6 URLAddress <URLAdr>

Presence: [0..1]

Definition: Address for the Universal Resource Locator (URL), for example an address used over the www (HTTP) service.

Datatype: "Max256Text" on page 380

13.1.15.2 PostalAddress6

Definition: Information that locates and identifies a specific address, as defined by postal services.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	AddressType <*AdrTp*>	[0..1]	CodeSet		267
	Department <*Dept*>	[0..1]	Text		267
	SubDepartment <*SubDept*>	[0..1]	Text		268
	StreetName <*StrtNm*>	[0..1]	Text		268
	BuildingNumber <*BldgNb*>	[0..1]	Text		268
	PostCode <*PstCd*>	[0..1]	Text		268
	TownName <*TwnNm*>	[0..1]	Text		268
	CountrySubDivision <*CtrySubDvsn*>	[0..1]	Text		268
	Country <*Ctry*>	[0..1]	CodeSet	C18	268
	AddressLine <*AdrLine*>	[0..7]	Text		269

13.1.15.2.1 AddressType <AdrTp>

Presence: [0..1]

Definition: Identifies the nature of the postal address.

Datatype: "AddressType2Code" on page 361

CodeName	Name	Definition
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

13.1.15.2.2 Department <Dept>

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 382

13.1.15.2.3 SubDepartment <SubDept>

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 382

13.1.15.2.4 StreetName <StrtNm>

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max70Text" on page 382

13.1.15.2.5 BuildingNumber <BldgNb>

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 380

13.1.15.2.6 PostCode <PstCd>

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 380

13.1.15.2.7 TownName <TwnNm>

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 381

13.1.15.2.8 CountrySubDivision <CtrySubDvsn>

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 381

13.1.15.2.9 Country <Ctry>

Presence: [0..1]

Definition: Nation with its own government.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.15.2.10 AddressLine <AdrLine>

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 382

13.1.16 Regulatory Reporting

13.1.16.1 RegulatoryReporting3

Definition: Information needed due to regulatory and/or statutory requirements.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DebitCreditReportingIndicator <*DbtCdtRptgInd*>	[0..1]	CodeSet		269
	Authority <*Authrty*>	[0..1]			270
	Name <*Nm*>	[0..1]	Text		270
	Country <*Ctry*>	[0..1]	CodeSet	C18	270
	Details <*Dtls*>	[0..*]			270
	Type <*Tp*>	[0..1]	Text		271
	Date <*Dt*>	[0..1]	Date		271
	Country <*Ctry*>	[0..1]	CodeSet	C18	271
	Code <*Cd*>	[0..1]	Text		271
	Amount <*Amt*>	[0..1]	Amount	C2, C20	271
	Information <*Inf*>	[0..*]	Text		272

13.1.16.1.1 DebitCreditReportingIndicator <DbtCdtRptgInd>

Presence: [0..1]

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Datatype: "RegulatoryReportingType1Code" on page 372

CodeName	Name	Definition
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.

CodeName	Name	Definition
BOTH	Both	Regulatory information applies to both credit and debit sides.

13.1.16.1.2 Authority <Authrty>

Presence: [0..1]

Definition: Entity requiring the regulatory reporting information.

Authority <Authrty> contains the following **RegulatoryAuthority2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		270
	Country <*Ctry*>	[0..1]	CodeSet	C18	270

13.1.16.1.2.1 Name <Nm>

Presence: [0..1]

Definition: Name of the entity requiring the regulatory reporting information.

Datatype: "Max140Text" on page 379

13.1.16.1.2.2 Country <Ctry>

Presence: [0..1]

Definition: Country of the entity that requires the regulatory reporting information.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.16.1.3 Details <Dtls>

Presence: [0..*]

Definition: Set of elements used to provide details on the regulatory reporting information.

Details <Dtls> contains the following **StructuredRegulatoryReporting3** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]	Text		271
	Date <*Dt*>	[0..1]	Date		271
	Country <*Ctry*>	[0..1]	CodeSet	C18	271
	Code <*Cd*>	[0..1]	Text		271
	Amount <*Amt*>	[0..1]	Amount	C2, C20	271
	Information <*Inf*>	[0..*]	Text		272

13.1.16.1.3.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of the information supplied in the regulatory reporting details.

Datatype: "Max35Text" on page 381

13.1.16.1.3.2 Date <Dt>

Presence: [0..1]

Definition: Date related to the specified type of regulatory reporting details.

Datatype: "ISODate" on page 376

13.1.16.1.3.3 Country <Ctry>

Presence: [0..1]

Definition: Country related to the specified type of regulatory reporting details.

Impacted by: C18 "Country"

Datatype: "CountryCode" on page 363

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.1.16.1.3.4 Code <Cd>

Presence: [0..1]

Definition: Specifies the nature, purpose, and reason for the transaction to be reported for regulatory and statutory requirements in a coded form.

Datatype: "Max10Text" on page 379

13.1.16.1.3.5 Amount <Amt>

Presence: [0..1]

Definition: Amount of money to be reported for regulatory and statutory requirements.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.16.1.3.6 Information <Inf>

Presence: [0..*]

Definition: Additional details that cater for specific domestic regulatory requirements.

Datatype: "Max35Text" on page 381

13.1.17 Settlement Instruction

13.1.17.1 SettlementMethod1Choice

Definition: Settlement details to determine whether payment is a credit or debit.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Credit <*Cdt*>	[1..1]		C22, C23, C24, C28, C30	279
	PaymentIdentification <*PmtId*>	[1..1]	±		283
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		283
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		284
	Amount <*Amt*>	[1..1]	Amount	C1, C19	284
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		285
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C16	285
	Frequency <*Frqcy*>	[0..1]			286
	Sequence <*Seq*>	[0..1]	Text		287
	StartDate <*StartDt*>	[1..1]	Date		287
	EndPointChoice <*EndPtChc*>	[1..1]			287
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		287
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		287
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		288
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		288
	TransferInstruction <*TrfInstr*>	[0..1]			288
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		288
	Code <*Cd*>	[1..1]	Text		289
	Proprietary <*Prtry*>	[0..1]	Text		289
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		289
	StartDate <*StartDt*>	[0..1]	Date		289
	Description <*Desc*>	[0..1]	Text		289
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		289
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		290
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		290
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		290
	CreditorAgent <*CdtrAgt*>	[1..1]	±		291
	Creditor <*Cdtr*>	[0..1]	±		291
	CreditorAccount <*CdtrAcct*>	[0..1]	±		291
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		292

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		292
	Purpose <*Purp*>	[0..1]			292
{Or	Code <*Cd*>	[1..1]	CodeSet		293
Or}	Proprietary <*Prtry*>	[1..1]	Text		293
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		293
	Tax <*Tax*>	[0..1]			294
	Creditor <*Cdtr*>	[0..1]			296
	TaxIdentification <*TaxId*>	[0..1]	Text		296
	RegistrationIdentification <*RegnId*>	[0..1]	Text		296
	TaxType <*TaxTp*>	[0..1]	Text		296
	Debtor <*Dbtr*>	[0..1]			297
	TaxIdentification <*TaxId*>	[0..1]	Text		297
	RegistrationIdentification <*RegnId*>	[0..1]	Text		297
	TaxType <*TaxTp*>	[0..1]	Text		297
	Authorisation <*Authstn*>	[0..1]			297
	Title <*Titl*>	[0..1]	Text		298
	Name <*Nm*>	[0..1]	Text		298
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		298
	ReferenceNumber <*RefNb*>	[0..1]	Text		298
	Method <*Mtd*>	[0..1]	Text		298
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	298
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	299
	Date <*Dt*>	[0..1]	Date		299
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		299
	Record <*Rcrd*>	[0..*]			299
	Type <*Tp*>	[0..1]	Text		300
	Category <*Ctgy*>	[0..1]	Text		300
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		301
	DebtorStatus <*DbtrSts*>	[0..1]	Text		301
	CertificateIdentification <*CertId*>	[0..1]	Text		301
	FormsCode <*FrmsCd*>	[0..1]	Text		301

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Period <*Prd*>	[0..1]			301
	Year <*Yr*>	[0..1]	Date		301
	Type <*Tp*>	[0..1]	CodeSet		302
	FromToDate <*FrToDt*>	[0..1]			302
	FromDate <*FrDt*>	[1..1]	Date		303
	ToDate <*ToDt*>	[1..1]	Date		303
	TaxAmount <*TaxAmt*>	[0..1]			303
	Rate <*Rate*>	[0..1]	Rate		303
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	304
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	304
	Details <*Dtls*>	[0..*]			304
	Period <*Prd*>	[0..1]			305
	Year <*Yr*>	[0..1]	Date		305
	Type <*Tp*>	[0..1]	CodeSet		305
	FromToDate <*FrToDt*>	[0..1]			306
	FromDate <*FrDt*>	[1..1]	Date		306
	ToDate <*ToDt*>	[1..1]	Date		307
	Amount <*Amt*>	[1..1]	Amount	C2, C20	307
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		307
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		307
	RemittanceInformation <*RmtInf*>	[0..1]			308
	Unstructured <*Ustrd*>	[0..*]	Text		308
	Structured <*Strd*>	[0..*]			308
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			309
	Type <*Tp*>	[0..1]			309
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			310
{Or	Code <*Cd*>	[1..1]	CodeSet		310
Or}	Proprietary <*Prtry*>	[1..1]	Text		311
	Issuer <*Issr*>	[0..1]	Text		311
	Number <*Nb*>	[0..1]	Text		311
	RelatedDate <*RltdDt*>	[0..1]	Date		311

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		311
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		312
	Invoicer <*Invcr*>	[0..1]	±		313
	Invoicee <*Invcee*>	[0..1]	±		313
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		314
Or}	Debit <*Dbt*>	[1..1]		C22, C23, C24, C28, C30	314
	PaymentIdentification <*PmtId*>	[1..1]	±		318
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		318
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		319
	Amount <*Amt*>	[1..1]	Amount	C1, C19	319
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		320
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C16	320
	Frequency <*Frqcy*>	[0..1]			321
	Sequence <*Seq*>	[0..1]	Text		322
	StartDate <*StartDt*>	[1..1]	Date		322
	EndPointChoice <*EndPtChc*>	[1..1]			322
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		322
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		322
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		323
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		323
	TransferInstruction <*TrfInstr*>	[0..1]			323
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		323
	Code <*Cd*>	[1..1]	Text		324
	Proprietary <*Prtry*>	[0..1]	Text		324
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		324
	StartDate <*StartDt*>	[0..1]	Date		324
	Description <*Desc*>	[0..1]	Text		324
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		324
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		325
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		325

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		325
	CreditorAgent <*CdtrAgt*>	[1..1]	±		326
	Creditor <*Cdtr*>	[0..1]	±		326
	CreditorAccount <*CdtrAcct*>	[0..1]	±		326
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		327
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		327
	Purpose <*Purp*>	[0..1]			327
{Or	Code <*Cd*>	[1..1]	CodeSet		328
Or}	Proprietary <*Prtry*>	[1..1]	Text		328
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		328
	Tax <*Tax*>	[0..1]			329
	Creditor <*Cdtr*>	[0..1]			331
	TaxIdentification <*TaxId*>	[0..1]	Text		331
	RegistrationIdentification <*RegnId*>	[0..1]	Text		331
	TaxType <*TaxTp*>	[0..1]	Text		331
	Debtor <*Dbtr*>	[0..1]			332
	TaxIdentification <*TaxId*>	[0..1]	Text		332
	RegistrationIdentification <*RegnId*>	[0..1]	Text		332
	TaxType <*TaxTp*>	[0..1]	Text		332
	Authorisation <*Authstn*>	[0..1]			332
	Title <*Titl*>	[0..1]	Text		333
	Name <*Nm*>	[0..1]	Text		333
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		333
	ReferenceNumber <*RefNb*>	[0..1]	Text		333
	Method <*Mtd*>	[0..1]	Text		333
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	333
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	334
	Date <*Dt*>	[0..1]	Date		334
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		334
	Record <*Rcrd*>	[0..*]			334
	Type <*Tp*>	[0..1]	Text		335

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Category <*Ctgy*>	[0..1]	Text		335
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		336
	DebtorStatus <*DbtrSts*>	[0..1]	Text		336
	CertificateIdentification <*CertId*>	[0..1]	Text		336
	FormsCode <*FrmsCd*>	[0..1]	Text		336
	Period <*Prd*>	[0..1]			336
	Year <*Yr*>	[0..1]	Date		336
	Type <*Tp*>	[0..1]	CodeSet		337
	FromToDate <*FrToDt*>	[0..1]			337
	FromDate <*FrDt*>	[1..1]	Date		338
	ToDate <*ToDt*>	[1..1]	Date		338
	TaxAmount <*TaxAmt*>	[0..1]			338
	Rate <*Rate*>	[0..1]	Rate		338
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	339
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	339
	Details <*Dtls*>	[0..*]			339
	Period <*Prd*>	[0..1]			340
	Year <*Yr*>	[0..1]	Date		340
	Type <*Tp*>	[0..1]	CodeSet		340
	FromToDate <*FrToDt*>	[0..1]			341
	FromDate <*FrDt*>	[1..1]	Date		341
	ToDate <*ToDt*>	[1..1]	Date		342
	Amount <*Amt*>	[1..1]	Amount	C2, C20	342
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		342
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		342
	RemittanceInformation <*RmtInf*>	[0..1]			343
	Unstructured <*Ustrd*>	[0..*]	Text		343
	Structured <*Strd*>	[0..*]			343
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			344
	Type <*Tp*>	[0..1]			344
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			345

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		345
Or}	Proprietary <*Prtry*>	[1..1]	Text		346
	Issuer <*Issr*>	[0..1]	Text		346
	Number <*Nb*>	[0..1]	Text		346
	RelatedDate <*RltdDt*>	[0..1]	Date		346
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		346
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		347
	Invoicer <*Invcr*>	[0..1]	±		348
	Invoicee <*Invcee*>	[0..1]	±		348
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		349

13.1.17.1.1 Credit <Cdt>

Presence: [1..1]

Definition: Specifies details of the payment to be made by the old account servicer to the new account servicer in case of a positive closing balance.

Impacted by: C22 "InstructionForCreditorAgentRule", C23 "IntermediaryAgent2Rule", C24 "IntermediaryAgent3Rule", C28 "UltimateCreditorGuideline", C30 "UltimateDebtorGuideline"

Credit <Cdt> contains the following **CreditTransferTransaction27** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PaymentIdentification <*PmtId*>	[1..1]	±		283
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		283
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		284
	Amount <*Amt*>	[1..1]	Amount	C1, C19	284
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		285
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C16	285
	Frequency <*Frqcy*>	[0..1]			286
	Sequence <*Seq*>	[0..1]	Text		287
	StartDate <*StartDt*>	[1..1]	Date		287
	EndPointChoice <*EndPtChc*>	[1..1]			287
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		287
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		287
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		288
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		288
	TransferInstruction <*TrfInstr*>	[0..1]			288
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		288
	Code <*Cd*>	[1..1]	Text		289
	Proprietary <*Prtry*>	[0..1]	Text		289
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		289
	StartDate <*StartDt*>	[0..1]	Date		289
	Description <*Desc*>	[0..1]	Text		289
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		289
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		290
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		290
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		290
	CreditorAgent <*CdtrAgt*>	[1..1]	±		291
	Creditor <*Cdtr*>	[0..1]	±		291
	CreditorAccount <*CdtrAcct*>	[0..1]	±		291
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		292
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		292
	Purpose <*Purp*>	[0..1]			292

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		293
Or}	Proprietary <*Prtry*>	[1..1]	Text		293
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		293
	Tax <*Tax*>	[0..1]			294
	Creditor <*Cdtr*>	[0..1]			296
	TaxIdentification <*TaxId*>	[0..1]	Text		296
	RegistrationIdentification <*RegnId*>	[0..1]	Text		296
	TaxType <*TaxTp*>	[0..1]	Text		296
	Debtor <*Dbtr*>	[0..1]			297
	TaxIdentification <*TaxId*>	[0..1]	Text		297
	RegistrationIdentification <*RegnId*>	[0..1]	Text		297
	TaxType <*TaxTp*>	[0..1]	Text		297
	Authorisation <*Authstn*>	[0..1]			297
	Title <*Titl*>	[0..1]	Text		298
	Name <*Nm*>	[0..1]	Text		298
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		298
	ReferenceNumber <*RefNb*>	[0..1]	Text		298
	Method <*Mtd*>	[0..1]	Text		298
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	298
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	299
	Date <*Dt*>	[0..1]	Date		299
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		299
	Record <*Rcrd*>	[0..*]			299
	Type <*Tp*>	[0..1]	Text		300
	Category <*Ctgy*>	[0..1]	Text		300
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		301
	DebtorStatus <*DbtrSts*>	[0..1]	Text		301
	CertificateIdentification <*CertId*>	[0..1]	Text		301
	FormsCode <*FrmsCd*>	[0..1]	Text		301
	Period <*Prd*>	[0..1]			301
	Year <*Yr*>	[0..1]	Date		301

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]	CodeSet		302
	FromToDate <*FrToDt*>	[0..1]			302
	FromDate <*FrDt*>	[1..1]	Date		303
	ToDate <*ToDt*>	[1..1]	Date		303
	TaxAmount <*TaxAmt*>	[0..1]			303
	Rate <*Rate*>	[0..1]	Rate		303
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	304
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	304
	Details <*Dtls*>	[0..*]			304
	Period <*Prd*>	[0..1]			305
	Year <*Yr*>	[0..1]	Date		305
	Type <*Tp*>	[0..1]	CodeSet		305
	FromToDate <*FrToDt*>	[0..1]			306
	FromDate <*FrDt*>	[1..1]	Date		306
	ToDate <*ToDt*>	[1..1]	Date		307
	Amount <*Amt*>	[1..1]	Amount	C2, C20	307
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		307
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		307
	RemittanceInformation <*RmtInf*>	[0..1]			308
	Unstructured <*Ustrd*>	[0..*]	Text		308
	Structured <*Strd*>	[0..*]			308
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			309
	Type <*Tp*>	[0..1]			309
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			310
{Or	Code <*Cd*>	[1..1]	CodeSet		310
Or}	Proprietary <*Prtry*>	[1..1]	Text		311
	Issuer <*Issr*>	[0..1]	Text		311
	Number <*Nb*>	[0..1]	Text		311
	RelatedDate <*RltdDt*>	[0..1]	Date		311
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		311
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		312

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Invoicer <*Invcr*>	[0..1]	±		313
	Invoicee <*Invcee*>	[0..1]	±		313
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		314

Constraints

- **InstructionForCreditorAgentRule**

  If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

```
On Condition
    /CreditorAccount is present
 And    /InstructionForCreditorAgent[1] is present
Following Must be True
    /InstructionForCreditorAgent[*]/Code Must be within DataType <<Code>>
PartialInstruction3Code
```

- **IntermediaryAgent2Rule**

  If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

```
On Condition
    /IntermediaryAgent2 is present
Following Must be True
    /IntermediaryAgent1 Must be present
```

- **IntermediaryAgent3Rule**

  If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

```
On Condition
    /IntermediaryAgent3 is present
Following Must be True
    /IntermediaryAgent2 Must be present
```

- **UltimateCreditorGuideline**

  UltimateCreditor may only be present if different from Creditor.

- **UltimateDebtorGuideline**

  UltimateDebtor may only be present if different from Debtor.

13.1.17.1.1.1 PaymentIdentification <PmtId>

Presence: [1..1]

Definition: Set of elements used to reference a payment instruction.

PaymentIdentification <PmtId> contains the following elements (see "PaymentIdentification1" on page 173 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionIdentification <*InstrId*>	[0..1]	Text		173
	EndToEndIdentification <*EndToEndId*>	[1..1]	Text		173

13.1.17.1.1.2 PaymentTypeInformation <PmtTpInf>

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

PaymentTypeInformation <PmtTpInf> contains the following elements (see "PaymentTypeInformation19" on page 260 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		260
	ServiceLevel <*SvcLvl*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		261
	LocalInstrument <*LclInstrm*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		262
	CategoryPurpose <*CtgyPurp*>	[0..1]			262
{Or	Code <*Cd*>	[1..1]	CodeSet		262
Or}	Proprietary <*Prtry*>	[1..1]	Text		262

13.1.17.1.1.3 TaxRateMarker <TaxRateMrkr>

Presence: [0..1]

Definition: Specifies the rate of tax levied.

Datatype: "TaxRateMarker1Code" on page 374

CodeName	Name	Definition
ALPR	AmountQuotedLessLifeAssurance	Specifies the amount quoted less life assurance premium rate income tax.
ALIT	AmountQuotedLessStandardRate	Specifies the amount quoted less standard rate income tax.
GRSS	GrossAmount	Specifies an amount before the deduction of tax.

13.1.17.1.1.4 Amount <Amt>

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Impacted by: C1 "ActiveCurrency", C19 "CurrencyAmount"

Datatype: "ActiveCurrencyAndAmount" on page 359

Constraints

- **ActiveCurrency**

  The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217

Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.1.5 ChargeBearer <ChrgBr>

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: "ChargeBearerType1Code" on page 362

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

13.1.17.1.1.6 ChequeInstruction <ChqInstr>

Presence: [0..1]

Definition: Set of elements needed to issue a cheque.

Impacted by: C16 "ChequeMaturityDateRule"

ChequeInstruction <ChqInstr> contains the following elements (see "Cheque7" on page 153 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ChequeType <*ChqTp*>	[0..1]	CodeSet		154
	ChequeNumber <*ChqNb*>	[0..1]	Text		154
	ChequeFrom <*ChqFr*>	[0..1]			155
	Name <*Nm*>	[1..1]	Text		155
	Address <*Adr*>	[1..1]	±		155
	DeliveryMethod <*DlvryMtd*>	[0..1]			155
{Or	Code <*Cd*>	[1..1]	CodeSet		156
Or}	Proprietary <*Prtry*>	[1..1]	Text		156
	DeliverTo <*DlvrTo*>	[0..1]			156
	Name <*Nm*>	[1..1]	Text		157
	Address <*Adr*>	[1..1]	±		157
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		157
	ChequeMaturityDate <*ChqMtrtyDt*>	[0..1]	Date		158
	FormsCode <*FrmsCd*>	[0..1]	Text		158
	MemoField <*MemoFld*>	[0..2]	Text		158
	RegionalClearingZone <*RgnlClrZone*>	[0..1]	Text		158
	PrintLocation <*PrtLctn*>	[0..1]	Text		158
	Signature <*Sgntr*>	[0..5]	Text		158

Constraints

- **ChequeMaturityDateRule**

  If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

```
On Condition
    /ChequeType is present
 And    /ChequeType is within DataType <<Code>> ChequeType3Code
Following Must be True
    /ChequeMaturityDate Must be absent
```

13.1.17.1.1.7 Frequency <Frqcy>

Presence: [0..1]

Definition: The schedule for a credit payment arrangement.

Frequency <Frqcy> contains the following **Frequency1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Sequence <*Seq*>	[0..1]	Text		287
	StartDate <*StartDt*>	[1..1]	Date		287
	EndPointChoice <*EndPtChc*>	[1..1]			287
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		287
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		287
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		288
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		288

13.1.17.1.1.7.1 Sequence <Seq>

Presence: [0..1]

Definition: Technical identifier of a Credit Transfer as part of a series of Credit Transfers within a single Payment Instruction. Assists the transfer of complex variable future payment schedules, associated with a single act of customer consent, within a single Payment Instruction.

Datatype: "Max3NumericText" on page 381

13.1.17.1.1.7.2 StartDate <StartDt>

Presence: [1..1]

Definition: The date of the first payment to be made for this payment schedule.

Datatype: "ISODate" on page 376

13.1.17.1.1.7.3 EndPointChoice <EndPtChc>

Presence: [1..1]

Definition: Information about when the payment arrangement will end.

EndPointChoice <EndPtChc> contains one of the following **EndPoint1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		287
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		287

13.1.17.1.1.7.3.1 NumberOfPayments <NbOfPmts>

Presence: [0..1]

Definition: Number of the payments that will be made in completing this frequency sequence including any executed since the sequence start date.

Datatype: "Max35Text" on page 381

13.1.17.1.1.7.3.2 LastPaymentDate <LastPmtDt>

Presence: [0..1]

Definition: Final payment of the standing order due.

Datatype: "ISODate" on page 376

13.1.17.1.1.7.4 RequestedFrequencyPattern <ReqdFrqcyPttrn>

Presence: [0..1]

Definition: Payment schedule frequency pattern which indicates how frequently a payment is made.

RequestedFrequencyPattern <ReqdFrqcyPttrn> contains one of the following elements (see "Frequency37Choice" on page 175 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		175
Or}	Proprietary <*Prtry*>	[1..1]	Text		176

13.1.17.1.1.7.5 NonWorkingDayAdjustment <NonWorkgDayAdjstmnt>

Presence: [0..1]

Definition: Adjustment indicator for a non-working day to enable payment to be made on the next working day.

Datatype: "BusinessDayConvention1Code" on page 361

CodeName	Name	Definition
FWNG	Following	The date will be the first following day that is a business day.
PREC	Preceding	The date will be the first preceding day that is a business day.

13.1.17.1.1.8 TransferInstruction <TrfInstr>

Presence: [0..1]

Definition: Provides further information about the status of transferred scheduled payment(s).

TransferInstruction <TrfInstr> contains the following **TransferInstruction1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		288
	Code <*Cd*>	[1..1]	Text		289
	Proprietary <*Prtry*>	[0..1]	Text		289
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		289
	StartDate <*StartDt*>	[0..1]	Date		289
	Description <*Desc*>	[0..1]	Text		289

13.1.17.1.1.8.1 TransferIndicator <TrfInd>

Presence: [0..1]

Definition: Indicates whether a payment arrangement is transferable.

Usage: Default value for TransferIndicator is false.

Datatype: One of the following values must be used (see "YesNoIndicator" on page 378):

- *Meaning When True:* Yes
- *Meaning When False:* No

13.1.17.1.1.8.2 Code <Cd>

Presence: [1..1]

Definition: Specifies an additional parameter to be applied to the requested transaction schedule.

Datatype: "Max35Text" on page 381

13.1.17.1.1.8.3 Proprietary <Prtry>

Presence: [0..1]

Definition: Specifies an additional parameter to be applied to the transaction schedule in a proprietary format.

Datatype: "Max256Text" on page 380

13.1.17.1.1.8.4 StartDateTime <StartDtTm>

Presence: [0..1]

Definition: The date and time at which the event specified by Code commences.

Datatype: "ISODateTime" on page 376

13.1.17.1.1.8.5 StartDate <StartDt>

Presence: [0..1]

Definition: The date on which the event specified by Code commences.

Datatype: "ISODate" on page 376

13.1.17.1.1.8.6 Description <Desc>

Presence: [0..1]

Definition: Additional switch parameters in a free text format.

Datatype: "Max350Text" on page 380

13.1.17.1.1.9 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

UltimateDebtor <UltmtDbtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.17.1.1.10 IntermediaryAgent1 <IntrmyAgt1>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

IntermediaryAgent1 <IntrmyAgt1> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.17.1.1.11 IntermediaryAgent2 <IntrmyAgt2>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

IntermediaryAgent2 <IntrmyAgt2> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.17.1.1.12 IntermediaryAgent3 <IntrmyAgt3>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

IntermediaryAgent3 <IntrmyAgt3> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.17.1.1.13 CreditorAgent <CdtrAgt>

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

CreditorAgent <CdtrAgt> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.17.1.1.14 Creditor <Cdtr>

Presence: [0..1]

Definition: Party to which an amount of money is due.

Creditor <Cdtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.17.1.1.15 CreditorAccount <CdtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

CreditorAccount <CdtrAcct> contains the following elements (see "CashAccount24" on page 146 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		146
	Type <*Tp*>	[0..1]	±		146
	Currency <*Ccy*>	[0..1]	CodeSet	C2	147
	Name <*Nm*>	[0..1]	Text		147

13.1.17.1.1.16 UltimateCreditor <UltmtCdtr>

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

UltimateCreditor <UltmtCdtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.17.1.1.17 InstructionForCreditorAgent <InstrForCdtrAgt>

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

InstructionForCreditorAgent <InstrForCdtrAgt> contains the following elements (see "InstructionForCreditorAgent1" on page 212 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Code <*Cd*>	[0..1]	CodeSet		212
	InstructionInformation <*InstrInf*>	[0..1]	Text		213

13.1.17.1.1.18 Purpose <Purp>

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

Purpose <Purp> contains one of the following **Purpose2Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		293
Or}	Proprietary <*Prtry*>	[1..1]	Text		293

13.1.17.1.1.18.1 Code <Cd>

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: "ExternalPurpose1Code" on page 368

13.1.17.1.1.18.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: "Max35Text" on page 381

13.1.17.1.1.19 RegulatoryReporting <RgltryRptg>

Presence: [0..10]

Definition: Information needed due to regulatory and statutory requirements.

RegulatoryReporting <RgltryRptg> contains the following elements (see "RegulatoryReporting3" on page 269 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DebitCreditReportingIndicator <*DbtCdtRptgInd*>	[0..1]	CodeSet		269
	Authority <*Authrty*>	[0..1]			270
	Name <*Nm*>	[0..1]	Text		270
	Country <*Ctry*>	[0..1]	CodeSet	C18	270
	Details <*Dtls*>	[0..*]			270
	Type <*Tp*>	[0..1]	Text		271
	Date <*Dt*>	[0..1]	Date		271
	Country <*Ctry*>	[0..1]	CodeSet	C18	271
	Code <*Cd*>	[0..1]	Text		271
	Amount <*Amt*>	[0..1]	Amount	C2, C20	271
	Information <*Inf*>	[0..*]	Text		272

13.1.17.1.1.20 Tax <Tax>

Presence: [0..1]

Definition: Provides details on the tax.

Tax <Tax> contains the following **TaxInformation6** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Creditor <*Cdtr*>	[0..1]			296
	TaxIdentification <*TaxId*>	[0..1]	Text		296
	RegistrationIdentification <*RegnId*>	[0..1]	Text		296
	TaxType <*TaxTp*>	[0..1]	Text		296
	Debtor <*Dbtr*>	[0..1]			297
	TaxIdentification <*TaxId*>	[0..1]	Text		297
	RegistrationIdentification <*RegnId*>	[0..1]	Text		297
	TaxType <*TaxTp*>	[0..1]	Text		297
	Authorisation <*Authstn*>	[0..1]			297
	Title <*Titl*>	[0..1]	Text		298
	Name <*Nm*>	[0..1]	Text		298
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		298
	ReferenceNumber <*RefNb*>	[0..1]	Text		298
	Method <*Mtd*>	[0..1]	Text		298
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	298
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	299
	Date <*Dt*>	[0..1]	Date		299
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		299
	Record <*Rcrd*>	[0..*]			299
	Type <*Tp*>	[0..1]	Text		300
	Category <*Ctgy*>	[0..1]	Text		300
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		301
	DebtorStatus <*DbtrSts*>	[0..1]	Text		301
	CertificateIdentification <*CertId*>	[0..1]	Text		301
	FormsCode <*FrmsCd*>	[0..1]	Text		301
	Period <*Prd*>	[0..1]			301
	Year <*Yr*>	[0..1]	Date		301
	Type <*Tp*>	[0..1]	CodeSet		302
	FromToDate <*FrToDt*>	[0..1]			302
	FromDate <*FrDt*>	[1..1]	Date		303
	ToDate <*ToDt*>	[1..1]	Date		303

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxAmount <*TaxAmt*>	[0..1]			303
	Rate <*Rate*>	[0..1]	Rate		303
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	304
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	304
	Details <*Dtls*>	[0..*]			304
	Period <*Prd*>	[0..1]			305
	Year <*Yr*>	[0..1]	Date		305
	Type <*Tp*>	[0..1]	CodeSet		305
	FromToDate <*FrToDt*>	[0..1]			306
	FromDate <*FrDt*>	[1..1]	Date		306
	ToDate <*ToDt*>	[1..1]	Date		307
	Amount <*Amt*>	[1..1]	Amount	C2, C20	307
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		307

13.1.17.1.1.20.1 Creditor <Cdtr>

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

Creditor <Cdtr> contains the following **TaxParty1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxIdentification <*TaxId*>	[0..1]	Text		296
	RegistrationIdentification <*RegnId*>	[0..1]	Text		296
	TaxType <*TaxTp*>	[0..1]	Text		296

13.1.17.1.1.20.1.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.1.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.1.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Set of elements used to identify the party on the debit side of the transaction to which the tax applies.

Debtor <Dbtr> contains the following **TaxParty2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxIdentification <*TaxId*>	[0..1]	Text		297
	RegistrationIdentification <*RegnId*>	[0..1]	Text		297
	TaxType <*TaxTp*>	[0..1]	Text		297
	Authorisation <*Authstn*>	[0..1]			297
	Title <*Titl*>	[0..1]	Text		298
	Name <*Nm*>	[0..1]	Text		298

13.1.17.1.1.20.2.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.2.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.2.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.2.4 Authorisation <Authstn>

Presence: [0..1]

Definition: Details of the authorised tax paying party.

Authorisation <Authstn> contains the following **TaxAuthorisation1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Title <*Titl*>	[0..1]	Text		298
	Name <*Nm*>	[0..1]	Text		298

13.1.17.1.1.20.2.4.1 Title <Titl>

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.2.4.2 Name <Nm>

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: "Max140Text" on page 379

13.1.17.1.1.20.3 AdministrationZone <AdmstnZn>

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.4 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "Max140Text" on page 379

13.1.17.1.1.20.5 Method <Mtd>

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.6 TotalTaxableBaseAmount <TtlTaxblBaseAmt>

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.1.20.7 TotalTaxAmount <TtlTaxAmt>

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.1.20.8 Date <Dt>

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: "ISODate" on page 376

13.1.17.1.1.20.9 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: "Number" on page 378

13.1.17.1.1.20.10 Record <Rcrd>

Presence: [0..*]

Definition: Record of tax details.

Record <Rcrd> contains the following **TaxRecord2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]	Text		300
	Category <*Ctgy*>	[0..1]	Text		300
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		301
	DebtorStatus <*DbtrSts*>	[0..1]	Text		301
	CertificateIdentification <*CertId*>	[0..1]	Text		301
	FormsCode <*FrmsCd*>	[0..1]	Text		301
	Period <*Prd*>	[0..1]			301
	Year <*Yr*>	[0..1]	Date		301
	Type <*Tp*>	[0..1]	CodeSet		302
	FromToDate <*FrToDt*>	[0..1]			302
	FromDate <*FrDt*>	[1..1]	Date		303
	ToDate <*ToDt*>	[1..1]	Date		303
	TaxAmount <*TaxAmt*>	[0..1]			303
	Rate <*Rate*>	[0..1]	Rate		303
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	304
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	304
	Details <*Dtls*>	[0..*]			304
	Period <*Prd*>	[0..1]			305
	Year <*Yr*>	[0..1]	Date		305
	Type <*Tp*>	[0..1]	CodeSet		305
	FromToDate <*FrToDt*>	[0..1]			306
	FromDate <*FrDt*>	[1..1]	Date		306
	ToDate <*ToDt*>	[1..1]	Date		307
	Amount <*Amt*>	[1..1]	Amount	C2, C20	307
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		307

13.1.17.1.1.20.10.1 Type <Tp>

Presence: [0..1]

Definition: High level code to identify the type of tax details.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.10.2 Category <Ctgy>

Presence: [0..1]

Definition: Specifies the tax code as published by the tax authority.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.10.3 CategoryDetails <CtgyDtls>

Presence: [0..1]

Definition: Provides further details of the category tax code.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.10.4 DebtorStatus <DbtrSts>

Presence: [0..1]

Definition: Code provided by local authority to identify the status of the party that has drawn up the settlement document.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.10.5 CertificateIdentification <CertId>

Presence: [0..1]

Definition: Identification number of the tax report as assigned by the taxing authority.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.10.6 FormsCode <FrmsCd>

Presence: [0..1]

Definition: Identifies, in a coded form, on which template the tax report is to be provided.

Datatype: "Max35Text" on page 381

13.1.17.1.1.20.10.7 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following **TaxPeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		301
	Type <*Tp*>	[0..1]	CodeSet		302
	FromToDate <*FrToDt*>	[0..1]			302
	FromDate <*FrDt*>	[1..1]	Date		303
	ToDate <*ToDt*>	[1..1]	Date		303

13.1.17.1.1.20.10.7.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 376

13.1.17.1.1.20.10.7.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 375

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

13.1.17.1.1.20.10.7.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following **DatePeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FromDate <*FrDt*>	[1..1]	Date		303
	ToDate <*ToDt*>	[1..1]	Date		303

13.1.17.1.1.20.10.7.3.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: "ISODate" on page 376

13.1.17.1.1.20.10.7.3.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: "ISODate" on page 376

13.1.17.1.1.20.10.8 TaxAmount <TaxAmt>

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

TaxAmount <TaxAmt> contains the following **TaxAmount2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Rate <*Rate*>	[0..1]	Rate		303
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	304
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	304
	Details <*Dtls*>	[0..*]			304
	Period <*Prd*>	[0..1]			305
	Year <*Yr*>	[0..1]	Date		305
	Type <*Tp*>	[0..1]	CodeSet		305
	FromToDate <*FrToDt*>	[0..1]			306
	FromDate <*FrDt*>	[1..1]	Date		306
	ToDate <*ToDt*>	[1..1]	Date		307
	Amount <*Amt*>	[1..1]	Amount	C2, C20	307

13.1.17.1.1.20.10.8.1 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: "PercentageRate" on page 378

13.1.17.1.1.20.10.8.2 TaxableBaseAmount <TaxblBaseAmt>

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.1.20.10.8.3 TotalAmount <TtlAmt>

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.1.20.10.8.4 Details <Dtls>

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

Details <Dtls> contains the following **TaxRecordDetails2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Period <*Prd*>	[0..1]			305
	Year <*Yr*>	[0..1]	Date		305
	Type <*Tp*>	[0..1]	CodeSet		305
	FromToDate <*FrToDt*>	[0..1]			306
	FromDate <*FrDt*>	[1..1]	Date		306
	ToDate <*ToDt*>	[1..1]	Date		307
	Amount <*Amt*>	[1..1]	Amount	C2, C20	307

13.1.17.1.1.20.10.8.4.1 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following **TaxPeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		305
	Type <*Tp*>	[0..1]	CodeSet		305
	FromToDate <*FrToDt*>	[0..1]			306
	FromDate <*FrDt*>	[1..1]	Date		306
	ToDate <*ToDt*>	[1..1]	Date		307

13.1.17.1.1.20.10.8.4.1.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 376

13.1.17.1.1.20.10.8.4.1.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 375

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.

CodeName	Name	Definition
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

13.1.17.1.1.20.10.8.4.1.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following **DatePeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FromDate <*FrDt*>	[1..1]	Date		306
	ToDate <*ToDt*>	[1..1]	Date		307

13.1.17.1.1.20.10.8.4.1.3.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: "ISODate" on page 376

13.1.17.1.1.20.10.8.4.1.3.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: "ISODate" on page 376

13.1.17.1.1.20.10.8.4.2 Amount <Amt>

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.1.20.10.9 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: "Max140Text" on page 379

13.1.17.1.1.21 RelatedRemittanceInformation <RltdRmtInf>

Presence: [0..10]

Definition: Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain.

RelatedRemittanceInformation <RltdRmtInf> contains the following elements (see "RemittanceLocation2" on page 173 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	RemittanceIdentification <*RmtId*>	[0..1]	Text		174
	RemittanceLocationMethod <*RmtLctnMtd*>	[0..1]	CodeSet		174
	RemittanceLocationElectronicAddress <*RmtLctnElctrncAdr*>	[0..1]	Text		174
	RemittanceLocationPostalAddress <*RmtLctnPstlAdr*>	[0..1]			174
	Name <*Nm*>	[1..1]	Text		175
	Address <*Adr*>	[1..1]	±		175

13.1.17.1.1.22 RemittanceInformation <RmtInf>

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

RemittanceInformation <RmtInf> contains the following **RemittanceInformation14** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Unstructured <*Ustrd*>	[0..*]	Text		308
	Structured <*Strd*>	[0..*]			308
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			309
	Type <*Tp*>	[0..1]			309
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			310
{Or	Code <*Cd*>	[1..1]	CodeSet		310
Or}	Proprietary <*Prtry*>	[1..1]	Text		311
	Issuer <*Issr*>	[0..1]	Text		311
	Number <*Nb*>	[0..1]	Text		311
	RelatedDate <*RltdDt*>	[0..1]	Date		311
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		311
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		312
	Invoicer <*Invcr*>	[0..1]	±		313
	Invoicee <*Invcee*>	[0..1]	±		313
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		314

13.1.17.1.1.22.1 Unstructured <Ustrd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: "Max140Text" on page 379

13.1.17.1.1.22.2 Structured <Strd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

Structured <Strd> contains the following **StructuredRemittanceInformation14** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			309
	Type <*Tp*>	[0..1]			309
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			310
{Or	Code <*Cd*>	[1..1]	CodeSet		310
Or}	Proprietary <*Prtry*>	[1..1]	Text		311
	Issuer <*Issr*>	[0..1]	Text		311
	Number <*Nb*>	[0..1]	Text		311
	RelatedDate <*RltdDt*>	[0..1]	Date		311
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		311
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		312
	Invoicer <*Invcr*>	[0..1]	±		313
	Invoicee <*Invcee*>	[0..1]	±		313
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		314

13.1.17.1.1.22.2.1 ReferredDocumentInformation <RfrdDocInf>

Presence: [0..*]

Definition: Set of elements used to identify the documents referred to in the remittance information.

ReferredDocumentInformation <RfrdDocInf> contains the following **ReferredDocumentInformation3** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			309
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			310
{Or	Code <*Cd*>	[1..1]	CodeSet		310
Or}	Proprietary <*Prtry*>	[1..1]	Text		311
	Issuer <*Issr*>	[0..1]	Text		311
	Number <*Nb*>	[0..1]	Text		311
	RelatedDate <*RltdDt*>	[0..1]	Date		311

13.1.17.1.1.22.2.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of referred document.

Type <Tp> contains the following **ReferredDocumentType2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			310
{Or	Code <*Cd*>	[1..1]	CodeSet		310
Or}	Proprietary <*Prtry*>	[1..1]	Text		311
	Issuer <*Issr*>	[0..1]	Text		311

13.1.17.1.1.22.2.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the referred document.

CodeOrProprietary <CdOrPrtry> contains one of the following **ReferredDocumentType1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		310
Or}	Proprietary <*Prtry*>	[1..1]	Text		311

13.1.17.1.1.22.2.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: "DocumentType5Code" on page 364

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and

CodeName	Name	Definition
		conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.

13.1.17.1.1.22.2.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: "Max35Text" on page 381

13.1.17.1.1.22.2.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "Max35Text" on page 381

13.1.17.1.1.22.2.1.2 Number <Nb>

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: "Max35Text" on page 381

13.1.17.1.1.22.2.1.3 RelatedDate <RltdDt>

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: "ISODate" on page 376

13.1.17.1.1.22.2.2 ReferredDocumentAmount <RfrdDocAmt>

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

ReferredDocumentAmount <RfrdDocAmt> contains the following elements (see "RemittanceAmount2" on page 177 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DuePayableAmount <*DuePyblAmt*>	[0..1]	Amount	C2, C20	178
	DiscountAppliedAmount <*DscntApldAmt*>	[0..*]			179
	Type <*Tp*>	[0..1]			179
{Or	Code <*Cd*>	[1..1]	CodeSet		179
Or}	Proprietary <*Prtry*>	[1..1]	Text		179
	Amount <*Amt*>	[1..1]	Amount	C2, C20	179
	CreditNoteAmount <*CdtNoteAmt*>	[0..1]	Amount	C2, C20	180
	TaxAmount <*TaxAmt*>	[0..*]			180
	Type <*Tp*>	[0..1]			180
{Or	Code <*Cd*>	[1..1]	CodeSet		181
Or}	Proprietary <*Prtry*>	[1..1]	Text		181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	181
	AdjustmentAmountAndReason <*AdjstmntAmtAndRsn*>	[0..*]			181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	182
	CreditDebitIndicator <*CdtDbtInd*>	[0..1]	CodeSet		182
	Reason <*Rsn*>	[0..1]	Text		182
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		182
	RemittedAmount <*RmtdAmt*>	[0..1]	Amount	C2, C20	183

13.1.17.1.1.22.2.3 CreditorReferenceInformation <CdtrRefInf>

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

CreditorReferenceInformation <CdtrRefInf> contains the following elements (see "CreditorReferenceInformation2" on page 162 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			162
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			162
{Or	Code <*Cd*>	[1..1]	CodeSet		163
Or}	Proprietary <*Prtry*>	[1..1]	Text		163
	Issuer <*Issr*>	[0..1]	Text		163
	Reference <*Ref*>	[0..1]	Text		163

13.1.17.1.1.22.2.4 Invoicer <Invcr>

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

Invoicer <Invcr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.17.1.1.22.2.5 Invoicee <Invcee>

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

Invoicee <Invcee> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.17.1.1.22.2.6 AdditionalRemittanceInformation <AddtlRmtInf>

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: "Max140Text" on page 379

13.1.17.1.2 Debit <Dbt>

Presence: [1..1]

Definition: Specifies details of the payment to be made by the new account servicer to the old account servicer in case of a negative closing balance.

Impacted by: C22 "InstructionForCreditorAgentRule", C23 "IntermediaryAgent2Rule", C24 "IntermediaryAgent3Rule", C28 "UltimateCreditorGuideline", C30 "UltimateDebtorGuideline"

Debit <Dbt> contains the following **CreditTransferTransaction27** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	PaymentIdentification <*PmtId*>	[1..1]	±		318
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		318
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		319
	Amount <*Amt*>	[1..1]	Amount	C1, C19	319
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		320
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C16	320
	Frequency <*Frqcy*>	[0..1]			321
	Sequence <*Seq*>	[0..1]	Text		322
	StartDate <*StartDt*>	[1..1]	Date		322
	EndPointChoice <*EndPtChc*>	[1..1]			322
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		322
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		322
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		323
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		323
	TransferInstruction <*TrfInstr*>	[0..1]			323
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		323
	Code <*Cd*>	[1..1]	Text		324
	Proprietary <*Prtry*>	[0..1]	Text		324
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		324
	StartDate <*StartDt*>	[0..1]	Date		324
	Description <*Desc*>	[0..1]	Text		324
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		324
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		325
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		325
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		325
	CreditorAgent <*CdtrAgt*>	[1..1]	±		326
	Creditor <*Cdtr*>	[0..1]	±		326
	CreditorAccount <*CdtrAcct*>	[0..1]	±		326
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		327
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		327
	Purpose <*Purp*>	[0..1]			327

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		328
Or}	Proprietary <*Prtry*>	[1..1]	Text		328
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		328
	Tax <*Tax*>	[0..1]			329
	Creditor <*Cdtr*>	[0..1]			331
	TaxIdentification <*TaxId*>	[0..1]	Text		331
	RegistrationIdentification <*RegnId*>	[0..1]	Text		331
	TaxType <*TaxTp*>	[0..1]	Text		331
	Debtor <*Dbtr*>	[0..1]			332
	TaxIdentification <*TaxId*>	[0..1]	Text		332
	RegistrationIdentification <*RegnId*>	[0..1]	Text		332
	TaxType <*TaxTp*>	[0..1]	Text		332
	Authorisation <*Authstn*>	[0..1]			332
	Title <*Titl*>	[0..1]	Text		333
	Name <*Nm*>	[0..1]	Text		333
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		333
	ReferenceNumber <*RefNb*>	[0..1]	Text		333
	Method <*Mtd*>	[0..1]	Text		333
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	333
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	334
	Date <*Dt*>	[0..1]	Date		334
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		334
	Record <*Rcrd*>	[0..*]			334
	Type <*Tp*>	[0..1]	Text		335
	Category <*Ctgy*>	[0..1]	Text		335
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		336
	DebtorStatus <*DbtrSts*>	[0..1]	Text		336
	CertificateIdentification <*CertId*>	[0..1]	Text		336
	FormsCode <*FrmsCd*>	[0..1]	Text		336
	Period <*Prd*>	[0..1]			336
	Year <*Yr*>	[0..1]	Date		336

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]	CodeSet		337
	FromToDate <*FrToDt*>	[0..1]			337
	FromDate <*FrDt*>	[1..1]	Date		338
	ToDate <*ToDt*>	[1..1]	Date		338
	TaxAmount <*TaxAmt*>	[0..1]			338
	Rate <*Rate*>	[0..1]	Rate		338
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	339
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	339
	Details <*Dtls*>	[0..*]			339
	Period <*Prd*>	[0..1]			340
	Year <*Yr*>	[0..1]	Date		340
	Type <*Tp*>	[0..1]	CodeSet		340
	FromToDate <*FrToDt*>	[0..1]			341
	FromDate <*FrDt*>	[1..1]	Date		341
	ToDate <*ToDt*>	[1..1]	Date		342
	Amount <*Amt*>	[1..1]	Amount	C2, C20	342
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		342
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		342
	RemittanceInformation <*RmtInf*>	[0..1]			343
	Unstructured <*Ustrd*>	[0..*]	Text		343
	Structured <*Strd*>	[0..*]			343
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			344
	Type <*Tp*>	[0..1]			344
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			345
{Or	Code <*Cd*>	[1..1]	CodeSet		345
Or}	Proprietary <*Prtry*>	[1..1]	Text		346
	Issuer <*Issr*>	[0..1]	Text		346
	Number <*Nb*>	[0..1]	Text		346
	RelatedDate <*RltdDt*>	[0..1]	Date		346
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		346
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		347

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Invoicer <*Invcr*>	[0..1]	±		348
	Invoicee <*Invcee*>	[0..1]	±		348
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		349

Constraints

- **InstructionForCreditorAgentRule**

  If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

```
On Condition
    /CreditorAccount is present
 And    /InstructionForCreditorAgent[1] is present
Following Must be True
    /InstructionForCreditorAgent[*]/Code Must be within DataType <<Code>>
PartialInstruction3Code
```

- **IntermediaryAgent2Rule**

  If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

```
On Condition
    /IntermediaryAgent2 is present
Following Must be True
    /IntermediaryAgent1 Must be present
```

- **IntermediaryAgent3Rule**

  If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

```
On Condition
    /IntermediaryAgent3 is present
Following Must be True
    /IntermediaryAgent2 Must be present
```

- **UltimateCreditorGuideline**

  UltimateCreditor may only be present if different from Creditor.

- **UltimateDebtorGuideline**

  UltimateDebtor may only be present if different from Debtor.

13.1.17.1.2.1 PaymentIdentification <PmtId>

Presence: [1..1]

Definition: Set of elements used to reference a payment instruction.

PaymentIdentification <PmtId> contains the following elements (see "PaymentIdentification1" on page 173 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionIdentification <*InstrId*>	[0..1]	Text		173
	EndToEndIdentification <*EndToEndId*>	[1..1]	Text		173

13.1.17.1.2.2 PaymentTypeInformation <PmtTpInf>

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

PaymentTypeInformation <PmtTpInf> contains the following elements (see "PaymentTypeInformation19" on page 260 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		260
	ServiceLevel <*SvcLvl*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		261
	LocalInstrument <*LclInstrm*>	[0..1]			261
{Or	Code <*Cd*>	[1..1]	CodeSet		261
Or}	Proprietary <*Prtry*>	[1..1]	Text		262
	CategoryPurpose <*CtgyPurp*>	[0..1]			262
{Or	Code <*Cd*>	[1..1]	CodeSet		262
Or}	Proprietary <*Prtry*>	[1..1]	Text		262

13.1.17.1.2.3 TaxRateMarker <TaxRateMrkr>

Presence: [0..1]

Definition: Specifies the rate of tax levied.

Datatype: "TaxRateMarker1Code" on page 374

CodeName	Name	Definition
ALPR	AmountQuotedLessLifeAssurance	Specifies the amount quoted less life assurance premium rate income tax.
ALIT	AmountQuotedLessStandardRate	Specifies the amount quoted less standard rate income tax.
GRSS	GrossAmount	Specifies an amount before the deduction of tax.

13.1.17.1.2.4 Amount <Amt>

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Impacted by: C1 "ActiveCurrency", C19 "CurrencyAmount"

Datatype: "ActiveCurrencyAndAmount" on page 359

Constraints

- **ActiveCurrency**

  The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217

Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.2.5 ChargeBearer <ChrgBr>

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: "ChargeBearerType1Code" on page 362

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

13.1.17.1.2.6 ChequeInstruction <ChqInstr>

Presence: [0..1]

Definition: Set of elements needed to issue a cheque.

Impacted by: C16 "ChequeMaturityDateRule"

ChequeInstruction <ChqInstr> contains the following elements (see "Cheque7" on page 153 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ChequeType <*ChqTp*>	[0..1]	CodeSet		154
	ChequeNumber <*ChqNb*>	[0..1]	Text		154
	ChequeFrom <*ChqFr*>	[0..1]			155
	Name <*Nm*>	[1..1]	Text		155
	Address <*Adr*>	[1..1]	±		155
	DeliveryMethod <*DlvryMtd*>	[0..1]			155
{Or	Code <*Cd*>	[1..1]	CodeSet		156
Or}	Proprietary <*Prtry*>	[1..1]	Text		156
	DeliverTo <*DlvrTo*>	[0..1]			156
	Name <*Nm*>	[1..1]	Text		157
	Address <*Adr*>	[1..1]	±		157
	InstructionPriority <*InstrPrty*>	[0..1]	CodeSet		157
	ChequeMaturityDate <*ChqMtrtyDt*>	[0..1]	Date		158
	FormsCode <*FrmsCd*>	[0..1]	Text		158
	MemoField <*MemoFld*>	[0..2]	Text		158
	RegionalClearingZone <*RgnlClrZone*>	[0..1]	Text		158
	PrintLocation <*PrtLctn*>	[0..1]	Text		158
	Signature <*Sgntr*>	[0..5]	Text		158

Constraints

- **ChequeMaturityDateRule**

  If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or ELDR.

```
On Condition
    /ChequeType is present
 And    /ChequeType is within DataType <<Code>> ChequeType3Code
Following Must be True
    /ChequeMaturityDate Must be absent
```

13.1.17.1.2.7 Frequency <Frqcy>

Presence: [0..1]

Definition: The schedule for a credit payment arrangement.

Frequency <Frqcy> contains the following **Frequency1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Sequence <*Seq*>	[0..1]	Text		322
	StartDate <*StartDt*>	[1..1]	Date		322
	EndPointChoice <*EndPtChc*>	[1..1]			322
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		322
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		322
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		323
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		323

13.1.17.1.2.7.1 Sequence <Seq>

Presence: [0..1]

Definition: Technical identifier of a Credit Transfer as part of a series of Credit Transfers within a single Payment Instruction. Assists the transfer of complex variable future payment schedules, associated with a single act of customer consent, within a single Payment Instruction.

Datatype: "Max3NumericText" on page 381

13.1.17.1.2.7.2 StartDate <StartDt>

Presence: [1..1]

Definition: The date of the first payment to be made for this payment schedule.

Datatype: "ISODate" on page 376

13.1.17.1.2.7.3 EndPointChoice <EndPtChc>

Presence: [1..1]

Definition: Information about when the payment arrangement will end.

EndPointChoice <EndPtChc> contains one of the following **EndPoint1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		322
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		322

13.1.17.1.2.7.3.1 NumberOfPayments <NbOfPmts>

Presence: [0..1]

Definition: Number of the payments that will be made in completing this frequency sequence including any executed since the sequence start date.

Datatype: "Max35Text" on page 381

13.1.17.1.2.7.3.2 LastPaymentDate <LastPmtDt>

Presence: [0..1]

Definition: Final payment of the standing order due.

Datatype: "ISODate" on page 376

13.1.17.1.2.7.4 RequestedFrequencyPattern <ReqdFrqcyPttrn>

Presence: [0..1]

Definition: Payment schedule frequency pattern which indicates how frequently a payment is made.

RequestedFrequencyPattern <ReqdFrqcyPttrn> contains one of the following elements (see "Frequency37Choice" on page 175 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		175
Or}	Proprietary <*Prtry*>	[1..1]	Text		176

13.1.17.1.2.7.5 NonWorkingDayAdjustment <NonWorkgDayAdjstmnt>

Presence: [0..1]

Definition: Adjustment indicator for a non-working day to enable payment to be made on the next working day.

Datatype: "BusinessDayConvention1Code" on page 361

CodeName	Name	Definition
FWNG	Following	The date will be the first following day that is a business day.
PREC	Preceding	The date will be the first preceding day that is a business day.

13.1.17.1.2.8 TransferInstruction <TrfInstr>

Presence: [0..1]

Definition: Provides further information about the status of transferred scheduled payment(s).

TransferInstruction <TrfInstr> contains the following **TransferInstruction1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		323
	Code <*Cd*>	[1..1]	Text		324
	Proprietary <*Prtry*>	[0..1]	Text		324
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		324
	StartDate <*StartDt*>	[0..1]	Date		324
	Description <*Desc*>	[0..1]	Text		324

13.1.17.1.2.8.1 TransferIndicator <TrfInd>

Presence: [0..1]

Definition: Indicates whether a payment arrangement is transferable.

Usage: Default value for TransferIndicator is false.

Datatype: One of the following values must be used (see "YesNoIndicator" on page 378):

- *Meaning When True:* Yes
- *Meaning When False:* No

13.1.17.1.2.8.2 Code <Cd>

Presence: [1..1]

Definition: Specifies an additional parameter to be applied to the requested transaction schedule.

Datatype: "Max35Text" on page 381

13.1.17.1.2.8.3 Proprietary <Prtry>

Presence: [0..1]

Definition: Specifies an additional parameter to be applied to the transaction schedule in a proprietary format.

Datatype: "Max256Text" on page 380

13.1.17.1.2.8.4 StartDateTime <StartDtTm>

Presence: [0..1]

Definition: The date and time at which the event specified by Code commences.

Datatype: "ISODateTime" on page 376

13.1.17.1.2.8.5 StartDate <StartDt>

Presence: [0..1]

Definition: The date on which the event specified by Code commences.

Datatype: "ISODate" on page 376

13.1.17.1.2.8.6 Description <Desc>

Presence: [0..1]

Definition: Additional switch parameters in a free text format.

Datatype: "Max350Text" on page 380

13.1.17.1.2.9 UltimateDebtor <UltmtDbtr>

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

UltimateDebtor <UltmtDbtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.17.1.2.10 IntermediaryAgent1 <IntrmyAgt1>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

IntermediaryAgent1 <IntrmyAgt1> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.17.1.2.11 IntermediaryAgent2 <IntrmyAgt2>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

IntermediaryAgent2 <IntrmyAgt2> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.17.1.2.12 IntermediaryAgent3 <IntrmyAgt3>

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

IntermediaryAgent3 <IntrmyAgt3> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.17.1.2.13 CreditorAgent <CdtrAgt>

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

CreditorAgent <CdtrAgt> contains the following elements (see "BranchAndFinancialInstitutionIdentification5" on page 164 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FinancialInstitutionIdentification <*FinInstnId*>	[1..1]	±		164
	BranchIdentification <*BrnchId*>	[0..1]	±		164

13.1.17.1.2.14 Creditor <Cdtr>

Presence: [0..1]

Definition: Party to which an amount of money is due.

Creditor <Cdtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.17.1.2.15 CreditorAccount <CdtrAcct>

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

CreditorAccount <CdtrAcct> contains the following elements (see "CashAccount24" on page 146 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Identification <*Id*>	[1..1]	±		146
	Type <*Tp*>	[0..1]	±		146
	Currency <*Ccy*>	[0..1]	CodeSet	C2	147
	Name <*Nm*>	[0..1]	Text		147

13.1.17.1.2.16 UltimateCreditor <UltmtCdtr>

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

UltimateCreditor <UltmtCdtr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.17.1.2.17 InstructionForCreditorAgent <InstrForCdtrAgt>

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

InstructionForCreditorAgent <InstrForCdtrAgt> contains the following elements (see "InstructionForCreditorAgent1" on page 212 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Code <*Cd*>	[0..1]	CodeSet		212
	InstructionInformation <*InstrInf*>	[0..1]	Text		213

13.1.17.1.2.18 Purpose <Purp>

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

Purpose <Purp> contains one of the following **Purpose2Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		328
Or}	Proprietary <*Prtry*>	[1..1]	Text		328

13.1.17.1.2.18.1 Code <Cd>

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: "ExternalPurpose1Code" on page 368

13.1.17.1.2.18.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: "Max35Text" on page 381

13.1.17.1.2.19 RegulatoryReporting <RgltryRptg>

Presence: [0..10]

Definition: Information needed due to regulatory and statutory requirements.

RegulatoryReporting <RgltryRptg> contains the following elements (see "RegulatoryReporting3" on page 269 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DebitCreditReportingIndicator <*DbtCdtRptgInd*>	[0..1]	CodeSet		269
	Authority <*Authrty*>	[0..1]			270
	Name <*Nm*>	[0..1]	Text		270
	Country <*Ctry*>	[0..1]	CodeSet	C18	270
	Details <*Dtls*>	[0..*]			270
	Type <*Tp*>	[0..1]	Text		271
	Date <*Dt*>	[0..1]	Date		271
	Country <*Ctry*>	[0..1]	CodeSet	C18	271
	Code <*Cd*>	[0..1]	Text		271
	Amount <*Amt*>	[0..1]	Amount	C2, C20	271
	Information <*Inf*>	[0..*]	Text		272

13.1.17.1.2.20 Tax <Tax>

Presence: [0..1]

Definition: Provides details on the tax.

Tax <Tax> contains the following **TaxInformation6** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Creditor <*Cdtr*>	[0..1]			331
	TaxIdentification <*TaxId*>	[0..1]	Text		331
	RegistrationIdentification <*RegnId*>	[0..1]	Text		331
	TaxType <*TaxTp*>	[0..1]	Text		331
	Debtor <*Dbtr*>	[0..1]			332
	TaxIdentification <*TaxId*>	[0..1]	Text		332
	RegistrationIdentification <*RegnId*>	[0..1]	Text		332
	TaxType <*TaxTp*>	[0..1]	Text		332
	Authorisation <*Authstn*>	[0..1]			332
	Title <*Titl*>	[0..1]	Text		333
	Name <*Nm*>	[0..1]	Text		333
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		333
	ReferenceNumber <*RefNb*>	[0..1]	Text		333
	Method <*Mtd*>	[0..1]	Text		333
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	333
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	334
	Date <*Dt*>	[0..1]	Date		334
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		334
	Record <*Rcrd*>	[0..*]			334
	Type <*Tp*>	[0..1]	Text		335
	Category <*Ctgy*>	[0..1]	Text		335
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		336
	DebtorStatus <*DbtrSts*>	[0..1]	Text		336
	CertificateIdentification <*CertId*>	[0..1]	Text		336
	FormsCode <*FrmsCd*>	[0..1]	Text		336
	Period <*Prd*>	[0..1]			336
	Year <*Yr*>	[0..1]	Date		336
	Type <*Tp*>	[0..1]	CodeSet		337
	FromToDate <*FrToDt*>	[0..1]			337
	FromDate <*FrDt*>	[1..1]	Date		338
	ToDate <*ToDt*>	[1..1]	Date		338

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxAmount <*TaxAmt*>	[0..1]			338
	Rate <*Rate*>	[0..1]	Rate		338
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	339
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	339
	Details <*Dtls*>	[0..*]			339
	Period <*Prd*>	[0..1]			340
	Year <*Yr*>	[0..1]	Date		340
	Type <*Tp*>	[0..1]	CodeSet		340
	FromToDate <*FrToDt*>	[0..1]			341
	FromDate <*FrDt*>	[1..1]	Date		341
	ToDate <*ToDt*>	[1..1]	Date		342
	Amount <*Amt*>	[1..1]	Amount	C2, C20	342
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		342

13.1.17.1.2.20.1 Creditor <Cdtr>

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

Creditor <Cdtr> contains the following **TaxParty1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxIdentification <*TaxId*>	[0..1]	Text		331
	RegistrationIdentification <*RegnId*>	[0..1]	Text		331
	TaxType <*TaxTp*>	[0..1]	Text		331

13.1.17.1.2.20.1.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.1.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.1.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.2 Debtor <Dbtr>

Presence: [0..1]

Definition: Set of elements used to identify the party on the debit side of the transaction to which the tax applies.

Debtor <Dbtr> contains the following **TaxParty2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	TaxIdentification <*TaxId*>	[0..1]	Text		332
	RegistrationIdentification <*RegnId*>	[0..1]	Text		332
	TaxType <*TaxTp*>	[0..1]	Text		332
	Authorisation <*Authstn*>	[0..1]			332
	Title <*Titl*>	[0..1]	Text		333
	Name <*Nm*>	[0..1]	Text		333

13.1.17.1.2.20.2.1 TaxIdentification <TaxId>

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.2.2 RegistrationIdentification <RegnId>

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.2.3 TaxType <TaxTp>

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.2.4 Authorisation <Authstn>

Presence: [0..1]

Definition: Details of the authorised tax paying party.

Authorisation <Authstn> contains the following **TaxAuthorisation1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Title <*Titl*>	[0..1]	Text		333
	Name <*Nm*>	[0..1]	Text		333

13.1.17.1.2.20.2.4.1 Title <Titl>

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.2.4.2 Name <Nm>

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: "Max140Text" on page 379

13.1.17.1.2.20.3 AdministrationZone <AdmstnZn>

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.4 ReferenceNumber <RefNb>

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "Max140Text" on page 379

13.1.17.1.2.20.5 Method <Mtd>

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.6 TotalTaxableBaseAmount <TtlTaxblBaseAmt>

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.2.20.7 TotalTaxAmount <TtlTaxAmt>

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.2.20.8 Date <Dt>

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: "ISODate" on page 376

13.1.17.1.2.20.9 SequenceNumber <SeqNb>

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: "Number" on page 378

13.1.17.1.2.20.10 Record <Rcrd>

Presence: [0..*]

Definition: Record of tax details.

Record <Rcrd> contains the following **TaxRecord2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]	Text		335
	Category <*Ctgy*>	[0..1]	Text		335
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		336
	DebtorStatus <*DbtrSts*>	[0..1]	Text		336
	CertificateIdentification <*CertId*>	[0..1]	Text		336
	FormsCode <*FrmsCd*>	[0..1]	Text		336
	Period <*Prd*>	[0..1]			336
	Year <*Yr*>	[0..1]	Date		336
	Type <*Tp*>	[0..1]	CodeSet		337
	FromToDate <*FrToDt*>	[0..1]			337
	FromDate <*FrDt*>	[1..1]	Date		338
	ToDate <*ToDt*>	[1..1]	Date		338
	TaxAmount <*TaxAmt*>	[0..1]			338
	Rate <*Rate*>	[0..1]	Rate		338
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	339
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	339
	Details <*Dtls*>	[0..*]			339
	Period <*Prd*>	[0..1]			340
	Year <*Yr*>	[0..1]	Date		340
	Type <*Tp*>	[0..1]	CodeSet		340
	FromToDate <*FrToDt*>	[0..1]			341
	FromDate <*FrDt*>	[1..1]	Date		341
	ToDate <*ToDt*>	[1..1]	Date		342
	Amount <*Amt*>	[1..1]	Amount	C2, C20	342
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		342

13.1.17.1.2.20.10.1 Type <Tp>

Presence: [0..1]

Definition: High level code to identify the type of tax details.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.10.2 Category <Ctgy>

Presence: [0..1]

Definition: Specifies the tax code as published by the tax authority.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.10.3 CategoryDetails <CtgyDtls>

Presence: [0..1]

Definition: Provides further details of the category tax code.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.10.4 DebtorStatus <DbtrSts>

Presence: [0..1]

Definition: Code provided by local authority to identify the status of the party that has drawn up the settlement document.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.10.5 CertificateIdentification <CertId>

Presence: [0..1]

Definition: Identification number of the tax report as assigned by the taxing authority.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.10.6 FormsCode <FrmsCd>

Presence: [0..1]

Definition: Identifies, in a coded form, on which template the tax report is to be provided.

Datatype: "Max35Text" on page 381

13.1.17.1.2.20.10.7 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following **TaxPeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		336
	Type <*Tp*>	[0..1]	CodeSet		337
	FromToDate <*FrToDt*>	[0..1]			337
	FromDate <*FrDt*>	[1..1]	Date		338
	ToDate <*ToDt*>	[1..1]	Date		338

13.1.17.1.2.20.10.7.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 376

13.1.17.1.2.20.10.7.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 375

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

13.1.17.1.2.20.10.7.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following **DatePeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FromDate <*FrDt*>	[1..1]	Date		338
	ToDate <*ToDt*>	[1..1]	Date		338

13.1.17.1.2.20.10.7.3.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: "ISODate" on page 376

13.1.17.1.2.20.10.7.3.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: "ISODate" on page 376

13.1.17.1.2.20.10.8 TaxAmount <TaxAmt>

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

TaxAmount <TaxAmt> contains the following **TaxAmount2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Rate <*Rate*>	[0..1]	Rate		338
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	339
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	339
	Details <*Dtls*>	[0..*]			339
	Period <*Prd*>	[0..1]			340
	Year <*Yr*>	[0..1]	Date		340
	Type <*Tp*>	[0..1]	CodeSet		340
	FromToDate <*FrToDt*>	[0..1]			341
	FromDate <*FrDt*>	[1..1]	Date		341
	ToDate <*ToDt*>	[1..1]	Date		342
	Amount <*Amt*>	[1..1]	Amount	C2, C20	342

13.1.17.1.2.20.10.8.1 Rate <Rate>

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: "PercentageRate" on page 378

13.1.17.1.2.20.10.8.2 TaxableBaseAmount <TaxblBaseAmt>

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.2.20.10.8.3 TotalAmount <TtlAmt>

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.2.20.10.8.4 Details <Dtls>

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

Details <Dtls> contains the following **TaxRecordDetails2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Period <*Prd*>	[0..1]			340
	Year <*Yr*>	[0..1]	Date		340
	Type <*Tp*>	[0..1]	CodeSet		340
	FromToDate <*FrToDt*>	[0..1]			341
	FromDate <*FrDt*>	[1..1]	Date		341
	ToDate <*ToDt*>	[1..1]	Date		342
	Amount <*Amt*>	[1..1]	Amount	C2, C20	342

13.1.17.1.2.20.10.8.4.1 Period <Prd>

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

Period <Prd> contains the following **TaxPeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Year <*Yr*>	[0..1]	Date		340
	Type <*Tp*>	[0..1]	CodeSet		340
	FromToDate <*FrToDt*>	[0..1]			341
	FromDate <*FrDt*>	[1..1]	Date		341
	ToDate <*ToDt*>	[1..1]	Date		342

13.1.17.1.2.20.10.8.4.1.1 Year <Yr>

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 376

13.1.17.1.2.20.10.8.4.1.2 Type <Tp>

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 375

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.

CodeName	Name	Definition
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

13.1.17.1.2.20.10.8.4.1.3 FromToDate <FrToDt>

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

FromToDate <FrToDt> contains the following **DatePeriod2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	FromDate <*FrDt*>	[1..1]	Date		341
	ToDate <*ToDt*>	[1..1]	Date		342

13.1.17.1.2.20.10.8.4.1.3.1 FromDate <FrDt>

Presence: [1..1]

Definition: Start date of the range.

Datatype: "ISODate" on page 376

13.1.17.1.2.20.10.8.4.1.3.2 ToDate <ToDt>

Presence: [1..1]

Definition: End date of the range.

Datatype: "ISODate" on page 376

13.1.17.1.2.20.10.8.4.2 Amount <Amt>

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Impacted by: C2 "ActiveOrHistoricCurrency", C20 "CurrencyAmount"

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 359

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.1.17.1.2.20.10.9 AdditionalInformation <AddtlInf>

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: "Max140Text" on page 379

13.1.17.1.2.21 RelatedRemittanceInformation <RltdRmtInf>

Presence: [0..10]

Definition: Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain.

RelatedRemittanceInformation <RltdRmtInf> contains the following elements (see "RemittanceLocation2" on page 173 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	RemittanceIdentification <*RmtId*>	[0..1]	Text		174
	RemittanceLocationMethod <*RmtLctnMtd*>	[0..1]	CodeSet		174
	RemittanceLocationElectronicAddress <*RmtLctnElctrncAdr*>	[0..1]	Text		174
	RemittanceLocationPostalAddress <*RmtLctnPstlAdr*>	[0..1]			174
	Name <*Nm*>	[1..1]	Text		175
	Address <*Adr*>	[1..1]	±		175

13.1.17.1.2.22 RemittanceInformation <RmtInf>

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

RemittanceInformation <RmtInf> contains the following **RemittanceInformation14** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Unstructured <*Ustrd*>	[0..*]	Text		343
	Structured <*Strd*>	[0..*]			343
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			344
	Type <*Tp*>	[0..1]			344
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			345
{Or	Code <*Cd*>	[1..1]	CodeSet		345
Or}	Proprietary <*Prtry*>	[1..1]	Text		346
	Issuer <*Issr*>	[0..1]	Text		346
	Number <*Nb*>	[0..1]	Text		346
	RelatedDate <*RltdDt*>	[0..1]	Date		346
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		346
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		347
	Invoicer <*Invcr*>	[0..1]	±		348
	Invoicee <*Invcee*>	[0..1]	±		348
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		349

13.1.17.1.2.22.1 Unstructured <Ustrd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: "Max140Text" on page 379

13.1.17.1.2.22.2 Structured <Strd>

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

Structured <Strd> contains the following **StructuredRemittanceInformation14** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			344
	Type <*Tp*>	[0..1]			344
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			345
{Or	Code <*Cd*>	[1..1]	CodeSet		345
Or}	Proprietary <*Prtry*>	[1..1]	Text		346
	Issuer <*Issr*>	[0..1]	Text		346
	Number <*Nb*>	[0..1]	Text		346
	RelatedDate <*RltdDt*>	[0..1]	Date		346
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		346
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		347
	Invoicer <*Invcr*>	[0..1]	±		348
	Invoicee <*Invcee*>	[0..1]	±		348
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		349

13.1.17.1.2.22.2.1 ReferredDocumentInformation <RfrdDocInf>

Presence: [0..*]

Definition: Set of elements used to identify the documents referred to in the remittance information.

ReferredDocumentInformation <RfrdDocInf> contains the following **ReferredDocumentInformation3** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			344
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			345
{Or	Code <*Cd*>	[1..1]	CodeSet		345
Or}	Proprietary <*Prtry*>	[1..1]	Text		346
	Issuer <*Issr*>	[0..1]	Text		346
	Number <*Nb*>	[0..1]	Text		346
	RelatedDate <*RltdDt*>	[0..1]	Date		346

13.1.17.1.2.22.2.1.1 Type <Tp>

Presence: [0..1]

Definition: Specifies the type of referred document.

Type <Tp> contains the following **ReferredDocumentType2** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			345
{Or	Code <*Cd*>	[1..1]	CodeSet		345
Or}	Proprietary <*Prtry*>	[1..1]	Text		346
	Issuer <*Issr*>	[0..1]	Text		346

13.1.17.1.2.22.2.1.1.1 CodeOrProprietary <CdOrPrtry>

Presence: [1..1]

Definition: Provides the type details of the referred document.

CodeOrProprietary <CdOrPrtry> contains one of the following **ReferredDocumentType1Choice** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		345
Or}	Proprietary <*Prtry*>	[1..1]	Text		346

13.1.17.1.2.22.2.1.1.1.1 Code <Cd>

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: "DocumentType5Code" on page 364

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and

CodeName	Name	Definition
		conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.

13.1.17.1.2.22.2.1.1.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: "Max35Text" on page 381

13.1.17.1.2.22.2.1.1.2 Issuer <Issr>

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "Max35Text" on page 381

13.1.17.1.2.22.2.1.2 Number <Nb>

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: "Max35Text" on page 381

13.1.17.1.2.22.2.1.3 RelatedDate <RltdDt>

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: "ISODate" on page 376

13.1.17.1.2.22.2.2 ReferredDocumentAmount <RfrdDocAmt>

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

ReferredDocumentAmount <RfrdDocAmt> contains the following elements (see "RemittanceAmount2" on page 177 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	DuePayableAmount <*DuePyblAmt*>	[0..1]	Amount	C2, C20	178
	DiscountAppliedAmount <*DscntApldAmt*>	[0..*]			179
	Type <*Tp*>	[0..1]			179
{Or	Code <*Cd*>	[1..1]	CodeSet		179
Or}	Proprietary <*Prtry*>	[1..1]	Text		179
	Amount <*Amt*>	[1..1]	Amount	C2, C20	179
	CreditNoteAmount <*CdtNoteAmt*>	[0..1]	Amount	C2, C20	180
	TaxAmount <*TaxAmt*>	[0..*]			180
	Type <*Tp*>	[0..1]			180
{Or	Code <*Cd*>	[1..1]	CodeSet		181
Or}	Proprietary <*Prtry*>	[1..1]	Text		181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	181
	AdjustmentAmountAndReason <*AdjstmntAmtAndRsn*>	[0..*]			181
	Amount <*Amt*>	[1..1]	Amount	C2, C20	182
	CreditDebitIndicator <*CdtDbtInd*>	[0..1]	CodeSet		182
	Reason <*Rsn*>	[0..1]	Text		182
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		182
	RemittedAmount <*RmtdAmt*>	[0..1]	Amount	C2, C20	183

13.1.17.1.2.22.2.3 CreditorReferenceInformation <CdtrRefInf>

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

CreditorReferenceInformation <CdtrRefInf> contains the following elements (see "CreditorReferenceInformation2" on page 162 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			162
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			162
{Or	Code <*Cd*>	[1..1]	CodeSet		163
Or}	Proprietary <*Prtry*>	[1..1]	Text		163
	Issuer <*Issr*>	[0..1]	Text		163
	Reference <*Ref*>	[0..1]	Text		163

13.1.17.1.2.22.2.4 Invoicer <Invcr>

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

Invoicer <Invcr> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.17.1.2.22.2.5 Invoicee <Invcee>

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

Invoicee <Invcee> contains the following elements (see "PartyIdentification125" on page 208 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Name <*Nm*>	[0..1]	Text		209
	PostalAddress <*PstlAdr*>	[0..1]	±		209
	Identification <*Id*>	[0..1]			209
{Or	OrganisationIdentification <*OrgId*>	[1..1]	±		210
Or}	PrivateIdentification <*PrvtId*>	[1..1]	±		210
	CountryOfResidence <*CtryOfRes*>	[0..1]	CodeSet	C18	211
	ContactDetails <*CtctDtls*>	[0..1]	±		211

13.1.17.1.2.22.2.6 AdditionalRemittanceInformation <AddtlRmtInf>

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: "Max140Text" on page 379

13.1.18 Status

13.1.18.1 ResponseDetails1

Definition: Additional details to clarify response codes.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	ResponseCode <*RspnCd*>	[1..1]	Text		349
	AdditionalDetails <*AddtlDtls*>	[0..1]	Text		349

13.1.18.1.1 ResponseCode <RspnCd>

Presence: [1..1]

Definition: Code for account servicer warnings, rejections, pay no/pay responses and technical rejections.

Datatype: "Max35Text" on page 381

13.1.18.1.2 AdditionalDetails <AddtlDtls>

Presence: [0..1]

Definition: Additional information to elaborate upon response codes.

Datatype: "Max350Text" on page 380

13.1.19 System Identification

13.1.19.1 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Code <*Cd*>	[1..1]	CodeSet		350
Or}	Proprietary <*Prtry*>	[1..1]	Text		350

13.1.19.1.1 Code <Cd>

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: "ExternalClearingSystemIdentification1Code" on page 366

13.1.19.1.2 Proprietary <Prtry>

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: "Max35Text" on page 381

13.1.20 Transfer

13.1.20.1 BalanceTransfer1

Definition: Information that enables any payments made in connection with the fulfilment of an account switch to be reconciled by the relevant account servicer with the associated request.

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	BalanceTransferReference <*BalTrfRef*>	[0..1]			350
	BalanceTransferReference <*BalTrfRef*>	[1..1]	Text		351
	BalanceTransferMethod <*BalTrfMtd*>	[0..1]	±		351
	BalanceTransferFundingLimit <*BalTrfFndgLmt*>	[0..1]			358
	CurrencyAmount <*CcyAmt*>	[1..1]	Amount	C1, C19	358

13.1.20.1.1 BalanceTransferReference <BalTrfRef>

Presence: [0..1]

Definition: Reference that enables the creditor to reconcile a payment received through a different payment channel with the payment request.

BalanceTransferReference <BalTrfRef> contains the following **BalanceTransferReference1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	BalanceTransferReference <*BalTrfRef*>	[1..1]	Text		351

13.1.20.1.1.1 BalanceTransferReference <BalTrfRef>

Presence: [1..1]

Definition: Used by the debtor in a suitable reference field of a payment message sent over an alternative payment channel to enable the creditor to match the payment with the payment request.

Datatype: "Max35Text" on page 381

13.1.20.1.2 BalanceTransferMethod <BalTrfMtd>

Presence: [0..1]

Definition: Contains details of the clearance and settlement method chosen to make the appropriate payment from account servicer to account servicer in order to transfer the positive or negative closing balance of the old account to the new account.

BalanceTransferMethod <BalTrfMtd> contains one of the following elements (see "SettlementMethod1Choice" on page 272 for details)

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
{Or	Credit <*Cdt*>	[1..1]		C22, C23, C24, C28, C30	279
	PaymentIdentification <*PmtId*>	[1..1]	±		283
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		283
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		284
	Amount <*Amt*>	[1..1]	Amount	C1, C19	284
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		285
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C16	285
	Frequency <*Frqcy*>	[0..1]			286
	Sequence <*Seq*>	[0..1]	Text		287
	StartDate <*StartDt*>	[1..1]	Date		287
	EndPointChoice <*EndPtChc*>	[1..1]			287
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		287
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		287
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		288
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		288
	TransferInstruction <*TrfInstr*>	[0..1]			288
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		288
	Code <*Cd*>	[1..1]	Text		289
	Proprietary <*Prtry*>	[0..1]	Text		289
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		289
	StartDate <*StartDt*>	[0..1]	Date		289
	Description <*Desc*>	[0..1]	Text		289
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		289
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		290
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		290
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		290
	CreditorAgent <*CdtrAgt*>	[1..1]	±		291
	Creditor <*Cdtr*>	[0..1]	±		291

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CreditorAccount <*CdtrAcct*>	[0..1]	±		291
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		292
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		292
	Purpose <*Purp*>	[0..1]			292
{Or	Code <*Cd*>	[1..1]	CodeSet		293
Or}	Proprietary <*Prtry*>	[1..1]	Text		293
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		293
	Tax <*Tax*>	[0..1]			294
	Creditor <*Cdtr*>	[0..1]			296
	TaxIdentification <*TaxId*>	[0..1]	Text		296
	RegistrationIdentification <*RegnId*>	[0..1]	Text		296
	TaxType <*TaxTp*>	[0..1]	Text		296
	Debtor <*Dbtr*>	[0..1]			297
	TaxIdentification <*TaxId*>	[0..1]	Text		297
	RegistrationIdentification <*RegnId*>	[0..1]	Text		297
	TaxType <*TaxTp*>	[0..1]	Text		297
	Authorisation <*Authstn*>	[0..1]			297
	Title <*Titl*>	[0..1]	Text		298
	Name <*Nm*>	[0..1]	Text		298
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		298
	ReferenceNumber <*RefNb*>	[0..1]	Text		298
	Method <*Mtd*>	[0..1]	Text		298
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	298
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	299
	Date <*Dt*>	[0..1]	Date		299
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		299
	Record <*Rcrd*>	[0..*]			299
	Type <*Tp*>	[0..1]	Text		300
	Category <*Ctgy*>	[0..1]	Text		300
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		301
	DebtorStatus <*DbtrSts*>	[0..1]	Text		301

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CertificateIdentification <*CertId*>	[0..1]	Text		301
	FormsCode <*FrmsCd*>	[0..1]	Text		301
	Period <*Prd*>	[0..1]			301
	Year <*Yr*>	[0..1]	Date		301
	Type <*Tp*>	[0..1]	CodeSet		302
	FromToDate <*FrToDt*>	[0..1]			302
	FromDate <*FrDt*>	[1..1]	Date		303
	ToDate <*ToDt*>	[1..1]	Date		303
	TaxAmount <*TaxAmt*>	[0..1]			303
	Rate <*Rate*>	[0..1]	Rate		303
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	304
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	304
	Details <*Dtls*>	[0..*]			304
	Period <*Prd*>	[0..1]			305
	Year <*Yr*>	[0..1]	Date		305
	Type <*Tp*>	[0..1]	CodeSet		305
	FromToDate <*FrToDt*>	[0..1]			306
	FromDate <*FrDt*>	[1..1]	Date		306
	ToDate <*ToDt*>	[1..1]	Date		307
	Amount <*Amt*>	[1..1]	Amount	C2, C20	307
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		307
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		307
	RemittanceInformation <*RmtInf*>	[0..1]			308
	Unstructured <*Ustrd*>	[0..*]	Text		308
	Structured <*Strd*>	[0..*]			308
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			309
	Type <*Tp*>	[0..1]			309
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			310
{Or	Code <*Cd*>	[1..1]	CodeSet		310
Or}	Proprietary <*Prtry*>	[1..1]	Text		311
	Issuer <*Issr*>	[0..1]	Text		311

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Number <*Nb*>	[0..1]	Text		311
	RelatedDate <*RltdDt*>	[0..1]	Date		311
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		311
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		312
	Invoicer <*Invcr*>	[0..1]	±		313
	Invoicee <*Invcee*>	[0..1]	±		313
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		314
Or}	Debit <*Dbt*>	[1..1]		C22, C23, C24, C28, C30	314
	PaymentIdentification <*PmtId*>	[1..1]	±		318
	PaymentTypeInformation <*PmtTpInf*>	[0..1]	±		318
	TaxRateMarker <*TaxRateMrkr*>	[0..1]	CodeSet		319
	Amount <*Amt*>	[1..1]	Amount	C1, C19	319
	ChargeBearer <*ChrgBr*>	[0..1]	CodeSet		320
	ChequeInstruction <*ChqInstr*>	[0..1]	±	C16	320
	Frequency <*Frqcy*>	[0..1]			321
	Sequence <*Seq*>	[0..1]	Text		322
	StartDate <*StartDt*>	[1..1]	Date		322
	EndPointChoice <*EndPtChc*>	[1..1]			322
{Or	NumberOfPayments <*NbOfPmts*>	[0..1]	Text		322
Or}	LastPaymentDate <*LastPmtDt*>	[0..1]	Date		322
	RequestedFrequencyPattern <*ReqdFrqcyPttrn*>	[0..1]	±		323
	NonWorkingDayAdjustment <*NonWorkgDayAdjstmnt*>	[0..1]	CodeSet		323
	TransferInstruction <*TrfInstr*>	[0..1]			323
	TransferIndicator <*TrfInd*>	[0..1]	Indicator		323
	Code <*Cd*>	[1..1]	Text		324
	Proprietary <*Prtry*>	[0..1]	Text		324
	StartDateTime <*StartDtTm*>	[0..1]	DateTime		324
	StartDate <*StartDt*>	[0..1]	Date		324
	Description <*Desc*>	[0..1]	Text		324
	UltimateDebtor <*UltmtDbtr*>	[0..1]	±		324

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	IntermediaryAgent1 <*IntrmyAgt1*>	[0..1]	±		325
	IntermediaryAgent2 <*IntrmyAgt2*>	[0..1]	±		325
	IntermediaryAgent3 <*IntrmyAgt3*>	[0..1]	±		325
	CreditorAgent <*CdtrAgt*>	[1..1]	±		326
	Creditor <*Cdtr*>	[0..1]	±		326
	CreditorAccount <*CdtrAcct*>	[0..1]	±		326
	UltimateCreditor <*UltmtCdtr*>	[0..1]	±		327
	InstructionForCreditorAgent <*InstrForCdtrAgt*>	[0..*]	±		327
	Purpose <*Purp*>	[0..1]			327
{Or	Code <*Cd*>	[1..1]	CodeSet		328
Or}	Proprietary <*Prtry*>	[1..1]	Text		328
	RegulatoryReporting <*RgltryRptg*>	[0..10]	±		328
	Tax <*Tax*>	[0..1]			329
	Creditor <*Cdtr*>	[0..1]			331
	TaxIdentification <*TaxId*>	[0..1]	Text		331
	RegistrationIdentification <*RegnId*>	[0..1]	Text		331
	TaxType <*TaxTp*>	[0..1]	Text		331
	Debtor <*Dbtr*>	[0..1]			332
	TaxIdentification <*TaxId*>	[0..1]	Text		332
	RegistrationIdentification <*RegnId*>	[0..1]	Text		332
	TaxType <*TaxTp*>	[0..1]	Text		332
	Authorisation <*Authstn*>	[0..1]			332
	Title <*Titl*>	[0..1]	Text		333
	Name <*Nm*>	[0..1]	Text		333
	AdministrationZone <*AdmstnZn*>	[0..1]	Text		333
	ReferenceNumber <*RefNb*>	[0..1]	Text		333
	Method <*Mtd*>	[0..1]	Text		333
	TotalTaxableBaseAmount <*TtlTaxblBaseAmt*>	[0..1]	Amount	C2, C20	333
	TotalTaxAmount <*TtlTaxAmt*>	[0..1]	Amount	C2, C20	334
	Date <*Dt*>	[0..1]	Date		334
	SequenceNumber <*SeqNb*>	[0..1]	Quantity		334

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Record <*Rcrd*>	[0..*]			334
	Type <*Tp*>	[0..1]	Text		335
	Category <*Ctgy*>	[0..1]	Text		335
	CategoryDetails <*CtgyDtls*>	[0..1]	Text		336
	DebtorStatus <*DbtrSts*>	[0..1]	Text		336
	CertificateIdentification <*CertId*>	[0..1]	Text		336
	FormsCode <*FrmsCd*>	[0..1]	Text		336
	Period <*Prd*>	[0..1]			336
	Year <*Yr*>	[0..1]	Date		336
	Type <*Tp*>	[0..1]	CodeSet		337
	FromToDate <*FrToDt*>	[0..1]			337
	FromDate <*FrDt*>	[1..1]	Date		338
	ToDate <*ToDt*>	[1..1]	Date		338
	TaxAmount <*TaxAmt*>	[0..1]			338
	Rate <*Rate*>	[0..1]	Rate		338
	TaxableBaseAmount <*TaxblBaseAmt*>	[0..1]	Amount	C2, C20	339
	TotalAmount <*TtlAmt*>	[0..1]	Amount	C2, C20	339
	Details <*Dtls*>	[0..*]			339
	Period <*Prd*>	[0..1]			340
	Year <*Yr*>	[0..1]	Date		340
	Type <*Tp*>	[0..1]	CodeSet		340
	FromToDate <*FrToDt*>	[0..1]			341
	FromDate <*FrDt*>	[1..1]	Date		341
	ToDate <*ToDt*>	[1..1]	Date		342
	Amount <*Amt*>	[1..1]	Amount	C2, C20	342
	AdditionalInformation <*AddtlInf*>	[0..1]	Text		342
	RelatedRemittanceInformation <*RltdRmtInf*>	[0..10]	±		342
	RemittanceInformation <*RmtInf*>	[0..1]			343
	Unstructured <*Ustrd*>	[0..*]	Text		343
	Structured <*Strd*>	[0..*]			343
	ReferredDocumentInformation <*RfrdDocInf*>	[0..*]			344

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	Type <*Tp*>	[0..1]			344
	CodeOrProprietary <*CdOrPrtry*>	[1..1]			345
{Or	Code <*Cd*>	[1..1]	CodeSet		345
Or}	Proprietary <*Prtry*>	[1..1]	Text		346
	Issuer <*Issr*>	[0..1]	Text		346
	Number <*Nb*>	[0..1]	Text		346
	RelatedDate <*RltdDt*>	[0..1]	Date		346
	ReferredDocumentAmount <*RfrdDocAmt*>	[0..1]	±		346
	CreditorReferenceInformation <*CdtrRefInf*>	[0..1]	±		347
	Invoicer <*Invcr*>	[0..1]	±		348
	Invoicee <*Invcee*>	[0..1]	±		348
	AdditionalRemittanceInformation <*AddtlRmtInf*>	[0..3]	Text		349

13.1.20.1.3 BalanceTransferFundingLimit <BalTrfFndgLmt>

Presence: [0..1]

Definition: Maximum value that the new account servicer will pay to the old account servicer when the closing balance on the old account is negative.

BalanceTransferFundingLimit <BalTrfFndgLmt> contains the following **BalanceTransferFundingLimit1** elements

Or	MessageElement<*XML Tag*>	Mult.	Type	Constr. No.	Page
	CurrencyAmount <*CcyAmt*>	[1..1]	Amount	C1, C19	358

13.1.20.1.3.1 CurrencyAmount <CcyAmt>

Presence: [1..1]

Definition: Maximum value and related currency that can be sent by the new account servicer to the old account servicer in case of a negative closing balance.

Impacted by: C1 "ActiveCurrency", C19 "CurrencyAmount"

Datatype: "ActiveCurrencyAndAmount" on page 359

Constraints

- **ActiveCurrency**

  The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217

Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.2 Message Datatypes

13.2.1 Amount

13.2.1.1 ActiveCurrencyAndAmount

Definition: A number of monetary units specified in an active currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type contains the following XML attribute:

Name	Attribute XML Name	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 360

Format

minInclusive	0
totalDigits	18
fractionDigits	5

Constraints

- **ActiveCurrency**

  The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.2.1.2 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type contains the following XML attribute:

Name	Attribute XML Name	Datatype
Currency	Ccy	"ActiveOrHistoricCurrencyCode" on page 360

Format

minInclusive	0
totalDigits	18
fractionDigits	5

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

- **CurrencyAmount**

  The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

  Note: The decimal separator is a dot.

13.2.2 CodeSet

13.2.2.1 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}

Constraints

- **ActiveCurrency**

  The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

13.2.2.2 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}

Constraints

- **ActiveOrHistoricCurrency**

  The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

13.2.2.3 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

CodeName	Name	Definition
ADDR	Postal	Address is the complete postal address.
PBOX	POBox	Address is a postal office (PO) box.
HOME	Residential	Address is the home address.
BIZZ	Business	Address is the business address.
MLTO	MailTo	Address is the address to which mail is sent.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.

13.2.2.4 BalanceTransferWindow1Code

Definition: Specifies the processing window in which the balance transfer will be processed on the switch date.

Type: CodeSet

CodeName	Name	Definition
DAYH	InHours	Indicates in business hours processing.
EARL	OutOfHours	Indicates out of business hours processing.

13.2.2.5 BusinessDayConvention1Code

Definition: Indicates how a date is adjusted when it falls on a non-business day.

Type: CodeSet

CodeName	Name	Definition
FWNG	Following	The date will be the first following day that is a business day.
PREC	Preceding	The date will be the first preceding day that is a business day.

13.2.2.6 ChargeBearerType1Code

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: CodeSet

CodeName	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

13.2.2.7 ChequeDelivery1Code

Definition: Specifies the method to be used in delivering a cheque to a party.

Type: CodeSet

CodeName	Name	Definition
MLDB	MailToDebtor	Cheque is to be sent through mail services to debtor.
MLCD	MailToCreditor	Cheque is to be sent through mail services to creditor.
MLFA	MailToFinalAgent	Cheque is to be sent through mail services to creditor agent.
CRDB	CourierToDebtor	Cheque is to be sent through courier services to debtor.
CRCD	CourierToCreditor	Cheque is to be sent through courier services to creditor.
CRFA	CourierToFinalAgent	Cheque is to be sent through courier services to creditor agent.
PUDB	PickUpByDebtor	Cheque will be picked up by the debtor.
PUCD	PickUpByCreditor	Cheque will be picked up by the creditor.
PUFA	PickUpByFinalAgent	Cheque will be picked up by the creditor agent.
RGDB	RegisteredMailToDebtor	Cheque is to be sent through registered mail services to debtor.
RGCD	RegisteredMailToCreditor	Cheque is to be sent through registered mail services to creditor.

CodeName	Name	Definition
RGFA	RegisteredMailToFinalAgent	Cheque is to be sent through registered mail services to creditor agent.

13.2.2.8 ChequeType2Code

Definition: Specifies the type of cheque.

Type: CodeSet

CodeName	Name	Definition
CCHQ	CustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. Synonym is 'corporate cheque'.
CCCH	CertifiedCustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. The financial institution prints and certifies the cheque, guaranteeing the payment.
BCHQ	BankCheque	Cheque drawn on the account of the debtor's financial institution, which is debited on the debtor's account when the cheque is issued.These cheques are printed by the debtor's financial institution and payment is guaranteed by the financial institution. Synonym is 'cashier's cheque'.
DRFT	Draft	A guaranteed bank cheque with a future value date (do not pay before], which in commercial terms is a 'negotiatable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.
ELDR	ElectronicDraft	An instrument with a future value date (do not pay before], which in commercial terms is a 'negotiatable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.

13.2.2.9 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern	[A-Z]{2,2}

Constraints

- **Country**

  The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

13.2.2.10 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

CodeName	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

13.2.2.11 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, eg, in a cover scenario.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
DISP	DispatchAdvice	Document is a dispatch advice.
PUOR	PurchaseOrder	Document is a purchase order.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

13.2.2.12 DocumentType5Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

CodeName	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.

CodeName	Name	Definition
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
CINV	CommercialInvoice	Document is an invoice.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
DISP	DispatchAdvice	Document is a dispatch advice.
BOLD	BillOfLading	Document is a shipping notice.
VCHR	Voucher	Document is an electronic payment document.
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.

13.2.2.13 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

13.2.2.14 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

13.2.2.15 ExternalCategoryPurpose1Code

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

13.2.2.16 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	5

13.2.2.17 ExternalDiscountAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

13.2.2.18 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

13.2.2.19 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	35

13.2.2.20 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

13.2.2.21 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

13.2.2.22 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

13.2.2.23 ExternalServiceLevel1Code

Definition: Specifies the external service level code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

13.2.2.24 ExternalTaxAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

minLength	1
maxLength	4

13.2.2.25 Frequency10Code

Definition: Specifies the regularity of an event.

Type: CodeSet

CodeName	Name	Definition
NEVR	Never	Event does never take place.
YEAR	Annual	Event takes place every year or once a year.
RATE	Rate	Event takes place based on a change of a rate.
MIAN	SemiAnnual	Event takes place every six months or two times a year.
QURT	Quarterly	Event takes place every three months or four times a year.

13.2.2.26 Gender1Code

Definition: Specifies the gender of a person.

Type: CodeSet

CodeName	Name	Definition
FEMA	Female	Individual is a female.
MALE	Male	Individual is a male.

13.2.2.27 Instruction3Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: CodeSet

CodeName	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/ claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/ claimant by the most efficient means of telecommunication.

13.2.2.28 LanguageCode

Definition: Specifies a language.

Type: CodeSet

Constraints

- **ValidationByTable**

  Must be a valid terrestrial language.

13.2.2.29 NamePrefix1Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

CodeName	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MIST	Mister	Title of the person is Mister or Mr.
MISS	Miss	Title of the person is Miss.
MADM	Madam	Title of the person is Madam.

13.2.2.30 NationalityCode

Definition: Specifies the country where a person was born or is naturalised.

Type: CodeSet

Constraints

- **ValidationByTable**

  Must be a valid nationality.

13.2.2.31 OrganisationLegalStatus1Code

Definition: Specifies the status of a legal entity.

Type: CodeSet

CodeName	Name	Definition
CIOC	CharitableIncorporatedOrganisation	Charitable incorporated organisation (CIO)
CHAR	Charity	Charity
CICC	CommunityInterestCompany	Community Interest Company (CIC)
GENP	GeneralPartnership	General partnership
IAPS	IndustrialAndProvidentSociety	For example a co-operative, which does include Ltd. or charity.
LLPP	LimitedLiabilityPartnership	Limited liability partnership (LLP)
PCLG	PrivateCompanyLimitedByGuarantee	Private company limited by guarantee (Ltd.)
LIMP	LimitedPartnership	Limited partnership (LP)
PCLS	PrivateCompanyLimitedByShares	Private company limited by shares (Ltd.)
PCLC	PublicLimitedCompany	Public limited company (Plc.)
SOLE	SoleProprietorship	Sole proprietorship/Sole trader

CodeName	Name	Definition
UNLC	UnlimitedCompany	Unlimited company
UNLT	UnlimitedTrust	Unlimited trust

13.2.2.32 PaymentMethod3Code

Definition: Specifies the transfer method that will be used to transfer an amount of money.

Type: CodeSet

CodeName	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.

13.2.2.33 PersonIdentificationType5Code

Definition: Specifies an alternative identification of an individual person, for example, national registration identification number, passport number.

Type: CodeSet

CodeName	Name	Definition
AREG	AlienRegistrationNumber	Number assigned by a government agency to identify foreign nationals.
CPFA	CPFAccountNumber	Account issued by the Central Provident Fund Board (Singapore).
DRLC	DriversLicenseNumber	Number assigned by a license authority to a driver's license.
EMID	EmployerIdentificationNumber	Number assigned to an employer by a registration authority.
IDCD	IdentityCardNumber	Number assigned by a national authority to an identity card.
NRIN	NationalRegistrationIdentificationNumber	National registration identification number. In Singapore this is known as the NRIC.
OTHR	Other	Another type of identification type.
PASS	PassportNumber	Number assigned by a passport authority to a passport.
POCD	PostOfficeCardNumber	Post office card number as assigned by a national post office.
SOCS	SocialSecurityNumber	Number assigned by a social security agency.
SRSA	SRSAccountNumber	Supplementary retirement scheme account number.

CodeName	Name	Definition
GUNL	GunLicenseNumber	Gun license number as assigned by a gun licensing authority.

13.2.2.34 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

CodeName	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

13.2.2.35 RegulatoryReportingType1Code

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Type: CodeSet

CodeName	Name	Definition
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.
BOTH	Both	Regulatory information applies to both credit and debit sides.

13.2.2.36 RemittanceLocationMethod2Code

Definition: Specifies the method used to deliver the remittance advice information.

Type: CodeSet

CodeName	Name	Definition
FAXI	Fax	Remittance advice information must be faxed.
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.
EMAL	EMail	Remittance advice information must be sent through e-mail.
POST	Post	Remittance advice information must be sent through postal services.

CodeName	Name	Definition
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).

13.2.2.37 ResidentialStatus1Code

Definition: Specifies the residential status of an individual.

Type: CodeSet

CodeName	Name	Definition
RESI	Resident	Resident.
PRES	PermanentResident	Permanent resident.
NRES	NonResident	Non-resident.

13.2.2.38 SwitchStatus1Code

Definition: Specifies the status of a given account switch.

Type: CodeSet

CodeName	Name	Definition
ACPT	Accepted	Account switch is accepted. Usage: Accepted status should be used when account switch service receives and validates an information response request accepting the switch.
BTRQ	BalanceTransferRequested	Account balance transfer is requested. Usage: Balance transfer requested status should be used when account switch service receives and validates a request balance transfer request.
BTRS	BalanceTransferResponse	Balance transfer responded. Usage: Balance transfer responded staus should be used when the account switch service receives and validates an acknowledge balance transfer request.
COMP	Completed	Account switch is completed. Usage: Completed status should be used when account switch service receives and validates a notify account switch complete request.
REDT	Redirection	Request for redirection. Usage: Redirection status should be used when the account switch service

CodeName	Name	Definition
		receives and validates the first redirection request.
REDE	RedirectionEnded	Redirection ended at the end of the redirection period. Usage: Indicates the cessation of account redirection by a particular service.
REJT	Rejected	Account switch is rejected. Usage: Rejected status should be used when account switch service receives and validates an information response request rejecting the account switch.
REQU	Requested	Information is requested for the account switch. Usage: Requested status should be used when the account switch service receives and validates an information request.
TMTN	Termination	Account switch is terminated. Usage: Terminated status should be used when the account switch service receives and validates a terminate switch request.

13.2.2.39 SwitchType1Code

Definition: Specifies the status of the switch either full or part for a given account.

Type: CodeSet

CodeName	Name	Definition
FULL	FullSwitch	Indicates a full switch for an account.
PART	PartSwitch	Indicates a partial switch for an account.

13.2.2.40 TaxRateMarker1Code

Definition: Specifies the rate of tax levied.

Type: CodeSet

CodeName	Name	Definition
ALPR	AmountQuotedLessLifeAssurance	Specifies the amount quoted less life assurance premium rate income tax.
ALIT	AmountQuotedLessStandardRate	Specifies the amount quoted less standard rate income tax.
GRSS	GrossAmount	Specifies an amount before the deduction of tax.

13.2.2.41 TaxRecordPeriod1Code

Definition: Specifies the period related to the tax payment.

Type: CodeSet

CodeName	Name	Definition
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.

13.2.3 Date

13.2.3.1 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

13.2.4 DateTime

13.2.4.1 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

13.2.5 IdentifierSet

13.2.5.1 AnyBICIdentifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Identification scheme: SWIFT; AnyBICIdentifier

Format

pattern	[A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

Constraints

- **AnyBIC**

  Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

13.2.5.2 BICFIIdentifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Identification scheme: SWIFT; BICIdentifier

Format

pattern	[A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

Constraints

- **BICFI**

  Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

13.2.5.3 IBAN2007Identifier

Definition: An identifier used internationally by financial institutions to uniquely identify the account of a customer at a financial institution, as described in the latest edition of the international standard ISO 13616: 2007 - "Banking and related financial services - International Bank Account Number (IBAN)".

Type: IdentifierSet

Identification scheme: National Banking Association; International Bank Account Number (ISO 13616)

Format

pattern	[A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Constraints

- **IBAN**

  A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

13.2.6 Indicator

13.2.6.1 BatchBookingIndicator

Definition: Identifies whether the sending party requests a single debit or credit entry per individual transaction or a batch entry for the sum of the amounts of all transactions.

Type: Indicator

Meaning When True: Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.

Meaning When False: Identifies that a single entry for each of the transactions in the batch or message is requested.

13.2.6.2 TrueFalseIndicator

Definition: A flag indicating a True or False value.

Type: Indicator

Meaning When True: True

Meaning When False: False

13.2.6.3 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

13.2.7 Quantity

13.2.7.1 DecimalNumber

Definition: Number of objects represented as a decimal number, eg, 0.75 or 45.6.

Type: Quantity

Format

totalDigits	18
fractionDigits	17

13.2.7.2 Number

Definition: Number of objects represented as an integer.

Type: Quantity

Format

totalDigits	18
fractionDigits	0

13.2.8 Rate

13.2.8.1 PercentageRate

Definition: Rate expressed as a percentage, ie, in hundredths, eg, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

totalDigits	11
fractionDigits	10
baseValue	100.0

13.2.9 Text

13.2.9.1 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}

13.2.9.2 Extended350Code

Definition: Code and / or description for values that are not yet part of the related code list.

Type: Text

Format

minLength	1
maxLength	350

13.2.9.3 Max10Text

Definition: Specifies a character string with a maximum length of 10 characters.

Type: Text

Format

minLength	1
maxLength	10

13.2.9.4 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

minLength	1
maxLength	140

13.2.9.5 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}

13.2.9.6 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

minLength	1
maxLength	16

13.2.9.7 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

minLength	1
maxLength	2048

13.2.9.8 Max256Text

Definition: Specifies a character string with a maximum length of 256 characters.

Type: Text

Format

minLength	1
maxLength	256

13.2.9.9 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

minLength	1
maxLength	34

13.2.9.10 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

minLength	1
maxLength	350

13.2.9.11 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

minLength	1
maxLength	35

13.2.9.12 Max3NumericText

Definition: Specifies a numeric string with a maximum length of 3 digits.

Type: Text

Format

pattern	[0-9]{1,3}

13.2.9.13 Max4AlphaNumericText

Definition: Specifies an alphanumeric string with a maximum length of 4 characters.

Type: Text

Format

minLength	1
maxLength	4
pattern	[a-zA-Z0-9]{1,4}

13.2.9.14 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

minLength	1
maxLength	4

13.2.9.15 Max6Text

Definition: Specifies a character string with a maximum length of 6 characters.

Type: Text

Format

minLength	1
maxLength	6

13.2.9.16 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

minLength	1
maxLength	70

13.2.9.17 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+" and "-" (up to 30 characters).

Type: Text

Format

pattern	\+[0-9]{1,3}-[0-9()+\-]{1,30}