## 1、初始化sdk

-(void)registerSDKWithAppID:(NSString \*)appID AppKey:(NSString \*)appKey result:
(YMTBigClassRoomRegisterResult)result;

- appld:业务后台分配
- appKey:业务后台分配
- result:结果回调

#### 2、登录

-(void)loginRoomWithRoomID:(NSString\*)roomID userID:(NSString \*)userID result:
(YMTBigClassRoomLoginRoomResult)result;

- roomld:房间ID
- userId:用户ID
- result:结果回调
- 说明,调用login 触发onLogin,获取YiMiToken

#### 3、加入教室

- (void)joinCloudRoomWithRoomID:(NSString \*)roomID userID:(NSString \*)userID
token:(NSString \*)yimiToken userRole:(NSUInteger)role nickName:(NSString
\*)nickName bussinessData:(NSString \*)bussinessData result:
(YMTBigClassRoomJoinRoomResult)result;

- roomld:房间ID
- userId:用户ID
- userRole:1=老师、2=学生 3=班主任
- nickName:用户昵称或者名字
- YiMIToken:登录获取的token
- bussinessData: 自定义业务json数据result: onJoinCloudRoom 回调

#### 4、退出教室

- (void)leaveCloudRoom:(YMTBigClassRoomLevelRoomResult)result;

- 离开教室
- result: leaveCloudRoom 回调

## 5、房间销毁

- (void)destroy;
- 释放和教室相关的信息


# 6、录播回放

- (void)recordPlayToken:(NSString \*)YiMiToken roomID:(NSString \*)roomId;
- YiMiToken: 登录返回的token
- roomld:房间Id

## 教室相关回调

```
typedef void(^YMTBigClassRoomRegisterResult)(B00L success, YMTRoomInfoCode code);
typedef void(^YMTBigClassRoomLoginRoomResult)(B00L success, YMTRoomInfoCode code);
typedef void(^YMTBigClassRoomJoinRoomResult)(B00L success, YMTRoomInfoCode code);
typedef void(^YMTBigClassRoomLevelRoomResult)(B00L success, YMTRoomInfoCode code);
```

## 云教室交互流程



# 云教室错误码定义

YMTRoomInfoCode:错误定义

```
typedef NS_ENUM(NSUInteger, YMTRoomInfoCode) {
   /**
   * 成功
    */
   YMTRoomInfoCodeSuccess,
   /**
   * 登录失败
   YMTRoomInfoCodeLoginFailed = 100,
    * 进入房间失败
    */
   YMTRoomInfoCodeJoinRoomFailed = 101,
    * 房间秘钥错误
   YMTRoomInfoCodeRoomSecretError = 102,
   * token 失效
    */
   YMTRoomInfoCodeTokenInvalid = 201,
    * 录播文件下载失败
   YMTRoomInfoCodeRecord_File_Download_Failed = 301
};
```