UMA & Optimus Schematics Documen

IVY Bridge(rPGA989)

Intel PCH(Panther Point)

DY :NotInstalled
UMA:UMA platform installed
OPS:Optimus
HR:Huron River
CR:Chief River
V: V-Series installed

<Core Design>

緯創資通 Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C

Title: Cover Page		
Size: A4	Document Number: LA480	Rev: SD
Date: Friday, January 06, 2012	Sheet 1 of 103	

Block Diagram (UMA/Optimus co-lay)

	LA480	LA580
Project Code	91.4TD01.001	91.4TE01.001
PCB P/N	11264	11273
Revision	SC	SC

##OnMainBoard

VRAM 2GB/1GB/512MB 88,89,90,91

DDR3 800MHz

NVIDIA N13P-GL (V) N13M-GE1 (B) 83.84,85,86,87

PCIe x 16 (Discrete only)

Intel CPU IVY Bridge DDRIII: 1066/1333/1600 MHz 4,5,6,7,8,9,10

DDRIII 1066/1333/1600 Channel A → DDRIII Slot 0 1066/1333/1600 14

DDRIII 1066/1333/1600 Channel B → DDRIII Slot 1 1066/1333/1600 15

FDI x 4 x 2 (UMA only)

DMI x 4

71.08111.N03, IC PCIE CTRL RTL8111F-CGT QFN 48P

HDMI 51

LCD 49

CRT 50

HDMI

LVDS

RGB CRT

Intel PCH Panther Point
USB 3.0/2.0 ports (14)
ETHERNET (10/100/1000Mb)
High Definition Audio
SATA ports (6)
PCIE ports (8)
LPC I/F
ACPI 1.1
17,18,19,20,21,22,23,24,25

PCIE x 1 → GLAN REALTEK RTL8111F 31 → RJ45 CONN 59

PCIE x 1/USB2.0 x 1 → Mini-Card WLAN 65

SATA x 1/USB2.0 x 1 → Mini-Card 66

USB 3.0 x 2 → USB x 2

USB 2.0 x 2 → USB x 2

SATA x 2 → HDD 56

SATA x 2 → ODD 56

Bluetooth 63

CAMERA 49

Finger Print BD

Finger Print 64

USB2.0 x 3

SD/MMC+/MS/ MS Pro/xD 74

CardReader ALCOR AU6435B52

USB 2.0 x 1

AZALIA

(V only) Internal DMIC

(B only) Analog DMIC

Combo Jack

Azalia CODEC REALTEK ALC269Q-VC2 29

2CH SPEAKER

SPI

Flash ROM 8MB 60

LPC Bus

LPC debug port 71

KBC NUVOTON NPCE885G 27

SMBus

G-Sensor (V only) 79

Touch PAD 69

Int. KB 69

Thermal EMC2103-2-AP 28

Fan 28

CPU
TPS5
INPUTS
DCBATOUT

SYSTEM
TPS
INPUTS
DCBATOUT 1D05V_VTT

SYSTEM DC/DC TPS51225 41	
INPUTS	OUTPUTS
DCBATOUT	3D3V_AUX_S5 5V_S5 3D3V_S5

SYSTEM DC/DC RT8207M 46	
INPUTS	OUTPUTS
DCBATOUT	0D75V_S0 1D5V_S3 DDR_VREF_S3

SYSTEM DC/DC TPS51640 44	
INPUTS	OUTPUTS
DCBATOUT	VCC_GFXCORE

VGA TPS51728 92	
INPUTS	OUTPUTS
DCBATOUT	VGA_CORE

TI CHARGER BQ24737 40	
INPUTS	OUTPUTS
+DC_IN_S5 +PBATT	DCBATOUT

SYSTEM DC/DC RT8068A 47	
INPUTS	OUTPUTS
3D3V_S5	1D8V_S0

LDO RT8207 46	
INPUTS	OUTPUTS
5V_S5	0D75V_S0

PCB LAYER

L1:Top	L5:VCC
L2:GND	L6:Signal
L3:Signal	L7:GND
L4:Signal	L8:Signal

<Core Design>

Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C

Title: Block Diagram

Size: A3 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 2 of 103

PCH Strapping

Chief River Schematic Checklist Rev0.72

Name	Schematics Notes
SPKR	**Reboot option at power-up** **Default Mode:** Internal weak Pull-down. **No Reboot Mode with TCO Disabled:** Connect to Vcc3_3 with 8.2-kΩ - 10-kΩ weak pull-up resistor.
INIT3_3V#	Weak internal pull-up. Leave as "No Connect".
GNT3#/GPIO55 GNT2#/GPIO53 GNT1#/GPIO51	GNT[3:0]# functionality is not available on Mobile. Mobile: Used as GPIO only Pull-up resistors are not required on these signals. If pull-ups are used, they should be tied to the Vcc3_3power rail.
SPI_MOSI	**Enable Danbury:** Connect to Vcc3_3 with 8.2-k? weak pull-up resistor. **Disable Danbury:** Left floating, no pull-down required.
NV_ALE	**Enable Danbury:** Connect to +NVRAM_VCCQ with 8.2-kohm weak pull-up resistor [CRB has it pulled up with 1-kohm no-stuff resistor] **Disable Danbury:** Leave floating (internal pull-down)
NC_CLE	DMI termination voltage. Weak internal pull-up. Do not pull low.
HAD_DOCK_EN# /GPIO[33]	Low (0) - Flash Descriptor Security will be overridden. Also, when this signals is sampled on the rising edge of PWROK then it will also disable Intel ME and its features. High (1) - Security measure defined in the Flash Descriptor will be enabled. Platform design should provide appropriate pull-up or pull-down depending on the desired settings. If a jumper option is used to tie this signal to GND as required by the functional strap, the signal should be pulled low through a weak pull-down in order to avoid asserting HDA_DOCK_EN# inadvertently. Note: CRB recommends 1-kohm pull-down for FD Override. There is an internal pull-up of 20 kohm for DA_DOCK_EN# which is only enabled at boot/reset for strapping functions.
HDA_SDO	Weak internal pull-down. Do not pull high. Sampled at rising edge of RSMRST#.
HDA_SYNC	Weak internal pull-down. Do not pull high. Sampled at rising edge of RSMRST#.
GPIO15	Low(0) - Intel ME Crypto Transport Layer Security (TLS) cipher suite with no confidentiality. High(1) - Intel ME Crypto Transport Layer Security (TLS) cipher suite with confidentiality. Note : This is an un-muxed signal. This signal has a weak internal pull-down of 20 kohm which is enabled when PWROK is low. Sampled at rising edge of RSMRST#. CRB has a 1-kohm pull-up on this signal to +3.3VA rail.
GPIO8	GPIO8 on PCH is the Integrated Clock Enable strap and is required to be pulled-down using a 1k +/- 5% resistor. When this signal is sampled high at the rising edge of RSMRST#, Integrated Clocking is enabled, When sampled low, Buffer Through Mode is enabled.
GPIO27	**Default = Do not connect (floating)** High(1) = Enables the internal VccVRM to have a clean supply for analog rails. No need to use on-board filter circuit. Low (0) = Disables the VccVRM. Need to use on-board filter circuits for analog rails.

Processor Strapping

Chief River Schematic Checklist Rev0.72

Pin Name	Strap Description	Configuration (Default value for each bit is 1 unless specified otherwise)	Default Value
CFG[2]	**PCI-Express Static Lane Reversal**	**1:** Normal Operation. **0:** Lane Numbers Reversed 15 -> 0, 14 -> 1, ...	**1**
CFG[4]		**1:** Disabled - No Physical Display Port attached to Embedded DisplayPort. **0:** Enabled - An external Display Port device is connectd to the EMBEDDED display Port	**0**
CFG[6:5]	**PCI-Express Port Bifurcation Straps**	11 : x16 - Device 1 functions 1 and 2 disabled 10 : x8, x8 - Device 1 function 1 enabled ; function 2 disabled 01 : Reserved - (Device 1 function 1 disabled ; function 2 enabled) 00 : x8, x4, x4 - Device 1 functions 1 and 2 enabled	**11**
CFG[7]	**PEG DEFER TRAINING**	**1:** PEG Train immediately following xxRESETB de assertion **0:** PEG Wait for BIOS for training	**1**

POWER PLANE	VOLTAGE	Voltage Rails ACTIVE IN	DESCRIPTION
5V_S0 3D3V_S0 1D8V_S0 1D5V_S0 1D05V_VTT 1D0V_S0 VCCSA 0D75V_S0 VCC_CORE VCC_GFXCORE 1D8V_VGA_S0 3D3V_VGA_S0 1V_VGA_S0	5V 3.3V 1.8V 1.5V 1.05V 1.0V 0.9 - 0.675V 0.75V 0.35V to 1.5V 0.4 to 1.25V 1.8V 3.3V 1V	S0	CPU Core Rail Graphics Core Rail
5V_USBX_S3 1D5V_S3 DDR_VREF_S3	5V 1.5V 0.75V	S3	
BT+ DCBATOUT 5V_S5 5V_AUX_S5 3D3V_S5 3D3V_AUX_S5	6V-14.1V 6V-14.1V 5V 5V 3.3V 3.3V	All S states	AC Brick Mode only
1D05V_LAN	1.05V	S0/M0, SX/M3	ON whenever iAMT is active
3D3V_M 1D05V_M	3.3V 1.05V	S0/M0, SX/M3, WOL_EN	ON for iAMTLegacy WOL
3D3V_AUX_KBC	3.3V	DSW, Sx	ON for supporting Deep Sleep states
3D3V_AUX_S5	3.3V	G3, Sx	Powered by Li Coin Cell in G3 and 3D3V_S5 in Sx

PCIe Routing

LANE1	X
LANE2	Mini Card2(WWAN)
LANE3	Card Reader
LANE4	Mini Card1(WLAN)
LANE5	X
LANE6	Intel GBE LAN / LAN
LANE7	X
LANE8	Express Card

USB Table

port9 is debug port

Pair	Device
0	USB3.0 ext port 1
1	USB3.0 ext port 2
2	USB3.0 ext port 3
3	USB3.0 ext port 4
4	BLUETOOTH (USB1.1)
5	Fingerprint (USB1.1)
6	X
7	X
8	Mini Card2 (WWAN)
9	USB ext. port 4 / E-SATA /USB CHARGER
10	CARD READER
11	Mini Card1 (WLAN)
12	CCD
13	New Card

SMBus ADDRESSES

I²C / SMBus Addresses Device	Ref Des	Chief River CRV Address	Hex	Bus
EC SMBus 1 Battery CHARGER				BAT_SCL/BAT_SDA BAT_SCL/BAT_SDA BAT_SCL/BAT_SDA
EC SMBus 2 PCH eDP				SML1_CLK/SML1_DATA SML1_CLK/SML1_DATA SML1_CLK/SML1_DATA
PCH SMBus SO-DIMMA (SPD) SO-DIMMB (SPD) Digital Pot G-Sensor MINI				PCH_SMBDATA/PCH_SMBCLK PCH_SMBDATA/PCH_SMBCLK PCH_SMBDATA/PCH_SMBCLK PCH_SMBDATA/PCH_SMBCLK PCH_SMBDATA/PCH_SMBCLK PCH_SMBDATA/PCH_SMBCLK

SATA Table

SATA Pair	Device
0	HDD1
1	mSATA
2	N/A
3	N/A
4	ODD
5	ESATA

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: Table of Content

Size: A3 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 3 of 103

SSID = CPU

01.00IVY.000 IVY BRIDGE ORCAD SYMBOL.

Note:
Intel DMI supports both Lane Reversal and polarity inversion but only at PCH side. This is enabled via a soft strap.

Signal Routing Guideline:
PEG_ICOMPO keep W/S=12/15 mils and routing length less than 500 mils.
PEG_ICOMPI & PEG_RCOMPO keep W/S=4/15 mils and routing length less than 500 mils.

CPU1A — SANDY — 1 OF 9

DMI: DMI_TXN[3:0] / DMI_TXP[3:0] / DMI_RXN[3:0] / DMI_RXP[3:0]

Note:
Intel FDI supports both Lane Reversal and polarity inversion but only at PCH side. This is enabled via a soft strap.

Intel(R) FDI: FDI_TXN[7:0] / FDI_TXP[7:0] / FDI_FSYNC0 / FDI_FSYNC1 / FDI_INT / FDI_LSYNC0 / FDI_LSYNC1

Note:
Lane reversal does not apply to FDI sideband signals.

eDP: 1D05V_VTT, R402 24D9R2F-L-GP, R403 10KR2J-3-GP (DY), DP_COMP, eDP_HPD, EDP_COMPIO, EDP_ICOMPO, EDP_HPD, EDP_AUX, EDP_AUX#, EDP_TX0–3, EDP_TX#0–3

PCI EXPRESS* - GRAPHICS

PEG_ICOMPI / PEG_ICOMPO / PEG_RCOMPO — J22 PEG_IRCOMP_R — R401 1 24D9R2F-L-GP — 1D05V_VTT

NOTE.
If PEG is not implemented, the RX&TX pairs can be left as No Connect

PEG_RXN[0..15] 83 — PEG_RXP[0..15] 83

PEG Static Lane Reversal

PEG_TXN[0..15] 83 — PEG_TXP[0..15] 83

SCD22U10V2KX-1GP (OPS)

SANDY — SKT-BGA989C470395-1H180

62.10055.421
2nd = 62.10040.771

NOTE:
Select a Fast FET similar to 2N7002E whose rise/ fall time is less than 6 ns. If HPD on eDP interface is disabled, connect it to CPU VCCIO via a 10-kΩ pull-Up resistor on the motherboard.

Signal Routing Guideline:
EDP_ICOMPO keep W/S=12/15 mils and routing length less than 500 mils.
EDP_COMPIO keep W/S=4/15 mils and routing length less than 500 mils.

NOTE.
Processor strap CFG[4] should be pulled low to enable Embedded DisplayPort.

<Core Design>

緯創資通 Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C

Title: CPU (PCIE/DMI/FDI)
Size: A3 | Document Number: LA480 | Rev: SD
Date: Friday, January 06, 2012 | Sheet 4 of 103

SSID = CPU



Disabling Guidelines:
If motherboard only supports
Connect DPLL_REF_SSCLK on Pr
1K +/- 5% resistor.
Connect DPLL_REF_SSCLK# on P
through 1K +/- 5% resistorpo
wasted.

ugh

In order to minimize resistance, use thick traces to route all COMP signals, use 10-mils wide trace for routing less than 500 mils, or 20-mils wide trace for routing between 500 mils and 1000 mils. Keep 20-mils spacing to any other signals in order to minimize crosstalk.

DEL U501
DEL R519
DEL C503
DEL R517
DEL R515

ASM R510
ASM R509

<Core Design>

Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C

Title: CPU (THERMAL/CLOCK/PM)

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 5 of 103

SSID = CPU



<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title	CPU (DDR)	
Size A3	Document Number LA480	Rev SD
Date: Friday, January 06, 2012	Sheet 6 of 103	

SSID = CPU



PEG Static Lane Reversal - CFG2 is for the 16x	
CFG2	1: Normal Operation; Lane # definition matches socket pin map definition 0:Lane Reversed



Display Port Presence Strap	
CFG4	1: Disabled; No Physical Display Port attached to Embedded Display Port 0: Enabled; An external Display Port device is connected to the Embedded Display Port



PCIE Port Bifurcation Straps	
CFG[6:5]	11: x16 - Device 1 functions 1 and 2 disabled 10: x8, x8 - Device 1 function 1 enabled ; function 2 disabled 01: Reserved - (Device 1 function 1 disabled ; function 2 enabled) 00: x8,x4,x4 - Device 1 functions 1 and 2 enabled



PEG DEFER TRAINING	
CFG7	1: PEG Train immediately following xxRESETB de assertion 0: PEG Wait for BIOS for training



<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: CPU (RESERVED)

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 7 of 103

POWER

CPU1F

6 OF 9

SANDY

PEG AND DDR

CORE SUPPLY

SVID

SENSE LINES

0511-CHECK CAP.

VCC CORE:53A

VCC_CORE

C801 C802 DY C803 C804 DY C811 SC10U6D3V5KX-1GP

C815 C817 C818 C819 C820 SC10U6D3V5KX-1GP

C816 C821 C822 C823 DY C824 C825 C826 C827 SC10U6D3V5KX-1GP

C837 C836 C835 C834 C833 C832 DY C831 C828 SC10U6D3V5KX-1GP

VCC_CORE

AG35 AG34 AG33 AG32 AG31 AG30 AG29 AG28 AG27 AG26 AF35 AF34 AF33 AF32 AF31 AF30 AF29 AF28 AF27 AF26 AD35 AD34 AD33 AD32 AD31 AD30 AD29 AD28 AD27 AD26 AC35 AC34 AC33 AC32 AC31 AC30 AC29 AC28 AC27 AC26 AA35 AA34 AA33 AA32 AA31 AA30 AA29 AA28 AA27 AA26 Y35 Y34 Y33 Y32 Y31 Y30 Y29 Y28 Y27 Y26 V35 V34 V33 V32 V31 V30 V29 V28 V27 V26 U35 U34 U33 U32 U31 U30 U29 U28 U27 U26 R35 R34 R33 R32 R31 R30 R29 R28 R27 R26 P35 P34 P33 P32 P31 P30 P29 P28 P27 P26 — VCC

0511-CHECK CAP.

VCCIO:8.5A

0511-CHECK

1D05V_VTT

VCCIO: AH13 AH10 AG10 AC10 Y10 U10 P10 L10 J14 J13 J12 J11 H14 H12 H11 G14 G13 G12 F14 F13 F12 F11 E14 E12

C805 C806 C807 C808 C809 C810 C838 C839 C840 DY C841 SC10U6D3V5KX-1GP

Reserve C846 & C847

VCCIO: E11 D14 D13 D12 D11 C14 C13 C12 C11 B14 B12 A14 A13 A12 A11

C812 C813 C814 C829 C830 C842 C843 C844 DY C845 SC10U6D3V5KX-1GP

VCCIO: J23

For CRB VIDSOUT need to pull high 130 ohm closr to CPU and IMVP7
For CRB VIDALERT# need to pull high 75 ohm close to CPU

R807 75R2F-2-GP 1D05V_VTT

VIDALERT# AJ29 H_CPU_SVIDALRT#
VIDSCLK AJ30 H_CPU_SVIDCLK
VIDSOUT AJ28 H_CPU_SVIDDAT

R803 43R2J-GP

VR_SVID_ALERT# 42
H_CPU_SVIDCLK 42
H_CPU_SVIDDAT 42

R804 130R2F-1-GP 1D05V_VTT 0511-CHECK

check
Place neer PCU pin.

1D05V_VTT

R808 10R2F-L-GP VCCIO_SENSE

VSSIO_SENSE

R809 10R2F-L-GP

VCC_CORE

R801 100R2F-L1-GP-U

VCC_SENSE AJ35
VSS_SENSE AJ34

VCCSENSE 42
VSSSENSE 42

R802 100R2F-L1-GP-U

VCCIO_SENSE B10
VSSIO_SENSE A10

VCCIO_SENSE 45
VSSIO_SENSE 45

SANDY
62.10055.421
2nd = 62.10040.771

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: CPU (VCC_CORE)

Size: Custom | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 8 of 103

POWER

0511-CHECK CAP

VCC_GFXCORE

PROCESSOR VAXG: 24A

0511-CHECK

C901 C902 C903 C904 C905 C906 RC901 — SC10U6D3V5KX-1GP; RC901 SC33P50V2JN-3GP DY

C907 C908 C918 C919 C920 C921 RC902 — SC10U6D3V5KX-1GP; RC902 SC33P50V2JN-3GP DY

CPU1G — 7 OF 9 — SANDY

GRAPHICS

AT24 AT23 AT21 AT20 AT18 AT17 AR24 AR23 AR21 AR20 AR18 AR17 AP24 AP23 AP21 AP20 AP18 AP17 AN24 AN23 AN21 AN20 AN18 AN17 AM24 AM23 AM21 AM20 AM18 AM17 AL24 AL23 AL21 AL20 AL18 AL17 AK24 AK23 AK21 AK20 AK18 AK17 AJ24 AJ23 AJ21 AJ20 AJ18 AJ17 AH24 AH23 AH21 AH20 AH18 AH17 — VAXG

SENSE LINES

VAXG_SENSE — AK35 — VCC_AXG_SENSE 42

VSSAXG_SENSE — AK34 — VSS_AXG_SENSE 42

VCC_GFXCORE

R906 100R2F-L1-GP-U

VCC_AXG_SENSE

VSS_AXG_SENSE

R907 100R2F-L1-GP-U

Refer to the latest Huron River Mainstream PDG (Doc# 436735) for more details on S3 power reduction implementation.

+V_SM_VREF_CNT should have 10 mil trace width

VREF

SM_VREF — AL1 — +V_SM_VREF_CNT 37

Routing Guideline:
Power from DDR_VREF_S3 and +V_SM_VREF_CNT should have 10 mils trace width.

DDR3 -1.5V RAILS

VDDQ:5A

1D5V_S0

VDDQ — AF7 AF4 AF1 AC7 AC4 AC1 Y7 Y4 Y1 U7 U4 U1 P7 P4 P1

C909 DY C910 C911 C912 C913 C914 — SC10U6D3V5KX-1GP

SA RAIL

VCCA:6A

VCCSA

VCCSA — M27 M26 L26 J26 J25 J24 H26 H25

C916 C915 C917 — SC10U6D3V5KX-1GP

+V0.85S - VCCSA - System Agent rail voltage can be
[0.9, 0.725, 0.8, 0.675] V for IVB
[0.9, 0.8] V for SNB

MISC

VCCSA_SENSE — H23 — VCCSA_SENSE 48

FC_C22 — C22

VCCSA_VID1 — C24

VCCSA_SELECT0 48

VCCSA_SELECT1 48

RN901 SRN1KJ-7-GP

1.8V RAIL

1D8V_S0

VCCPLL:1.2A

VCCPLL — B6 A6 A2

C926 C923 C922 C924 — SC10U6D3V5KX-1GP; SC10U10V2KX-1GP

SANDY
62.10055.421
2nd = 62.10040.771

<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: CPU (VCC_GFXCORE)

Size: A3 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 9 of 103

SSID = CPU





<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: CPU (VSS)

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 10 of 103

BLANK

<Core Design>

緯創資通 Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C

Title: <Title>		
Size: A4	Document Number: LA480	Rev: SD
Date: Friday, January 06, 2012	Sheet 11 of 103	

VREF circuit -M1 (Voltage Driver Network) & M3 (Driven by Processor) Implementation

CAD Note: All VREF traces should have 20:20 mil trace geometry. Note that while 20 mil trace width is optimal, short violations is acceptable if required due to tight routing constraints.



<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title			
M3			
Size A3	Document Number LA480		Rev SD
Date: Friday, January 06, 2012	Sheet 12 of 103		

BLANK

<Core Design>

緯創資通 Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C

Title: <Title>		
Size: A4	Document Number: LA480	Rev: SD
Date: Friday, January 06, 2012	Sheet 13 of 103	

SSID = MEMORY



Note:
If SA0 DIM0 = 0, SA1_DIM0 = 0
SO-DIMMA SPD Address is 0xA0
SO-DIMMA TS Address is 0x30

If SA0 DIM0 = 1, SA1_DIM0 = 0
SO-DIMMA SPD Address is 0xA2
SO-DIMMA TS Address is 0x32

Thermal EVENT

Place these caps close to VTT1 and VTT2.

SODIMM A DECOUPLING

Layout Note:
Place these Caps near SO-DIMMB.

<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: DDR3-SODIMM1

Size: A2 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 14 of 103

SSID = MEMORY



Place these caps close to VTT1 and VTT2.

Note:
SO-DIMMB SPD Address is 0xA4
SO-DIMMB TS Address is 0x34

SO-DIMMB is placed farther from the Processor than SO-DIMMA

62.10017.X41
3RD:62.10017.V51

<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: DDR3-SODIMM2

Size	Document Number	Rev
A2	LA480	SD

Date: Friday, January 06, 2012 Sheet 15 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***DDR3-SODIMM2***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 16 of 103



<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: PCH : LVDS/CRT/DDI

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 17 of 103



BOOT BIOS Strap

GNT1#/GPIO51	SATA1GP/GPIO19	BOOT BIOS Location
0	0	LPC
0	1	Reserved
1	0	Reserved
1	1	SPI(Default)

Gx8 USB Table

Pair	Device
0	X
1	USB3.0, ext port1
2	USB2.0, ext port4
3	USB3.0, ext port2
4	Bluetooth
5	CARD READER
6	X
7	X
8	3G
9	USB2.0, ext. port 3
10	Finger Print
11	Mini Card1 (WLAN)
12	CAMERA
13	X

USB 2.0 Overcurrent Pin Default Usage

Pin	Default Port Mapping	Pin	Default Port Mapping
OC0#	Port 0, Port 1	OC4#	Port 8, Port 9
OC1#	Port 2, Port 3	OC5#	Port 10, Port 11
OC2#	Port 4, Port 5	OC6#	Port 12, Port 13
OC3#	Port 6, Port 7	OC7#	Not Used

<Core Design>
緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.

Title: PCH : PCI/USB/NVRAM/RSVD

Size: A2 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 18 of 103

SSID = PCH



<Core Design>
Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.

Title: **PCH : DMI/FDI/PM**

Size	Document Number	Rev
A2	LA480	SD

Date: Friday, January 06, 2012 Sheet 19 of 103



Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.

Title: PCH : PCIE/SMBUS/CLK

Size: A2 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 20 of 103

SSID = PCH



<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.

Title: PCH : HDA/JTAG/SATA

Size	Document Number	Rev
A2	LA480	SD

Date: Friday, January 06, 2012 Sheet 21 of 103

R2202
HR:200K (64.20035.6DL)
CRV:10K (63.10334.1DL)

3D3V_S0 — R2202 10KR2J-3-GP — SATA_ODD_PRSNT#

3D3V_S0 — RN2203 SRN10KJ-5-GP — H_A20GATE, H_RCIN#

GPIO27 has a weak[20K] internal pull up. To enable on-die PLL Voltage regurator, should not place external pull down.

G-Sensor	ST	KIXNOK
R2226	DY	10K
R2221	10K	DY

Note:
For PCH debug with XDP, need to NO STUFF R2218

PCH1F — 6 OF 10

GPIO: BMBUSY#/GPIO0, TACH1/GPIO1, TACH2/GPIO6, TACH3/GPIO7, GPIO8, LAN_PHY_PWR_CTRL/GPIO12, GPIO15, SATA4GP/GPIO16, TACH0/GPIO17, SCLOCK/GPIO22, GPIO24, GPIO27, GPIO28, STP_PCI#/GPIO34, GPIO35, SATA2GP/GPIO36, SATA3GP/GPIO37, SLOAD/GPIO38, SDATAOUT0/GPIO39, SDATAOUT1/GPIO48, SATA5GP/GPIO49/TEMP_ALERT#, GPIO57

CPU/MISC: TACH4/GPIO68, TACH5/GPIO69, TACH6/GPIO70, TACH7/GPIO71, A20GATE, PECI, RCIN#, PROCPWRGD, THRMTRIP#, INIT3_3V#, DF_TVS, TS_VSS1, TS_VSS2, TS_VSS3, TS_VSS4, NC_1

NCTF: VSS_NCTF_15#BG2, VSS_NCTF_16#BG48, VSS_NCTF_17#BH3, VSS_NCTF_18#BH47, VSS_NCTF_19#BJ4, VSS_NCTF_20#BJ44, VSS_NCTF_21#BJ45, VSS_NCTF_22#BJ46, VSS_NCTF_23#BJ5, VSS_NCTF_24#BJ6, VSS_NCTF_25#C2, VSS_NCTF_26#C48, VSS_NCTF_27#D1, VSS_NCTF_28#D49, VSS_NCTF_29#E1, VSS_NCTF_30#E49, VSS_NCTF_31#F1, VSS_NCTF_32#F49

NCTF_TEST_PINS: A1, A47, A48, A49, A5, A6, B3, B47, B1, B48, B2, B49, B51, BE49, B52, BE48, BH3, BH47, BJ4, BJ44, BJ45, BJ46, BJ5, BJ6, C2, C48, D1, D49, E1, E49, F1, F49

PANTHER-GP-NF

21 S_GPIO — R2218 100R2J-2-GP — GPIO0
EC_SMI#
DGPU_HPD_INTR#
27 EC_SCI# — EC_SCI#
ICC_EN#
60 RTC_DET#
PCH_GPIO15
56 SATA_ODD_PRSNT# — SATA_ODD_PRSNT# — R2215 0R2J-2-GP — PCH_GPIO16
92,93 DGPU_PWROK — R2216 0R2J-2-GP — DGPU_PWROK_C
PCH_GPIO22
Gsensor_ID
PCH_GPIO27
PLL_ODVR_EN
PSW_CLR#
FP_DET#
DMI_OVRVLTG
FDI_OVRVLTG
MFG_MODE
GFX_CRB_DET
PCH_GPIO48
PCH_TEMP_ALERT#
USB3_PWR_ON

D2201 CH751H-40-1-GP

G2201 GAP-OPEN

SATA_ODD_PWRGT 56
SBA_Support# 20
VRAM_SIZE1
VRAM_SIZE2
H_A20GATE 27
H_PECI R — R2203 0R2J-2-GP — H_PECI 5,27
H_RCIN# 27
H_CPUPWRGD 5,97
PCH_THERMTRIP R — R2204 390R2J-1-GP — H_THERMTRIP# 5,36
INIT3_3V# — TP2201
NV_CLE

1D8V_S0 — R1808 2K2R2J-2-GP — NV_CLE — R1809 1KR2J-1-GP — H_SNB_IVB# 5

DMI & FDI Termination Voltage	
NV_CLE	Set to Vss when LOW Set to Vcc when HIGH

PROCPWRGD (PCH) --> UNCOREPOWRGOOD (CPU)
Indicates that VccSA, VDDQ, VccA (1.0V) and VccIO power supplies are stable. This signal will be asserted only after PWROK assertion.

TS Signal Disable Guideline:
TS_VSS1, TS_VSS2, TS_VSS3 and TS_VSS4 should not float on the motherboard. They should be tied to GND directly.

TS_VSS — R2210 0R0402-PAD

3D3V_S0 — R2207 10KR2J-3-GP — FDI_OVRVLTG — R2208 10KR2J-3-GP

FDI TERMINATION VOLTAGE OVERRIDE	
GPIO37 (FDI_OVRVLTG)	LOW - Tx, Rx terminated to same voltage (DC Coupling Model DEFAULT)

3D3V_S0 — R2209 10KR2J-3-GP — DMI_OVRVLTG — R2210 10KR2J-3-GP

DMI TERMINATION VOLTAGE OVERRIDE	
GPIO36 (DMI_OVRVLTG)	LOW - Tx, Rx terminated to same voltage (DC Coupling Model DEFAULT)

3D3V_S0 — R2220 10KR2J-3-GP — PCH_GPIO48
FP_DET# — R2224 10KR2J-3-GP
PCH_TEMP_ALERT# — R2222 10KR2J-3-GP
RN2201 SRN10KJ-6-GP — EC_SMI#, EC_SCI#, DGPU_HPD_INTR#, PCH_GPIO22
R2225 10KR2J-3-GP — PSW_CLR#
R2228 10KR2J-3-GP — MFG_MODE
R2229 10KR2J-3-GP — PCH_GPIO27

3D3V_S5 — R2221 10KR2J-3-GP — Gsensor_ID — R2226 10KR2J-3-GP

3D3V_S5 — RN2204 SRN10KJ-5-GP — RTC_DET#, USB3_PWR_ON
R2201 1KR2J-1-GP — PCH_GPIO15
R2234 10KR2J-3-GP — PLL_ODVR_EN

FP_DET# — R2223 10KR2J-3-GP

TP2206 — PCH_NCTF_1
TP2212 — PCH_NCTF_7
TP2214 — PCH_NCTF_9
TP2215 — PCH_NCTF_10
TP2210 — PCH_NCTF_5
TP2213 — PCH_NCTF_8
TP2211 — PCH_NCTF_6
TP2207 — PCH_NCTF_2
TP2208 — PCH_NCTF_3
TP2209 — PCH_NCTF_4

	INTERNAL GFX	EXTERNAL GFX
R2205	DY	10K
R2206	100K	DY

3D3V_S0 — R2205 10KR2J-3-GP — GFX_CRB_DET — R2206 100KR2J-1-GP

3D3V_S0 — R2230 10KR2J-3-GP — R2232 10KR2J-3-GP — VRAM_SIZE1, VRAM_SIZE2

PLL ON DIE VR ENABLE
NOTE:This signal has a weak internal pull-up 20K ENABLED -- HIGH (R2212 UNSTUFFED) DEFAULT DISABLED -- LOW (R2212 STUFFED)

PLL_ODVR_EN — R2212 1KR2J-1-GP

Integrated Clock Enable functionality is achieved via soft-strap. The default is integrated clock enable.

Integrated Clock Chip Enable	
ICC_EN#	HIGH (R2211 DY)- DISABLED [DEFAULT] LOW (R2211)- ENABLED

ICC_EN# — R2211 1KR2J-1-GP

R2211 BOM CTRL
HR:1K
CRV:DY

GPIO8 has a weak[20K] internal pull up.
Integrated Clock Enable functionality is achieved via soft-strap. The default is integrated clock enable.

<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.

Title: PCH : GPIO/NTCF/MISC
Size: A2 | Document Number: LA480 | Rev: SD
Date: Friday, January 06, 2012 | Sheet 22 of 103

SSID = PCH

6A



<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: PCH : POWER1

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 23 of 103

SSID = PCH

POWER

PCH1J

PANTHER-GP-NF

10 OF 10

Clock and Miscellaneous | USB | PCI/GPIO/LPC | SATA | MISC | CPU | RTC | HDA



0.002A (0.1uFx1)

1.01A (Total current of VCCASW)

0.16A (Totally current of VCCVRM)

0.097A (Totally current of VCCSUS3_3)

0.08A

0.08A

0.055A

0.095A

0.001A

0.001A

0.01A

6uA

(10uFx1) (1uFx1)

(10uFx1)

(0.1uFx1)

(1uFx1)

(0.1uFx2) (4.7uFx1_0603)

(0.1uFx2) (1uFx1)

(1uFx1) (220uFx1)

(0.1uFx2)

<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: PCH : POWER2

Size: A3 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 24 of 103

SSID = PCH





<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: **PCH : VSS**

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 25 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Reserved***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 26 of 103


SSID = KBC
65W: 1.7V
90W: 3.3V
Code change to Low Active on 8/19
EC_GPIO47 High Active
Reset IC: Prevent BIOS data loss solution
EC GPIO standard PH/PL
BOM CTRL
MODEL_ID_AD (Pin100)
Pull Down
Pull High
Voltage
UMA
100.0K
33.0K
2.481V
OPTIMUS
100.0K
47.0K
2.245V
PCB Version A/D (Pin98)
Pull-Low Resistor
Pull-High Resistor (3D3V_AUX_S5)
Voltage
SA
100.0K
10.0K
3.0V
SB
100.0K
20.0K
2.75V
SC
100.0K
33.0K
2.48V
-1
100.0K
47.0K
2.24V
Reserved
100.0K
64.9K
2.0V
Reserved
100.0K
76.8K
1.87V
Reserved
100.0K
100.0K
1.65V
71.00885.A0G
IC EMB CTRL NPCE885PA0DX LQFP 128P
Wistron Corporation
Title
Size
Document Number
Rev
Date
Sheet
of

SSID = Thermal

Thermal sensor

Close to SO-DIMM on top side.

SA 0905 change to 390p

3
C2803 SC390P50V2KX-GP
Q2802 MMBT3904WT1G-GP

2200p close to smsc2103 chip

2
C2804 SC390P50V2KX-GP DY
Q2804 MMBT3904WT1G-GP
C2805 SC2200P50V2KX-2GP
REMOTE2-
REMOTE2+

between CPU, VGA and DIMM on bottom side

20110718_Carrey:
For Vendor suggestion, add 390pF Cap. as closed to pin B/C and E of Q2803

T8

1
Q2803 MMBT3904WT1G-GP
C2808 SC390P50V2KX-GP
2200p close to smsc2103 chip
C2802 SC2200P50V2KX-2GP
H_THERMDA
H_THERMDC

CPU backside or inside the socket

CPU TEMP:
H_THERMDA and H_THERMDC routing 10mil trace width and spacing. Locate Capacity near Thermal diode.

20110718_Carrey:
For Vendor suggestion, add 10k pull high to 3D3V_S0

3D3V_S0
R2812 10KR2J-3-GP DY
THERM_SCI#

3D3V_S0
R2801 6K8R2J-GP
SHDN_SEL

SHDN --> 2N3904 ON External diode

3D3V_S0
R2805 68R2-GP
U2801
C2806 SCD1U10V2KX-4GP
2103_VDD
VDD
DP1
DN1
DP2/DN3
ND2/DP3
SYS_SHDN#
ALERT#
SMCLK
SMDATA
GND
GND
GPIO1
GPIO2
TACH
PWM
TRIP_SET
SHDN_SEL
EMC2103-2-AP-GP
H_THERMDA
H_THERMDC
REMOTE2+
REMOTE2-
THERM_SYS_SHDN#
THERM_SCI#
27,86 SMBC_THERM
27,86 SMBD_THERM
2103_4
2103_5
TP2802
TP2803
RN2801
SRN10KJ-5-GP
3D3V_S0
FAN_TACH_1
D2801
CH551H-30PT-GP
83.R5003.C8F
1st = 83.R5003.J8F
2ND = 83.R5003.I8F
FAN_TACH
FAN_PWM
TRIP_SET R2806
649R2F-GP
T8 = 98
TRIP_SET: 649 ohm => 87 dgree C

pin6, ALERT# OD
pin7, SYS_SHDN# OD

4 WIRE PWM Fan Control circuit

5V_S0
C2801 SC4D7U6D3V3KX-GP
R2803 10KR2J-3-GP
R2802 0R0805-PAD
AFTP2807
FAN1
5V_S0_FAN
FAN_TACH
FAN_PWM
R2804 0R0402-PAD
EC2802 SC1KP50V2KX-1GP DY
EC2801 SC1KP50V2KX-1GP DY
FAN_PWM_C
ACES-CON4-GP-U1
20.F0714.004
CHECK PIN DEFINE
20100707_EMI
AFTP2801
AFTP2805
AFTP2806
FAN_PWM_C
FAN_TACH
5V_S0_FAN

3D3V_AUX_S5
D2802 BAT54PT-GP
83.00054.T81 DY
2ND = 83.BAT54.D81
3rd = 83.BAT54.S81
27,36,86 PURE_HW_SHUTDOWN#
R2810 10KR2J-3-GP DY
C2807 SCD1U10V2KX-5GP DY
Q2801 2N7002K-2-GP
84.2N702.031
2ND = 84.2N702.J31
THERM_SYS_SHDN#
IMVP_PWRGD_T
3D3V_S0
R2808 100KR2J-1-GP
3D3V_S0
R2809 10KR2J-3-GP
R2811 0R0402-PAD
IMVP_PWRGD 36,42

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: THERMAL SENSOR SMSC EMC2103

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 28 of 103



<Core Design>
緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.

Title: AUDIO CODEC

Size	Document Number	Rev
A2	LA480	SD

Date: Friday, January 06, 2012 Sheet 29 of 103

BLANK

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title

Reserved

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 30 of 103

25MHz XTAL



	C3103	C3148
VB480	15pF 78.15034.1FL	12pF
VB580	12pF 78.12034.1FL	12pF













緯創資通	Wistron Corporation 21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.	
Title	LAN_RTL8111F	
Size: A2	Document Number: LA480	Rev: SD
Date: Friday, January 06, 2012	Sheet 31 of 103	

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: R5U220 (CARD READER)

Size	Document Number	Rev
A1	LA480	SD

Date: Friday, January 06, 2012 Sheet 32 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Reserved***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 33 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Reserved***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 34 of 103

BLANK

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title

USB 3.0 Controller

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 35 of 103

Power Sequence



Run Power



1D5V_S0

MAX Current 3000 mA
Design Current 2100 mA
Total= 11.39A





<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: Power Plane Enable

Size	Document Number	Rev
A1	LA480	SD

Date: Friday, January 06, 2012 Sheet 36 of 103

Close to CPU
S3 Power Reduction Circuit Processor VREF_DQ Implementation

DEL R3714
R3705 ->100K
DY C3701

FROM M1/M3

12 +V_SM_VREF

R3707 1 DY 0R2J-2-GP

Q3708 2N7002K-2-GP
84.2N702.J31
2ND = 84.2N702.031

R3705 100KR2J-1-GP

C3701 SCD1U10V2KX-4GP DY

+V_SM_VREF_CNT 9

PM_SLP_S3# 19,27,36,47

Close to DIMM
S3 Power Reduction Circuit SM_DRAMPWROK

0D75V_S0

R3703 22R2J-2-GP

Q3701 2N7002K-2-GP
84.2N702.J31
2ND = 84.2N702.031

36,97 PS_S3CNTRL

1D5V_S0

R3704 220R2J-L2-GP DY

Q3702 DY 2N7002K-2-GP
84.2N702.J31
2ND = 84.2N702.031

PS_S3CNTRL

SM_DRAMPWROK must have a maximum of 15ns rise or fall time over VDDQ * 0.55± 200mV and the edge must be monotonic

Close to CPU
S3 Power Reduction Circuit SM_DRAMPWROK

3D3V_S5

add 0.1uF

R3713 200R2F-L-GP

19 PM_DRAM_PWRGD

R3715

PM_DRAM_PWRGD_R 0R0402-PAD

0D75V_EN

U3701 IN B VCC IN A GND OUT Y
74VHC1G09DFT2G-GP
OD AND gate required
73.01G09.AAH
2nd = 73.01G09.0AB
3rd = 73.01G09.BAH

C3704 SCD1U10V2KX-5GP DY

VDDPWRGOOD_R

1D5V_S0

R3708 200R2F-L-GP

R3719 130R2F-1-GP

VDDPWRGOOD 5

R3722 39R2J-L-GP DY

R3720 0R2J-2-GP DY

Q3707 DY 2N7002K-2-GP
84.2N702.J31
2ND = 84.2N702.031

36,97 PS_S3CNTRL

Close to CPU
S3 Power Reduction Circuit SM_DRAMPWROK

1D5V_S3

R3706 1KR2F-3-GP

R3709 DY 0R2J-2-GP

5 SM_DRAMRST#

R3711 0R0402-PAD

SM_DRAMRST#_R

Q3703 2N7002K-2-GP
84.2N702.J31
2ND = 84.2N702.031

R3701 4K99R2F-L-GP DY

SM_DRAMRST#_D

R3712 1KR2F-3-GP

DDR3_DRAMRST# 14,15

C3702 SC100P50V2JN-3GP DY

DRAMRST_CNTRL_PCH 12,20

C3703 SCD047U16V2KX-1-GP

S3 Power Reduction Circuit
SM_DRAMRST#

5 S3 Power Reduction

36,97 PS_S3CNTRL

Q3704 2N7002K-2-GP
84.2N702.J31
2ND = 84.2N702.031

0D75V_EN

1.05VTT_PWRGD 45,48

R3710 0R0402-PAD

19,27,36,47 PM_SLP_S3#

R3716 DY 22R2J-2-GP

0D75V_EN 46

C3705 SCD1U10V2KX-5GP DY

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ADAPTER

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 37 of 103

Adaptor in to generate DCBATOUT



DCIN14 for 14" VB480 & VB485
DCIN15 for 15" VB580 & VB585

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title	*DCIN_JACK*	
Size A3	Document Number **LA480**	Rev **SD**
Date: Friday, January 06, 2012	Sheet 38 of 103	

BATTERY CONNECTOR



DY on LAB stage

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title	BATT_CONN	
Size	Document Number LA480	Rev SD
Date: Friday, January 06, 2012	Sheet 39 of 103	



SSID = PWR.Plane.Regulator_5v3p3v



<Core Design>
緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title	TPS51123_5V_3D3V	
Size	Document Number	Rev SD
Date: Friday, January 06, 2012	Sheet 41 of 103	



<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title	TPS51640_CPU_CORE(1/3)	
Size	Document Number <Doc>	Rev SD
Date: Friday, January 06, 2012	Sheet 42 of 103	



	Main source	2nd source
PU4402	84.07608.037 FDMS7608S-GP	
PU4403	84.07608.037 FDMS7608S-GP	

BOM control

DCBATOUT

DCBATOUT_VCC_GFXCORE

PG4401 GAP-CLOSE-PWR
PG4402 GAP-CLOSE-PWR
PG4403 GAP-CLOSE-PWR
PG4404 GAP-CLOSE-PWR

DCBATOUT_VCC_GFXCORE

PC4409 SC10U25V5KX-GP
PC4402 SC10U25V5KX-GP
PC4403 SC10U25V5KX-GP
PC4404 SC10U25V5KX-GP
PC4410 SCD1U50V3KX-GP

PU4402
PU4403
FDMS3600-02-RJK0215-COLAY-GP
84.07608.037

PWR_GFX_CORE_DRVH
PWR_GFX_CORE_SW
PWR_GFX_CORE_BST
PWR_GFX_CORE_DRVL

PR4401 0R3J-0-U-GP
PWR_GFX_CBST1_1
PC4401 SC1U25V3KX-1-GP

Design current: 22A

PL4401 L-D36UH-1-GP

VCC_GFXCORE

PR4410 18KR2F-GP
PG4303 GAP-CLOSE-PWR-3-GP
PT4401 PT4402 PT4403 ST330U2VDM-4-GP

PR4407 121KR2F-L-GP

PR4405 28KR2F-GP
NTC-100K-1-GP PR4409
1st = 69.60011.071

PC4408 SCD022U25V2KX-GP

PWR_GFX_CORE_GSCN 42
PWR_GFX_CORE_GSCP 42

PU4401 TPS51601DRBR-GP
BST SKIP# PWM GND GND DRVH SW VDD DRVL

PWR_GFX_CORE_BST
42 PWR_GFX_GSKIP#
42 PWR_GFX_GPWM
PWR_GFX_CORE_DRVH
PWR_GFX_CORE_SW
PWR_GFX_CORE_DRVL

5V_S5
PC4407 SC2D2U10V3KX-1GP

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: TPS51640_CPU_CORE(3/3)

Size | Document Number: <Doc> | Rev: SD

Date: Friday, January 06, 2012 | Sheet 44 of 103

TPS51219 for 1D05V



<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: TPS51211_1D05V

Size | Document Number | Rev: SD

Date: Friday, January 06, 2012 | Sheet 45 of 103

SSID = PWR.Plane.Regulator_1p5v0p75v



<Core Design>

緯創資通	Wistron Corporation 21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.	
Title	RT8207M_1D5V_0D75V	
Size	Document Number <Doc>	Rev SD
Date: Friday, January 06, 2012	Sheet 46 of 103	

SSID = PWR.Plane.Regulator_1p8v

RT8068A for 1D8V_S0

Design Current=1.1A



<Core Design>

緯創資通	**Wistron Corporation** 21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.
Title	***PWM_1D8V_RT8015B***
Size	Document Number: Rev SD
Date: Friday, January 06, 2012	Sheet 47 of 103

TPS51461 for VCCSA



VID0	VID1	VCCSA
L	L	0.9V
L	H	0.8V
H	L	0.725V
H	H	0.675V

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title	*VCCSA_TPS51461*	
Size	Document Number <Doc>	Rev SD
Date: Friday, January 06, 2012	Sheet 48 of 103	

SSID = VIDEO

LVDS connector

LCD / Inverter Connector



CAMERA POWER



SILERGY	74.06288.07F	SY6288CAAC	High Active
DIODES	74.02171.07F	AP2171WG-7	High Active
UPI	74.07534.A7F	OBS	High Active
GMT	74.05240.A7F	OBS	High Active

LCD POWER









For EMI request
Close to LVDS connector



Panel BL brightness/Power En/BL En



<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: LCD Connector

Size	Document Number	Rev
A2	LA480	SD

Date: Friday, January 06, 2012 Sheet 49 of 103

CRT connector



CRT DDCDATA & DDCCLK level shift

Pull High 5V Design on CRT Board



CRT Hsync & Vsync level shift



CRT RGB







<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: CRT Connector

Size: A2 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 50 of 103

SSID = VIDEO

HDMI Passive Level Shifter

Close to HDMI Connector



HDMI CONNECTOR



EMI's request





ESD Request



HDMI DDC Passive Level Shifter





<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: HDMI Level Shifter/Connector

Size: A2 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 51 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***eDP***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 52 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***S-VIDEO***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 53 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Reserved***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 54 of 103

SSID = User.Interface

ITP Connector

H_CPURST# use pull-up Resistor close
ITP connector 500 mil (max),
others place near CPU side.



<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ITP		
Size: A4	Document Number: LA480	Rev: SD
Date: Friday, January 06, 2012	Sheet 55 of 103	

SATA HDD Connector



ODD Connector

SATA_RX- and SATA_RX+ Trace Length match within 20 mil

Mars:
Exchange ODD and ESATA differential pair each other.





74.02069.079 TI TPS2069DGNR MSOP 8P
74.07534.D79 UPI UP7534PRA8-15 MSOP 8P
74.00547.C79 GMT G547F1P81U MSOP 8P (OBS)
74.07534.A79 UPI UP7534ARA8-15 MSOP8P



When the drive is powered on, the FET to the MD/DA pin drive is OFF.
When the drive is powered off, the FET to the MD/DA pin is ON



SUPPORT ZERO SATA ODD



SATA Zero Power ODD

Current limit
Active High
typ =>2A



TI	74.02069.079	TPS2069DGNR	High Active
DIODES		AP2171WG-7	High Active
UPI	74.07534.A7F	OBS	High Active

<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: HDD/ODD
Size: A3 | Document Number: LA480 | Rev: SD
Date: Friday, January 06, 2012 | Sheet 56 of 103

BLANK

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: *E-SATA+USB*

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 57 of 103

Int. Digital MIC for V series





ME change P/N at SIT
Old 20.F1639.004
New 20.F1621.004

Int. Mono Analog MIC for B series



INTERNAL STEREO SPEAKERS





Table 58.1 - Bi-direction ESD multi-source

Supplier	Description	Lenovo P/N	Wistron P/N
ROHM	RSB5.6SMT2R	N/A	83.RSB56.BAF
ON SEMI	ESD5B5.0ST1G	N/A	83.ESD5B.0AF
NXP	PESD5V0S1BB	N/A	83.0005V.0AF

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: Audio Jack

Size: A2 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 58 of 103

FOR CO-LAY

GIGA Lan Transformer



1st
68.IH601.301(Taimag) for 1000
68.HH035.301(Taimag) for 10/100
2nd
68.2413S.30A(Lankom) for 1000
68.H6441.301(Lankom) for 10/100

TVS
83.00005.BAE
DIODE ARR SRV05-4.TCT S

83.09904.AAE
DIODE ESD AZC099-04S SOT23-6L

Swap for V480



LAN Connector





<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: RJ45 / Transformer

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 59 of 103

SSID = Flash.ROM

SPI FLASH ROM (8M byte) for PCH





4MB			
SO8	Marcronix	MX25L3206EM2I-12G	72.25320.C01
	Winbond	W25Q032BVSSIG	72.25Q32.A01
	Numonyx	N25Q032A13ESE40	72.25032.H01
8MB			
SO8	Marcronix	MX25L6406EM2I-12G	72.25640.D01
	Winbond	W25Q064CVSSIG	72.25Q64.B01
	Numonyx	N25Q064A13ESE40	72.25Q64.D01
16MB			
WSON	Marcronix	MX25L12836EZNI-10G	72.25128.X01
		MX25L12835EZNI-10G	72.25128.Y01
	Winbond	W25Q128BVEIG	72.25128.I01
	Numonyx	N25Q128A13EF840	72.25128.B03

SSID = RBATT





<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Flash/RTC***

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 60 of 103

USB Board CONN.



Place U6102 close to USBCN1

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: USB Connector

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 61 of 103

USB3.0 Port1

USB3.0 Port2

USB3.0 Port3

USB3.0 Port4

2A





TC6201 place near
the USB1 connector



TC6202 place near
the USB2 connector













<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: USB 3.0 Port*2

Size: A2 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 62 of 103

SSID = User.Interface

Bluetooth conn.



SILERGY	74.06288.07F	SY6288CAAC	High Active
DIODES	74.02171.07F	AP2171WG-7	High Active
UPI	74.07534.A7F	OBS	High Active
GMT	74.05240.A7F	OBS	High Active

BT Module pin definition is same as LA470





<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Bluetooth***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 63 of 103

Finger Printer Connector



<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title	***Finger Printer Connector***	
Size A4	Document Number **LA480**	Rev **SD**
Date: Friday, January 06, 2012	Sheet 64 of 103	

SSID = Wireless

Mini Card Connector(802.11a/b/g/n)



Place near MINI Card CONN



Reserve for AOAC





G6506~G6511
placememt close close WLAN1
in bottom side

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: MINICARD(WLAN)/ITP CONN

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 65 of 103

SSID = Wireless

mSATA for V Series Only

Mini Card Connector(Full Card)



<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***WWAN Connector***

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 66 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Reserved***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 67 of 103

SSID = User.Interface

















<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: LED Bard/Power Button

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 68 of 103

SSID = KBC

Internal KeyBoard Connector



KB14 for 14" VB480 & VB485
KB15 for 15" VB580 & VB585

* Membrane Pin Out Top View :

PIN #	7	11	13	18	14	10	17	15	16	4	23	22	19	20	21	24	12	1	8	9	5	6	3	2
As-sign	D 1	D 2	D 3	D 4	D 5	D 6	D 7	D 8	D 9	D 10	D 11	D 12	D 13	D 14	D 15	D 16	S 1	S 2	S 3	S 4	S 5	S 6	S 7	S 8

SSID = Touch.Pad

Normal Pad for B Series 5V
ClickPad for V Series 3.3V



Synaptics P/N	Models			
	B480	V480	B580	V580
TM-01146-006	✓			
TM-02023-001		✓		
TM-02060-001			✓	
TM-02045-001				✓
VDD	5V	3.3V	5V	3.3V
Pin 1	VDD	VDD	VDD	VDD
Pin 2	CLK	CLK	CLK	CLK
Pin 3	DAT	DAT	DAT	DAT
Pin 4	Left button	GND	GND	GND
Pin 5	Right button	NC	Left button	NC
Pin 6	GND	NC	Right button	NC

<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: TOUCH PAD CONNECTOR

Size: A2 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 69 of 103

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title
Hall Sensor

Size	Document Number	Rev
A4	**LA480**	**SD**

Date: Friday, January 06, 2012 Sheet 70 of 103



<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Dubug connector***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 71 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Reserved***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 72 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Reserved***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 73 of 103

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***CARD Reader CONN***

Size	Document Number	Rev
A2	LA480	SD

Date: Friday, January 06, 2012 Sheet 74 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***New Card***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 75 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Reserved***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 76 of 103

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title

Reserved

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 77 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***Reserved***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 78 of 103

G-Sensor
V Series Only





Layout Comment :

(1) Place C483, C484, Q46, R528, R530, C479, C476, R509, R508 close to U55.

(2) Avoid routing under DCDC switching area.

<Core Design>

緯創資通	**Wistron Corporation** 21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.	
Title	**G-Sensor**	
Size A4	Document Number **LA480**	Rev **SD**
Date: Friday, January 06, 2012	Sheet 79 of 103	

RFID



Table 80.1- Transistor multi-source

Supplier	Description	Lenovo P/N	Wistron P/N
NXP	PDTC115TE	N/A	84.00115.E1K
ROHM	LTC015TEB	N/A	84.00015.B1H
Panasonic	DRC9115T0L	N/A	84.09115.A11

Table 80.2- EEPROM multi-source

Supplier	Description	Lenovo P/N	Wistron P/N
ROHM	BUL08-1FVJ-WGE2	N/A	72.BUL08.A0Q
NXP	PCA24S08ADP	N/A	72.24S08.A0Q
SANYO	LE26CAP08TT-TLM-H	N/A	72.26C08.00R

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: RF ID

Size: A4 | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 80 of 103

BLANK

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title

Reserved

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 81 of 103

R8201 and R8203 Dual layout with TR8201



<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: IO Board Connector

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 82 of 103

SPEC. (DG-05587-001_v03_p.70)
PEX_CLK_REQ_N is an open-drain bi-directional signal;
by default it should have a 10 kΩ pull-up to 3.3V.
This signal is an active low signal.

PCI Express PEX_IOVVD/Q Combined (DG-05587-001_v03_p.72_Table 10)

Capacitor	Type	Footprint	Population	Location
1.0uF	X6S	0402	4	Under GPU
4.7uF	X6S	0603	2	Near GPU
10uF	X5R	0805	4	Midway Between GPU and Power Supply
22uF	X5R	0805	4	Midway Between GPU and Power Supply

X6S (+/-22%、-55~105℃)
X5R (+/-15%、-55~85℃)

1.05V ±30mV 3300mA total (DG-05587-001_v03_p.71_Table 9)

1uF(X5R) K0402 ×4 | 4.7uF(X5R) K0603 ×2 | 10uF(X5R) M0805 ×4 | 22uF(X5R) M0805 ×4

Under GPU | Near GPU | Midway Between GPU and Power Supply

SPEC. (DG-05587-001_v03_p.70)
For PCI ECPRESS connection,
please use 0.22uF,20%,0402,X5R
or better AC couplimg capacitors.

0.22uF(X5R) K0402

PCI Express PEX_SVDD/PLL_HVDD Connected to NV3V3 (DG-05587-001_v03_p.72_Table 12)

Capacitor	Type	Footprint	Population	Location
0.1uF	X5R	0402	1	Near GPU
4.7uF	X5R	0603	2	Near GPU

X5R (+/-15%、-55~85℃)

3.3V ±10% 210mA total (DG-05587-001_v03_p.71_Table 9)

0.1uF(X5R) K0402 ×1 | 4.7uF(X5R) K0603 ×2

Near GPU

dGPU reset

PCI Express PEX_PLLVDD (DG-05587-001_v03_p.72_Table 11)

Capacitor	Type	Footprint	Population	Location
100nF	X6S	0402	1	Under GPU
1.0uF	X5R	0603	1	Near GPU
4.7uF	X5R	0805	1	Near GPU

X6S (+/-22%、-55~105℃)
X5R (+/-15%、-55~85℃)

SPEC. (DG-05587-001_v03_p.70)
PEX_TSTCLK_OUT should be
terminated with a 200Ω resistor.

100nF(X7R) K0402 ×1 | 1.0nF(X5R) K0402 ×1 | 4.7nF(X5R) K0603 ×1

1.05V ±30mV 150mA total (DG-05587-001_v03_p.71_Table 9)

Stuff 0 ohm(63.00000.00L) for N13P-GS/N13M-GS,
Stuff bead(68.00082.001) for N13P-GL/N13M-GE

SPEC. (DG-05587-001_v03_p.214)
By default, pull-down the TESTMODE pin to GND with a 10kΩ resistor.
For XOR tree testing, TESTMODE should be pulled up to 3v3 with a 10 kΩ resistor.

SPEC. (DG-05587-001_v03_p.70)
PEX_TERMP is used for internal calibration;
pull-down this signal with 2.49 kΩ,1% resistor.

<Core Design>
Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C

Title: N13P_GPU (1/5): PEG
Size: A2 | Document Number: LA48 | Rev: SD
Date: Friday, January 06, 2012 | Sheet 83 of 103

LVDS Interface

SPEC. (DG-05587-001_v03_p.160)
Pull down IFPxy IOVDD with 10kΩ resistor.
Pull down IFPxy PLLVDD with 10kΩ resistor.
The other IO pins can be NC, this includes unused data lines.







HDMI Interface



<Core Design>

緯創資通 Wistron Corporation	21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.
Title	N13P_GPU (2/5): DIGITALOUT
Size A2 / Document Number LA48 / Rev SD	
Date: Friday, January 06, 2012	Sheet 84 of 103

E1 (DA-05691-001_v03_p.44_Table 2)
N13P-GL NC
N13M_GE1 NC
N13M-GS Pull down FB_CLAMP with a 10kΩ
N13P-GS Pull down FB_CLAMP with a 10kΩ

35mA
(DG-05587-001_v03_p.88_Table 25)

Mode D Command Mapping
(DG-05587-001_v03_p.78_Table 16)

N13x DDR3 mode D	Data Bits [31:0]	Data Bits [63:32]
FBx_CMD0	CS0#	
FBx_CMD1		
FBx_CMD2	ODT	
FBx_CMD3	CKE	
FBx_CMD4	A14	A14
FBx_CMD5	RST	RST
FBx_CMD6	A9	A9
FBx_CMD7	A7	A7
FBx_CMD8	A2	A2
FBx_CMD9	A0	A0
FBx_CMD10	A4	A4
FBx_CMD11	A1	A1
FBx_CMD12	BA0	BA0
FBx_CMD13	WE#	WE#
FBx_CMD14	A15	A15
FBx_CMD15	CAS#	CAS#
FBx_CMD16		CS0#
FBx_CMD17		
FBx_CMD18		ODT
FBx_CMD19		CKE
FBx_CMD20	A13	A13
FBx_CMD21	A8	A8
FBx_CMD22	A6	A6
FBx_CMD23	A11	A11
FBx_CMD24	A5	A5
FBx_CMD25	A3	A3
FBx_CMD26	BA2	BA2
FBx_CMD27	BA1	BA1
FBx_CMD28	A12	A12
FBx_CMD29	A10	A10
FBx_CMD30	RAS#	RAS#
FBx_CMD31		

FB CMD mapping
Mode D-N13x

FB CMD mapping
Mode D-N13x

66mA
(DG-05587-001_v03_p.88_Table 25)

1.05V ±30mV 167mA total
100nF(X7R)
K0402 ×3

66mA
(DG-05587-001_v03_p.88_Table 25)

Under GPU

Stuff 0 ohm(63.00000.00L) for N13P-GS/N13M-GS,
Stuff bead(68.00084.H41) for N13P-GL/N13M-GE

GPU FBVDDQ Decoupling (DG-05587-001_v03_p.86_Table 22)

Capacitor	Type	Footprint	Population		Locati
0.1uF	X7R	0402	8	8	Under
1uF	X7R	0603	2	2	Under
4.7uF	X6S	0603	2	2	Under
10uF	X5R	0805	4	4	Near

X7R (+/-15%、-55~125℃)
X6S (+/-22%、-55~105℃)
X5R (+/-15%、-55~85℃)

0.1uF(X7R)
K0402 ×8

Under GPU

1uF(X7R)
K0603 ×4

Near GPU

4.7uF(X5R)
K0603 ×2

10uF(X5R)
M0805 ×2

Default GPU Drive Calibration for DDR3 (DG-05587-001_v03_p.82_Table 17)

Memory/PKG	FBVDDQ	FBCAL_PU_GND	FBCAL_PU_VDDQ	FBCAL_TERM_GND
DDR3	1.5V	42.2Ω	40.2Ω	51.1Ω

*Use only 1% resistors for driver calibration.

FBx_PLL_AVDD, FB_DLL_AVDD and PLLVDD combined
(DG-05587-001_v03_p.88_Table 26)

Capacitor	Type	Footprint	Population	Location
100nF 22uF	X7R X5R	0402 0805	1 per pin 1	Under GPU Near GPU
Bead Type				
30Ω @100MHz (ESR=0.01Ω)		0603	1	Near GPU

X7R (+/-15%、-55~125℃)
X5R (+/-15%、-55~85℃)

FBCLK Termination placed at each VRAM
(DG-05587-001_v03_p.83_Table 19)

Memory ODTx, CKEx and RST Termination
(DG-05587-001_v03_p.84_Table 20)

Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C

Title: N13P_GPU (3/5): VRAM I/F
Size: A2
Document Number: LA48
Rev: SD
Date: Friday, January 06, 2012
Sheet 85 of 103





GPIO Description (DG-05587-001_v03_p.82_Tale 98)

GPIO pin Name	Normal Function	I/O	Function Description
GPIO0	GPU_VID4	O	GPU Core VDD VID4
GPIO1	GPU_VID3	O	GPU Core VDD VID3
GPIO2	LCD_BL_PWM	O	Panel Backlight PWM Brightness Control
GPIO3	LCD_VCC	O	Panel Power Enable
GPIO4	LCD_BLEN	O	panel Backlight Enale
GPIO5	GPU_VID1	O	GPU Core VDD VID1
GPIO6	GPU_VID2	O	GPU Core VDD VID2
GPIO7	3D Vision	O	3D Vision Left/Right signal
GPIO8	OVERT	I/O	Active Low Thermal Catastrophic Over Temperature
GPIO9	ALERT	I/O	Active Low Thermal Alert
GPIO10	MEM_VREF_CTL	O	Memory VREF Control
GPIO11	GPU_VID0	O	GPU Core VDD VID0
GPIO12	PWR_LEVEL	I	AC Power Detect Input. High = AC, Low = Battery
GPIO13	GPU_VID5	O	GPU Core VDD VID5
GPIO14	HPD_AB	I	Hot Plog Detect for IFPAB
GPIO15	HPD_C	I	Hot Plog Detect for IFPC
GPIO16	MEM_VDD_CTL	O	Memory VDD VID
GPIO17	HPD_D	I	Hot Plog Detect for IFPD
GPIO18	HPD_E	I	Hot Plog Detect for IFPE
GPIO19	HPD_F	I	Hot Plog Detect for IFPF
GPIO20	Reserved		
GPIO21	Reserved		



PLL Power Rail Filter-PLL_VDD
(DG-05587-001_v03_p.177_Table 96)

Capacitor Type		Footprint	Population	Location
100nF	X7R	0402	1	Under GPU
22uF	X7R	0805	1	Near GPU
Bead Type				
30Ω(ESR=0.05)		0402	1	Near GPU

X7R (+/-15% \ -55~125℃)

PLL Power Rail Filter-SP_PLLVDD and VIDPLLVDD Combined
(DG-05587-001_v03_p.178_Table 97)

Capacitor Type		Footprint	Population	Location
100nF	X7R	0402	2	Under GPU
4.7uF	X7R	0402	1	Near GPU
22uF	X7R	0805	1	Near GPU
Bead Type				
180Ω(ESR=0.2)		0603	1	Near GPU

X7R (+/-15% \ -55~125℃)

SPEC. (DG-05587-001_v03_p.176)
XTALOUTBUFF signal should be pull down using a 10kΩ resistor.
XTALSSIN signal should be pull down using a 10kΩ resistor.
REmember to place components as close ti the GPU as possible.

SPEC. (DG-05587-001_v03_p.162)
Adding a pull down to the DACA_VDD with a 10kΩ resistor to GND.
All other DAC I/O pins (including DACA_VREF, DACA_REST)
can be left floating.





SPEC. (DG-05587-001_v03_p.191_Table 102)
Multi_Strap_Ref0_GND 40.2kΩ 1% to GND

L3	(DA 05091-001_v04.p.3_Table 2)
N13P-GL	10kΩ pull-up to 3.3V
N13M_GE1	NC
N13M-GS	NC
N13P-GS	NC

TABLE VIDEO MEMORY

	HYNIX 128Mx16 0110	SAMSUNG 128Mx16 0111	HYNIX 64Mx16 0010	Samsung 64Mx16 0011
900MHz	72.52G63.A0U 1-007155	72.42164.D0U 1-007156	72.51G63.H0U 1-007157	72.41164.Q0U 1-007356
ROM_SI PD R8627	34.8Kohm 64.34825.6DL	45.3Kohm 64.45325.6DL	15Kohm 64.15025.6DL	20Kohm 64.20025.6DL

The GB4-128 package is available in a 29 mm × 29mm footprint.
128-bit memory interfaces respectively.

Recommended NVVDD Voltage Regulator Phase Coount

GPU SKU	Phase Count Target
N13M-GE1	Single phase
N13M-GS	Two phase
N13P-GL	Two phase
N13P-GS	Two phase

29 x 29 PACKAGE
V: N13P-GS/GL (25~30w)
B: N13M-GS/GE (15~20w)

128Mx16:

hynix - H5TQ2G63BFR-11C
Samsung - K4W2G1646C-HC11

64Mx16:

Hynix - H5TQ1G63DFR-11C
Samsung - K4W1G1646G-BC11

TABLE NVIDIA		N12P-GE DEV ID: 0xDF5 0101	N12P-GV DEV ID: 0x0DF7(ES)	N12M-GE DEV ID: 0xA7A 1010
STRAP1	R8632	DY	DY	35Kohm 64.34825.6DL
	R8633	35Kohm 64.34825.6DL	35Kohm 64.34825.6DL	DY
STRAP2	R8634	DY	45Kohm 64.45325.6DL	15Kohm 64.15025.6DL
	R8635	30Kohm 64.30025.6DL	DY	DY



<Core Design>
Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C
Title: N13P_GPU (4/5): GPIO/STRAP
Size: A1 | Document Number: LA48 | Rev: SD
Date: Friday, January 06, 2012 | Sheet 65 of 103





NVVDD Decoupling Requirement
(DG-05587-001_v03_p.56_Table 7)

Capacitor Type		Footprint		Population	Location
4.7uF	X6S	0603	15	10	Under GPU
0.1uF	X7R	0402	8	4	Under GPU
47uF	X5R	0805	1	1	Near GPU
22uF	X5R	0805	1	1	Near GPU
4.7uF	X5R	0805	5	5	Near GPU

X7R (+/-15%、-55~125℃)
X6S (+/-22%、-55~105℃)
X5R (+/-15%、-55~85℃)

VDD33 Decoupling (DG-05587-001_v03_p.57_Table 8)

Capacitor Type		Footprint		Population	Location
0.1uF	X7R	0402	3	3	Under GPU
1uF	X5R	0402	2	2	Near GPU
4.7uF	X5R	0603	1	1	Near GPU

X7R (+/-15%、-55~125℃)
X5R (+/-15%、-55~85℃)

<Core Design>

緯創資通 Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C

Title: N13P_GPU (5/5): PWR/GND
Size: A3 | Document Number: LA48 | Rev: SD
Date: Friday, January 06, 2012 | Sheet 87 of 103

VIDEO FRAME BUFFER PORT A



FB CMD mapping
Mode D-N13x



FB CMD mapping
Mode D-N13x

```
128 X 16
72.52G63.A0U
72.42164.D0U  IC VRAM K4W2G1646C-HC1

64 X 16
72.51G63.H0U  IC VRAM H5TQ1G63DFR-11C FBGA 96BALLS
72.41646.Q0U  IC VRAM K4W1G1646G-BC11 FBGA 96BALLS
```

```
128Mx16:

hynix - H5TQ2G63BFR-11C
Samsung - K4W2G1646C-HC11

64Mx16:

Hynix - H5TQ1G63DFR-11C
Samsung - K4W1G1646G-BC11
```

Combined Memory FBVDD/Q Decoupling DDR3×16 with Clamshell Layout
(DG-05587-001_v03_p.87_Table 23)

Capacitor	Type	Footprint	Population	Location
0.1uF	X7R	0402	4	Close to VRAM
1uF	X7R	0603	8	Close to VRAM

X7R (+/-15%、-55~125℃)
*Per clamshell pair





<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: CHANNEL-A_VRAM1,2 (1/4)

Size	Document Number	Rev
A3	LA48	SD

Date: Friday, January 06, 2012 Sheet 88 of 103

VIDEO FRAME BUFFER PORT A





Combined Memory FBVDD/Q Decoupling DDR3×16 with Clamshell Layout
(DG-05587-001_v03_p.87_Table 23)

Capacitor Type		Footprint	Population	Location
0.1uF	X7R	0402	4	Close to VRAM
1uF	X7R	0603	8	Close to VRAM

X7R (+/-15%、-55~125℃)
*Per clamshell pair





<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: CHANNEL-A_VRAM3,4 (2/4)

Size	Document Number	Rev
A3	LA48	SD

Date: Friday, January 06, 2012 Sheet 89 of 103

VIDEO FRAME BUFFER PORT C





Combined Memory FBVDD/Q Decoupling DDR3×16 with Clamshell Layout
(DG-05587-001_v03_p.87_Table 23)

Capacitor Type		Footprint	Population	Location
0.1uF	X7R	0402	4	Close to VRAM
1uF	X7R	0603	8	Close to VRAM

X7R (+/-15%、-55~125℃)
*Per clamshell pair





<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title	CHANNEL-C_VRAM5,6 (3/4)	
Size A3	Document Number LA48	Rev SD
Date: Friday, January 06, 2012	Sheet 90 of 103	



VIDEO FRAME BUFFER PORT C

FB CMD mapping
Mode D-N13x



FB CMD mapping
Mode D-N13x

0.1uF(X7R)
K0402 ×4



1.0uF(X7R)
K0603 ×8



Close to VRAM(For VRAM7 & VRAM8)

Combined Memory FBVDD/Q Decoupling DDR3×16 with Clamshell Layout
(DG-05587-001_v03_p.87_Table 23)

Capacitor Type		Footprint	Population	Location
0.1uF	X7R	0402	4	Close to VRAM
1uF	X7R	0603	8	Close to VRAM

X7R (+/-15%、-55~125℃)
*Per clamshell pair



<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: CHANNEL-C_VRAM7,8 (4/4)

Size: A3 | Document Number: LA48 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 91 of 103

SSID = PWR.Plane.Regulator_GFX

	Main source	2nd source
PU9202	84.03606.037 FDMS3606S-GP-U	
PU9206	84.03606.037 FDMS3606S-GP-U	

BOM control

		N13P-GS 71.0N13P.00U	N13P-GL 71.0N13P.B0U	N13M-GS 71.0N13M.E0U	N13M-GE1 71.0N13M.C0U
NVVDD Boot Voltage		0.9V VID[6:0]=0110000	0.975V VID[6:0]=0101010	0.9V VID[6:0]=0110000	0.875V VID[6:0]0110010
NV_VID1	PR9215	DY	63.10334.1DL	DY	63.10334.1DL
	PR9230	63.10334.1DL	DY	63.10334.1DL	DY
NV_VID3	PR9217	DY	63.10334.1DL	DY	DY
	PR9232	63.10334.1DL	DY	63.10334.1DL	63.10334.1DL
NV_VID4	PR9218	63.10334.1DL	DY	63.10334.1DL	63.10334.1DL
	PR9233	DY	63.10334.1DL	DY	DY

Panasonic. 0.36uH 10*11.5*4
DCR=1.1mohm
Idc=17A, Isat=24A

Q1: Id=11A, Qg=10~14nC,
Rdson=7.5~9.8 mohm
Q2: Id=23A, Qg=27~38nC,
Rdson=1.7~2.1 mohm

<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: TPS51728_VGA_CORE
Size: Document Number: <Doc> Rev: SD
Date: Friday, January 06, 2012 Sheet 92 of 103

+3VS to 3.3V_DELAY Transfer



1D5V_VGA_S0

AO4468, SO-8
Id=11.6A, Qg=9~12nC
Rdson=17.4~22m ohm



1.05V to 1.05V_VGA_S0 Tran





<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: **DISCRETE VGA POWER**

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 93 of 103

BLANK

<Core Design>

緯創資通 Wistron Corporation
21F,88,Sec.1,Hsin Tai Wu Rd.,Hsichih,
Taipei Hsien 221, Taiwan, R.O.C

Title: <Title>		
Size: A4	Document Number: LA480	Rev: SD
Date: Friday, January 06, 2012	Sheet 94 of 103	

BLANK

<Core Design>

緯創資通	**Wistron Corporation** 21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.
Title	***Reserved***
Size: A4	Document Number: **LA480**
Rev: **SD**	
Date: Friday, January 06, 2012	Sheet 95 of 103

BLANK

<Core Design>

緯創資通 **Wistron Corporation**
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: ***TOUCH PANEL***

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 96 of 103

CPU Plate

H14 HOLET157B276R134-GP ZZ.SCREW.091
H15 HOLET157B276R134-GP ZZ.SCREW.091
H16 HOLET157B276R134-GP ZZ.SCREW.091
H17 HOLET157B276R134-GP ZZ.SCREW.091

VGA Std-Off

H1 STF237R128H42-1-GP 34.4GD01.001
H2 STF237R128H42-1-GP 34.4GD01.001
H21 STF237R128H42-1-GP 34.4GD01.001

MINI PCIE

H18 STF256R89H178-GP 34.4B417.001

DCBATOUT
EC9729 EC9727 EC9728 SCD1U25V2KX-GP
VCCSA
EC9730 SC1KF50V2KX-1GP
DY EC9731 EC9732 EC9733 SCD1U25V2KX-GP

XDP_DBRESET# 5,19
H_CPUPWRGD 5,22
PLT_RST# 5,18,27,31,36,65,66,71,80,82,83

14" Structure boss

H3 HOLE256R115-GP ZZ.00PAD.D11
H4 HOLE256R115-GP ZZ.00PAD.D11
H5 HOLE315X315R91-S1-GP ZZ.00PAD.581
H7 HOLE355X355R111-S1-GP ZZ.00PAD.571
H8 HOLE335R115-GP ZZ.00PAD.D01
H10 HOLE237R95-GP ZZ.00PAD.921
H11 HOLE237R95-GP ZZ.00PAD.921
H12 HOLE335R115-GP ZZ.00PAD.D01
H13 HOLE237R95-GP ZZ.00PAD.921
H19 HOLE315R95-GP ZZ.00PAD.911

DCBATOUT
EC9705 EC9706 EC9707 EC9708 EC9709 EC9710 EC9711 EC9712 EC9713 EC9714 SCD1U25V2KX-GP

3D3V_S0_CAMERA
EC9715 SCD1U25V2KX-GP

3D3V_AUX_S5
EC9716 SCD1U25V2KX-GP

3D3V_AUX_KBC
EC9717 SCD1U25V2KX-GP

3D3V_VGA_S0
EC9718 SCD1U25V2KX-GP

ODD_PWR_5V
EC9719 SCD1U25V2KX-GP

VCC_CORE
EC9720 EC9721 SCD1U25V2KX-GP

5V_S5
EC9722 EC9723 EC9724 SCD1U25V2KX-GP

3D3V_S0
R9704 100R2J-2-GP DY
3D3V_RUNPWR
Q9704 2N7002A-7-GP DY
PS_S3CNTRL

5V_S0
R9705 100R2J-2-GP DY
5V_RUNPWR
Q9705 2N7002A-7-GP DY
PS_S3CNTRL

5V_USB2_S3
EC9725 SCD1U25V2KX-GP

5V_USB1_S3
EC9726 SCD1U25V2KX-GP

1D05V_VTT
R9701 100R2J-2-GP DY
VTT_RUNPWR
Q9701 2N7002A-7-GP DY
36,37 PS_S3CNTRL
PS_S3CNTRL

VCC_CORE
R9706 100R2J-2-GP DY
CORE_RUNPWR
Q9706 2N7002A-7-GP DY
PS_S3CNTRL

VCC_GFXCORE
R9707 100R2J-2-GP DY
GFX_RUNPWR
Q9707 2N7002A-7-GP DY
PS_S3CNTRL

VCCSA
R9709 100R2J-2-GP DY
1D05V_RUNPWR
Q9709 2N7002A-7-GP DY
PS_S3CNTRL

1D8V_S0
R9702 100R2J-2-GP DY
1D8V_RUNPWR
Q9702 2N7002A-7-GP DY
PS_S3CNTRL

AD+
EC9702 EC9703 EC9704 SCD1U25V2KX-GP

For Discharge

3D3V_S5
R9710 100KR2J-1-GP DY
PM_SLP_S4
Q9710 2N7002A-7-GP DY
19,27,46 PM_SLP_S4#

1D5V_S3
R9711 100R2J-2-GP DY
1D5V_RUNPWR
Q9711 2N7002A-7-GP DY

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: UNUSED PARTS/EMI Capacitors
Size: A3 | Document Number: LA480 | Rev: SD
Date: Friday, January 06, 2012 | Sheet 97 of 103

(Blanking)

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: *Change History*

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 98 of 103

Intel-Power Sequence

(S5-to-S0-to-S5)



Intel PCH Pin Name	Main board PCH Pin Name
VccSUS (5V/3V)	3D3V_AUX_S5
PWRBTN#	PM_PWRBTN#
SLP_A#	SLP_A#
SLP_LAN#	SLP_LAN#
SLP_S5#	PM_SLP_S5#
SLP_S4#	PM_SLP_S4#
SLP_S3#	PM_SLP_S3#
VccASW/ VccSPI	VccASW/ VccSPI
Vcc_WLAN	+3V_MINI_WLAN
PWROK/APWROK	S0_PWR_GOOD
CL_ RST#	CL_ RST#
VCCPLL	1D8V_S0
VDDQ	1D5V_S0
VR_VDDQPWRGOOD	VDDPWRGOOD
VCCSA	VCCSA
IMVP7_VR_EN	D85V_PWRGD
VccCore	VCC_CORE
VccAXG	VCC_GFXCORE
IMVP7_PWRGD	IMVP_PWRGD
SYS_PWROK	SYS_PWROK
PWROK	S0_PWR_GOOD
DRAMPWROK	PM_DRAM_PWRGD
UNCOREPWRGOOD	H_CPUPWRGD
PLTRST#	PLT_RST#

(S3-to-S0-to-S3)



<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: Change History

Size	Document Number	Rev
A2	LA480	SD

Date: Friday, January 06, 2012 Sheet 99 of 103



<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: Power Block Diagram

Size	Document Number	Rev
A3	LA480	SD

Date: Friday, January 06, 2012 Sheet 100 of 103

PCH SMBus Block Diagram

KBC SMBus Block Diagram



<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: SMBUS Block Diagram

Size	Document Number	Rev
A2	LA480	SD

Date: Friday, January 06, 2012 Sheet 101 of 103

Thermal Block Diagram



Audio Block Diag



<Core Design>
緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: Thermal/Audio Block Diagram

Size: Custom | Document Number: LA480 | Rev: SD

Date: Friday, January 06, 2012 | Sheet 102 of 103

(Blanking)

<Core Design>

緯創資通 Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

Title: *Change History*

Size	Document Number	Rev
A4	LA480	SD

Date: Friday, January 06, 2012 Sheet 103 of 103