SSID = Charger

X01-0217 change PU4002, PU4003 to 84.04407.G37

EE need pull high and net name

0802 Rename H_PROCHOT#

PU4002 AO4407AL-GP
Id= -10A
Qg= -22nC
Rdson=14~13mohm

PU4003 AO4407AL-GP
Id= -10A
Qg= -22nC
Rdson=14~13mohm

A00-0412 dummy PR4037

A00-0412 stuff PQ4005

A00-0412 Change PR4029 to 54.9K

A00-0412 Change PR4013 to 49.9K

A00-0412 stuff PR4030& PR4032

A00-0412 Change PR4027 to 19.6K

2N7002KDW-GP
84.2N702.A3F
2nd = 84.DM601.03F

BQ24707ARGRR-GP

Charger Current=1.4~3.6A

delete net name 11/10

delete net name 11/15

11/10

11/18

X01-0217 change PU4001, PU4004 to 84.04496.037

Add net name 11/10

EE need check pull high

ROSA

11/15

Adapter Type	PR4023
65W	24K
90W	33.2K
130W	59K

11/29

BOM merge 12/15

PR4034 can dummy if you use external 10mW

X01-0127 DY PQ4007, PR4038, PR4039 for new version BQ24707

EC code only BQ24707

H_PROCHOT#	AD_IA_HW	AD_IA_HW2
65W	0	0
90W	1	0
130W	0	1

<Core Design>

Wistron Corporation
21F, 88, Sec.1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan, R.O.C.

Title: CHARGER BQ24707

Size: Custom | Document Number: Enrico Caruso 14 | Rev: A00

Date: Wednesday, April 13, 2011 | Sheet 40 of 105