

Assignment 3 : Calibration

Please edit the cell below to include your name and student ID #

name: Lydia Qiao

SID: 45837573

1. Parameterizing 3D Rotations

In order to optimize over the camera rotation during calibration, we need a way to parameterize the space of 3D rotations. There are many different ways to do this and each comes with different tradeoffs, but for our purposes we will adopt a simple approach of building a rotation by a sequence of rotations around the X, Y and Z axes (so called *Tait-Bryan angles*, see https://en.wikipedia.org/wiki/Euler_angles (https://en.wikipedia.org/wiki/Euler_angles) for more discussion)

1.1 Implement

Write a function **makerotation** which takes as input three angles **rx,ry,rz** and returns a rotation matrix corresponding to rotating by **rx** degrees around the x-axis, followed by a rotation of **ry** degrees around the y-axis, followed by a rotation of **rz** degrees around the z-axis.

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
import scipy.optimize
import matplotlib.patches as patches
from mpl_toolkits.mplot3d import Axes3D
import visutils
%matplotlib inline
```

```
In [2]: def makerotation(rx,ry,rz):
        """
        Generate a rotation matrix

        Parameters
        -----
        rx,ry,rz : floats
            Amount to rotate around x, y and z axes in degrees

        Returns
        -----
        R : 2D numpy.array (dtype=float)
            Rotation matrix of shape (3,3)
        """
        xangle=np.radians(rx)
        yangle=np.radians(ry)
        zangle=np.radians(rz)
        rz_matrix= np.array([[np.cos(zangle),- np.sin(zangle),0],[np.sin(
        ry_matrix= np.array([[np.cos(yangle),0, np.sin(yangle)],[0,1,0],[0
        rx_matrix= np.array([[1,0,0],[0,np.cos(xangle),- np.sin(xangle)],
        r_matrix= rx_matrix.dot(ry_matrix)
        r_matrix= r_matrix.dot(rz_matrix)
        return r_matrix
```

1.2 Test

Work out by hand what a 90 degree rotation should look like. Then execute the test examples below and verify/convince yourself that the output of your code matches.

Find a way to achieve the same rotation as **makerotation(90,90,0)** but without using rotation around the x-axis. That is, determine some angles so that **makerotation(0,?,?) == makerotation(90,90,0)**

```

In [3]: #
# test your function on some simple examples
#
np.set_printoptions(precision=4, suppress=True)

print(makerotation(90,0,0))

print(makerotation(0,90,0))

print(makerotation(0,0,90))

print(makerotation(90,90,0))

ry = 90
rz = 90
print(makerotation(0,ry,rz))

# figure out what ry,rz values are needed in order to pass this test
assert((makerotation(90,90,0)-makerotation(0,ry,rz)<1e-9).all())

[[ 1.  0.  0.]
 [ 0.  0. -1.]
 [ 0.  1.  0.]]
[[ 0.  0.  1.]
 [ 0.  1.  0.]
 [-1.  0.  0.]]
[[ 0. -1.  0.]
 [ 1.  0.  0.]
 [ 0.  0.  1.]]
[[ 0.  0.  1.]
 [ 1.  0. -0.]
 [-0.  1.  0.]]
[[ 0. -0.  1.]
 [ 1.  0.  0.]
 [-0.  1.  0.]]

```

2. Reprojection Error

We will now specify a function which computes the reprojection error. This is the function that we will later optimize when calibrating the camera extrinsic parameters. Take a look at the documentation for **scipy.optimize.leastsq**. The optimizer expects that our function should take a vector of parameters and return a vector of residuals which it will square and sum up to get the total error. For this reason, we will structure our code in the following way.

First, write a member function for the Camera class called **update_extrinsics** which takes a vector of 6 parameters (rx,ry,rz,tx,ty,tz). The function should keep the same intrinsic parameters (f,c) but update the extrinsic parameters (R,t) based on the entries in the parameter vector.

Second, implement a function named **residuals** which computes the difference between a provided set of 2D point coordinates and the projection of 3D point coordinates by specified camera. The residuals function takes as input the 3D points, the target 2D points, a camera with specified intrinsic parameters, and an extrinsic parameter vector. You should use **update_extrinsics** to update the extrinsic parameters, compute the projection of the 3D points with the updated camera and return a 1D vector containing the differences of all the x and y coordinates.

```
In [4]: class Camera:
        """
        A simple data structure describing camera parameters

        The parameters describing the camera
        cam.f : float    --- camera focal length (in units of pixels)
        cam.c : 2x1 vector --- offset of principle point
        cam.R : 3x3 matrix --- camera rotation
        cam.t : 3x1 vector --- camera translation

        """

        def __init__(self,f,c,R,t):
            self.f = f
            self.c = c
            self.R = R
            self.t = t

        def __str__(self):
            return f'Camera : \n f={self.f} \n c={self.c.T} \n R={self.R}

        def project(self,pts3):
            """
            Project the given 3D points in world coordinates into the spec
```

```

Parameters
-----
pts3 : 2D numpy.array (dtype=float)
        Coordinates of N points stored in a array of shape (3,N)

Returns
-----
pts2 : 2D numpy.array (dtype=float)
        Image coordinates of N points stored in an array of shape

"""
assert(pts3.shape[0]==3)
temp=pts3.copy()
#     print(self.t.reshape((3,1)))
temp=np.subtract(temp,self.t)

rr=np.linalg.inv(self.R)
r=np.dot(rr,temp)
r[0,:]=np.divide(r[0,:],r[2,:])
r[1,:]=np.divide(r[1,:],r[2,:])
r= r*self.f
pts2=r[0:2,:]
pts2=pts2+self.c
assert(pts2.shape[1]==pts3.shape[1])
assert(pts2.shape[0]==2)

return pts2

def update_extrinsics(self,params):
    """
    Given a vector of extrinsic parameters, update the camera
    to use the provided parameters.

    Parameters
    -----
    params : 1D numpy.array of shape (6,) (dtype=float)
            Camera parameters we are optimizing over stored in a vector
            params[:3] are the rotation angles, params[3:] are the tra

    """
    self.t=params[3:].reshape(3,1)
    self.R=makerotation(params[0],params[1],params[2])

```

In [5]: `def residuals(pts3,pts2,cam,params):`

```

    """
    Compute the difference between the projection of 3D points by the
    with the given parameters and the observed 2D locations

```

Parameters

```

pts3 : 2D numpy.array (dtype=float)
        Coordinates of N points stored in a array of shape (3,N)

pts2 : 2D numpy.array (dtype=float)
        Coordinates of N points stored in a array of shape (2,N)

params : 1D numpy.array (dtype=float)
        Camera parameters we are optimizing stored in a vector of shape (3,1)

```

Returns

```

residual : 1D numpy.array (dtype=float)
        Vector of residual 2D projection errors of size 2*N

```

```

#####
#     print("residuals",pts2.size,pts3.size)
z= np.zeros((1,pts2[0].size))
cam.update_extrinsics(params)
pts2_d=cam.project(pts3)
z=pts2-pts2_d
zz=np.reshape(z,pts2.size, order='F')

return zz
#     def fun_x(a,b):
#         return arg min(sum(((a-b)**2,axis=0))
#     for i in range(pts2.shape[1]):
#         temp= np.dstack((pts2[:,i],pts2_d[:,i]))
#         temp= temp.reshape(2,2)
#         print(temp)
#         print(cam.t)
#         y=pts2[:,i]-pts2_d[:,i]

#         x = arg min(sum(fun_x(y)**2,axis=0))
#         ztemp =scipy.optimize.leastsq(x, z)
#         z[0,i]=ztemp[0][0]
#         z[1,i]=ztemp[0][1]
#         z[i]= (pts2[0,i]-pts2_d[0,i])**2
#         z[i+1] = (pts2[1,i]-pts2_d[1,i])**2
#         i+=1
return z

```

```

In [6]: #
# Test the residual function to make sure it is doing the right thing.
#

```

```

# create two cameras with same intrinsic but slightly different extrin
camA = Camera(f=200,c=np.array([[50,50]]).T,t=np.array([[0,0,0]]).T, f
camB = Camera(f=200,c=np.array([[50,50]]).T,t=np.array([[0,0,0]]).T, f

paramsA = np.array([0,0,0,0.5,0.5,-2.5])
paramsB = np.array([0,0,5,0.5,0.5,-3])
camA.update_extrinsics(paramsA)
camB.update_extrinsics(paramsB)

print(camA)
print(camB)

# create a test object (corners of a 3D cube)
pts3 = np.array([[0,0,0],[0,0,1],[0,1,1],[0,1,0],[1,1,0],[1,0,0],[1,0,
# print(pts3)

# visualize the two projections
pts2A = camA.project(pts3)
pts2B = camB.project(pts3)

plt.plot(pts2A[0,:],pts2A[1,:],'r')
plt.plot(pts2B[0,:],pts2B[1,:],'b')
plt.show()

# double check that the residuals are the same as the difference in th
print("\n residuals of camB relative to camA")
print(residuals(pts3,pts2A,camB,paramsB))
print(pts2A-pts2B)

print("\n residuals of camA relative to camB")
print(residuals(pts3,pts2B,camA,paramsA))
print(pts2B-pts2A)


```

```

Camera :
  f=200
  c=[[50 50]]
  R=[[1.  0.  0.]
     [0.  1.  0.]
     [0.  0.  1.]]
  t = [[ 0.5  0.5 -2.5]]
Camera :
  f=200
  c=[[50 50]]
  R=[[ 0.9962 -0.0872  0.    ]
     [ 0.0872  0.9962  0.    ]
     [ 0.      0.      1.    ]]
  t = [[ 0.5  0.5 -3.  ]]

```





```

residuals of camB relative to camA
[-3.8883 -9.6987 -1.4877 -5.8455 -5.8455  1.4877 -9.6987  3.8883  3.8
883
 9.6987  9.6987 -3.8883  5.8455 -1.4877  1.4877  5.8455]
[[-3.8883 -1.4877 -5.8455 -9.6987  3.8883  9.6987  5.8455  1.4877]
 [-9.6987 -5.8455  1.4877  3.8883  9.6987 -3.8883 -1.4877  5.8455]]

residuals of camA relative to camB
[ 3.8883  9.6987  1.4877  5.8455  5.8455 -1.4877  9.6987 -3.8883 -3.8
883
-9.6987 -9.6987  3.8883 -5.8455  1.4877 -1.4877 -5.8455]
[[ 3.8883  1.4877  5.8455  9.6987 -3.8883 -9.6987 -5.8455 -1.4877]
 [ 9.6987  5.8455 -1.4877 -3.8883 -9.6987  3.8883  1.4877 -5.8455]]

```

3. Camera Pose Estimation

We are now ready to estimate camera pose using `optimize`. Implement a function **`calibratePose`** which takes as input the 3D coordinates of a calibration object, the observed 2D coordinates in the image, and an initial guess of the camera. Your function should use **`scipy.optimize.leastsq`** to optimize the extrinsic parameters in order to minimize the reprojection error. Since the **`residuals`** function takes additional arguments and **`leastsq`** expects a function which only takes the parameter vector as input, you should use Python's **`lambda`** function to wrap **`residuals`**, substituting in the parameters that are fixed during the optimization. Once you have determined the optimum parameters, update the extrinsic parameters to the optimum and return the resulting camera.

3.1 Implementation


```

In [7]: def calibratePose(pts3,pts2,cam,params_init):
        """
        Calibrate the provided camera by updating R,t so that pts3 project
        as close as possible to pts2

        Parameters
        -----
        pts3 : 2D numpy.array (dtype=float)
               Coordinates of N points stored in a array of shape (3,N)

        pts2 : 2D numpy.array (dtype=float)
               Coordinates of N points stored in a array of shape (2,N)

        cam : Camera
               Initial estimate of camera

        params_init : 1D numpy.array (dtype=float)
                      Initial estimate of camera extrinsic parameters ()
                      params[0:2] are the rotation angles, params[2:5] are the trans

        Returns
        -----
        cam : Camera
               Refined estimate of camera with updated R,t parameters

        """
        x = lambda params_init,pts3=pts3,pts2=pts2,cam=cam: residuals(pts3,
        input_int = [pts3,pts2,cam,params_init]
        ex= scipy.optimize.leastsq(x,params_init)
        cam.update_extrinsics(ex[0])
        return cam

```

3.2 Synthetic Test Example and Failure Cases

Use the code below to check that your calibrate function works. Add some code to also visualize the point locations in 3D and the location and orientation of the camera (i.e., using the 3D plotting functions from Assignment 2)

Once you are confident that your calibration function is behaving correctly, you should experiment with changing the initial parameters. Find a set of initial parameters which yields a **wrong** solution (i.e. where the Final Camera is not similar to the True Camera). In the text box below indicate what bad initialization you used and the resulting set of camera parameters after the optimization. Give a brief explanation of where this bad camera is located and what direction it is oriented in.

```
In [8]: # 3D calibration object
pts3 = np.array([[0,0,0],[0,0,1],[0,1,1],[0,1,0],[1,1,0],[1,0,0],[1,0,1],[0,1,0]])

# true camera
cam_true = Camera(f=50,c=np.array([[50,50]]).T,t=np.array([[ -1,-1,-2]]))

print("\n True Camera")
print(cam_true)

# image of calibration object with some simulated noise in the 2D location
pts2 = cam_true.project(pts3)
noiselevel = 0.5
pts2 = pts2 + noiselevel*np.random.randn(pts2.shape[0],pts2.shape[1])

# initial guess of camera params
cam = Camera(f=50,c=np.array([[50,50]]).T,t=np.array([[0,0,0]]).T, R=np.eye(3))
params_init = np.array([0,0,0,0,0,-2])
cam.update_extrinsics(params_init)

print("\n Initial Camera")
print(cam)
pts2init = cam.project(pts3)

# now run calibration
cam = calibratePose(pts3,pts2,cam,params_init)

print("\n Final Camera")
print(cam)
pts2final = cam.project(pts3)

#
# Plot the true, initial and final reprojections
```

```
# The final reprojection should be on top of the true image
#
plt.plot(pts2[0,:],pts2[1,:],'bo')
plt.plot(pts2init[0,:],pts2init[1,:],'r')
plt.plot(pts2final[0,:],pts2final[1,:],'k')
plt.show()

#
# Add some additional visualiztion here to show the points in 3D and t
# of cam_true and cam. You can either use a 3D plot or show multiple
# and side views)
#
```

True Camera

Camera :

```
f=50
c=[[50 50]]
R=[[ 1.      0.      0.    ]
 [ 0.      0.9848 -0.1736]
 [ 0.      0.1736  0.9848]]
t = [[-1 -1 -2]]
```

Initial Camera


Camera :


```
f=50
c=[[50 50]]
R=[[1. 0. 0.]
 [0. 1. 0.]
 [0. 0. 1.]]
t = [[ 0  0 -2]]
```

Final Camera

Camera :

```
f=50
c=[[50 50]]
R=[[ 0.9999  0.0158  0.0017]
 [-0.0153  0.9841 -0.177 ]
 [-0.0044  0.1769  0.9842]]
t = [[-1.0441 -0.9642 -1.9988]]
```





```
In [9]: #
# Now repeat the calibration but with a setting for params_init that
# in the optimization finding a poor solution (a bad local minima)
#np.array([0,10,0,1,1,2])
params_init = np.array([0,10,0,1,1,2])
cam = Camera(f=50,c=np.array([[50,50]]).T,t=np.array([[0,0,0]]).T, R=np
cam.update_extrinsics(params_init)

print("\n Initial Camera")
print(cam)
pts2init = cam.project(pts3)

# now run calibration
cam = calibratePose(pts3,pts2,cam,params_init)


print("\n Final Camera")
print(cam)
pts2final = cam.project(pts3)

#
# Plot the true, initial and final reprojections
# The final reprojection should be on top of the true image
#
plt.plot(pts2[0,:],pts2[1:], 'bo')
plt.plot(pts2init[0,:],pts2init[1:], 'r')
plt.plot(pts2final[0,:],pts2final[1:], 'k')
plt.show()
#
# Visualize the resulting bad solution.
#
print("The camera located at [1 1 2] and rotate 10 degrees around the
```

```
Initial Camera
Camera :
f=50
c=[[50 50]]
R=[[ 0.9848  0.      0.1736]
 [ 0.      1.      0.      ]
 [-0.1736  0.      0.9848]]
t = [[1 1 2]]
```

```
Final Camera
Camera :
```

```
f=50  
c=[[50 50]]  
R=[[-0.5454  0.577  0.608 ]  
 [ 0.4535 -0.4069  0.793 ]  
 [ 0.7049  0.7082 -0.0397]]  
t = [[2.1578 2.1879 2.8821]]
```



The camera located at $[1,1,2]$ and rotate 10 degrees around the y axis

describe the failure mode here... how is the camera located and oriented for the bad local minima?

4. Calibration from real images

There is a provided set of calibration images (images of a planar checkerboard) along with stereo pair depicting an object. In order to calibrate the intrinsic camera parameters we will use the OpenCV library which includes functionality for automatically detecting corners of the checkerboard and estimating intrinsic parameters. To install OpenCV python libraries in your Anaconda environment. You can do this from the terminal via the command **conda install opencv** or via the Anaconda Navigator gui.

I have provide a standalone script **calibrate.py** which uses OpenCV to carry out calibration of the camera intrinsic parameters for a series of checkerboard images. Read through the provided script to understand the code and modify file paths as necessary in order to compute the intrinsic camera parameters from the set of provided calibration images.

4.1 Implementation

Fill in the code snippet below to carry out the following steps.

0. Run the **calibrate.py** script to estimate the intrinsic camera parameters.
1. Load in the intrinsic parameter calibration data saved by the script in *calibration.pickle*. Since our camera model assumes that the focal length is the same in the x and y axes, you can set your f to be the average of the two estimated by the script.
2. Load in the test images *Left.jpg* and *Right.jpg* and use the **cv2.findChessboardCorners** function in order to automatically get the 2D coordinates of the corners in the image.
3. Specify the true 3D coordinates of the 6x8 grid of checkerboard corners. The squares are 2.8cm x 2.8cm.
4. Use your **calibratePose** function to estimate the R, t for each camera. You will likely need to experiment with selecting the initial parameters in order to get a good solution (e.g., translate so the cameras have positive z coordinates and rotate so they are looking down on the checkerboard).
5. Finally, as a consistency check, once you have the calibrated pose for each camera, you can use your triangulate function to estimate the 3D coordinates of the checkerboard corners based on the 2D points in the left and right camera. The re-triangulated points should be close to the specified true 3D coordinates.

```
In [10]: def triangulate(pts2L, camL, pts2R, camR):
         """
         Triangulate the set of points seen at location pts2L / pts2R in the
         corresponding pair of cameras. Return the 3D coordinates relative
         to the global coordinate system
```

Parameters

```

-----
pts2L : 2D numpy.array (dtype=float)
    Coordinates of N points stored in a array of shape (2,N) seen

pts2R : 2D numpy.array (dtype=float)
    Coordinates of N points stored in a array of shape (2,N) seen

camL : Camera
    The first "left" camera view

camR : Camera
    The second "right" camera view

```

Returns

```

-----
pts3 : 2D numpy.array (dtype=float)
    (3,N) array containing 3D coordinates of the points in global

```

```

.....

```

```

#
# Your code goes here. I recommend adding assert statements to check
# sizes of the inputs and outputs to make sure they are correct
#

```

```

#qL, and qR

```

```

a= pts2L.copy()
a= a-camL.c
a= np.divide(a,camL.f)

```

```

b= pts2R.copy()
b= b-camR.c
b= np.divide(b,camR.f)

```

```

one=np.ones((1,pts2L.shape[1]))
qL= np.concatenate((a,one))
qR= np.concatenate((b,one))

```

```

#Ax=t

```

```

A0=np.dot(camL.R,qL)
A1=-np.dot(camR.R,qR)
t=camR.t-camL.t

```

```

z= np.zeros((2,pts2L[0].size))

```

```

# print(A0,A1)
for i in range(A0.shape[1]):
    temp= np.dstack((A0[:,i],A1[:,i]))
    temp= temp.reshape(3,2)
# print(temp)

```

```

#         print(temp)
        ztemp = np.linalg.lstsq(temp,t)
        z[0,i]=ztemp[0][0]
        z[1,i]=ztemp[0][1]
#         print(ztemp[0])

        pL= z[0,:]*qL
        pR=z[1,:]*qR

        ptsL =np.dot(camL.R,pL)+ camL.t
        ptsR=np.dot(camR.R,pR)+ camR.t
        pts3=(ptsL+ptsR)/2
#         print(pts3[0:3,0])
        return pts3

```

```

In [11]: import cv2
import pickle

# import calibrate.py
# calibrate
# load in the intrinsic camera parameters from 'calibration.pickle'
intrinsic_param = pickle.load(open('/Users/ooo/Documents/CS117/Assignment3/calibration.pickle','rb'))
# print(intrinsic_param)
fc= (intrinsic_param['fx']+intrinsic_param['fy'])/2

# create Camera objects representing the left and right cameras
# use the known intrinsic parameters you loaded in.
camL = Camera(f=fc,c=np.array([[intrinsic_param['cx'],intrinsic_param['cy'],0]]).T, R=makerotation(0,0,0))
camR = Camera(f=fc,c=np.array([[intrinsic_param['cx'],intrinsic_param['cy'],0]]).T, R=makerotation(0,0,0))
# load in the left and right images and find the coordinates of
# the chessboard corners using OpenCV
imgL = plt.imread('calib1/Left.jpg')
ret, cornersL = cv2.findChessboardCorners(imgL, (8,6), None)
pts2L = cornersL.squeeze().T

imgR = plt.imread('calib1/Right.jpg')
ret, cornersR = cv2.findChessboardCorners(imgR, (8,6), None)
pts2R = cornersR.squeeze().T

# generate the known 3D point coordinates of points on the checkerboard
pts3 = np.zeros((3,6*8))
yy,xx = np.meshgrid(np.arange(8),np.arange(6))
pts3[0,:] = 2.8*xx.reshape(1,-1)
pts3[1,:] = 2.8*yy.reshape(1,-1)

# Now use your calibratePose function to get the extrinsic parameters
# for the two images. You may need to experiment with the initializat

```



```

# for the two images. You may need to experiment with the initialized
# in order to get a good result

params_init = np.array([0,0,0,0,0,-2])

camL = calibratePose(pts3,pts2L,camL,params_init)
camR = calibratePose(pts3,pts2R,camR,params_init)

print(camL)
print(camR)

# As a final test, triangulate the corners of the checkerboard to get
pts3r = triangulate(pts2L,camL,pts2R,camR)

# Display the reprojected points overlayed on the images to make
# sure they line up
plt.rcParams['figure.figsize']=[15,15]
pts2Lp = camL.project(pts3)
plt.imshow(imgL)
plt.plot(pts2Lp[0,:],pts2Lp[1,:],'bo')
plt.plot(pts2L[0,:],pts2L[1,:],'rx')
plt.show()

pts2Rp = camR.project(pts3)
plt.imshow(imgR)
plt.plot(pts2Rp[0,:],pts2Rp[1,:],'bo')
plt.plot(pts2R[0,:],pts2R[1,:],'rx')
plt.show()

```

```

Camera :
f=1561.0139694324007
c=[[1021.1465  755.8365]]
R=[[ 0.7928  0.5479 -0.2671]
 [ 0.6058 -0.66    0.4443]
 [ 0.0671 -0.514  -0.8552]]
t = [[20.2533 -0.3845 37.7861]]

```


```


Camera :
f=1561.0139694324007
c=[[1021.1465  755.8365]]
R=[[ 0.9506  0.271  -0.1511]
 [ 0.3029 -0.7042  0.6421]
 [ 0.0676 -0.6562 -0.7516]]
t = [[ 17.4715 -11.9475 24.0513]]

```

/Users/ooo/opt/anaconda3/lib/python3.7/site-packages/ipykernel_launcher.py:58: FutureWarning: `rcond` parameter will change to the default of machine precision times ``max(M, N)`` where M and N are the input matrix dimensions.

To use the future default and silence this warning we advise to pass `rcond=None`, to keep using the old, explicitly pass `rcond=-1`.





The code below provides a visualization of the estimate camera positions relative to the checkerboard.

```
In [12]: # generate coordinates of a line segment running from the center
# of the camera to 3 units in front of the camera

lookL = np.hstack((camL.t, camL.t + camL.R @ np.array([[0, 0, 2]]).T))
lookR = np.hstack((camR.t, camR.t + camR.R @ np.array([[0, 0, 2]]).T))
```

```

# visualize the left and right image overlaid
fig = plt.figure()
ax = fig.add_subplot(2,2,1,projection='3d')
ax.plot(pts3[0,:],pts3[1,:],pts3[2,:],'.')
ax.plot(pts3r[0,:],pts3r[1,:],pts3r[2,:], 'rx')
ax.plot(camR.t[0],camR.t[1],camR.t[2], 'ro')
ax.plot(camL.t[0],camL.t[1],camL.t[2], 'bo')
ax.plot(lookL[0,:],lookL[1,:],lookL[2,:], 'b')
ax.plot(lookR[0,:],lookR[1,:],lookR[2,:], 'r')
visutils.set_axes_equal_3d(ax)
visutils.label_axes(ax)
plt.title('scene 3D view')


ax = fig.add_subplot(2,2,2)
ax.plot(pts3[0,:],pts3[2,:],'.')
ax.plot(pts3r[0,:],pts3r[2,:], 'rx')
ax.plot(camR.t[0],camR.t[2], 'ro')
ax.plot(camL.t[0],camL.t[2], 'bo')
ax.plot(lookL[0,:],lookL[2,:], 'b')
ax.plot(lookR[0,:],lookR[2,:], 'r')
plt.title('XZ-view')
plt.grid()
plt.xlabel('x')
plt.ylabel('z')

ax = fig.add_subplot(2,2,3)
ax.plot(pts3[1,:],pts3[2,:],'.')
ax.plot(pts3r[1,:],pts3r[2,:], 'rx')
ax.plot(camR.t[1],camR.t[2], 'ro')
ax.plot(camL.t[1],camL.t[2], 'bo')
ax.plot(lookL[1,:],lookL[2,:], 'b')
ax.plot(lookR[1,:],lookR[2,:], 'r')
plt.title('YZ-view')
plt.grid()
plt.xlabel('y')
plt.ylabel('z')

ax = fig.add_subplot(2,2,4)
ax.plot(pts3[0,:],pts3[1,:],'.')
ax.plot(pts3r[0,:],pts3r[1,:], 'rx')
ax.plot(camR.t[0],camR.t[1], 'ro')
ax.plot(camL.t[0],camL.t[1], 'bo')
ax.plot(lookL[0,:],lookL[1,:], 'b')
ax.plot(lookR[0,:],lookR[1,:], 'r')
plt.title('XY-view')
plt.grid()
plt.xlabel('x')
plt.ylabel('y')

```


Out[12]: Text(0, 0.5, 'y')



4.2 Recovered Pose

Using the provided calibration images, what are the recovered parameters for the left and right cameras? How far apart are the camera centers in centimeters (i.e. what is the baseline) ?

```
In [13]: print("Transpose of two camera: ",camL.t,camR.t)
print("Rotation of two camera: ",camL.R,camR.R)
x=(camL.t-camR.t)**2
print("The distance between two camera centers in centimeters is: ",np

# dis=np.linalg.lstsq(camL.t[:2]-camR.t[:2])
# print(dis)
```

```
Transpose of two camera: [[20.2533]
 [-0.3845]
 [37.7861]] [[ 17.4715]
 [-11.9475]
 [ 24.0513]]
Rotation of two camera: [[ 0.7928  0.5479 -0.2671]
 [ 0.6058 -0.66    0.4443]
 [ 0.0671 -0.514  -0.8552]] [[ 0.9506  0.271  -0.1511]
 [ 0.3029 -0.7042  0.6421]
 [ 0.0676 -0.6562 -0.7516]]
The distance between two camera centers in centimeters is: 18.168235
34855803
```

Type *Markdown* and LaTeX: α^2

4.3 Reconstruction Accuracy

Using the estimated camL and camR and the 2D point locations, triangulate to get 3D locations. What is the average error (in cm) for your recovered 3D locations of the grid corner points relative to their true coordinates? Where might this error be coming from?

```
In [14]: x=pts3-pts3r
dis=np.linalg.norm(x, axis=0)
diss= sum(dis)/pts3[0].size
print("The average error for recovered 3D locations of the grid corner
,diss)
print("This error may come from finding the local minimum or Triangulation")
```

```
The average error for recovered 3D locations of the grid corner point
s is: 0.2375567703633784
This error may come from finding the local minimum or Triangulation.
```

Type *Markdown* and LaTeX: α^2

4.4 Focal Length

The checkerboard photos were taken with an iPhone Xs. Teardowns of this device reveal that the sensor is 5.6mm wide. Based on this and your recovered value for f , what was the focal length in millimeters? Explain how you computed this. Is the result you get a reasonable match to the published focal length of 4.25mm?

In [15]:

```
print("The rate between the image and actual camera is: ",2016/5.6)
print("The focal length in millimeters is: ",camR.f/360)
print("The result is a reasonable match to the published focal length
```

```
The rate between the image and actual camera is: 360.0
The focal length in millimeters is: 4.336149915090002
The result is a reasonable match to the published focal length of 4.2
5mm since the different is 0.08 mm
```

Type *Markdown* and LaTeX: α^2