

Ancillary qubits

Quantum Computing Minicourse ICTP-SAIFR

Stefano Carrazza[‡] and Matteo Robbiati[†]

8 April 2024


[‡] Associate Professor & Researcher, University of Milan and INFN Milan, Italy.

[†] PhD candidate, University of Milan, Italy and CERN, Switzerland.



Ancillary qubits

Ancilla qubits are extra qubits, which help a qubit system in some computations. For example:



The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

1. Take into account two qubits: a system qubit x and an ancilla y .

The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

1. Take into account two qubits: a system qubit x and an ancilla y .
2. Suppose we prepare x into a superposed state and y into the excited state:

$$|x\rangle = H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}, \quad |y\rangle = |1\rangle.$$

The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

1. Take into account two qubits: a system qubit x and an ancilla y .
2. Suppose we prepare x into a superposed state and y into the excited state:

$$|x\rangle = H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}, \quad |y\rangle = |1\rangle.$$

3. Let's consider now a gate G for which $|1\rangle$ is eigenvector: $G|1\rangle = \lambda_G|1\rangle$.
4. What happens if we now apply a controlled- G gate on y using x as control?

The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

1. Take into account two qubits: a system qubit x and an ancilla y .
2. Suppose we prepare x into a superposed state and y into the excited state:

$$|x\rangle = H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}, \quad |y\rangle = |1\rangle.$$

3. Let's consider now a gate G for which $|1\rangle$ is eigenvector: $G|1\rangle = \lambda_G|1\rangle$.
4. What happens if we now apply a controlled- G gate on y using x as control?
5. we could expect something happen on the target qubit! Not really:

The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

1. Take into account two qubits: a system qubit x and an ancilla y .
2. Suppose we prepare x into a superposed state and y into the excited state:

$$|x\rangle = H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}, \quad |y\rangle = |1\rangle.$$

3. Let's consider now a gate G for which $|1\rangle$ is eigenvector: $G|1\rangle = \lambda_G|1\rangle$.
4. What happens if we now apply a controlled- G gate on y using x as control?
5. we could expect something happen on the target qubit! Not really:

$$CG\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CG\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) =$$

The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

1. Take into account two qubits: a system qubit x and an ancilla y .
2. Suppose we prepare x into a superposed state and y into the excited state:

$$|x\rangle = H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}, \quad |y\rangle = |1\rangle.$$

3. Let's consider now a gate G for which $|1\rangle$ is eigenvector: $G|1\rangle = \lambda_G|1\rangle$.
4. What happens if we now apply a controlled- G gate on y using x as control?
5. we could expect something happen on the target qubit! Not really:

$$CG\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CG\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) = \frac{|01\rangle + G|11\rangle}{\sqrt{2}} =$$

The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

1. Take into account two qubits: a system qubit x and an ancilla y .
2. Suppose we prepare x into a superposed state and y into the excited state:

$$|x\rangle = H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}, \quad |y\rangle = |1\rangle.$$

3. Let's consider now a gate G for which $|1\rangle$ is eigenvector: $G|1\rangle = \lambda_G|1\rangle$.
4. What happens if we now apply a controlled- G gate on y using x as control?
5. we could expect something happen on the target qubit! Not really:

$$CG\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CG\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) = \frac{|01\rangle + G|11\rangle}{\sqrt{2}} = \frac{|01\rangle + \lambda_G|11\rangle}{\sqrt{2}} =$$

The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

1. Take into account two qubits: a system qubit x and an ancilla y .
2. Suppose we prepare x into a superposed state and y into the excited state:

$$|x\rangle = H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}, \quad |y\rangle = |1\rangle.$$

3. Let's consider now a gate G for which $|1\rangle$ is eigenvector: $G|1\rangle = \lambda_G|1\rangle$.
4. What happens if we now apply a controlled- G gate on y using x as control?
5. we could expect something happen on the target qubit! Not really:

$$CG\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CG\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) = \frac{|01\rangle + G|11\rangle}{\sqrt{2}} = \frac{|01\rangle + \lambda_G|11\rangle}{\sqrt{2}} = \frac{|0\rangle + \lambda_G|1\rangle}{\sqrt{2}} \otimes |1\rangle.$$

The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

1. Take into account two qubits: a system qubit x and an ancilla y .
2. Suppose we prepare x into a superposed state and y into the excited state:

$$|x\rangle = H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}, \quad |y\rangle = |1\rangle.$$

3. Let's consider now a gate G for which $|1\rangle$ is eigenvector: $G|1\rangle = \lambda_G|1\rangle$.
4. What happens if we now apply a controlled- G gate on y using x as control?
5. we could expect something happen on the target qubit! Not really:

$$CG\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CG\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) = \frac{|01\rangle + G|11\rangle}{\sqrt{2}} = \frac{|01\rangle + \lambda_G|11\rangle}{\sqrt{2}} = \frac{|0\rangle + \lambda_G|1\rangle}{\sqrt{2}} \otimes |1\rangle.$$

6. adding an extra H to the control qubit, we will detect the state manipulation!

The phase kickback

One clever trick we can implement using ancillas is the **phase kickback**.

1. Take into account two qubits: a system qubit x and an ancilla y .
2. Suppose we prepare x into a superposed state and y into the excited state:

$$|x\rangle = H|0\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}, \quad |y\rangle = |1\rangle.$$

3. Let's consider now a gate G for which $|1\rangle$ is eigenvector: $G|1\rangle = \lambda_G|1\rangle$.
4. What happens if we now apply a controlled- G gate on y using x as control?
5. we could expect something happen on the target qubit! Not really:

$$CG\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CG\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) = \frac{|01\rangle + G|11\rangle}{\sqrt{2}} = \frac{|01\rangle + \lambda_G|11\rangle}{\sqrt{2}} = \frac{|0\rangle + \lambda_G|1\rangle}{\sqrt{2}} \otimes |1\rangle.$$

6. adding an extra H to the control qubit, we will detect the state manipulation!

Important

This happens if the ancilla is prepared into a state which is eigenvector of the controlled operation.

Oracles

It can be useful to define the phase kickback using the concept of quantum **oracle**.

1. let's consider a system of qubits of state $|x\rangle$ and a set of extra qubits of state $|y\rangle$;

Oracles

It can be useful to define the phase kickback using the concept of quantum **oracle**.

1. let's consider a system of qubits of state $|x\rangle$ and a set of extra qubits of state $|y\rangle$;
2. in reversible computation x is called **input register** and y **output register**. In this course x will always be composed of our system of qubits and y will be ancillary qubits;

Oracles


It can be useful to define the phase kickback using the concept of quantum **oracle**.

1. let's consider a system of qubits of state $|x\rangle$ and a set of extra qubits of state $|y\rangle$;
2. in reversible computation x is called **input register** and y **output register**. In this course x will always be composed of our system of qubits and y will be ancillary qubits;
3. let's consider also a policy f , defined as a function $f : \{0, 1\}^N \rightarrow \{0, 1\}$.

Oracles

It can be useful to define the phase kickback using the concept of quantum **oracle**.

1. let's consider a system of qubits of state $|x\rangle$ and a set of extra qubits of state $|y\rangle$;
2. in reversible computation x is called **input register** and y **output register**. In this course x will always be composed of our system of qubits and y will be ancillary qubits;
3. let's consider also a policy f , defined as a function $f : \{0, 1\}^N \rightarrow \{0, 1\}$.
4. this function is typically embedded into an oracle U_f , a **black box** operator whose action on the system is:




where the symbol \oplus represents the “addition modulo 2” operation, equivalent to the logical operation XOR:

$$1 \oplus 1 = 0, \quad 0 \oplus 0 = 0, \quad 0 \oplus 1 = 1, \quad 0 \oplus 1 = 1.$$

Oracles

It can be useful to define the phase kickback using the concept of quantum **oracle**.

1. let's consider a system of qubits of state $|x\rangle$ and a set of extra qubits of state $|y\rangle$;
2. in reversible computation x is called **input register** and y **output register**. In this course x will always be composed of our system of qubits and y will be ancillary qubits;
3. let's consider also a policy f , defined as a function $f : \{0, 1\}^N \rightarrow \{0, 1\}$.
4. this function is typically embedded into an oracle U_f , a **black box** operator whose action on the system is:



where the symbol \oplus represents the “addition modulo 2” operation, equivalent to the logical operation XOR:

$$1 \oplus 1 = 0, \quad 0 \oplus 0 = 0, \quad 0 \oplus 1 = 1, \quad 0 \oplus 1 = 1.$$

In other terms, the action of this oracle can be expressed as $U_f |x\rangle |y\rangle = |x\rangle |y \oplus f(x)\rangle$.

A remarkable case: the phase flip

If we set G to be a Z gate, then the action of the phase kickback will be a complete phase flip.

$$CZ\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CZ\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) =$$

A remarkable case: the phase flip

If we set G to be a Z gate, then the action of the phase kickback will be a complete phase flip.

$$CZ\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CZ\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) = \frac{|01\rangle + Z|11\rangle}{\sqrt{2}} =$$

A remarkable case: the phase flip

If we set G to be a Z gate, then the action of the phase kickback will be a complete phase flip.

$$CZ\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CZ\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) = \frac{|01\rangle + Z|11\rangle}{\sqrt{2}} = \frac{|01\rangle - |11\rangle}{\sqrt{2}} =$$

A remarkable case: the phase flip

If we set G to be a Z gate, then the action of the phase kickback will be a complete phase flip.

$$CZ\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CZ\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) = \frac{|01\rangle + Z|11\rangle}{\sqrt{2}} = \frac{|01\rangle - |11\rangle}{\sqrt{2}} = \frac{|0\rangle - |1\rangle}{\sqrt{2}} \otimes |1\rangle.$$

This will be incredibly useful when we will implement some more complex algorithm.

A remarkable case: the phase flip

If we set G to be a Z gate, then the action of the phase kickback will be a complete phase flip.

$$CZ\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CZ\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) = \frac{|01\rangle + Z|11\rangle}{\sqrt{2}} = \frac{|01\rangle - |11\rangle}{\sqrt{2}} = \frac{|0\rangle - |1\rangle}{\sqrt{2}} \otimes |1\rangle.$$

This will be incredibly useful when we will implement some more complex algorithm.

We can recall the oracle notation introduced in the previous slide defining $f(x) = x$ and writing an oracle action which reproduces the phase kickbak:

$$U_f |x\rangle |1\rangle = (-1)^{f(x)} |x\rangle |1\rangle.$$

A remarkable case: the phase flip

If we set G to be a Z gate, then the action of the phase kickback will be a complete phase flip.

$$CZ\left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \otimes |1\rangle\right) = CZ\left(\frac{|01\rangle + |11\rangle}{\sqrt{2}}\right) = \frac{|01\rangle + Z|11\rangle}{\sqrt{2}} = \frac{|01\rangle - |11\rangle}{\sqrt{2}} = \frac{|0\rangle - |1\rangle}{\sqrt{2}} \otimes |1\rangle.$$

This will be incredibly useful when we will implement some more complex algorithm.

We can recall the oracle notation introduced in the previous slide defining $f(x) = x$ and writing an oracle action which reproduces the phase kickbak:

$$U_f |x\rangle |1\rangle = (-1)^{f(x)} |x\rangle |1\rangle.$$

The previous formula can be extended to the case of using multi-controlled operations once the policy is rewritten so that:

$$f(x) = \begin{cases} 1 & \text{if } x = |11\dots1\rangle \\ 0 & \text{otherwise.} \end{cases}$$

Is the phase kickback useful?

Some of the most powerful and famous quantum computing algorithms make use of the phase kickback



Figure 1: Deutsch-Josza




Figure 2: Grover




Figure 3: Shor




Figure 4: HHL

All of them are proved to outperform any classical algorithm, leading to a theoretical **quantum advantage**!

Let's code!

