

Introduction to Quantum Computing

Quantum Computing Minicourse

Stefano Carrazza and Matteo Robbiati


8 April 2024



Compute quantum mechanics


Compute quantum mechanics

- ✖ Representing N particles is difficult;



Compute quantum mechanics

- ✿ Representing N particles is difficult;
- ✿ considering N spins (\uparrow, \downarrow), we deal with a 2^N dimensional Hilbert space!



What can we do?

What can we do?

1. we can try to use classical methods to represent the system;

What can we do?

1. we can try to use classical methods to represent the system;
2. we can build a quantum computer.


What can we do?

1. we can try to use classical methods to represent the system;
2. we can build a quantum computer.



What can we do?

1. we can try to use classical methods to represent the system;
2. we can build a quantum computer.



Nature isn't classical, dammit, and if you want to make a simulation of nature, you'd better make it quantum mechanical, and by golly it's a wonderful problem, because it doesn't look so easy.

— Richard Feynman, 1982, Simulating Physics with Computers

What can we do?

1. we can try to use classical methods to represent the system;
2. we can build a quantum computer.



Nature isn't classical, dammit, and if you want to make a simulation of nature, you'd better make it quantum mechanical, and by golly it's a wonderful problem, because it doesn't look so easy.

— Richard Feynman, 1982, Simulating Physics with Computers

Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** (\uparrow, \downarrow).

Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** (\uparrow, \downarrow).

1. Each float 64 requires 8 bytes of memory to be stored;

Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** (\uparrow, \downarrow).

1. Each `float 64` requires 8 bytes of memory to be stored;
2. each `complex 128` requires 16 bytes of memory;

Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** (\uparrow, \downarrow).

1. Each float 64 requires 8 bytes of memory to be stored;
2. each complex 128 requires 16 bytes of memory;
3. let's take a nice 32Gb of RAM: it can store up to 2 billions of complex 128.

Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** (\uparrow, \downarrow).

1. Each float 64 requires 8 bytes of memory to be stored;
2. each complex 128 requires 16 bytes of memory;
3. let's take a nice 32Gb of RAM: it can store up to 2 billions of complex 128.
4. a 30 qubits state requires ~ 1 billion of complex numbers;

Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** (\uparrow, \downarrow).

1. Each float 64 requires 8 bytes of memory to be stored;
2. each complex 128 requires 16 bytes of memory;
3. let's take a nice 32Gb of RAM: it can store up to 2 billions of complex 128.
4. a 30 qubits state requires ~ 1 billion of complex numbers;
5. a 31 qubits state cannot be represented by my PC;

Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** (\uparrow, \downarrow).

1. Each float 64 requires 8 bytes of memory to be stored;
2. each complex 128 requires 16 bytes of memory;
3. let's take a nice 32Gb of RAM: it can store up to 2 billions of complex 128.
4. a 30 qubits state requires ~ 1 billion of complex numbers;
5. a 31 qubits state cannot be represented by my PC;
6. no problem. Let's get serious: Fugaku!



Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** (\uparrow, \downarrow).

1. Each float 64 requires 8 bytes of memory to be stored;
2. each complex 128 requires 16 bytes of memory;
3. let's take a nice 32Gb of RAM: it can store up to 2 billions of complex 128.
4. a 30 qubits state requires ~ 1 billion of complex numbers;
5. a 31 qubits state cannot be represented by my PC;
6. no problem. Let's get serious: Fugaku!




Some smart strategies

Some smart strategies

1. Variational Monte Carlo (VMC): given a wave function $\Psi(x|\theta)$ and a target H , MC methods are used to minimize:

$$\frac{\int dx \Psi^*(x|\theta) H \Psi(x|\theta)}{\int dx |\Psi(x|\theta)|^2} \geq E_0;$$




arXiv:1508.02989

Some smart strategies


1. Variational Monte Carlo (VMC): given a wave function $\Psi(x|\theta)$ and a target H , MC methods are used to minimize:

$$\frac{\int dx \Psi^*(x|\theta) H \Psi(x|\theta)}{\int dx |\Psi(x|\theta)|^2} \geq E_0;$$

2. Tensor Networks (TNs): contraction of complex systems into simpler structures;



arXiv:1508.02989




arXiv:1708.00006

Some smart strategies


1. Variational Monte Carlo (VMC): given a wave function $\Psi(x|\theta)$ and a target H , MC methods are used to minimize:

$$\frac{\int dx \Psi^*(x|\theta) H \Psi(x|\theta)}{\int dx |\Psi(x|\theta)|^2} \geq E_0;$$


2. Tensor Networks (TNs): contraction of complex systems into simpler structures;
3. Neural Network Quantum States: use complex ANNs to represent the state.




arXiv:1508.02989



arXiv:1708.00006



arXiv:1606.02318




A snapshot of quantum computing

Qubits


Qubits

1. classical bits are replaced by **qubits** $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$.



Superconducting loops

A resistance-free current oscillates back and forth around a circuit loop. An injected microwave signal excites the current into superposition states.




Trapped ions

Electrically charged atoms, or ions, have quantum energies that depend on the location of electrons. Tuned lasers cool and trap the ions, and put them in superposition states.




Silicon quantum dots

These "artificial atoms" are made by adding an electron to a small piece of pure silicon. Microwaves control the electron's quantum state.



Topological qubits

Quasiparticles can be seen in the behavior of electrons channeled through semiconductor structures. Their braided paths can encode quantum information.




Diamond vacancies

A nitrogen atom and a vacancy add an electron to a diamond lattice. Its quantum spin state, along with those of nearby carbon nuclei, can be controlled with light.


Qubits

1. classical bits are replaced by **qubits** $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$.
2. we can manipulate the qubit state applying **gates**: $|\psi'\rangle = \mathcal{U}(\theta)|\psi\rangle$.
Typically we use 1-qubit and 2-qubits gates!




Qubits

1. classical bits are replaced by **qubits** $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$.
2. we can manipulate the qubit state applying **gates**: $|\psi'\rangle = \mathcal{U}(\theta)|\psi\rangle$.
Typically we use 1-qubit and 2-qubits gates!
3. combine together gates to build **quantum circuits**;



Qubits

1. classical bits are replaced by **qubits** $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$.
2. we can manipulate the qubit state applying **gates**: $|\psi'\rangle = \mathcal{U}(\theta)|\psi\rangle$.
Typically we use 1-qubit and 2-qubits gates!
3. combine together gates to build **quantum circuits**;
4. to access the information we need to measure the system.



New computational power: an example

New computational power: an example

With quantum computing, we introduce new tools.

New computational power: an example

With quantum computing, we introduce new tools.

- ☞ prepare a quantum state in the computational zero $|0\rangle$;

New computational power: an example

With quantum computing, we introduce new tools.

- ☞ prepare a quantum state in the computational zero $|0\rangle$;
- ☰ we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)$$

New computational power: an example

With quantum computing, we introduce new tools.

- ☞ prepare a quantum state in the computational zero $|0\rangle$;
- ≡ we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad \text{with} \quad H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix};$$

New computational power: an example

With quantum computing, we introduce new tools.

👉 prepare a quantum state in the computational zero $|0\rangle$;

☰ we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad \text{with} \quad H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix};$$

⌚ let's apply a controlled-NOT (CNOT) gate on a second qubit prepared in $|0\rangle$:

$$\text{CNOT}\left(\underbrace{\frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)}_{\text{control}} \otimes |0\rangle\right) =$$

New computational power: an example

With quantum computing, we introduce new tools.

☞ prepare a quantum state in the computational zero $|0\rangle$;

☞ we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad \text{with} \quad H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix};$$

☞ let's apply a controlled-NOT (CNOT) gate on a second qubit prepared in $|0\rangle$:

$$\text{CNOT}\left(\underbrace{\frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)}_{\text{control}} \otimes |0\rangle\right) = \frac{1}{\sqrt{2}}(|00\rangle + \text{NOT}_{\text{targ}}|10\rangle) =$$

New computational power: an example

With quantum computing, we introduce new tools.

☞ prepare a quantum state in the computational zero $|0\rangle$;

☞ we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad \text{with} \quad H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix};$$

☞ let's apply a controlled-NOT (CNOT) gate on a second qubit prepared in $|0\rangle$:

$$\text{CNOT} \left(\underbrace{\frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \otimes |0\rangle}_{\text{control}} \right) = \frac{1}{\sqrt{2}}(|00\rangle + \text{NOT}_{\text{targ}}|10\rangle) = \frac{1}{\sqrt{2}}(|00\rangle + |11\rangle).$$

New computational power: an example


With quantum computing, we introduce new tools.

- 👉 prepare a quantum state in the computational zero $|0\rangle$;
- 👉 we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad \text{with} \quad H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix};$$

- 👉 let's apply a controlled-NOT (CNOT) gate on a second qubit prepared in $|0\rangle$:

$$\text{CNOT}\left(\underbrace{\frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)}_{\text{control}} \otimes |0\rangle\right) = \frac{1}{\sqrt{2}}(|00\rangle + \text{NOT}_{\text{targ}}|10\rangle) = \frac{1}{\sqrt{2}}(|00\rangle + |11\rangle).$$



Parametric gates prepare variational quantum states

Parametric gates prepare variational quantum states

💡 Among the gates, parametric ones can be useful!

Parametric gates prepare variational quantum states

- 💡 Among the gates, parametric ones can be useful!
- 💡 Let's consider a single qubit system:


$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

Parametric gates prepare variational quantum states

💡 Among the gates, parametric ones can be useful!

💡 Let's consider a single qubit system:

$$|\psi\rangle = \alpha |0\rangle + \beta |1\rangle \quad \text{with} \quad \alpha = \cos \frac{\theta}{2}, \quad \beta = e^{i\phi} \sin \frac{\theta}{2}.$$




Parametric gates prepare variational quantum states

💡 Among the gates, parametric ones can be useful!

💡 Let's consider a single qubit system:

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle \quad \text{with} \quad \alpha = \cos \frac{\theta}{2}, \quad \beta = e^{i\phi} \sin \frac{\theta}{2}.$$



We can use as parametric gates the rotation around the axis of the block sphere:

$$R_k(\theta) = \exp[-i\theta\sigma_k], \quad \text{with} \quad \sigma_k \in \{I, \sigma_x, \sigma_y, \sigma_z\}.$$

But can this work?

But can this work?

1. Depend on the problem

But can this work?

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!

But can this work?

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

But can this work?


1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

Using Variational Quantum Circuits we define a Variational Quantum Computer!

But can this work?

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

Using Variational Quantum Circuits we define a Variational Quantum Computer!




But can this work?

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

Using Variational Quantum Circuits we define a Variational Quantum Computer!

1. we want a quantum circuit $\mathcal{U}(\theta)$ to approximates some law V ;




But can this work?

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

Using Variational Quantum Circuits we define a Variational Quantum Computer!

1. we want a quantum circuit $\mathcal{U}(\theta)$ to approximates some law V ;
2. executing $\mathcal{U}(\theta)$ we use a variational quantum state to reach the solution;




But can this work?

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

Using Variational Quantum Circuits we define a Variational Quantum Computer!

1. we want a quantum circuit $\mathcal{U}(\theta)$ to approximates some law V ;
2. executing $\mathcal{U}(\theta)$ we use a variational quantum state to reach the solution;
3. **Solovay-Kitaev theorem:** the number of gates needed by \mathcal{U} to represent V with precision δ is $\mathcal{O}(\log^c \delta^{-1})$, where $c < 4$.



Qibo as full-stack playground

Simulation, control and calibration with Qibo

