

# **Introduction to Quantum Computing**

## Quantum Computing Minicourse

---

Stefano Carrazza and Matteo Robbiati


8 April 2024



# Compute quantum mechanics


# Compute quantum mechanics

- ✖ Representing  $N$  particles is difficult;



# Compute quantum mechanics

- ✿ Representing  $N$  particles is difficult;
- ✿ considering  $N$  spins ( $\uparrow, \downarrow$ ), we deal with a  $2^N$  dimensional Hilbert space!



## What can we do?

---

## What can we do?

---

1. we can try to use classical methods to represent the system;

## What can we do?

---

1. we can try to use classical methods to represent the system;
2. we can build a quantum computer.

## What can we do?


---

1. we can try to use classical methods to represent the system;
2. we can build a quantum computer.



# What can we do?

1. we can try to use classical methods to represent the system;
2. we can build a quantum computer.



*Nature isn't classical, dammit, and if you want to make a simulation of nature, you'd better make it quantum mechanical, and by golly it's a wonderful problem, because it doesn't look so easy.*

— Richard Feynman, 1982, Simulating Physics with Computers

# What can we do?

1. we can try to use classical methods to represent the system;
2. we can build a quantum computer.



*Nature isn't classical, dammit, and if you want to make a simulation of nature, you'd better make it quantum mechanical, and by golly it's a wonderful problem, because it doesn't look so easy.*

— Richard Feynman, 1982, Simulating Physics with Computers

## Can we represent a state with a classical computer?

---

Let's suppose we want to represent a system of **qubits** ( $\uparrow, \downarrow$ ).

## Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** ( $\uparrow, \downarrow$ ).

1. Each float 64 requires 8 bytes of memory to be stored;

## Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** ( $\uparrow, \downarrow$ ).

1. Each `float 64` requires 8 bytes of memory to be stored;
2. each `complex 128` requires 16 bytes of memory;

## Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** ( $\uparrow, \downarrow$ ).

1. Each float 64 requires 8 bytes of memory to be stored;
2. each complex 128 requires 16 bytes of memory;
3. let's take a nice 32Gb of RAM: it can store up to 2 billions of complex 128.

## Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** ( $\uparrow, \downarrow$ ).

1. Each float 64 requires 8 bytes of memory to be stored;
2. each complex 128 requires 16 bytes of memory;
3. let's take a nice 32Gb of RAM: it can store up to 2 billions of complex 128.
4. a 30 qubits state requires  $\sim 1$  billion of complex numbers;

## Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** ( $\uparrow, \downarrow$ ).

1. Each float 64 requires 8 bytes of memory to be stored;
2. each complex 128 requires 16 bytes of memory;
3. let's take a nice 32Gb of RAM: it can store up to 2 billions of complex 128.
4. a 30 qubits state requires  $\sim 1$  billion of complex numbers;
5. a 31 qubits state cannot be represented by my PC;

# Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** ( $\uparrow, \downarrow$ ).

1. Each float 64 requires 8 bytes of memory to be stored;
2. each complex 128 requires 16 bytes of memory;
3. let's take a nice 32Gb of RAM: it can store up to 2 billions of complex 128.
4. a 30 qubits state requires  $\sim 1$  billion of complex numbers;
5. a 31 qubits state cannot be represented by my PC;
6. no problem. Let's get serious: Fugaku!



# Can we represent a state with a classical computer?

Let's suppose we want to represent a system of **qubits** ( $\uparrow, \downarrow$ ).

1. Each float 64 requires 8 bytes of memory to be stored;
2. each complex 128 requires 16 bytes of memory;
3. let's take a nice 32Gb of RAM: it can store up to 2 billions of complex 128.
4. a 30 qubits state requires  $\sim 1$  billion of complex numbers;
5. a 31 qubits state cannot be represented by my PC;
6. no problem. Let's get serious: Fugaku!




## Some smart strategies

---

## Some smart strategies

1. Variational Monte Carlo (VMC): given a wave function  $\Psi(x|\theta)$  and a target  $H$ , MC methods are used to minimize:

$$\frac{\int dx \Psi^*(x|\theta) H \Psi(x|\theta)}{\int dx |\Psi(x|\theta)|^2} \geq E_0;$$




arXiv:1508.02989

## Some smart strategies


1. Variational Monte Carlo (VMC): given a wave function  $\Psi(x|\theta)$  and a target  $H$ , MC methods are used to minimize:

$$\frac{\int dx \Psi^*(x|\theta) H \Psi(x|\theta)}{\int dx |\Psi(x|\theta)|^2} \geq E_0;$$

2. Tensor Networks (TNs): contraction of complex systems into simpler structures;



arXiv:1508.02989




arXiv:1708.00006

## Some smart strategies


1. Variational Monte Carlo (VMC): given a wave function  $\Psi(x|\theta)$  and a target  $H$ , MC methods are used to minimize:

$$\frac{\int dx \Psi^*(x|\theta) H \Psi(x|\theta)}{\int dx |\Psi(x|\theta)|^2} \geq E_0;$$


2. Tensor Networks (TNs): contraction of complex systems into simpler structures;
3. Neural Network Quantum States: use complex ANNs to represent the state.



arXiv:1508.02989




arXiv:1708.00006



arXiv:1606.02318





## A snapshot of quantum computing


---

# Qubits

---


# Qubits

1. classical bits are replaced by **qubits**  $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$ .



## Superconducting loops

A resistance-free current oscillates back and forth around a circuit loop. An injected microwave signal excites the current into superposition states.




## Trapped ions

Electrically charged atoms, or ions, have quantum energies that depend on the location of electrons. Tuned lasers cool and trap the ions, and put them in superposition states.




## Silicon quantum dots

These "artificial atoms" are made by adding an electron to a small piece of pure silicon. Microwaves control the electron's quantum state.



## Topological qubits

Quasiparticles can be seen in the behavior of electrons channeled through semiconductor structures. Their braided paths can encode quantum information.




## Diamond vacancies

A nitrogen atom and a vacancy add an electron to a diamond lattice. Its quantum spin state, along with those of nearby carbon nuclei, can be controlled with light.


# Qubits

1. classical bits are replaced by **qubits**  $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$ .
2. we can manipulate the qubit state applying **gates**:  $|\psi'\rangle = \mathcal{U}(\theta)|\psi\rangle$ .  
Typically we use 1-qubit and 2-qubits gates!




# Qubits

1. classical bits are replaced by **qubits**  $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$ .
2. we can manipulate the qubit state applying **gates**:  $|\psi'\rangle = \mathcal{U}(\theta)|\psi\rangle$ .  
Typically we use 1-qubit and 2-qubits gates!
3. combine together gates to build **quantum circuits**;



# Qubits

1. classical bits are replaced by **qubits**  $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$ .
2. we can manipulate the qubit state applying **gates**:  $|\psi'\rangle = \mathcal{U}(\theta)|\psi\rangle$ .  
Typically we use 1-qubit and 2-qubits gates!
3. combine together gates to build **quantum circuits**;
4. to access the information we need to measure the system.



## New computational power: an example

---

## New computational power: an example

---

With quantum computing, we introduce new tools.

## New computational power: an example

With quantum computing, we introduce new tools.

- ☞ prepare a quantum state in the computational zero  $|0\rangle$ ;

## New computational power: an example

With quantum computing, we introduce new tools.

- ☞ prepare a quantum state in the computational zero  $|0\rangle$ ;
- ≡ we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)$$

## New computational power: an example

With quantum computing, we introduce new tools.

- ☞ prepare a quantum state in the computational zero  $|0\rangle$ ;
- ≡ we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad \text{with} \quad H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix};$$

## New computational power: an example

With quantum computing, we introduce new tools.

👉 prepare a quantum state in the computational zero  $|0\rangle$ ;

☰ we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad \text{with} \quad H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix};$$

⌚ let's apply a controlled-NOT (CNOT) gate on a second qubit prepared in  $|0\rangle$ :

$$\text{CNOT} \left( \underbrace{\frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)}_{\text{control}} \otimes |0\rangle \right) =$$

## New computational power: an example

With quantum computing, we introduce new tools.

☞ prepare a quantum state in the computational zero  $|0\rangle$ ;

☞ we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad \text{with} \quad H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix};$$

☞ let's apply a controlled-NOT (CNOT) gate on a second qubit prepared in  $|0\rangle$ :

$$\text{CNOT}\left(\underbrace{\frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)}_{\text{control}} \otimes |0\rangle\right) = \frac{1}{\sqrt{2}}(|00\rangle + \text{NOT}_{\text{targ}}|10\rangle) =$$

## New computational power: an example

With quantum computing, we introduce new tools.

☞ prepare a quantum state in the computational zero  $|0\rangle$ ;

☞ we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad \text{with} \quad H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix};$$

☞ let's apply a controlled-NOT (CNOT) gate on a second qubit prepared in  $|0\rangle$ :

$$\text{CNOT} \left( \underbrace{\frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \otimes |0\rangle}_{\text{control}} \right) = \frac{1}{\sqrt{2}}(|00\rangle + \text{NOT}_{\text{targ}}|10\rangle) = \frac{1}{\sqrt{2}}(|00\rangle + |11\rangle).$$

## New computational power: an example


With quantum computing, we introduce new tools.

- 👉 prepare a quantum state in the computational zero  $|0\rangle$ ;
- 👉 we can prepare superposition:

$$H|0\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \quad \text{with} \quad H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad |0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix};$$

- 👉 let's apply a controlled-NOT (CNOT) gate on a second qubit prepared in  $|0\rangle$ :

$$\text{CNOT}\left(\underbrace{\frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)}_{\text{control}} \otimes |0\rangle\right) = \frac{1}{\sqrt{2}}(|00\rangle + \text{NOT}_{\text{targ}}|10\rangle) = \frac{1}{\sqrt{2}}(|00\rangle + |11\rangle).$$



## Parametric gates prepare variational quantum states

## Parametric gates prepare variational quantum states

💡 Among the gates, parametric ones can be useful!

## Parametric gates prepare variational quantum states

- 💡 Among the gates, parametric ones can be useful!
- 💡 Let's consider a single qubit system:


$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

## Parametric gates prepare variational quantum states

💡 Among the gates, parametric ones can be useful!

💡 Let's consider a single qubit system:

$$|\psi\rangle = \alpha |0\rangle + \beta |1\rangle \quad \text{with} \quad \alpha = \cos \frac{\theta}{2}, \quad \beta = e^{i\phi} \sin \frac{\theta}{2}.$$




## Parametric gates prepare variational quantum states

💡 Among the gates, parametric ones can be useful!

💡 Let's consider a single qubit system:

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle \quad \text{with} \quad \alpha = \cos \frac{\theta}{2}, \quad \beta = e^{i\phi} \sin \frac{\theta}{2}.$$



We can use as parametric gates the rotation around the axis of the block sphere:

$$R_k(\theta) = \exp[-i\theta\sigma_k], \quad \text{with} \quad \sigma_k \in \{I, \sigma_x, \sigma_y, \sigma_z\}.$$

**But can this work?**

---

## But can this work?

---

1. Depend on the problem

## But can this work?

---

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!

## But can this work?

---

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

## But can this work?

---


1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

Using Variational Quantum Circuits we define a Variational Quantum Computer!

## But can this work?

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

Using Variational Quantum Circuits we define a Variational Quantum Computer!




## But can this work?

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

Using Variational Quantum Circuits we define a Variational Quantum Computer!

1. we want a quantum circuit  $\mathcal{U}(\theta)$  to approximates some law  $V$ ;




## But can this work?

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

Using Variational Quantum Circuits we define a Variational Quantum Computer!

1. we want a quantum circuit  $\mathcal{U}(\theta)$  to approximates some law  $V$ ;
2. executing  $\mathcal{U}(\theta)$  we use a variational quantum state to reach the solution;




## But can this work?

1. Depend on the problem, e.g. playing in the Hilbert space makes sense when tackling a many body problem!
2. We can take some more rational proof of utility.

Using Variational Quantum Circuits we define a Variational Quantum Computer!

1. we want a quantum circuit  $\mathcal{U}(\theta)$  to approximates some law  $V$ ;
2. executing  $\mathcal{U}(\theta)$  we use a variational quantum state to reach the solution;
3. **Solovay-Kitaev theorem:** the number of gates needed by  $\mathcal{U}$  to represent  $V$  with precision  $\delta$  is  $\mathcal{O}(\log^c \delta^{-1})$ , where  $c < 4$ .



## **Qibo as full-stack playground**

---



# Simulation, control and calibration with Qibo

