

Quotation # S01186

Quotation Date: 18/06/2026
Expiration: 18/07/2026
Salesperson: Fauzan Pahok

Supplier: Cherrytech Asia Co.,Ltd (U.K)
M.10 264-264/1 Lampang-Chiang Mai Superhighway,
Umong, Mueang Lamphun District, Lamphun 51550, Thailand

Product Lines and Attached Specifications

Long notes from the original description column have been grouped under the product line immediately above them so that every specification stays with the correct item.

Description	Quantity	Unit Price	Amount
1. JT Automation - LD-400C Automatic Magazine Loader	1.00 Units	\$ 5,440.00	\$ 5,440.00

Specifications

- External dimension: L1975 x W860 x H1280 +/- 30 mm
- Special aluminum profile guide rail and special plastic chain
- 90 W brake motor drive adopts ball screw to make magazine step up and down
- The transmission motor adopts 25 W constant speed motor
- Pneumatic clamp structure
- Turnover box specification: L460 x W400 x H565 mm
- PCB specification max: L400 x W330
- Direction: right to left / left to right
- Lifting platform pitch selections: 10, 20, 30, 40
- Transmission height: H = 920 +/- 30 mm
- Xinjie PLC control
- Automatic board loading function
- Leisai stepping motor push plate
- Power supply: 220 V, 50 Hz
- Air source: 0.4-0.6 MPa
- Full-load storage plate quantity: 50 pcs
- One set of electric control box

Description	Quantity	Unit Price	Amount
2. JT Automation - BC-350 Link Conveyor	3.00 Units	\$ 1,360.00	\$ 4,080.00

Specifications

- Rail length: 800 mm or specified length
- Dimension: Standard rail 734 x 910 mm (aluminum side guard)
- Dimension: ESD rail 860 x 910 mm (antistatic aluminum side guard)
- Board width range: 50-350 mm
- Optional max width: 300 / 400 / 450 mm
- Conveyor height: Standard 900 +/- 20 mm; Optional 950 +/- 20 mm
- PCB direction: Standard L to R; Optional R to L
- Conveyor speed range: 0-10 m/min
- Power supply: Standard AC 220 V 1 phase 50/60 Hz; Optional AC 110 V
- Communication port: Interface SMEMA signal
- Accessories: Foot switch, lighting, SOP rack
- Stopper type: 2/3 belt segment transfer, PLC control

Description	Quantity	Unit Price	Amount
3. DESEN - DGHP Automatic SMT Stencil Screen Printer	1.00 Units	\$ 60,690.00	\$ 60,690.00
Printing Performance - Accuracy: +/-18 um @ 66, Cpk > 2.0 - Repeat accuracy: +/-10 um @ 66, Cpk > 2.0 - Cycle time: 7 s (no cleaning/printing) - Printing pressure: 0-20 kg (software control) - Printing gap: 0-20 mm Board Handling - PCB size: 50 x 50 mm - 510 x 510 mm - PCB thickness: 0.4-6 mm - PCB warpage: <= 1% - Conveyor height: 900 +/- 40 mm - Conveyor speed: <= 1500 mm/s Optical System - Camera: 1.3 MP (up/down) - FOV: 10 x 8 mm - Fiducial types: Square, round, triangle, cross Software & Control - OS: Desen V2.2 - PC software: Windows 10 / XP - Interface: SMEMA standard Machine Dimensions - Size (L x W x H): 1240 x 1430 x 1550 mm - Weight: approx. 1280 kg Power & Air - Voltage: 220 V +/- 10%, single phase 50/60 Hz - Power: 2 kW - Air supply: 4.5-6 kgf/cm2 - Air consumption: 5 L/min			

Description	Quantity	Unit Price	Amount
4. MagicRay Inline SPI Machine - Icon+ (12MP Camera, CE machine)	1.00 Units	\$ 45,980.00	\$ 45,980.00

Image System

- Camera: 12 MP industrial camera
- Resolution: 5.5 um, 10 um, 12 um, 15 um
- Height resolution: 0.37 um
- Lighting: 3-color ring shape LED (RGB)
- Height measurement method: Projectors

Movement Structure

- X/Y movement: AC servo
- Platform: Granite
- Width adjustment: Automatic
- Transport type: Belt
- Board loading direction: Left to right or right to left (select at order)
- Fixed rail: Front rail (1st & 3rd fixed rail or 1st & 4th fixed rail)

Hardware Configuration

- Operating system: Windows 10
- Communicator: Ethernet, SMTA
- Power requirement: Single phase 220 V, 50/60 Hz, 5 A
- Air requirement: 0.4-0.6 MPa
- Conveyor height: 900 +/- 20 mm
- Equipment dimensions (L x W x H): 1000 x 1360 x 1620 mm (without tower light)
- Equipment weight: 950 kg

Board Handling

- PCB size: 50 x 50 - 510 x 610 mm
- Clamping edge: 3 mm
- Maximum pad height: 600 um
- Minimum pad spacing: 100 um (within height of 150 um)
- Maximum solder paste inspection size: 20 x 20 mm
- Minimum solder paste inspection size: 0.1 mm

Inspection Functions

- GR&R: <= 10%
- Defects detected: Icicle, insufficient solder, excess solder, average height, offset, solder bridge, odd shape, exposed copper, gold finger, etc.
- Inspection speed: 400-450 ms / FOV

Description	Quantity	Unit Price	Amount
5. Panasonic Mounter NPM W2, 16 Nozzle Head	2.00 Units	\$ 100,000.00	\$ 200,000.00

Note

- 2020/2021 models

Description	Quantity	Unit Price	Amount
6. MagicRay Inline 3D AOI Machine - Cube+ (12MP Camera, CE machine)	1.00 Units	\$ 78,290.00	\$ 78,290.00

Image System

- Camera: 12 MP industrial camera
- Resolution: 15 um, 12 um, 10 um
- FOV: 60 x 45 mm (12 um, 15 um)
- Lighting: 4-color ring shape LED (RGBW)
- Height measurement method: 4-way projectors

Movement Structure

- X/Y movement: AC servo (dual drive)
- Platform: Granite
- Width adjustment: Automatic
- Transport type: Belt
- Board loading direction: Left to right or right to left (select at order)
- Fixed rail: Single lane: 1st fixed rail; Dual lane: 1st & 3rd fixed rail or 1st & 4th fixed rail

Hardware Configuration

- Operating system: Windows 10
- Communication: Ethernet, SMEMA
- Power requirement: Single phase 220 V, 50/60 Hz, 5 A
- Air requirement: 0.4-0.6 MPa
- Conveyor height: 900 +/- 20 mm
- Equipment dimensions (L x W x H): 1140 x 1360 x 1620 mm (without tower light)
- Equipment weight: 1100 kg

PCB Size & Handling

- PCB size: 50 x 60 - 510 x 510 mm
- Thickness: <= 6.0 mm
- Warping: +/- 3.0 mm
- Component clearance: Top 25-50 mm (adjustable), bottom 45 mm
- Clamping edge: 3.0 mm
- PCB weight: <= 3.0 kg

Inspection Categories

- Component defects: Wrong component, missing, polarity, shift, reverse, damage, IC lead bend, IC lifted lead, foreign material, float, coplanarity, tombstone, etc.
- Solder joint defects: No solder, insufficient solder, open solder, excess solder, solder bridge, solder ball, etc.
- Component size: Chip 03015 and above (3D); LSI 0.3 mm pitch and above; others: odd-shape component
- Measurable range: 35 mm (15 um)
- Height resolution: 0.37 um
- Inspection speed: 450 ms / FOV

Description	Quantity	Unit Price	Amount
7. JT Automation - JTR-1000 Hot Air Lead-Free Reflow Oven (PCB Width 400 mm)	1.00 Units	\$ 46,500.00	\$ 46,500.00

General Description

- Dimension (L x W x H): 6300 x 1430 x 1530 mm
- Color: White
- Net weight: approx. 2700 kg
- Air exhaust: 10 m3/min x 2 channels

Power & Supply

- Electrical supply: 5-wire 3-phase 380 V 50/60 Hz (option: 220 V 50/60 Hz)
- Start power: 36 kW
- Working power: 10 kW
- Warming time: approx. 25 min
- Temperature range: Room - 300 deg C

PCB Handling

- Max PCB width: 400 mm (option: 460 mm)
- Component height: Top 30 mm / Bottom 25 mm
- Conveyor direction: L to R (option: R to L)
- Conveyor fixed method: Front fixed (option: rear fixed)
- Conveyor height: 900 +/- 20 mm
- Conveyor speed: 300-2000 mm/min

Control & Operation

- Parameter storage: Multiple production setups and conditions storable
- Abnormal alarm: Extra-high/low temperature alarm with light & sound
- Lubricant refueling: Manual and auto

Equipment Specifications

- Heating/cooling zones: Top 10 + bottom 10 heating zones; top 3 + bottom 3 cooling zones
- Control system: Windows 10 + PC + PLC
- Temperature control: PID closed-loop control + SSR driving
- Temperature wire: 4-wire
- Conveyor system: Single rail
- Conveyor control method: Inverter + imported motor
- Chain structure: Dual-link to avoid blockage
- Rail structure: Integrated segmented type
- Rail width adjustment: Electronic adjustable
- Cover open method: Electronic open for easy maintenance
- UPS backup: Included

Description	Quantity	Unit Price	Amount
8. JT Automation - BC-350 Link Conveyor (1200 mm) with Cooling Fan	1.00 Units	\$ 1,700.00	\$ 1,700.00

Specifications

- Rail length: 1200 mm or specified length
- Dimension: Standard rail 734 x 910 mm (aluminum side guard)
- Dimension: ESD rail 860 x 910 mm (antistatic aluminum side guard)
- Board width range: 50-350 mm
- Optional max width: 300 / 400 / 450 mm
- Conveyor height: Standard 900 +/- 20 mm; Optional 950 +/- 20 mm
- PCB direction: Standard L to R; Optional R to L
- Conveyor speed range: 0-10 m/min
- Power supply: Standard AC 220 V 1 phase 50/60 Hz; Optional AC 110 V
- Communication port: Interface SMEMA signal
- Accessories: Foot switch, lighting, SOP rack
- Stopper type: 2/3 belt segment transfer, PLC control
- 4 cooling fans

Description	Quantity	Unit Price	Amount
9. JT Automation - ULD-400C Automatic Magazine Unloader	1.00 Units	\$ 6,120.00	\$ 6,120.00

Specifications

- External dimension: L2730 x W860 x H1280 mm +/- 30 mm
- Special aluminum profile guide rail and special plastic chain
- 90 W brake motor drives ball screw to make magazine step up and down
- Pneumatic clamp structure
- With a set of 0.9 m-long push plate conveyor
- Turnover box specification: L460 x W400 x H565 mm
- PCB specification max: L400 x W330
- Direction: left to right / right to left
- Lifting platform pitch selections: 10, 20, 30, 40
- Xinjie PLC control
- Automatic closing function
- Touch screen display control
- Power supply: 220 V, 50 Hz
- Air source: 0.4-0.6 MPa
- Full-load storage plate quantity: 50 pcs
- One set of electric control box

Description	Quantity	Unit Price	Amount
10. Offline 3D/CT X-Ray Inspector X-7900 Ultra	1.00 Units	\$ 200,000.00	\$ 200,000.00
Tube System - Type: Open tube - Spatial resolution: 1 um - Tube voltage: 160 kV - Tube current: 500 uA - Image taking type: Flat-panel digital - Imaging precision: 85 um - A/D convert quantified density value: 16 bit (65,536) - DPI: 1536 x 1536 px - Frame frequency: 20 FPS - Software type: 3D software - Magnification: 2000x / 7500x Power & Safety - Power supply: AC 110-220 V, 50-60 Hz, 1200 W - Radiation safety test: < 1 uSv/h - FPD rotation angle: +/- 70 deg Stage & Motion - Stage size: 670 x 670 mm - Sensing range: 600 x 600 mm - Load-bearing: <= 10 kg - Stage movement: Automatic / Manual Machine Structure - Machine size (L x W x H): 1578 x 1675 x 1910 mm - Machine size (including monitor): 1578 x 1675 x 2265 mm - Machine weight: 2200 kg Certification & Compliance - CE certificate: Yes (STE23113101S) - Radiation safety permit: Yes - State immunity: Guangdong Environmental Radiation Safety Permit [B0640]			

Description	Quantity	Unit Price	Amount
Ocean Freight	1.00 Units	\$ 6,000.00	\$ 6,000.00

Total	\$ 654,800.00		
-------	---------------	--	--

Commercial Terms

Payment Terms: 50% deposit, 50% to be paid before shipment.
Lead Time: 45-60 days.
Warranty: The Screen Printer is covered by a 15-month warranty. Loaders, Conveyors, and Reflow Oven are covered by a 2-year warranty. SPI, AOI, and X-Ray machines are covered by a 1-year warranty.
Used Chip Mounters are supplied without warranty.
Installation and training fee included.
Delivery Term: DAP.
Prices do not include local import taxes or customs duties (if any).