

Final Project Algorithm Documentation

Folio - Personalized arXiv Paper Recommendation System

Kind Monkeys

May 1, 2026

1 Project Summary

Folio is a personalized arXiv paper recommendation system designed for researchers who want both a passive daily feed and an active search experience. The user-facing problem is that modern research discovery is simultaneously too broad and too fragmented: keyword search is useful when the user already knows what to ask, while generic feeds often collapse into a narrow or noisy view of the literature. Folio addresses this by building a persistent user-interest representation and reusing it across two product modes:

1. **Daily Feed:** a personalized top-20 feed generated from the user’s inferred research threads, recency signals, and diversity controls.
2. **Personalized Query Search:** a query search bar that treats the user’s explicit query as the primary intent while using the learned profile as a personalization prior.

The core algorithmic idea is to represent a user as a small set of research-thread centroids rather than a single averaged vector. Onboarding signals can come from arXiv categories, predefined concept tags, and free-text interests. These heterogeneous signals are converted into normalized embeddings, grouped by threshold-based agglomeration, and capped at at most three user-interest threads. The same multi-centroid user profile then supports both feed serving and query-search reranking.

The system uses SPECTER2-style scientific-paper embeddings, a MiniBatchKMeans spatial index over the full corpus for efficient retrieval, arXiv category centroids for interpretable cold-start labels, and cached concept embeddings for non-arXiv interests such as Healthcare AI, Climate and Weather, Computational Biology, and Scientific ML. The k-means layer is deliberately treated as a spatial index, not as human-readable topic discovery.

Evaluation is designed around ranked top-20 outputs. Relevance is judged at the paper level and aggregated with Strict Precision@20, Soft Precision@20, Mean Relevance@20, and NDCG@20. For Daily Feed, we additionally report Thread Coverage@20 and Redundancy@20 to ensure that the system is not merely relevant but also diverse across the user’s inferred research threads.

2 Algorithm Description

2.1 System overview

The current system has one offline artifact-building pipeline and three online modules: user initialization, daily-feed serving, and query-search serving. Offline, the corpus is embedded and indexed.

Online, onboarding choices create a multi-centroid user profile. Daily Feed retrieves papers around that profile, while Query Search retrieves around both the query and the user profile.

2.2 Notation

Let N be the number of papers in the indexed corpus and $d = 768$ the embedding dimension. For paper p , let $e_p \in \mathbb{R}^d$ be its normalized embedding. Let $E \in \mathbb{R}^{N \times d}$ be the matrix of paper embeddings. Let K_c be the number of MiniBatchKMeans spatial-index clusters, $z_p \in \{1, \dots, K_c\}$ the cluster id of paper p , and $C \in \mathbb{R}^{K_c \times d}$ the matrix of normalized k-means centroids.

A user profile is represented as

$$U = \{(\mathbf{u}_1, \pi_1), \dots, (\mathbf{u}_m, \pi_m)\}, \quad 1 \leq m \leq 3,$$

where $\mathbf{u}_j \in \mathbb{R}^d$ is a normalized research-thread centroid and $\pi_j \geq 0$ is the normalized thread weight, with $\sum_{j=1}^m \pi_j = 1$. The user diversity index is denoted by $\delta \in [0, 1]$.

Table 1: Runtime and offline artifacts.

Artifact	Shape / Type	Role
E	$N \times 768$ matrix	Unit-normalized paper embeddings; dot product equals cosine similarity.
z_p	integer cluster id	Spatial-index assignment for paper p .
C	$K_c \times 768$ matrix	MiniBatchKMeans centroids used to select candidate clusters.
Category centroids	dict: arXiv code $\rightarrow \mathbb{R}^{768}$	Human-interpretable onboarding anchors derived from arXiv categories.
Concept embeddings	dict: concept tag $\rightarrow \mathbb{R}^{768}$	Cached embeddings for predefined non-arXiv tags.
Paper metadata	table / JSONL	Titles, abstracts, categories, timestamps, arXiv ids, and display fields.
Optional visualization assets	reducer and 2D coordinates	Used only for visualization; not part of ranking.

3 Offline Artifact Pipeline

3.1 Corpus text and embedding

For each arXiv paper, the encoder input is the scientific text

$$T_p = \text{title}_p + ". " + \text{abstract}_p.$$

The paper embedding is

$$e_p = \text{normalize}(\text{SPECTER2}(T_p)).$$

All retrieval and ranking similarities use dot products between normalized vectors.

3.2 k-means spatial index

MiniBatchKMeans is trained on E to produce a spatial index:

$$(z_1, \dots, z_N), C = \text{MiniBatchKMeans}(E, K_c).$$

For a query vector or user centroid, the system first selects nearby clusters and then computes exact dot-product scores only within the selected clusters. This is an efficiency mechanism. The cluster ids are not interpreted as semantic topics.

3.3 Category and concept anchors

For an arXiv category a , define

$$P_a = \{p : a \in \text{categories}(p)\}, \quad c_a = \text{normalize} \left(\frac{1}{|P_a|} \sum_{p \in P_a} e_p \right).$$

These category centroids are interpretable anchors for onboarding.

Predefined concept tags are embedded using descriptive scientific templates rather than raw short labels. If x is a concept label, the cached concept vector is

$$v_x = \text{normalize}(\text{Embed}(\text{expand}(x))),$$

where $\text{expand}(x)$ is a research-context prompt describing methods, applications, datasets, benchmarks, and scientific contributions relevant to x .

4 User Embedding Initialization

4.1 Design goal

The current initialization algorithm replaces the older small-seed k-means approach. It is designed to handle heterogeneous onboarding inputs and infer a small number of coherent research threads. The key design principle is that broad tags should support the profile but should not automatically create separate interests. Specific signals, especially free text and specific concept tags, are allowed to form threads.

Current tuned initialization parameters.

$$\text{MERGE_THRESHOLD} = 0.05, \quad \text{MAX_THREADS} = 3, \quad \text{CORE_SPLIT_POWER} = 0.6.$$

4.2 Seed sources

The unified onboarding UI may contain arXiv-category tags and predefined concept tags in the same visible pool. The backend routes them differently:

- arXiv labels call the category-seed path and may map to one or more arXiv category centroids;
- concept labels call the concept-seed path and use cached concept embeddings;

- optional free-text interests are expanded and embedded at runtime.

Each input becomes a seed signal

$$s = (\text{text}_s, \mathbf{v}_s, \text{source}_s, w_s, r_s, \sigma_s, \rho_s),$$

where $\mathbf{v}_s$ is unit-normalized, w_s is base weight, r_s is reliability, σ_s is specificity, and ρ_s is split power. The effective weight used for centroid construction is

$$w_s^{\text{eff}} = w_s r_s \sigma_s.$$

The current seed-source defaults are summarized in Table 2. Broad predefined tags have low split power; specific predefined tags and free text can create threads.

Table 2: Default seed-source parameters for current initialization.

Seed type	w_s	r_s	σ_s	ρ_s
Broad predefined tag	1.0	0.9	0.5	0.3
Specific predefined tag	1.5	0.9	0.7	0.7
Free text	2.0	0.8	0.9	1.0

4.3 Free-text expansion

For a free-text user interest x , the system embeds expanded retrieval text instead of the raw phrase. A typical template is

Research papers about {x}. Focus on relevant methods, datasets, benchmarks, applications, theoretical contributions, and recent scientific progress.

Then

$$\mathbf{v}_x = \text{normalize}(\text{Embed}(\text{expand}(x))).$$

4.4 Core and support seeds

A seed is a thread-forming core seed when

$$\rho_s \geq \rho_{\min} = \text{CORE_SPLIT_POWER} = 0.6.$$

Otherwise it is a support seed. Core seeds determine the initial thread structure. Support seeds are assigned to the nearest inferred thread and contribute to the final weighted centroid.

4.5 Agglomerative threshold grouping

For normalized vectors, cosine distance is

$$d(\mathbf{a}, \mathbf{b}) = 1 - \mathbf{a}^\top \mathbf{b}.$$

The algorithm starts with each core seed as a singleton group. For a group G , its centroid is

$$\mathbf{g}_G = \text{normalize} \left(\sum_{s \in G} w_s^{\text{eff}} \mathbf{v}_s \right).$$

At each step, the closest pair of groups is merged if

$$\min_{G_i \neq G_j} d(\mathbf{g}_{G_i}, \mathbf{g}_{G_j}) \leq \tau_{\text{merge}}, \quad \tau_{\text{merge}} = 0.05.$$

Merging stops when no pair is close enough. If the number of groups exceeds three, the implementation enforces $m \leq 3$ by merging or retaining the strongest groups according to the configured cap. If no seed is specific enough to be core, all seeds are promoted to the core set so that a user profile is always initialized.

After the core groups are inferred, every support seed is assigned to its nearest core group:

$$\ell(s) = \arg \max_j \mathbf{v}_s^\top \mathbf{g}_{G_j}.$$

Final user centroids and thread weights are recomputed from all seeds assigned to each group:

$$\mathbf{u}_j = \text{normalize} \left(\sum_{s: \ell(s)=j} w_s^{\text{eff}} \mathbf{v}_s \right), \quad \pi_j = \frac{\sum_{s: \ell(s)=j} w_s^{\text{eff}}}{\sum_{h=1}^m \sum_{s: \ell(s)=h} w_s^{\text{eff}}}.$$

The result is $U = \{(\mathbf{u}_j, \pi_j)\}_{j=1}^m$ with $m \leq 3$.

5 Daily Feed Algorithm

5.1 Purpose

The original recommendation algorithm is now the algorithm behind the Daily Feed feature. It generates a top-20 personalized feed from the multi-centroid user profile. The objective is to return papers that match the user’s interests, reward timely preprints, and avoid collapsing the feed into one near-duplicate local cluster.

5.2 Cluster selection

For each user centroid $\mathbf{u}_j$, cluster relevance is $C_c^\top \mathbf{u}_j$. The diversity index controls the number of nearby clusters searched:

$$B_{\text{feed}}(\delta) = \lceil 2 + 3\delta \rceil.$$

The selected feed clusters are the union of top-ranked clusters contributed by the user threads:

$$\mathcal{C}_{\text{feed}} = \bigcup_{j=1}^m \text{TopB} \left(\{C_c^\top \mathbf{u}_j\}_{c=1}^{K_c}, B_j \right),$$

where the budgets B_j are allocated from $B_{\text{feed}}(\delta)$ so that active threads receive local neighborhoods when possible.

5.3 Candidate pool and scoring

The candidate pool is

$$\mathcal{P}_0 = \{p : z_p \in \mathcal{C}_{\text{feed}}\} \setminus \mathcal{S}_{\text{seen}},$$

where $\mathcal{S}_{\text{seen}}$ is the set of papers already shown to the user. User similarity is the best match over user threads:

$$s_u(p) = \max_{1 \leq j \leq m} \mathbf{u}_j^\top \mathbf{e}_p.$$

For paper age a_p in days, feed recency is

$$s_r(p) = \exp\left(-\frac{a_p}{30}\right).$$

The Daily Feed score is

$$S_{\text{feed}}(p) = s_u(p) + 0.25s_r(p).$$

The system keeps a pre-finalization pool, typically $M_{\text{feed}} \in [100, 300]$, before diversity filtering.

5.4 Final top-20 diversification

The displayed feed contains $K = 20$ papers. For candidate p , its nearest user thread is

$$t(p) = \arg \max_{1 \leq j \leq m} \mathbf{u}_j^\top \mathbf{e}_p.$$

Candidates are processed in descending $S_{\text{feed}}(p)$ order. The diversification layer controls repeated k-means clusters and encourages thread coverage, especially when δ is high. The exact cap can be tuned, but the invariant is that the final feed should not be dominated by one dense embedding neighborhood or one user thread.

6 Personalized Query Search Algorithm

6.1 Purpose

Personalized Query Search is the search bar above the Daily Feed. Unlike Daily Feed, Query Search is query-centered: explicit query relevance is the dominant signal. The user profile is used as a personalization prior and a retrieval expansion mechanism, not as a replacement for query intent.

6.2 Query expansion and embedding

For raw query q , construct expanded scientific retrieval text $\text{expand}(q)$ and embed it:

$$\mathbf{q} = \text{normalize}(\text{Embed}(\text{expand}(q))).$$

6.3 Candidate retrieval

Query-centered clusters are

$$\mathcal{C}_q = \text{TopB}\left(\{C_c^\top \mathbf{q}\}_{c=1}^{K_c}, B_q\right), \quad B_q \in [8, 12].$$

User-centered cluster relevance is

$$r_c = \max_{1 \leq j \leq m} C_c^\top \mathbf{u}_j,$$

and user-centered clusters are

$$\mathcal{C}_u = \text{TopB}\left(\{r_c\}_{c=1}^{K_c}, B_u\right), \quad B_u = \lceil 2 + 4\delta \rceil.$$

The searched cluster set and candidate pool are

$$\mathcal{C} = \mathcal{C}_q \cup \mathcal{C}_u, \quad \mathcal{P} = \{p : z_p \in \mathcal{C}\} \setminus \mathcal{S}_{\text{seen}}.$$

The query-search pre-reranking pool is intentionally larger than the feed pool, typically $M \in \{500, 1000\}$.

6.4 Reranking components

The four component scores are:

$$\begin{aligned} s_q(p) &= \mathbf{q}^\top \mathbf{e}_p, \\ s_u(p) &= \max_{1 \leq j \leq m} \left(\mathbf{u}_j^\top \mathbf{e}_p + \beta \log(\pi_j + \varepsilon) \right), \quad \beta = 0.05, \\ s_r(p) &= \exp \left(-\frac{a_p}{45} \right), \\ s_\ell(p) &= \ell_p, \end{aligned}$$

where s_q measures query relevance, s_u measures personalized compatibility with a thread-weight adjustment, s_r is a softer recency bonus than Daily Feed, and s_ℓ is an optional lexical score such as keyword overlap or BM25.

For diagnostics, the paper’s matched user thread is

$$t(p) = \arg \max_{1 \leq j \leq m} \left(\mathbf{u}_j^\top \mathbf{e}_p + \beta \log(\pi_j + \varepsilon) \right).$$

Each component is normalized over the candidate set:

$$\text{Norm}_{\mathcal{P}}(x_p) = \frac{x_p - \mu_{\mathcal{P}}(x)}{\sigma_{\mathcal{P}}(x) + \eta},$$

where $\eta > 0$ prevents division by zero. The final score is

$$S(p \mid q, U) = 0.60 \text{Norm}_{\mathcal{P}}(s_q(p)) + 0.25 \text{Norm}_{\mathcal{P}}(s_u(p)) + 0.10 \text{Norm}_{\mathcal{P}}(s_r(p)) + 0.05 \text{Norm}_{\mathcal{P}}(s_\ell(p)).$$

Post-ranking filters remove seen papers, optionally cap repeated near-duplicate clusters, and return the top displayed results. Diversity is lighter than in Daily Feed because the query intent should remain primary.

7 Evaluation Experiment Design

7.1 Evaluation goals

The evaluation asks four questions:

1. Does Personalized Query Search outperform a query-only baseline on expected-use queries?
2. Does Query Search still respect query intent on stress-test queries that are weakly aligned with the user’s profile?
3. Does the Daily Feed benefit from multi-centroid initialization and explicit diversity filtering?
4. Does increasing the diversity index improve coverage and reduce redundancy without causing an unacceptable relevance drop?

7.2 Paper-level scores

All headline metrics use paper-level relevance scores on a $[0, 2]$ scale. For Query Search, the judge assigns

$$q_i, u_i, s_i \in \{0, 1, 2\},$$

where q_i is query relevance, u_i is user-interest relevance, and s_i is usefulness. The normal Query Search paper score is

$$r_i^{\text{query}} = 0.60q_i + 0.30u_i + 0.10s_i.$$

For Daily Feed, the judge assigns

$$u_i, s_i, f_i \in \{0, 1, 2\},$$

where u_i is user-interest relevance, s_i is usefulness, and f_i is freshness or timeliness. The Daily Feed paper score is

$$r_i^{\text{feed}} = 0.70u_i + 0.20s_i + 0.10f_i.$$

For query-profile mismatch stress tests, we also report a query-dominant diagnostic score

$$r_i^{\text{stress}} = 0.85q_i + 0.15s_i.$$

This stress score is diagnostic rather than the main Query Search headline score.

7.3 Aggregate relevance metrics

For a ranked list of $K = 20$ papers with paper-level scores $r_1, \dots, r_{20} \in [0, 2]$, define

$$\text{Strict Precision@20} = \frac{1}{20} \sum_{i=1}^{20} \mathbb{I}[r_i \geq 1.5],$$

$$\text{Soft Precision@20} = \frac{1}{20} \sum_{i=1}^{20} \mathbb{I}[r_i \geq 0.8],$$

$$\text{Mean Relevance@20} = \frac{1}{20} \sum_{i=1}^{20} \frac{r_i}{2}.$$

Ranking quality is measured by

$$\text{DCG@20} = \sum_{i=1}^{20} \frac{2^{r_i} - 1}{\log_2(i + 1)}, \quad \text{NDCG@20} = \frac{\text{DCG@20}}{\text{IDCG@20}},$$

with NDCG@20 defined as zero when all relevance scores are zero.

7.4 Daily Feed diversity metrics

For each returned feed paper, assign it to its nearest user thread:

$$t_i = \arg \max_{1 \leq j \leq m} \mathbf{e}_i^\top \mathbf{u}_j.$$

With relevance threshold $\tau = 1.0$, Thread Coverage@20 is

$$\text{Thread Coverage@20} = \frac{\left| \left\{ j : \exists i \leq 20 \text{ such that } t_i = j \text{ and } r_i^{\text{feed}} \geq \tau \right\} \right|}{m}.$$

Redundancy@20 is average pairwise embedding similarity:

$$\text{Redundancy@20} = \frac{2}{20(20-1)} \sum_{1 \leq i < j \leq 20} \mathbf{e}_i^\top \mathbf{e}_j.$$

A good diversity-index behavior increases Thread Coverage@20 and decreases Redundancy@20 as δ increases, while keeping Mean Relevance@20 reasonably stable.

7.5 Query Search evaluation

Query Search is evaluated on two groups of cases:

1. **Expected-use queries:** queries related to the user profile that refine one of the user’s existing interests.
2. **Stress-test queries:** novel, interdisciplinary, or weakly profile-aligned queries that test whether explicit query intent remains dominant.

The main baseline is query-only retrieval and reranking:

$$S_{\text{query only}}(p) = \lambda_q \text{Norm}(s_q(p)) + \lambda_r \text{Norm}(s_r(p)) + \lambda_\ell \text{Norm}(s_\ell(p)),$$

with no user-profile component. The personalized algorithm should improve expected-use performance while remaining competitive on stress tests.

7.6 Daily Feed evaluation variants

Daily Feed evaluation compares three variants:

1. **Variant A: Single-vector average baseline.** Average all onboarding seed vectors into one normalized user vector, retrieve by cosine similarity, and optionally include the same recency bonus.
2. **Variant B: Multi-centroid profile without diversity filter.** Use threshold-based initialization and max similarity over user centroids, but disable explicit thread coverage and redundancy controls.
3. **Variant C: Full Daily Feed algorithm.** Use threshold-based initialization, recency-aware reranking, and diversity-index behavior.

The diversity sweep evaluates $\delta \in \{0.0, 0.5, 1.0\}$ and reports relevance/diversity tradeoffs.

7.7 Recommended plots and reported artifacts

The final report should include:

- a headline metrics table for each feature and variant;
- Query Search comparison: personalized vs query-only, separated into expected-use and stress-test cases;
- Daily Feed variant comparison across Variants A, B, and C;
- diversity-index sweep plots for Thread Coverage@20, Redundancy@20, and Mean Relevance@20;
- relevance-by-rank curves for visualizing whether relevant papers concentrate near the top;
- qualitative examples of returned papers with judge explanations.

8 Implementation Invariants

1. All vectors used in retrieval and scoring are L2-normalized.
2. MiniBatchKMeans clusters are used as a spatial index, not as interpretable topics.
3. Category centroids and concept embeddings are onboarding anchors, not retrieval clusters.
4. User initialization uses threshold-based agglomerative grouping with $\tau_{\text{merge}} = 0.05$, $m \leq 3$, and core split power 0.6.
5. Broad support seeds can shape final centroids but should not easily create standalone threads.
6. Daily Feed and Query Search share embeddings and user profiles but optimize different objectives.
7. Daily Feed returns 20 papers and must be evaluated with both relevance and diversity metrics.
8. Query Search gives primary weight to explicit query relevance and uses the user profile as a personalization prior.
9. Seen-paper filtering is applied before display unless explicitly disabled for diagnostics.
10. Evaluation must include baselines or ablations, because absolute metrics alone do not show which algorithmic components matter.

9 Presentation-Level Summary

For a five-minute project presentation, the complete story is:

1. Folio solves research discovery by combining a daily personalized feed with profile-aware query search.
2. The central representation is a multi-centroid user profile, initialized from arXiv tags, concept tags, and free text.
3. The profile is built using tuned threshold-based agglomerative grouping rather than forcing small-seed k-means.
4. Daily Feed uses user-centered retrieval, recency reranking, and diversity control to return 20 papers.
5. Query Search combines query-centered clusters, user-centered clusters, and a normalized four-component reranking score.
6. Evaluation reports top-20 relevance, ranking quality, thread coverage, redundancy, and baseline comparisons.