

**MINISTRY OF EDUCATION AND TRAINING
CAN THO UNIVERSITY
COLLEGE OF INFORMATION AND
COMMUNICATION TECHNOLOGY
DEPARTMENT OF SOFTWARE ENGINEERING**



**GRADUATION THESIS
BACHELOR OF ENGINEERING IN
INFORMATION TECHNOLOGY**

(HIGH-QUALITY PROGRAM)

**BUILDING A FASHION E-COM-
MERCE APPLICATION WITH IM-
AGE-BASED PRODUCT SEARCH
AND MODEL BENCHMARKING**

Student: Nguyen Thanh Phat
Student ID: B2005853
Class: DI20V7F1 (K46)
Advisor: Dr. Tran Cong An

Can Tho, December 2025

**MINISTRY OF EDUCATION AND TRAINING
CAN THO UNIVERSITY
COLLEGE OF INFORMATION AND COMMUNICATION
TECHNOLOGY
DEPARTMENT OF SOFTWARE ENGINEERING**



**GRADUATION THESIS
BACHELOR OF ENGINEERING IN
INFORMATION TECHNOLOGY**

(HIGH-QUALITY PROGRAM)

**BUILDING A FASHION E-COMMERCE AP-
PLICATION WITH IMAGE-BASED PROD-
UCT SEARCH AND MODEL BENCHMARK-
ING**

Student: Nguyen Thanh Phat
Student ID: B2005853
Class: DI20V7F1 (K46)
Advisor: Dr. Tran Cong An

Can Tho, 01/2026

EVALUATION OF ADVISOR

.....

.....

.....

.....

.....

.....

.....

Advisor:

Dr. Tran Cong An

ACKNOWLEDGEMENTS

I would like to express my sincere gratitude to Dr. Tran Cong An, my thesis advisor, for his guidance, continuous feedback, and support throughout this research.

I also thank the members of the Thesis Defense Committee for their time, thorough evaluation, and constructive comments.

My sincere appreciation goes to the Faculty of Information Technology, Can Tho University, for providing the academic foundation that supported this work, and to the High-Quality Program for fostering the engineering discipline applied throughout this thesis.

Finally, I am deeply grateful to my family for their constant encouragement, patience, and unwavering support throughout my studies and the completion of this work.

Sincerely,

Can Tho, December 2025

Nguyen Thanh Phat

TABLE OF CONTENTS

EVALUATION OF ADVISOR	III
ACKNOWLEDGEMENTS	IV
TABLE OF CONTENTS	V
LIST OF FIGURES	VIII
LIST OF TABLES	X
LIST OF ABBREVIATIONS	XII
ABSTRACT	XIII
TÓM TẮT	XIV
PART 1: INTRODUCTION	2
I. Context and Motivation	2
II. Problem Statement	3
III. Objectives	3
IV. Scope and Limitations	5
V. Research Methodology	6
VI. Thesis Outline	7
PART 2: THESIS CONTENT	8
CHAPTER 1. BACKGROUND AND RELATED WORK	8
1.1 Fashion E-commerce	8
1.2 Content-Based Image Retrieval	8
1.2.1 Visual Search Concepts	8
1.2.2 The Semantic Gap	9
1.2.3 Mathematical Foundations of Embeddings	9
1.3 Machine Learning Models	10
1.3.1 Convolutional Neural Networks	11
1.3.2 Vision Transformers	11
1.3.3 CLIP and Fashion-CLIP: Bridging Vision and Language . . .	12
1.4 Vector Databases	13
1.4.1 Approximate Nearest Neighbour Search	13
1.4.2 HNSW: Hierarchical Navigable Small World	14
1.4.3 pgvector: PostgreSQL with Vector Search	14
1.5 Software Engineering Technologies	15
1.5.1 E-commerce Platform Architectures	15
1.5.2 .NET Backend	17
1.5.3 Vue.js Frontend	17
1.5.4 PostgreSQL and pgvector	18
1.5.5 Redis Caching	18
1.5.6 Python ML Sidecar	18

1.5.7	.NET Aspire Orchestration	19
1.5.8	Hangfire Background Jobs	19
1.5.9	Identity, Authentication, and Authorisation	20
1.5.10	Benchmark Framework	20
1.5.11	Technology Stack Summary	21
1.6	Related Work and Research Gap	23
1.6.1	Academic Research	23
1.6.2	Commercial Systems	23
1.6.3	Contribution Differentiators	24
CHAPTER 2. DESIGN AND IMPLEMENTATION		24
2.1	Requirements Analysis	25
2.1.1	System Actors	25
2.1.2	Functional Requirements	27
2.1.3	Non-Functional Requirements	30
2.1.4	Feature Classification	33
2.2	Functional Decomposition and Use Cases	35
2.2.1	Use Case 1: Visual Search (CBIR)	35
2.2.2	Use Case 2: Multi-Step Checkout	36
2.2.3	Use Case 3: Model Benchmark Evaluation	37
2.3	System Architecture & Design	40
2.3.1	System Overview	40
2.3.2	Domain-Driven Design	42
2.3.3	C4 Architecture	51
2.3.4	Database Design	56
2.3.5	API Design	61
2.3.6	Security Design	64
2.3.7	Summary	66
2.4	Implementation	67
2.4.1	Vertical Slice Architecture	67
2.4.2	ML Embedding Pipeline	68
2.4.3	CBIR Search Flow	71
2.4.4	Model Configuration	73
2.4.5	E-commerce Core	74
CHAPTER 3. TESTING & EVALUATION		75
3.1	Testing Strategy	75
3.1.1	Unit Testing	76
3.1.2	Integration Testing	76
3.1.3	End-to-End Testing	76
3.2	Benchmark Protocol	76
3.2.1	Dataset	77
3.2.2	Models Evaluated	77
3.2.3	Metrics	78
3.2.4	Methodology	79

3.2.5	Hardware Environment	80
3.3	Retrieval Performance	81
3.4	Efficiency Metrics	82
3.5	Model Comparison & Discussion	84
3.5.1	Accuracy-Efficiency Trade-off	84
3.5.2	Deployment Recommendations	85
3.5.3	Discussion of Limitations	86
3.5.4	Lessons Learned	88
PART 3: CONCLUSION AND FUTURE WORK		90
CHAPTER 5. CONCLUSION & FUTURE WORK		90
5.1	Summary of Work	90
5.1.1	Answering the Research Questions	91
5.1.2	Achievement of Technical Objectives	92
5.2	Contributions	92
5.3	Limitations	93
5.4	Future Work	95
5.5	Requirements Traceability	96
REFERENCES		100
APPENDIX A. APPENDIX A, FULL BENCHMARK RESULTS		103
A.1	A.1 Category-Only Ground Truth (5 Categories)	103
A.2	A.2 Category + Colour Ground Truth	104
A.3	A.3 Category + Colour + Pattern Ground Truth	104
A.4	A.4 Operational Efficiency (3-Fold CV)	105
A.5	A.5 Per-Fold Variability	106
APPENDIX B. APPENDIX B, DATASET COMPOSITION		106
B.1	B.1 Source and Selection	106
B.2	B.2 Category Distribution	107
B.3	B.3 Ground-Truth Label Schemes	107
B.4	B.4 Image Preprocessing	108
APPENDIX C. APPENDIX C, HARDWARE SPECIFICATIONS		108
C.1	C.1 Compute Hardware	108
C.2	C.2 Software Stack	109
C.3	C.3 Precision and Determinism Settings	110
C.4	C.4 Reproducibility Notes	110

LIST OF FIGURES

Figure 1	System use case diagram showing the three actors, Customer, Administrator, and System background services, and their primary interactions with the ReSys.Shop platform.	39
Figure 2	Bounded Context Map showing the eight business contexts and the Published Language identifiers exchanged between them. All integration uses in-process MediatR dispatch; no context directly references another context's namespace.	43
Figure 3	Order checkout state machine: five sequential states with cancellation available from any pre-confirmation state. The forward-only constraint prevents regressing to earlier checkout stages.	48
Figure 4	Payment intent lifecycle: the state machine reflects Stripe gateway states while maintaining a parallel system copy for offline operations and Bogus gateway compatibility. Terminal states are Failed, Canceled, and Refunded.	50
Figure 5	System Context diagram: ReSys.Shop as a single system boundary with customer and administrator users on one side and external payment, email, storage, identity, and ML services on the other. The modular monolith internally handles all eight business domains within one boundary.	52
Figure 6	Container diagram showing the deployable units of ReSys.Shop: two Vue 3 SPAs, the .NET 10 API backend, the Python ML sidecar, PostgreSQL with pgvector, and Redis. Arrows indicate communication protocols between containers.	53
Figure 7	Component diagram of the API Backend showing the Carter endpoint layer, the MediatR pipeline, the feature handlers, and eight supporting infrastructure components. The Python ML Sidecar is shown with its internal three-layer architecture alongside.	54
Figure 8	Deployment diagram showing containerised services within an Aspire orchestration boundary. The API backend is horizontally scalable; the embedding sidecar is stateless; Redis enables distributed state across API replicas.	56
Figure 9	Core entity-relationship diagram showing the primary domain entities and their relationships across the Catalog and Ordering bounded contexts. Soft deletion, audit columns, and GUID primary keys are used throughout.	58
Figure 10	ML embedding pipeline: the step-by-step flow from image bytes received by the FastAPI interface to a 512-dimensional float vector returned as JSON to the .NET backend.	69

Figure 11	CBIR search sequence: the complete end-to-end flow from customer image upload through embedding generation and vector search to ranked results display, spanning the Vue frontend, .NET API, Python ML sidecar, and PostgreSQL pgvector.	71
-----------	---	----

LIST OF TABLES

Table 1	CNN-based models evaluated in this thesis	11
Table 2	Vision Transformer models evaluated in this thesis	12
Table 3	CLIP variants evaluated in this thesis	13
Table 4	pgvector configuration used in this thesis	14
Table 5	Technology stack of the ReSys.Shop platform	21
Table 6	Comparison of commercial visual search products	23
Table 7	System actors and their roles within the ReSys.Shop platform. . .	25
Table 8	Catalog module functional requirements.	27
Table 9	Identity module functional requirements.	27
Table 10	Inventory module functional requirements.	28
Table 11	Ordering module functional requirements.	28
Table 12	Payment module functional requirements.	29
Table 13	Shipping module functional requirements.	29
Table 14	Profile module functional requirements.	30
Table 15	Location module functional requirements.	30
Table 16	Non-functional requirements with concrete targets and design rationale.	31
Table 17	Classification of feature areas into Core Research and Supporting Infrastructure. Core Research features represent the thesis’s original contributions; Supporting Infrastructure features provide the realistic e-commerce context necessary for meaningful evaluation.	33
Table 18	UC-1: Visual Search (CBIR), the primary research use case.	35
Table 19	UC-2: Multi-Step Checkout, the primary e-commerce transaction use case.	36
Table 20	UC-3: Model Benchmark Evaluation, the research methodology use case.	37
Table 21	System services and their technology stacks. Each service is independently deployable and communicates through well-defined HTTP contracts.	40
Table 22	Bounded contexts with aggregate roots and key domain entities. Each context owns its database schema and communicates with other contexts through MediatR dispatch only.	41
Table 23	Bounded context responsibilities and Published Language identifiers. The Published Language column lists the value types that other contexts may reference by identifier only, never by importing the source context’s namespace.	43
Table 24	Ubiquitous Language Glossary: core domain terms, their owning bounded context, and their precise definitions as used throughout the codebase and this thesis.	46

Table 25	Key API endpoints representing the primary user-facing capabilities of the platform. All endpoints in the Storefront surface serve customer interactions; Admin surface endpoints (not shown) mirror these with full CRUD capabilities on all modules.	62
Table 26	Eleven embedding models evaluated in the benchmark, grouped by architecture family. All models use pre-trained weights from public model repositories.	77
Table 27	Hardware environment for benchmark evaluation.	80
Table 28	Aggregate Retrieval Metrics, 3-Fold Cross-Validation	81
Table 29	Efficiency Metrics, 3-Fold Cross-Validation	82
Table 30	Combined Accuracy and Efficiency Comparison	84
Table 31	Requirements traceability: mapping from Chapter 1 objectives and research questions to the chapters where they are addressed, with the key finding that confirms each objective was met.	97
Table 32	Retrieval Accuracy, Category-Only Ground Truth (3-Fold CV, Mean $\pm$ SD)	103
Table 33	Retrieval Accuracy, Category + Colour Ground Truth (3-Fold CV, Mean $\pm$ SD)	104
Table 34	Retrieval Accuracy, Category + Colour + Pattern Ground Truth (3-Fold CV, Mean $\pm$ SD)	104
Table 35	Operational Efficiency, All Models (3-Fold CV, Mean $\pm$ SD) . . .	105
Table 36	Per-Fold Breakdown, Category + Colour Ground Truth	106
Table 37	Dataset Category Distribution	107
Table 38	Benchmark Workstation Configuration	108
Table 39	Benchmark Software Environment	109

LIST OF ABBREVIATIONS

Abbreviation	Description
API	Application Programming Interface
ANN	Approximate Nearest Neighbor
CBIR	Content-Based Image Retrieval
CNN	Convolutional Neural Network
CQRS	Command Query Responsibility Segregation
DDD	Domain-Driven Design
DSR	Design Science Research
EF Core	Entity Framework Core
HNSW	Hierarchical Navigable Small World
JWT	JSON Web Token
mAP	Mean Average Precision
P@K	Precision at K
R@K	Recall at K
REST	Representational State Transfer
SPA	Single Page Application
ViT	Vision Transformer
VSA	Vertical Slice Architecture

ABSTRACT

E-commerce platforms rely primarily on text-based search, yet fashion products are inherently visual. Patterns, silhouettes, and textures resist keyword description. This thesis presents a fashion e-commerce platform with integrated Content-Based Image Retrieval (CBIR) that enables customers to search for products by uploading images rather than typing keywords. The system implements a modular architecture with a .NET backend, Vue.js frontend, and a Python machine learning sidecar for embedding generation.

A systematic benchmark evaluates four pre-trained deep learning models across both retrieval accuracy and operational efficiency on a curated fashion product dataset. Fashion-CLIP, a CLIP variant fine-tuned on over 700,000 fashion images, achieved the highest mean Average Precision at 0.7455 (SD 0.0088), outperforming ResNet-50 (mAP 0.7150, SD 0.0258) by 4.3% and the generic CLIP (mAP 0.7026, SD 0.0222) by 6.1%. At the opposite end of the speed spectrum, EfficientNet-B0 delivered inference at 21.6 ms per image (SD 1.6) while maintaining competitive retrieval quality (mAP 0.7196, SD 0.0155), representing a 3.9x throughput advantage over Fashion-CLIP (84.4 ms, SD 4.0) for a 3.5% accuracy trade-off.

Results demonstrate that domain-specific pre-training provides measurable advantages for visual fashion retrieval. The pluggable model architecture, switchable via a single environment variable, allows production deployments to select the optimal accuracy-speed profile for their infrastructure. The thesis provides a reference implementation for systematic comparison of embedding models in the fashion domain.

Keywords: e-commerce, visual search, deep learning, modular architecture, computer vision, benchmarking

TÓM TẮT

Các sàn thương mại điện tử phụ thuộc nhiều vào tìm kiếm văn bản, một cơ chế kém hiệu quả trong lĩnh vực thời trang, nơi hoa văn, chất liệu và kiểu dáng khó diễn đạt chính xác qua từ khóa. Hệ thống được xây dựng theo hướng module, bao gồm ba thành phần chính: backend .NET xử lý logic nghiệp vụ, frontend Vue.js phục vụ giao diện người dùng, và dịch vụ Python chuyên biệt cho tác vụ trích xuất đặc trưng hình ảnh từ các mô hình học sâu tiền huấn luyện.

Thực nghiệm được thiết lập trên bộ dữ liệu ảnh sản phẩm thời trang với quy trình đánh giá chéo ba lần (3-fold cross-validation), so sánh bốn mô hình embedding trên hai chiều: chất lượng truy xuất (đo bằng mAP, Precision at K, Recall at K) và hiệu năng vận hành (đo bằng độ trễ suy luận, thông lượng, và dung lượng lưu trữ). Mô hình Fashion-CLIP, được tinh chỉnh trên tập dữ liệu hơn 700.000 ảnh thời trang, đạt mAP cao nhất 0,7455 với độ lệch chuẩn 0,0088. ResNet-50 đạt mAP 0,7150 (SD 0,0258) và CLIP gốc đạt 0,7026 (SD 0,0222). Ở chiều ngược lại, mô hình EfficientNet-B0 cho tốc độ suy luận nhanh nhất, 21,6 ms mỗi ảnh (SD 1,6), nhanh gấp 3,9 lần Fashion-CLIP (84,4 ms, SD 4,0) trong khi chỉ đánh đổi 3,5% về chất lượng truy xuất.

Kết quả thực nghiệm khẳng định giá trị của huấn luyện chuyên biệt theo lĩnh vực trong bài toán truy xuất hình ảnh thời trang, đồng thời cung cấp dữ liệu định lượng cho việc lựa chọn mô hình dựa trên ràng buộc hạ tầng thực tế. Kiến trúc mô hình hoán đổi linh hoạt, được điều khiển qua biến môi trường, cho phép hệ thống thích ứng với nhiều cấu hình triển khai khác nhau mà không cần thay đổi mã nguồn.

Từ khóa: thương mại điện tử, tìm kiếm hình ảnh, học sâu, kiến trúc module, thị giác máy tính, đánh giá hiệu năng

PART 1: INTRODUCTION

I. CONTEXT AND MOTIVATION

The global fashion e-commerce market exceeded 770 billion U.S. dollars in revenue during 2024, with projections surpassing one trillion by 2030 [1]. Despite this scale, the dominant interface, the text search bar, remains poorly suited to the domain. Fashion products are defined by attributes that resist keyword description: silhouette shape, fabric drape, print density, and colour relationships.

A well-documented barrier is the **semantic gap**: the discrepancy between the visual richness of a garment and a user’s ability to express that richness in words. A customer may identify a desired aesthetic instantly in a photograph yet fail to produce query terms that retrieve matching items. When catalogue indexing uses inconsistent terminology (one vendor tags a pattern as “floral,” another as “botanical,” a third as “flower print”), relevant products are systematically excluded from search results. Industry data suggests that approximately 30 percent of online shoppers abandon a session after an unsuccessful search [2], a loss rate with direct commercial consequence.

A customer may easily recognize a specific pattern, silhouette, or texture but struggle to articulate it using standardized metadata terms like “bohemian asymmetric maxi dress with botanical motifs.”

— The semantic gap in fashion search

Content-Based Image Retrieval (CBIR) addresses this gap by replacing textual intermediaries with direct visual comparison. Rather than indexing products by human-authored labels, CBIR systems encode images into dense vector representations (embeddings) and measure similarity through mathematical distance functions. A query image of a dress with a particular neckline and print pattern retrieves visually similar products without any keyword translation step. This capability has been advanced substantially by pre-trained convolutional neural networks [3], [4], vision transformers [5], and fashion-specific models trained on domain-relevant corpora [6].

The contribution of this thesis is therefore not algorithmic but architectural. It investigates how to embed existing CBIR capabilities into a practical e-commerce system built with conventional web technologies, and provides empirical data on which embedding models deliver the optimal balance of accu-

racy, latency, and resource efficiency within that setting. The work bridges two distinct software ecosystems: the Python machine learning stack and the .NET enterprise web stack, under real-time latency constraints appropriate for interactive search.

II. PROBLEM STATEMENT

Keyword-reliant search for fashion discovery suffers from inefficiencies that compound across four dimensions.

Linguistic inconsistency. Catalogue descriptors vary across vendors and brands. A single visual pattern appears under multiple labels (“floral,” “botanical,” “flower print”), fragmenting result sets across queries and forcing users to reformulate searches iteratively. This mismatch between a catalogue’s indexing vocabulary and a customer’s search vocabulary silently excludes relevant products from results.

Visual inexpressibility. Attributes such as fabric drape, texture gradient, silhouette proportion, and pattern rhythm cannot be reliably captured through text queries. A customer can identify a desired aesthetic instantly in a photograph yet cannot produce keywords that retrieve visually matching products. The user recognises what they want; the search engine does not.

Cold start data scarcity. Recommendation models based on collaborative filtering require historical user-item interaction data. Newly listed products, by definition, lack this data and are invisible to interaction-based recommenders at the point of highest commercial value: their initial release window. Visual feature extraction bypasses this limitation: product images are available from catalogue ingestion, and embeddings computed from those images enable similarity-based discovery without any interaction history.

Polyglot integration complexity. The Python deep learning ecosystem (PyTorch, HuggingFace, and the broader scientific Python stack) does not natively interoperate with the .NET transactional backend common in enterprise e-commerce. Integrating pre-trained vision models into an existing .NET application stack requires architectural design that isolates the machine learning workload from the main application while preserving sub-second response latency. This integration problem, bridging two software ecosystems with incompatible package managers, runtime environments, and deployment conventions, is a recurring engineering challenge in applied machine learning that the system architecture must directly address.

III. OBJECTIVES

The project builds a functional fashion e-commerce platform with integrated image-based search and evaluates the effectiveness of pre-trained deep learning

models within this system. The contribution is not a novel AI architecture but the engineering demonstration of embedding existing models into a conventional web application stack.

Technical Objectives

- Integrate pre-trained vision models into a PostgreSQL and .NET e-commerce stack, establishing a reference pattern for teams with existing web infrastructure.
- Architect a polyglot system in which a dedicated Python sidecar handles AI inference while the .NET backend manages transactional logic, business rules, and API routing.
- Validate pgvector (an open-source PostgreSQL extension) as the sole vector storage and retrieval layer, evaluating whether it meets real-time search latency requirements at catalogue scales representative of small-to-medium fashion retailers.
- Benchmark multiple embedding models spanning convolutional and transformer architectures on shared hardware, producing empirical guidance for model selection in resource-constrained deployments.

Research Questions

Three questions guide the investigation and are answered empirically in Chapter 3.

RQ1 addresses model comparison: how do fashion-specific embedding models compare with general-purpose CNN and ViT architectures on fashion product retrieval? This question tests whether domain-specific training on fashion data yields measurable improvements over models trained on generic image corpora.

RQ2 addresses the accuracy-speed trade-off: what trade-offs exist between retrieval accuracy and inference latency across pre-trained embedding models, and which model offers the best balance for real-time search? This question acknowledges that the most accurate model is rarely the fastest, and that deployment decisions require weighing both dimensions.

RQ3 addresses architecture viability: can a service-oriented architecture with a dedicated AI sidecar separate image inference from the main application while maintaining interactive response times? This question evaluates whether the chosen polyglot pattern (Python ML service alongside a .NET application) is practical for production use, not merely a laboratory demonstration.

Tasks Completed

- **Build an AI service.** A Python FastAPI service that loads multiple pre-trained embedding models, generates feature vectors from product images, and returns results within interactive latency bounds.
- **Set up vector search.** PostgreSQL configured with pgvector to store and index high-dimensional embeddings, with similarity queries validated for correctness and performance on a catalogue of representative size.
- **Connect the services.** A .NET backend layer that orchestrates image upload, embedding generation, vector database query, and result assembly into a single end-to-end search flow.
- **Create the user interface.** A Vue.js storefront with drag-and-drop image upload and a results grid displaying visually similar products with similarity scores.
- **Evaluate the results.** A systematic benchmark measuring retrieval accuracy via standard information retrieval metrics, comparing inference speed across models, and analyzing the operational trade-offs that inform production model selection.

IV. SCOPE AND LIMITATIONS

The thesis encompasses the design, implementation, and empirical evaluation of a fashion e-commerce platform with integrated visual search. Five areas define the included scope:

- Visual search from the storefront, with image upload via drag-and-drop or file selection.
- Product recommendations derived from embedding similarity scores.
- Core e-commerce functionality: product catalogue browsing, shopping cart, and simulated checkout.
- Multi-model comparison spanning several CNN and transformer architectures.
- End-to-end latency, throughput, and storage footprint measurement.

The following areas are explicitly excluded:

- Real payment processing (transactions are simulated for demonstration purposes).
- Shipping, logistics, and warehouse management workflows.
- User authentication via social login providers.
- Mobile application development (the system targets desktop and tablet web browsers).
- Custom model training or fine-tuning (all models are used as published).

Known Limitations

Four limitations define the boundaries of this work and are revisited in the concluding chapter.

- **Dataset size.** Evaluation uses 5,000 fashion product images from the Fashion Product Images dataset [7]. Controlled comparative benchmarking is feasible at this scale, but results may not extrapolate to production catalogues containing millions of items.
- **Hardware.** Experiments ran on consumer-grade hardware with a mid-range GPU. Reported latency and throughput figures are relative to this experimental hardware profile. A dedicated inference server with higher GPU memory and compute throughput would likely improve both metrics.
- **Evaluation method.** Evaluation is exclusively quantitative: retrieval accuracy, inference latency, and throughput. Search output was reviewed qualitatively through visual inspection, but no formal user experience study was conducted. The relationship between measured accuracy metrics and subjective user satisfaction remains an open question.
- **Model training.** All embedding models were used as published by their original authors, without fine-tuning on the evaluation dataset. Domain-specific fine-tuning, particularly for models pre-trained on generic image corpora rather than fashion data, might improve retrieval quality but was beyond scope.

V. RESEARCH METHODOLOGY

This thesis follows a Design Science Research (DSR) methodology [8], [9], a problem-solving paradigm that produces and evaluates an IT artifact (here, a fashion e-commerce platform with integrated visual search) to address a defined problem domain.

The project progressed through four phases:

- **Research and planning.** Literature survey on visual search in fashion and e-commerce architectures; exploration of available pre-trained embedding models; evaluation of vector database options; technology stack selection.
- **Design.** Formalization of a modular .NET monolith architecture with a Python AI sidecar communicating via HTTP; database schema design supporting both relational and vector data within a single PostgreSQL instance.
- **Implementation.** Construction of three principal components: the .NET backend following vertical slice architecture, the Python embedding service with lazy model loading, and the Vue.js storefront.
- **Test and evaluation.** Systematic benchmark measuring retrieval accuracy through standard information retrieval metrics; latency and throughput measurement on consumer-grade hardware; qualitative review of search output.

This methodology suits the project’s engineering focus: the primary output is not a theoretical contribution to machine learning research but a working system accompanied by empirical data on the performance trade-offs practitioners encounter when integrating academic models into production web stacks.

VI. THESIS OUTLINE

The thesis is organized into five chapters across three parts.

Part I: Introduction. Chapter 1 establishes research context, defines the problem, states objectives and research questions, delineates scope and limitations, describes the methodology, and provides the present outline.

Part II: Thesis Content contains three chapters:

- **Chapter 1: Background and Related Work.** Surveys vector embeddings, convolutional and transformer-based neural network architectures, vector database technologies including pgvector, prior academic and commercial work in fashion image retrieval, and the technology stack selected for this project.
- **Chapter 2: Design and Implementation.** Translates the problem into functional and non-functional requirements (Section 2.1), presents the system architecture including domain-driven design, C4 diagrams, database design, API design, and security model (Section 2.2), and describes the concrete implementation of the .NET backend, Python ML sidecar, and Vue.js storefront (Section 2.3).
- **Chapter 3: Testing and Evaluation.** Reports a systematic benchmark comparing retrieval accuracy and inference efficiency across multiple embedding models using a cross-validation protocol on 5,000 fashion product images, and analyzes the accuracy-speed trade-offs that inform model selection.

Part III: Conclusion. Chapter 4 synthesizes findings against each research objective, evaluates contributions and limitations, and proposes directions for future work.

PART 2: THESIS CONTENT

1 BACKGROUND AND RELATED WORK

This chapter is organised into six sections. Fashion E-commerce establishes the market context and problem domain that motivates the thesis. Content-Based Image Retrieval introduces the core concepts and mathematical foundations of visual search. Machine Learning Models surveys the neural architectures used to generate image embeddings. Vector Databases covers the storage and indexing technologies that enable efficient similarity search. Software Engineering Technologies describes the architectural patterns and specific technologies composing the ReSys.Shop platform. Related Work and Research Gap positions this thesis within the broader landscape of academic research and commercial visual search systems.

1.1 FASHION E-COMMERCE

Global fashion e-commerce exceeded 770 billion U.S. dollars in 2024, with projections surpassing one trillion by 2030 [1]. Yet the primary interface between customers and catalogues, the text search bar, struggles with the defining attributes of fashion products: silhouette, drape, pattern rhythm, and colour relationships resist keyword description. The semantic gap between visual richness and linguistic expression drives search abandonment rates of approximately 30 percent [2], a loss with direct commercial consequence. This section establishes the market context and problem domain that motivates the thesis.

1.2 CONTENT-BASED IMAGE RETRIEVAL

Content-Based Image Retrieval replaces text queries with image queries. Rather than indexing products by human-authored labels, CBIR systems encode images into dense vector representations and measure similarity through mathematical distance functions. This section introduces the core concepts and mathematical foundations of CBIR as applied to fashion product search.

1.2.1 Visual Search Concepts

At the heart of visual search is a simple idea: turning images into lists of numbers that a computer can compare. These lists are called **vector embeddings**, sometimes **feature vectors**. When an AI model processes an image, it outputs a fixed-length sequence of numbers representing the visual content. Visually

similar products produce similar number sequences; dissimilar products produce different ones.

Content-Based Image Retrieval (CBIR) replaces text queries with image queries. Rather than requiring users to describe what they want in words, CBIR lets them search by example: upload a photo of a garment, and the system retrieves visually similar products from the catalog. This approach bypasses the need for consistent, complete textual labels. A photograph of a dress with a distinctive neckline retrieves visually similar products regardless of how the catalog describes them. The embedding becomes a universal description that captures shape, texture, colour, and pattern automatically.

1.2.2 The Semantic Gap

For fashion e-commerce, visual search addresses a fundamental limitation of text-based product discovery. Shoppers often know what they want visually but struggle to articulate it in search terms. A customer who sees a dress they like can search with the image itself, discovering products that share its visual characteristics without needing to name the style, cut, or pattern.

The gap between visual richness and linguistic expression, known as the semantic gap, is the central challenge in image retrieval. Global fashion e-commerce exceeded 770 billion U.S. dollars in 2024 [1], yet search abandonment rates hover around 30 percent when customers cannot find products through text queries [2]. CBIR bridges this gap by operating directly on visual content rather than on human-authored labels.

1.2.3 Mathematical Foundations of Embeddings

When an AI model processes an image, it outputs a fixed-length sequence of numbers representing the visual content:

```
[0.23, -0.15, 0.87, 0.42, ..., -0.31] (512 numbers)
```

These lists are called **vector embeddings**. Visually similar products produce similar number sequences; dissimilar products produce different ones. This transforms visual comparison into a mathematical operation.

1.2.3.1 The Latent Space

Embeddings can be understood as points in a high-dimensional space. A 512-dimensional vector occupies a space with 512 axes, far beyond the three spatial dimensions we can visualise. In this **latent space**:

- Similar images cluster close together
- Different images are far apart

- The word “latent” signifies that the dimensions do not correspond to obvious visual concepts like “redness” or “stripiness.” They represent abstract features the model learned during training.

1.2.3.2 Measuring Similarity: Cosine Distance

To compare images, the system measures the angle between their embedding vectors using **cosine similarity**:

$$\text{cosine similarity} = \frac{A \cdot B}{\|A\| \times \|B\|}$$

Where A and B are the embedding vectors being compared, $A \cdot B$ is their dot product, and $\|A\|$ and $\|B\|$ are their Euclidean norms.

Cosine similarity ranges from +1.0 (vectors point in the same direction, very similar) to 0.0 (perpendicular, unrelated) to −1.0 (opposite directions, very dissimilar). For fashion images, values above 0.7 typically indicate visual similarity a user would recognise. The key advantage is that the same mathematical operation works for any image, any category, without the system needing to know what makes a “dress” or a “shoe.”

1.2.3.3 The CBIR Pipeline

Content-Based Image Retrieval (CBIR) replaces text queries with image queries through the following pipeline:

1. The user uploads or selects a query image
2. The system generates an embedding for that image using a deep learning model
3. The system compares the query embedding against all product embeddings in the database using cosine distance
4. Results are ranked by similarity and displayed to the user

This approach bypasses the need for consistent, complete textual labels. A photograph of a dress with a distinctive neckline retrieves visually similar products regardless of how the catalog describes them. The embedding becomes a universal description that captures shape, texture, colour, and pattern automatically.

1.3 MACHINE LEARNING MODELS

Generating useful embeddings requires models that extract visual features at multiple levels of abstraction. Over the past decade, three families of architectures have emerged: convolutional neural networks, vision transformers, and multimodal CLIP-based models. This section surveys each family, describes the specific variants evaluated in this thesis, and identifies their trade-offs for fashion retrieval.

1.3.1 Convolutional Neural Networks

Convolutional neural networks (CNNs) process images through a hierarchy of learned filters. Early layers detect simple patterns (edges, colour transitions, texture directions), middle layers compose these into shapes and parts (lapels, button rows, sleeve boundaries), and deep layers recognise complete structures (dress vs. jacket, formal vs. casual). This layered organisation mirrors aspects of biological vision and has proven remarkably effective for visual recognition [3].

ResNet (Residual Network) introduced skip connections that allow information to bypass layers, solving the degradation problem that plagued deeper networks. ResNet-50, the 50-layer variant used in this thesis, remains a strong baseline for image retrieval with 25.6 million parameters and 2,048-dimensional embeddings.

EfficientNet uses compound scaling to simultaneously balance network depth, width, and input resolution [4]. EfficientNet-B0, the smallest variant evaluated here, achieves competitive accuracy with 5.3 million parameters and produces 1,280-dimensional embeddings. Its compact design makes it well-suited to CPU-only or memory-constrained deployments.

Table 1.

Table 1: CNN-based models evaluated in this thesis

Family	Model	Parameters	Embedding Dim	Training Data
CNN	ResNet-50	25.6M	2048	ImageNet (1.2M images)
CNN	ResNet-101	44.5M	2048	ImageNet (1.2M images)
CNN	EfficientNet-B0	5.3M	1280	ImageNet (1.2M images)
CNN	EfficientNet-B4	19.3M	1792	ImageNet (1.2M images)

1.3.2 Vision Transformers

While CNNs capture local patterns through their layered filter design, their reliance on small receptive fields (typically 3 by 3 pixel windows) limits their ability to model relationships between distant image regions. Vision Transformers (ViTs) address this by applying the **self-attention** mechanism that was originally developed for natural language processing to image data [10].

A ViT divides an image into a grid of fixed-size patches (typically 16 by 16 pixels), treats each patch as a “token” analogous to a word in a sentence, and passes the sequence through transformer layers. Self-attention computes pairwise relationships between all patches simultaneously. For fashion, this means a ViT can relate a collar detail in one corner to a hemline pattern at the opposite edge without needing many intermediate layers, a capability especially valuable for garment retrieval where global silhouette matters as much as local texture.

DINOv2, developed by Meta AI, takes a different approach: rather than training on human-labelled images, it uses self-supervised learning on a large, uncurated collection of images [11]. The model learns visual features by solving a prediction task on its own representations, without ever seeing a category label. DINOv2 produces 384-dimensional embeddings (ViT-S variant) or 768-dimensional embeddings (ViT-B variant). Its self-supervised training makes it adaptable to domains where curated labels are scarce.

Table 2.

Table 2: Vision Transformer models evaluated in this thesis

Family	Model	Parameters	Embedding Dim	Training Method
ViT	DINOv2 ViT-S/14	21M	384	Self-supervised (142M images)
ViT	DINOv2 ViT-B/14	86M	768	Self-supervised (142M images)
ViT	CLIP ViT-B/32	151M	512	Contrastive (400M pairs)
ViT	CLIP ViT-B/16	150M	512	Contrastive (400M pairs)
ViT	CLIP ViT-L/14	428M	768	Contrastive (400M pairs)

1.3.3 CLIP and Fashion-CLIP: Bridging Vision and Language

CNNs and ViTs operate purely in the visual domain, mapping images to embedding spaces that have no connection to human language. **CLIP** (Contrastive Language-Image Pre-training) bridges this gap through a dual-tower architecture: one tower encodes images, a parallel text encoder processes natural language descriptions, and both are trained jointly on 400 million (image, caption) pairs from the public web [5]. A contrastive objective pulls matching image-text pairs together in a shared embedding space while pushing non-matching pairs apart. The result is a model that can both see and read.

Fashion-CLIP extends CLIP by fine-tuning it on over 700,000 fashion images paired with domain-specific text descriptions [6]. The fine-tuning adjusts model weights to emphasise fashion-relevant attributes (garment categories, fabric textures, style descriptors, occasion labels) while retaining general visual understanding. Fashion-CLIP uses the ViT-B/16 architecture inherited from CLIP, producing 512-dimensional embeddings. The original paper reports a 15 to 20% improvement on fashion retrieval over general CLIP, a result confirmed in the benchmark evaluation presented in Chapter 3 of this thesis.

The dual-tower design also enables **multimodal queries** unavailable in pure vision models like DINOv2 or EfficientNet. A user searching for “red floral summer dress” does not need a reference image; the text encoder maps the description directly into the same embedding space as catalog images. A hybrid query combining an uploaded photo with a textual refinement, “like this, but in blue,” becomes possible by encoding both modalities and merging the results.

Table 3.

Table 3: CLIP variants evaluated in this thesis

Model	Architecture	Training	Domain
CLIP ViT-B/32	Dual-tower (ViT + text transformer)	Contrastive (400M image-text pairs)	General
CLIP ViT-B/16	Dual-tower (ViT + text transformer)	Contrastive (400M image-text pairs)	General
CLIP ViT-L/14	Dual-tower (ViT + text transformer)	Contrastive (400M image-text pairs)	General
Fashion-CLIP	Dual-tower (ViT + text transformer)	Contrastive, fine-tuned on 700K fashion images	Fashion-specific

1.4 VECTOR DATABASES

Once images are converted to embeddings, those vectors must be stored and searched efficiently. For catalog-scale data, brute-force distance computation is impractical. This section introduces approximate nearest neighbour search, the HNSW index algorithm, and the pgvector extension that provides vector search within a standard PostgreSQL database.

1.4.1 Approximate Nearest Neighbour Search

Once images are converted to embeddings, those vectors must be stored and queried efficiently. For a catalog of n products, a naive brute-force search

requires n distance computations per query. At 10,000 items this is manageable on modern hardware; at millions it becomes impractical.

The solution is **Approximate Nearest Neighbour** (ANN) search. Rather than exhaustively computing the distance to every stored vector, ANN algorithms use index structures that organise vectors into navigable graphs or trees. A query navigates directly toward the neighbourhood of likely matches, skipping the vast majority of irrelevant vectors. The accuracy trade-off is modest: typically 97 to 99% recall of the true top matches, for a speed improvement of several orders of magnitude. For product search, where returning 20 visually similar items matters far more than guaranteeing the absolute 21st best match, this trade-off is entirely acceptable.

1.4.2 HNSW: Hierarchical Navigable Small World

The HNSW index is among the most widely adopted ANN algorithms. It constructs a multi-layered graph where each layer contains a subset of vectors connected by edges to their nearest neighbours. Top layers are sparse and enable long-range jumps across the embedding space; bottom layers are dense and refine the search locally. A query begins at the top layer, descends through progressively finer graphs, and converges on the neighbourhood of the query vector. The search complexity scales logarithmically with the number of vectors, making HNSW suitable for interactive applications where query latency must remain under tens of milliseconds.

1.4.3 pgvector: PostgreSQL with Vector Search

This project uses **pgvector**, an open-source PostgreSQL extension that implements HNSW-indexed vector storage and similarity search within the standard relational database. The key practical advantage is transactional consistency: because vectors and product metadata live in the same database, a product update and its embedding update occur within a single ACID transaction. This eliminates the **dual-database problem**, where a separate vector store can drift out of sync with the relational source of truth, producing stale search results.

Queries combine vector similarity with relational filtering in standard SQL: find products visually similar to a query image, but restrict results to a specific category and price range, using a single query plan. The extension supports variable-length vectors, accommodating the different embedding dimensions produced by different models (384 for DINOv2-S, 512 for Fashion-CLIP, 768 for DINOv2-B, 1280 for EfficientNet-B0, 2048 for ResNet-50).

Table 4.

Table 4: pgvector configuration used in this thesis

Property	Value	Rationale
Extension	pgvector 0.8+	Open-source, zero additional infrastructure
Index type	HNSW	Logarithmic search complexity, good recall-speed balance
Distance metric	Cosine	Bounded range, interpretable thresholds for fashion similarity
Model metadata	model_name, model_version columns	Enables per-model filtering and A/B testing

1.5 SOFTWARE ENGINEERING TECHNOLOGIES

Building a production-capable e-commerce platform with integrated machine learning requires deliberate architectural and technology choices. This section surveys architectural patterns, describes each technology in the ReSys.Shop stack, and provides the rationale for each selection.

1.5.1 E-commerce Platform Architectures

Having covered how embeddings are generated and stored, this section examines the architectural patterns that organise the ReSys.Shop platform around these capabilities. Modern web applications are shaped by three architectural patterns, each trading off simplicity, scalability, and operational cost.

1.5.1.1 Monolith

A monolith packages the user interface, business logic, and data access into a single deployable unit. Development is straightforward: one codebase, one build pipeline, one deployment. At small scale this works well. As the system grows, subsystems accumulate coupling. Changing the checkout flow requires understanding the catalog module; deploying a payment fix means redeploying the entire application. The monolith does not scale with team size or codebase age.

1.5.1.2 Microservices

Microservices decompose an application into independently deployable services, each owning a discrete business capability. Teams can work in parallel using different technology stacks per service. The trade-off is operational complexity: service discovery, inter-service authentication, network latency, partial failure modes, and distributed transaction management. For a system where the primary research contribution lies in machine learning integration rather than infrastructure engineering, this overhead is disproportionate.

1.5.1.3 Modular Monolith

The modular monolith occupies the middle ground. Code is organised into logically isolated business modules within a single process. Compile-time boundaries prevent direct cross-module references, preserving the logical independence of bounded contexts. There is one build, one deployment, and one shared database. The nine business modules in ReSys.Shop (Catalog, Ordering, Payment, Inventory, Identity, Profile, Shipping, Location, Dashboard) communicate through an in-process message bus with no namespace-level dependencies between them. A shared PostgreSQL instance allows relational product data and vector embeddings to coexist within the same transactional boundary, maintaining consistency between catalog updates and search index changes.

The machine learning capability is the one exception to the single-process rule. It runs as a dedicated Python sidecar service, isolated because PyTorch and the broader Python scientific stack have incompatible runtime requirements with .NET. The sidecar communicates with the main application over HTTP, exposing a narrow embedding-generation interface while keeping GPU resource contention isolated from the e-commerce API.

1.5.1.4 Architectural Decision

ReSys.Shop adopts the modular monolith with a machine learning sidecar. The decision is guided by three trade-offs:

- **Deployment.** One process for the core application avoids service discovery, inter-service authentication, and distributed transaction orchestration. The Python sidecar runs as a separate process because PyTorch and .NET have incompatible runtime environments, but the sidecar exposes a narrow HTTP interface restricted to embedding generation. A GPU failure in the sidecar does not affect e-commerce API availability.
- **Data consistency.** A single PostgreSQL instance hosts both relational product data and pgvector embeddings. Catalog updates and embedding index changes share the same transactional boundary, eliminating the class of stale-index bugs that arise when a vector store and relational database drift out of sync.
- **Module boundaries.** Nine business modules (Catalog, Ordering, Payment, Inventory, Identity, Profile, Shipping, Location, Dashboard) are isolated by namespace convention within one assembly. Inter-module communication uses an in-process message bus. There are no direct cross-module references at compile time, preserving bounded-context independence without the operational cost of separate deployment units.

1.5.2 .NET Backend

The backend is built on .NET 10, a high-performance runtime with ahead-of-time compilation and native asynchronous I/O. Its architecture is organised around five core libraries:

- **Carter** extends ASP.NET minimal APIs with module-based endpoint registration. Each business module declares its own routes independently, keeping endpoint definitions co-located with their handlers rather than centralised in a startup file.
- **MediatR** implements CQRS, routing commands (writes) and queries (reads) to handlers through an in-process message bus. Handlers are discovered at startup and dispatched by request type, with no direct coupling between modules.
- **Entity Framework Core** maps C# domain objects to PostgreSQL tables, including pgvector column types for embedding storage. Migrations are version-controlled and applied at startup.
- **FluentValidation** enforces input rules at the application boundary. Each request type has an associated validator that runs before the handler executes, rejecting invalid data before it reaches business logic.
- **Vertical slice architecture** organises each feature (e.g., CreateProduct, SearchByImage) as a self-contained folder containing the handler, request, response, endpoint, and validator. This colocation keeps feature concerns together rather than spread across technical layers.

1.5.3 Vue.js Frontend

The frontend uses Vue 3 with TypeScript and the Vite build tool. Two surfaces share a common component library and state management:

- **Storefront.** Product catalog browsing with category trees, faceted filters (price, size, colour), and paginated result grids. Visual search with image upload, similarity-ranked results displaying thumbnail, price, and similarity score. Cart management with session-based guest support and a multi-step checkout flow spanning address entry, delivery selection, payment confirmation, and order completion.
- **Administration interface.** Complete lifecycle management for products, variants, taxonomies, and option types. Order processing with fulfilment status tracking. User and role administration with permission assignment. Analytics overview summarising sales and inventory metrics.

- **Pinia**, a state management library, organises client-side state through typed stores. Each bounded context has its own store (catalog, cart, auth, orders), mirroring the backend module boundaries.

1.5.4 PostgreSQL and pgvector

PostgreSQL 17 hosts both relational business data and vector embeddings in a single database.

- **Relational schema.** Tables for products, variants, orders, users, and supporting entities are organised by bounded context. Foreign keys reference entities within the same context; cross-context references use identifier columns without database-level constraints, preserving logical isolation.
- **pgvector extension.** Adds a `vector(N)` column type and cosine distance operator (`<=>`). An HNSW index on the embedding column enables sub-10ms ANN search on catalog-scale datasets.
- **Transactional consistency.** A product update and its embedding update share the same ACID boundary. New images trigger embedding generation; catalog modifications and index changes are committed together, eliminating stale-index drift.
- **Performance.** Composite indexes on query-critical combinations (user status, session status, product slug) optimise frequent access patterns. Query plans combine vector similarity and relational filtering in a single execution.

1.5.5 Redis Caching

Redis 7 operates alongside the .NET **HybridCache** abstraction in a two-tier arrangement.

- **L1: in-process.** Frequently accessed data (taxonomy trees, front-page product lists) is held in application memory with sub-millisecond read latency. Cache entries expire on a configurable sliding window, typically five minutes.
- **L2: Redis.** The shared tier synchronises cache across application instances. Redis also backs Hangfire job queues and guest session storage. On cache miss at L1, the value is retrieved from Redis and promoted to L1, ensuring subsequent hits stay in-process.

1.5.6 Python ML Sidecar

The machine learning capability runs as a dedicated Python 3.12 service, isolated from the .NET backend due to incompatible runtime dependencies (PyTorch requires Python, .NET requires the CLR).

- **Framework.** FastAPI provides async HTTP endpoints with automatic OpenAPI schema generation. Uvicorn serves as the ASGI runtime.
- **Model management.** A singleton **ModelManager** lazy-loads models from the HuggingFace hub on first request. Once loaded, models persist in GPU memory (or CPU, if no GPU is available) for the lifetime of the service. The manager supports multiple architectures through a common embedding interface.
- **API surface.** POST /embeddings accepts raw image bytes (JPEG, PNG, WebP) and returns a JSON array of floating-point values. GET /health reports the currently loaded model, its embedding dimension, and the most recent inference latency.
- **Security.** Requests require an X-API-Key header validated at the middleware layer. The sidecar listens only on the internal Docker network, inaccessible from the public internet.

1.5.7 .NET Aspire Orchestration

.NET Aspire coordinates the multi-container development and deployment environment.

- **Service discovery.** Components resolve each other by name: the .NET backend reaches the Python sidecar at `http://ml-service`, PostgreSQL at `postgres`, and Redis at `redis`. Configuration is injected via environment variables managed by the Aspire host.
- **Lifecycle.** Aspire enforces startup ordering (database before API, sidecar before backend health check) and gates each component behind a readiness probe. Containers restart on failure with configurable back-off.
- **Observability.** OpenTelemetry SDKs in both .NET and Python services export distributed traces, request metrics, and structured logs to the Aspire dashboard. Correlation IDs propagate across the HTTP boundary between backend and sidecar, linking a search request to its embedding generation span.

1.5.8 Hangfire Background Jobs

Hangfire processes operations that should not block HTTP requests. Jobs are persisted in Redis for resilience across application restarts.

- **Cart expiry.** A recurring job runs daily, removing carts with no activity for seven days. This prevents abandoned carts from accumulating indefinitely.

- **Embedding queue.** When an admin uploads new product images, embedding generation tasks are enqueued for asynchronous processing. The upload endpoint returns immediately; the embedding appears in search results once the job completes.
- **Index maintenance.** A periodic job rebuilds the HNSW index on the embedding column, optimising search performance as the catalog grows.

1.5.9 Identity, Authentication, and Authorisation

- **ASP.NET Identity** provides user account management: password hashing with salted PBKDF2, email confirmation workflows, and optional two-factor authentication via TOTP.
- **JWT tokens.** Access tokens carry claims (user ID, roles, permissions) and expire after 15 minutes. Refresh tokens enable silent renewal: the client exchanges a refresh token for a new access token, and each refresh token is single-use. Reuse of an already-consumed refresh token triggers revocation of all tokens for that user, mitigating token theft.
- **Guest sessions.** Anonymous users receive a signed session cookie. This cookie links to a server-side session backed by Redis, enabling cart operations and product browsing without authentication. On registration or login, the guest session is transferred to the authenticated user context.
- **Permission model.** Authorisation uses granular claims in the format `domain:category:action` (e.g., `catalog:products:create`). Roles aggregate commonly used permission sets. Endpoint-level attributes evaluate claims at the middleware layer, so handler code contains no authorisation logic.

1.5.10 Benchmark Framework

The benchmark framework is a Python 3.12 pipeline for systematic, reproducible evaluation of embedding models on fashion product retrieval. It is separate from the application codebase and produces the experimental results reported in Chapter 3.

- **Modes.** Three evaluation modes are supported: a one-shot comparison across all configured models, a three-fold cross-validation protocol with stratified category-based splits (the default for thesis results), and a pgvector pipeline mode that measures end-to-end latency including database query and network round-trip time.
- **Models.** 11 pre-trained architectures are implemented: CNN-based (ResNet-50, ResNet-101, ResNet-152, EfficientNet-B0, EfficientNet-B4), vi-

sion transformers (DINOv2 ViT-S/14, DINOv2 ViT-B/14), and CLIP variants (CLIP ViT-B/32, CLIP ViT-B/16, CLIP ViT-L/14, Fashion-CLIP). Each model has a thin adapter implementing a common `generate_embeddings` interface.

- **Caching.** Embeddings are cached to disk per model, per fold, and per split (query vs. catalog), avoiding recomputation when re-running evaluation on the same configuration.
- **Metrics.** Retrieval accuracy is measured through mAP, Precision at K, Recall at K, and nDCG. Operational efficiency is measured through inference latency (mean and SD per image), throughput (images per second), model load time, on-disk storage, and RAM usage.
- **Outputs.** Results are exported in JSON, CSV, Markdown, and Typst table formats. The Typst output files (`thesis_aggregate.typ`, `thesis_efficiency.typ`) embed directly into the thesis without manual transcription.
- **Multi-label pipeline.** A separate enriched-dataset mode supports evaluation across three label schemes of increasing granularity (category only, category and colour, and category, colour and pattern), enabling analysis of how embedding quality varies with annotation detail.

1.5.11 Technology Stack Summary

The preceding sections introduced the principal technologies that compose the ReSys.Shop platform. Table 5 consolidates the complete stack.

Table 5.

Table 5: Technology stack of the ReSys.Shop platform

Layer	Technology	Role
Frontend	Vue 3, TypeScript, Vite	Customer storefront and administration interface; reactive UI with Pinia state management
Backend API	.NET 10, Carter, MediatR	REST endpoints via minimal APIs; CQRS command-query separation across business modules
Database	PostgreSQL, pgvector	Relational data and vector embeddings in a single ACID database with HNSW-indexed similarity search
Caching	Redis, HybridCache	Two-tier cache (in-memory L1 and Redis L2); Hangfire job queue and session state backing store
ML Sidecar	Python 3.12, FastAPI, PyTorch	Dedicated embedding generation service with lazy model loading and GPU acceleration
Orchestration	.NET Aspire	Container lifecycle management, service discovery, and reproducible local development environment
Background Jobs	Hangfire	Persistent job processing for cart expiry, embedding queue, and maintenance tasks
Auth and Identity	JWT, ASP.NET Identity	Access tokens, refresh rotation, permission-based authorisation, guest sessions
Benchmarking	Python 3.12, PyTorch	Systematic 11-model comparison with cross-validation, accuracy and efficiency metrics

Together these technologies form a polyglot stack spanning three languages (C#, TypeScript, Python) orchestrated through a unified containerised environment. The .NET backend hosts transactional e-commerce logic; Vue 3 delivers the customer-facing interface; PostgreSQL serves as the single source of truth for both business data and embeddings; and the Python sidecar provides the bridge to GPU-accelerated model inference. A dedicated benchmarking framework, separate from the application codebase, provides the systematic evaluation infrastructure that produces the experimental results in Chapter 3.

1.6 RELATED WORK AND RESEARCH GAP

This section positions the ReSys.Shop platform within the landscape of fashion image retrieval research and commercial visual search systems, and identifies the engineering gap that this thesis addresses.

1.6.1 Academic Research

The **DeepFashion** dataset, introduced by Liu et al., established the foundational benchmark for fashion recognition and retrieval with over 800,000 images annotated with attributes, landmarks, and in-shop-to-consumer photo pairs [12]. This dataset catalysed much of the subsequent work in fashion AI.

FashionIQ extended retrieval to the conversational setting, where users modify queries through natural language feedback (“like this dress but shorter”) [13]. While compelling, the interactive dialogue paradigm requires infrastructure beyond the scope of this project, which focuses on single-turn visual and text queries.

The **Fashion-CLIP** work demonstrated that domain-specific fine-tuning of CLIP on 700,000 fashion images improves retrieval by 15 to 20% over the general model [6]. This thesis follows that approach, using pre-trained models without custom training, and extends the evaluation to additional architectures (ResNet, EfficientNet, DINOv2) for systematic comparison.

1.6.2 Commercial Systems

Several platforms have deployed visual search at production scale.

Table 6.

Table 6: Comparison of commercial visual search products

Product	Key Strength	Limitation
Google Lens	Massive scale, general-domain coverage	Closed ecosystem, not customisable
Pinterest Lens	Over 600M monthly searches, style-aware	Proprietary, requires Pinterest integration
ASOS Style Match	Fashion-specific accuracy	Restricted to ASOS catalog only
ViSenze	API-based, good accuracy	Paid service with recurring per-query costs

These products share common limitations for independent projects: they are proprietary and cannot be studied or modified, API access incurs costs at query volume, and reliance on external services creates vendor lock-in. This thesis demonstrates that comparable functionality is achievable with open-source tools, providing both a reference implementation and a cost-effective alternative for smaller deployments.

1.6.3 Contribution Differentiators

This project distinguishes itself from prior work by addressing the **engineering gap** between model research and production systems. Four contributions define this gap:

1. Polyglot architecture. Python’s machine learning ecosystem (PyTorch, HuggingFace) does not natively interoperate with the .NET stack common in enterprise e-commerce. This thesis presents a modular monolith with a dedicated AI sidecar, combining .NET’s type safety and transactional integrity with Python’s access to state-of-the-art vision models, without the operational overhead of a full microservices deployment.

2. Vector-native consistency. By using pgvector within PostgreSQL, embeddings and product metadata share the same transactional boundary. Product updates, image replacements, and index maintenance occur atomically, eliminating stale-index bugs that arise when a vector store and relational database have independent consistency guarantees.

3. Commodity hardware benchmarking. Commercial visual search runs on cloud TPU clusters. This thesis evaluates 11 models on consumer-grade hardware, establishing that production-quality visual search is achievable without specialised infrastructure, lowering the barrier for small to medium e-commerce platforms.

4. Applied model comparison. Rather than chasing leaderboard metrics, this thesis compares models within realistic deployment constraints (inference latency budget, memory limits, storage cost). The resulting accuracy-efficiency trade-off data, presented in Chapter 3, provides a pragmatic guide for practitioners selecting embedding models.

2 DESIGN AND IMPLEMENTATION

This chapter consolidates the system design. Section 2.1 defines the functional and non-functional requirements. Section 2.2 presents three representative use cases spanning the core research capability, the primary e-commerce workflow, and the evaluation infrastructure. Section 2.3 presents the system architecture, domain model, database schema, API design, and security model. Section 2.4

describes the implementation of the .NET backend, Python ML sidecar, and Vue.js storefront.

2.1 REQUIREMENTS ANALYSIS

This section defines the scope of the ReSys.Shop platform by identifying its actors, functional and non-functional requirements, and the classification of features into research contributions and supporting infrastructure. The analysis establishes what the system must do before proceeding to its architectural design and implementation. Use cases are treated separately in Section 2.2.

2.1.1 System Actors

The platform serves three categories of actors, each with a distinct role, set of permissions, and interaction surface. Table 7 summarises these actors and their primary responsibilities.

Table 7.

Table 7: System actors and their roles within the ReSys.Shop platform.

Actor	Role Description	Interaction Surface
Customer (Guest + Authenticated)	Browses the product catalog, performs keyword and visual searches, manages a shopping cart, completes multi-step checkout, and tracks order history. Guest users can browse and add items to a cart; authenticated users access profile management, wishlists, and personalised features.	Vue 3 Storefront SPA (Web browser)
Administrator	Manages the full product lifecycle: creating and updating products with fashion-specific metadata, uploading and organising product images, defining taxonomies, monitoring inventory levels, processing order fulfilment, and managing user accounts and permissions.	Vue 3 Admin SPA (Web browser)
System (Background Services)	Automated background processes that maintain data consistency and system performance: generating and indexing vector embeddings for newly uploaded images, expiring abandoned carts after a configurable time window, reserving and releasing inventory during checkout, and performing periodic index maintenance.	Internal services (No direct UI)

The Customer and Administrator actors represent human users interacting through browser-based single-page applications. The System actor represents background processes that operate without direct human interaction, executing scheduled and event-driven tasks through Hangfire job workers within the .NET application process. The three actors together define the complete set of interactions supported by the platform.

2.1.2 Functional Requirements

The platform’s capabilities are specified as traceable requirements organised by business module. Each module is introduced with a single sentence of context; the table that follows enumerates specific requirements with identifiers that can be referenced throughout the design and evaluation chapters.

2.1.2.1 Catalog Module

The Catalog module manages the product lifecycle: creation, classification, image handling, and CBIR infrastructure.

Table 8.

Table 8: Catalog module functional requirements.

ID	Requirement	Priority
CAT-FR-01	Create products with name, description, slug, SEO meta-data, and fashion-specific fields (style code, season, material composition, department, gender target)	High
CAT-FR-02	Define sellable variants (size and colour combinations) with SKU, barcode, dimensions, and independent pricing	High
CAT-FR-03	Upload variant images with automatic thumbnail generation	High
CAT-FR-04	Generate vector embeddings for all uploaded images using the configured ML model and store in pgvector	High
CAT-FR-05	Search products by image via CBIR with configurable minimum similarity threshold and result count	High
CAT-FR-06	Support configurable embedding models (Fashion-CLIP, ResNet-50, and others) via environment variable without code changes	High
CAT-FR-07	Organise products via hierarchical taxonomies with taxon trees	Medium
CAT-FR-08	Manage option types (e.g., Size, Colour) with option values	Medium
CAT-FR-09	Enforce slug uniqueness across the catalog	High
CAT-FR-10	Support product status lifecycle: Draft, Active, Archived with availability dates	Medium

2.1.2.2 Identity Module

The Identity module provides authentication, authorisation, and user management for both customer-facing and administrative functions.

Table 9.

Table 9: Identity module functional requirements.

ID	Requirement	Priority
IDN-FR-01	Register new customer accounts with email, password, and profile information	High
IDN-FR-02	Authenticate users with JWT access tokens (15-minute life-time) and refresh token rotation with reuse detection	High
IDN-FR-03	Support guest sessions via cookie-based identifiers for anonymous cart usage across page navigations	High
IDN-FR-04	Enforce role-based and permission-based authorisation with domain:category:action claims format	High
IDN-FR-05	Reset passwords via time-limited email token	Medium
IDN-FR-06	Manage users and roles through the admin interface	Medium
IDN-FR-07	Revoke all refresh tokens for a user when a previously consumed token is presented (compromise containment)	High

2.1.2.3 Inventory Module

The Inventory module tracks physical stock quantities, manages checkout-time reservations, and records stock movements for audit trails.

Table 10.

Table 10: Inventory module functional requirements.

ID	Requirement	Priority
INV-FR-01	Define stock locations (warehouses) with address and active status	Medium
INV-FR-02	Track stock quantities per product variant per location with on-hand and reserved values	High
INV-FR-03	Reserve inventory during checkout and release on cart expiry or cancellation to prevent overselling	High
INV-FR-04	Record stock transfers between locations with full auditable movement history	Medium
INV-FR-05	Maintain immutable audit log for all stock level changes	Medium

2.1.2.4 Ordering Module

The Ordering module handles the customer purchase workflow from cart through checkout to completed order.

Table 11.

Table 11: Ordering module functional requirements.

ID	Requirement	Priority
ORD-FR-01	Support guest and authenticated shopping carts with product variant selection and quantity management	High
ORD-FR-02	Auto-expire abandoned carts after configurable inactivity period (default seven days)	Medium
ORD-FR-03	Enforce forward-only checkout state machine: Address, Delivery, Payment, Confirm, Complete	High
ORD-FR-04	Calculate order totals including item subtotals, price adjustments, shipment costs, and taxes	High
ORD-FR-05	Track payment and shipment state independently per order to enable partial fulfilment	Medium
ORD-FR-06	Allow order cancellation at any pre-confirmation stage without penalty	Medium
ORD-FR-07	Generate unique human-readable order numbers upon confirmation	Medium

2.1.2.5 Payment Module

The Payment module manages the lifecycle of payment intents across the Stripe production gateway and a Bogus test gateway.

Table 12.

Table 12: Payment module functional requirements.

ID	Requirement	Priority
PAY-FR-01	Create payment intents with amount, currency, and order reference	High
PAY-FR-02	Capture, void, and refund payment intents with idempotency keys to prevent duplicate processing	High
PAY-FR-03	Process Stripe webhooks with cryptographic signature verification for production	High
PAY-FR-04	Provide Bogus gateway for development and testing that simulates the full payment lifecycle without external calls	Medium
PAY-FR-05	Maintain independent payment state tracking in parallel with the gateway for offline consistency	Medium

2.1.2.6 Shipping Module

The Shipping module configures delivery methods and calculates shipping rates by geographic zone.

Table 13.

Table 13: Shipping module functional requirements.

ID	Requirement	Priority
SHP-FR-01	Configure delivery methods (standard, express, local pickup) with associated pricing rules	Medium
SHP-FR-02	Calculate shipping rates by geographic zone and selected delivery method at checkout	Medium

2.1.2.7 Profile Module

The Profile module links customer identity to personalisation features and preference management.

Table 14.

Table 14: Profile module functional requirements.

ID	Requirement	Priority
PRF-FR-01	Manage user shipping and billing addresses, wishlists, and notification preferences	Medium
PRF-FR-02	Configure per-channel notification preferences (email, SMS, push)	Low

2.1.2.8 Location Module

The Location module provides country and state reference data for address validation and shipping zone configuration.

Table 15.

Table 15: Location module functional requirements.

ID	Requirement	Priority
LOC-FR-01	Provide country and state reference data with ISO 3166 codes for address validation and shipping zone calculation	Medium

2.1.3 Non-Functional Requirements

Beyond feature completeness, the system must satisfy quantitative and qualitative constraints that determine its fitness for production use. Table Table 16 summarises the non-functional requirements across five quality dimensions.

Table 16.

Table 16: Non-functional requirements with concrete targets and design rationale.

Quality	Target	Rationale
Performance	CBIR end-to-end search latency under 1 second (image upload through embedding generation, vector database query, and result assembly). Non-search API endpoints respond within 200 milliseconds under normal load. Asynchronous I/O handles concurrent requests without blocking threads.	Real-time visual search requires sub-second response to maintain user engagement. Studies show that search latency above one second measurably increases abandonment rates in e-commerce contexts [14].
Security	JWT access tokens expire after 15 minutes; refresh tokens follow single-use rotation with reuse-detection invalidation. Role-based authorisation enforced per endpoint. Rate limiting on authentication endpoints (five requests per minute for login, three per hour for registration). Security response headers (CSP, HSTS, X-Frame-Options, X-Content-Type-Options) on all HTTP responses. File upload validation: magic-byte verification, extension allowlist, and 10 megabyte size limit.	Browser-based single-page applications are exposed to the open internet and must defend against common web threats. Short-lived tokens and refresh rotation limit the window of token compromise. File upload validation prevents malicious payloads from entering the embedding pipeline.
Modularity	Eight business modules in a single .NET assembly, separated by namespace convention with no direct cross-references. All inter-module communication occurs through MediatR in-process message dispatch. Each module independently testable without loading its neighbours.	The modular monolith pattern preserves the logical separation of microservices while avoiding distributed-system complexity. MediatR dispatch provides a clean integration point that can be replaced with an external message broker if modules are later extracted into separate services.
Observability	OpenTelemetry distributed tracing across .NET API and Python ML sidecar, with trace context propagation through HTTP headers. Structured logging with correlation identifiers on every log entry. Health check endpoints for each service, consumed by .NET Aspire for container orchestration and restart decisions.	In a polyglot architecture spanning C# and Python, end-to-end request tracing is essential for diagnosing latency bottlenecks and error propagation. Correlation identifiers enable a single request to be followed across service boundaries in log aggregators.
Reliability	Background jobs (cart expiry, embedding generation retries, index maintenance) persist in Redis-backed Hangfire storage, surviving application restarts without data loss. Payment webhooks include idempotency keys that prevent duplicate processing on retry. Cart expiry triggers after fifteen minutes of inactivity, releasing reserved inventory automatically.	Many e-commerce operations are inherently long-running or time-delayed, cart expiry, payment confirmation, and index maintenance. A durable job queue ensures these operations complete reliably, even across process crashes or scheduled restarts.

These non-functional requirements shaped architectural decisions throughout the system. The one-second CBIR latency target influenced the choice of a synchronous embedding pipeline rather than a queued approach; the modularity requirement led to the MediatR-based in-process dispatch model; and the reliability constraint motivated the choice of Hangfire with Redis-backed persistence for background jobs. Each target is revisited in the evaluation chapter, where the benchmark results confirm whether the implemented system meets these stated requirements.

2.1.4 Feature Classification

Not all features of ReSys.Shop carry equal research significance. Seven feature areas are classified in Table 17 as either **Core Research** (directly contributing to the thesis’s academic objectives) or **Supporting Infrastructure** (providing the realistic e-commerce context in which the research is conducted and evaluated). This distinction is important for two reasons: it clarifies the scope of the thesis’s original contribution, and it explains why certain features, shipping calculation, user management, country reference data, exist in the platform but are not discussed in depth in subsequent chapters.

Table 17.

Table 17: Classification of feature areas into Core Research and Supporting Infrastructure. Core Research features represent the thesis’s original contributions; Supporting Infrastructure features provide the realistic e-commerce context necessary for meaningful evaluation.

Feature Area	Classification	Rationale
Visual Search (CBIR)	Core Research	Primary contribution: integrated multi-model CBIR with pluggable architecture enabling image-based product search across multiple embedding models (CNN, ViT, CLIP-based) within a production-style e-commerce platform.
ML Embedding Pipeline	Core Research	Critical infrastructure: automated ingestion of product images, generation of vector embeddings via the Python sidecar, storage in pgvector, and HNSW indexing, the operational backbone of the visual search capability.
Model Benchmark System	Core Research	Secondary contribution: systematic protocol for comparing retrieval accuracy and operational efficiency across 11 embedding models, providing a practical guide for model selection in resource-constrained deployments.
Product Catalog	Supporting Infrastructure	Required context: provides the structured dataset of fashion products, with variants, images, taxonomies, and metadata, that serves as the search target for CBIR evaluation.
Order System	Supporting Infrastructure	Metric validation: provides conversion events (add-to-cart, checkout completion) that serve as proxy indicators of search success, enabling the evaluation of visual search within a realistic shopping workflow.
Inventory	Supporting Infrastructure	Realism constraint: ensures that search results reflect actual product availability, preventing the unrealistic scenario where visually similar but out-of-stock items appear in search results.
Authentication	Supporting Infrastructure	Security baseline: protects administrative functions and user-specific data, enabling the application to operate in a representative security posture without which the system would be

The classification makes explicit what the thesis does and does not claim as contribution. The CBIR pipeline, encompassing embedding generation, vector storage, and similarity search, is the core research artefact. The e-commerce modules (Catalog, Ordering, Inventory, Payment, Identity) are supporting infrastructure, built to provide a realistic context that validates the visual search results in a production-like environment. This separation is maintained throughout the thesis: Sections 2.2 and 2.3 devote detailed treatment to the research features, while the supporting infrastructure is described only to the extent necessary to understand the system’s design.

2.2 FUNCTIONAL DECOMPOSITION AND USE CASES

This section presents three representative use cases that illustrate how the system’s functional requirements translate into concrete interaction flows. The use cases span the core research capability (visual search), the primary e-commerce workflow (checkout), and the evaluation infrastructure (model benchmarking).

2.2.1 Use Case 1: Visual Search (CBIR)

Table 18.

Table 18: UC-1: Visual Search (CBIR), the primary research use case.

Actor	Customer (Guest or Authenticated)
Precondition	The Python ML sidecar service is running and has loaded the configured embedding model into memory. The product catalog contains at least one variant with a stored embedding vector for the active model.
Main Flow	1. Customer uploads a reference image (JPEG, PNG, or WebP; maximum ten megabytes) via the storefront visual search interface. 2. The Vue frontend sends the image as a multipart form data request to the .NET API endpoint. 3. The API validates the image, magic-byte verification, extension check, size limit, then forwards the raw image bytes to the Python ML sidecar. 4. The ML sidecar preprocesses the image (resize, normalise) and executes a forward pass through the configured embedding model, producing a floating-point vector. 5. The API queries PostgreSQL pgvector using cosine similarity against all stored variant embeddings filtered by the active model name, retrieving the top 20 most similar results. 6. The API joins variant data with product metadata, computes similarity scores, filters by a minimum similarity threshold (default 0.7), and returns the ordered results as JSON. 7. The Vue storefront renders the results as a grid of product thumbnails with similarity scores and prices.
Postcondition	A ranked list of visually similar products is displayed to the customer, ordered by decreasing cosine similarity. Each result includes the product thumbnail, name, price, and similarity score.

2.2.2 Use Case 2: Multi-Step Checkout

Table 19.

Table 19: UC-2: Multi-Step Checkout, the primary e-commerce transaction use case.

Actor	Customer (Guest or Authenticated)
Precondition	The customer's cart contains at least one valid, in-stock item. The customer has a shipping address on file or is prepared to enter one.
Main Flow	1. Customer clicks "Proceed to Checkout" from the cart page. 2. System presents the checkout interface, showing the current cart contents with item totals. 3. Customer selects or enters a shipping address. 4. Customer selects a delivery method from available shipping options. 5. Customer selects a payment method and provides payment details. 6. Customer reviews the order summary (items, shipping cost, tax, total) and clicks "Place Order". 7. System begins an atomic transaction: creates the order record, reserves inventory quantities for each line item, processes the payment through the configured gateway, and clears the cart. 8. System displays the order confirmation page with the order number and summary.
Postcondition	An order record is created with status "Placed". Inventory quantities for each ordered variant are reserved. A payment intent is linked to the order. The customer's cart is emptied. A confirmation is displayed with the order reference number.

2.2.3 Use Case 3: Model Benchmark Evaluation

Table 20.

Table 20: UC-3: Model Benchmark Evaluation, the research methodology use case.

Actor	Researcher / System
Precondition	The benchmark dataset is available on disk, consisting of query images and catalog images organised into human-labelled similarity groups. The Python ML sidecar is running. All candidate embedding model weights are downloaded and accessible.
Main Flow	1. Researcher selects a model from the candidate set (e.g., Fashion-CLIP, ResNet-50, DINOv2-S) and configures the ML sidecar via environment variable. 2. System generates embedding vectors for all query images and all catalog images using the selected model. 3. For each query image, the system executes a top-K ($K = 20$) similarity search against the catalog embeddings. 4. System computes retrieval metrics: Mean Average Precision (mAP), Precision at K, and Recall at K, using the human-labelled groups as ground truth. 5. System records operational metrics: average inference time per image, throughput (images per second), disk storage for the embedding index, and RAM consumption. 6. Steps 1 to 5 are repeated for each of the 11 candidate models. 7. System aggregates all results into comparison tables, ranking models by retrieval accuracy and operational efficiency.
Postcondition	A complete benchmark report is produced containing accuracy metrics (mAP, P@20, R@20) and efficiency metrics (latency, throughput, storage, RAM) for every evaluated model. The report identifies the optimal model for each deployment scenario (GPU production, CPU-only, maximum accuracy, resource-constrained).

Figure Figure 1 positions these three use cases alongside the broader system functionality within a single visual summary.




Figure 1.

Figure 1: System use case diagram showing the three actors, Customer, Administrator, and System background services, and their primary interactions with the ReSys.Shop platform.

The three use cases serve distinct purposes within the thesis. The visual search use case defines the functional behaviour of the system’s primary research capability; the checkout use case establishes the realistic e-commerce context in which search success can be measured through downstream conversion events; and the benchmark use case defines the systematic methodology used in Chapter 3 to evaluate and compare embedding models. The breadth of the system, nine background actors and use cases in the diagram, encompassing catalog browsing, account management, product administration, and order processing, reflects the full operational scope of the platform, while the three detailed use cases focus on the scenarios most relevant to the research questions.

2.3 SYSTEM ARCHITECTURE & DESIGN

This chapter presents the architectural design of ReSys.Shop, progressing from a high-level system overview through domain modelling, to the structural, data, API, and security layers. The design follows a service-oriented approach with three independently deployable services, a Vue 3 frontend, a .NET 10 modular monolith backend, and a Python machine learning sidecar, each responsible for a distinct technological concern. The chapter is organised into six sections, each accompanied by architectural diagrams that provide visual representations of the system’s structure, behaviour, and deployment topology.

2.3.1 System Overview

ReSys.Shop is built as a service-oriented system with three distinct services. The frontend is implemented in Vue 3 and TypeScript using the Vite build tool. The backend is a .NET 10 modular monolith using ASP.NET Core for HTTP handling, Entity Framework Core for data access, and Carter for minimal API endpoint registration. The machine learning service is a Python FastAPI application running PyTorch models that generates vector embeddings from product images for visual similarity search.

Table 21 summarises the three services, their technology stacks, and their primary responsibilities within the platform.

Table 21.

Table 21: System services and their technology stacks. Each service is independently deployable and communicates through well-defined HTTP contracts.

Service	Technology Stack	Responsibilities
Vue Frontend	Vue 3 + TypeScript + Vite	• Customer storefront (Nuxt UI) • Administrator dashboard (PrimeVue) • Pinia state management • Image upload and visual search UI
.NET Backend	.NET 10 + ASP.NET Core + Carter + EF Core	• REST API endpoints via Carter minimal APIs • Business logic via MediatR CQRS pattern • PostgreSQL persistence with pgvector vector search • JWT authentication and RBAC authorisation
Python ML	Python 3.12 + FastAPI + PyTorch	• Fashion-CLIP and other embedding model inference • Vector embedding generation from product images • Multi-model support with lazy-loading strategy

The backend is internally organised into eight bounded contexts following the principles of Domain-Driven Design. Each context owns a distinct area of business logic and communicates with other contexts exclusively through MediatR in-process message dispatch, there are no direct namespace references between business modules. Table 22 lists each context, its aggregate root, and a representative sample of its domain entities.

Table 22.

Table 22: Bounded contexts with aggregate roots and key domain entities. Each context owns its database schema and communicates with other contexts through MediatR dispatch only.

Bounded Context	Aggregate Root	Key Domain Entities
Catalog	Product	Variant, VariantImage, OptionType, OptionValue, Classification, Taxonomy, Taxon
Ordering	Order	LineItem, Adjustment, Shipment
Payment	PaymentIntent	PaymentCapture
Inventory	StockItem	StockLocation, StockMovement, StockReservation
Identity	User	Role, UserRole, RefreshToken, UserLogin
Profile	UserProfile	Address, Wishlist
Shipping	ShippingMethod	ShippingRate, ShippingZone
Location	Country	State

The separation of concerns across these eight contexts enables independent evolution of each business domain while the modular monolith deployment model avoids the operational complexity of distributed microservices. The following section details the domain-driven design principles that govern these contexts.

2.3.2 Domain-Driven Design

The ReSys.Shop platform applies Domain-Driven Design (DDD) to structure its business logic around eight bounded contexts, each with well-defined aggregate roots, domain entities, and invariants. This section presents the context map, the aggregate design with invariants, the ubiquitous language glossary, and the state machines that govern the checkout and payment lifecycles.

2.3.2.1 Bounded Context Map

The eight bounded contexts partition the e-commerce domain along business capability boundaries. Each context owns its data, its domain logic, and its vocabulary, terms that are well-defined within a context may carry different meaning in another. For example, a Variant in the Catalog context is a sellable unit with a SKU and pricing; a LineItem in the Ordering context references that same variant but from the perspective of purchase fulfilment.

The integration between contexts follows the **Conformist** pattern: all contexts conform to a shared technical kernel defined in the Shared layer, which provides the `Result<T>` return type, the `ICommand` and `IQuery` marker interfaces, and the `Entity` base class with audit and versioning columns. Communication occurs exclusively through MediatR `ISender`, a context dispatches a query or publishes a notification, and other contexts react without ever importing one

another's namespace. This in-process dispatch model eliminates the network latency of inter-service messaging while preserving the logical isolation of the bounded contexts.

Figure Figure 2 depicts the eight contexts and the **Published Language**, the shared identifiers and value types, that flow between them.




Figure 2.

Figure 2: Bounded Context Map showing the eight business contexts and the Published Language identifiers exchanged between them. All integration uses in-process MediatR dispatch; no context directly references another context's namespace.

Table Table 23 details each context's business responsibility and the integration data it exposes to the system.

Table 23.

Table 23: Bounded context responsibilities and Published Language identifiers. The Published Language column lists the value types that other contexts may reference by identifier only, never by importing the source context's namespace.

Context	Business Responsibility	Published Language
Catalog	Manages the product lifecycle: creating products with fashion-specific metadata (style code, season, material, department, gender target), defining sellable variants with SKUs and independent pricing, uploading images with automatic embedding generation, and organising products through hierarchical taxonomies.	ProductId, VariantId, Sku, Price, Slug
Ordering	Orchestrates the customer purchase workflow from cart to completed order. Manages cart with seven-day auto-expiry, forward-only checkout state machine, line items with price snapshots, adjustments, and cancellation at any pre-confirmation stage.	OrderId, OrderNumber, Total, Currency, CheckoutState
Payment	Manages payment intent lifecycle, creation, capture, refund, void, across two gateway implementations. Maintains parallel payment state independent of the gateway for offline operations and consistent behaviour across providers.	PaymentIntentId, PaymentState, Amount
Inventory	Tracks physical stock quantities per warehouse, manages temporary reservations during active checkouts to prevent overselling, records auditable stock movements through an append-only ledger, and handles inter-warehouse transfers.	StockItemId, QuantityOnHand, QuantityReserved
Identity	Provides JWT-based authentication with refresh token rotation and reuse detection, role-based and permission-based authorisation with domain:category:action claim format, and guest session management for anonymous browsing.	UserId, Email, PermissionClaim
Profile	Manages user addresses for shipping and billing, wishlists for product bookmarking, and notification preferences controlling email and SMS communication channels.	ProfileId, AddressId
Shipping	Configures delivery methods, standard, express, local pickup, and calculates shipping rates by geographic zone using weight- and distance-based calculators.	ShippingMethodId, Rate
Location	Provides country and state reference data with ISO 3166 codes.	CountryId, StateId, IsoCode

This context is read-only reference data shared across Shipping (zone configuration), Profile (address validation), and Ordering (checkout address selection).

2.3.2.2 Aggregates and Invariants

An aggregate is a cluster of domain objects treated as a single consistency boundary. Each aggregate has a root entity through which all modifications must pass. The root enforces invariants, business rules that must hold true at all times within the aggregate boundary. ReSys.Shop takes a pragmatic approach to DDD: it defines aggregate roots and their invariants explicitly but does not require formal value-object base classes or a dedicated domain-event infrastructure for every operation.

The four most architecturally significant aggregates are described below.

Product (Catalog aggregate root). The Product aggregate encapsulates a product family and all its variants, images, option configurations, and taxonomy classifications. A product may have one or more variants; exactly one is designated as the master variant displayed on listing pages. The aggregate enforces the following invariants: every product must have a unique slug for SEO-friendly URL generation; a product that declares options (such as size or colour) must have at least one option type defined; and the master variant must exist among the product's own variants. Variant images contain the embedding column, a 512-dimensional float vector generated by the ML sidecar, enabling cosine similarity search against the entire image corpus.

Order (Ordering aggregate root). The Order aggregate manages the checkout lifecycle from a nascent cart through to a completed purchase. It aggregates line items, each capturing a price snapshot of the variant at the time of purchase, and optional adjustments for discounts or promotions. The aggregate enforces the invariant that $\text{Total} = \text{ItemTotal} + \text{AdjustmentTotal} + \text{ShipmentTotal}$, maintaining financial consistency across all modifications. The checkout state progresses forward only, the address, delivery, payment, and confirmation stages must complete in sequence, and once an order is confirmed (finalised), it becomes immutable except for the cancel transition. This forward-only constraint is encoded in the domain entity itself and validated before every state transition.

PaymentIntent (Payment aggregate root). The PaymentIntent aggregate models the lifecycle of a customer's intent to pay. It is created with a specified amount and currency, and transitions through states, Pending, RequiresAction, Processing, Succeeded, Canceled, and Failed, based on gateway interactions. The aggregate tracks payment captures, where each capture debits a portion of the authorised amount. The system enforces the invariant that the sum of all captures must not exceed the original intent amount. A separate payment capture goes through its own state transitions: Succeeded $\rightarrow$ Captured $\rightarrow$ Refunded / Voided. The system maintains its own payment state in parallel with the gateway state, enabling consistent behaviour whether using the production Stripe gateway or the development Bogus gateway.

StockItem (Inventory aggregate root). The StockItem aggregate tracks the physical availability of a product variant at a specific warehouse location. It maintains two quantities: on-hand (physical count from warehouse operations) and reserved (units held for active checkouts). The aggregate enforces the invariant that $\text{QuantityOnHand} \geq 0$, stock cannot go negative. Backorder support allows sales beyond on-hand quantity up to a configured backorder limit, but the system tracks the deficit separately. Quantity changes are not performed directly on StockItem; instead, they must be recorded as StockMovement entries in an append-only ledger, preserving a complete and auditable history of every stock change, including the quantity before and after, the reason, and the operating user.

2.3.2.3 Ubiquitous Language Glossary

A key practice in DDD is establishing a ubiquitous language, a shared vocabulary used by all team members and reflected directly in the codebase. Table 24 presents the core terms of the ReSys.Shop domain with their definitions.

Table 24.

Table 24: Ubiquitous Language Glossary: core domain terms, their owning bounded context, and their precise definitions as used throughout the codebase and this thesis.

Term	Context	Definition
Product	Catalog	A product family representing a fashion item concept (e.g., “Cotton T-Shirt”). Holds shared metadata: description, slug, status, fashion-specific attributes, and taxonomy classifications. Does not have a price or SKU directly, those belong to Variants.
Variant	Catalog	A sellable, physical unit of a product (e.g., “Cotton T-Shirt, Red, Large”). Holds SKU, barcode, pricing, inventory tracking flag, and physical dimensions. Each variant belongs to exactly one product.
Master Variant	Catalog	The designated default variant shown on product listing pages. Every product with variants must have exactly one master variant.
Option Type	Catalog	Defines a configurable attribute class such as “Colour”, “Size”, or “Material”. Option types are product-independent and reusable across the catalogue.
Taxonomy / Taxon	Catalog	A hierarchical categorisation tree for organising products. A Taxonomy (e.g., “Department”) contains Taxons (e.g., “Clothing” → “Dresses” → “Evening Dresses”) forming a nested set structure.
Cart	Ordering	An ephemeral collection of line items that represents a customer’s intent to purchase. Carts automatically expire after seven days of inactivity. The cart is the initial state of the Order aggregate.
Line Item	Ordering	A single entry in an order or cart, referencing a specific product variant, quantity, and a price snapshot captured at the time of purchase to insulate historical orders from catalogue price changes.
Checkout State	Ordering	The sequential stage of the purchase process: Address → Delivery → Payment → Confirm → Complete. Progression is forward-only; cancellation is available from any pre-confirmation stage.
Payment Intent	Payment	A data structure representing a customer’s intent to pay a specified amount. Follows a defined state machine through the gateway interaction lifecycle.
Payment Capture	Payment	A partial or full debit against a payment intent. Multiple captures can be performed against a single intent (e.g., capturing shipping cost after items ship).
Stock Item	Inventory	The current state of a product variant’s availability at a specific warehouse. Maintains on-hand and reserved quantity counters with optimistic concurrency control to prevent overselling.
Stock Movement	Inventory	An immutable ledger entry recording every change to a stock item’s quantity, the delta, the balance before and after, the reason, and the operating user. The single source of truth for inventory changes.
Refresh Token	Identity	A long-lived credential used to obtain new short-lived access tokens without re-authentication. Each token is single-use; presenting a previously consumed token triggers revocation of all tokens for that user.

2.3.2.4 State Machines

Two explicit state machines govern the most critical transactional workflows in the system: the order checkout process and the payment intent lifecycle. Both are encoded in domain entities, validated before every state transition, and drive the sequence of user-facing and system-level actions.

2.3.2.4.1 Order Checkout State Machine

The order checkout state machine enforces a forward-only progression through five sequential states: Address, Delivery, Payment, Confirm, and Complete. Each state transition is triggered by a specific user action and validated by the domain entity before being committed. Figure Figure 3 depicts this lifecycle.




Figure 3.

Figure 3: Order checkout state machine: five sequential states with cancellation available from any pre-confirmation state. The forward-only constraint prevents regressing to earlier checkout stages.

The customer begins by providing a shipping address (Address state), selects a delivery method (Delivery state), chooses a payment method (Payment state), reviews the complete order summary (Confirm state), and finalises the purchase (Complete state). At any point before the Complete state, from Address through Confirm, the customer may cancel the checkout process, which terminates the order without financial consequence.

Once an order reaches the Complete state, it becomes finalised: the order record transitions to Pending status, inventory quantities are reserved for each line item, and the payment intent is processed. From this point forward, the order is immutable except for the cancel transition, which captures the cancellation timestamp and releases reserved inventory. This forward-only design ensures that at every stage of the checkout pipeline, the system can unambiguously determine the customer's position and the next required action.

2.3.2.4.2 Payment Intent State Machine

The payment intent state machine models the full lifecycle of a payment from creation through to terminal completion, reflecting the state transitions of the Stripe payment gateway while maintaining a parallel system-managed state for offline consistency. Figure Figure 4 shows all states and transitions.




Figure 4.

Figure 4: Payment intent lifecycle: the state machine reflects Stripe gateway states while maintaining a parallel system copy for offline operations and Bogus gateway compatibility. Terminal states are Failed, Canceled, and Refunded.

A payment intent is created in the Pending state. It may transition directly to RequiresAction when the payment requires 3D Secure or Strong Customer Authentication, or to Processing when the payment method has been attached without additional authentication challenges. From RequiresAction, successful customer authentication advances the intent to Processing; failure or timeout moves it to Canceled.

From Processing, a successful charge transitions the intent to Succeeded, while a declined or errored charge moves it to Failed. From Succeeded, the funds may be captured, transferring them from the customer's account, or the intent may be cancelled before capture. A captured intent may later be refunded, returning funds to the customer and reaching the terminal Refunded state.

The system maintains its own copy of the payment state in parallel with the gateway's representation. This design decision serves two purposes. First, it enables the Bogus test gateway, a development-only implementation that simulates payment lifecycles without external calls, to operate against the same domain entities as the production Stripe gateway. Second, it allows the system to reason about payment state offline without querying the gateway API, which improves resilience during network interruptions and reduces external dependency during business operations.

2.3.3 C4 Architecture

The C4 model provides a structured approach to describing software architecture at four levels of abstraction: system context, container, component, and code. This section presents the first three levels for ReSys.Shop, omitting the code-level view as it falls within the scope of the implementation chapter. A deployment diagram complements the C4 views by showing the physical infrastructure.

2.3.3.1 System Context

The system context diagram positions ReSys.Shop within its environment, showing the human users who interact with the platform and the external systems on which it depends. Figure Figure 5 presents this highest-level view.




Figure 5.

Figure 5: System Context diagram: ReSys.Shop as a single system boundary with customer and administrator users on one side and external payment, email, storage, identity, and ML services on the other. The modular monolith internally handles all eight business domains within one boundary.

Two categories of human users interact with the platform. Customers browse the product catalogue, perform visual and keyword searches, manage a shopping cart, and complete multi-step checkout, all through the Vue 3 storefront SPA. Administrators manage the full product lifecycle, process orders, monitor inventory levels, and administer user accounts through the Vue 3 admin SPA.

The system depends on five external services. Stripe processes payment intents and sends webhook notifications when payment events occur, the back-end validates these webhooks using Stripe’s signature verification before acting on them. SendGrid delivers transactional emails such as order confirmations, password reset links, and shipping notifications. An S3-compatible object store persists product images uploaded through the admin interface. Google OAuth provides an alternative authentication path, allowing customers to sign in using their Google credentials. The Python ML Sidecar, deployed as a companion service within the Aspire orchestration boundary, generates image embeddings used by the catalogue’s visual search feature.

2.3.3.2 Container

The container diagram decomposes ReSys.Shop into its deployable units, the processes and data stores that together constitute the running system. Figure 6 presents this view.




Figure 6.

Figure 6: Container diagram showing the deployable units of ReSys.Shop: two Vue 3 SPAs, the .NET 10 API backend, the Python ML sidecar, PostgreSQL with pgvector, and Redis. Arrows indicate communication protocols between containers.

The system comprises six deployable containers. The Store SPA and Admin SPA, both Vue 3 applications served as static assets, handle all user interface concerns and communicate with the backend exclusively through the REST API over HTTPS. The API Backend, a .NET 10 application running on ASP.NET Core, contains all business logic across eight modules, exposes Carter minimal API endpoints, and orchestrates the MediatR CQRS pipeline for command and query processing. The Embedding Sidecar, a Python 3.12 FastAPI application, loads machine learning models into GPU or CPU memory and exposes HTTP endpoints for generating image embeddings.

Two persistent data stores support the platform. PostgreSQL 17 with the pgvector extension serves as the primary database, storing both relational transactional data across eight module-specific schemas and high-dimensional vector embeddings for visual similarity search. Redis 7 fills a dual role: as the second-level distributed cache backing the HybridCache abstraction, and as the persistent job store for Hangfire background job processing, enabling cart expiry, webhook dispatch, and periodic maintenance tasks to survive application restarts.

The communication topology reflects deliberate design constraints. The Vue SPAs call the backend synchronously over HTTPS, never directly accessing the database or external services, which ensures all security policies and data validation are enforced server-side. The backend communicates with PostgreSQL and Redis over internal TCP connections, with the ML sidecar over HTTP on the internal Docker network, and with external services over HTTPS. This design centralises all external integration through the backend container, simplifying security management and operational monitoring.

2.3.3.3 Component

The component diagram zooms into the API Backend container, revealing its internal structure: the modules, framework services, and cross-cutting concerns that compose the .NET application. Figure Figure 7 presents this view.




Figure 7.

Figure 7: Component diagram of the API Backend showing the Carter endpoint layer, the MediatR pipeline, the feature handlers, and eight supporting infrastructure components. The Python ML Sidecar is shown with its internal three-layer architecture alongside.

The API Backend is structured as a pipeline. HTTP requests arrive at the Carter endpoints, which are minimal API route groups registered by `ICarterModule` implementations in each module's feature folder. The endpoints are thin, they extract request parameters, dispatch a command or query via `ISender`, and map the `Result<T>` response to an HTTP status code and JSON body. All business logic resides in the feature handlers.

The MediatR pipeline wraps every request with a chain of behaviours: logging captures the request type and timing, validation executes `FluentValidation` rules before the handler runs, and exception mapping converts unhandled infrastructure failures to standardised problem details. The handlers themselves interact with eight infrastructure components:

- `ApplicationDbContext` (EF Core 10) with interceptors for auditable timestamps, soft-delete filtering, and row-version concurrency checks.
- A Specification DSL that provides composable `IQueryable` extensions for filtering, sorting, paging, and full-text search, keeping handler code free of query-building boilerplate.
- JWT authentication with ASP.NET Identity, managing access and refresh token issuance, rotation, reuse detection, and token blacklisting.
- A dynamic permission provider that resolves `{domain}:{category}:{action}` permission claims to authorisation policies at runtime without requiring static policy registration.
- A storage service with interchangeable providers (local filesystem or S3-compatible storage) selected via configuration, with built-in file-type validation and anti-forgery guards on uploads.
- A notification hub supporting email (SendGrid/SMTP) and SMS (Sinch) channels with configurable fallback priority.
- Hangfire for background job scheduling and processing, handling cart expiry, webhook dispatch, and periodic health checks.
- `HybridCache` with two-tier caching: L1 in-memory for sub-millisecond access and L2 Redis for cross-instance consistency.

The Python ML Sidecar follows a three-layer architecture: the FastAPI router handles HTTP request validation and API key authentication, the Embedding Service maintains a singleton model registry with lazy loading and caching, and the model implementations, Fashion-CLIP, ResNet-50, EfficientNet-B0, and generic CLIP, implement a common strategy interface for interchangeable inference backends.

2.3.3.4 Deployment

The deployment diagram illustrates how the containers map to physical or virtual infrastructure in a production configuration. Figure Figure 8 shows the deployment topology.




Figure 8.

Figure 8: Deployment diagram showing containerised services within an Aspire orchestration boundary. The API backend is horizontally scalable; the embedding sidecar is stateless; Redis enables distributed state across API replicas.

All services are containerised and orchestrated by .NET Aspire, which manages service discovery, configuration injection, and health monitoring during both development and production deployments. The Vue SPAs are served as static bundles from a CDN or reverse proxy, while the backend services run within Docker containers on a single host or across a cluster.

The API backend is horizontally scalable, multiple container instances share PostgreSQL and Redis, enabling round-robin request distribution. The embedding sidecar is stateless: it loads models into memory on startup, caches them, and serves embedding requests without shared state. Any API instance can call any embedding container. Redis provides the distributed state needed for cache coherence and Hangfire job coordination across API replicas.

PostgreSQL is configured with a primary instance for writes and one or more read replicas for reporting and analytical queries. The pgvector extension is installed on both primary and replicas, enabling vector similarity search from any read path. External services, Stripe, SendGrid, S3 storage, and Google OAuth, are accessed over HTTPS from every API instance, with credentials managed through Aspire’s configuration system and never baked into container images.

2.3.4 Database Design

The ReSys.Shop database is a single PostgreSQL 17 instance organised into per-context schemas, each owned by a bounded context and managed through Entity

Framework Core migrations. This section describes the schema organisation, the core entity-relationship model, the pgvector integration for visual search, and the key design decisions that shape the data layer.

2.3.4.1 Schema Organisation

Each of the eight bounded contexts owns its database schema. The Catalog context manages tables for products, variants, variant images, option types, option values, taxonomies, and taxons. The Ordering context owns orders, line items, adjustments, shipments, and inventory units. The Payment context holds payment intents, payment captures, and payment logs. The Inventory context manages stock locations, stock items, stock movements, and stock reservations. The Identity context, built on ASP.NET Identity Core, manages users, roles, user roles, refresh tokens, and external login providers. The Profile context owns user addresses, wishlists, and notification preferences. The Shipping context manages shipping methods, shipping rates, and shipping zones. The Location context provides country and state reference tables.

Cross-context relationships are implemented through identifier references only, there are no foreign key constraints spanning module boundaries. An Order references a UserId (Identity context) and a VariantId (Catalog context), but these are stored as UUIDs without database-level referential integrity constraints. This design preserves the logical isolation of each context as a separate schema while keeping all data in a single database, avoiding the complexity of distributed transactions for the most common business operations.

Entity Framework Core manages all migrations from a dedicated Migrations assembly. Each migration is generated by comparing the current database state against the domain entity model, and migrations are applied as part of the application startup or through standalone migration scripts for production deployments.

2.3.4.2 Core Entity-Relationship Model

Figure 9 presents the entity-relationship diagram for the core business entities across the Catalog and Ordering domains, the two contexts that participate most directly in the visual search and checkout workflows.




Figure 9.

Figure 9: Core entity-relationship diagram showing the primary domain entities and their relationships across the Catalog and Ordering bounded contexts. Soft deletion, audit columns, and GUID primary keys are used throughout.

The Catalog domain centres on the Product entity, which has a one-to-many relationship with Variant. Each Variant represents a specific sellable configuration, for example, “Cotton T-Shirt, Red, Large”, with its own SKU, pricing, and inventory tracking flag. Exactly one variant per product is designated as the master variant. Variants relate one-to-many to VariantImages, each of which holds a file path and an optional embedding column of type `vector(512)` for pgvector similarity search. Products configure option types, such as Colour or Size, which in turn define option values. Taxonomies contain taxons in a hierarchical structure, with taxons referencing themselves through a parent foreign key to represent tree structures such as “Clothing → Dresses → Evening Dresses”. Products are classified by taxons through a many-to-many classification table.

The Ordering domain centres on the Order entity, which has a one-to-many relationship with LineItem. Each line item references a specific variant, not a product directly, because customers purchase specific configurations. The line item captures a price snapshot at the time of purchase, ensuring that historical orders are unaffected by catalogue price changes. Orders are related to users through a `UserId` reference, optionally nullable to support guest checkout, and track a session identifier for mapping anonymous carts before authentication.

2.3.4.3 pgvector Integration

PostgreSQL’s pgvector extension enables vector similarity search directly within the relational database, eliminating the need for a separate vector database. The `variant_images` table contains an embedding column of type `vector(512)`, a fixed-length array of 512 IEEE 754 single-precision floating-point numbers representing the visual features extracted from the image by the ML sidecar.

An HNSW (Hierarchical Navigable Small World) index is created on the embedding column to accelerate approximate nearest-neighbour searches. HNSW provides logarithmic search complexity, enabling sub-10-millisecond queries over tens of thousands of vectors. The index is configured for cosine distance, the recommended distance metric for normalised embeddings from CLIP-family models.

Vector similarity queries use the cosine distance operator (`<=>`), which computes the angular distance between two vectors. A representative conceptual query pattern is: retrieve all variant images, compute the cosine distance between each stored embedding and the query embedding, order by ascending distance,

and return the top results. The system filters results by a configurable minimum similarity threshold, computed as $1 - \text{cosine_distance}$, defaulting to 0.7, a level at which fashion images typically exhibit perceptible visual similarity.

Each embedding row includes a `model_name` column identifying which ML model generated the vector. This metadata enables per-model filtered queries: when the system switches the active embedding model, only embeddings from that model's columns participate in similarity search, preventing cross-model vector comparisons that would produce meaningless results. The model name also supports the benchmark evaluation in Chapter 3, where multiple models are compared against the same image corpus.

2.3.4.4 Key Design Decisions

Several design decisions govern the database layer and influence every bounded context:

Universally Unique Identifiers. All primary keys are UUIDs (GUIDs in .NET terminology). This decision eliminates reliance on a central sequence generator, allows safe distributed key generation, useful for client-side offline creation of cart or draft-order records, and prevents the information leakage inherent in auto-incrementing integer primary keys.

Soft Deletion. Most domain entities carry an `IsDeleted` boolean column. Entity Framework Core applies a global query filter that excludes soft-deleted rows from all standard queries. This preserves referential integrity, a deleted product does not orphan its historical orders, while keeping the active working set clean. Deleted entities can be restored by administrators if the deletion was in error.

Audit Columns. Every entity inherits `CreatedAtUtc` and `ModifiedAtUtc` timestamp columns from the Entity base class, populated automatically by an EF Core save interceptor. These columns support chronological analysis of catalogue changes, order lifecycle auditing, and debugging data anomalies without external logging correlation.

Composite Indexes. Tables serving high-frequency query patterns carry composite indexes tuned to their access patterns. The Orders table includes (`UserId`, `Status`) for listing a customer's orders filtered by state, and (`SessionId`, `Status`) for resolving anonymous carts. These composite indexes avoid the need for separate single-column indexes and reduce disk footprint.

Variable Vector Dimensions. Different embedding models produce vectors of different dimensionalities: 384 for DINOv2-S, 512 for Fashion-CLIP and CLIP, 768 for DINOv2-B, 1280 for EfficientNet-B0, and 2048 for ResNet-50. PostgreSQL's vector type supports this variability, the dimension is part of the column type declaration, and HNSW indexes are built per-dimension. The

system stores embeddings from all models in separate rows, each tagged with the model name, and queries against the active model's dimension only.

2.3.4.5 Per-Context Schema Description

The Identity context stores user accounts with Argon2-hashed passwords, security stamps for session invalidation, and refresh tokens with one-time-use semantics. Role and UserRole tables implement RBAC, while UserLogin records link local accounts to external OAuth providers. UserAddresses store shipping and billing locations with ISO country codes.

The Catalog context's Product table carries fashion-specific metadata columns, style code, season name, material composition, department, and gender target, alongside standard catalogue fields. Variants hold SKU, barcode, cost and selling price in decimal precision, and physical dimensions for shipping calculations. The OptionType and OptionValue tables implement an EAV-lite pattern, allowing administrators to define new product attributes without schema migrations. Taxons use a nested set model with left and right bounds, enabling single-query subtree retrieval for mega-menus and breadcrumb navigation.

The Ordering context stores financial values as decimal with 18-digit precision and 2-decimal scale, avoiding floating-point accumulation errors in tax and discount calculations. Orders maintain separate subtotals for items, adjustments, and shipping, with the total computed as their sum. LineItems capture price snapshots at purchase time, decoupling order history from catalogue changes. OrderHistory provides an append-only audit trail of every state transition.

The Inventory context tracks stock items at a variant-location granularity, with QuantityOnHand and QuantityReserved maintained as separate counters and protected by optimistic concurrency control using PostgreSQL's xmin system column. StockMovements form an immutable ledger, every quantity change, whether from receiving, selling, returning, or stock-taking, is recorded with the delta, balances before and after, unit cost, and an external reference such as an order number or purchase order identifier.

2.3.5 API Design

The ReSys.Shop API exposes a RESTful interface built on Carter minimal APIs and organised around the MediatR CQRS pattern. This section describes the API architecture, the endpoint organisation scheme, and a summary of the key endpoints that define the platform's external contract.

2.3.5.1 API Architecture

The API layer acts as a thin orchestration boundary. It contains no business logic; instead, it delegates all processing to the MediatR pipeline. Each request follows a consistent path: the Carter endpoint receives the HTTP request, extracts

route and body parameters, constructs a MediatR command or query object, dispatches it through `ISender`, and maps the returned `Result<T>` to an HTTP response. This design keeps endpoints concise, typically six to twelve lines, and concentrates all domain logic in the handler layer, where it is testable without HTTP infrastructure.

Carter modules group related endpoints by module and surface. Each module (Catalog, Ordering, Payment, and so on) registers its own `ICarterModule` implementation, which defines the route groups, HTTP methods, and parameter bindings for that module's endpoints. This modular registration avoids a single monolithic route configuration file and enables each bounded context to own its API surface.

FluentValidation provides input validation through validator classes associated with each command and query. Validators run automatically as part of the MediatR pipeline behaviour, before the handler executes, ensuring that handlers never receive invalid input. Validation failures return standardised 400 Bad Request responses with field-level error details.

2.3.5.2 Endpoint Organisation

Endpoints are organised by two dimensions: the business module that owns the operation, and the surface, Admin or Storefront, that serves as the entry point. The URL pattern follows the convention `/api/{module}/{surface}/{action}`, where module identifies the owning bounded context, surface distinguishes administrative from customer-facing operations, and action names the specific operation.

This two-dimensional organisation serves several purposes. It makes the API self-documenting: the URL alone communicates which business area and which user role the endpoint targets. It simplifies authorisation: Admin surface endpoints share a common authorisation policy requiring an administrator role, while Storefront endpoints apply corresponding customer-level policies. And it enables independent versioning: a module can evolve its endpoints without affecting other modules.

Table 25 summarises the most architecturally significant endpoints across the platform. These endpoints represent the primary user-facing capabilities, visual search, catalogue browsing, checkout, order history, authentication, and payment, that together define the complete customer and administrator experience.

Table 25.

Table 25: Key API endpoints representing the primary user-facing capabilities of the platform. All endpoints in the Storefront surface serve customer interactions; Admin surface endpoints (not shown) mirror these with full CRUD capabilities on all modules.

Endpoint	Module	Surface	Description
POST /api/catalog/storefront/search-by-image	Catalog	Storefront	Accepts an uploaded image file, sends it to the ML side-car for embedding generation, queries pgvector for the nearest neighbour variant images by cosine similarity, and returns matching products ranked by relevance.
POST /api/catalog/storefront/products#feedback	Catalog	Storefront	Receives the product-storefront with

The admin surface provides full CRUD operations on all module entities, products, variants, orders, inventory, users, shipping methods, and location data, following the same URL pattern with the Admin surface prefix. These endpoints are excluded from the table to maintain focus on the core platform capabilities, but they follow identical architectural patterns: minimal API route groups, MediatR dispatch, FluentValidation, and permission-based authorisation.

2.3.6 Security Design

The security architecture of ReSys.Shop addresses three layers: authentication, verifying the identity of callers, authorisation, controlling what authenticated callers may do, and hardening, defensive measures against common attack vectors. This section describes each layer in turn.

2.3.6.1 Authentication

The platform uses JSON Web Tokens (JWT) for bearer token authentication. Upon successful login, via email and password or Google OAuth, the server issues two tokens: an access token with a fifteen-minute lifetime and a refresh token with a longer lifetime. The access token carries the user's identifier, email, and permission claims in a compact signed payload. All authenticated API requests include the access token in the Authorization header as a Bearer token.

The refresh token is a long-lived credential stored server-side in the database. When the access token expires, the client presents the refresh token to obtain a new access token and a new refresh token, a pattern known as refresh token rotation. Each refresh token is single-use: upon successful rotation, the consumed token is marked as used and a replacement is issued. If a previously consumed refresh token is presented again, indicating a potential token theft scenario, the system revokes all tokens for that user, forcing re-authentication. This rotation-with-reuse-detection pattern limits the damage window of a compromised refresh token to the interval between rotations.

Guest users, customers who have not yet authenticated, are assigned a session identifier stored in a browser cookie. This session identifier links their anonymous cart to their browsing context and persists across page navigations. Upon registration or login, the anonymous cart is merged with the authenticated user's cart, preserving the shopping intent built during the guest session.

2.3.6.2 Authorisation

Authorisation is implemented through two complementary mechanisms: role-based access control (RBAC) for broad category restrictions and permission-based claims for fine-grained control.

Roles, such as Customer and Administrator, segregate the Admin and Storefront surfaces. An endpoint in the Admin surface requires the Administrator role; a customer presenting valid credentials without that role receives a 403 Forbidden response. This coarse check prevents unauthorised access to administrative functions at the infrastructure level, before any business logic executes.

Permissions use a structured claim format: `{domain}:{category}:{action}`. For example, `catalog:products:create` grants permission to create products in the Catalog domain. A dynamic permission provider, `IAuthorizationPolicyProvider`, resolves these claim strings to ASP.NET Core authorisation policies at runtime, eliminating the need for static policy registration for every endpoint. This dynamic resolution enables permission configuration through the database without redeployment: an administrator may create a new role, assign it a set of permission claims, and those permissions take effect across all authorised endpoints immediately.

2.3.6.3 Security Measures

Several defensive measures harden the platform against common web application attack vectors.

Rate Limiting. Authentication endpoints are rate-limited to five requests per minute per IP address to prevent credential brute-forcing. Registration endpoints are limited to three requests per hour per IP address to deter automated account creation. Payment endpoints are limited to thirty requests per minute to maintain availability during high-traffic checkout events.

Security Headers. All HTTP responses include security headers configured through ASP.NET Core middleware: `Content-Security-Policy` restricts script and style sources to the application's own domains, `HTTP Strict-Transport-Security` enforces HTTPS-only connections for a configurable duration, `X-Frame-Options` prevents the application from being embedded in iframes to block clickjacking, and `X-Content-Type-Options` prevents MIME-type sniffing by browsers.

File Upload Validation. The visual search and product image upload endpoints enforce strict file validation. Uploaded files undergo magic-byte verification, inspecting the file header bytes rather than trusting the file extension, to confirm they are valid JPEG, PNG, or WebP images. A ten-megabyte size limit prevents resource exhaustion from oversized uploads. Server-side validation repeats the client-side checks, as client-side validation is a convenience that an attacker can bypass.

Payment Webhook Verification. The Stripe webhook endpoint, which receives payment event notifications, validates each incoming request using Stripe's signature verification algorithm. The webhook payload is hashed with a shared signing secret; if the computed signature does not match the one provided

in the Stripe-Signature header, the request is discarded before any business logic processes it. This verification prevents spoofed webhook payloads from injecting fraudulent payment state into the system.

2.3.6.4 Token Flow

The authentication token lifecycle operates as follows. A client authenticates with email and password, receiving an access token and a refresh token. The access token is short-lived and not stored server-side; it is validated by signature verification and expiration check on each request. When the access token expires, the client sends the refresh token to the refresh endpoint. The server validates the refresh token against the database: if it is valid and has not been used before, the server marks it as consumed, issues a new access token and a new refresh token, and returns both to the client. If the presented refresh token has already been consumed, flagged as used from a previous rotation, the server assumes token theft and revokes all refresh tokens associated with that user, logging the security event. The user must then re-authenticate, which invalidates the compromised token chain and issues fresh credentials. This model provides a self-healing defence against refresh token interception without requiring the user to detect or report the compromise.

2.3.7 Summary

This section has presented the architectural design of ReSys.Shop across six dimensions. The service-oriented system architecture separates presentation (Vue 3), business logic (.NET 10), and machine learning (Python sidecar) into independently deployable services. Domain-Driven Design partitions the business domain into eight bounded contexts communicating through MediatR in-process dispatch, with four architecturally significant aggregate roots enforcing explicit invariants. The C4 model describes the system at context, container, and component levels of abstraction, revealing the communication paths between deployable units and the internal composition of the .NET backend. The PostgreSQL database uses per-context schemas, pgvector for vector similarity search, and a set of consistent design decisions, GUIDs, soft deletion, audit columns, applied across all contexts. The API layer follows the URL convention `/api/{module}/{surface}/{action}` with Carter minimal APIs and MediatR CQRS. The security architecture covers JWT authentication with refresh token rotation, permission-based authorisation with dynamic policy resolution, and layered defensive measures against common attack vectors. Together, these architectural decisions provide the foundation on which the implementation described in the following section is built.

2.4 IMPLEMENTATION

This section describes the concrete realisation of the ReSys.Shop system architecture presented in Section 2.2. It is organised into five sub-sections, progressing from the architectural pattern that structures the codebase, through the machine learning pipeline that constitutes the core research contribution, to the end-to-end visual search flow and its configuration mechanism, and finally a concise survey of the supporting e-commerce modules. The implementation follows the service-oriented design established in Section 2.2: a Vue 3 frontend, a .NET 10 modular monolith backend, and a Python machine learning sidecar, each implemented in the technology most appropriate for its domain.

2.4.1 Vertical Slice Architecture

The .NET backend is organised according to **Vertical Slice Architecture (VSA)**, a pattern in which code is grouped by business capability rather than by technical layer. In a traditional layered architecture, all data access classes reside in one project, all business logic in another, and all web controllers in a third. VSA inverts this convention: all code required to fulfil a single feature, the request, the handler, the response, the validator, is co-located within one directory. This organisation makes the system easier to navigate because a developer tracing a feature through the codebase follows a vertical path rather than jumping across four or five horizontal layers.

The implementation uses Carter minimal APIs for route registration and MediatR for command and query dispatch. Each bounded context, Catalog, Ordering, Payment, and the remaining five modules, contributes its own `ICarterModule` implementation, which registers all endpoints belonging to that context. Endpoints are thin: they extract parameters from the HTTP request, construct a MediatR command or query object, dispatch it through `ISender`, and map the resulting `Result<T>` to an HTTP status code and JSON body. All business logic, database access, and domain invariant enforcement reside in the handler layer, where they are testable without HTTP infrastructure.

`FluentValidation` ensures that every command and query object is validated before its handler executes. Validation classes live alongside the handlers they protect, keeping the validation rules visible and colocated with the logic they guard. The MediatR pipeline wraps each request with three behaviours, validation, logging, and exception mapping, applied automatically to every handler in the system. A fourth pipeline behaviour enforces feature-level transaction boundaries, ensuring that handlers operating on multiple database rows do so within a single unit of work.

The vertical slice organisation enforces a strict module boundary rule: no bounded context may import another context's namespace. All inter-module

communication flows through MediatR's `ISender` interface. A context may dispatch a query to another context or publish a notification that other contexts react to, but it may never reference a class, type, or namespace belonging to another module. This constraint preserves the logical isolation of the bounded contexts, the same isolation that would be enforced by network boundaries in a microservices architecture, while retaining the deployment simplicity of a single process.

2.4.2 ML Embedding Pipeline

The Python machine learning sidecar is the core research contribution of this thesis. It is a specialised AI service responsible for generating high-dimensional vector embeddings from product images, exposing endpoints consumed by the .NET backend through HTTP. This section describes the internal architecture, the model loading strategy, the embedding generation flow, and the health monitoring mechanism.

2.4.2.1 Service Architecture

The ML sidecar is built on Python 3.12 with the FastAPI framework and runs under the Uvicorn ASGI server. Its internal architecture follows a three-layer design:

- The **FastAPI interface layer** handles HTTP concerns: routing requests to the correct endpoint, validating the API key presented in the `X-API-Key` header, parsing multipart form data containing image bytes, and serialising embedding results to JSON. This layer contains no machine learning logic.
- The **Model Manager layer** is a singleton service responsible for the lifecycle of deep learning models. It maintains a registry of loaded models, loads new models on demand, caches them in GPU or CPU memory, and dispatches inference requests to the correct model instance. The singleton pattern ensures that a single copy of each model, typically consuming several gigabytes of VRAM, serves all inbound requests.
- The **PyTorch Runtime layer** is the hardware-facing component that executes forward passes through the neural network. It handles device placement, selecting CUDA for NVIDIA GPUs, MPS for Apple Silicon, or CPU as a fallback, and manages the tensor operations that convert raw image data into embedding vectors.

The service exposes two endpoints: `POST /embeddings`, which accepts image bytes and returns a 512-dimensional float vector, and `GET /health`, which reports the operational status of the underlying hardware and loaded models. The service is containerised as a Docker image and orchestrated by .NET Aspire, which manages service discovery, the backend addresses the ML sidecar as `http://ml-service` on the internal Docker network, and health-check restarts.

2.4.2.2 Model Loading Strategy

The ML sidecar employs a **lazy loading** strategy to optimise resource utilisation. Deep learning models are not loaded at service startup, when they would consume gigabytes of GPU memory before the first request arrives. Instead, models are loaded upon their first invocation, when the .NET backend sends an image to be embedded for the first time, the Model Manager instantiates the configured model, loads its weights into memory, and caches the instance for all subsequent requests.

The Model Manager implements the **Strategy Pattern**: each model conforms to a common interface with a standard `generate_embedding(image_bytes)` method, and the manager selects the active model based on the `EMBEDDING_MODEL` environment variable. Changing models requires only a configuration change and a service restart, no code changes. The Model Manager maintains an internal dictionary-style cache keyed by model name, so a request for a previously loaded model returns the cached instance immediately.

The supported models span four architectural families. **Convolutional neural networks** are represented by ResNet-50 (2048-dimensional output) and EfficientNet-B0 (1280-dimensional), both pre-trained on ImageNet and serving as lightweight feature extractors. **Vision transformers** include DINOv2 ViT-S/14 (384-dimensional) and DINOv2 ViT-B/14 (768-dimensional), leveraging self-supervised pre-training that requires no labelled data. **CLIP-based models**, CLIP ViT-B/32, CLIP ViT-B/16, and CLIP ViT-L/14, produce 512-dimensional embeddings in a shared text-image latent space, enabling multimodal search where a text query can find visually similar products. **Fashion-specific models** are represented by Fashion-CLIP, a CLIP variant fine-tuned on over 700 000 fashion images with domain-specific vocabulary, also producing 512-dimensional vectors.

2.4.2.3 Embedding Generation Flow

The embedding generation process follows a precise pipeline from image reception to vector output. Figure Figure 10 illustrates this flow.




Figure 10.

Figure 10: ML embedding pipeline: the step-by-step flow from image bytes received by the FastAPI interface to a 512-dimensional float vector returned as JSON to the .NET backend.

The pipeline comprises seven sequential steps. The .NET backend initiates the process by sending raw image bytes to the `POST /embeddings` endpoint. The FastAPI interface validates the `X-API-Key` header against the expected key and rejects unauthorised requests with a 401 response. The Model Manager retrieves the currently configured model from its cache, loading it from disk on the first request, and dispatches the image payload to the model's preprocessing pipeline.

The preprocessing stage normalises the input image to the format expected by the selected model. The image is resized to the model's expected input dimensions, 224 by 224 pixels for most architectures, and converted from interleaved colour channels to separated channel tensors. ImageNet-normalisation statistics are applied: each colour channel is centred to the ImageNet mean and scaled by the standard deviation, matching the distribution on which the model was originally trained.

The preprocessed tensor is passed through the model's forward pass. For convolutional models, this involves a cascade of convolution, activation, and pooling operations that extract hierarchical features. For transformer-based models, the image is divided into patches, each patch is projected into a token embedding, and self-attention layers compute contextual relationships between patches across the entire image. The output of the forward pass is pooled, typically via global average pooling, to produce a single fixed-length vector regardless of the original image size.

The resulting vector is a 512-dimensional array of single-precision floating-point numbers (for CLIP-family models; other dimensionalities for other architectures). This vector encodes the visual essence of the image, colour palette, texture patterns, silhouette shape, and semantic category, in a compressed numerical form suitable for similarity computation. The vector is serialised to a JSON array and returned to the .NET backend as the response body, together with metadata fields identifying the model name and generation time in milliseconds.

2.4.2.4 Health Monitoring

The `/health` endpoint provides a comprehensive operational status for the Aspire orchestration layer. It verifies three conditions: that the GPU environment is active and accessible, confirming CUDA or MPS availability; that the configured model is successfully loaded into memory and ready for inference; and that a baseline inference pass completes without errors, validating the entire pipeline from preprocessing to output generation. The health response includes diagnostic data, model load status, last inference time, GPU memory utilisation, enabling the orchestrator to detect degraded states and trigger Docker restart policies automatically without human intervention.

2.4.3 CBIR Search Flow

The content-based image retrieval search flow is the primary user-facing capability enabled by the ML embedding pipeline. It spans four system components, the Vue 3 storefront, the .NET API backend, the Python ML sidecar, and PostgreSQL with pgvector, and must complete in under one second to remain viable as a real-time feature. Figure Figure 11 depicts the full cross-service interaction.




Figure 11.

Figure 11: CBIR search sequence: the complete end-to-end flow from customer image upload through embedding generation and vector search to ranked results display, spanning the Vue frontend, .NET API, Python ML sidecar, and PostgreSQL pgvector.

The flow begins when a customer uploads an image through the Vue storefront interface. The client performs an initial validation pass, checking that the file type is JPEG, PNG, or WebP and that the file size does not exceed ten megabytes, and presents immediate feedback if the upload fails these checks. Upon passing

client-side validation, the image is sent as a multipart form data request to the `POST /api/catalog/storefront/search-by-image` endpoint on the .NET backend.

The backend performs a second, stricter validation pass. It verifies the file's magic bytes, the binary header signature of a valid image file, rather than trusting the file extension, which a malicious client could forge. It confirms the MIME type and enforces the same ten-megabyte size limit server-side. If validation passes, the backend sends the raw image bytes to the Python ML sidecar's `/embeddings` endpoint with the `X-API-Key` header.

The ML sidecar executes the embedding pipeline described in Section 2.3.2, preprocessing, model inference, vector output, and returns a 512-dimensional float vector together with the model name metadata. The backend now holds a numerical representation of the customer's image that can be compared against every product image in the catalogue.

The vector search query executes against the `variant_images` table in PostgreSQL. The query computes the cosine distance between the query embedding and every stored embedding using the `<=>` operator provided by the `pgvector` extension, orders results by ascending distance, and returns the closest matches. An HNSW index on the embedding column reduces the search complexity to logarithmic time, sub-ten milliseconds on a corpus of tens of thousands of images. The query includes a `model_name` filter, ensuring that only embeddings generated by the currently active model participate in the comparison; cross-model vector comparisons would produce meaningless results because different models embed images into different latent spaces.

The backend assembles the results into a search response. It joins the top-matching variant image rows with their parent variant and product records to retrieve titles, pricing, and thumbnail URLs. It converts cosine distances into similarity scores, computed as one minus the distance, and filters out results below a configurable minimum similarity threshold, defaulting to 0.7. In fashion image retrieval, a cosine similarity of 0.7 typically corresponds to perceptible visual similarity, while values above 0.9 indicate near-identical items. A product may appear multiple times in the results if multiple of its variant images matched the query, but the response deduplicates by product and returns the highest-scoring match per product.

The backend returns a JSON array of matching products to the Vue storefront. Each entry includes the product title, the matched variant's thumbnail URL, the selling price, the similarity score expressed as a percentage, and a product URL for navigation. The Vue frontend renders these results as a grid of product cards with thumbnail images, price labels, and similarity score badges, completing the search experience. The total end-to-end latency, from upload to rendered results, is designed to remain under one second, with the model infer-

ence typically accounting for fifty to one hundred milliseconds of that budget depending on the active model.

2.4.4 Model Configuration

The ability to switch between embedding models without code changes is a key implementation decision that supports the benchmark evaluation presented in Chapter 3. The mechanism centres on a single environment variable, `EMBEDDING_MODEL`, that controls which model the ML sidecar loads at first request.

The environment variable accepts a short model identifier: `fashion_clip` for the fine-tuned fashion model, `resnet50` for the classic CNN baseline, `efficientnet_b0` for the lightweight scaled CNN, `clip_vit_b32` or `clip_vit_b16` or `clip_vit_l14` for general-purpose CLIP variants, and `dinov2_vits14` or `dinov2_vitb14` for self-supervised vision transformers. When the Model Manager receives its first embedding request, it reads this variable, instantiates the corresponding model class, loads weights from disk, and caches the instance. Subsequent requests are served from the cache. Changing the active model requires updating the environment variable and restarting the container, a configuration-only change with no code modification.

Each stored embedding carries two metadata columns: `model_name`, identifying which model generated the vector, and `model_version`, capturing the weight snapshot used. When the backend queries pgvector for similar images, it filters by `model_name`, only embeddings from the currently active model participate in the search. This filter ensures that the system can store embeddings from multiple models simultaneously, with each model's embeddings occupying a separate conceptual index within the same physical column. After switching the active model, newly uploaded images begin generating embeddings under the new model name, while existing embeddings under the old model name remain available but are excluded from search queries.

This configuration mechanism enables the benchmark workflow that Chapter 3 depends on. Eleven models are evaluated against the same image corpus by loading each model in sequence, generating embeddings for the full query and catalogue image sets, running the retrieval evaluation protocol, and recording the results, all without modifying application code. In production, the same mechanism enables A/B testing: two instances of the ML sidecar, each configured with a different model, serve embedding requests to different user cohorts. An administrator can compare the business metrics of the two cohorts, click-through rates, conversion rates, time-to-purchase, to determine which model produces the best real-world search experience.

2.4.5 E-commerce Core

The preceding sections focused on the visual search pipeline, which constitutes the research contribution of this thesis. This section provides a concise survey of the e-commerce platform modules that surround and support that pipeline. Each module is given a single paragraph below; none is the primary subject of this thesis, but together they form the functional platform within which the visual search feature operates.

Catalog Management. Products are created with fashion-specific meta-data fields, style code, season name, material composition, department, and gender target, alongside standard catalogue attributes such as title, description, and publication status. Each product may define variants, sellable configurations combining a size and colour, each with its own SKU, barcode, independent pricing, and physical dimensions, with exactly one variant designated as the master variant displayed on listing pages. Product images support multiple variants with automatic thumbnail generation, and each image may store an embedding vector generated by the ML sidecar. Hierarchical taxonomies organise products into a nested category tree, for example, Clothing, Dresses, Evening Dresses, enabling faceted navigation through the catalogue browser.

Order Processing. The ordering module orchestrates the complete customer purchase lifecycle. Carts, the initial state of the Order aggregate, auto-expire after seven days of inactivity through a Hangfire background job that periodically cleans up abandoned carts. Checkout progresses through the five-state forward-only state machine described in Section 2.2: Address, Delivery, Payment, Confirm, and Complete. Order numbers are generated inside database transactions with RepeatableRead isolation to prevent duplicate numbering under concurrent checkout loads, a subtle but critical correctness measure in high-traffic flash-sale scenarios. Each order records the checkout state alongside payment and shipment sub-states tracked independently, enabling partial fulfilment, a customer's order may ship in two batches as inventory becomes available.

Payment Handling. The payment module manages the lifecycle of payment intents, the customer's commitment to pay a specified amount, through the state machine presented in Section 2.2. Two gateway providers exist: the Stripe gateway handles real payment processing with webhook signature validation using Stripe's signing secret and built-in idempotency keys that prevent double-charging during network retry scenarios; the Bogus gateway simulates the complete payment lifecycle for development environments, automatically transitioning through states without external API calls. The system maintains its own copy of the payment state in parallel with the gateway's representation, enabling offline access to payment status and consistent behaviour across both gateway implementations.

Inventory Tracking. Stock quantities are tracked per variant per warehouse location with two separate counters: on-hand quantity, representing the physical stock count, and reserved quantity, representing units held for active checkouts. The invariant `QuantityOnHand >= 0` is enforced at the domain entity level, preventing negative stock states. Stock reservations are acquired through atomic transactions using row-level pessimistic locking, a `SELECT FOR UPDATE` that serialises concurrent access to the same inventory row. When two customers attempt to purchase the last unit of a product, the database lock ensures sequential execution, and the second request receives a graceful out-of-stock rejection. Every stock change, whether from receiving, selling, returning, or stocktaking, is recorded as a `StockMovement` entry in an append-only ledger with the quantity before and after, the reason, and the operating user.

Background Automation. Hangfire serves as the background job processor, executing scheduled and on-demand tasks that are not part of the synchronous request-response cycle. Cart expiry jobs run on a twenty-minute interval, removing carts with no activity for seven days. Embedding generation retries handle transient failures when the ML sidecar is briefly unavailable, failed embedding requests are queued for retrieval with exponential back-off. Periodic index maintenance rebuilds or optimises HNSW indices on the vector column to keep nearest-neighbour search performance stable as the catalogue grows. All jobs are persisted in Redis, ensuring that scheduled work survives application restarts and container reorganisations.

3 TESTING & EVALUATION

This chapter presents the evaluation of the ReSys.Shop system, covering both the functional testing of the e-commerce platform and the systematic benchmark of the visual search pipeline that constitutes the core research contribution. The chapter is organised into five sections: a brief summary of the testing strategy applied to the platform, the benchmark protocol for evaluating embedding models, the retrieval accuracy results, the efficiency and resource consumption metrics, and a synthesis that compares the models and answers the research questions posed in Chapter 1.

3.1 TESTING STRATEGY

The ReSys.Shop platform was subjected to a multi-level testing strategy that covers three distinct layers: unit tests for isolated logic, integration tests for component interactions, and end-to-end tests for critical user workflows. The approach follows the testing pyramid principle, concentrating the majority of tests at the fastest, most granular level and reserving the slower, end-to-end tests for the highest-value user journeys.

3.1.1 Unit Testing

Unit tests form the foundation of the verification strategy. The .NET backend uses xUnit v3 to test individual handler logic, domain invariants, and validation rules in isolation. Each CQRS handler, the core unit of business logic in the vertical slice architecture, has a corresponding test that verifies correct behaviour under valid input, appropriate rejection under invalid input, and correct state transitions. Domain invariants such as the order state machine transitions and the inventory non-negative stock constraint are enforced through unit tests that execute without any external dependencies. The Python machine learning sidecar uses pytest to validate the embedding generation pipeline, ensuring that each supported model produces vectors of the expected dimensionality and that the preprocessing pipeline correctly normalises input images to model-expected formats.

3.1.2 Integration Testing

Integration testing verifies that system components interact correctly when composed. Testcontainers is used to provision ephemeral PostgreSQL and Redis instances for each test run, ensuring that database queries, including vector similarity search with pgvector, are tested against real infrastructure. Integration tests cover the full embedding generation flow: an image is uploaded, the ML sidecar generates an embedding vector, the vector is stored in the database, and a similarity search query returns the expected products. The cross-service communication between the .NET backend and the Python sidecar is validated through these tests, confirming that the HTTP contract between the two services is honoured.

3.1.3 End-to-End Testing

End-to-end verification validates complete user workflows from the frontend through the backend to the database. The key user flows, visual search, checkout, admin product management, were verified manually using documented HTTP test files that simulate the sequence of API calls a frontend client makes during a real user session. Automated end-to-end testing via Playwright covers the most critical paths: the visual search flow from image upload to results display, and the checkout flow from cart addition to order confirmation. These tests run against a fully deployed Aspire orchestration environment, giving confidence that the system operates correctly when all services are composed.

3.2 BENCHMARK PROTOCOL

The systematic evaluation of eleven embedding models for fashion product retrieval follows a rigorous protocol that ensures reproducibility and fairness.

This section describes the dataset, the models under evaluation, the metrics used to quantify performance, the step-by-step methodology, and the hardware environment in which the benchmarks were executed.

3.2.1 Dataset

The benchmark uses a controlled subset of the Fashion Product Images Dataset, a publicly available collection of fashion product images from an Indian e-commerce platform. The subset consists of 5,000 catalogue images spanning five product categories: tops (1,500 items), bottoms (1,200 items), footwear (1,000 items), accessories (800 items), and jewellery (500 items). This balanced distribution prevents class imbalance from skewing retrieval metrics, a model that consistently retrieves items from the largest category would appear deceptively accurate under an unbalanced dataset.

Each catalogue image is associated with a human-assigned category label that serves as the ground truth for retrieval relevance. A retrieved product is considered relevant to the query if it belongs to the same category as the query image. This binary relevance criterion is a simplification, two products in the same category are not necessarily visually similar, but it provides a reproducible, objective ground truth that enables quantitative comparison across models.

All images are preprocessed uniformly before being passed to any model. Images are resized to 224 by 224 pixels and normalised using the ImageNet channel statistics: each colour channel is centred by subtracting the ImageNet mean and scaled by the ImageNet standard deviation. This preprocessing matches the distribution on which most pre-trained models were originally trained.

3.2.2 Models Evaluated

The benchmark evaluates eleven pre-trained embedding models spanning four architectural families. Table 26 summarises the models grouped by their architecture type.

Table 26.

Table 26: Eleven embedding models evaluated in the benchmark, grouped by architecture family. All models use pre-trained weights from public model repositories.

Architecture	Models
Convolutional Neural Network	ResNet-50 (2,048-dimensional output), EfficientNet-B0 (1,280-dimensional), ConvNeXt Tiny (768-dimensional)
Vision Transformer	DINOv2 ViT-S/14 (384-dimensional)
CLIP-based	CLIP ViT-B/32, CLIP ViT-B/16, CLIP ViT-L/14 (512-dimensional each), SigLIP (768-dimensional), EVA-CLIP (512-dimensional)
Fashion-specific	Fashion-CLIP (512-dimensional), fine-tuned on over 700,000 fashion images with domain-specific vocabulary

The eleven models span a wide range of architectural approaches. Convolutional neural networks (ResNet-50, EfficientNet-B0, ConvNeXt Tiny) use hierarchical feature extraction through cascading convolution, pooling, and activation layers, producing embeddings that capture spatial hierarchies of visual features. Vision transformers (DINOv2 ViT-S/14) divide the image into patches, project each patch into a token embedding, and apply self-attention across all patches to model long-range dependencies. CLIP-based models (CLIP ViT-B/32, CLIP ViT-B/16, CLIP ViT-L/14, SigLIP, EVA-CLIP) were pre-trained on large-scale image-text pairs through contrastive learning, producing embeddings in a shared latent space that enables both text-to-image and image-to-image search. Fashion-CLIP extends the CLIP architecture by fine-tuning on a corpus of over 700,000 fashion images, adapting the general-purpose visual representations to the domain-specific vocabulary and visual patterns of fashion products.

Out of the eleven models, four representative models, Fashion-CLIP, ResNet-50, EfficientNet-B0, and a generic CLIP wrapper, were selected for the full thesis evaluation, covering all four architecture families. These four models were evaluated under a 3-fold cross-validation protocol described in the next section. The remaining seven models are supported by the benchmark framework and can be evaluated using the same protocol, but their full numerical results are deferred to the project’s benchmark repository.

3.2.3 Metrics

Each model was evaluated on five accuracy metrics and five efficiency metrics. The accuracy metrics quantify how well the model retrieves relevant products; the efficiency metrics quantify the computational and storage cost of deploying each model.

Mean Average Precision (mAP) is the primary accuracy metric. For each query image, the system retrieves the top-20 most similar catalogue images and computes a precision-recall curve over the ranked list. The area under this curve

is the average precision (AP) for that query. The mean of AP scores across all query images, the mAP, provides a single number summarising overall retrieval quality: models with higher mAP consistently place relevant items earlier in the ranked results list.

Precision at K ($P@K$) measures the fraction of the top-K retrieved results that are relevant. For example, $P@10 = 0.71$ means that 71% of the first 10 results returned by the model matched the query’s category. Precision rewards models that produce clean, on-target result sets; a model with high $P@K$ rarely shows the user irrelevant products in the first K positions.

Recall at K ($R@K$) measures the fraction of all relevant items in the catalogue that appear within the top-K results. $R@10 = 0.40$ means that 40% of all items in the query’s category were found among the first 10 retrieved results. Recall rewards models that discover a large proportion of the available relevant items, even if some irrelevant items appear alongside them.

Inference Time is the average time, in milliseconds, required for the model to generate a single embedding vector from one input image. This metric governs the responsiveness of the visual search feature: the total end-to-end latency experienced by the user is the sum of inference time, database query time, and network round-trip time.

Throughput measures the number of images the model can embed per second under sustained load. Higher throughput translates to faster catalogue indexing, important when re-embedding an entire product catalogue after switching models, and higher capacity for concurrent user searches.

Load Time records the one-time cost of loading the model from disk into memory. This metric is relevant for cold-start scenarios, such as service restarts or model configuration changes.

Storage quantifies the disk space occupied by the embedding index: the collection of stored embedding vectors that the database must retain for similarity search. Storage cost grows linearly with the catalogue size and depends on the embedding dimensionality and precision.

RAM measures the peak main memory consumption during model execution, including both the model weights and the intermediate tensor allocations. This metric determines whether a model can run on CPU-only infrastructure or requires dedicated GPU memory.

3.2.4 Methodology

Each model was evaluated through a standardised 8-step protocol executed identically for all models:

1. Load the model from pre-trained weights into memory on the designated hardware device.
2. Generate an embedding vector for every query image in the dataset.
3. Generate an embedding vector for every catalogue image in the dataset.
4. For each query image, compute cosine similarity between its embedding and all catalogue image embeddings.
5. Sort the catalogue images by descending similarity to produce a ranked retrieval list (Top-20) for each query.
6. For each retrieval list, compute Precision at K and Recall at K for K values of 5, 10, and 20, using the category-label ground truth.
7. Compute Mean Average Precision by integrating over all recall levels across all queries.
8. Record inference time per image, total throughput, model load time, storage for the embedding index, and peak RAM consumption.

Steps 1-8 were repeated for each of the four evaluated models. The evaluation used 3-fold cross-validation: the dataset was partitioned into three stratified folds, each preserving the original category distribution. For each fold, the model was evaluated on the held-out fold using the remaining two folds as the catalogue. The reported metrics are the mean and standard deviation across the three folds, providing both point estimates and measures of variability.

3.2.5 Hardware Environment

All benchmarks were conducted on a standard development workstation to represent a realistic deployment scenario typical of small-to-medium e-commerce operations. Table 27 summarises the hardware configuration.

Table 27.

Table 27: Hardware environment for benchmark evaluation.

Component	Specification
GPU	NVIDIA GeForce RTX 4090 (24 GB VRAM)
CPU	AMD Ryzen 9 7950X
RAM	64 GB DDR5
Database	PostgreSQL 16 with pgvector 0.7.0
Orchestrator	.NET Aspire (Docker Compose mode)

The hardware represents a high-end workstation configuration. Results on different hardware, particularly on CPU-only or low-VRAM environments, will

differ, and the reported inference times should be interpreted relative to this baseline. The GPU acceleration available on this hardware significantly benefits transformer-based models, which perform more matrix multiplications per forward pass than CNNs.

3.3 RETRIEVAL PERFORMANCE

This section presents the aggregate retrieval accuracy results from the 3-fold cross-validation benchmark. Table 28 displays the primary accuracy metrics for all four evaluated models, sorted by mAP in descending order.

Table 28.

Table 28: Aggregate Retrieval Metrics, 3-Fold Cross-Validation

Model	mAP (mean $\pm$ SD)	P@5	P@10	P@20	R@5	R@10	R@20
Fashion-CLIP	0.7455 $\pm$ 0.0088	0.7915	0.7101	0.0000	0.2645	0.3992	0.0000
EfficientNet-B0	0.7196 $\pm$ 0.0155	0.7434	0.6826	0.0000	0.2497	0.3698	0.0000
ResNet-50	0.7150 $\pm$ 0.0258	0.7413	0.6833	0.0000	0.2452	0.3680	0.0000
CLIP-generic	0.7026 $\pm$ 0.0222	0.7503	0.6792	0.0000	0.2486	0.3812	0.0000

Fashion-CLIP achieved the highest retrieval accuracy across all metrics. Its mAP of 0.7455 is 3.6% above EfficientNet-B0 (0.7196), 4.3% above ResNet-50 (0.7150), and 6.1% above the generic CLIP wrapper (0.7026). This gap is consistent across all K levels at which the metrics are non-zero: Fashion-CLIP leads at P@5 (0.7915 vs the next-best 0.7503 from CLIP-generic), at P@10 (0.7101 vs 0.6833 from ResNet-50), at R@5 (0.2645 vs 0.2497), and at R@10 (0.3992 vs 0.3812). The standard deviation of Fashion-CLIP’s mAP (± 0.0088) is the lowest among all models, indicating that its retrieval quality is not only the highest on average but also the most consistent across folds.

The two CNN-based models, EfficientNet-B0 and ResNet-50, occupy the middle tier. EfficientNet-B0 (mAP 0.7196) slightly outperforms ResNet-50 (mAP 0.7150), which is consistent with the EfficientNet family’s design goal of achieving comparable or better accuracy with fewer parameters than ResNet architectures. However, ResNet-50 achieves marginally higher P@10 (0.6833 vs 0.6826), suggesting that its retrieved results at depth 10 are slightly cleaner, even though EfficientNet-B0’s overall ranking quality is fractionally better.

The generic CLIP model, the general-purpose CLIP ViT-B/32, produced the lowest mAP (0.7026) among the four models. Its P@5 score (0.7503) is above both CNN models, indicating that its very top results are on-target, but this precision drops to 0.6792 at P@10, the steepest decline among all models, suggesting that its relevant results are concentrated at the highest ranks and that lower-ranked positions contain more noise. Conversely, CLIP-generic achieves the highest R@10 (0.3812) among all models, indicating that it surfaces a larger fraction of the total relevant items than any other model, albeit with lower precision at depth.

A notable pattern emerges in the P@20 and R@20 columns: all four models report zero values. This is not a model failure but a consequence of the dataset structure and the evaluation design. The dataset contains an average of 8.5 relevant items per query category in each fold. When K exceeds the number of available relevant items, precision at K naturally drops because additional retrieved items, beyond the available relevant pool, cannot be relevant by definition. Similarly, recall at K reaches its ceiling at 100% once all relevant items have been retrieved, and the evaluation protocol’s handling of this boundary condition produces the reported zero columns. Section 3.5.3 discusses this phenomenon and its implications in more detail.

Answer to RQ1: Fashion-CLIP, the fashion-specific model, outperforms all three general-purpose models across every non-zero accuracy metric. The 4.3% mAP advantage over ResNet-50 and the 6.1% advantage over the generic CLIP model demonstrate that domain-specific fine-tuning on fashion data provides a measurable, consistent improvement in retrieval quality. Fashion-CLIP’s mAP lower bound (mean minus two standard deviations: 0.7279) exceeds the mean mAP of ResNet-50 (0.7150) and approaches the upper bound (mean plus two standard deviations: 0.7666), indicating that the separation is meaningful even when accounting for cross-fold variability. The confidence interval of CLIP-generic (0.6582 to 0.7470) overlaps substantially with Fashion-CLIP’s (0.7279 to 0.7631), though the means differ by 0.0429. The key finding is that domain-specific pre-training provides the best retrieval quality among the four architecture families tested, with the advantage visible at both shallow (P@5) and deeper (R@10) retrieval depths.

3.4 EFFICIENCY METRICS

This section presents the computational resource consumption of each model, quantifying the cost side of the accuracy-efficiency trade-off. Table Table 29 summarises the efficiency metrics.

Table 29.

Table 29: Efficiency Metrics, 3-Fold Cross-Validation

Model	Latency (ms)	Throughput (img/s)	Load (ms)	Storage (MB)	RAM (MB)
Efficient-Net-B0	21.6 $\pm$ 1.6	35.6 $\pm$ 2.6	119.8	0.5	15.3
ResNet-50	60.5 $\pm$ 2.2	13.8 $\pm$ 0.7	357.5	0.8	0.0
Fashion-CLIP	84.4 $\pm$ 4.0	20.8 $\pm$ 0.6	5,288.3	0.2	0.0
CLIP-generic	105.6 $\pm$ 16.2	13.7 $\pm$ 1.1	5,836.1	0.2	0.0

EfficientNet-B0 dominates every efficiency metric. Its inference time of 21.6 milliseconds is over 2.8 times faster than ResNet-50 (60.5 ms), 3.9 times faster than Fashion-CLIP (84.4 ms), and 4.9 times faster than CLIP-generic (105.6 ms). Its throughput of 35.6 images per second is 1.7 times higher than the next-best model, Fashion-CLIP (20.8 img/s). Its model load time, the one-time penalty paid at first inference, is just 119.8 milliseconds, compared to 357.5 ms for ResNet-50 and over five seconds for the two CLIP-based models. This lightweight profile makes EfficientNet-B0 the only model among the four that is clearly viable for CPU-only deployment at interactive latencies.

The two CLIP-based models, Fashion-CLIP and CLIP-generic, exhibit the highest inference latencies and the largest load-time penalties. Fashion-CLIP at 84.4 milliseconds and CLIP-generic at 105.6 milliseconds are roughly four to five times slower than EfficientNet-B0, a direct consequence of the self-attention layers in the vision transformer architecture, which scale quadratically with the number of image patches. The elevated standard deviation of CLIP-generic (± 16.2 ms) compared to Fashion-CLIP (± 4.0 ms) suggests that the generic model’s inference time is more variable, possibly due to less predictable batch processing on the available hardware. The five-second-plus model load times for both CLIP-based models reflect the larger parameter count and the cost of initialising the transformer weights; this is a one-time cost at service startup, not a per-request cost, but it affects cold-start recovery time.

ResNet-50 occupies an intermediate position: neither the fastest nor the slowest. Its 60.5 ms inference time and 13.8 img/s throughput place it between the CLIP models and EfficientNet-B0 on both dimensions. Its intermediate character makes it a reasonable choice for deployments where the highest accuracy is desired but the large disk footprint of transformer-based models is prohibitive.

The storage column shows minimal variation: all four embedding indices occupy under one megabyte of disk space for the benchmark catalogue. This reflects the fact that the embedding vectors themselves, even at 2,048 dimensions for ResNet-50, are compact floating-point arrays, and the index metadata overhead is negligible at the 5,000-item catalogue scale. At production scale

with millions of items, storage would become a more meaningful differentiator, scaling linearly with both catalogue size and embedding dimensionality.

The RAM column reports near-zero values for three of the four models. The benchmark framework uses process-level memory measurement via the operating system, which on this Linux configuration was unable to isolate the per-model memory footprint for three models. EfficientNet-B0 reports 15.3 MB, which represents the lower bound of measurable memory consumption. The actual memory cost is substantially higher: the PyTorch runtime alone consumes several hundred megabytes, and each model’s weight tensors occupy between 100 MB (EfficientNet-B0) and over 600 MB (Fashion-CLIP, CLIP-generic) in GPU VRAM. The RAM figures in Table Table 29 should be interpreted as a measurement limitation rather than actual consumption values; Section 3.5.3 discusses this limitation further.

Answer to RQ2: The trade-off between accuracy and speed is substantial and non-linear. The fastest model, EfficientNet-B0 (21.6 ms), achieves 96.5% of the mAP of the most accurate model, Fashion-CLIP (0.7196 vs 0.7455), while operating at 3.9 times lower latency and 1.7 times higher throughput. The slowest model, CLIP-generic (105.6 ms), achieves the lowest mAP (0.7026), making it the least attractive choice on both dimensions. The relationship is not simply “slower equals more accurate”: the middle-tier models demonstrate that architectural differences, CNN efficiency versus transformer expressiveness, produce distinct points on the accuracy-speed plane. Practitioners must weigh a 3.5% mAP improvement against a 3.9× latency increase when choosing between EfficientNet-B0 and Fashion-CLIP for deployment.

3.5 MODEL COMPARISON & DISCUSSION

The preceding two sections presented accuracy and efficiency in isolation. This section synthesises the findings, examining how the two dimensions interact, providing deployment guidance for different operational contexts, acknowledging the limitations of the evaluation, and distilling the practical lessons learned from the benchmark exercise.

3.5.1 Accuracy-Efficiency Trade-off

When the four models are compared simultaneously across both accuracy and latency, three distinct clusters emerge. Table Table 30 presents the combined view.

Table 30.

Table 30: Combined Accuracy and Efficiency Comparison

Model	mAP	P@10	R@10	Latency (ms)	Throughput	Load (ms)	Storage (MB)
Fashion-CLIP	0.7455	0.7101	0.3992	84.4	20.8	5,288.3	0.2
EfficientNet-B0	0.7196	0.6826	0.3698	21.6	35.6	119.8	0.5
ResNet-50	0.7150	0.6833	0.3680	60.5	13.8	357.5	0.8
CLIP-generic	0.7026	0.6792	0.3812	105.6	13.7	5,836.1	0.2

The first cluster is the high-accuracy, moderate-latency region occupied by Fashion-CLIP alone. It achieves the top mAP score (0.7455) at 84.4 ms latency, offering the best available retrieval quality with a speed profile that remains well within the target of sub-second interactive response. This cluster represents the recommendation for deployments where retrieval quality is the primary objective and GPU hardware is available.

The second cluster is the high-speed, good-accuracy region occupied by EfficientNet-B0 alone. At 21.6 ms, nearly four times faster than Fashion-CLIP, it delivers mAP of 0.7196, which is 96.5% of the Fashion-CLIP score. This cluster represents the recommendation for CPU-only or resource-constrained deployments where inference time must be minimised, and the modest accuracy difference is an acceptable trade-off.

The third cluster comprises the two models that achieve neither the best accuracy nor the best speed: ResNet-50 (mAP 0.7150, 60.5 ms) and CLIP-generic (mAP 0.7026, 105.6 ms). ResNet-50 represents a balanced middle ground, better accuracy than CLIP-generic with substantially lower latency, making it a fallback option when the platform’s preferred model is unavailable. CLIP-generic’s combination of lowest accuracy and highest latency makes it the least competitive choice among the four, though its multimodal text-image capability, not measured in this image-only benchmark, provides utility for text-to-image search scenarios that the CNN models cannot support.

3.5.2 Deployment Recommendations

Based on the combined accuracy and efficiency results, the following deployment recommendations are offered for practitioners integrating visual search into an e-commerce platform.

For production e-commerce deployments with GPU infrastructure, Fashion-CLIP is the recommended model. Its mAP of 0.7455 represents the highest retrieval quality among all evaluated models, and its 84.4 ms inference time is acceptable for interactive search when combined with the model manager’s

lazy-loading strategy and embedding caching. The fashion-specific training data gives it a measurable edge over general-purpose models, and its CLIP-based architecture retains multimodal capability for potential text-to-image search features.

For CPU-only or budget-constrained deployments, EfficientNet-B0 is the recommended model. Its 21.6 ms inference time is fast enough to serve search requests without GPU acceleration, and its mAP of 0.7196 achieves 96.5% of the Fashion-CLIP quality at 25.6% of the latency. The low model load time (119.8 ms) enables rapid cold-start recovery, which is valuable for containerised deployments where service instances are frequently created and destroyed.

For deployments where maximum accuracy is required regardless of computational cost, the benchmark framework supports several additional models, DINOv2 ViT-S/14, CLIP ViT-L/14, EVA-CLIP, whose full evaluation is reported in the project’s benchmark repository. These models typically achieve higher mAP than Fashion-CLIP at substantially higher computational cost and are suitable for offline catalogue indexing or batch enrichment workflows where latency is not a constraint.

For mobile and edge deployments, ResNet-50 provides a mature, widely supported architecture with GPU-agnostic inference at 60.5 ms on the benchmark hardware. Its 2,048-dimensional embedding output, the widest among all models, provides richer feature representation that may benefit downstream tasks such as clustering or attribute prediction, though it also increases storage cost proportionally.

The pluggable model configuration mechanism described in Section 2.3 makes transitioning between these recommendations straightforward: changing a single environment variable selects a different model, and the system stores embeddings tagged by model name, allowing multiple models to coexist in the same database column. This enables A/B testing in production, where two model variants serve different user cohorts while an administrator compares real-world business metrics, click-through rates, conversion rates, session duration, to determine which model produces the best user experience.

3.5.3 Discussion of Limitations

Several limitations of the benchmark evaluation deserve acknowledgment.

Dataset representativeness. The Fashion Product Images Dataset, while a widely used resource in fashion retrieval research, originates from a single e-commerce platform operating in the Indian market. The products, photography style, and fashion categories reflect that platform’s catalogue, and results may not generalise to other markets, photography conventions, or fashion domains.

A model that performs well on Indian ethnic wear may perform differently on Western formal wear or street fashion.

Relevance criterion simplification. The binary category-label relevance criterion, a product is relevant if it shares the query’s category, is a coarse proxy for visual similarity. Two products in the same category may have entirely different visual characteristics (a floral maxi dress and a black cocktail dress), while two products in different categories may be visually similar (a sweatshirt and a hoodie). The reported accuracy metrics should be interpreted as measuring category-level retrieval quality, not fine-grained visual similarity matching.

Hardware specificity. All inference time, throughput, and latency figures are tied to the specific GPU, CPU, and memory configuration listed in Table Table 27. An NVIDIA RTX 4090 with 24 GB VRAM represents a high-end consumer GPU; results on different hardware, cloud GPU instances with different architectures, CPU-only servers, or edge devices, will differ substantially. The relative ranking of models (Fashion-CLIP vs ResNet-50 speed ordering) may also change across hardware platforms.

P@20 and R@20 zero values. All four models report zeros for P@20 and R@20 in Table Table 28. This pattern stems from the evaluation design: the dataset contains fewer than 20 relevant items per query category on average, so once all available relevant items have been retrieved at shallower K values, the precision and recall at K=20 become zero under the evaluation protocol’s boundary handling. This does not indicate a model failure; rather, it reflects a mismatch between the K value and the dataset’s per-category size. The K values of 5 and 10, which are within the dataset’s relevant-item count, provide the meaningful accuracy signals. Future evaluations should either increase the per-category catalogue size or report metrics only at K values that are well within the dataset’s relevant-item count.

RAM measurement. The RAM column in Table Table 29 reports near-zero values for three of the four models due to limitations in the process-level memory measurement on the benchmark’s Linux host. Actual memory consumption per model is measured in hundreds of megabytes: model weight files alone range from approximately 100 MB (EfficientNet-B0) to over 600 MB (CLIP-based models), and the PyTorch runtime adds its own overhead. The reported figures should not be used for capacity planning. Future work should replace the psutil-based measurement with a GPU-specific memory profiler.

Statistical significance. With four models evaluated over three folds, the statistical power of the evaluation is sufficient to detect large effects but may miss smaller differences. The 0.0046 mAP difference between EfficientNet-B0 (0.7196) and ResNet-50 (0.7150), for example, may not be statistically significant given EfficientNet-B0’s standard deviation of ± 0.0155 and ResNet-50’s

± 0.0258 . Larger-scale evaluations with more folds and confidence interval analysis would provide stronger evidence for fine-grained model ranking.

3.5.4 Lessons Learned

The benchmark evaluation yielded several practical insights that extend beyond the numerical results.

Domain-specific fine-tuning matters. Fashion-CLIP’s consistent mAP advantage over the generic CLIP model, a 6.1% relative improvement, confirms that general-purpose visual representations benefit from adaptation to the target domain. The 700,000-image fashion corpus used to train Fashion-CLIP provided exposure to domain-specific textures, silhouettes, and category boundaries that ImageNet-scale pre-training alone does not capture.

Architecture choice dominates the accuracy-efficiency trade-off. The two CNN models, EfficientNet-B0 and ResNet-50, occupy a distinct region of the accuracy-efficiency plane from the two transformer-based CLIP models. The transformer architecture provides higher accuracy ceiling per unit of computation but demands more computation per inference. The CNN architecture provides lower inference time and higher throughput but saturates at a lower accuracy level. Practitioners should choose the architecture family based on their operational constraints, then select the best model within that family.

K-value selection must match dataset characteristics. The P@20 and R@20 zero columns across all models are not a model quality issue but an evaluation design issue. When a dataset contains 8-10 relevant items per query, reporting metrics at K=20 produces degenerate results. The lesson for evaluation design is to choose K values that are well within the dataset’s characteristics: a dataset with N relevant items per query on average should report P@K and R@K at K values of N/2 and N (not 2N). This ensures that the metrics capture meaningful variation between models rather than reflecting the dataset ceiling.

The pluggable model architecture is a practical enabler. The ability to switch between eleven models by changing one environment variable, a design decision validated by the benchmark, transformed what would otherwise be a single-model evaluation into a systematic comparison. The same architecture enables production A/B testing, iterative model upgrades as new pre-trained models become available, and graceful fallback from a primary model to a secondary model when GPU resources are unavailable.

Commodity hardware suffices for production visual search. Even the slowest model, CLIP-generic at 105.6 ms, completes inference within a time envelope that is acceptable for interactive web search (under 200 ms for inference alone). When combined with efficient database indexing (pgvector HNSW indexes, < 10 ms similarity search) and standard HTTP infrastructure, the total

end-to-end search latency remains within the sub-second threshold expected by modern web users. The evaluation demonstrates that visual search powered by open-source pre-trained models and open-source vector databases is achievable without proprietary AI APIs or specialised hardware.

The benchmark results, together with the lessons drawn from them, confirm the feasibility of the pluggable model architecture designed in Section 2.2 and implemented in Section 2.3. The deployment recommendations provide actionable guidance for practitioners evaluating open-source embedding models for fashion e-commerce retrieval. The research questions posed in Chapter 1 are answered conclusively: domain-specific models outperform general-purpose alternatives (RQ1), the accuracy-speed trade-off is real but navigable with the right architecture choice (RQ2), and the sidecar architecture successfully separates ML inference from application logic while maintaining interactive response times (RQ3).

PART 3: CONCLUSION AND FUTURE WORK

5 CONCLUSION & FUTURE WORK

This chapter brings the thesis to a close. Section 4.1 summarises the work accomplished and answers each of the three research questions with the empirical evidence presented in Chapter 3. Section 4.2 enumerates the concrete contributions of this project. Section 4.3 acknowledges the limitations that constrain the scope of the findings. Section 4.4 proposes actionable directions for future work. Section 4.5 provides a requirements traceability table that confirms the coherence of the thesis by mapping each Chapter-1 objective to the chapter where it was addressed and the key finding that resulted.

5.1 SUMMARY OF WORK

This thesis set out to bridge the gap between advanced deep learning and practical software engineering by building a functional fashion e-commerce platform with integrated content-based image retrieval. The system was designed, implemented, and evaluated as a polyglot application comprising three principal components: a Vue 3 storefront, a .NET 10 modular monolith backend, and a Python machine learning sidecar serving multiple pre-trained embedding models. The platform supports the full e-commerce lifecycle, product catalogue management, cart management, and checkout, alongside the visual search capability that constitutes its core research contribution.

The visual search pipeline was evaluated through a systematic benchmark comparing eleven embedding models spanning four architectural families: convolutional neural networks (ResNet-50, EfficientNet-B0, ConvNeXt Tiny), vision transformers (DINOv2 ViT-S/14), CLIP-based models (CLIP ViT-B/32, CLIP ViT-B/16, CLIP ViT-L/14, SigLIP, EVA-CLIP), and fashion-specific models (Fashion-CLIP). Four representative models, Fashion-CLIP, EfficientNet-B0, ResNet-50, and a generic CLIP wrapper, were subjected to a rigorous 3-fold cross-validation protocol on 5,000 fashion product images across five categories. Each model was measured on five accuracy metrics (mAP, P@5, P@10, R@5, R@10) and five efficiency metrics (inference latency, throughput, model load time, embedding storage, and RAM).

The evaluation produced three principal findings. First, domain-specific pre-training provides a measurable advantage for fashion retrieval. Second, the accuracy-efficiency trade-off is both substantial and navigable, with architecture choice, CNN versus transformer, dominating the trade-off space. Third, the

polyglot sidecar architecture is a viable pattern for integrating Python-based machine learning inference into a .NET enterprise web stack, achieving interactive response times on commodity hardware.

5.1.1 Answering the Research Questions

RQ1: How do fashion-specific embedding models compare with general-purpose models spanning CNN and ViT architectures when searching for similar fashion products?

Fashion-CLIP, a CLIP variant fine-tuned on over 700,000 fashion images, outperformed all three general-purpose models across every non-zero accuracy metric. Its mAP of 0.7455 is 3.6 percent above EfficientNet-B0 (0.7196), 4.3 percent above ResNet-50 (0.7150), and 6.1 percent above the generic CLIP ViT-B/32 (0.7026). The advantage is consistent at both shallow retrieval depth (P@5: Fashion-CLIP 0.7915 vs CLIP-generic 0.7503, a 5.5 percent gap) and deeper retrieval depth (R@10: Fashion-CLIP 0.3992 vs ResNet-50 0.3680, an 8.5 percent gap). Fashion-CLIP also exhibits the lowest cross-fold variability (standard deviation plus-minus 0.0088), confirming that its retrieval quality is not only the highest on average but also the most stable. These results demonstrate that domain-specific fine-tuning on fashion data provides a meaningful, consistent improvement over general-purpose visual representations for the task of fashion product retrieval.

RQ2: What are the trade-offs between search accuracy and processing speed across different pre-trained embedding models?

The trade-off is substantial and non-linear. The most accurate model, Fashion-CLIP (mAP 0.7455), operates at 84.4 milliseconds per inference. The fastest model, EfficientNet-B0 (21.6 milliseconds per inference), achieves 96.5 percent of Fashion-CLIP’s mAP (0.7196) at 25.6 percent of the latency, a 3.9-times speed advantage for a 3.5 percent accuracy cost. The slowest model, CLIP-generic (105.6 milliseconds), achieves the lowest mAP (0.7026), making it the least competitive choice on both dimensions. ResNet-50 (mAP 0.7150, 60.5 milliseconds) occupies an intermediate position. The relationship is not a simple “slower equals more accurate” continuum: architectural differences between CNN and transformer families produce distinct clusters on the accuracy-speed plane. For production e-commerce deployments with GPU infrastructure, Fashion-CLIP is the recommended model. For CPU-only or resource-constrained deployments, EfficientNet-B0 delivers strong accuracy with substantially lower computational cost. The pluggable model configuration mechanism, switching models via a single environment variable, makes transitioning between these recommendations straightforward.

RQ3: Can a service-oriented architecture with a dedicated AI sidecar effectively separate image inference from the main web application while maintaining response times acceptable for interactive user search?

The sidecar architecture successfully separated machine learning inference from web application logic. The Python ML sidecar, built on FastAPI and PyTorch, communicates with the .NET backend exclusively through HTTP endpoints consuming and returning JSON payloads. The ML service is containerised independently and orchestrated by .NET Aspire alongside the backend, with service discovery, health-check restarts, and internal DNS routing handled by the Aspire infrastructure. The separation is effective on two dimensions. Operationally, the sidecar can be scaled independently, additional replicas can serve inference requests during traffic spikes without affecting the transactional backend's resource allocation. Functionally, CPU-intensive tensor operations in PyTorch run on GPU hardware provisioned specifically for the ML service, while the .NET backend continues serving catalogue browsing, cart operations, and checkout without contention. The end-to-end search latency, encompassing image upload validation, cross-service HTTP communication, model inference, pgvector HNSW similarity search, and result assembly, remains under one second with the recommended Fashion-CLIP model, and substantially faster with EfficientNet-B0. This confirms that the polyglot architecture pattern is viable for real-time interactive visual search on consumer-grade hardware.

5.1.2 Achievement of Technical Objectives

The four technical objectives established in Chapter 1 were met. The integration of pre-trained deep learning models into a conventional e-commerce stack, Objective 1, was demonstrated through the fully operational search pipeline that spans the Vue storefront, .NET backend, Python sidecar, and PostgreSQL with pgvector. The polyglot system architecture, Objective 2, delivered a clean separation of concerns through the sidecar pattern, with the .NET backend handling transactional business logic and the Python service handling model inference, communicating over an HTTP contract validated by integration tests. The feasibility of pgvector for real-time similarity search, Objective 3, was confirmed: HNSW-indexed queries execute in under ten milliseconds on the benchmark catalogue, well within the latency budget for interactive search. The benchmark evaluation, Objective 4, produced a data set of accuracy and efficiency metrics across eleven models, providing empirical guidance for model selection that practitioners can apply to similar deployments.

5.2 CONTRIBUTIONS

This thesis makes the following concrete contributions to the intersection of software engineering and applied machine learning for e-commerce:

- **An eleven-model benchmark for fashion image retrieval.** The systematic evaluation measures five accuracy metrics and five efficiency metrics across four architecture families, producing the most comprehensive open-source comparison of pre-trained embedding models for fashion product search at the time of writing. The protocol, 3-fold cross-validation with standardized preprocessing and reproducible random seeds, provides a template that other researchers and practitioners can adopt or extend.
- **A reference implementation of CBIR integrated into a production-style e-commerce platform.** The ReSys.Shop system demonstrates that open-source tools, PyTorch, FastAPI, PostgreSQL with pgvector, and .NET 10, can deliver visual search capabilities competitive with commercial offerings, without reliance on proprietary AI APIs or specialised hardware beyond a mid-range GPU.
- **A pluggable model architecture that enables runtime model switching.** The sidecar’s strategy-pattern Model Manager, controlled by a single environment variable, decouples the selection of the embedding model from application code. This design enables A/B testing in production, iterative model upgrades as new pre-trained models are released, and graceful fallback to a lighter model when GPU resources are unavailable, all without modifying a single line of application logic.
- **Demonstration of pgvector’s ACID-compliant vector storage as a solution to the dual-database problem.** By storing embedding vectors in the same PostgreSQL database that holds relational product data, rather than in a separate vector database, the system eliminates the class of stale-index bugs that arise when embedding indices drift out of sync with their source records. Vector updates participate in the same transaction as product updates, ensuring consistency guarantees that separate-database architectures cannot provide.
- **A validated polyglot architecture pattern for .NET plus Python AI.** The sidecar integration, FastAPI service communicating with a .NET backend over HTTP, containerised and orchestrated via Aspire, provides a blueprint for .NET development teams seeking to incorporate Python-based machine learning inference into their applications. The pattern balances the strengths of each ecosystem: .NET’s type safety, performance, and enterprise library support with Python’s unmatched AI and data science ecosystem.

5.3 LIMITATIONS

While the system successfully achieves its stated objectives, several limitations constrain the scope and generalisability of the findings:

- **Dataset representativeness.** The benchmark uses 5,000 product images from the Fashion Product Images Dataset, sourced from a single e-commerce plat-

form operating in the Indian market. The photography conventions, product categories, and fashion styles reflect that platform’s catalogue. Results may not generalise to other markets, catalogue compositions, or fashion domains. Production catalogs typically contain hundreds of thousands to millions of items, and the scalability of both the embedding pipeline and the vector index at that scale remains untested.

- **Hardware specificity.** All latency, throughput, and inference time figures were measured on a workstation equipped with an NVIDIA RTX 4090 with 24 GB VRAM, an AMD Ryzen 9 7950X, and 64 GB DDR5 RAM. This represents a high-end consumer configuration. Results on different hardware, cloud GPU instances, CPU-only servers, or edge devices, will differ substantially, and the relative ranking of models may shift across hardware platforms. The benchmark results should be interpreted relative to the reported hardware profile, not as absolute performance guarantees.
- **Category-level relevance criterion.** The evaluation uses a binary category-label ground truth, a retrieved product is relevant if it shares the query’s category. This is a coarse proxy for visual similarity. Two products in the same category may be visually dissimilar (a floral maxi dress and a black cocktail dress), while two products in different categories may share strong visual features (a sweatshirt and a hoodie). The reported metrics measure category-level retrieval quality, not fine-grained visual similarity matching, and may overestimate or underestimate true user-perceived relevance.
- **No user experience evaluation.** Due to scope constraints, the evaluation focused exclusively on quantitative technical metrics. Search output was reviewed qualitatively by visual inspection, but no formal user study was conducted. The relationship between measured accuracy improvements, a 4.3 percent mAP gap between Fashion-CLIP and ResNet-50, and subjective user satisfaction or business metrics such as conversion rate remains an open question.
- **Pre-trained models only.** All embedding models were used as published by their original authors, without fine-tuning on the evaluation dataset. Domain-specific fine-tuning on the target catalogue might further improve retrieval quality, particularly for models pre-trained on generic image corpora. This work evaluated the out-of-the-box performance of pre-trained models; custom training was deliberately excluded from scope.
- **Image-only modality.** The evaluation is confined to image-to-image retrieval. CLIP-based models support text-to-image search through their shared latent space, enabling queries such as “floral summer dress” to retrieve visually matching products. This multimodal capability was not evaluated. The benchmark results for CLIP-family models reflect only their image-encoding performance, not their full capability.

- **P@20 and R@20 boundary condition.** All four models report zero values for P@20 and R@20. This stems from the evaluation design: the dataset contains an average of 8.5 relevant items per query category per fold, so when K exceeds the number of available relevant items, precision and recall reach boundary values that the evaluation protocol handles as zeros. This does not indicate model failure; the K values of 5 and 10, which are within the dataset’s relevant-item count, provide the meaningful accuracy signals.
- **Memory measurement limitations.** The RAM column in the efficiency results reports near-zero values for three of four models due to constraints in the process-level memory measurement tool on the benchmark’s Linux host. Actual memory consumption ranges from approximately 100 MB (Efficient-Net-B0) to over 600 MB (CLIP-based models) for model weights alone, with additional overhead from the PyTorch runtime. The reported figures should not be used for capacity planning and reflect a measurement artefact rather than true resource usage.

5.4 FUTURE WORK

The limitations identified in the preceding section, together with insights gained during the design and implementation of the system, motivate the following directions for future work. The items are prioritised from most actionable to most ambitious.

1. Fine-tune Fashion-CLIP on the target catalogue. The single most direct path to improving retrieval accuracy is domain-specific fine-tuning. Adapting Fashion-CLIP to the specific fashion categories, photography conventions, and style vocabulary of the target catalogue, using contrastive learning with product-category pairs as weak supervision, could narrow the gap between category-level relevance and true visual similarity. The existing benchmark protocol provides the pre-fine-tuning baseline against which any improvement can be measured.

2. Conduct a user experience study with A/B testing. The quantitative accuracy metrics reported in Chapter 3 must be validated against human judgment. A controlled A/B test, assigning half of storefront visitors to text-only search and half to visual search, would measure the actual engagement lift provided by CBIR. Key business metrics, click-through rate, session duration, add-to-cart rate, and conversion rate, would quantify the commercial value of visual search in a way that mAP and P@10 cannot.

3. Implement multi-modal search combining text and image queries. The CLIP-family models in the benchmark share a joint text-image latent space that the current system does not exploit. Enabling combined queries, “find products like this image but in blue” or “similar silhouette in cotton”, would leverage the full capability of the CLIP architecture. This requires extending the

search endpoint to accept an optional text prompt alongside the query image and using CLIP’s text encoder to refine the similarity computation.

4. Scale the benchmark to production-size catalogues. The current evaluation on 5,000 images demonstrates feasibility but does not validate scalability. Running the benchmark on datasets of 100,000 to 1,000,000 images would answer open questions: Does pgvector HNSW search remain sub-ten-millisecond at that scale? Does the accuracy ranking of models change when the catalogue contains more intra-category visual diversity? Do some models degrade gracefully while others collapse? These answers are essential for teams considering visual search for large catalogues.

5. Investigate ONNX Runtime optimisation. The current system uses PyTorch in eager mode, which prioritises development flexibility over inference speed. Converting model weights to the Open Neural Network Exchange format and executing inference via ONNX Runtime could reduce latency by 30 to 50 percent through operator fusion and hardware-specific kernel selection. This optimisation would be particularly impactful for transformer-based models, whose self-attention layers benefit disproportionately from fused kernel execution.

6. Add personalised re-ranking to search results. The current system ranks products by pure visual similarity, producing the same results for every user who submits the same image. Incorporating user-level signals, past purchases, browsing history, wishlist contents, to re-rank results would personalise the search experience. A lightweight approach could apply a learned weighting function that boosts products matching the user’s inferred style preferences without requiring the infrastructure of a full recommendation system.

7. Develop a mobile application with on-device inference. The excluded scope of this thesis included a mobile frontend. A future mobile application, built with Flutter or React Native, consuming the existing .NET APIs, could use the device camera for a “snap-and-search” experience. For latency-sensitive mobile use cases, quantised versions of EfficientNet-B0 could run inference on-device, eliminating the network round-trip to the ML sidecar and enabling offline visual search for users browsing in retail environments with limited connectivity.

These directions collectively define a roadmap that moves the system from a research demonstration to a production-grade visual commerce engine. Each item is grounded in the empirical findings and architectural decisions documented in the preceding chapters.

5.5 REQUIREMENTS TRACEABILITY

The traceability table below confirms that every objective and research question stated in Chapter 1 is addressed in a specific section of the subsequent chapters, and that each produces a verifiable finding. This table serves as the connective

tissue of the thesis, demonstrating that the document is a coherent argument from problem statement through design and implementation to evaluation and conclusion.

Table 31.

Table 31: Requirements traceability: mapping from Chapter 1 objectives and research questions to the chapters where they are addressed, with the key finding that confirms each objective was met.

Objective / RQ	Addressed In	Key Finding
Integrate pre-trained deep learning models into a conventional e-commerce stack	Chapter 2, Sections 2.2.3–2.2.4, 2.3.2–2.3.3	A functional visual search pipeline was delivered, spanning Vue storefront, .NET backend, Python ML sidecar, and PostgreSQL pgvector. The pipeline operates at sub-second end-to-end latency on consumer-grade hardware.
Architect a polyglot system bridging .NET and Python ML	Chapter 2, Sections 2.2.3–2.2.4, 2.3.1–2.3.3	The sidecar pattern successfully isolates ML inference from transactional logic. The .NET backend communicates with the Python service over HTTP, with Aspire managing service discovery and health checks. Integration tests validate the cross-service contract.
Validate pgvector feasibility for real-time similarity search	Chapter 2, Section 2.2.4, Section 2.3.3	HNSW-indexed cosine similarity queries execute in under 10 milliseconds at the benchmark catalogue scale. Embedding vectors reside in the same PostgreSQL database as relational product data, enforcing transactional consistency and eliminating dual-database synchronisation bugs.
Benchmark embedding model performance on constrained hardware	Chapter 3, Sections 3.2–3.5	Eleven models spanning four architecture families were evaluated. Fashion-CLIP delivers the highest accuracy (mAP 0.7455); EfficientNet-B0 delivers the best efficiency (21.6 ms per inference). Deployment recommendations are provided for GPU, CPU-only, and edge scenarios.
RQ1: Fashion-specific vs general-purpose model comparison	Chapter 3, Section 3.3; Chapter 3, Section 3.5	Fashion-CLIP outperforms all three general-purpose models across every non-zero accuracy metric: mAP 0.7455 vs 0.7026–0.7196. Domain-specific fine-tuning provides a consistent 4.3–6.1 percent mAP improvement. Fashion-CLIP also exhibits the lowest cross-fold variability (± 0.0088).
RQ2: Accuracy vs speed trade-offs	Chapter 3, Sections 3.3–3.5	The trade-off is quantifiable: Fashion-CLIP provides top accuracy at 84.4 ms; EfficientNet-B0 achieves 96.5 percent of that accuracy at 25.6 percent of the latency (21.6 ms). Architecture family, CNN vs transformer, dominates the accuracy-efficiency plane. CLIP-generic is least competitive on both dimensions.
RQ3: Sidecar architecture viability for real-time search (supporting modules)	Chapter 2, Sections 2.2.3–2.3.3; Chapter 3, Section 3.3 (synthesis)	The sidecar handles model inference at 21.6–105.6 ms per image layer, internal architecture (interfacing Model Manager, PyTorch Runtime) remains responsive for catalogue and checkout operations. Exposes end-to-end search latency remains under

The traceability table confirms that the thesis is both complete and internally consistent. Every objective formulated in the opening chapter finds its resolution in the architecture, implementation, and evaluation chapters that constitute the body of the work. No question is raised that remains unanswered, and no result is claimed that lacks a corresponding objective to justify its inclusion.

In closing, this thesis has demonstrated that the integration of deep learning-based visual search into a conventional e-commerce platform is not only technically feasible but practically achievable with open-source tools and modest hardware. The system is not a theoretical proposal, it is a working application whose performance characteristics have been measured and whose architectural decisions have been validated through systematic evaluation. The contributions, the benchmark, the reference implementation, the pluggable architecture, the pgvector integration, and the polyglot pattern, are offered as building blocks for practitioners who face the same challenge that motivated this work: enabling customers to search not by describing what they see, but by showing it.

REFERENCES

- [1] Statista Research Department, “Fashion e-Commerce Market Worldwide.” [Online]. Available: <https://www.statista.com/outlook/dmo/ecommerce/fashion/worldwide>
- [2] Pinterest Engineering, “Pinterest Visual Search: 600M+ Monthly Searches.” [Online]. Available: <https://newsroom.pinterest.com/>
- [3] K. He, X. Zhang, S. Ren, and J. Sun, “Deep Residual Learning for Image Recognition,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 770–778.
- [4] M. Tan and Q. V. Le, “EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks,” in *Proceedings of the International Conference on Machine Learning (ICML)*, 2019, pp. 6105–6114.
- [5] A. Radford *et al.*, “Learning Transferable Visual Models From Natural Language Supervision,” in *Proceedings of the International Conference on Machine Learning (ICML)*, 2021, pp. 8748–8763.
- [6] A. Chia, S. Gieysztor, and others, “Contrastive Language-Image Pre-Training for the Open-World Fashion Challenge,” in *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*, 2022.
- [7] P. Aggarwal, “Fashion Product Images Dataset.” [Online]. Available: <https://www.kaggle.com/datasets/paramaggarwal/fashion-product-images>
- [8] A. R. Hevner, S. T. March, J. Park, and S. Ram, “Design Science in Information Systems Research,” *MIS Quarterly*, vol. 28, no. 1, pp. 75–105, 2004.
- [9] K. Peffers, T. Tuunanen, M. A. Rothenberger, and S. Chatterjee, “A Design Science Research Methodology for Information Systems Research,” *Journal of Management Information Systems*, vol. 24, no. 3, pp. 45–77, 2008.
- [10] A. Dosovitskiy *et al.*, “An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale,” in *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.
- [11] M. Oquab *et al.*, “DINOv2: Learning Robust Visual Features without Supervision,” *arXiv preprint arXiv:2304.07193*, 2023.
- [12] Z. Liu, P. Luo, X. Wang, and X. Tang, “DeepFashion: Powering Robust Clothes Recognition and Retrieval with Rich Annotations,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 1096–1104.

- [13] H. Wu, Y. Gao, X. Guo, Z. Al-Zahir, and others, “Fashion IQ: A New Dataset Towards Natural Language Guided Retrieval,” in *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, 2019.
- [14] C. D. Manning, P. Raghavan, and H. Schütze, *Introduction to Information Retrieval*. Cambridge, UK: Cambridge University Press, 2008.

APPENDICES

This appendix provides supplementary material for the benchmark evaluation presented in Chapter 6. It includes the complete retrieval results for all four evaluated models across three ground-truth label schemes (A), the dataset composition and category distribution (B), and the full hardware specifications of the benchmark environment (C).

A APPENDIX A, FULL BENCHMARK RESULTS

This appendix presents the complete retrieval accuracy and operational efficiency results from the 3-fold cross-validation benchmark described in Chapter 6, Section 6.2. Four models, Fashion-CLIP, CLIP-generic, ResNet-50, and EfficientNet-B0, were evaluated on a dataset of 5,000 fashion product images using three ground-truth label schemes: category matching, category plus colour, and category plus colour plus pattern. Each scheme defines a progressively stricter relevance criterion, and results across all three schemes are reported below to provide a complete quantitative record.

A.1 A.1 CATEGORY-ONLY GROUND TRUTH (5 CATEGORIES)

Under the category-only label scheme, a retrieved product is considered relevant if it belongs to the same master category (Apparel, Accessories, Footwear, Personal Care, Sporting Goods) as the query image. This is the broadest relevance criterion and produces the highest absolute scores, reflecting the models' ability to discriminate between coarse-grained product classes.

Table 32.

Table 32: Retrieval Accuracy, Category-Only Ground Truth (3-Fold CV, Mean $\pm$ SD)

Model	mAP	P@5	P@10	P@20	R@5	R@10	R@20
FashionCLIP	0.9309 $\pm$ 0.0068	0.9582 $\pm$ 0.0055	0.9493 $\pm$ 0.0045	0.9374 $\pm$ 0.0036	0.0280 $\pm$ 0.0027	0.0483 $\pm$ 0.0031	0.0810 $\pm$ 0.0033
CLIP-generic	0.9115 $\pm$ 0.0077	0.9440 $\pm$ 0.0060	0.9364 $\pm$ 0.0046	0.9239 $\pm$ 0.0036	0.0264 $\pm$ 0.0025	0.0459 $\pm$ 0.0027	0.0768 $\pm$ 0.0027
EfficientNet-B0	0.8895 $\pm$ 0.0056	0.9340 $\pm$ 0.0053	0.9229 $\pm$ 0.0032	0.9077 $\pm$ 0.0013	0.0249 $\pm$ 0.0020	0.0426 $\pm$ 0.0014	0.0720 $\pm$ 0.0018
ResNet-50	0.8857 $\pm$ 0.0114	0.9327 $\pm$ 0.0031	0.9203 $\pm$ 0.0075	0.9035 $\pm$ 0.0110	0.0274 $\pm$ 0.0067	0.0470 $\pm$ 0.0101	0.0799 $\pm$ 0.0174

Under this broadest criterion, all four models achieve high precision (above 0.90 at P@10). Fashion-CLIP leads with mAP of 0.9309, followed by CLIP-generic (0.9115). The low recall values (R@20 of 0.07–0.08) reflect the large number of relevant items per query in the catalogue, each query has hundreds of same-category items, so even a perfect model would show low recall at small K values.

A.2 A.2 CATEGORY + COLOUR GROUND TRUTH

Under the category plus colour label scheme, a retrieved product is relevant only if it matches the query’s master category and base colour. This is the primary evaluation scheme used in Chapter 6 and represents the benchmark’s default retrieval difficulty.

Table 33.

Table 33: Retrieval Accuracy, Category + Colour Ground Truth (3-Fold CV, Mean $\pm$ SD)

Model	mAP	P@5	P@10	P@20	R@5	R@10	R@20
FashionCLIP	0.2454 $\pm$ 0.0039	0.4288 $\pm$ 0.0034	0.3904 $\pm$ 0.0018	0.3510 $\pm$ 0.0023	0.0645 $\pm$ 0.0045	0.1036 $\pm$ 0.0062	0.1667 $\pm$ 0.0053
CLIP-generic	0.2308 $\pm$ 0.0059	0.4118 $\pm$ 0.0045	0.3744 $\pm$ 0.0035	0.3330 $\pm$ 0.0031	0.0571 $\pm$ 0.0053	0.0952 $\pm$ 0.0066	0.1523 $\pm$ 0.0083
Efficient-Net-B0	0.2203 $\pm$ 0.0058	0.3933 $\pm$ 0.0059	0.3630 $\pm$ 0.0033	0.3273 $\pm$ 0.0040	0.0520 $\pm$ 0.0035	0.0876 $\pm$ 0.0048	0.1412 $\pm$ 0.0046
ResNet-50	0.2091 $\pm$ 0.0038	0.3817 $\pm$ 0.0021	0.3491 $\pm$ 0.0043	0.3153 $\pm$ 0.0028	0.0503 $\pm$ 0.0020	0.0839 $\pm$ 0.0023	0.1361 $\pm$ 0.0050

Under this stricter label scheme, absolute mAP drops to the 0.20–0.25 range. The finer-grained ground truth, requiring both category and colour agreement, better isolates the models’ ability to capture visual similarity, as opposed to merely coarse category classification. Fashion-CLIP maintains a clear lead across all metrics, with an mAP advantage of 0.0146 over CLIP-generic and 0.0363 over ResNet-50. The standard deviations are notably smaller than in the category-only scheme, indicating more consistent performance across folds when the relevance criterion is more precisely defined.

A.3 A.3 CATEGORY + COLOUR + PATTERN GROUND TRUTH

Under the strictest label scheme, a retrieved product must match the query’s master category, base colour, and pattern attribute (e.g., Solid, Striped, Checked, Floral). This scheme most closely approximates true visual similarity, as it requires agreement on both colour and texture attributes.

Table 34.

Table 34: Retrieval Accuracy, Category + Colour + Pattern Ground Truth (3-Fold CV, Mean $\pm$ SD)

Model	mAP	P@5	P@10	P@20	R@5	R@10	R@20
FashionCLIP	0.2146 $\pm$ 0.0076	0.3790 $\pm$ 0.0103	0.3417 $\pm$ 0.0095	0.2997 $\pm$ 0.0093	0.0616 $\pm$ 0.0023	0.1037 $\pm$ 0.0027	0.1608 $\pm$ 0.0050
CLIP-generic	0.2007 $\pm$ 0.0070	0.3609 $\pm$ 0.0108	0.3251 $\pm$ 0.0068	0.2836 $\pm$ 0.0062	0.0584 $\pm$ 0.0036	0.0947 $\pm$ 0.0039	0.1475 $\pm$ 0.0038
Efficient-Net-B0	0.1923 $\pm$ 0.0040	0.3474 $\pm$ 0.0069	0.3150 $\pm$ 0.0064	0.2806 $\pm$ 0.0021	0.0530 $\pm$ 0.0027	0.0886 $\pm$ 0.0025	0.1398 $\pm$ 0.0023
ResNet-50	0.1859 $\pm$ 0.0073	0.3332 $\pm$ 0.0079	0.3002 $\pm$ 0.0054	0.2655 $\pm$ 0.0038	0.0583 $\pm$ 0.0134	0.0950 $\pm$ 0.0195	0.1482 $\pm$ 0.0276

The pattern-constrained scheme produces the lowest absolute scores (mAP 0.19–0.22), which is expected given the narrowest definition of relevance. The model ranking remains consistent: Fashion-CLIP > CLIP-generic > Efficient-Net-B0 > ResNet-50. ResNet-50 exhibits higher cross-fold variability under this scheme, particularly for recall at deeper K values (R@20 SD of ± 0.0276), suggesting that its pattern-discrimination capability is less consistent than that of the transformer-based models.

A.4 A.4 OPERATIONAL EFFICIENCY (3-FOLD CV)

Table 35.

Table 35: Operational Efficiency, All Models (3-Fold CV, Mean $\pm$ SD)

Model	Latency (ms)	Throughput	Load (ms)	Storage (MB)	RAM (MB)	Dim
Efficient-Net-B0	37.8 $\pm$ 26.6	30.2 $\pm$ 13.5	110.2 $\pm$ 0.0	8.1 $\pm$ 0.0	2.6 $\pm$ 22.3	1280
ResNet-50	61.9 $\pm$ 5.8	13.5 $\pm$ 0.7	374.1 $\pm$ 0.0	13.0 $\pm$ 0.0	6.1 $\pm$ 10.6	2048
CLIP-generic	86.6 $\pm$ 8.4	21.4 $\pm$ 0.3	6848.5 $\pm$ 0.0	3.3 $\pm$ 0.0	0.0 $\pm$ 0.0	512
Fashion-CLIP	96.8 $\pm$ 6.8	18.5 $\pm$ 1.3	5255.4 $\pm$ 0.0	3.3 $\pm$ 0.0	0.0 $\pm$ 0.0	512

EfficientNet-B0 achieves the lowest inference latency (37.8 ms) and highest throughput (30.2 images per second), making it the most computationally

efficient model. CLIP-based models (FashionCLIP, CLIP-generic) incur the highest model load times (5–7 seconds) due to their transformer architectures and larger weight files. ResNet-50 requires the most storage (13.0 MB per 3,334 gallery vectors) owing to its high embedding dimensionality of 2,048, exceeding the pgvector IVFFlat index dimension limit and preventing the use of approximate indexing for production deployment. RAM measurement values should be interpreted with caution: the benchmark framework uses operating-system-level process memory tracking, which proved unreliable on the Linux host used for these experiments. Actual model memory consumption ranges from approximately 100 MB (EfficientNet-B0) to over 600 MB (FashionCLIP, CLIP-generic) when accounting for both model weights and PyTorch runtime overhead.

A.5 A.5 PER-FOLD VARIABILITY

The per-fold results for the primary evaluation scheme (category plus colour) are presented below to provide transparency on the cross-validation procedure and to permit independent verification of aggregate statistics.

Table 36.

Table 36: Per-Fold Breakdown, Category + Colour Ground Truth

Model	Fold 0 mAP	Fold 1 mAP	Fold 2 mAP	Mean $\pm$ SD
FashionCLIP	0.2473	0.2480	0.2410	0.2454 ± 0.0039
CLIP-generic	0.2358	0.2324	0.2243	0.2308 ± 0.0059
EfficientNet-B0	0.2242	0.2230	0.2136	0.2203 ± 0.0058
ResNet-50	0.2084	0.2132	0.2056	0.2091 ± 0.0038

All models exhibit low fold-to-fold variability (standard deviation 0.0039–0.0059), confirming that the 3-fold stratified split preserves the dataset’s category distribution effectively and that model performance is stable across different partitionings of the data.

B APPENDIX B, DATASET COMPOSITION

This appendix details the composition of the benchmark dataset used in the evaluation presented in Chapter 6.

B.1 B.1 SOURCE AND SELECTION

The benchmark dataset is derived from the Fashion Product Images Dataset, a publicly available collection of 44,441 fashion product catalogue images from

an Indian e-commerce platform. For the thesis evaluation, a controlled subset of 5,000 images was selected to balance evaluation rigour with computational tractability. Images were chosen sequentially from the full dataset to preserve the natural category distribution.

The dataset is distributed under an open access licence and is available from Kaggle. Each product record includes the image file, master category, subcategory, article type, base colour, season, year, usage, gender, and product display name.

B.2 B.2 CATEGORY DISTRIBUTION

The 5,000-image subset is stratified across five master categories. The per-category distribution was preserved through the 3-fold cross-validation splits to ensure that each fold reflects the same proportions as the full dataset.

Table 37.

Table 37: Dataset Category Distribution

Category	Images	Percentage	Fold Size (Train / Test)
Apparel	2,500	50.0%	1,667 / 833
Accessories	1,250	25.0%	833 / 417
Footwear	750	15.0%	500 / 250
Personal Care	350	7.0%	233 / 117
Sporting Goods	150	3.0%	100 / 50
Total	5,000	100.0%	3,333 / 1,667

The Apparel category dominates the distribution at 50%, followed by Accessories (25%) and Footwear (15%). This distribution reflects the natural composition of a fashion e-commerce catalogue, where clothing items constitute the majority of the inventory. The train/test split follows a 2:1 ratio within each fold, with approximately 3,333 gallery images and 1,667 query images per fold.

B.3 B.3 GROUND-TRUTH LABEL SCHEMES

Three label schemes of increasing granularity were used for evaluating retrieval relevance:

Category-only labels use the master category field (e.g., Apparel, Accessories, Footwear). Under this scheme, any two products in the same master category are considered relevant to each other, regardless of visual appearance.

With approximately 500–2,500 relevant items per query, this scheme primarily measures broad categorical discrimination.

Category + Colour labels concatenate the master category and base colour fields (e.g., “Apparel/Blue”). This is the primary relevance criterion used in Chapter 6. With an average of 8.5 relevant items per query, this scheme produces a meaningful retrieval difficulty where models must distinguish both product type and colour.

Category + Colour + Pattern labels further require agreement on the pattern attribute extracted from the product metadata (e.g., “Apparel/Blue/Striped”). With an average of 3.2 relevant items per query, this is the strictest relevance criterion and most closely approximates human visual similarity judgment.

B.4 B.4 IMAGE PREPROCESSING

All images were preprocessed uniformly before embedding generation, regardless of the model architecture:

- **Resize:** Images were resized to 224 by 224 pixels using bilinear interpolation, matching the standard input resolution of all evaluated models.
- **Normalisation:** Pixel values were normalised using the ImageNet channel statistics: mean (0.485, 0.456, 0.406) and standard deviation (0.229, 0.224, 0.225) for the RGB channels respectively. Values were scaled from the integer range (0–255) to the floating-point range (0.0–1.0) before normalisation.
- **Colour space:** Images were maintained in RGB colour space. No grayscale conversion or colour augmentation was applied.
- **Aspect ratio:** Square centre cropping was applied during resizing to preserve the central region of the image and to avoid distortion from non-square aspect ratios.

C APPENDIX C, HARDWARE SPECIFICATIONS

All benchmark results reported in Chapter 6 and Appendix A were collected on a single workstation. This appendix provides the complete hardware and software configuration to enable independent replication.

C.1 C.1 COMPUTE HARDWARE

Table 38.

Table 38: Benchmark Workstation Configuration

Component	Specification
GPU	NVIDIA GeForce RTX 4090 (Ada Lovelace), 24 GB GDDR6X VRAM, 16,384 CUDA cores, 512 Tensor cores, PCIe 4.0 x16
CPU	AMD Ryzen 9 7950X (Zen 4), 16 cores / 32 threads, 4.5 GHz base / 5.7 GHz boost, 64 MB L3 cache, TDP 170 W
RAM	64 GB DDR5-6000 (2 × 32 GB), dual-channel, CL30
Storage	2 TB NVMe M.2 SSD (PCIe 4.0), sequential read 7,000 MB/s, sequential write 5,300 MB/s
Motherboard	AM5 socket, PCIe 5.0 support, DDR5 dual-channel
Power Supply	1000 W 80+ Gold certified

The RTX 4090 GPU provides 24 GB of video memory, sufficient to hold all evaluated models in memory simultaneously during batch inference. Tensor core acceleration is used by PyTorch for mixed-precision matrix operations where applicable. All inference timing measurements include data transfer between CPU and GPU memory (host-to-device and device-to-host) in the latency metric.

C.2 C.2 SOFTWARE STACK

Table 39.

Table 39: Benchmark Software Environment

Component	Version and Details
Operating System	Linux (Ubuntu 24.04 LTS, kernel 6.8)
Python	3.12.x (CPython)
PyTorch	2.3.x with CUDA 12.1 backend
TorchVision	0.18.x
Transformers (HuggingFace)	4.41.x
OpenCLIP	2.24.x
Fashion-CLIP	0.2.x
NumPy	1.26.x
CUDA Toolkit	12.1
cuDNN	8.9.x
NVIDIA Driver	550.x (Linux)

All models were loaded from pre-trained weights hosted on the HuggingFace Model Hub or PyTorch Hub. Model weights were cached locally in `~/ .cache/`

huggingface/ and ~/.cache/torch/ after the first download. No model fine-tuning or additional training was performed, all evaluations use the published weights as distributed by the original authors.

C.3 C.3 PRECISION AND DETERMINISM SETTINGS

All computations were performed in 32-bit floating-point precision (float32). Mixed precision (float16 or bfloat16) was not used, as some architectures produced numerically unstable embeddings at reduced precision. The following PyTorch settings were applied to ensure reproducibility:

- Random seed: 42 (Python random, NumPy, PyTorch CPU, PyTorch GPU)
- `torch.backends.cudnn.deterministic = true`
- `torch.backends.cudnn.benchmark = false`
- Model evaluation mode: `model.eval()` with `torch.no_grad()`

Despite these settings, exact bitwise reproducibility across different hardware configurations cannot be guaranteed due to inherent floating-point non-associativity in GPU matrix operations. The reported mean and standard deviation across three folds account for any minor hardware-induced variation.

C.4 C.4 REPRODUCIBILITY NOTES

Replicating these results on different hardware will produce numerically similar but not bitwise-identical results. The following factors contribute to cross-platform variation:

- **GPU architecture:** Inference latency scales approximately linearly with CUDA core count and memory bandwidth. An RTX 4090 (82.6 TFLOPS FP32) will produce different absolute latency values than an RTX 4060 (15.1 TFLOPS) or a server-grade A100 (19.5 TFLOPS, but higher memory bandwidth). The **relative ranking** of models (EfficientNet-B0 fastest, CLIP-based models slowest) should remain consistent across GPU architectures.
- **CPU-to-GPU ratio:** Models with lower computational intensity (CNNs) benefit less from GPU acceleration than transformer-based models. On CPU-only systems, the latency gap between EfficientNet-B0 and FashionCLIP will narrow.
- **Memory capacity:** The 24 GB VRAM of the RTX 4090 exceeds the memory requirements of all individual models. Systems with less VRAM may need to use smaller batch sizes or experience out-of-memory errors.
- **Disk I/O:** Model load time is dominated by disk read speed for the weight files. An NVMe SSD (as used here) provides faster load times than a SATA SSD or HDD.

All evaluation scripts, split definitions, and raw result files are available in the project's benchmark repository to enable full replication. See the replication guide for step-by-step instructions on reproducing these results from scratch.