We create chemistry

Joncryl® PDX-7339

General

A customized water-based acrylic copolymer for lacquer formulations used in the production of metalized paper for inner liner.

Key features & benefits

- good gloss and hold-out
- fast drying
- excellent transfer and printability
- excellent wet rub resistance

Properties

Appearance

white partly transparent emulsion

Typical characteristics

(should not be interpreted as specifications)

non-volatile	42.9 %
viscosity at 25 °C	370 mPa.s
acid value	76
density at 25 °C	1.03 g/cm³
minimum film-forming temperature	22 °C
pH	7.9
freeze/thaw-stable	yes

Application

Joncryl® PDX-7339 is an acrylic emulsion for use in the inner liner metalized paper like tobacco packaging, which can provide good gloss and wet rub resistance.

Safety
When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note
The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

BASF East Asia Regional Headquarters Ltd.
45th Floor, Jardine House, No. 1 Connaught Place, Central, Hong Kong