

Irganox® 1010

Product Description

Irganox1010 is a highly effective, non-discoloring, sterically hindered primary phenolic antioxidant stabilizer that protects organic substrates against thermo-oxidative degradation.

Key Features & Benefits

- Good compatibility
- High resistance to extraction
- Low volatility
- Odorless
- Can be used in combination with other additives
- Manufactured using a tin-free process

Chemical Composition

Pentaerythritol tetrakis (3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate)

$$\begin{array}{c|c} & O \\ & | \\ & | \\ & C \\ & C$$

Properties

Typical Properties

Resins

Appearance
CAS number
Molecular w eight
Melting range
Flash point
Vapor pressure at 20°C

Density at 20°C
Density (bulk)

w hite, free-flow ing pow der 6683-19-8 1,178 g/mol 110 – 125°C 297°C 7 E-10 Pa (extrapolated) 1.15 g/ml

530 - 630 g/l

Solubility at 20°C (g/100 g solution)

 Acetone
 47

 Chloroform
 71

 Ethanol
 1.5

 Ethyl acetate
 47

 n-Hexane
 0.3

 Methanol
 0.9

 Methylene chloride
 63

These typical values should not be interpreted as specifications.

Modified and unmodified natural resins; these are added as solutions or dispersions

Pigments Adhesives can be colored with the water-dispersable Dispers® or Luconyl® preparations

* These typical values should not be interpreted as specifications.

May 2018 rev page 1 of 3

Applications

Irganox1010 is used in polyolefins such as polyethylene, polypropylene, polybutene, as well as, in olefin co-polymers such as ethylene vinyl acetate co-polymers. It is also recommended for the processing of polymers such as polyacetals, polyamides, and polyurethanes, polyesters, PVC, styrene homo- and co-polymers, ABS, elastomers such as butyl rubber (IIR), SBS, SEBS, EPM, and EPDM, other synthetic rubbers, adhesives, natural and synthetic tackifiers resins, and other organic substrates.

It has good compatibility, high resistance to extraction, low volatility, and odorless. Irganox1010 can be used in combination with other additives such as co-stabilizers (thioethers, phosphites, phosphonites), light stabilizers, and other functional stabilizers.

Irganox1010 is recommended for applications such as:

- Solvent-based coating applications
- Tackifier resins
- Hot-melt adhesives

Recommended Concentrations

The amount of Irganox1010 required for optimum performance should be determined in trials covering a concentration range. Concentrations up to several percent may be used depending on the substrate, processing conditions, requirements of the end application, and long term thermal stability requirements.

0.05 - 0.1% ppm of Irganox1010 provides long term thermal stability to the polymer.

<u>Application</u>	<u>Concentration</u>
Polyolefins	0.05 - 0.4%
Hot melt adhesives	0.2 - 1%
Synthetic tackifier resins	0.1 - 0.5%
Solvent-based coatings	0.2 - 1.0%

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. NO WARRANTIES OF ANY KIND, ETHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE. Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Irganox is a registered trademark of BASF Group.

© BASF Corporation, 2019



BASF Corporation is fully committed to the Responsible Care[®] initiative in the USA, Canada, and Mexico.
For more information on Responsible Care[®] go to:
U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Resins
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612

Email: CustCare-Charlotte@basf.com Email: edtech-info@basf.com www.basf.us/formulation-additives

October 2019 Rev 3