


Irganox[®] 245

Product Description	Irganox 245 is a phenolic primary antioxidant for processing and long term thermal stabilization.
Key Features & Benefits	<ul style="list-style-type: none"> - High extraction resistance - Low volatility - Odorless - Good color stability
Chemical Composition	Ethylene bis(oxyethylene) bis-(3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate)



Properties

Typical Properties	Appearance	white, free-flowing powder
	CAS number	36443-68-2
	Molecular weight	586.8
	Melting range	76 – 79 °C
	Flash point	> 150 °C
	Vapor pressure at 20°C	4 e ⁻⁸ Pa
	Density at 20°C	1.14 g/ml
	<u>Solubility at 25°C (g/100 g solution)</u>	
	Acetone	> 50
	Benzene	18
	Chloroform	> 40
	Ethyl acetate	37
	Ethanol	10
	n-Hexane	< 0.1
	Methanol	12
	Methylene chloride	> 40
	Toluene	6
	Styrene	6
	Polyetherol	~ 3
	Water	< 0.01
	<u>Volatility (TGA, air at 20 K/min)</u>	
	Temperature at 1% weight loss	280 °C
	Temperature at 10% weight loss	330 °C

These typical values should not be interpreted as specifications.

Application

Irganox 245 is a sterically hindered phenolic antioxidant that protects organic substrates against thermo-oxidative degradation during manufacturing, processing, and end use.

Irganox 245 is effective in styrene polymers, particularly impact-modified polystyrenes, ABS, MBS, SB, and SBR-latexes, as well as in POM homo- and co-polymers. It is also very useful for the thermal stabilization of polyurethanes, polyamides, thermoplastic polyesters, PVC, and other polymers. In addition to imparting thermostability to the finished polymer, it is effective as a chain stopper during PVC polymerization.

Irganox 245 can be used in combination with other additives such as co-stabilizers (e.g. thioesters, phosphites, phosphonites), light stabilizers, and other functional stabilizers. The effectiveness of Irganox 245 with Irgafos® 168 is particularly noteworthy.

Irganox 245 is recommended for applications such as:

- Hot-melt adhesives
- Sealants
- Solvent-based coatings

Recommended Concentrations

The amount of Irganox 245 required for optimum performance should be determined in laboratory trials covering a concentration range. Concentrations up to 1.0% can be used depending upon the substrate, processing conditions, long term thermal stability requirements, and end application requirements.

0.05 – 0.1% of Irganox 245 provides long term thermal stability to the polymer.

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State, and Local health and safety regulations, thorough ventilation of the workplace, good skin care, and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Irganox 245.

Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Irganox is a registered trademark of BASF Group.

© BASF Corporation, 2019



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® go to:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico

BASF Corporation

Dispersions and Resins

11501 Steele Creek Road

Charlotte, North Carolina 28273

Phone: (800) 251 – 0612

Email: CustCare-Charlotte@basf.com

Email: edtech-info@basf.com

www.basf.us/dpsolutions