

Foamaster® MO 2150

general

- excellent defoamer for mid to high PVC decorative coatings
- exceptional product stability. Retains its antifoaming properties during paint storage.
- excellent price/performance ratio.
- defoamer based on mineral oil.

chemical nature

blend of foam destroying substances

Properties

physical form

yellowish liquid

storage

Foamaster® MO 2150 might form a slight sedimentation or phase separation during storage. The defoaming properties of Foamaster® MO 2150 are not affected, if the product is mixed thoroughly prior to use.

typical properties

solubility in water	insoluble
density at 20 °C (68 °F)	~ 0.86 g/cm ³
viscosity	~ 400 mPa·s

Application

Foamaster® MO 2150 is recommended for use in synthetic latex, water-based architectural coatings, plasters based on organosilicate, and aqueous adhesives.

recommended concentrations

A dosage of 0.1 – 0.4% calculated on total formulation is recommended for effective defoaming.

When manufacturing paints, Foamaster® MO 2150 is best added during grinding in order to achieve perfect incorporation of the defoamer into the system. In emulsion polymerization processes, add the defoamer directly onto the foam as it forms.

Contacts worldwide

Asia

BASF East Asia Regional Headquarters

Ltd 45/F, Jardine House

No. 1 Connaught Place

Central Hong Kong

China

formulation-additives-asia@basf.com

North America

BASF Corporation

11501 Steele Creek Road

Charlotte, NC 28273

USA

formulation-additives-nafta@basf.com

Europe

BASF SE

Formulation Additives

67056 Ludwigshafen

Germany

formulation-additives-europe@basf.com

South America

BASF S.A

Rochaverá - Crystal Tower

Av. das Nações Unidas, 14.171

Morumbi - São Paulo-SP

Brazil

formulation-additives-south-america@basf.com**Validity**

This Technical Data Sheet is valid for all versions of the Foamaster MO 2150; Foamaster MO 2150, Foamaster MO 2150 AC, Foamaster MO 2150 AJ.

Safety

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

www.basf.com/formulation-additives