

FoamStar[®] ST 2438

general

defoamer

FoamStar[®] ST 2438 is a 100% active defoamer compound combining a hyper-branched FoamStar polymer with high-end organo-silicones to deliver fast foam knock down with very high efficiency.

- does not reduce the gloss of high gloss paints and coatings
- effective in difficult to defoam high gloss formulations
- fast bubble-break versus conventional defoamers
- effective against microfoam
- does not separate or settle
- very good persistence
- effective in deep and clear/neutral bases

chemical nature

defoamer on the basis of organomodified polysiloxanes and hyper-branched star polymer

Properties

physical form

light yellow, clear to slightly hazy liquid

storage

FoamStar[®] ST 2438 should be stored in a cool dry place.

typical properties (no supply specification)

Brookfield viscosity at 23°C (73°F)	~ 140 mPa·s
density at 20°C (68°F)	~ 0.95 g/cm ³

Application

FoamStar[®] ST 2438 is part of a novel series of defoamers based on FoamStar chemistry. It is effective in high gloss paints and coatings based on acrylic, styrene acrylic and vinyl acrylic latex.

recommended concentrations

0.25 - 0.50% on total formulation

FoamStar addition may be equally divided between the grind and let-down stages. Its effectiveness is the same in the grind and the let-down.

Contacts worldwide

Asia

BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

North America

BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

Europe

BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

South America

BASF S.A
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Foamstar® ST 2438.

Safety

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

www.basf.com/formulation-additives