

FoamStar® ST 2410

Product description

FoamStar ST 2410 represents a novel series of defoamers based on new defoamer chemistry. It is the first new defoamer chemistry in over 30 years.

FoamStar is a defoaming molecule that defoams by a different mechanism. Unlike conventional defoamers (mineral oil or silicone), FoamStar defoams on a molecular level. It also has wetting properties not found in other conventional defoamers.

Key benefits

- Defoams at the molecular level
- Has wetting properties not found in other conventional defoamers

Chemical nature

Molecule compounded in an enhanced mineral-oil system

Properties

Physical form

Opaque, off-white liquid

Technical data

(no supply specification)

Active content	%	100
Moisture	%	~ 0.5
Bulk density	lbs/gal	~ 7.4
Dispersibility		dispersible

Application

FoamStarST 2410 has the following advantages:

- Use 1/3 1/2 Less Defoamer
- Save at least 20 % on Defoamer Costs
- Non-separating & non-settling
- Extremely Effective in Low VOC coatings.
- Very Fast bubble-break versus conventional defoamers
- · Effective against Micro-foam

April 2019 rev 4 page 1 of 2

Formulation guideline

In the grind portion of a flat paint formula, use 0.25 - 0.50 pounds of FoamStar ST 2410 per 100 gallons. In semi-gloss paint grind, use 0.50 - 1.0 pounds of FoamStar ST 2410 per 100 gallons. The rest of the FoamStar ST 2410 addition can be made to the letdown. FoamStar ST 2410 will be equally effective in both the letdown and the grind.

Storage

FoamStar ST 2410 is subject to appropriate storage under the usual storage and temperature conditions, our products are durable for at least 1 year. FoamStar ST 2410 is shipped in 55gallon (200 liter) steel drums and plastic tote tanks. If subjected to below freezing temperatures, product may congeal or stratify. Warm to room temperature and mix well before using.

Contacts worldwide

Asia
BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

Europe
BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

North America BASF Corporation 11501 Steele Creek Road Charlotte, NC 28273 USA

formulation-additives-nafta@basf.com

South America BASF S.A Rochaverá - Crystal Tower Av. das Naçoes Unidas, 14.171 Morumbi - São Paulo-SP Brazil

 $\underline{formulation\text{-}additives\text{-}south\text{-}america@basf.com}}$

Validity

This Technical Data Sheet is valid for all versions of the 0BFoamStar® ST 2410.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

April 2019 rev 4 page 2 of 2