

Sovermol® 819

General Sovermol[®] 819 is a polyol used in the manufacturing of polyurethanes.

Key features & benefits Raw materials are registered in EU-Directive

Low viscosity universal polyol Good self-leveling properties Extremely hydrophobic

Good bonding properties

High renewable raw material content

The product might be slightly cloudy - this does not affect the product

properties in a negative way

Chemical nature Oleochemical Polyester

Properties

Appearance Yellow, low viscous liquid

Typical characteristics

(should not be interpreted as specifications)

Water content	ISO 4317	≤ 0.2 %
Acid number	ISO 660	≤ 3.0
Hydroxyl number	ISO 4326	230 – 250 mg KOH/g
Viscosity, dynamic, 25 °C	ISO 2555	750 – 950 mPa·s
Density, 20 °C	ISO 2811-3	0.96 - 1.02 g/cm ³

Application

In combination with Polymer MDI Sovermol® 819 can be used for the production of 2-pack coating and casting materials. Due to the hydrophobic properties and its low viscosity, this material is therefore eminently suitable for electro potting compounds.

In addition, Sovermol[®] 819 shows particular water repellency, which results in less sensitivity to moisture while curing.

Mixing formulation (without filler)

100 g Sovermol® 819 5 g Zeolith Paste 58 g Polymer MDI*

*e.g. Lupranate M 20 S - BASF Polyurethanes

Fechnical Data Sheet Automotive & General Industrial Paints		
For further detailed application information please contact our Technical Support Department.		
Safety When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.		
Note The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.		
® = registered trademark, ™ = trademark of the BASF Group, unless otherwise noted		

BASF Advanced Chemical Co., Ltd. No. 300 Jiang Xin Sha Rd, Pudong, Shanghai, China