

分类算法

Logistic Regression 逻辑回归算法

二元分类问题

S 型函数 sigmoid function or
logistic function

Logistic Regression Model

Want $0 \leq h_{\theta}(x) \leq 1$

$$h_{\theta}(x) = g(\theta^T x)$$


$$\rightarrow g(z) = \frac{1}{1 + e^{-z}}$$

$\theta^T x$

→ Sigmoid function

→ Logistic function


$$h_{\theta}(x) = \frac{1}{1 + e^{-\theta^T x}}$$



Parameters θ .

决策边界 Decision Boundary

Decision Boundary



$$\theta = \begin{bmatrix} -3 \\ 1 \\ 1 \end{bmatrix} \leftarrow$$

$$\rightarrow h_{\theta}(x) = g(\theta_0 + \theta_1 x_1 + \theta_2 x_2)$$

Decision boundary

Predict " $y = 1$ " if $-3 + x_1 + x_2 \geq 0$


$\theta^T x$

$$\rightarrow \underline{x_1 + x_2 \geq 3}$$

$$\leftarrow x_1 + x_2 < 3$$


x_1, x_2
 $\rightarrow h_{\theta}(x) = 0.5$
 $\boxed{x_1 + x_2 = 3}$

Non-linear decision boundaries




Cost function

Cost function




Logistic regression cost function

$$\text{Cost}(h_{\theta}(x), y) = \begin{cases} -\log(h_{\theta}(x)) & \text{if } y = 1 \\ -\log(1 - h_{\theta}(x)) & \text{if } y = 0 \end{cases}$$



Logistic regression cost function

$$\text{Cost}(h_{\theta}(x), y) = \begin{cases} -\log(h_{\theta}(x)) & \text{if } y = 1 \\ -\log(1 - h_{\theta}(x)) & \text{if } y = 0 \end{cases}$$



Logistic regression cost function

$$\rightarrow J(\theta) = \frac{1}{m} \sum_{i=1}^m \text{Cost}(h_{\theta}(x^{(i)}), y^{(i)})$$

$$\rightarrow \text{Cost}(h_{\theta}(x), y) = \begin{cases} -\log(h_{\theta}(x)) & \text{if } y = 1 \\ -\log(1 - h_{\theta}(x)) & \text{if } y = 0 \end{cases}$$

Note: $y = 0$ or 1 always

$$\rightarrow \text{Cost}(h_{\theta}(x), y) = -y \log(h_{\theta}(x)) - (1-y) \log(1 - h_{\theta}(x))$$

If $y=1$: $\text{Cost}(h_{\theta}(x), y) = -\log h_{\theta}(x)$

If $y=0$: $\text{Cost}(h_{\theta}(x), y) = -\log(1 - h_{\theta}(x))$

Logistic regression cost function

$$\begin{aligned} J(\theta) &= \frac{1}{m} \sum_{i=1}^m \text{Cost}(h_{\theta}(x^{(i)}), y^{(i)}) \\ &= -\frac{1}{m} \left[\sum_{i=1}^m y^{(i)} \log h_{\theta}(x^{(i)}) + (1 - y^{(i)}) \log(1 - h_{\theta}(x^{(i)})) \right] \end{aligned}$$

To fit parameters θ :

$$\min_{\theta} J(\theta) \quad \text{Get } \theta$$

To make a prediction given new x :

$$\text{Output } h_{\theta}(x) = \frac{1}{1 + e^{-\theta^T x}}$$

$$p(y=1 | x; \theta)$$

Gradient Descent

$$\rightarrow J(\theta) = -\frac{1}{m} \left[\sum_{i=1}^m y^{(i)} \log h_{\theta}(x^{(i)}) + (1 - y^{(i)}) \log(1 - h_{\theta}(x^{(i)})) \right]$$

Want $\min_{\theta} J(\theta)$:

Repeat {

$$\theta_j := \theta_j - \alpha \frac{\partial}{\partial \theta_j} J(\theta)$$

(simultaneously update all θ_j)

}

Gradient Descent

$$J(\theta) = -\frac{1}{m} \left[\sum_{i=1}^m y^{(i)} \log h_{\theta}(x^{(i)}) + (1 - y^{(i)}) \log (1 - h_{\theta}(x^{(i)})) \right]$$

Want $\min_{\theta} J(\theta)$:

$$\Theta = \begin{bmatrix} \theta_0 \\ \theta_1 \\ \theta_2 \\ \vdots \\ \theta_n \end{bmatrix}$$

Repeat {

$$\rightarrow \theta_j := \theta_j - \alpha \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)}) x_j^{(i)}$$

(simultaneously update all θ_j)

$$h_{\theta}(x) = \Theta^T x$$

$$h_{\theta}(x) = \frac{1}{1 + e^{-\Theta^T x}}$$

Algorithm looks identical to linear regression!

优化

Optimization algorithm

Given θ , we have code that can compute

$$\begin{bmatrix} - J(\theta) \\ - \frac{\partial}{\partial \theta_j} J(\theta) \end{bmatrix} \quad (\text{for } j = 0, 1, \dots, n)$$

Optimization algorithms:

- - Gradient descent
- Conjugate gradient
- BFGS
- L-BFGS

共轭梯度法 BFGS (变尺度法) 和

L-BFGS (限制变尺度法) 就是其中

Optimization algorithm

Given θ , we have code that can compute

$$\begin{aligned} & - J(\theta) \\ & - \frac{\partial}{\partial \theta_j} J(\theta) \end{aligned} \quad \leftarrow \quad (\text{for } j = 0, 1, \dots, n)$$

Optimization algorithms:

- - Gradient descent
- Conjugate gradient
- BFGS
- L-BFGS

Advantages:

- No need to manually pick α
- Often faster than gradient descent.

Disadvantages:

- More complex

*****优化*****

Example: $\min_{\theta} J(\theta)$
 $\rightarrow \theta = \begin{bmatrix} \theta_1 \\ \theta_2 \end{bmatrix}$ $\theta_1=5, \theta_2=5.$

$J(\theta) = (\theta_1 - 5)^2 + (\theta_2 - 5)^2$

$\frac{\partial}{\partial \theta_1} J(\theta) = 2(\theta_1 - 5)$


$\frac{\partial}{\partial \theta_2} J(\theta) = 2(\theta_2 - 5)$

```
function [jVal, gradient]
    = costFunction(theta)
    jVal = (theta(1)-5)^2 + ...
           (theta(2)-5)^2;
    gradient = zeros(2,1);
    gradient(1) = 2*(theta(1)-5);
    gradient(2) = 2*(theta(2)-5);

> options = optimset('GradObj', 'on', 'MaxIter', '100');
> initialTheta = zeros(2,1);
[optTheta, functionVal, exitFlag] ...
    = fminunc(@costFunction, initialTheta, options);
```

多类的逻辑回归问题

One-vs-all (one-vs-rest):



One-vs-all

Train a logistic regression classifier $\underline{h_{\theta}^{(i)}(x)}$ for each class \underline{i} to predict the probability that $\underline{y = i}$.

On a new input \underline{x} , to make a prediction, pick the class i that maximizes

$$\max_{\underline{i}} \underline{h_{\theta}^{(i)}(x)}$$