

构建模型方法

Debugging a learning algorithm:

Suppose you have implemented regularized linear regression to predict housing prices.

$$\rightarrow J(\theta) = \frac{1}{2m} \left[\sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)})^2 + \lambda \sum_{j=1}^m \theta_j^2 \right]$$

However, when you test your hypothesis on a new set of houses, you find that it makes unacceptably large errors in its predictions. What should you try next?

- Get more training examples
- Try smaller sets of features $x_1, x_2, x_3, \dots, x_{100}$
- Try getting additional features
- Try adding polynomial features ($x_1^2, x_2^2, x_1x_2, \text{etc.}$)
- Try decreasing λ
- Try increasing λ

机器学习诊断法

Machine learning diagnostic:

Diagnostic: A test that you can run to gain insight what is/isn't working with a learning algorithm, and gain guidance as to how best to improve its performance.

Diagnostics can take time to implement, but doing so can be a very good use of your time.

评估假设函数

Evaluating your hypothesis

Dataset:

Size	Price	
2104	400	70% Training set
1600	330	
2400	369	
1416	232	
3000	540	
1985	300	
1534	315	
1427	199	30% Test set
1380	212	
1494	243	

$(x^{(1)}, y^{(1)})$
 $(x^{(2)}, y^{(2)})$
 \vdots
 $(x^{(m)}, y^{(m)})$

$(x_{test}^{(1)}, y_{test}^{(1)})$
 $(x_{test}^{(2)}, y_{test}^{(2)})$
 \vdots
 $(x_{test}^{(m_{test})}, y_{test}^{(m_{test})})$

$m_{test} = \text{no. of test example}$
 $(x_{test}^{(i)}, y_{test}^{(i)})$

Training/testing procedure for linear regression

- - Learn parameter θ from training data (minimizing training error $J(\theta)$) 70%

- Compute test set error:

$$J_{test}(\theta) = \frac{1}{2m_{test}} \sum_{i=1}^{m_{test}} (h_{\theta}(x_{test}^{(i)}) - y_{test}^{(i)})^2$$

Training/testing procedure for logistic regression

- - Learn parameter θ from training data m_{test}

- Compute test set error:

$$J_{test}(\theta) = -\frac{1}{m_{test}} \sum_{i=1}^{m_{test}} y_{test}^{(i)} \log h_{\theta}(x_{test}^{(i)}) + (1 - y_{test}^{(i)}) \log h_{\theta}(x_{test}^{(i)})$$

- Misclassification error (0/1 misclassification error):

$$\text{err}(h_{\theta}(x), y) = \begin{cases} 1 & \text{if } h_{\theta}(x) \geq 0.5, y = 0 \\ & \text{or if } h_{\theta}(x) < 0.5, y = 1 \end{cases} \text{ error}$$

0 otherwise

$$\text{Test error} = \frac{1}{m_{test}} \sum_{i=1}^{m_{test}} \text{err}(h_{\theta}(x_{test}^{(i)}), y_{test}^{(i)})$$

这样我就写出了我的定义方式

模型选择问题, lambda 参数选择, 几次函数模型选择

训练集 交叉验证集 测试集

Train/validation/test error

Training error:

$$\rightarrow J_{train}(\theta) = \frac{1}{2m} \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)})^2$$

Cross Validation error:

$$J_{cv}(\theta) = \frac{1}{2m_{cv}} \sum_{i=1}^{m_{cv}} (h_{\theta}(x_{cv}^{(i)}) - y_{cv}^{(i)})^2$$

Test error:

$$J_{test}(\theta) = \frac{1}{2m_{test}} \sum_{i=1}^{m_{test}} (h_{\theta}(x_{test}^{(i)}) - y_{test}^{(i)})^2$$

也就是对训练集数据进行预测得到的误差

Model selection

1. $h_{\theta}(x) = \theta_0 + \theta_1 x \rightarrow \min_{\theta} J(\theta) \rightarrow \theta^{(1)} \rightarrow J_{cv}(\theta^{(1)})$
2. $h_{\theta}(x) = \theta_0 + \theta_1 x + \theta_2 x^2 \rightarrow \theta^{(2)} \rightarrow J_{cv}(\theta^{(2)})$
3. $h_{\theta}(x) = \theta_0 + \theta_1 x + \dots + \theta_3 x^3 \rightarrow \theta^{(3)} \rightarrow J_{cv}(\theta^{(3)})$
⋮
10. $h_{\theta}(x) = \theta_0 + \theta_1 x + \dots + \theta_{10} x^{10} \rightarrow \theta^{(10)} \rightarrow J_{cv}(\theta^{(10)})$
↓
 $d=4$ ↑


Pick $\theta_0 + \theta_1 x_1 + \dots + \theta_4 x^4$ ←

Estimate generalization error for test set $J_{test}(\theta^{(4)})$

偏差 Bias 和 方差 Variance

Diagnosing bias vs. variance

Suppose your learning algorithm is performing less well than you were hoping. ($J_{cv}(\theta)$ or $J_{test}(\theta)$ is high.) Is it a bias problem or a variance problem?



Bias (underfit):


$$\left. \begin{array}{l} J_{train}(\theta) \text{ will be high} \\ J_{cv}(\theta) \approx J_{train}(\theta) \end{array} \right\}$$

Variance (overfit):


$$\left. \begin{array}{l} J_{train}(\theta) \text{ will be low} \\ J_{cv}(\theta) \gg J_{train}(\theta) \end{array} \right\}$$

Bias/variance as a function of the regularization parameter λ


$$\begin{aligned} J(\theta) &= \frac{1}{2m} \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)})^2 + \boxed{\frac{\lambda}{2m} \sum_{j=1}^m \theta_j^2} \\ J_{train}(\theta) &= \frac{1}{2m} \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)})^2 \\ J_{cv}(\theta) &= \frac{1}{2m_{cv}} \sum_{i=1}^{m_{cv}} (h_{\theta}(x_{cv}^{(i)}) - y_{cv}^{(i)})^2 \end{aligned}$$




High bias



If a learning algorithm is suffering from high bias, getting more training data will not (by itself) help much.




High variance



If a learning algorithm is suffering from high variance, getting more training data is likely to help.

$$h_{\theta}(x) = \theta_0 + \theta_1 x + \dots + \theta_{100} x^{100} \quad (\text{and small } \lambda)$$



结论:


Debugging a learning algorithm:

Suppose you have implemented regularized linear regression to predict housing prices. However, when you test your hypothesis in a new set of houses, you find that it makes unacceptably large errors in its prediction. What should you try next?

- Get more training examples → fixes high variance
- Try smaller sets of features → fixes high variance
- Try getting additional features → fixes high bias
- Try adding polynomial features (x_1^2, x_2^2, x_1x_2 , etc) → fixes high bias.
- Try decreasing λ → fixes high bias
- Try increasing λ → fixes high variance


Neural networks and overfitting

→ “Small” neural network
(fewer parameters; more prone to underfitting)



Computationally cheaper

→ “Large” neural network
(more parameters; more prone to overfitting)



Computationally more expensive.

Use regularization (λ) to address overfitting.