



**UNIVERSITY OF TORONTO**  
**Faculty of Applied Science and Engineering**  
**CIV100F – MECHANICS**  
**Final Examination – Sections 1, 2, 3, 4, 5, 6, 7, 8 and 9 (Online)**  
**Monday, 12<sup>th</sup> December 2022**  
**Examiner: Staff in Civil Engineering**  
**Time allowed: 2-½ hours**

First name (please write as legibly as possible within the boxes)

--	--	--	--	--	--	--	--	--	--	--	--	--	--

Last name

--	--	--	--	--	--	--	--	--	--	--	--	--

Student ID number

--	--	--	--	--	--	--	--	--	--	--	--	--

**INDICATE YOUR CALCULATOR TYPE:**

CASIO FX-991       SHARP EL-W516       OTHER: \_\_\_\_\_

- Notes:
1. Ensure that you have all 12 pages of the examination paper. Page 12 is blank
  2. Answer all five questions. The value of the questions is indicated below
  3. If you need more space for a question, continue on the page indicated at the bottom
  4. If information appears to be missing, make reasonable assumptions and state them clearly
  5. The only calculators permitted are listed above. Please indicate your model
  6. This is a closed-book examination. No other paper will be allowed on the desk
  7. Turn OFF all electronic equipment and place it in your bag
  8. Do not remove the staple

**DO NOT WRITE IN THIS SPACE.**

1	/10
2	/10
3	/10
4	/10
5	/10
TOTAL	/50



E4F32E62-AF7C-4D2F-992A-433815E5FAF5

final-exam-60c0a

#299 Page 2 of 12



NAME: \_\_\_\_\_

Page 2 of 12

1. The steel beam depicted below is supported by a frictionless surface at *A* and a fixed support at *C*. Member *AB* is loaded by a uniformly distributed force and is pinned to member *BC* at *B*.

(a) In the space provided draw the internal-force diagrams for the beam. Indicate the values at all points marked along the beam (viz. *A*, *B*, *C*, 1 and 2) and annotate the shape of the diagrams.

(b) The cross-section of the beam is also represented. Determine if the beam material remains elastic at all points across the section and everywhere along the beam, given that the yield stress for steel is 350 MPa.



Solution can be continued on Page 3

099FE143-A772-4CEF-979A-5EF9974954D6

final-exam-60c0a

#299 Page 3 of 12



NAME: \_\_\_\_\_

Page 3 of 12

*Question 1 can be continued on this page.*

Solution can be continued on Page 12




NAME: \_\_\_\_\_

Page 4 of 12

2. For the steel truss illustrated: (i) Determine the force in members  $AH$ ,  $HM$ ,  $CD$ ,  $IJ$  and  $JN$ , and indicate if the members are in tension or compression. Take  $P = 150 \text{ kN}$  and  $a = 2.5 \text{ m}$ .

(ii) From a different loading condition, the force in member  $EQ$  (cross-sectional area  $1,700 \text{ mm}^2$ , modulus of elasticity  $200 \text{ GPa}$ ) is  $580 \text{ kN}$  in tension. Determine the axial stress in, and the elongation of the member.





NAME: \_\_\_\_\_

Page 5 of 12


Question 2 can be continued on this page.



NAME: \_\_\_\_\_

Page 6 of 12

3. The cross-section of a 3.0 m-wide (in the plane of the figure), fresh-water tank with a slanted bottom is presented. A rectangular door in the bottom of the tank, 1.6 m by 0.8 m (normal to the plane of the figure), is hinged at A and can be opened by the vertical cable under a tension  $P$ , as shown. Determine the minimum tension force in the cable required to open the door. The door is fabricated from 16 mm-thick steel plate with a mass density of  $7,850 \text{ kg/m}^3$ .



CBAAAF7-34B4-471A-849B-4D8CF3CF2600

final-exam-60c0a

#299 Page 7 of 12



NAME: \_\_\_\_\_

Page 7 of 12

*Question 3 can be continued on this page.*

Solution can be continued on Page 12



8B050A15-43CE-4092-B09E-7407CC6DD424


final-exam-60c0a

#299 Page 8 of 12

NAME: \_\_\_\_\_

Page 8 of 12

4. The arm  $ADE$  of the boring machine is attached to a rigid support by pins at  $A$  and  $A'$  (not visible).  $DE$  is parallel to the  $x$ -axis. The arm is also supported by the hydraulic cylinder  $BD$  which has a ball-and-socket joint at each end. The applied loading consists of a force  $P = 6.2 \text{ kN}$  and a couple  $C = 4.8 \text{ kNm}$ , both acting at the boring tool  $E$ . Neglecting the weight of the members, determine the force in the cylinder  $BD$  (provide both the magnitude and the Cartesian vector expression).



Solution can be continued on Page 9

1EFA37A9-66F1-476F-AA22-ABB6E0ADFCB4

final-exam-60c0a

#299 Page 9 of 12



NAME: \_\_\_\_\_

Page 9 of 12

Question 4 can be continued on this page.

Solution can be continued on Page 12



SEA171F2-7F19-45CE-8617-1CFC7D027356


final-exam-60c0a

#299 Page 10 of 12

NAME: \_\_\_\_\_

Page 10 of 12

5. A lifting device for transporting steel barrels is presented. The mass of a barrel is 155 kg, while the mass of the lifting device can be neglected. Calculate the magnitude and direction of the total forces exerted on the barrel at *E* and *F*.



Solution can be continued on Page 11

1BA33FB6-C81E-4206-A5ED-29590972FD89

final-exam-60c0a

#299 Page 11 of 12



NAME: \_\_\_\_\_

Page 11 of 12

Question 5 can be continued on this page.

Solution can be continued on Page 12



70F52F91-5D2B-4D62-84D4-A2B201470702

final-exam-60c0a

#299 Page 12 of 12

NAME: \_\_\_\_\_

Page 12 of 12

*All Questions can be continued on this page. Indicate clearly which question is shown.*