



Name: CY-DC Model:



Product parameters



● Black



● White

Capacity 12.8V/15AH(192WH/60000mAh) or 12.8V/30AH(384WH/120000mAh)

Input 1.DC1, DC2, 14.6V/5A charger input
2.DC1 and DC2 support photovoltaic PWM tracking, 14.6-24V PV input,and both interfaces cannot be plugged into the power supply at the same time

Output 1. TYPE-C Output: QC3.0 MAX 12V/1.5A(18W) PD MAX 12V/1.5A(18W)
2. USB-A1 Output: QC3.0 MAX 12V/1.5A(18W)
3. USB-A2 USB-A3 Output: Co output MAX 5V/3A(15W)
4. DC1、DC2:12V/10A(120W) MAX
5. LED light+RGB light: 5W

Cell Lithium iron phosphate power cell 33140 cylindrical type

Size 214*125*215mm

Material PC+V0 flame retardant

Color Black and white (Customizable colors)

Product weight 192WH : N.W:2.3kg, G.W:3.1kg / 384WH : N.W:3.65kg, G.W: 4.2kg
If there is customization and actual product, it shall prevail

Packaging size 260*165*260mm/1; 345*275*280mm/2



Name: CY-HY-600W Model: B1-1



Product parameters



- Orange
- Black
- Silvery
- White
- Green

Capacity 19.2V/30Ah(576WH/180000mAh)

- Input**
- 1. DC5521 12V-24V/1-5A Charger
 - 2. DC5521 12V-24V/1-5A Car charging 12-24V
 - 3. DC5521 12V-24V/1-5A PV Solar panels

- Output**
- 1. AC 220V or 110V versions, 600W, 50Hz/60Hz, sine wave
 - 2. DC car charging+DC connector (x2 interfaces) 12V-10A/120W total power
 - 3. USB-A (x2 U-ports) QC3.0 fast charging 5V-3A, 9V-2A, 12V-1.5A/18W total power
 - 4. USB-C1 PD/QC3.0 Fast Charging 5V/3A, 9V/2A, 2V/1.5A, 12V/2.5A 30W MAX
 - 5. USB-C2 PD fast charging 5V-3A, 9V-3A, 12V-3A, 15V-3A, 20V-3A/100W total power
 - 6. Lighting LED light with 1W high brightness, with 2-level dimming and SOS flashing
 - 7. Wireless charging : 15W

Cell Lithium iron phosphate power cell 33140 cylindrical type

Size 270*210*185mm

Material PC+V0 flame retardant

Color White main body and white panel (Customizable colors)

Product weight N.W:6kg, G.W:7.92 kg/If there is customization and actual product, it shall prevail

Packaging size 345*285*280mm



Name: CY-LG-2000W Model: A2-4



Product parameters



● Black

Capacity 51.2V/45Ah(2304WH/720000mAh) or 51.2V/60Ah(3072WH/960000mAh)

Input

- 1. DC5521 solar PV12-90V/10A MAX120W supports photovoltaic MPPT eye tracking
- 2. XT60 solar PV input 12-90V/20A MAX800W supports photovoltaic MPPT tracking
- 3. Pin Zi AC input interface 180V-250V Rated power 1000W

Output

- 1. AC Socket AC220V±5% Two interfaces 2000W pure sine wave
- 2. TYPE-C1 QC3.0 MAX 12W/1.5A(18W); PD MAX 12V/2.5A(30W)
- 3. TYPE-C2 PD/QC3.0 MAX 20V/5A (100W)
- 4. USB-A1 QC3.0 MAX 20V/3A (60W)
- 5. USB-A2 QC3.0 MAX 12V/1.5A/(18W)
- 6. DC1、DC、Cigarette lighter 12V/10A(120W) MAX
- 7. LED light 4-8W high brightness, with secondary dimming and SOS flashing

Cell Lithium iron phosphate power cell 33140 cylindrical type

Size 470*210*300mm

Material Sheet Metal

Color Black (Customizable)

Product weight 2304WH : N.W:26kg, G.W:27.3 kg / 3072WH : N.W:29.9kg, G.W:31 kg
If there is customization and actual product, it shall prevail

Packaging size 570*320*525mm