只使用css做到完全居中

笔记本: 前端工程师手册

创建时间: 2019/1/2 11:11 **更新时间:** 2019/1/2 16:58

作者: 15703002626@163.com

URL: https://www.w3cplus.com/css3/basic-selectors

只使用css做到完全居中

•

```
.Absolute-Center {
  margin: auto;
  position: absolute;
  top: 0; left: 0; bottom: 0; right: 0;
}
```

• 负margin值

```
.is-Negative {
    width: 300px;
    height: 200px;
    padding: 20px;
    position: absolute;
    top: 50%; left: 50%;
    margin-left: -170px; /* (width + padding)/2 */
    margin-top: -120px; /* (height + padding)/2 */
}
```

• transform法

```
.is-Transformed {
  width: 50%;
  margin: auto;
  position: absolute;
  top: 50%; left: 50%;
  -webkit-transform: translate(-50%,-50%);
    -ms-transform: translate(-50%,-50%);
        transform: translate(-50%,-50%);
}
```

• table-cell法

• inline-block法

```
<div class="Center-Container is-Inline">
  <div class="Center-Block">
```

```
<!-- CONTENT -->
  </div>
</div>
.Center-Container.is-Inline {
  text-align: center;
  overflow: auto;
.Center-Container.is-Inline:after,
.is-Inline .Center-Block {
  display: inline-block;
  vertical-align: middle;
.Center-Container.is-Inline:after {
  content: '';
  height: 100%;
  margin-left: -0.25em; /* To offset spacing. May vary by font */
.is-Inline .Center-Block {
  max-width: 99%; /* Prevents issues with long content causes the content block to be pushed to the top
  /* max-width: calc(100% - 0.25em) /* Only for IE9+ */
```

• Flexbox法

```
.Center-Container.is-Flexbox {
  display: -webkit-box;
  display: -moz-box;
  display: -ms-flexbox;
  display: -webkit-flex;
  display: flex;
  -webkit-box-align: center;
     -moz-box-align: center;
     -ms-flex-align: center;
  -webkit-align-items: center;
          align-items: center;
  -webkit-box-pack: center;
    -moz-box-pack: center;
     -ms-flex-pack: center;
  -webkit-justify-content: center;
          justify-content: center;
}
```