

Population Coding:

BIO 450/IBS 534 HW #2

Due before 11:59pm, Tuesday, February 4th

For this homework set, we will use study the coding properties of populations of neurons that are arrayed to encode a periodic stimulus (e.g., head-direction cells in the hippocampus). Specifically, we will use receptive fields that can be described via the von Mises distribution ($f(s) = r_{max}e^{\kappa \cos(2-\mu_i)}$), which is essentially a gaussian that has periodic boundary conditions on the circle. To make this process a little easier, the code will take the receptive field width (σ) as an input and will numerically calculate the appropriate value of κ needed to create the appropriate distribution (or, in some cases, it will use N and assume that $\sigma = \pi/N$).

Add the code from Canvas to your path and use `drawReceptiveFields(N)` to draw N evenly-space receptive fields. Try performing this for $N = 5, 10, 15$, and 20 to get a sense of the receptive fields.

1. If $y = Ax^m$, show that $\log y \propto m \log x$.
2. Use `[outputValues,~] = histogramMLEstimates(s,N,rMax,deltaT)` to plot the distribution of maximum likelihood estimates using the population code for $s = 1$ given $N = 10$ neurons, a maximum firing rate (r_{max}) of 20 , and a measurement time (Δt) of 2 . Report the mean ($\langle \hat{s} \rangle$) and standard deviation ($\sigma_{est}(\hat{s})$) of the distribution. Does the distribution look gaussian? (Note: `outputValues` is an array of all simulated estimated values. This will come in handy in a moment.)
3. What is the estimate's normalized error ($\frac{\langle \hat{s} \rangle - s}{\sigma_{est}(\hat{s})}$) for your results in the previous problem. Are these results consistent with those of an unbiased estimator?
4. The Cramér-Rao bound for this system is given by $\sigma_{est}^2(s) \geq \frac{\sqrt{2\pi\sigma^2}}{N^2 r_{max} \Delta t}$, where σ is the width of a single tuning curve. Using this information, estimate the smallest possible Δt you would need to have $\sigma_{est}(s) < 10^{-4}$ (all other parameters remaining the same). Confirm this finding by plugging this value into the above function (note that $\sigma = \pi/N$ here).
5. Calculate and plot ($\langle \hat{s} \rangle - s$) and $\sigma_{est}^2(\hat{s})$ as a function of N for $N = 5, 10, 15, \dots, 50$ (using `[outputValues,~] = histogramMLEstimates(s,N,rMax,deltaT,[],[],false)` to suppress plots). Again, use $s = 1$, $\Delta t = 2$, and $r_{max} = 20$.
6. Plot $\log \sigma_{est}^2(\hat{s})$ vs. $\log N$ from the previous question and calculate the slope of the resulting line. Do these results agree with your intuition from the Cramér-Rao bound? Explain your reasoning.
7. Now we will probe how altering σ , the tuning curve width, affects $\sigma_{est}^2(s)$. Use `[outputValues,~] = histogramMLEstimates(s,N,rMax,deltaT,[],sigma,false)` to find $\sigma_{est}^2(s)$ for $\sigma = 0.08, 0.10, 0.12, \dots, 0.98, 1.00$. Once more, use $s = 1$, $\Delta t = 2$, and $r_{max} = 20$. Plot $\sigma_{est}^2(s)$ vs. σ on a semi-log axis (`semilogy` in Matlab). You should find that the curve is non-monotonic. At what value of σ is the function minimized?

8. Use `drawReceptiveFields(N,rMax,sigma)` to draw the receptive fields for the value of σ that you found in the previous question.
9. Give an intuitive explanation (no equations allowed) as to why there should be an optimal value for σ , rather than the optimal value being infinitely large or infinitesimally small.