

```
% Find Mutual Information for 1ms binned "Words"
```

RUN THIS SECTION 1 TIME PER NEURON TO INITIATE YOUR VARIABLES

```
% Load data for Neuron 1
clear
load('Data_neuron2.mat')

% You should now have two variables in your workspace: spikes and pitches.
% spikes: - has dimensions of 1003 x 6.
% ----- -

% Make a vector for of timebin sizes.

%For the in-class assignment, you'll only need to use the first entry here
%- 40 msec bins. In your own code (on the homework), you can add other time
%bin widths here.
timeBins = [40,20,10,5,2,1];

% Make an empty vector to hold the mutual information values.
% Note- your assignment is to fill this in.
miValues = nan(size(timeBins));
```

STEP 1 BIN SPIKE AND PITCH DATA

```
% Make a vector of spike "words" - the total number of spikes in each 40ms
pre-motor window
% timeBins = [40,20,10,5,2,1];
% timeBins_choice = 6;
% timeBins_size = timeBins(timeBins_choice);
timeBins_size = 1;
for iTrial = 1:length(spikes)
    word = spikes(iTrial,1:end);

    % Segment data into 1 40ms bin.
    % Note- the second argument of the function histcounts dictates the
    % edges of the bins.
    [N, edges] = histcounts(word, -40:timeBins_size:0);

    words(iTrial, :) = N;

end

% Separate pitch into two bins
% First find median pitch
medianPitch = median(pitches);

% Make an empty vector to hold the binned pitch values
```

```

pitchValue = nan(size(pitches));

% Go through all the pitch values and put them into low or high groups
for iPitch = 1:length(pitches)

    % YOUR TURN: Set below-median pitch to be designated as 0
    % Note, here you should be modifying the variable pitchValue(iPitch,1)

    % YOUR TURN: Set above-median pitch to be designated as 1
    % Note, here you should be modifying the variable pitchValue(iPitch,1),
    % but you should never modify it above and here for the same iPitch.

    if pitches(iPitch) < medianPitch
        pitchValue(iPitch,1) = 0;
    else
        pitchValue(iPitch,1) = 1;
    end

end

% These variables will be deleted in the "clearvars" command below. I'm
% putting them here so that you can inspect them.
pitchValue

```

```

pitchValue = 408x1
    1
    1
    1
    1
    0
    1
    0
    1
    0
    1
    :

```

```

medianPitch

```

```

medianPitch =
3.8731e+03

```

```

words

```

```

words = 408x40
    0    0    0    0    0    0    0    1    0    0    0    0    0 ...
    0    0    0    0    0    0    0    1    0    1    0    0    0
    0    0    0    0    1    0    0    0    0    0    1    0    0
    0    0    0    0    0    0    1    0    0    0    0    0    0
    0    0    0    0    0    0    1    0    0    0    0    0    0
    0    0    0    1    0    1    0    1    0    0    0    1    0
    0    0    0    0    1    0    0    0    0    0    0    0    0
    0    0    0    1    0    0    0    0    0    0    0    0    0
    0    1    0    0    0    0    0    0    0    1    0    0    0
    0    0    0    0    0    0    0    0    0    0    0    0    1

```

⋮

STEP 2: FIND ENTROPY IN SPIKES

```
% Remember that  $I(X;Y) = H(X) - H(X|Y)$ .

% First we will find  $H(X)$ , or  $H(\text{spikes})$ .
%  $H(X) = -\text{Sum}(\text{plogp})$ .
% Find the probability of each different spike word.

%Find the all the different unique words
% uniqueWords = unique(words,'rows');
uniqueWords = unique(words,'rows');

% YOUR TURN: Make an empty vector for probabilities that is the length of
the number
% of unique words
pSpikes = zeros(size(uniqueWords,1),1);

% YOUR TURN: Find the total number of words.
totalWords = size(words,1);

% YOUR TURN: Go through each different word
for iWord = 1:size(uniqueWords, 1)

    % Set the word of interest (a single row pattern)
    word = uniqueWords(iWord, :);

    % Find the total number of times this word appears in all trials
    numWord = sum(ismember(words, word, 'rows')); % Ensure row-wise
comparison

    % Divide by the total number of words to get probability
    pSpikes(iWord, 1) = numWord / totalWords; % Assigning to column 1 (not
40)

end

% YOUR TURN: Now we have to find the total entropy of spike words
%
% Note: please use base-2 log – the command for this in MATLAB is log2.m
spikeEntropy = -sum(pSpikes.*log2(pSpikes))
```

```
spikeEntropy =
8.6724
```

```
% Make sure you have all the variables listed below defined.
```

```
% clearvars -except spikeEntropy pitchValue words spikes pitches timeBins  
miValues
```

STEP 3: FIND CONDITIONAL ENTROPY OF SPIKES GIVEN PITCH

```
% We need to split the spiking data into two groups based on the pitch  
% group. We need to keep track of the pitch group and the probability of  
% the data falling into each pitch group.
```

```
% YOUR TURN: Identify the unique pitch values  
pitchGroups = unique(pitchValue)
```

```
pitchGroups = 2x1  
0  
1
```

```
% YOUR TURN: Make an empty vector to store the probabilities of the pitch  
values.
```

```
pPitch = zeros(size(pitchGroups));
```

```
% Make an empty vector to store the conditional entropies for each pitch  
spikeEntropy_pitch = zeros(size(pitchGroups));
```

```
% Find the total number of different pitch values  
totalPitches = size(pitchValue,1);
```

```
% Go through each pitch group, identify spike words that correspond to that  
% group, find the conditional entropy of the spiking for that pitch.
```

```
for iPitch = 1:size(pitchGroups,1)
```

```
    % Find the pitch value for this group  
    pitch = pitchGroups(iPitch,1:end);
```

```
    % YOUR TURN: Identify the trial numbers with this pitch value  
    pitchIndices = find(pitchValue == pitch);
```

```
    % YOUR TURN: Find the total number of trials with this pitch value  
    numPitch = length(pitchIndices);
```

```
    % YOUR TURN: Find the probability of this pitch  
    pPitch(iPitch,1) = numPitch / totalPitches;
```

```
    % Get the spike words for these trial numbers  
    words_pitch = words(pitchIndices,1:end);
```

```
    % Find the entropy of the spike words associated with this pitch value  
    % The following code should be very similar to the code above.
```

```
    %YOUR TURN: Find the all the different unique words  
    uniqueWords_pitch = unique(words_pitch,'rows');
```

```

    % Make an empty vector for probabilities that is the length of the
    number
    % of unique words
    pSpikes_pitch = nan(size(uniqueWords_pitch,1),1);

    % Find the total number of words.
    totalWords_pitch = size(words_pitch,1);

    % Go through each different word
    for iWord_pitch = 1:length(uniqueWords_pitch)

    % Set the word of interest (full row)
        word_pitch = uniqueWords_pitch(iWord_pitch, :);

        % Count occurrences of this word in all trials (row-wise comparison)
        numWord_pitch = sum(ismember(words_pitch, word_pitch, 'rows'));

        % Compute the conditional probability
        pSpikes_pitch(iWord_pitch,1) = numWord_pitch / totalWords_pitch;
    end

    %YOUR TURN: Find the entropy of spiking conditioned on each pitch value
    spikeEntropy_pitch(iPitch,1) = -sum(pSpikes_pitch(pSpikes_pitch > 0) .*
    log2(pSpikes_pitch(pSpikes_pitch > 0)));

end

% These variables will be deleted in the "clearvars" command below. I'm
% putting them here so that you can inspect them.
pPitch

```

```

pPitch = 2x1
    0.5000
    0.5000

```

pSpikes_pitch

```

pSpikes_pitch = 204x1
    0.0049
    0.0049
    0.0049
    0.0049
    0.0049
    0.0049
    0.0049
    0.0049
    0.0049
    0.0049
    :

```

```

% The conditional entropy is just the weighted sum of the spike entropies

```

```
% for each pitch value.
```

```
spikeGivenPitchEntropy = sum(pPitch.*spikeEntropy_pitch);
```

```
%Make sure you have each of the variables listed below defined
```

```
clearvars -except spikeEntropy spikeGivenPitchEntropy pitchValue words  
spikes pitches timeBins miValues
```

STEP 4: FIND MUTUAL INFORMATION BETWEEN SPIKES AND PITCH

```
% Find mutual information for spikes in 40 ms bins
```

```
mi_40 = spikeEntropy - spikeGivenPitchEntropy;
```

```
% Put mutual information into a vector to align with the timebin size for
```

```
% plot
```

```
miValues(1,2) = mi_40
```

```
miValues = 1x6
```

```
NaN
```

```
1.0000
```

```
NaN
```

```
NaN
```


```
NaN
```

```
NaN
```

```
save('workInProgress-Neuron1.mat','miValues','timeBins')
```

Step 5: PLOT MUTUAL INFORMATION

```
plot(timeBins, miValues, '-o', 'LineWidth', 2, 'Color', 'r', 'MarkerSize',  
6);
```



```
% Improve visualization
```

```
xlabel('X Values');
```

```
ylabel('Y Values');
```

```
title('Bar Plot with Line Connection');
```

```
grid on;
```