**((Ccovesion**

Device Specification
WG-15XX

Free space PPLN Chip for CW Second Harmonic Generation (SHG)

Designed for OEM Researchers who need watt level output through a reliable method of SHG generation with C-band sources.

- **A reliable method of C-band pumped SHG**
- **Will also perform SPDC**
- **Simple to use**
- **Compatible with our PPLN ovens and OC3 temperature controller**
- **WG Pre-angled for optical path aligned to the oven**
- **Custom options available**

Specification	
Non-Linear Interaction	Type 0 (ee-e)
Input wavelength range for SHG [nm] (±2nm tuning)	1535-1570
Output wavelength range [nm]	767.5-785
Input Polarisation Alignment	e-pol (polarisation axis aligned to the crystal thickness)
Phase match temperature between [ºC]	30 to 110
Recommended max. CW pump launch [W]	4.5
Typical Output MFD @1560nm (2nd moment) ±20%	x = ~10.0µm y = ~8.8µm
Typical Output NA @1560nm ±20%	x = ~0.094, y = ~0.113
Typical Output MFD @780nm (2nd moment) ±20%	x = ~9.9µm y = ~8.3µm
Typical Output NA @780nm ±20%	x = 0.092, y = 0.085
WG End-facet AR Coating	775nm/1550nm Dual Band
Clip Dimension for 40mm long waveguide [mm]	40 x 5 x 1
End Facet Angle (Relative to Waveguide Length)	5.35º

*Specifications are representative of typical product performance

Contact us to discuss availability and pricing

Free space PPLN Chip for CW Second Harmonic Generation (SHG)

Designed for OEM Researchers who need watt level output through a reliable method of SHG generation with C-band sources.

Length 40mm

Reference Mark

5 ± 0.5 mm

1.0 ± 0.05 mm

Side view Ridge waveguide

Reference mark

1 2 3 4 5

~110µm

Accessories
OC3 Temperature Controller
PPLN oven

For more information, please contact us at:
Email: sales@covesion.com Tel: +44 (0)1794 521638

www.covesion.com

MADE IN BRITAIN

covesion