

UEFI & EDK II TRAINING EDK II Debugging through UEFI Boot Flow

tianocore.org



DEBUGGING COMMANDS CpuBreakpoint() added to Source



Source Level Debugging

View call stack

Insert CpuBreakpoint()

View and edit local/global variables

Set breakpoint Step into/over routines

View disassembled code

View/edit general purpose register values



CpuBreakpoint Vs. CpuDeadLoop

CpuBreakpoint

When using a Software debugger:

- Visual Studio
- GDB (ovmf with qemu)
- Intel® UDK Debugger
- Windriver* Simics
- Debug agent –SourceLevelDebugPkg

CpuDeadLoop

When using a Hardware debugger:

- In-Target Probe (ITP)
- Intel® SVT DCI cable
- Intel[®] SVT Closed Chassis Adapter (CCA)
- other 3rd Party Hardware (i.e. <u>Lauterbach</u> w/ JTAG)

The functions CpuBreakpoint() and CpuDeadLoop() are part of the EDK II Base Libraries and can be compiled with any UEFI or PI Module at any phase of the boot flow (SEC, PEI, DXE, BDS, TSL)



Special DCI Breakpoint with HW Debugger

CpuIceBreakpoint

The Intel Architecture has a special op-code for a breakpoint: int1 Better than a CpuDeadLoop() since it halts the processor. Better trace information

Downside:

- Requires a Hardware Debugger with DCI capabilities to intercept the int1 op code
- There is no "C" equivalent needs to be assembly code

Example of this code is the downloaded Lab Material: . . . /LabSampleCode/CpuIceBreakpoint Code




DEBUGGING THRU BOOT FLOW

Add Breakpoints to the Compiled BIOS / Firmware Source Code




Debugging the Boot Phases





Debugging the Boot Phases - SEC




Debugging Sec Phase

Hardware debugger capable only

- Break at the Reset Vector
- Check temporary memory CAR NEM
- Enable the "C" Code
- Transfer control to PEI



Debugging the Boot Phases - PEI



- Use debugger prior to PEI Main
- Check proper execution of PEI drivers
- Execute basic chipset & Memory init.
- Check memory availability
- Complete flash accessibility
- Execute recovery driver
- Detect DXE IPL



PEI Phase: Trace Each PEIM

There is a loop function in:

MdeModulePkg/Core/Pei/Dispatcher/Dispatcher.c

Add CpuBreakpoint(); before launching each PEIM



Check for transition from PEI to DXE

Critical point before calling DXE in:

MdeModulePkg/Core/Pei/PeiMain.c

Add CpuBreakpoint(); before entering Dxelpl

```
VOID
EFIAPI
PeiCore (
 IN CONST EFI_SEC_PEI_HAND_OFF
                                       *SecCoreDataPtr,
 IN CONST EFI_PEI_PPI_DESCRIPTOR
                                       *PpiList,
                                       *Data
  IN VOID
    Enter DxeIpl to load Dxe core.
 DEBUG ((EFI_D_INFO, "DXE IPL Entry\n"));
// Add a call to CpuBreakpoint(); approx. line 512
  CpuBreakpoint();
 Status = TempPtr.DxeIpl->Entry (
                             TempPtr.DxeIpl,
                             &PrivateData.Ps,
                             PrivateData.HobList
```



Check for transition from Dxelpl to DXE

Critical point before calling DXE Core in:

MdeModulePkg/Core/DxelplPeim/DxeLoad.c


Before entering Dxe Core (Notice also this is a standalone module - Dxelpl.efi)

```
EFI STATUS
EFIAPI
DxeLoadCore (
 IN CONST EFI_DXE_IPL_PPI *This,
 IN EFI_PEI_SERVICES **PeiServices,
  IN EFI PEI HOB POINTERS HobList
  // Transfer control to the DXE Core
  // The hand off state is simply a pointer to the HOB list
// Add a call to CpuBreakpoint(); approx. line 448
  CpuBreakpoint();
 HandOffToDxeCore (DxeCoreEntryPoint, HobList);
  // If we get here, then the DXE Core returned. This is an error
```

13



Debugging the Boot Phases - DXE



- Search for cyclic dependency check
- Trace ASSERTs caused during DXE execution
- Debug individual DXE drivers
- Check for architectural protocol failure
- Ensure BDS entry call



DXE: Trace Each Driver Load

DXE Dispatcher calls to each driver's entry point in:


MdeModulePkg/Core/Dxe/Image/Image.c

Break every time a DXE driver is loaded.

```
EFI_STATUS
EFIAPI
CoreStartImage (
 IN EFI_HANDLE ImageHandle,
 OUT UINTN *ExitDataSize,
                **ExitData OPTIONAL
 OUT CHAR16
    // Call the image's entry point
   Image->Started = TRUE;
// Add a call to CpuBreakpoint(); approx. line 1650
   CpuBreakpoint();
    Image->Status = Image->EntryPoint (ImageHandle, Image->Info.SystemTable);
```



Debugging the Boot Phases - BDS



- Detect console devices (input and output)
- Check enumeration of all devices' preset
- Detect boot policy
- Ensure BIOS "front page" is loaded



BDS Phase – Entry Point

DXE call to BDS entry point in:


MdeModulePkg/Core/Dxe/DxeMain/DxeMain.c

Add CpuBreakpoint(); to break before BDS.

```
VOID
EFIAPI
DxeMain (
  IN VOID *HobStart
    Transfer control to the BDS Architectural Protocol
// Add a call to CpuBreakpoint(); approx. line 550
  CpuBreakpoint();
  gBds->Entry (gBds);
    BDS should never return
  ASSERT (FALSE);
  CpuDeadLoop ();
```



Debugging the Boot Phases - Pre-Boot



- "C" source debugging
- UEFI Drivers
 - Init
 - Start
 - Supported
- UEFI Shell Applications
 - Entry point
 - Local variables
- CpuBreakpoint()



Debug in Pre-Boot – UEFI Shell Application

Add CpuBreakpoint() to SampleApp.c near the entry point

Add SampleApp.inf to the platform .dsc file

```
bash$ cd <edk2 workspace directory>
bash$ . edksetup.sh
bash$ build -m SampleApp/SampleApp.inf
```

Copy the binary SampleApp.efi to USB drive

```
SampleApp.c(~/src/edk2-ws/edk2/SampleApp) - gedit
                                                                  Save
EFI STATUS
EFIAPI
UefiMain (
                        ImageHandle,
  IN EFI HANDLE
  IN EFI SYSTEM TABLE
                        *SvstemTable
       UINTN
                           EventIndex;
       BOOLEAN
                          ExitLoop;
       EFI INPUT KEY
                          Key;
       DEBUG((0xfffffffff, "\n\nUEFI Base Training DEBUG DEMO\n"));
       CpuBreakpoint();
```









Return to Main Training Page



Return to Training Table of contents for next presentation link





ACKNOWLEDGEMENTS

Redistribution and use in source (original document form) and 'compiled' forms (converted to PDF, epub, HTML and other formats) with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code (original document form) must retain the above copyright notice, this list of conditions and the following disclaimer as the first lines of this file unmodified.

Redistributions in compiled form (transformed to other DTDs, converted to PDF, epub, HTML and other formats) must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS DOCUMENTATION IS PROVIDED BY TIANOCORE PROJECT "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL TIANOCORE PROJECT BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS DOCUMENTATION, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 2021, Intel Corporation. All rights reserved.