
Chapter 9: Main Memory



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP

Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html

Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html


Silberschatz, Galvin and Gagne ©2018



Chapter 9: Memory Management

- Background
- Contiguous Memory Allocation
- Paging
- Structure of the Page Table
- Swapping
- Example: The Intel 32 and 64-bit Architectures
- Example: ARMv8 Architecture

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Objectives

- To provide a detailed description of various ways of organizing memory hardware
- To discuss various memory-management techniques,
- To provide a detailed description of the Intel Pentium, which supports both pure segmentation and segmentation with paging

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Background

- Program must be brought (from disk) into memory and placed within a process for it to be run
- Main memory and registers are only storage CPU can access directly
- Memory unit only sees a stream of:
  - addresses + read requests, or
  - address + data and write requests
- Register access is done in one CPU clock (or less)
- Main memory can take many cycles, causing a **stall**
- **Cache** sits between main memory and CPU registers
- Protection of memory required to ensure correct operation


KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Protection

- Need to censure that a process can access only access those addresses in it address space.
- We can provide this protection by using a pair of **base** and **limit registers** define the logical address space of a process




KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Hardware Address Protection

- CPU must check every memory access generated in user mode to be sure it is between base and limit for that user



- the instructions to loading the base and limit registers are privileged

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Address Binding

- Programs on disk, ready to be brought into memory to execute form an **input queue**
  - Without support, must be loaded into address 0000
- Inconvenient to have first user process physical address always at 0000
  - How can it not be?
- Addresses represented in different ways at different stages of a program's life
  - Source code addresses usually symbolic
  - Compiled code addresses **bind** to relocatable addresses
    - i.e., "14 bytes from beginning of this module"
  - Linker or loader will bind relocatable addresses to absolute addresses
    - i.e., 74014
  - Each binding maps one address space to another

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Binding of Instructions and Data to Memory


- Address binding of instructions and data to memory addresses can happen at three different stages
  - **Compile time**: If memory location known a priori, **absolute code** can be generated; must recompile code if starting location changes
  - **Load time**: Must generate **relocatable code** if memory location is not known at compile time
  - **Execution time**: Binding delayed until run time if the process can be moved during its execution from one memory segment to another
    - Need hardware support for address maps (e.g., base and limit registers)

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Multistep Processing of a User Program



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP

Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html

Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Logical vs. Physical Address Space

- The concept of a logical address space that is bound to a separate **physical address space** is central to proper memory management
  - **Logical address** – generated by the CPU; also referred to as **virtual address**
  - **Physical address** – address seen by the memory unit
- Logical and physical addresses are the same in compile-time and load-time address-binding schemes; logical (virtual) and physical addresses differ in execution-time address-binding scheme
- **Logical address space** is the set of all logical addresses generated by a program
- **Physical address space** is the set of all physical addresses generated by a program


KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Memory-Management Unit (MMU)

- Hardware device that at run time maps virtual to physical address



- Many methods possible, covered in the rest of this chapter

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html





Memory-Management Unit (Cont.)

- Consider simple scheme. which is a generalization of the base-register scheme.
- The base register now called **relocation register**
- The value in the relocation register is added to every address generated by a user process at the time it is sent to memory
- The user program deals with *logical* addresses; it never sees the *real* physical addresses
  - Execution-time binding occurs when reference is made to location in memory
  - Logical address bound to physical addresses


KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Memory-Management Unit (Cont.)

- Consider simple scheme. which is a generalization of the base-register scheme.
- The base register now called **relocation register**
- The value in the relocation register is added to every address generated by a user process at the time it is sent to memory



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html





Dynamic Loading

- The entire program does need to be in memory to execute
- Routine is not loaded until it is called
- Better memory-space utilization; unused routine is never loaded
- All routines kept on disk in relocatable load format
- Useful when large amounts of code are needed to handle infrequently occurring cases
- No special support from the operating system is required
  - Implemented through program design
  - OS can help by providing libraries to implement dynamic loading

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Dynamic Linking

- **Static linking** – system libraries and program code combined by the loader into the binary program image
- Dynamic linking –linking postponed until execution time
- Small piece of code, **stub**, used to locate the appropriate memory-resident library routine
- Stub replaces itself with the address of the routine, and executes the routine
- Operating system checks if routine is in processes' memory address
  - If not in address space, add to address space
- Dynamic linking is particularly useful for libraries
- System also known as **shared libraries**
- Consider applicability to patching system libraries
  - Versioning may be needed

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Contiguous Allocation

- Main memory must support both OS and user processes
- Limited resource, must allocate efficiently
- Contiguous allocation is one early method
- Main memory usually into two **partitions**:
  - Resident operating system, usually held in low memory with interrupt vector
  - User processes then held in high memory
  - Each process contained in single contiguous section of memory

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Contiguous Allocation (Cont.)


- Relocation registers used to protect user processes from each other, and from changing operating-system code and data
  - Base register contains value of smallest physical address
  - Limit register contains range of logical addresses – each logical address must be less than the limit register
  - MMU maps logical address *dynamically*
  - Can then allow actions such as kernel code being **transient** and kernel changing size

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Hardware Support for Relocation and Limit Registers




KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Variable Partition

- Multiple-partition allocation
  - Degree of multiprogramming limited by number of partitions
  - **Variable-partition** sizes for efficiency (sized to a given process' needs)
  - **Hole** – block of available memory; holes of various size are scattered throughout memory
  - When a process arrives, it is allocated memory from a hole large enough to accommodate it
  - Process exiting frees its partition, adjacent free partitions combined
  - Operating system maintains information about:
    a) allocated partitions b) free partitions (hole)



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Dynamic Storage-Allocation Problem

How to satisfy a request of size ***n*** from a list of free holes?

- **First-fit**: Allocate the ***first*** hole that is big enough
- **Best-fit**: Allocate the ***smallest*** hole that is big enough; must search entire list, unless ordered by size
  - Produces the smallest leftover hole
- **Worst-fit**: Allocate the ***largest*** hole; must also search entire list
  - Produces the largest leftover hole

First-fit and best-fit better than worst-fit in terms of speed and storage utilization

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Fragmentation

- **External Fragmentation** – total memory space exists to satisfy a request, but it is not contiguous
- **Internal Fragmentation** – allocated memory may be slightly larger than requested memory; this size difference is memory internal to a partition, but not being used
- First fit analysis reveals that given *N* blocks allocated, 0.5 *N* blocks lost to fragmentation
  - 1/3 may be unusable -> **50-percent rule**

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Fragmentation (Cont.)

- Reduce external fragmentation by **compaction**
  - Shuffle memory contents to place all free memory together in one large block
  - Compaction is possible *only* if relocation is dynamic, and is done at execution time
  - I/O problem
    - Latch job in memory while it is involved in I/O
    - Do I/O only into OS buffers
- Now consider that backing store has same fragmentation problems

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Paging

- Physical address space of a process can be noncontiguous; process is allocated physical memory whenever the latter is available
  - Avoids external fragmentation
  - Avoids problem of varying sized memory chunks
- Divide physical memory into fixed-sized blocks called **frames**
  - Size is power of 2, between 512 bytes and 16 Mbytes
- Divide logical memory into blocks of same size called **pages**
- Keep track of all free frames
- To run a program of size ***N*** pages, need to find ***N*** free frames and load program
- Set up a **page table** to translate logical to physical addresses
- Backing store likewise split into pages
- Still have Internal fragmentation


KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Address Translation Scheme

- Address generated by CPU is divided into:
  - **Page number** (***p***) – used as an index into a **page table** which contains base address of each page in physical memory
  - **Page offset** (***d***) – combined with base address to define the physical memory address that is sent to the memory unit




  - For given logical address space 2^m and page size 2^n

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Paging Hardware




KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Paging Model of Logical and Physical Memory




KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Paging Example

- Logical address: n = 2 and m = 4. Using a page size of 4 bytes and a physical memory of 32 bytes (8 pages)



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Paging -- Calculating internal fragmentation


- Page size = 2,048 bytes
- Process size = 72,766 bytes
- 35 pages + 1,086 bytes
- Internal fragmentation of 2,048 - 1,086 = 962 bytes
- Worst case fragmentation = 1 frame – 1 byte
- On average fragmentation = 1 / 2 frame size
- So small frame sizes desirable?
- But each page table entry takes memory to track
- Page sizes growing over time
  - Solaris supports two page sizes – 8 KB and 4 MB

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Free Frames



Before allocation

After allocation

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Implementation of Page Table

- Page table is kept in main memory
  - **Page-table base register** (**PTBR**) points to the page table
  - **Page-table length register** (**PTLR**) indicates size of the page table
- In this scheme every data/instruction access requires two memory accesses
  - One for the page table and one for the data / instruction
- The two-memory access problem can be solved by the use of a special fast-lookup hardware cache called **translation look-aside buffers** (**TLBs**) (also called **associative memory**).

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Translation Look-Aside Buffer

- Some TLBs store **address-space identifiers** (**ASIDs**) in each TLB entry – uniquely identifies each process to provide address-space protection for that process
  - Otherwise need to flush at every context switch
- TLBs typically small (64 to 1,024 entries)
- On a TLB miss, value is loaded into the TLB for faster access next time
  - Replacement policies must be considered
  - Some entries can be **wired down** for permanent fast access

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Hardware

- Associative memory – parallel search

Page #	Frame #


- Address translation (p, d)
  - If p is in associative register, get frame # out
  - Otherwise get frame # from page table in memory

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Paging Hardware With TLB



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html





Effective Access Time

- Hit ratio – percentage of times that a page number is found in the TLB
- An 80% hit ratio means that we find the desired page number in the TLB 80% of the time.
- Suppose that 10 nanoseconds to access memory.
  - If we find the desired page in TLB then a mapped-memory access take 10 ns
  - Otherwise we need two memory access so it is 20 ns
- **Effective Access Time** (**EAT**)


  EAT = 0.80 x 10 + 0.20 x 20 = 12 nanoseconds

  implying 20% slowdown in access time
- Consider amore realistic hit ratio of 99%,

  EAT = 0.99 x 10 + 0.01 x 20 = 10.1ns

  implying only 1% slowdown in access time.

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Memory Protection


- Memory protection implemented by associating protection bit with each frame to indicate if read-only or read-write access is allowed
  - Can also add more bits to indicate page execute-only, and so on
- **Valid-invalid** bit attached to each entry in the page table:
  - "valid" indicates that the associated page is in the process' logical address space, and is thus a legal page
  - "invalid" indicates that the page is not in the process' logical address space
  - Or use **page-table length register** (**PTLR**)
- Any violations result in a trap to the kernel

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Valid (v) or Invalid (i) Bit In A Page Table



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Shared Pages


- **Shared code**
  - One copy of read-only (**reentrant**) code shared among processes (i.e., text editors, compilers, window systems)
  - Similar to multiple threads sharing the same process space
  - Also useful for interprocess communication if sharing of read-write pages is allowed
- **Private code and data**
  - Each process keeps a separate copy of the code and data
  - The pages for the private code and data can appear anywhere in the logical address space

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Shared Pages Example



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Structure of the Page Table

- Memory structures for paging can get huge using straight-forward methods
  - Consider a 32-bit logical address space as on modern computers
  - Page size of 4 KB (2^{12})
  - Page table would have 1 million entries (2^{32} / 2^{12})
  - If each entry is 4 bytes ➔ each process 4 MB of physical address space for the page table alone
    - Don't want to allocate that contiguously in main memory
  - One simple solution is to divide the page table into smaller units
    - Hierarchical Paging
    - Hashed Page Tables
    - Inverted Page Tables


KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Hierarchical Page Tables

- Break up the logical address space into multiple page tables
- A simple technique is a two-level page table
- We then page the page table




KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Two-Level Paging Example

- A logical address (on 32-bit machine with 1K page size) is divided into:
  - a page number consisting of 22 bits
  - a page offset consisting of 10 bits
- Since the page table is paged, the page number is further divided into:
  - a 10-bit page number
  - a 12-bit page offset
- Thus, a logical address is as follows:




- where p_1 is an index into the outer page table, and p_2 is the displacement within the page of the inner page table
- Known as **forward-mapped page table**

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Address-Translation Scheme




KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






64-bit Logical Address Space

- Even two-level paging scheme not sufficient
- If page size is 4 KB (2^{12})
  - Then page table has 2^{52} entries
  - If two level scheme, inner page tables could be 2^{10} 4-byte entries
  - Address would look like




  - Outer page table has 2^{42} entries or 2^{44} bytes
  - One solution is to add a 2nd outer page table
  - But in the following example the 2nd outer page table is still 2^{34} bytes in size
    - And possibly 4 memory access to get to one physical memory location


KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Three-level Paging Scheme





KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Hashed Page Tables


- Common in address spaces > 32 bits
- The virtual page number is hashed into a page table
  - This page table contains a chain of elements hashing to the same location
- Each element contains (1) the virtual page number (2) the value of the mapped page frame (3) a pointer to the next element
- Virtual page numbers are compared in this chain searching for a match
  - If a match is found, the corresponding physical frame is extracted
- Variation for 64-bit addresses is **clustered page tables**
  - Similar to hashed but each entry refers to several pages (such as 16) rather than 1
  - Especially useful for **sparse** address spaces (where memory references are non-contiguous and scattered)

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Hashed Page Table



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Inverted Page Table


- Rather than each process having a page table and keeping track of all possible logical pages, track all physical pages
- One entry for each real page of memory
- Entry consists of the virtual address of the page stored in that real memory location, with information about the process that owns that page
- Decreases memory needed to store each page table, but increases time needed to search the table when a page reference occurs
- Use hash table to limit the search to one — or at most a few — page-table entries
  - TLB can accelerate access
- But how to implement shared memory?
  - One mapping of a virtual address to the shared physical address

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Inverted Page Table Architecture



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Oracle SPARC Solaris

- Consider modern, 64-bit operating system example with tightly integrated HW
  - Goals are efficiency, low overhead
- Based on hashing, but more complex
- Two hash tables
  - One kernel and one for all user processes
  - Each maps memory addresses from virtual to physical memory
  - Each entry represents a contiguous area of mapped virtual memory,
    - More efficient than having a separate hash-table entry for each page
  - Each entry has base address and span (indicating the number of pages the entry represents)

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Oracle SPARC Solaris (Cont.)

- TLB holds translation table entries (TTEs) for fast hardware lookups
  - A cache of TTEs reside in a translation storage buffer (TSB)
    - Includes an entry per recently accessed page
- Virtual address reference causes TLB search
  - If miss, hardware walks the in-memory TSB looking for the TTE corresponding to the address
    - If match found, the CPU copies the TSB entry into the TLB and translation completes
    - If no match found, kernel interrupted to search the hash table
      - The kernel then creates a TTE from the appropriate hash table and stores it in the TSB, Interrupt handler returns control to the MMU, which completes the address translation.

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Swapping

- A process can be **swapped** temporarily out of memory to a backing store, and then brought **back** into memory for continued execution
  - Total physical memory space of processes can exceed physical memory
- **Backing store** – fast disk large enough to accommodate copies of all memory images for all users; must provide direct access to these memory images
- **Roll out, roll in** – swapping variant used for priority-based scheduling algorithms; lower-priority process is swapped out so higher-priority process can be loaded and executed
- Major part of swap time is transfer time; total transfer time is directly proportional to the amount of memory swapped
- System maintains a **ready queue** of ready-to-run processes which have memory images on disk

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Swapping (Cont.)


- Does the swapped out process need to swap back in to same physical addresses?
- Depends on address binding method
  - Plus consider pending I/O to / from process memory space
- Modified versions of swapping are found on many systems (i.e., UNIX, Linux, and Windows)
  - Swapping normally disabled
  - Started if more than threshold amount of memory allocated
  - Disabled again once memory demand reduced below threshold

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Schematic View of Swapping



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Context Switch Time including Swapping

- If next processes to be put on CPU is not in memory, need to swap out a process and swap in target process
- Context switch time can then be very high
- 100MB process swapping to hard disk with transfer rate of 50MB/sec
  - Swap out time of 2000 ms
  - Plus swap in of same sized process
  - Total context switch swapping component time of 4000ms (4 seconds)
- Can reduce if reduce size of memory swapped – by knowing how much memory really being used
  - System calls to inform OS of memory use via `request_memory()` and `release_memory()`

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Context Switch Time and Swapping (Cont.)

- Other constraints as well on swapping
  - Pending I/O – can't swap out as I/O would occur to wrong process
  - Or always transfer I/O to kernel space, then to I/O device
    - Known as **double buffering**, adds overhead
- Standard swapping not used in modern operating systems
  - But modified version common
    - Swap only when free memory extremely low

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Swapping on Mobile Systems


- Not typically supported
  - Flash memory based
    - Small amount of space
    - Limited number of write cycles
    - Poor throughput between flash memory and CPU on mobile platform
- Instead use other methods to free memory if low
  - iOS ***asks*** apps to voluntarily relinquish allocated memory
    - Read-only data thrown out and reloaded from flash if needed
    - Failure to free can result in termination
  - Android terminates apps if low free memory, but first writes **application state** to flash for fast restart
  - Both OSes support paging as discussed below

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Swapping with Paging



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Example: The Intel 32 and 64-bit Architectures

- Dominant industry chips
- Pentium CPUs are 32-bit and called IA-32 architecture
- Current Intel CPUs are 64-bit and called IA-64 architecture
- Many variations in the chips, cover the main ideas here

KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Example: The Intel IA-32 Architecture

- Supports both segmentation and segmentation with paging
  - Each segment can be 4 GB
  - Up to 16 K segments per process
  - Divided into two partitions
    - First partition of up to 8 K segments are private to process (kept in **local descriptor table** (**LDT**))
    - Second partition of up to 8K segments shared among all processes (kept in **global descriptor table** (**GDT**))


KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Example: The Intel IA-32 Architecture (Cont.)

- CPU generates logical address
  - Selector given to segmentation unit
    - Which produces linear addresses




  - Linear address given to paging unit
    - Which generates physical address in main memory
    - Paging units form equivalent of MMU
    - Pages sizes can be 4 KB or 4 MB


KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Logical to Physical Address Translation in IA-32






KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Intel IA-32 Segmentation




KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Intel IA-32 Paging Architecture




KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html






Intel IA-32 Page Address Extensions

- 32-bit address limits led Intel to create **page address extension** (**PAE**), allowing 32-bit apps access to more than 4GB of memory space
  - Paging went to a 3-level scheme
  - Top two bits refer to a **page directory pointer table**
  - Page-directory and page-table entries moved to 64-bits in size
  - Net effect is increasing address space to 36 bits – 64GB of physical memory









Intel x86-64

- Current generation Intel x86 architecture
- 64 bits is ginormous (> 16 exabytes)
- In practice only implement 48 bit addressing
  - Page sizes of 4 KB, 2 MB, 1 GB
  - Four levels of paging hierarchy
- Can also use PAE so virtual addresses are 48 bits and physical addresses are 52 bits




KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP
Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html
Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html







Example: ARM Architecture

- Dominant mobile platform chip (Apple iOS and Google Android devices for example)
- Modern, energy efficient, 32-bit CPU
- 4 KB and 16 KB pages
- 1 MB and 16 MB pages (termed **sections**)
- One-level paging for sections, two-level for smaller pages
- Two levels of TLBs
  - Outer level has two micro TLBs (one data, one instruction)
  - Inner is single main TLB
  - First inner is checked, on miss outers are checked, and on miss page table walk performed by CPU





End of Chapter 9



KIẾN THỨC - KỸ NĂNG - SÁNG TẠO - HỘI NHẬP

Sứ mệnh - Tầm nhìn: https://ut.edu.vn/articles/su-menh---tam-nhin-13.html

Triết lý giáo dục: https://ut.edu.vn/articles/triet-ly-giao-duc-119.html

Silberschatz, Galvin and Gagne ©2018