


SL-ULTRA PLUS 8KW 11KW



SunLife
SOLAR (PVT.) LTD.

- BUILT-IN WI-FI FOR MOBILE MONITORING
- MAX PV POWER 10000W
- DUAL OUTPUT FOR SMART LOAD MANAGEMENT
- AC OUTPUT 8000W
- BUILT-IN DC OUTPUT FOR DC FAN, LED BULB, ROUTER, ETC



- 48VDC BATTERY VOLTAGE
- PARALLEL CAPABILITY UP TO 6 UNITS
- MPPT
- NET METERING FUNCTIONALITY
- RESERVED COMMUNICATION PORT FOR BMS

MODEL	SL-ULTRA PLUS 8KW	SL-ULTRA PLUS 11KW
RATED POWER	8000VA/8000W	11000VA/11000W
PARALLEL CAPABILITY	YES, 6 units	
INPUT		
Voltage	230 VAC	
Selectable Voltage Range	V170-280 AC (For Personal Computers) ; 90-280 VAC (For Home Appliances)	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Mode)	230VAC \pm 5%	
Surge Power	16000VA	22000VA
Efficiency (Peak)	93%	
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)	
Waveform	Pure sine wave	
BATTERY		
Battery Voltage	48 VDC	
Floating Charge Voltage	54 VDC	
Overcharge Protection	63 VDC	
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	
Maximum PV Array Power	10000W (5000W x 2)	12000W (5000W x 2)
MPPT Range @ Operating Voltage	90 ~ 450 VDC	
Maximum PV Array Open Circuit Voltage	500 VDC	
Maximum Solar Charge Current	150A	
Maximum AC Charge Current	120A	150A
Maximum Charge Current	150A	
PHYSICAL		
Dimension, D x W x H (mm)	145 x 438 x 553.6	
Net Weight (kgs)	18.4	
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact/BTS	
External Current Sensor Port	Support optional GFCI, Rapid shutdown, AFCI detection Yes, built-in current transformer sensor	
OPERATING ENVIRONMENT		
Humidity	5% to 95% Relative Humidity(Non-condensing)	
Operating Temperature	-10°C to 50°C	
Storage Temperature	-15°C to 60°C	
STANDARD		
Compliance Safety	CE	

Product specifications are subject to change without further notice.