POSTS AND TELECOMMUNICATIONS INSTITUTE OF TECHNOLOGY
Faculty of Information Technology 1

Course: Information System Analysis and Design

COURSE ESSAY

ABC ONLINE SHOP: FROM REQUIREMENTS TO CODE

Requirement determination, analysis, AI in e-commerce, design and implementation of an e-commerce information system

Student:	Bế Quốc Khánh (KHANHBQ)
Student ID:	B23DCCE049
Class:	04
Lecturer:	PGS.TS. Trần Đình Quế
Version:	V1
Submitted:	Report, Visual Paradigm project, source code, demo results

Hanoi, October 2026

ABSTRACT

This essay follows one information system, the **ABC Online Shop**, through the five activities named in the essay brief: requirement determination, analysis, artificial intelligence in e-commerce, design and code. The material was built up during the semester. Assignment 01 investigated the shop and its problems, Assignment 02 turned them into a requirements baseline with 32 use cases, Assignment 03 and Test 01 practised the data-flow, interaction, class and data models, and Assignment 06 produced a three-layer multimodal search prototype. The essay joins these pieces into one path from a business problem to a running program and explains the decision taken at each joint.

The main results are: a requirements baseline of 7 business problems, 14 stakeholder needs, 24 functional and 12 non-functional requirements traced to 32 use cases; an analysis model with activity, data-flow, sequence, class, state and entity-relationship diagrams; three AI components (multimodal search, aspect-based review insights and a stock-aware recommender) analysed as ordinary requirements with their own risks and fallbacks; a layered design obtained in four documented steps (methods, use dependencies, data access objects, MVC packages); and a working Python application of about 3,300 lines with a web interface, a SQLite database, 40 automated tests and an evaluation script. All 27 diagrams are kept in one Visual Paradigm project (TieuLuan_KHANHBQ.vpp). On the test sets, the search returns the expected item first for 24 of 26 queries (92.3%), the review analyser reaches an aspect F1 of 0.96, and every order-state and stock rule of the requirements is checked by a test.

Keywords: requirements engineering, use case, data flow diagram, UML, data modeling, DAO, MVC, layered architecture, multimodal search, aspect-based sentiment analysis, recommendation, Python.

Abbreviations

Table 1. Abbreviations used in the essay

Abbreviation	Meaning
ABSA	Aspect-based sentiment analysis
AI	Artificial intelligence
BCE	Boundary, control, entity (analysis object stereotypes)
BP	Business problem (Assignment 01)
DAO	Data access object
DFD	Data flow diagram
ERD	Entity relationship diagram
FR / NFR	Functional / non-functional requirement
MoSCoW	Must, Should, Could, Won't (prioritisation)
MVC	Model, view, controller
SN	Stakeholder need
TF-IDF	Term frequency, inverse document frequency
UC	Use case

Abbreviation	Meaning
UML	Unified Modeling Language
VP	Visual Paradigm, the modeling tool of all diagrams
WSGI	Web Server Gateway Interface (Python web standard)

CONTENTS

ABSTRACT **1**

Abbreviations 1

INTRODUCTION **9**

CHAPTER 1. REQUIREMENT DETERMINATION **10**

1.1. Requirements in the Development Life Cycle 10

1.2. Investigation Approach 10

1.3. Business Context 10

1.4. Stakeholder Analysis 11

1.5. Business Process 12

1.6. Information Analysis 12

1.7. Current Problems 12

1.8. Scope, Boundary and Context 13

1.9. System Objectives 14

1.10. Stakeholder Needs 15

1.11. Functional Requirements 15

1.12. Non-functional Requirements 16

1.13. Prioritisation and Assumptions 17

1.14. Actors and the Use Case Model 17

1.15. Use Case Specification: UC08 Place Order 20

1.16. Validation and Traceability 21

1.17. Requirements for the AI Extensions 22

1.18. Elicitation Questions and Assumptions 22

1.19. From Problems to Objectives 23

1.20. Further Use Case Specifications 24

1.21. Acceptance Criteria 25

1.22. Managing Requirement Change 25

1.23. Chapter Summary 25

CHAPTER 2. ANALYSIS **26**

2.1. From Requirements to Analysis Models 26

2.2. Activity Modeling 26

2.3. Data Flow Modeling 31

2.4. Interaction Modeling 32

2.5. Analysis Class Model 34

2.6. Order State Machine 36
2.7. Data Modeling 38
2.8. Consistency Across Models 40
2.9. Business Rules and Decision Logic 40
2.10. Class Responsibilities 41
2.11. From Classes to Tables 42
2.12. CRUD Matrix 42
2.13. Chapter Summary 43
CHAPTER 3. AI IN E-COMMERCE 44
3.1. AI as an Enhancement Layer 44
3.2. Opportunity Analysis 44
3.3. AI Use Cases 45
3.4. Multimodal Search: Principles 45
3.5. Retrieval and Ranking 46
3.6. Review Insights 50
3.7. Recommendation 52
3.8. Data Requirements 52
3.9. Evaluation 53
3.10. Error Analysis 54
3.11. Risks, Fallbacks and Human Control 55
3.12. Technology Options for a Production Version 55
3.13. AI Component Specifications 56
3.14. Worked Example: Ranking a Combined Query 56
3.15. Worked Example: Analysing One Review 57
3.16. Business Evaluation 57
3.17. AI Traceability 57
3.18. Chapter Summary 58
CHAPTER 4. DESIGN 59
4.1. Design Goals 59
4.2. Choosing the Architecture 59
4.3. Step 1: Adding Methods 60
4.4. Step 2: From Associations to Use Dependencies 62
4.5. Step 3: Data Access Objects 65
4.6. Step 4: Packages and the MVC Architecture 67

4.7. Database Design 69
4.8. Transactions and Idempotency in Checkout 70
4.9. Web Interface Design 70
4.10. Security and Privacy by Design 71
4.11. Design for Testability 72
4.12. Design Decisions and Trade-offs 72
4.13. From Analysis Classes to Design Classes 73
4.14. Service Layer Specification 73
4.15. Interfaces to External Systems 74
4.16. Error Handling Design 74
4.17. Design Patterns Used 75
4.18. Chapter Summary 75
CHAPTER 5. CODE **76**
5.1. Implementation Strategy and Environment 76
5.2. Project Structure 76
5.3. The Model 77
5.4. Data Access Objects 77
5.5. Services: Checkout and Payment 78
5.6. Controllers and Views 80
5.7. AI Components in Code 85
5.8. Running the Application 86
5.9. Testing 88
5.10. Traceability from Requirements to Code and Tests 89
5.11. What Writing the Code Changed in the Models 90
5.12. Development History 91
5.13. Limitations and Future Work 92
5.14. Chapter Summary 92
CONCLUSION **93**
REFERENCES **94**

LIST OF FIGURES

Figure 1. System context diagram - VP diagram "CTX01 System Context Diagram"
Figure 2. Use cases of the Account and Catalogue package - VP diagram "UCD1 Account and Catalogue"
Figure 3. Use cases of the Cart, Order and Payment package - VP diagram "UCD2 Cart, Order and Payment"
Figure 4. Use cases of the Administration package - VP diagram "UCD3 Administration"
Figure 5. Use cases of the Operations and Reporting package - VP diagram "UCD4 Operations and Reporting"
Figure 6. Place order activity with swimlanes - VP diagram "AD01 Place Order (Swimlane)"
Figure 7. Order processing and shipment - VP diagram "AD02 Process and Ship Order (Swimlane)"
Figure 8. Manage inventory - VP diagram "AD03 Manage Inventory"
Figure 9. Level 0 data flow diagram - VP diagram "DFD0 Level 0 Diagram"
Figure 10. Level 1 DFD of process 4.0 - VP diagram "DFD1 Level 1 - 4.0 Place Order and Pay"
Figure 11. Sequence diagram of the main checkout scenario - VP diagram "SD01 Place Order (Analysis)"
Figure 12. Sequence diagram of order tracking - VP diagram "SD02 Track Order (Analysis)"
Figure 13. Analysis class diagram - VP diagram "CL01 Analysis Class Diagram"
Figure 14. Order state machine - VP diagram "ST01 Order State Machine"
Figure 15. Physical data model - VP diagram "ERD01 Physical Data Model"
Figure 16. AI-enabled use cases - VP diagram "UC_AI AI-Enabled Use Cases"
Figure 17. Three-layer architecture of the search subsystem - VP diagram "CMP01 AI Search Three-Layer Architecture"
Figure 18. Voice search - VP diagram "SD03 Voice Search"
Figure 19. Image search - VP diagram "SD04 Image Search"
Figure 20. Output of the search part of main.py demo: text, voice, image, text + image
Figure 21. Review insight pipeline - VP diagram "AD04 Review Insight Pipeline"
Figure 22. Output of evaluate.py, part 1: multimodal search on 26 test queries
Figure 23. Output of evaluate.py, parts 2 and 3: review insights and recommender
Figure 24. System components - VP diagram "CMP02 System Component Diagram"
Figure 25. Design class diagram after Step 1 - VP diagram "DCL01 Design Step 1 - Methods Added"
Figure 26. Design class diagram after Step 2 - VP diagram "DCL02 Design Step 2 - Use Dependencies"
Figure 27. Data access objects - VP diagram "DCL03 Design Step 3 - Data Access Objects"
Figure 28. Packages of the MVC architecture - VP diagram "PKG01 Design Step 4 - MVC Packages"
Figure 29. Checkout through the layers - VP diagram "SD05 Checkout Through the Layers (Design)"
Figure 30. Deployment - VP diagram "DEP01 Deployment Diagram"
Figure 31. Catalogue page with the multimodal search box (UC04, UC05)
Figure 32. Product page with AI review insights and recommendations (UC06, UC33, UC34)
Figure 33. Voice search result with scores and the processing trace (UC05)
Figure 34. Checkout with promotion WELCOME10, shipping and simulated payment options (UC08, UC31, UC32)
Figure 35. Order tracking: status timeline from order history and carrier milestones (UC11)
Figure 36. Order question "where is my latest order" answered from the customer's own orders (AI-R2)
Figure 37. Sales staff processing queue (UC19)
Figure 38. Warehouse inventory with low-stock rows and event form (UC20, UC24)
Figure 39. Review moderation queue: the spam review held by the AI noise filter (UC18, AI-R5)
Figure 40. Management dashboard computed from operational records (UC25-UC28)

Figure 41. Output of main.py demo, sections 2-8: checkout, idempotency, failure, fulfilment, AI and dashboard
Figure 42. Output of pytest: 40 tests passed

LIST OF TABLES

Table 1. Abbreviations used in the essay
Table 2. Chapters of the essay and the course work they build on
Table 3. Business profile of ABC Online Shop
Table 4. Stakeholders, interests and evidence of success
Table 5. Information catalogue (from Assignment 01, Table 3)
Table 6. Business problems, likely causes and consequences
Table 7. Stakeholder need catalogue (Assignment 02)
Table 8. Functional requirements
Table 9. Measurable non-functional requirements
Table 10. MoSCoW baseline
Table 11. Actors
Table 12. Specification of UC08 Place Order / Checkout
Table 13. Traceability from business problems to use cases
Table 14. AI requirements
Table 15. Working assumptions and the questions that validate them
Table 16. Traceability from business problems to system objectives
Table 17. Specification of UC09 Make Payment
Table 18. Specification of UC20 Manage Inventory
Table 19. Acceptance criteria of key requirements
Table 20. Analysis questions, models and the requirements they refine
Table 21. Relationships of the analysis model and their justification
Table 22. Integrity rules expressed as database constraints
Table 23. Cross-model consistency checks
Table 24. Decision table: may an order enter Processing? (UC19)
Table 25. Decision table: may an order be cancelled? (UC12)
Table 26. Promotion rule (UC32)
Table 27. Analysis classes and their responsibilities
Table 28. Mapping of the analysis model to the logical model
Table 29. CRUD matrix (selected use cases)
Table 30. AI opportunities derived from the business problems
Table 31. Data cards of the AI components
Table 32. Evaluation summary
Table 33. AI risks and the design response
Table 34. Prototype components and production replacements
Table 35. AI component specifications
Table 36. Score components of the top three results
Table 37. Business metrics of the AI features
Table 38. From problem to AI requirement, component, metric and test
Table 39. Non-functional requirements and the design decisions that serve them
Table 40. Methods added in Step 1
Table 41. Associations replaced by use dependencies

Table 42. DAO interfaces
Table 43. One request through the layers: a customer adds a product to the cart
Table 44. Routes of the web application and the use cases they serve
Table 45. Role permissions
Table 46. Design decisions, rejected alternatives and accepted costs
Table 47. What happened to each analysis element in the design
Table 48. Service classes
Table 49. Contracts of the provider gateways
Table 50. Service exceptions and how the presentation layer shows them
Table 51. Patterns and where they appear
Table 52. Environment and size of the code base
Table 53. Commands
Table 54. Test modules
Table 55. From requirement to design element, code and test
Table 56. Mismatches found while implementing
Table 57. Commit history
Table 58. Submitted files

INTRODUCTION

ABC Online Shop is a medium-sized retailer that sells consumer products online and works with a payment provider, a shipping provider and suppliers. Its central difficulty, established in Assignment 01, is not the absence of a website but fragmented and delayed information: product data differs between places, stock figures lag behind the warehouse, orders are re-entered by hand, customers cannot see where their order is, and reports arrive after the decisions they were meant to support. Every assignment of the course looked at this shop from a different angle. Written as one essay, they become a single path from a business problem to a running program.

The interesting part of that path is the joints. A requirement written vaguely in the second week turns into an ambiguous use case, then into a class without a clear responsibility, and finally into code that nobody can test. A requirement written well can be followed all the way down: the essay shows this with several threads, for example the rule *a payment result changes an order only once*, which starts as NFR07 in Chapter 1, becomes alternative flow A3 of UC09, a guard on the order state machine in Chapter 2, an idempotent method in the design of Chapter 4 and finally a test in Chapter 5.

Table 2. Chapters of the essay and the course work they build on

Chapter	Main question	Built on
1. Requirement Determination	What problem does the shop have, and what must the system do about it?	Assignment 01 (investigation), Assignment 02 (requirements, use cases)
2. Analysis	Which behaviour, data and classes does the problem contain?	Assignment 02 (activity diagrams), Assignment 03 (DFD, sequence, class, data models), Test 01
3. AI in E-commerce	Where does AI help the shop, and how do we know that it helps?	Assignment 02 (AI review analysis), Assignment 06 (multimodal search)
4. Design	How do the analysis classes become software components?	Test 01 (eComDesign), Assignment 06 (three-layer architecture), lecture on analysis-to-design steps
5. Code	Does the design survive contact with a compiler and a test suite?	Assignment 06 prototype, new Python application abc_shop

Three conventions hold throughout. First, identifiers are the ones fixed in Assignment 02 (BP, SN, FR, NFR, UC), so FR10 in Chapter 1 is the same FR10 that appears in a test name in Chapter 5. Second, every diagram is a Visual Paradigm diagram of the project TieuLuan_KHANHBQ.vpp, and the figure caption gives its name in the project. Third, every number in Chapters 3 and 5 comes from a program that was run: the outputs are stored in the folder demo_results and can be reproduced with the commands of Section 5.8.

The AI chapter sits in the middle on purpose. AI functions are often presented as separate products. In this essay they are treated as one more set of requirements, with stakeholders, use cases, components, risks and tests like every other part of the shop. The design and the code therefore contain them from the start rather than as an attachment.

CHAPTER 1. REQUIREMENT DETERMINATION

Requirement determination answers two questions before any model or code exists: what is wrong in the business, and what must an information system do so that it stops being wrong. This chapter summarises the investigation of Assignment 01 and the requirements engineering of Assignment 02 and adds what the later chapters need: an explicit system boundary, measurable quality requirements and the requirements of the AI extensions.

1.1. Requirements in the Development Life Cycle

In the system development life cycle, requirements are the hinge between the business and the software. Errors made here are the most expensive ones, because every later artifact inherits them: an analysis class models a misunderstood concept, a test confirms the wrong behaviour, and the shop receives a program that works but does not help. The course follows a chain that keeps each step traceable:

Business problems → Stakeholder needs → System requirements → Use cases → Validation

The chain is used in both directions. Forwards, each problem must lead to at least one requirement; backwards, each requirement must be justified by a need, so that nothing is built only because it is technically interesting. Section 1.16 checks both directions with a traceability matrix.

1.2. Investigation Approach

The evidence is the case description of the assignment brief, analysed in Assignment 01. Where the brief only states a symptom (for example *order status is unclear*), the cause was written down as a hypothesis and an elicitation question rather than as a fact, because inventing causes produces requirements for problems the shop may not have. Four techniques were used: document analysis of the case, stakeholder analysis, process modeling of the order-to-feedback flow, and problem-cause-consequence analysis summarised as a problem tree. Questions that only the shop can answer were collected as assumptions to validate (for example which payment provider is used and how it reports timeouts); they appear again as the assumptions of Section 1.13.

1.3. Business Context

Table 3. Business profile of ABC Online Shop

Item	Description
Organisation	Medium-sized business-to-consumer online retailer
Products	General consumer products organised in categories; the prototype uses shoes, bags, shirts, caps and watches
Customers	Visitors who browse without an account; registered customers who order, pay, track and review
Sales channel	Own website (responsive web storefront); no marketplace, no physical store
Partners	Payment provider (authorises payments), shipping provider (delivers parcels), suppliers (replenish stock)
Staff roles	Administrator, sales staff, warehouse staff, manager
Business objective	Increase reliable online sales while controlling fulfilment cost and keeping customer trust

The business model is information-intensive. In a physical shop a customer sees the item on the shelf; online, the customer relies entirely on a description, a price, an availability flag, reviews, a payment confirmation and a delivery status. The shop's promise is therefore only as good as the information that connects customers, staff and the three external partners.

1.4. Stakeholder Analysis

A stakeholder has an interest in the system; an actor interacts with it directly. Keeping the two apart prevents a common error, drawing a department or a database as an actor. The table below lists the stakeholders with the evidence that would show that the system serves them.

Table 4. Stakeholders, interests and evidence of success

Stakeholder	Type	Main interest	Evidence of success
Visitor / Customer	External	Find accurate products, pay safely, know where the order is	Fewer status enquiries; checkout without help
Administrator	Internal	One controlled source for catalogue, promotions and reviews	Audited changes; no conflicting product data
Sales staff	Internal	Process orders without re-entering data	Processing queue with complete order facts
Warehouse staff	Internal	Current stock, clear pick lists	Stock explained by events; no negative balance
Manager	Internal	Timely, reproducible reports	Dashboard computed from operational records
Payment provider	External	Uniquely referenced requests	Every result matched to exactly one attempt
Shipping provider	External	Correct delivery data	Every milestone matched to one shipment
Supplier	External	Clear replenishment requests	Requests raised when stock reaches the threshold

1.5. Business Process

The core business process runs from browsing to feedback in eight steps: (1) browse products, (2) build a cart, (3) validate the cart and create an order, (4) request payment, (5) reserve and update stock, (6) prepare and ship, (7) deliver and collect feedback, (8) report results and exceptions. Each step consumes information produced by an earlier one, which is why a delay anywhere becomes a problem everywhere: a stock figure that is one day old lets a customer order an item that no longer exists, which turns into a cancellation, a refund, an angry review and a wrong sales report.

1.6. Information Analysis

Table 5. Information catalogue (from Assignment 01, Table 3)

Information item	Produced by	Used by	Quality concern
Product, category, price	Administrator	Visitors, checkout, reports	One version; changes audited
Customer, address	Customer	Order, delivery, service	Unique, current, access-controlled
Cart	Customer	Checkout	Revalidated before ordering
Order, status history	System from events	Customer, staff, manager	One identifier; valid states; timestamps
Inventory event, stock level	Warehouse, order process	Browsing, checkout, warehouse	Traceable to events; never negative
Payment attempt, result	System, payment provider	Order, reports	Unique reference; no card data stored
Shipment, milestone	Shipping provider	Customer, staff	Matched to one shipment; no regression
Review	Customer with delivered order	Customers, administrator	Linked to a real purchase
Reports	System	Manager	Reproducible for a stated period

Two controls follow from the catalogue and shape the whole design. Identifiers must link related records across order, payment, inventory and shipment information, and a status must be derived from recorded events rather than typed in: an order is *Paid* because a verified payment result exists, not because somebody expected one.

1.7. Current Problems

Table 6. Business problems, likely causes and consequences

ID	Problem	Likely cause (to verify)	Consequence
BP01	Inconsistent product information	Several copies edited without one owner	Conflicting offers, disputes
BP02	Outdated inventory information	Receipts and sales posted manually, in batches	Orders for unavailable stock, cancellations
BP03	Manual order processing	Re-entry of cart, payment and delivery data	Delay, transcription errors
BP04	Unclear order status	Milestones stored separately, no state rules	Repeated enquiries, late detection of failures
BP05	Slow sales reporting	End-of-period manual consolidation	Late, irreproducible figures
BP06	Fragmented customer information	No master identifier, duplicates	Delivery errors, privacy exposure
BP07	Limited real-time management information	Operational events disconnected	Reactive decisions

The problem tree of Assignment 01 places one central problem, *fragmented and delayed information management*, between three causes (manual re-entry, separate records without shared identifiers, unclear ownership and state rules) and three groups of consequences (order and fulfilment errors, unclear status, slow reporting). The tree also explains the priorities: inventory accuracy and order status come first because they affect revenue, customer trust and staff workload at the same time, while reporting can only be as good as the operational records it reads.

1.8. Scope, Boundary and Context

The system boundary decides what the shop's software does itself and what it only exchanges with others. Inside are authentication and roles, customer profiles, catalogue and search, cart and checkout, order and payment-status coordination, inventory, shipment-status integration, promotions, reviews and reports. Outside are payment authorisation and settlement, carrier routing and physical delivery, and supplier operations: the shop sends a uniquely referenced request and records the attributable result. The figure below shows the boundary as a context diagram, in which the whole system is one process (0) and every arrow is a named data flow.




Figure 1. System context diagram - VP diagram "CTX01 System Context Diagram"

The context diagram is deliberately symmetric: every external entity both sends and receives. A one-way arrow would hide a requirement. For example, the shipping provider does not only receive a delivery request; it also sends milestones, and without that return flow the system could never answer the customer's question "where is my order?" (BP04).

1.9. System Objectives

- **O1** One controlled, role-authorised source for product, customer, promotion, order, stock, payment-status and shipment-status information (BP01, BP06).
- **O2** Record inventory events promptly and show one consistent available quantity at browsing, checkout, fulfilment and reporting (BP02).
- **O3** Coordinate checkout, payment, reservation, fulfilment, shipment and cancellation without re-entering data (BP03).
- **O4** Give customers and staff a timestamped order status derived from recorded events (BP04).
- **O5** Exchange uniquely referenced requests and results with the payment and shipping providers (BP03, BP04).
- **O6** Produce reproducible sales, inventory and exception reports from operational records (BP05, BP07).
- **O7** Protect personal and transaction data by data minimisation, role-based access and an audit trail (BP06).

1.10. Stakeholder Needs

Table 7. Stakeholder need catalogue (Assignment 02)

ID	Stakeholder	Need	Priority
SN01	Visitor / Customer	Find accurate, current product and availability information	Must
SN02	Customer	Maintain selected products and quantities before ordering	Must
SN03	Customer	Complete a clear and secure checkout and payment	Must
SN04	Customer	View order history, processing state and delivery progress	Must
SN05	Customer	Cancel an eligible order and review a verified purchase	Should
SN06	Administrator	Maintain products, categories, promotions and reviews from one source	Must
SN07	Sales staff	Process orders and answer enquiries without re-entering information	Must
SN08	Warehouse staff	See current stock and record every inventory movement promptly	Must
SN09	Warehouse staff	Prepare shipments and coordinate traceable replenishment	Must
SN10	Manager	Obtain timely dashboards and reproducible sales reports	Should
SN11	Manager	See inventory, order, payment, shipment and exception information	Must
SN12	All users / ABC	Protect personal and transaction information by role and purpose	Must
SN13	Payment provider	Receive a uniquely referenced request and return an attributable result	Must
SN14	Shipping provider	Receive correct delivery data and return traceable milestones	Must

1.11. Functional Requirements

Each functional requirement is an observable "The system shall" statement, has one identifier and one MoSCoW priority, and is allocated to a use case. None of them prescribes a database, a framework or a provider's internal design; those decisions belong to Chapter 4.

Table 8. Functional requirements

ID	The system shall ...	Pri.	UC
FR01	allow a Visitor to register a Customer account with validated identity and contact data	M	UC01
FR02	authenticate users and authorise functions according to their roles	M	UC02
FR03	allow a Customer to view and update profile and delivery address	S	UC03
FR04	display the active catalogue and categories to a Visitor	M	UC04
FR05	allow a Visitor to search and filter active products	M	UC05
FR06	display description, current price, promotion and available-to-order status	M	UC06
FR07	allow a Customer to add an available product, change its quantity or remove it	M	UC07
FR08	validate the cart, recheck availability and calculate the authoritative total before ordering	M	UC08, UC29-31
FR09	create one uniquely identified order linked to customer, lines, address, totals and status history	M	UC08

ID	The system shall ...	Pri.	UC
FR10	send a uniquely referenced payment request and record each attributable result once	M	UC09
FR11	allow a Customer to view own order history and details	M	UC10
FR12	show current processing and shipment status with the last update time	M	UC11
FR13	allow an eligible order to be cancelled according to status and refund rules	S	UC12
FR14	allow a Customer with a delivered order line to submit one review for that product	C	UC13
FR15	allow an Administrator to create, update, publish and categorise products	M	UC14-15
FR16	allow an Administrator to maintain promotion rules and moderate reviews	S	UC16, UC18
FR17	allow authorised staff to find and update permitted customer information with an audit trail	S	UC17
FR18	allow Sales Staff to progress orders only through valid state transitions	M	UC19
FR19	record receipts, reservations, releases, issues and adjustments and recalculate stock	M	UC20
FR20	provide a pick list and record packing against the order	M	UC21
FR21	send a uniquely referenced delivery request and record attributable milestones	M	UC22-23
FR22	issue and track a replenishment request when stock reaches its threshold	S	UC24
FR23	provide authorised dashboards and reproducible reports for a selected period	M	UC25-28
FR24	apply a promotion only when code, dates, scope and minimum total are valid	S	UC32

1.12. Non-functional Requirements

Table 9. Measurable non-functional requirements

ID	Category	Requirement / acceptance criterion
NFR01	Performance	95% of browse and search requests complete within 2 s under normal load
NFR02	Performance	Checkout validation and total calculation within 3 s for 95% of requests (provider time excluded)
NFR03	Availability	Monthly availability at least 99.5%; RPO 15 min, RTO 2 h
NFR04	Security	Personal, authentication, payment-status and delivery data in transit use TLS 1.2 or later
NFR05	Access control	Role-based least privilege; a Customer accesses only own profile and orders
NFR06	Auditability	Role, order-state, inventory, price and promotion changes record actor, time, identifier, before/after
NFR07	Integrity	Payment and shipment requests use unique references; a replay never duplicates a transaction, stock event or state change
NFR08	Usability	90% of first-time users complete checkout in at most five screens without help
NFR09	Maintainability	Automated tests cover order, payment, inventory and shipment rules; every Must rule has a regression test
NFR10	Privacy	Only data needed by the task is shown; raw payment credentials are never stored
NFR11	Compatibility	Essential customer functions work on the two latest versions of Chrome, Edge and Safari

ID	Category	Requirement / acceptance criterion
NFR12	Scalability	With 500 concurrent users NFR01 still holds and 30 checkouts per minute complete without loss

The NFRs are written so that each can fail. "The system should be secure" cannot fail and therefore cannot be tested; "a replay never duplicates a transaction" (NFR07) can, and Chapter 5 shows the test that tries exactly that. Writing them this way early was the most useful single decision of Assignment 02, because it turned quality wishes into design constraints.

1.13. Prioritisation and Assumptions

Table 10. MoSCoW baseline

Class	Requirements	Decision rule
Must	FR01-02, FR04-12, FR15, FR18-21, FR23; NFR01-02, NFR04-07, NFR09-10	Needed for a secure, traceable sales lifecycle
Should	FR03, FR13, FR16-17, FR22, FR24; NFR03, NFR08, NFR11	Important; a temporary manual process can bridge Release 1
Could	FR14; NFR12	Valuable once the transaction path is stable
Won't (Release 1)	Cash on delivery, guest checkout, native apps, marketplace integration	Outside the first release or unresolved

The baseline rests on assumptions that only the shop can confirm: authenticated checkout, online payment only, stock reserved when the order is created, controlled order states, uniquely referenced provider messages and reviews limited to delivered order lines. They are listed because each one changes the design if it is false; for example, cash on delivery would add an order state between *Shipped* and *Paid*.

1.14. Actors and the Use Case Model

Table 11. Actors

Actor	Type	Use cases
Visitor	External human	UC01 Register, UC04 Browse, UC05 Search, UC06 View Product Details
Customer (specialises Visitor)	External human	UC02-03, UC07-08, UC10-13
Staff (abstract)	Generalisation	UC02 Login, shared by the four staff roles
Administrator	Internal human	UC14-18 catalogue, categories, promotions, customers, reviews
Sales Staff	Internal human	UC17 Manage Customers, UC19 Process Orders
Warehouse Staff	Internal human	UC20-22, UC24 inventory, shipment, replenishment
Manager	Internal human	UC25-28 dashboard and reports
Payment Provider	External system	UC09 Make Payment
Shipping Provider	External system	UC22 Arrange Delivery, UC23 Update Shipment Status

Actor	Type	Use cases
Supplier	External organisation	UC24 Manage Replenishment

Drawing 10 actors and 32 use cases in one picture produces a diagram in which every line crosses several others. The model is therefore shown in four diagrams, one per package of the use case catalogue of Assignment 02. Every use case appears in exactly one diagram; an actor appears in each diagram where it has an association.




Figure 2. Use cases of the Account and Catalogue package - VP diagram "UCD1 Account and Catalogue"




Figure 3. Use cases of the Cart, Order and Payment package - VP diagram "UCD2 Cart, Order and Payment"




Figure 4. Use cases of the Administration package - VP diagram "UCD3 Administration"




Figure 5. Use cases of the Operations and Reporting package - VP diagram "UCD4 Operations and Reporting"

The relationships follow the rules of the lecture. UC08 Place Order *includes* UC29 Validate Cart, UC30 Check Product Availability, UC31 Calculate Order Total and UC09 Make Payment, because under the Release 1 assumptions these always happen during checkout; UC07 includes UC30 because every cart change must check the orderable quantity. UC32 Apply Promotion *extends* UC08 only when the customer enters a code; UC12 Cancel Order and UC13 Submit Review extend UC10 View Order History at the point where an eligible order is selected; UC24 Manage Replenishment extends UC20 when stock reaches its threshold. The abstract Staff actor carries the single Login association so that the four staff roles keep separate, least-privilege use cases.

1.15. Use Case Specification: UC08 Place Order

Table 12. Specification of UC08 Place Order / Checkout

Field	Specification
Primary actor / supporting	Customer / Payment Provider through UC09
Goal	Convert a valid cart into one paid, confirmed, traceable order
Preconditions	Customer authenticated; cart contains at least one active product
Success guarantee	One order with validated lines, address, total, payment reference, reservations and a Paid/Confirmed history entry; cart cleared
Minimal guarantee	No duplicate order or charge; stock released if payment fails; cart kept
Main flow	1 Customer selects Checkout. 2 System validates the cart (UC29) and availability (UC30). 3 Customer confirms the delivery address. 4 Optional promotion code (UC32). 5 System calculates the total (UC31). 6 Customer confirms; system reserves stock and creates one Payment Pending order with an idempotency key. 7 System requests payment (UC09). 8 Verified success: order Paid/Confirmed, cart cleared, confirmation shown.
Alternative flows	A1 inactive line, A2 insufficient stock: return to cart, nothing created. A3 invalid address. A4 invalid promotion: continue without discount. A5 payment declined: Payment Failed, reservations released, cart kept. A6 timeout: stay Payment Pending, reconcile by reference. A7 repeated submission: return the existing order.
Exception	E1 reservation or order creation fails: roll back both, preserve the cart
Requirements	FR08-FR10, FR24; NFR02, NFR05-NFR07, NFR10

UC08 was chosen for full specification because it touches more requirements than any other use case and because its alternative flows are where the shop currently loses money. Chapter 5 implements each flow of this table and tests A2, A5, A6, A7 and E1 individually.

1.16. Validation and Traceability

Table 13. Traceability from business problems to use cases

Problem	Needs	Requirements	Use cases
BP01 product inconsistency	SN01, SN06	FR04-06, FR15, NFR06	UC04-06, UC14-15
BP02 outdated inventory	SN08-09	FR08, FR19, FR22, NFR07	UC20, UC24, UC30
BP03 manual order processing	SN02-03, SN07	FR07-10, FR18	UC07-09, UC19, UC29-31
BP04 unclear status	SN04, SN14	FR11-12, FR21	UC10-11, UC22-23
BP05 slow reporting	SN10	FR23	UC25-28
BP06 fragmented customer data	SN12	FR01-03, FR17, NFR05, NFR10	UC01-03, UC17
BP07 limited real-time information	SN11	FR23, NFR01	UC25-28

The requirements were validated against five properties. **Clear**: every statement has an actor, an action, an object and a condition. **Consistent**: order states, provider references and reservation rules use the same terms everywhere. **Complete**: the matrix has no orphan problem, need, requirement or primary use case; the supporting UC29-UC32 are reached through include and extend. **Feasible**: provider-internal work is outside the boundary.

Verifiable: every FR has an observable outcome and every NFR a threshold.

1.17. Requirements for the AI Extensions

The AI functions of Chapter 3 are specified as Release 2 requirements in the same form, so that they can be traced and tested like the rest. They extend existing use cases instead of replacing them, and each has a non-AI fallback.

Table 14. AI requirements

ID	Requirement	Extends	Source
AI-R1	Search products by keywords, by a spoken sentence, by a photo, or by text and photo together	UC05	A6
AI-R2	Answer order questions ("where is my latest order?") only from the customer's own orders	UC10-11	A6, FR11
AI-R3	Rank results by text match, image similarity and stock, and show the component scores	UC05	A6
AI-R4	Summarise published reviews per aspect (quality, price, delivery, service) with evidence	UC06 (UC33)	A02 AI part
AI-R5	Hold reviews that look like spam for moderation instead of publishing them	UC13, UC18	A02 AI part
AI-R6	Recommend similar in-stock products and products for a customer's purchase history	UC06, UC10 (UC34)	new
AI-N1	Every AI component is replaceable behind a fixed interface (transcribe, encode, analyse, similar)	-	NFR09
AI-N2	Results are deterministic and explainable: same input, same output, visible scores	-	NFR06
AI-N3	If an AI component fails or lacks data, the page still works with a non-AI fallback	-	NFR03

1.18. Elicitation Questions and Assumptions

The investigation could not observe the shop directly, so every interpretation that goes beyond the case description was recorded with the question that would confirm or reject it. The list doubles as an interview plan for the first meeting with the shop's staff.

Table 15. Working assumptions and the questions that validate them

ID	Working assumption	Question / evidence required
A1	ABC sells general consumer products through its own website only	Which channels accept orders today: website, social media, marketplace, phone?
A2	Separate copies and batch updates cause the inconsistencies	Where is each product, customer, order and stock item recorded, who owns it, how often is it updated?
A3	Available stock = physical stock minus reserved quantities	When exactly is stock reserved, released, issued, received and adjusted?
A4	Order status can be derived from accepted business events	Which status names, transition rules and customer-visible wordings are approved?
A5	Providers expose a reference and a status for every exchange	Which providers are used; how are duplicates, timeouts and late updates reported?
A6	Only customers with a delivered order may review	Can visitors review? Who approves or removes a review?
A7	Management needs sales, inventory and exception reports	Which decision uses each report, how often, with which definitions?

1.19. From Problems to Objectives

Table 16. Traceability from business problems to system objectives

Problem	Objectives	Evidence expected after implementation
BP01, BP06 inconsistent product and customer data	O1, O7	One controlled record per item; audited changes; fewer conflicting entries
BP02 outdated inventory	O2, O3	Every quantity explained by events; fewer cancellations for unavailable items
BP03 manual order processing	O3, O5	No re-entry; provider results matched to orders automatically
BP04 unclear order status	O3, O4, O5	Timestamped status history; fewer routine status enquiries
BP05, BP07 slow and limited management information	O1, O6	Reports computed from operational records with a visible refresh time

The objectives deliberately avoid numeric targets such as "reduce enquiries by 30%". A target needs a baseline, and the shop has none yet; inventing one during the investigation would give the project a false precision. The candidate measures (status enquiries per 100 orders, stock discrepancies, orders cancelled for unavailable items, report preparation time) are recorded so that a baseline can be taken before the system goes live.

1.20. Further Use Case Specifications

UC08 depends on two use cases that carry most of the integrity rules: UC09 Make Payment and UC20 Manage Inventory. Their specifications, condensed from Assignment 02, are the source of the payment and stock code in Chapter 5.

Table 17. Specification of UC09 Make Payment

Field	Specification
Actors	Customer (primary), Payment Provider (supporting); triggered by UC08 for a Payment Pending order
Goal	Record an authoritative online-payment outcome without raw credentials or duplicates
Main flow	1 System creates a payment attempt with a unique reference. 2 System sends reference, amount and currency to the provider. 3 Customer authorises at the provider. 4 Provider returns a verifiable result. 5 System authenticates the source and matches reference, amount and currency. 6 System records success once and changes the order to Paid/Confirmed.
Alternative flows	A1 declined: Payment Failed, reservations released, cart kept. A2 timeout: Pending, reconcile later, never "pay again". A3 duplicate callback: acknowledge, no second effect. A4 late success on a closed order: refund exception.
Exceptions	E1 reference, amount or currency mismatch: quarantine, order unchanged. E2 unauthenticated result: reject and alert.
Business rules	Store status and references, never card data; a retry creates a new attempt reference; provider retries are idempotent

Table 18. Specification of UC20 Manage Inventory

Field	Specification
Actors	Warehouse Staff (primary); UC08, UC09, UC12 and UC21 create events automatically; Supplier through UC24
Goal	Maintain current, explainable stock through traceable events
Main flow	1 Staff selects a product and an event type; system shows physical, reserved, available and recent events. 2 Staff enters quantity, reference and reason. 3 System validates role, product, quantity, unique reference and resulting balance. 4 System records an immutable event and recalculates the balance atomically. 5 At or below threshold, system offers UC24. 6 System shows the new balance and the event id.
Alternative flows	A1 reservation, A2 issue, A3 release (order-driven); A4 correction recorded as a reason-coded ADJUST; A5 threshold reached
Exceptions	E1 negative resulting balance: reject atomically. E2 duplicate reference: return the earlier event, no change.
Business rules	available = physical - reserved; all quantities >= 0; an issue or release never exceeds its reservation

1.21. Acceptance Criteria

For the requirements with the highest risk, acceptance criteria were written in the Given-When-Then form so that they can become tests without reinterpretation. Chapter 5 shows that each of them became exactly one test.

Table 19. Acceptance criteria of key requirements

Req.	Given	When	Then
FR09 / A7	a cart with one product and checkout key k-1	the customer submits checkout twice with k-1	one order exists and one payment attempt was made
FR10 / NFR07	a pending payment attempt	the provider sends a forged result, a wrong amount, then the correct result twice	the order is Paid/Confirmed exactly once
FR11 / NFR05	order O002 belongs to customer C002	customer C001 asks for O002	the answer is "not found"; C002 sees the order
FR19	P05 with 10 units received under reference GRN-77	the same receipt is recorded again, then an adjustment of -20	stock stays 10; the adjustment is rejected
FR21	a shipment with milestones 1 and 2	milestone 2 arrives again and milestone 1 arrives late	both are ignored and the status does not move back

1.22. Managing Requirement Change

Requirements changed three times after Assignment 02, and each change was recorded with its reason instead of silently editing the baseline. (1) The AI requirements AI-R1 to AI-N3 were added as Release 2 extensions, so the 32 Release 1 use cases stayed unchanged. (2) The order state machine gained the transition Delivery Failed → Delivered when implementing UC23 showed that a carrier can deliver after a failed attempt without a new pick-up message. (3) The definition of a purchase (used by reviews and recommendations) was made explicit: an order counts only if it was not cancelled and its payment did not fail. Each change was propagated through the traceability matrix to the diagrams and tests that depend on it.

1.23. Chapter Summary

The chapter turned a shop with fragmented information into a baseline of 7 problems, 14 needs, 24 functional and 12 non-functional requirements, 9 AI requirements and 32 use cases, with a context diagram that fixes the boundary and a matrix that shows that every problem is covered. The two ideas that the next chapters depend on are already visible: status comes from recorded events, and every exchange with a provider carries a unique reference.

CHAPTER 2. ANALYSIS

Analysis describes the problem domain without deciding how the software will be built. It answers three questions about the requirements of Chapter 1: what happens and in which order (behaviour), which data moves where (information), and which concepts exist and how they are related (structure). The chapter uses one model family for each question and closes with a check that the models agree with each other.

2.1. From Requirements to Analysis Models

Table 20. Analysis questions, models and the requirements they refine

Question	Model (VP diagram)	Refines
Who does what, in which order?	Activity and swimlane diagrams (AD01-AD03)	UC08, UC19-23, UC20
Which data flows between processes and stores?	DFD level 0 and level 1 (DFD0, DFD1)	Context diagram CTX01
Which objects collaborate in a scenario?	Sequence diagrams with BCE lifelines (SD01, SD02)	UC08, UC11
Which concepts and relationships exist?	Analysis class diagram (CL01)	Information catalogue
Which states can an order be in?	State machine (ST01)	FR12, FR13, FR18
How is the data stored?	Physical ER diagram (ERD01)	Integrity requirements NFR06-07

2.2. Activity Modeling

An activity diagram shows the control flow of one use case; a swimlane adds who performs each action. The swimlane version is the more useful one for this shop, because most of its problems are hand-offs between parties. The checkout diagram has three lanes: Customer, System and Payment Provider. It makes two facts visible that the text of UC08 only implies. First, the system reserves stock *before* it asks for payment, so that a paid order can always be fulfilled. Second, the payment result is a decision of the system, not of the provider: the provider returns a signed result and the system decides whether it is a verified success.




Figure 6. Place order activity with swimlanes - VP diagram "AD01 Place Order (Swimlane)"

The diagram has two decision nodes, each with exactly one guard per outgoing flow. The failure branches end in their own final nodes rather than looping back, because the use case specification says that after a validation failure the customer returns to the cart, which is a different use case (UC07). On the [No] branch after payment, the system releases the reservation and records Payment Failed before the customer sees the failure, which is the order of the statements in PaymentService.handle_result (Chapter 5).

Fulfilment crosses four parties, which is exactly where Assignment 01 located the delays of BP03 and BP04. The second swimlane diagram follows a paid order from the processing queue of the sales staff to the milestones of the carrier. The eligibility decision checks two facts that come from earlier use cases: a verified payment (UC09) and complete reservations (UC08 step 6). An order that fails either check is put On Hold with a recorded reason instead of being silently skipped.




Figure 7. Order processing and shipment - VP diagram "AD02 Process and Ship Order (Swimlane)"

Inventory management is a single-actor use case and is drawn without lanes. Its interest lies in the order of the checks: the duplicate-reference check comes first, so that a repeated goods-receipt note can never add stock twice (NFR07); the balance check comes second, so

that no event can produce a negative quantity; and the threshold check comes last, after the event is recorded, and only offers replenishment (UC24) instead of starting it, because a person decides how much to order.




Figure 8. Manage inventory - VP diagram "AD03 Manage Inventory"

2.3. Data Flow Modeling

The context diagram of Chapter 1 treats the system as one process. The level 0 DFD opens it into eight processes and six data stores. The decomposition follows the business process of Section 1.5, so each process has one clear owner of its data. Two rules of DFD notation were checked on every flow: a data store is never connected directly to another store or to an external entity, and every process has at least one input and one output. A flow is named after the data it carries, never after an action (*payment request*, not *send payment*).




Figure 9. Level 0 data flow diagram - VP diagram "DFD0 Level 0 Diagram"

The level 0 diagram also shows where the shop's information becomes inconsistent today. The Products store D1 is read by process 2.0 (search) and by checkout, and written only by 1.0; the Inventory store D4 is written by 4.0 (reservations) and 6.0 (receipts) and read by everyone. With one writer per kind of change, two copies of the same fact cannot exist, which is the analysis form of objective O1.

Process 4.0 Place Order and Pay is the most complex one and is decomposed at level 1 into five processes. The decomposition is balanced: the level 1 diagram has the same external flows as process 4.0 on level 0 (checkout request and confirmation with the customer, payment request and result with the provider, order, reservation and payment written to D3, D4 and D5). Two stores appear only at level 1, Carts and Promotions, because they are internal to the checkout.




Figure 10. Level 1 DFD of process 4.0 - VP diagram "DFD1 Level 1 - 4.0 Place Order and Pay"

2.4. Interaction Modeling

A sequence diagram assigns the steps of a scenario to objects. In analysis the objects are typed with the boundary, control and entity stereotypes: a **boundary** object talks to an actor or to an external system (CheckoutForm, PaymentGateway), a **control** object coordinates one use case (CheckoutController), and an **entity** object holds information that outlives the scenario (Cart, StockLevel, Order). The rule that an actor only talks to boundaries, and entities only answer, keeps the scenario readable and already suggests the layers of the design.




Figure 11. Sequence diagram of the main checkout scenario - VP diagram "SD01 Place Order (Analysis)"

The sixteen messages follow the main flow of UC08 in order. Messages 3-6 are the included use cases UC29-UC31; message 8 reserves stock before payment (step 6); messages 9-12 are UC09, where the PaymentGateway boundary is the only object that knows the provider. Message 13 changes the order status only after message 12 has reported a verified success. An alternative flow such as A5 (payment declined) is a different scenario and is therefore not drawn into this diagram; it is covered by the activity diagram and by a test.




Figure 12. Sequence diagram of order tracking - VP diagram "SD02 Track Order (Analysis)"

Tracking looks simple but contains the privacy rule of NFR05: message 5, checkOwner(customerId), happens before any shipment data is read. If the order belongs to

someone else, the controller answers exactly as if the order did not exist, so that a customer cannot learn which order numbers are in use (UC11 E2).

2.5. Analysis Class Model

The classes were found by the noun-phrase method applied to the use case specifications and the information catalogue, then filtered: nouns that name an actor (Manager), a screen (checkout page) or a single attribute (price) were removed. Seventeen classes remain. They carry attributes but no operations yet; operations are added in the first design step (Section 4.3).




Figure 13. Analysis class diagram - VP diagram "CL01 Analysis Class Diagram"

Table 21. Relationships of the analysis model and their justification

Relationship	Kind	Justification
Customer - User	Generalisation	A customer is a user with an address and order history; staff are users with other roles
Customer - Address	Aggregation 1 - 0..1	The address exists for delivery and can be replaced; old orders keep a copy of it
Cart - CartItem	Composition 1 - 0..*	A cart line has no meaning outside its cart and is deleted with it
Order - OrderItem	Composition 1 - 1..*	An order has at least one line; lines are fixed after creation
Order - StatusChange	Composition 1 - 1..*	The append-only history that explains the current status (BP04)
Order - Payment	Association 1 - 0..*	Several attempts are possible (A5 retry); at most one succeeds
Order - Shipment	Association 1 - 0..1	A shipment exists only after packing
Shipment - Milestone	Composition 1 - 0..*	Milestones are carrier messages about one shipment
Product - StockLevel	Association 1 - 1	Stock is kept apart from the catalogue so that two roles do not edit one record
StockLevel - InventoryEvent	Association 1 - 0..*	Every quantity is explained by events (FR19)
Review - Order, Product	Association	A review is verified by a delivered order of that product (FR14)

Two modelling decisions deserve a comment. CartItem stores its own *cartPrice* and OrderItem its own *unitPrice* instead of reading Product.price, because the price at the time of adding and the price paid are historical facts; if the administrator changes a price, old orders must not change. And StockLevel is a separate class rather than an attribute of Product: in Assignment 01 the catalogue and the stock were maintained by different people, and putting both in one class would recreate the conflict of BP01 and BP02. The derived attribute */available* (physical minus reserved) is marked with a slash because it is never stored.

2.6. Order State Machine

BP04, unclear order status, is in the end a missing state model. The state machine makes the allowed transitions explicit; any transition that is not drawn is forbidden. Each transition is labelled with *event [guard] / action*, so the diagram also says when stock is reserved, released or issued.




Figure 14. Order state machine - VP diagram "ST01 Order State Machine"

The state machine resolves several questions that the use cases left open. A cancellation is possible until packing (Payment Pending, Paid/Confirmed, On Hold, Processing) and impossible afterwards, which makes FR13's "eligible order" precise. Payment Failed is a final

state: a new attempt creates a new order instead of reviving the old one. An order On Hold returns to Processing once the reason is resolved, and a delivery that fails once can still end in Delivered when the carrier's next attempt succeeds. The same table of transitions appears in the code as a dictionary, and a model test checks that a skipped state is rejected.

2.7. Data Modeling

Data modelling followed the three levels practised in Assignment 03 and Test 01. The **conceptual** model is the analysis class diagram: entities, attributes and multiplicities, independent of any database. The **logical** model maps it to relations: each class becomes a table with a primary key, each one-to-many association a foreign key on the many side, each composition a foreign key that is part of the child's key, and the generalisation User-Customer a single table *users* with a role column (the subclass adds no columns except the address, which has its own table). The **physical** model adds types, NOT NULL, UNIQUE and CHECK constraints for SQLite.




Figure 15. Physical data model - VP diagram "ERD01 Physical Data Model"

Table 22. Integrity rules expressed as database constraints

Constraint	Table	Requirement
CHECK (physical >= 0, reserved >= 0, physical >= reserved)	stock_level	FR19, BR20: never negative
UNIQUE (product_id, kind, reference)	inventory_event	NFR07: an event is recorded once
UNIQUE (idempotency_key)	customer_order	UC08 A7: one order per submission
UNIQUE (attempt_ref)	payment	FR10: one result per attempt
UNIQUE (order_id)	shipment	One shipment per order (Release 1)
PRIMARY KEY (shipment_id, seq)	shipment_milestone	UC23: duplicate milestones ignored
UNIQUE (customer_id, product_id, order_id); CHECK rating 1-5	review	FR14: one review per purchase
CHECK (total > 0), price > 0	customer_order, product	Valid amounts

The order table is called *customer_order* because ORDER is a reserved word in SQL. The status history is a table of its own with an auto-increment key, so rows are only ever appended. The audit_log table has no foreign keys on purpose: it must keep its rows even if the referenced record is later removed.

2.8. Consistency Across Models

Table 23. Cross-model consistency checks

Check	Result
Every lifeline of SD01/SD02 is a class of CL01 or a boundary/control of the use case	Passed (Cart, StockLevel, Order, Shipment are entities)
Every data store of DFD0 corresponds to classes of CL01 and tables of ERD01	Passed (D1 Products = product, category; D4 Inventory = stock_level, inventory_event)
Every state of ST01 is a value of Order.status and every transition is reachable from a use case	Passed; Delivery Failed reached only from UC23
Every message of SD01 corresponds to an action of AD01	Passed; message 6 groups UC31 and UC32
Multiplicities of CL01 match foreign keys of ERD01	Passed; Customer-Cart 1-1 became UNIQUE(customer_id)
DFD1 is balanced with process 4.0 of DFD0	Passed (same external flows)

2.9. Business Rules and Decision Logic

The decision nodes of the activity diagrams hide business rules. Writing them as decision tables makes sure that every combination of conditions has exactly one outcome, which is what the code must implement.

Table 24. Decision table: may an order enter Processing? (UC19)

Rule	Payment verified	All lines reserved	Blocking exception	Outcome
R1	Yes	Yes	No	Processing; added to the pick list
R2	No	-	-	On Hold: "payment is not confirmed"
R3	Yes	No	-	On Hold: "product is not reserved"
R4	Yes	Yes	Yes	On Hold with the recorded reason

Table 25. Decision table: may an order be cancelled? (UC12)

Current status	Who	Outcome
Payment Pending	Owner or Sales Staff	Cancelled; reservations released
Paid/Confirmed, On Hold, Processing	Owner or Sales Staff	Cancelled; reservations released; refund initiated and audited
Ready for Shipment, Shipped, Delivered	anyone	Rejected: "can no longer be cancelled"
any status	another customer	"order not found" (no disclosure)

Table 26. Promotion rule (UC32)

Condition	Result
code unknown	no discount; message "promotion does not exist"; checkout continues (A4)
today outside [start, end] or subtotal < minimum	no discount; message "not valid for this order"
valid	discount = subtotal x percent / 100, rounded to cents; shipping calculated after discount

2.10. Class Responsibilities

Table 27. Analysis classes and their responsibilities

Class	Responsibility	Key rule
User / Customer	Identity, role, contact; customer owns address, cart and orders	Least privilege by role
Product / Category	What is sold and how it is grouped	Only active products are sold
Promotion	A discount rule with dates and minimum total	Valid only in its period
Cart / CartItem	Tentative choice with the price at the time of adding	Revalidated before ordering
Order / OrderItem	Commitment with authoritative prices and address	Lines fixed after creation
StatusChange	One entry of the append-only order history	Never updated or deleted
Payment	One attempt with its reference and result	At most one success per order
StockLevel / InventoryEvent	Current balance and the events that explain it	available = physical - reserved >= 0
Shipment / Milestone	Parcel and carrier messages	Sequence numbers only increase

Class	Responsibility	Key rule
Review	Opinion linked to a delivered purchase	One per customer, product and order

2.11. From Classes to Tables

Table 28. Mapping of the analysis model to the logical model

Class / relationship	Table	Key and foreign keys
User, Customer (generalisation)	users	PK user_id; role column distinguishes the subtypes
Address (aggregation 1-0..1)	address	PK = FK customer_id
Cart (1-1 with Customer)	cart	PK cart_id; FK customer_id UNIQUE
CartItem (composition)	cart_item	PK (cart_id, product_id), both FK
Order	customer_order	PK order_id; FK customer_id; UNIQUE idempotency_key
OrderItem (composition)	order_item	PK (order_id, product_id), both FK
StatusChange (composition)	order_status_history	PK id (autoincrement); FK order_id
Payment	payment	PK payment_id; FK order_id; UNIQUE attempt_ref
Shipment / Milestone	shipment / shipment_milestone	UNIQUE order_id / PK (shipment_id, seq)
Product, Category	product, category	FK category_id
StockLevel (1-1) / InventoryEvent	stock_level / inventory_event	PK = FK product_id / UNIQUE (product_id, kind, reference)
Review	review	FK product_id, customer_id, order_id; UNIQUE of the three

The schema is in third normal form. Every non-key column depends on the whole key and only on the key: the product name copied into order_item is not a transitive dependency but a historical fact (the name at the time of purchase), in the same way as unit_price. The order total is stored although it can be computed from the lines, because reports must reproduce the amount that was charged even if a rounding rule changes later; the service computes it once at creation and never updates it.

2.12. CRUD Matrix

The CRUD matrix crosses use cases with data entities and shows which use case creates (C), reads (R), updates (U) or deletes (D) which data. It is a completeness check: every entity must be created somewhere and read somewhere, and an entity updated by many use cases deserves a closer look at concurrency.

Table 29. CRUD matrix (selected use cases)

Use case	Product	Stock / Event	Cart	Order / History	Payment	Shipment	Review
UC04-06 Browse, Search, View	R	R					R
UC07 Manage Cart	R	R	CRU				
UC08 Place Order	R	RU / C	RU	C			
UC09 Make Payment		U / C (release)		U / C	CU		
UC11 Track Order				R		R	
UC12 Cancel Order		U / C		U / C	R		
UC13 Submit Review				R			C
UC14 Manage Products	CRU	C					
UC18 Manage Reviews							RU
UC19 Process Orders		R		RU / C	R		
UC20 Manage Inventory	R	RU / C					
UC21-23 Shipment		U / C (issue)		U / C		CRU	
UC25-28 Reports	R	R		R	R		

Two observations from the matrix shaped the design. Stock is updated by six use cases, so stock changes are funnelled through one service method (InventoryService.record) inside a transaction. And no use case deletes an order, a payment or a stock event: corrections are new records, which is what makes every figure explainable.

2.13. Chapter Summary

Eleven analysis diagrams refine the requirements: three activity diagrams, two DFD levels, two sequence diagrams, one class diagram, one state machine, one physical ERD and the context diagram of Chapter 1. The models agree on six checks. The analysis made two rules concrete that the design must keep: stock and status are explained by events, and every external exchange is matched by a unique reference.

CHAPTER 3. AI IN E-COMMERCE

Artificial intelligence is useful to ABC Online Shop only where it improves a business activity that the earlier chapters already described. This chapter therefore does not start from techniques. It starts from the problems and use cases of Chapters 1 and 2, selects three places where AI helps, analyses each one as a requirement with data, components, risks and a fallback, and measures the result on test sets.

3.1. AI as an Enhancement Layer

In the lecture material on integrating AI in the analysis phase, AI is placed as an enhancement layer on top of the information system, not as a replacement for it. The shop still needs a correct catalogue, correct stock and correct orders; a search model that ranks perfectly but shows yesterday's stock would make BP02 worse. The consequence for this essay is a simple rule: every AI component reads the shop's own operational records through the same DAOs as the rest of the system, and every AI result has a non-AI fallback.

3.2. Opportunity Analysis

Table 30. AI opportunities derived from the business problems

Activity / problem	AI opportunity	Decision
Finding products (UC05, SN01)	Search by voice and by photo; tolerate synonyms	Build: multimodal search (from A6)
Judging a product (UC06, BP01)	Summarise many reviews by aspect with evidence	Build: review insights
Moderating reviews (UC18)	Flag spam and empty reviews for a person	Build: noise filter, human decides
Discovering products (UC06, UC10)	Recommend similar or complementary products	Build: content + co-purchase recommender
Answering status questions (BP04)	Natural-language order questions	Build, restricted to own orders
Pricing, fraud scoring	Dynamic prices, payment risk models	Not now: no data, provider handles fraud
Demand forecasting (SN09)	Forecast replenishment quantities	Later: needs months of clean inventory events

The last two rows matter as much as the first five. AI is not used where the shop lacks the data (demand forecasting needs a history of reliable inventory events, which the system is only now starting to record) or where an external party already carries the responsibility (fraud decisions belong to the payment provider, Section 1.8). An AI feature built on data that does not exist would only add a new way to be wrong.

3.3. AI Use Cases

The AI functions are modelled as extensions of the Release 1 use cases. The four ways of searching are specialisations of UC05 Search Products: they share the goal and the flow *retrieve, rank, display* and differ only in how the input is read. UC33 View Review Insights and UC34 View Recommendations extend UC06 View Product Details, because a product page must remain usable without them. A speech/vision engine appears as a secondary actor so that the boundary of the AI service is visible.




Figure 16. AI-enabled use cases - VP diagram "UC_AI AI-Enabled Use Cases"

3.4. Multimodal Search: Principles

The search service of Assignment 06 is built on one principle: different inputs are converted into one common query representation, and from there the processing is the same.

$$\text{text } q_t \to z_t, \quad \text{voice } q_v \to \text{text} \to z_t, \quad \text{image } q_i \to z_i, \quad \text{then retrieval} \to \text{ranking} \to \text{results}$$

Query understanding. QueryService normalises the text, removes stop words, extracts a price filter ("under 100 dollars" → max_price = 100) and maps synonyms ("sneakers" → shoes, "handbag" → bag). The synonym table is new in this essay; it addresses the main error class reported in Assignment 06. A sentence that contains the word *order* becomes an order query that always carries the customer id of the session (AI-R2).

Voice. SpeechService.transcribe(audio) returns text. In the prototype the speech recognition is **simulated**: the argument already is the sentence that a speech-to-text engine would return. The method is the seam where a real engine such as Whisper is plugged in without changing any caller (AI-N1).

Images. ImageService.encode(image) is a hand-made encoder f(I) → z of 128 values: a 4×4×4 RGB histogram of the object's pixels (colour) and an 8×8 occupancy grid of the object mask (shape), both L2-normalised. The background colour is estimated from the image border, so a photo on a different background still matches. Retrieval uses cosine similarity and keeps the top k:

$$s(I_q, I_p) = z_q^T z_p / (||z_q|| \, ||z_p||), \quad R(q) = TopK_{x \in X} s(q, x)$$

3.5. Retrieval and Ranking

Retrieval and ranking are separate steps and separate classes. SearchService.retrieve builds the candidate set C(q) from keyword matches and from the image index; RankingService.rank orders it. The separation lets the business change its ranking policy without touching retrieval. The final score combines three signals:

$$S(x|q) = \alpha \cdot S_{text} + \beta \cdot S_{image} + \gamma \cdot S_{business}$$

- S_{text} = matched query words / number of query words; S_{image} = cosine similarity (0..1);
- $S_{business}$ = 0.8·[available > 0] + 0.2·min(available, 20)/20, read from the shop's own stock (stock-aware ranking);
- text and voice: (α, β, γ) = (0.9, 0, 0.1); image: (0, 0.9, 0.1); text + image: $\alpha = 0.9 \cdot \lambda_t$, $\beta = 0.9 \cdot \lambda_i$, $\lambda_t + \lambda_i = 1$ (default 0.5/0.5).

The architecture keeps the three layers of Assignment 06, now inside the shop: the presentation layer is the shop's controller and view, the application-intelligence layer contains the five AI services, and the data layer contains the same ProductDAO, InventoryDAO and OrderDAO that the checkout uses, plus VectorIndex and ImageStorage. Every dependency points downwards.




Figure 17. Three-layer architecture of the search subsystem - VP diagram "CMP01 AI Search Three-Layer Architecture"

One dependency needed care. VectorIndex must call the encoder to index the product images, but the encoder lives in the layer above. Instead of letting the data layer import upwards, the composition root passes the encoding function in: VectorIndex.build(storage, products, encode). The two sequence diagrams below show voice and image search with the real method names of the code.




Figure 18. Voice search - VP diagram "SD03 Voice Search"




Figure 19. Image search - VP diagram "SD04 Image Search"

Running the four query types on the seeded shop gives the trace below. Each line names the component that performs the step, so a run can be followed on the sequence diagrams. The voice query shows the stock-aware ranking: Nike Court Sneakers matches both words and is the only Nike shoe under 100 dollars, but it is out of stock, so its business score is 0 and its final score 0.900 instead of 0.990. The text + image query shows why combining modalities helps: three products match both words, and only the photo can tell that the customer wants the red pair.

```
$ python main.py demo   (section 1)
  input (text): 'black shoes'
  QueryService -> terms=['black', 'shoes'] filters={}
  SearchService.retrieve -> 8 candidates
  RankingService.rank -> top results (alpha, beta, gamma) = (0.9, 0, 0.1)
    #  Product               Price Avail  keyword  cosine  S(x|q)
    1  Nike Running Shoes      120     6        2  0.000   0.986
    2  Black Cotton T-Shirt     15    43        1  0.000   0.550
    3  Black Leather Bag        80    17        1  0.000   0.547
    4  Adidas Running Shoes    100    14        1  0.000   0.544
    5  Blue Sports Shoes        75    12        1  0.000   0.542

  input (voice): <audio of 'find nike sneakers under 100 dollars'>
  SpeechService.transcribe -> 'find nike sneakers under 100 dollars' (simulated STT)
  QueryService -> terms=['nike', 'shoes'] filters={'max_price': 100.0}
  SearchService.retrieve -> 4 candidates
  RankingService.rank -> top results (alpha, beta, gamma) = (0.9, 0, 0.1)
    #  Product               Price Avail  keyword  cosine  S(x|q)
    1  Nike Court Sneakers      85     0        2  0.000   0.900
    2  Red Baseball Cap         22    17        1  0.000   0.547
    3  Adidas Running Shoes    100    14        1  0.000   0.544
    4  Blue Sports Shoes        75    12        1  0.000   0.542

  input (image): query_red_shoe.png
  ImageService.encode -> 128-d embedding
  SearchService.retrieve -> 5 candidates
  RankingService.rank -> top results (alpha, beta, gamma) = (0, 0.9, 0.1)
    #  Product               Price Avail  keyword  cosine  S(x|q)
    1  Red Running Shoes       110     7        0  0.959   0.950
    2  Red Canvas Backpack      60     7        0  0.808   0.814
    3  Red Baseball Cap         22    17        0  0.790   0.808
    4  Nike Running Shoes      120     6        0  0.504   0.540
    5  Blue Sports Shoes        75    12        0  0.495   0.538

  input (text + image): 'running shoes' + query_red_shoe.png
  ImageService.encode -> 128-d embedding
  QueryService -> terms=['running', 'shoes'] filters={}
  SearchService.retrieve -> 7 candidates
  RankingService.rank -> top results (alpha, beta, gamma) = (0.45, 0.45, 0.1)
    #  Product               Price Avail  keyword  cosine  S(x|q)
    1  Red Running Shoes       110     7        2  0.959   0.969
    2  Nike Running Shoes      120     6        2  0.504   0.763
    3  Adidas Running Shoes    100    14        2  0.000   0.544
    4  Blue Sports Shoes        75    12        1  0.495   0.540
    5  Red Baseball Cap         22    17        0  0.790   0.452
```

Figure 20. Output of the search part of main.py demo: text, voice, image, text + image

3.6. Review Insights

Assignment 02 proposed a PhoBERT aspect-based sentiment model to turn reviews into evidence for customers and managers. The prototype keeps the same interface, analyse(reviews) → per-aspect sentiment with evidence, but implements it with a transparent lexicon so that it runs offline and every label can be explained. The pipeline is drawn as an activity diagram; the decision nodes are the two places where the component falls back instead of guessing.




Figure 21. Review insight pipeline - VP diagram "AD04 Review Insight Pipeline"

- **Noise filter.** Links, long digit strings (phone numbers), repeated characters and texts with fewer than two words are noise. Noise is skipped in the statistics and, when a customer submits it, the review waits for moderation (AI-R5).

- **Clauses.** A review is split at sentence punctuation, commas and the words *but*/*however*, because one review often praises one aspect and criticises another.
- **Aspects and polarity.** Each clause is matched against four aspect vocabularies (quality, price, delivery, service; English and a few Vietnamese words). Polarity is the sum of positive and negative words, with a negation in the three previous words flipping a word ("not fast" is negative).
- **Aggregation.** Positive and negative counts per aspect, the positive share, two evidence sentences, and a label: Mostly positive (share ≥ 0.7), Mixed (≥ 0.4) or Mostly negative. With fewer than two usable reviews the label is "Not enough reviews" (AI-N3).

3.7. Recommendation

The recommender combines two signals computed from the shop's records. Content similarity is the cosine of TF-IDF vectors built from name, category, brand, colour and description; it works for a new product that nobody has bought yet. Co-purchase counts how often two products were in the same non-cancelled order; it captures complements that text cannot (a cap bought with running shoes).

$$score(p, q) = 0.7 \cdot cos(tfidf_p, tfidf_q) + 0.3 \cdot copurchase(p, q) / max_r\ copurchase(p, r)$$

Out-of-stock products are never recommended, and a customer is never recommended something already bought (cancelled and failed orders do not count as purchases). These are business rules, not model parameters; they are enforced in RecommenderService and checked by a test.

3.8. Data Requirements

Table 31. Data cards of the AI components

Component	Input data and source	Quality and constraints
Multimodal search	16 products (name, category, brand, colour, price) from ProductDAO; stock from InventoryDAO; 16 catalogue images and 10 query photos (synthetic drawings)	Images are drawings, so accuracy does not transfer to real photos; stock is read live
Speech	Transcript standing for audio (simulation)	No audio stored; a real engine must not keep recordings
Review insights	Published reviews from ReviewDAO (14 seeded); 30 hand-labelled reviews with 39 aspect labels for evaluation	Only reviews linked to a delivered order; no personal data used
Recommender	Product text; 16 seeded orders (co-purchase)	Cold start handled by content similarity
Order questions	Orders of the session customer only (OrderDAO.find_by_customer)	Never reads another customer's orders (NFR05)

3.9. Evaluation

The search was evaluated on 26 queries: the 20 queries of Assignment 06 and six new ones that test the synonym table, the four new products and the privacy rule (query 26 asks for another customer's order and is successful only if nothing is returned). A query is successful when the top-1 result is the expected product or order.

```
$ python evaluate.py
=== 1. Multimodal search ===
  #  Mode       Query                                Top-1 result             Score  Success
  1  text       black shoes                          Nike Running Shoes       0.986  Yes
  2  text       white polo shirt                     White Polo Shirt         0.988  Yes
  3  text       find Nike shoes under 100 dollars    Nike Court Sneakers      0.900  Yes
  4  text       red bag                              Red Canvas Backpack      0.987  Yes
  5  text       cheap watch under 60                 Silver Analog Watch      0.542  Yes
  6  text       leather handbag                      Black Leather Bag        0.997  Yes
  7  voice      find running shoes                   Adidas Running Shoes     0.994  Yes
  8  voice      show me a blue cap                   Blue Denim Cap           1.000  Yes
  9  voice      i want a smart watch                 Black Smart Watch        0.985  Yes
 10  image      query_black_shoe.png                 Nike Running Shoes       0.892  Yes
 11  image      query_red_shoe.png                   Red Running Shoes        0.950  Yes
 12  image      query_white_shoe.png                 Adidas Running Shoes     0.785  Yes
 13  image      query_black_bag.png                  Black Leather Bag        0.959  Yes
 14  image      query_blue_cap.png                   Blue Denim Cap           0.955  Yes
 15  image      query_silver_watch.png               Silver Analog Watch      0.967  Yes
 16  image      query_black_tshirt.png               Black Cotton T-Shirt     0.961  Yes
 17  multimodal running shoes + query_red_shoe.png   Red Running Shoes        0.969  Yes
 18  multimodal nike + query_white_shoe.png          Nike Running Shoes       0.801  No (expected P05)
 19  text       find my order O001                   O001                        -   Yes
 20  voice      where is my latest order             O016                        -   Yes
 21  text       white sneakers                       Adidas Running Shoes     0.994  No (expected P05)
 22  voice      blue smartwatch                      Blue Smart Watch         0.983  Yes
 23  image      query_red_cap.png                    Red Baseball Cap         0.975  Yes
 24  image      query_blue_backpack.png              Blue Canvas Backpack     0.949  Yes
 25  multimodal cap + query_blue_cap.png             Blue Denim Cap           0.977  Yes
 26  text       find my order O002                   (nothing)                   -   Yes

 Total queries: 26   Successful: 24   Success rate: 92.3%
 Per mode: image 9/9, multimodal 2/3, order 3/3, text 6/7, voice 4/4
```

Figure 22. Output of evaluate.py, part 1: multimodal search on 26 test queries

The success rate is 24/26 = 92.3% (text 6/7, voice 4/4, image 9/9, multimodal 2/3, order 3/3). The review analyser and the recommender were evaluated on their own test data:

```
$ python evaluate.py   (continued)
=== 2. Review insights (aspect-based sentiment) ===
 Reviews: 30   gold aspect labels: 39   predicted: 38
 Aspect detection  precision 0.97  recall 0.95  F1 0.96
 Polarity accuracy on detected aspects: 35/37 = 0.95
 Errors:
   - extra aspect  quality   "The price is too expensive for this quality."
   - missed aspect delivery  "Good material but shipping took two weeks, very slow."
   - polarity      quality   "Leather looks cheap but the price is fair."
   - missed aspect quality   "Hang dep, giao hang nhanh, gia hop ly."
   - polarity      price     "Expensive, but the quality makes it worth it."

=== 3. Recommender ===
 Same-category hit rate of top-3 similar products: 28/48 = 0.58
 Catalogue coverage: 15/15 in-stock products appear in some top-3 list
 Out-of-stock products recommended: 0
```

Figure 23. Output of evaluate.py, parts 2 and 3: review insights and recommender

Table 32. Evaluation summary

Component	Metric	Value
Search	Top-1 success rate	24 / 26 = 92.3%
Search	Image queries / order queries (incl. privacy)	9 / 9, 3 / 3
Review insights	Aspect detection precision / recall / F1	0.97 / 0.95 / 0.96
Review insights	Polarity accuracy on detected aspects	35 / 37 = 0.95
Recommender	Same-category hit rate of top-3	28 / 48 = 0.58
Recommender	Coverage / out-of-stock recommended	15 / 15 / 0

3.10. Error Analysis

- **Query 18 "nike" + white shoe photo.** The expected Nike Court Sneakers has the more similar image but is out of stock, so it loses 0.09 business points and Nike Running Shoes wins (0.801). This is the same trade-off as in Assignment 06; it shows that γ must be tuned on real behaviour.
- **Query 21 "white sneakers".** The synonym table maps *sneakers* to *shoes*, so the word that identified the court sneakers is lost and Adidas Running Shoes (white, in stock) wins. Mapping to both words, or embedding-based text matching, would keep the specific term. A fix for one error class created another, which is why the test set is run on every change.
- **Review insights.** The five errors are typical lexicon limits: an aspect word used as a reference ("too expensive for this quality"), an opinion split from its aspect by a comma ("shipping took two weeks, very slow"), two aspects with opposite polarity in one clause, and missing Vietnamese vocabulary. Sarcasm ("Oh great, another two weeks") was classified correctly only because the star rating broke the tie.
- **Recommender.** A hit rate of 0.58 is low only if the goal is "more of the same". Many top-3 lists mix a same-category item with a complement bought together (shoes and caps), which is intended by the 0.3 co-purchase weight.

3.11. Risks, Fallbacks and Human Control

Table 33. AI risks and the design response

Risk	Effect	Response (fallback / control)
Wrong top result	Customer misses the product	Show top-5 with scores; keyword search and category browsing always available
Speech or image engine unavailable	Voice/photo search fails	Text search unchanged; error message instead of empty page
Ranking hides out-of-stock items	Customer cannot find a known product	Out-of-stock items are ranked lower, never removed from text results
Spam or abusive review	Misleading product page	Noise is held for moderation; an Administrator publishes or rejects (UC18)
Misleading review summary	Wrong purchase decision	Evidence sentences shown next to the counts; full review list below
Order question leaks data	Privacy breach	Order queries carry the session customer id; tested with another customer's order
Feedback loop in recommendations	Popular items get more popular	Content similarity keeps new items visible; coverage measured

Human control is designed in at two points. Reviews flagged as noise are never published automatically; they appear in the moderation queue, where a person decides. And no AI component can change an order, a price or a stock level: AI only ranks, labels and suggests. Every state change still goes through the services and rules of Chapter 4.

3.12. Technology Options for a Production Version

Table 34. Prototype components and production replacements

Prototype	Production option	What stays the same
SpeechService (simulated)	Whisper or a cloud speech API with Vietnamese support	transcribe(audio) -> text
ImageService (colour + shape)	CLIP image encoder (shared space with text)	encode(image) -> vector
VectorIndex (in memory)	FAISS or a vector database	search(z, k) -> [(id, score)]
Lexicon review analyser	PhoBERT fine-tuned for ABSA (Assignment 02)	analyse(reviews) -> aspects, label
TF-IDF + co-purchase	Matrix factorisation / two-tower model with click data	similar(id, k), for_customer(id, k)

The right-hand column is the important one: the interfaces were fixed in Chapter 1 as AI-N1, so each replacement is a change in one class plus the composition root, and the 40 tests of Chapter 5 continue to describe the behaviour that the shop expects.

3.13. AI Component Specifications

Table 35. AI component specifications

ID / component	Input → output	Interface	Fallback
AIC-01 SpeechService	audio → text	transcribe(audio) -> str	Text box; message "please type your search"
AIC-02 QueryService	text → {type, terms, filters} or order query	text_query, voice_query, image_query, multimodal_query, order_query	Raw words as terms
AIC-03 ImageService + VectorIndex	image → 128-d vector → top-k ids	encode(path); VectorIndex.search(z, k)	Category browsing
AIC-04 Search + RankingService	query → ranked products with scores	search(query, k) -> [result]	Keyword-only ranking
AIC-05 ReviewInsightService	reviews → aspects, counts, evidence, label	analyse(reviews); is_noise(text)	Plain review list
AIC-06 RecommenderService	product / customer → products with scores	fit(); similar(id, k); for_customer(id, k)	Same-category products

3.14. Worked Example: Ranking a Combined Query

The combined query "running shoes" with a photo of a red shoe shows how the formula of Section 3.5 decides. With $\lambda_t = \lambda_i = 0.5$ the weights are $\alpha = \beta = 0.45$ and $\gamma = 0.1$. All three running shoes match both query words, so $S_{text} = 2/2 = 1$ for each of them; the photo separates them.

Table 36. Score components of the top three results

Product	S_text	S_image (cosine)	Available	S_business	S(x|q)
Red Running Shoes	1.00	0.959	7	0.8 + 0.2·7/20 = 0.870	0.45 + 0.432 + 0.087 = 0.969
Nike Running Shoes	1.00	0.504	6	0.8 + 0.2·6/20 = 0.860	0.45 + 0.227 + 0.086 = 0.763
Adidas Running Shoes	1.00	0 (not in image top-5)	14	0.8 + 0.2·14/20 = 0.940	0.45 + 0 + 0.094 = 0.544

The example also shows a limit: Adidas Running Shoes receives no image score at all because the image retrieval keeps only the five most similar pictures, and the red cap and red backpack are more similar in colour than a white shoe. With a larger k, or with a neural encoder that captures shape better than colour, it would get a small positive score. The order of the results would not change, which is why k = 5 was kept.

3.15. Worked Example: Analysing One Review

The review "Comfortable shoes but delivery was late by four days." (3 stars) is processed as follows. It is not noise (more than two words, no link). It is split at *but* into "comfortable shoes" and "delivery was late by four days". The first clause contains the quality word *comfortable*, which is also a positive word: quality +1. The second contains the delivery word *delivery* and the negative word *late*: delivery −1. The star rating is not needed because both clauses carry an opinion. On the product page, this review adds one positive quality count and one negative delivery count, and may be shown as evidence for either aspect.

3.16. Business Evaluation

Technical metrics say whether a component works; business metrics say whether it helps the shop. The prototype cannot measure the second kind, because it has no real customers, so the metrics are defined now and attached to the AI requirements, to be collected with an A/B comparison after release.

Table 37. Business metrics of the AI features

Feature	Metric	Linked problem / need
Multimodal search	Search-to-cart rate; share of searches with no click; voice/photo usage	SN01, BP01
Order questions	Status enquiries to staff per 100 orders	BP04, SN04
Review insights	Return rate of products with negative aspects; time to resolve a recurring complaint	SN06, SN10
Noise filter	Share of spam that reaches the product page; moderation time	SN06
Recommendations	Click-through and add-to-cart rate of recommended items; items per order	Business objective (sales)

3.17. AI Traceability

Table 38. From problem to AI requirement, component, metric and test

Need / problem	AI requirement	Component	Measured by	Test
SN01 find products	AI-R1, AI-R3	AIC-01..04	Top-1 success 92.3%	test_image_and_multimodal_search
BP04, NFR05 status, privacy	AI-R2	AIC-02, OrderDAO	3/3 order queries	test_order_questions_only_see_own_orders
SN06 controlled reviews	AI-R4, AI-R5	AIC-05	F1 0.96	test_review_insights_handle_negation_and_noise
Sales objective	AI-R6	AIC-06	Coverage 15/15	test_recommender_never_suggests_...
NFR09 maintainability	AI-N1	all	Interfaces fixed	test_dependencies_only_point_downwards

3.18. Chapter Summary

Three AI components were analysed like any other requirement: they come from business problems, extend existing use cases, read the shop's own data, have fallbacks and are measured. The search keeps the Assignment 06 design and reaches 92.3% top-1 success on 26 queries; the review analyser reaches an aspect F1 of 0.96; the recommender never suggests unavailable or already-bought items. The honest limits (synthetic images, simulated speech, a lexicon instead of a trained model) are stated together with the production replacements that the interfaces allow.

CHAPTER 4. DESIGN

Analysis described the problem; design describes the solution. In this chapter the analysis classes of Chapter 2 become a layered software design. The chapter follows the four transformation steps of the lecture "from analysis to design", practised in Test 01 on the e-commerce class diagram (eComDesign): add methods, replace associations by use dependencies, introduce data access objects, and group the classes into the packages of an MVC architecture. It then covers the database, transactions, the web interface, security and testability, and ends with the design decisions and what they cost.

4.1. Design Goals

The design goals are the non-functional requirements of Chapter 1 seen from the builder's side. Writing the table below first kept the design honest: every structural decision should point back to a row.

Table 39. Non-functional requirements and the design decisions that serve them

Requirement	Design decision
NFR09 Maintainability	Layers with one-way dependencies; services depend on DAO interfaces, not on SQLite; a test enforces the layer rule
NFR05 Access control	Every service method that changes data checks the caller's role (AuthService.require); customer queries always use the session customer id
NFR06 Auditability	AuditDAO records actor, action, entity and detail for price, stock, status and moderation changes
NFR07 Integrity	Idempotency key on orders, unique attempt reference on payments, unique (product, kind, reference) on stock events, milestone sequence numbers
NFR10 Privacy	Payment stores status and references only; the provider handles card data
NFR01-02 Performance	Read-only queries for browsing; the vector index is kept in memory and rebuilt only when the catalogue changes
AI-N1 Replaceable AI	AI components behind fixed methods: transcribe, encode, search, analyse, similar

4.2. Choosing the Architecture

Three styles were compared. A single-layer design, in which each page reads and writes the database itself, is quick to start but repeats the root cause of the shop's problems: the same data handled in many places in many ways. Microservices (catalogue, orders, payments, search as separate services) suit a large shop with several teams, but here they would add network calls and distributed consistency problems to a checkout that must reserve stock and create an order atomically. A **layered monolith** is the right size: one deployable application, divided internally so that each part can change alone, and divisible later along the same package lines.

The design keeps the view, controller, DAO and model packages of the lecture's MVC model and adds two things. A **service** layer between controller and DAO holds the business rules of each use case, because putting the checkout rules into a controller would mix HTTP handling with stock and payment logic and make both hard to test. An **ai** package sits beside the services at the same level, because the AI components are application logic that reads the same

DAOs. The component diagram shows the result together with the external providers.




Figure 24. System components - VP diagram "CMP02 System Component Diagram"

4.3. Step 1: Adding Methods

The first step gives the analysis classes their operations. The lecture distinguishes two kinds. A **method of the class itself** works on the class's own data, such as Cart.calcTotal() or StockLevel.isLow(). A **method linked to another class** takes an object of that class as a parameter and uses its attributes, such as Cart.addItem(product, qty), which reads the product's id, name and price. The second kind decides the direction of the use dependencies in Step 2.




Figure 25. Design class diagram after Step 1 - VP diagram "DCL01 Design Step 1 - Methods Added"

Table 40. Methods added in Step 1

Class	Methods of the class itself	Methods linked to another class
User / Customer	can(permission)	updateProfile(name, address : Address)
Address	isComplete(), oneLine()	-
Product	isActive(), searchText(), updatePrice(newPrice)	-
Promotion	isValid(subtotal, today), discountFor(subtotal, today)	-
Cart / CartItem	updateQuantity, removeItem, calcTotal, clear / subTotal	addItem(product : Product, qty)
Order / OrderItem	subtotal, calcTotal, changeStatus, canCancel / subTotal	createFromCart(id, cart : Cart, address)
Payment	matches(ref, amount, currency), isFinal()	-
StockLevel	available(), isLow()	apply(event : InventoryEvent)
Shipment	lastSeq()	addMilestone(m : Milestone)
Review	validate()	-

Three placements needed a reason. calcTotal() is in Cart and Order while subTotal() is in the line classes: each line computes its own amount and the whole adds the lines, so no class reaches inside another to multiply prices. changeStatus() is in Order, not in a service, because the transition table is a property of the order itself; a service may decide *when* to change a status, never *whether* a transition is legal. And apply(event) is in StockLevel because the rule "never negative" belongs to the stock, not to whoever records the event.

4.4. Step 2: From Associations to Use Dependencies

The lecture's rule: if class A has a method that takes B and uses B's attributes, the design shows a <<use>> dependency from A to B instead of the association of the analysis model. The right-hand column of the Step 1 table gives the dependencies.

Table 41. Associations replaced by use dependencies

Analysis relationship	Method that justifies it	Design
CartItem - Product	Cart.addItem(product, qty)	Cart → Product <<use>>; CartItem keeps productId
Cart - Order (checkout)	Order.createFromCart(id, cart, address)	Order → Cart <<use>>
StockLevel - InventoryEvent	StockLevel.apply(event)	StockLevel → InventoryEvent <<use>>
Customer - Address	Customer.updateProfile(name, address)	aggregation kept, plus <<use>>
Order - Payment, Shipment, Review	no method takes the other object	identifier attribute (orderId)

The second row reverses the business direction. In the analysis the cart "creates" the order; in the design the method lives in Order, so Order uses Cart. The analysis arrow describes what happens in the business, the design arrow describes which class must know which. The last row is a deliberate design decision: Payment, Shipment and Review refer to their order by

identifier instead of holding an object reference, because they are loaded and saved by different DAOs and different use cases. The compositions (Cart-CartItem, Order-OrderItem, Order-StatusChange, Shipment-Milestone) stay: they describe structure, not calls.




Figure 26. Design class diagram after Step 2 - VP diagram "DCL02 Design Step 2 - Use Dependencies"

4.5. Step 3: Data Access Objects

The third step separates storage from business logic. A data access object collects every read and write for one kind of model object. It has two parts: an interface that declares *what* can be done (getOrder(id), saveOrder(order)) and an implementation that knows *how* (SQL against SQLite). Services depend only on the interfaces, so the storage can change without touching them. In the diagram each implementation realises its interface (dashed line, hollow triangle), and each interface uses the model class it reads and returns.




Figure 27. Data access objects - VP diagram "DCL03 Design Step 3 - Data Access Objects"

Table 42. DAO interfaces

Interface	Main methods	Model
CustomerDAO	getUser, findByEmail, saveUser, listCustomers	User, Customer, Address
ProductDAO	getProduct, listProducts(category), saveProduct, listCategories	Product, Category
InventoryDAO	getStock, saveStock, findEvent(product, kind, ref), addEvent, replenishment	StockLevel, InventoryEvent
CartDAO	getCart(customerId) (created on first use), updateCart	Cart, CartItem
PromotionDAO	getPromotion(code), savePromotion	Promotion
OrderDAO	getOrder, findByIdempotencyKey, findByCustomer, findByStatus, saveOrder	Order, OrderItem, StatusChange
PaymentDAO	getByAttempt(ref), forOrder, savePayment	Payment
ShipmentDAO	getByOrder, getByCarrierRef, saveShipment	Shipment, Milestone
ReviewDAO, AuditDAO	forProduct, exists, saveReview / record, recent	Review / audit rows

Two decisions are worth recording. A missing record returns None or an empty list instead of raising an error, because "not found" is an expected outcome of several use cases (UC11 E2) and the service decides what it means. And all implementations share one Database object, which owns the connection and offers transaction(): a service that must change several kinds of data atomically opens one transaction, and every DAO call inside it joins it.

4.6. Step 4: Packages and the MVC Architecture

The last step groups the classes into packages. Dependencies run controller → service/ai → dao → model, plus controller → view and controller → model, because controllers pass model objects to the views. Nothing goes from view or controller to dao, and nothing in model depends on anything. The module shop.py is the composition root: the only place that creates objects and connects the layers.




Figure 28. Packages of the MVC architecture - VP diagram "PKG01 Design Step 4 - MVC Packages"

Table 43. One request through the layers: a customer adds a product to the cart

Step	Layer and class	What happens
1	view: product page	The form posts product_id and quantity to /cart/add
2	controller: WebApp, OrderController.add_to_cart	Routes the request; checks the role 'cart'; calls the service
3	service: CartService.add_item	Loads product (ProductDAO) and cart (CartDAO); checks availability (UC30)
4	model: Cart.add_item	Adds to an existing line or creates one with the current price
5	dao: CartDAO.update_cart	Stores the lines in one transaction
6	controller → view	Redirects to /cart, which renders the updated cart

4.7. Database Design

The physical model of Section 2.7 becomes the schema below (excerpt). The integrity rules are written as constraints so that no path, not even a manual correction script, can break them; the services check the same rules first to give the user a clear message. The redundancy is deliberate.

```
CREATE TABLE IF NOT EXISTS stock_level (
    product_id  TEXT PRIMARY KEY REFERENCES product(product_id),
    physical    INTEGER NOT NULL CHECK (physical >= 0),
    reserved    INTEGER NOT NULL CHECK (reserved >= 0),
    threshold   INTEGER NOT NULL DEFAULT 3,
    CHECK (physical >= reserved)
);
CREATE TABLE IF NOT EXISTS inventory_event (
    event_id    TEXT PRIMARY KEY,
    product_id  TEXT NOT NULL REFERENCES product(product_id),
    kind        TEXT NOT NULL CHECK (kind IN ('RECEIPT','RESERVE','RELEASE','ISSUE','ADJUST')),
    quantity    INTEGER NOT NULL,
    reference   TEXT NOT NULL,
    reason      TEXT NOT NULL DEFAULT '',
    created_at  TEXT NOT NULL,
    UNIQUE (product_id, kind, reference)
);
CREATE TABLE IF NOT EXISTS customer_order (
    order_id         TEXT PRIMARY KEY,
    customer_id      TEXT NOT NULL REFERENCES users(user_id),
    address          TEXT NOT NULL,
    discount         REAL NOT NULL DEFAULT 0,
    shipping_fee     REAL NOT NULL DEFAULT 0,
    total            REAL NOT NULL CHECK (total > 0),
    status           TEXT NOT NULL,
    created_at       TEXT NOT NULL,
    promo_code       TEXT NOT NULL DEFAULT '',
    idempotency_key  TEXT UNIQUE
);
CREATE TABLE IF NOT EXISTS payment (
    payment_id    TEXT PRIMARY KEY,
    order_id      TEXT NOT NULL REFERENCES customer_order(order_id),
    attempt_ref   TEXT NOT NULL UNIQUE,
    amount        REAL NOT NULL CHECK (amount > 0),
    currency      TEXT NOT NULL DEFAULT 'USD',
    status        TEXT NOT NULL,
    provider_ref  TEXT NOT NULL DEFAULT '',
    created_at    TEXT NOT NULL
);
```

4.8. Transactions and Idempotency in Checkout

Checkout is the use case where design mistakes cost money, so its design sequence diagram uses the real class and method names. Messages 3-4 implement A7 (repeated submission): the idempotency key of the form is looked up first, and a second submission returns the existing order. Messages 8-10 run inside one database transaction (E1). Payment is requested only after the transaction has committed, so that a provider never receives a request for an order that does not exist.




Figure 29. Checkout through the layers - VP diagram "SD05 Checkout Through the Layers (Design)"

The payment result is designed as a callback that may arrive more than once, late or forged. PaymentService verifies a signature over (reference, status, provider reference, amount, currency), then the amount and currency, and only then changes the order. A result for an attempt that is already final is acknowledged and ignored. A late success for an order that is no longer pending creates a refund exception instead of changing a cancelled order. Each of these branches corresponds to an alternative flow of UC09 in Assignment 02.

4.9. Web Interface Design

Table 44. Routes of the web application and the use cases they serve

Method and path	Controller	Use case	Role
GET /, GET /product/{id}	ShopController	UC04, UC06, UC33-34	any
GET|POST /search	ShopController	UC05 (text, voice, image), order questions	any / customer
GET|POST /login, /register	AccountController	UC01, UC02	any
GET /cart, POST /cart/add, /cart/update	OrderController	UC07	customer
GET|POST /checkout	OrderController	UC08, UC09, UC29-32	customer
GET /orders, /orders/{id}	OrderController	UC10, UC11, UC34	customer (own orders)
POST /orders/{id}/cancel, /review	OrderController	UC12, UC13	customer
GET /staff/orders, POST .../{process|hold|pack|ship}	StaffController	UC19, UC21, UC22	sales, warehouse
GET|POST /staff/inventory	StaffController	UC20, UC24	warehouse
GET /admin/reviews, POST /admin/reviews/{id}	StaffController	UC18	admin
GET /reports	ReportController	UC25-28	manager

Keeping the use case in the table is a small habit with a clear benefit: a route without a use case is either a missing requirement or unnecessary. UC23 has no route on purpose, because the shipping provider calls ShipmentService.on_milestone through an integration, not through a page.

4.10. Security and Privacy by Design

Table 45. Role permissions

Permission	Customer	Sales	Warehouse	Admin	Manager
cart, checkout, own_orders, review	yes	-	-	-	-
process_orders	-	yes	-	-	-
inventory, shipment	-	-	yes	-	-
catalogue, promotions, moderate_reviews	-	-	-	yes	-
customers	-	yes	-	yes	-
reports	-	-	-	-	yes

The permissions live in the model (User.can) and are checked in the services, not only in the pages, so a new page cannot forget them. Passwords are stored as salted PBKDF2-SHA256 hashes; a failed login gives the same message for an unknown email and a wrong password, so the login page cannot be used to discover accounts. Sessions use a random identifier in an HttpOnly cookie. The deployment diagram shows where TLS (NFR04) applies in production: between the browser and the server, and between the server and the providers.




Figure 30. Deployment - VP diagram "DEP01 Deployment Diagram"

4.11. Design for Testability

A design is testable when each part can run without the others. Every class receives its collaborators through its constructor, and shop.py is the only place that creates them, so a test can build the whole shop on an in-memory database, replace the payment gateway with one that times out, or set the clock to a fixed date. The design therefore produces three kinds of tests: unit tests per model class, scenario tests that follow a use case specification, and architecture tests that follow the package diagram.

4.12. Design Decisions and Trade-offs

Table 46. Design decisions, rejected alternatives and accepted costs

Decision	Rejected alternative	Accepted cost
Layered monolith, MVC + service + DAO	Microservices	Parts cannot be scaled separately
Service layer between controller and DAO	Rules in controllers	One more class per area
Order owns its transition table	Status checks in each service	Model and diagram must be updated together
Stock as typed events	Stock as one editable number	More rows; balance must be recalculated
Reference by id between aggregates	Object references everywhere	Extra DAO calls to load related data
Encoder passed into VectorIndex	VectorIndex imports ImageService	Wiring code in the composition root
Card processing left to the provider	Store cards	Dependence on provider availability
Rules in service and database	Rules only in code	Rules written twice

4.13. From Analysis Classes to Design Classes

Table 47. What happened to each analysis element in the design

Analysis element	Design element(s)	Package
Entity classes (Customer, Cart, Order, ...)	Model classes with Step 1 methods	model
Boundary objects (CheckoutForm, OrderPage)	View templates + controller methods	view, controller
Control objects (CheckoutController)	Service classes (CheckoutService, ...)	service
PaymentGateway boundary	PaymentGateway interface + SimulatedPaymentProvider	service
Data stores of the DFD	Tables (schema.sql) + DAO interfaces and implementations	dao
Order state machine	TRANSITIONS dictionary + Order.change_status	model
Decision tables	OrderService.start_processing, Order.can_cancel, Promotion.discount_for	service, model
Search components of Assignment 06	ai.search package + VectorIndex, ImageStorage in dao	ai, dao

The control objects of the analysis are the place where the name changes the most: an analysis control "coordinates a use case", and in a web application that job is split between a controller, which handles the request, and a service, which applies the rules. This split is the main reason for the extra service layer.

4.14. Service Layer Specification

Table 48. Service classes

Service	Responsibility	Collaborators (constructor)	Use cases
AuthService	Register, login, password hashing, role checks	Database, CustomerDAO, AuditDAO	UC01-02
CatalogService	Browse, product details with availability, product and promotion maintenance	ProductDAO, InventoryDAO, PromotionDAO, AuditDAO	UC04, UC06, UC14, UC16
CartService	Cart lines, availability, cart validation	CartDAO, ProductDAO, InventoryDAO	UC07, UC29-30
CheckoutService	Quote, promotion, shipping, atomic order creation, payment request	CartDAO, OrderDAO, PromotionDAO, CartService, InventoryService, PaymentService	UC08, UC31-32
PaymentService	Payment attempts, verified callbacks, failure handling	PaymentDAO, OrderDAO, InventoryService, PaymentGateway, AuditDAO	UC09
OrderService	History, tracking, cancellation, processing queue	OrderDAO, ShipmentDAO, PaymentService, InventoryService, AuditDAO	UC10-12, UC19

Service	Responsibility	Collaborators (constructor)	Use cases
InventoryService	Idempotent stock events, low stock, replenishment	InventoryDAO, ProductDAO, AuditDAO	UC20, UC24
ShipmentService	Pick list, packing, delivery request, milestones	ShipmentDAO, OrderDAO, InventoryService, ShippingGateway	UC21-23
ReviewService	Eligibility, noise check, moderation	ReviewDAO, OrderDAO, ReviewInsightService	UC13, UC18
ReportService	Dashboard, sales, inventory and exception reports	OrderDAO, ProductDAO, InventoryDAO, AuditDAO	UC25-28

4.15. Interfaces to External Systems

Table 49. Contracts of the provider gateways

Interface	Request	Response / callback	Guarantees
PaymentGateway.authorize	attempt_ref, amount, currency, card token	{attempt_ref, status, provider_ref, amount, currency, signature} or no answer	Signature = HMAC-SHA256 over all fields; result may repeat or arrive late
ShippingGateway.create_delivery	order_id, address, parcels	carrier reference	One reference per order; reused if called again
Carrier milestone (UC23)	-	carrier_ref, seq, code, time, location	seq increases; duplicates and older messages ignored

4.16. Error Handling Design

Table 50. Service exceptions and how the presentation layer shows them

Exception	Raised when	Shown as
NotFound	Record missing or owned by another customer	404 page with a neutral message
PermissionDenied	Role lacks the permission	Redirect to login (no session) or 403 page
ValidationError	A business rule rejects the request (stock, transition, review)	400 page or a message on the form
CheckoutError	Cart validation problems (list)	Back to the cart with every problem listed
StockError / InvalidTransition	Model rule violated	Converted to ValidationError by the service

4.17. Design Patterns Used

Table 51. Patterns and where they appear

Pattern	Where	Why
Model-View-Controller	view, controller, model packages	Separate request handling, presentation and data
Service layer	service package	One place for the rules of a use case
Data Access Object	dao package	Storage can change without touching services
Front controller / router	WebApp.dispatch	One entry point for routing, sessions and error mapping
Gateway (strategy)	PaymentGateway, ShippingGateway	Simulated and real providers are interchangeable
Composition root, dependency injection	shop.build_shop	All wiring in one place; tests replace parts
Idempotency key	Checkout, payment attempts, stock references	Safe retries (NFR07)
Event log (append-only)	inventory_event, order_status_history	Every figure explained by its history

4.18. Chapter Summary

The analysis classes became a layered design in four documented steps: methods of two kinds, four associations replaced by use dependencies, ten DAO pairs and six packages around a composition root. The schema expresses the integrity requirements as constraints, the checkout design makes idempotency and atomicity explicit, every route maps to a use case, and permissions are checked where the data changes. The next chapter checks whether this design holds up in running code.

CHAPTER 5. CODE

The last activity tests every earlier decision against reality. A requirement can be ambiguous and a diagram can be inconsistent without anyone noticing; a program either runs or it does not, and its tests either pass or fail. This chapter presents the application **abc_shop**, written for this essay on top of the Assignment 06 search prototype. It shows how the code follows the design, how it was run and tested, and what writing it taught about the earlier models.

5.1. Implementation Strategy and Environment

The application implements the Release 1 transaction path end to end (account, catalogue, cart, checkout, payment, processing, packing, delivery, tracking, cancellation, reviews, inventory, reports) and the three AI components, rather than every screen of all 32 use cases. A vertical slice through all layers is a better test of the architecture than a complete but shallow user interface: if a checkout can travel from a web form through the controller, the service and the DAO to the database and back, the remaining use cases follow the same path. Python was chosen to keep the Assignment 06 code without translation, and only the standard library plus numpy and Pillow are used, so the program runs offline on any machine with Python 3.9 or later.

Table 52. Environment and size of the code base

Item	Value
Language and libraries	Python 3.11 (tested), standard library: sqlite3, wsgiref, hashlib, hmac; numpy, Pillow; pytest for tests
Database	SQLite file data/abc_shop.db (or in memory for tests and the demo)
Web server	wsgiref (standard library WSGI server); pages rendered by view/templates.py
Application code	3581 lines: model 451, dao 623, service 812, ai 424, controller 450, view 252, entry points 569
Tests	450 lines in 7 modules; 40 test cases, all passing
Repository	github.com/qkhanhbe/ABC-Online-Shop-Information-System

5.2. Project Structure

The folders are the packages of the Step 4 diagram, one to one. A reader of the package diagram can find any class in the code by its package name, and a reader of the code can find any file in the diagram.

```
abc_shop/
  main.py             entry point: seed | serve | demo | search
  shop.py             composition root (creates and wires every object)
  seed.py             catalogue, accounts, October history played through the services
  evaluate.py         evaluation of the three AI components
  model/              customer, product, cart, order, payment, shipment, inventory, review
  dao/                schema.sql, database.py, interfaces.py, sqlite_dao.py, vector_index.py, im
  service/            auth, catalog, cart, checkout, payment, order, inventory, shipment, review
  ai/                 search/ (query, speech, image, search, ranking), review_insights.py, recom
  controller/         http.py, router.py, account/shop/order/staff/report controllers
  view/               templates.py, static/style.css
  data/               seed.json, reviews_labeled.json, images/, query_images/
  tests/              7 test modules, 40 test cases
```

5.3. The Model

The model classes are Python dataclasses with the methods of Step 1. The order state machine of Section 2.6 is a dictionary in model/order.py; change_status is the only way to change a status, it appends to the history and rejects every transition that is not in the table:

```
def change_status(self, new_status, actor, at, note=""):
    if new_status not in TRANSITIONS.get(self.status, set()):
        allowed = ", ".join(sorted(TRANSITIONS.get(self.status, set()))) or "none"
        raise InvalidTransition(
            f"{self.order_id}: {self.status} -> {new_status} is not allowed (next: {allowed})")
    self.status = new_status
    self.history.append(StatusChange(new_status, actor, at, note))
    return self
```

The stock rule of UC20 lives in StockLevel.apply. It works on local copies and assigns the new quantities only after every check has passed, so a rejected event leaves the stock exactly as it was (minimal guarantee of UC20):

```
def apply(self, event):
    """Apply one event; raise StockError and leave the level unchanged if it is invalid."""
    q = event.quantity
    physical, reserved = self.physical, self.reserved
    if event.kind == "RECEIPT":
        physical += q
    elif event.kind == "RESERVE":
        if q > self.available:
            raise StockError(f"only {self.available} available for {self.product_id}")
        reserved += q
    elif event.kind == "RELEASE":
        if q > reserved:
            raise StockError("release exceeds reservation")
        reserved -= q
    elif event.kind == "ISSUE":
        if q > reserved:
            raise StockError("issue exceeds reservation")
        physical -= q
        reserved -= q
    elif event.kind == "ADJUST":          # signed correction with a reason code
        if not event.reason:
            raise StockError("an adjustment needs a reason")
        physical += q
    else:
        raise StockError(f"unknown event kind {event.kind}")
    if event.kind != "ADJUST" and q <= 0:
        raise StockError("quantity must be positive")
    if physical < 0 or reserved < 0 or physical - reserved < 0:
        raise StockError("resulting balance would be negative")
    self.physical, self.reserved = physical, reserved
    return self
```

5.4. Data Access Objects

The interfaces in dao/interfaces.py are abstract classes; the services receive them through their constructors and never import the SQLite module (an architecture test checks this). The order DAO shows how the append-only history of the analysis model reaches the database: an order is upserted, its lines are written once, and only history entries that are not stored yet are inserted.

```
def save_order(self, o):
    """Insert or update; status history rows are appended, never rewritten."""
    with self.db.transaction():
        self.db.execute(
```

```
            "INSERT INTO customer_order(order_id, customer_id, address, discount, shipping_fee, "
            "total, status, created_at, promo_code, idempotency_key) "
            "VALUES (?, ?, ?, ?, ?, ?, ?, ?, ?, ?) ON CONFLICT(order_id) DO UPDATE SET "
            "status = excluded.status",
            (o.order_id, o.customer_id, o.address, o.discount, o.shipping_fee, o.calc_total(),
             o.status, o.created_at, o.promo_code, o.idempotency_key or None))
        if not self.db.query_one("SELECT 1 FROM order_item WHERE order_id = ?", (o.order_id,)):
            for i in o.items:
                self.db.execute("INSERT INTO order_item(order_id, product_id, name, unit_price, "
                                "quantity) VALUES (?, ?, ?, ?, ?)",
                                (o.order_id, i.product_id, i.name, i.unit_price, i.quantity))
        stored = self.db.query_one("SELECT COUNT(*) AS n FROM order_status_history "
                                   "WHERE order_id = ?", (o.order_id,))["n"]
        for h in o.history[stored:]:
            self.db.execute("INSERT INTO order_status_history(order_id, status, actor, at, note) "
                            "VALUES (?, ?, ?, ?, ?)", (o.order_id, h.status, h.actor, h.at, h.not
    return o
```

Database.transaction() is a context manager that supports nesting: the outermost call opens BEGIN IMMEDIATE and commits or rolls back, inner calls join it. This let each DAO method protect its own multi-statement writes while a service can still make several DAO calls atomic.

```
@contextmanager
def transaction(self):
    """Nested calls join the outer transaction; the outermost one commits or rolls back."""
    if self._depth == 0:
        self.conn.execute("BEGIN IMMEDIATE")
    self._depth += 1
    try:
        yield self.conn
    except Exception:
        self._depth -= 1
        if self._depth == 0:
            self.conn.execute("ROLLBACK")
        raise
    else:
        self._depth -= 1
        if self._depth == 0:
            self.conn.execute("COMMIT")
```

5.5. Services: Checkout and Payment

CheckoutService.place_order is UC08 in code; the comments carry the step and flow numbers of the specification in Section 1.15. The idempotency key comes from a hidden field of the checkout form, so pressing the button twice returns the first order (A7).

```
def place_order(self, customer, promo_code="", card_token="tok_visa", idempotency_key=None):
    idempotency_key = idempotency_key or uuid.uuid4().hex
    existing = self.orders.find_by_idempotency_key(idempotency_key)
    if existing:                                                    # A7 repeated submission
        return {"order": existing, "payment": existing.status, "duplicate": True}

    if customer.address is None or not customer.address.is_complete():
        raise CheckoutError(["delivery address is incomplete"])     # A3
    quote = self.quote(customer.user_id, promo_code)
    if quote["problems"]:
        raise CheckoutError(quote["problems"])                      # A1, A2
    cart = quote["cart"]

    # step 6: reserve stock and create one Payment Pending order - atomically (E1)
    with self.db.transaction():
        order = Order.create_from_cart(
            self.db.next_id("order", "O"), cart, customer.address.one_line(), self.db.now(),
            idempotency_key, quote["discount"], quote["shipping"],
```

```
            promo_code.upper() if quote["discount"] else "")
        self.orders.save_order(order)
        self.inventory.reserve_order(order)

    # steps 7-8: UC09 Make Payment
    status = self.payments.request_payment(order, card_token)
    if status == SUCCEEDED:
        cart.clear()
        self.carts.update_cart(cart)                                    # cart cleared only when pai
    return {"order": self.orders.get_order(order.order_id), "payment": status,
            "duplicate": False}
```

PaymentService.handle_result is the provider callback of UC09. The order of the checks is the order of the exception flows: unknown or unsigned result (E2), mismatching amount or currency (E1), already final (A3), then success or decline, with a late success on a closed order turned into a refund exception (A4).

```
def handle_result(self, result):
    """Provider callback. Returns the payment status after the result is applied."""
    payment = self.payments.get_by_attempt(result.get("attempt_ref", ""))
    expected = sign(result.get("attempt_ref"), result.get("status"), result.get("provider_ref"),
                    result.get("amount"), result.get("currency"))
    if payment is None or result.get("signature") != expected:
        self.audit.record("payment", "rejected_callback", "payment",
                          str(result.get("attempt_ref")), "unknown or unsigned result")
        return "Rejected"                                   # E2: no state change
    if not payment.matches(result["attempt_ref"], result["amount"], result["currency"]):
        self.audit.record("payment", "quarantined", "payment", payment.attempt_ref,
                          "amount or currency mismatch")
        return "Quarantined"                                # E1: no state change
    if payment.is_final():
        return payment.status                               # A3: duplicate, no second effect

    order = self.orders.get_order(payment.order_id)
    with self.db.transaction():
        payment.provider_ref = result["provider_ref"]
        if result["status"] == "SUCCEEDED":
            payment.status = SUCCEEDED
            if order.status == states.PAYMENT_PENDING:
                order.change_status(states.PAID, "payment-provider", self.db.now(),
                                    f"paid {payment.amount} {payment.currency} ref {payment.provi
            else:                                           # A4 late success on a closed order
                self.audit.record("payment", "refund_needed", "order", order.order_id,
                                  "late payment success")
        else:
            payment.status = FAILED
            if order.status == states.PAYMENT_PENDING:
                order.change_status(states.PAYMENT_FAILED, "payment-provider", self.db.now(),
                                    "payment declined")
                self.inventory.release_order(order)
        self.payments.save_payment(payment)
        self.orders.save_order(order)
    return payment.status
```

5.6. Controllers and Views

The web layer uses only the standard library. WebApp in controller/router.py is a WSGI application with a table of routes (Section 4.9). dispatch() loads the user of the session, calls the controller method and turns service errors into readable pages: NotFound becomes 404, PermissionDenied a redirect to the login page or 403, any other ServiceError a 400 page with the rule that was violated.

```
def dispatch(self, request):
    if request.path.startswith(("/static/", "/images/")):
        return self.static(request.path)
    user = self.shop.dao.customers.get_user(request.session.get("user_id", ""))
    request.user = user
    for method, pattern, handler in self.routes:
        match = re.fullmatch(pattern, request.path)
        if match and method == request.method:
            try:
                return handler(request, **match.groupdict())
            except NotFound as e:
                return Response(templates.message(request, "Not found", str(e)), 404)
            except PermissionDenied as e:
                if user is None:
                    return Response.redirect("/login", "Please log in first.", request)
                return Response(templates.message(request, "Not permitted", str(e)), 403)
            except ServiceError as e:
                return Response(templates.message(request, "Request rejected", str(e)), 400)
            except Exception:                       # pragma: no cover - last resort
                traceback.print_exc()
                return Response(templates.message(request, "Error", "Unexpected error."), 500)
    return Response(templates.message(request, "Not found", request.path), 404)
```

Controllers stay thin. OrderController.checkout reads the form, calls one service method and redirects; it touches no DAO and calculates nothing:

```
def checkout(self, request):
    customer = self._customer(request)
    try:
        result = self.checkout_service.place_order(customer, request.get("promo"),
                                                   request.get("card", "tok_visa"),
                                                   request.get("key") or None)
    except CheckoutError as e:
        return Response.redirect("/cart", "Checkout stopped: " + str(e), request)
    request.session.pop("checkout_key", None)
    order = result["order"]
    self.recommender.fit()
    return Response.redirect(f"/orders/{order.order_id}",
                             f"Order {order.order_id}: {order.status}.", request)
```

The screenshots below were taken from the running application (python main.py serve) with the seeded data. The catalogue reads price and availability from the same records as the checkout; the product page combines the catalogue with the two AI sections of Chapter 3.




Figure 31. Catalogue page with the multimodal search box (UC04, UC05)




Figure 32. Product page with AI review insights and recommendations (UC06, UC33, UC34)




Figure 33. Voice search result with scores and the processing trace (UC05)




Figure 34. Checkout with promotion WELCOME10, shipping and simulated payment options (UC08, UC31, UC32)




Figure 35. Order tracking: status timeline from order history and carrier milestones (UC11)




Figure 36. Order question "where is my latest order" answered from the customer's own orders (AI-R2)




Figure 37. Sales staff processing queue (UC19)




Figure 38. Warehouse inventory with low-stock rows and event form (UC20, UC24)




Figure 39. Review moderation queue: the spam review held by the AI noise filter (UC18, AI-R5)




Figure 40. Management dashboard computed from operational records (UC25-UC28)

5.7. AI Components in Code

The search keeps the Assignment 06 classes; the change is in where the data comes from. SearchService now reads ProductDAO and InventoryDAO, so a result shows the same available quantity as the product page, and order questions go through OrderDAO.find_by_customer, so the privacy rule is structural:

```
def search_orders(self, query):
    """Order questions only ever see the orders of the customer in the session (FR11)."""
    own = self.orders.find_by_customer(query["customer_id"])
    if query.get("order_id"):
        return [o for o in own if o.order_id == query["order_id"]]
    if query.get("latest"):
        return own[:1]
    return own
```

The review analyser's core is the clause classifier with the negation window of Section 3.6:

```
def classify_clause(self, clause):
    """Return (aspects, polarity) for one clause; polarity is +1, -1 or 0."""
    tokens = re.findall(r"[a-z']+", clause)
    aspects = [a for a, words in ASPECTS.items()
               if any(w in tokens or (" " in w and w in clause) for w in words)]
    score = 0
    for i, t in enumerate(tokens):
        value = 1 if t in POSITIVE else -1 if t in NEGATIVE else 0
        if value and any(n in tokens[max(0, i - 3):i] for n in NEGATIONS):
```

```
            value = -value
        score += value
    return aspects, (score > 0) - (score < 0)
```

The composition root wires the AI components like every other service. The last lines show the design decision of Section 3.5: the encoder is passed into the data layer instead of being imported by it.

```
def _rebuild_index(shop):
    """The encoder is passed into the data layer, which never imports the AI layer."""
    shop.search.vector_index = VectorIndex.build(shop.storage, shop.dao.products.list_products(),
                                                 shop.image.encode)
    return shop.search.vector_index
```

5.8. Running the Application

Table 53. Commands

Command	What it does
pip install -r requirements.txt	numpy, Pillow, pytest
python main.py seed	Create data/abc_shop.db: 16 products, 4 customers, 4 staff, 16 orders, 14 reviews
python main.py serve --port 8000	Run the web application on http://localhost:8000 (demo accounts on the login page)
python main.py demo	End-to-end scenario printed step by step (in-memory database)
python main.py search --voice "find running shoes"	One search; also --text, --image FILE, --text + --image
python evaluate.py	Search, review-insight and recommender evaluation
python -m pytest -q	All 40 tests

The seed is not inserted into the tables directly. seed.py plays one month of history through the real services with a simulated clock: customers fill carts and check out, payments succeed, fail or time out, sales staff process and hold orders, the warehouse packs, the carrier sends milestones and customers review delivered products. Every row in the demo database was therefore produced by the same rules that the tests check. The demo then continues with a new checkout, a repeated submission, a declined payment and a full fulfilment path including duplicate and out-of-order carrier messages:

```
$ python main.py demo   (sections 2-8)
--- 2. UC07 + UC08 checkout with promotion WELCOME10 ---
  cart: [('P12', 1), ('P09', 2)]  subtotal 160  discount 16  shipping 0  total 144
  CheckoutService.place_order -> O017 Paid/Confirmed (payment Succeeded)
  P12 available 7 -> 6 (reserved for O017)
  same submission again -> O017, duplicate=True (no second order/charge)

--- 3. Payment declined: order fails, reservation released, cart kept ---
  O018: Payment Failed; P10 available 5; cart still has ['P10']

--- 4. UC19 -> UC21 -> UC22 -> UC23: fulfilment of O017 ---
  processed by S01, packed SH011, carrier ref VNPF21E3D57B
  milestone 1 PICKED_UP  -> accepted
  milestone 2 IN_TRANSIT -> accepted
  milestone 2 IN_TRANSIT -> ignored (duplicate/older)
  milestone 1 PICKED_UP  -> ignored (duplicate/older)
  milestone 3 DELIVERED  -> accepted
  UC11 Track Order -> Delivered, 9 timeline entries

--- 5. Order questions are limited to the customer's own orders ---
  input (text): 'where is my latest order'
  QueryService -> order query (order_id=None, latest=True, customer=C001)
  Order: O018  Status: Payment Failed  Total: 150  Date: 2026-10-19
  input (text): 'find my order O002'
  QueryService -> order query (order_id=O002, latest=False, customer=C001)
  no order of this customer matches

--- 6. AI review insights for P01 Nike Running Shoes ---
  4 reviews used, 0 skipped -> Mostly positive
  quality   +4 -0  positive share 1.00
  price     +1 -0  positive share 1.00
  delivery  +2 -1  positive share 0.67
  waiting for moderation: [('R012', 'Click www.free-money-now.biz f')]

--- 7. Recommendations ---
  similar to P01: P12 Red Running Shoes      score 0.378 (bought together 0x)
  similar to P01: P03 Black Leather Bag      score 0.359 (bought together 1x)
  similar to P01: P07 Black Cotton T-Shirt   score 0.355 (bought together 1x)
  for C001:       P02 Adidas Running Shoes   score 0.981
  for C001:       P14 Red Baseball Cap       score 0.667
  for C001:       P13 White Cotton T-Shirt   score 0.665

--- 8. UC25 management dashboard ---
  orders 18  revenue 1537  average 118.23  exceptions 2  low stock ['P05', 'P15']
```

Figure 41. Output of main.py demo, sections 2-8: checkout, idempotency, failure, fulfilment, AI and dashboard

5.9. Testing

The tests were written from the use case specifications and the design rules, so a failing test names the requirement that is broken. The architecture test turns the package diagram into code: it parses every module with Python's ast module and fails if a layer imports a layer it must not use.

```
FORBIDDEN = {
    "model": {"dao", "service", "ai", "controller", "view", "shop"},
    "dao": {"service", "ai", "controller", "view", "shop"},
    "service": {"controller", "view", "shop", "ai"},
    "ai": {"controller", "view", "shop", "service"},
    "controller": {"dao", "shop"},
    "view": {"dao", "service", "ai", "shop", "controller"},
}

@pytest.mark.parametrize("layer", FORBIDDEN)
def test_dependencies_only_point_downwards(layer):
    for module in modules_of(layer):
        illegal = imported_packages(module) & FORBIDDEN[layer]
        assert not illegal, f"{os.path.relpath(module, ROOT)} imports {illegal}"
```

The payment test is the clearest example of a requirement becoming a test. NFR07 says that a replay must not duplicate a state change, and UC09 lists forged results (E2), mismatching amounts (E1) and duplicate callbacks (A3). The test sends all of them to the same payment attempt and checks that the order became Paid/Confirmed exactly once:

```
def test_payment_callbacks_are_verified_and_idempotent(shop, users):
    shop.cart.add_item("C001", "P10", 1)
    order = shop.checkout.place_order(users["C001"], "", "tok_timeout")["order"]
    attempt = shop.dao.payments.for_order(order.order_id)[0]
    good = {"attempt_ref": attempt.attempt_ref, "status": "SUCCEEDED", "provider_ref": "PSP-X",
            "amount": attempt.amount, "currency": "USD"}
    forged = dict(good, signature="0000")
    assert shop.payment.handle_result(forged) == "Rejected"                        # E2
    wrong_amount = dict(good, amount=1.0)
    wrong_amount["signature"] = sign(attempt.attempt_ref, "SUCCEEDED", "PSP-X", 1.0, "USD")
    assert shop.payment.handle_result(wrong_amount) == "Quarantined"               # E1
    assert shop.dao.orders.get_order(order.order_id).status == "Payment Pending"
    good["signature"] = sign(attempt.attempt_ref, "SUCCEEDED", "PSP-X", attempt.amount, "USD")
    assert shop.payment.handle_result(good) == "Succeeded"
    assert shop.payment.handle_result(good) == "Succeeded"                         # A3 duplicate
    history = shop.dao.orders.get_order(order.order_id).history
    assert [h.status for h in history].count("Paid/Confirmed") == 1
```

Table 54. Test modules

Module	Tests	What is checked
test_model.py	5	Cart totals, order transitions, stock rules, promotion validity, milestone ordering
test_checkout.py	9	UC08 main flow and A2, A4, A5, A6, A7, price change, address; UC09 E1, E2, A3
test_operations.py	8	Tracking ownership, cancellation and refund, processing roles, fulfilment path, inventory idempotency, replenishment, review rules, reports
test_ai.py	7	Text/voice/image/multimodal search, synonyms, stock-aware ranking, order privacy, review negation and noise, recommender rules
test_web.py	4	Pages through WSGI: catalogue, search trace, a customer buying through the web, role enforcement
test_architecture.py	7	Layer rule for six packages (parametrised) and no storage import in services

```
$ python -m pytest -v
test_ai.py::test_text_voice_and_price_filter PASSED
test_ai.py::test_synonyms_map_sneakers_to_shoes PASSED
test_ai.py::test_image_and_multimodal_search PASSED
test_ai.py::test_ranking_is_stock_aware PASSED
test_ai.py::test_order_questions_only_see_own_orders PASSED
test_ai.py::test_review_insights_handle_negation_and_noise PASSED
test_ai.py::test_recommender_never_suggests_out_of_stock_or_bought_items PASSED
test_architecture.py::test_dependencies_only_point_downwards[model] PASSED
test_architecture.py::test_dependencies_only_point_downwards[dao] PASSED
test_architecture.py::test_dependencies_only_point_downwards[service] PASSED
test_architecture.py::test_dependencies_only_point_downwards[ai] PASSED
test_architecture.py::test_dependencies_only_point_downwards[controller] PASSED
test_architecture.py::test_dependencies_only_point_downwards[view] PASSED
test_architecture.py::test_services_never_import_a_storage_implementation PASSED
test_checkout.py::test_successful_checkout_reserves_stock_pays_and_clears_cart PASSED
test_checkout.py::test_promotion_and_shipping_are_part_of_the_authoritative_total PASSED
test_checkout.py::test_repeated_submission_returns_the_same_order PASSED
test_checkout.py::test_declined_payment_releases_reservation_and_keeps_cart PASSED
test_checkout.py::test_timeout_keeps_order_pending_and_reserved PASSED
test_checkout.py::test_insufficient_stock_stops_checkout_without_side_effects PASSED
test_checkout.py::test_changed_price_is_reported_before_payment PASSED
test_checkout.py::test_incomplete_address_is_rejected PASSED
test_checkout.py::test_payment_callbacks_are_verified_and_idempotent PASSED
test_model.py::test_cart_adds_to_an_existing_line_and_totals_the_lines PASSED
test_model.py::test_order_follows_only_the_allowed_transitions PASSED
test_model.py::test_stock_level_keeps_available_equal_physical_minus_reserved PASSED
test_model.py::test_promotion_checks_dates_and_minimum_total PASSED
test_model.py::test_shipment_ignores_duplicate_and_older_milestones PASSED
test_operations.py::test_customer_only_tracks_own_orders PASSED
test_operations.py::test_cancel_releases_the_reservation_and_notes_a_refund PASSED
test_operations.py::test_processing_needs_staff_role_and_a_paid_order PASSED
test_operations.py::test_full_fulfilment_path_and_milestones PASSED
test_operations.py::test_inventory_events_are_idempotent_and_never_negative PASSED
test_operations.py::test_low_stock_and_replenishment PASSED
test_operations.py::test_reviews_only_for_delivered_purchases_and_spam_waits_for_moderation PASSED
test_operations.py::test_reports_are_for_managers_and_match_the_orders PASSED
test_web.py::test_catalogue_and_product_page_with_ai_sections PASSED
test_web.py::test_search_shows_the_processing_steps PASSED
test_web.py::test_customer_buys_through_the_web PASSED
test_web.py::test_roles_are_enforced_on_screens PASSED
============================== 40 passed in 13.46s ==============================
```

Figure 42. Output of pytest: 40 tests passed

5.10. Traceability from Requirements to Code and Tests

Table 55. From requirement to design element, code and test

Requirement	Design element	Code	Checked by
FR08 validate before ordering	CartService.validate_cart (UC29-30)	service/cart_service.py	test_changed_price_is_reported_before_payment, test_insufficient_stock_...
FR09 + A7 one order per submission	idempotency key, UNIQUE constraint	checkout_service.py, schema.sql	test_repeated_submission_returns_the_same_order
FR10, NFR07 payment once	PaymentService.handle_result	service/payment_service.py	test_payment_callbacks_are_verified_and_idempotent
FR11-12, NFR05 own orders only	OrderService.own_order, search_orders	order_service.py, search_service.py	test_customer_only_tracks_own_orders, test_order_questions_only_see_own_orders
FR18 valid transitions	Order.change_status, TRANSITIONS	model/order.py	test_order_follows_only_the_allowed_transitions
FR19 stock never negative	StockLevel.apply, CHECK constraints	model/inventory.py, schema.sql	test_inventory_events_are_idempotent_and_never_negative
FR21 milestones, no regression	Shipment.add_milestone	model/shipment.py	test_shipment_ignores_duplicate_and_older_milestones
FR14, AI-R5 reviews	ReviewService.submit + insight noise filter	review_service.py	test_reviews_only_for_delivered_purchases_and_spam_...
NFR09 layers	Package diagram PKG01	all packages	test_dependencies_only_point_downwards

5.11. What Writing the Code Changed in the Models

Checking the code against the diagrams found four real mismatches. None produced a wrong result in the demo, which is exactly why they are dangerous: they appear only when someone later changes the system.

Table 56. Mismatches found while implementing

Mismatch	How it was found	Fix
Two controllers read DAOs through a service attribute (order_service.orders.find_by_status)	Reading the controller imports against PKG01	ShipmentService.ready_list and a shipment id in the redirect; no DAO access remains in controllers
The image index was built before the catalogue was loaded, so image search returned nothing	First run of the demo (0 candidates)	seed.py rebuilds the index after loading the catalogue; composition root offers rebuild_index()
The state machine did not allow Delivery Failed -> Delivered	Writing the carrier milestone handler	Transition added to ST01 and to TRANSITIONS; unexpected milestones are audited instead of crashing
The recommender test counted cancelled orders as purchases	Failing test on the seeded data	The test now uses the same definition as the service and the analysis: cancelled and failed orders are not purchases

5.12. Development History

The code was developed in small commits over four days, in the order of the layers: model, DAO, services, AI, presentation, tests, models and report. The history is public in the repository.

Table 57. Commit history

Date and time	Commit
2026-10-18 09:42	Initial project structure
2026-10-18 10:15	Add customer, product and cart model classes
2026-10-18 14:37	Add order state machine, payment, shipment and review models
2026-10-18 16:02	Add event-based inventory model
2026-10-18 21:18	Add SQLite schema and database helper with nested transactions
2026-10-19 08:55	Add DAO interfaces and SQLite implementations
2026-10-19 10:41	Add auth, catalogue and cart services
2026-10-19 13:26	Add inventory service and checkout with idempotency key
2026-10-19 15:50	Add payment service and simulated provider gateways
2026-10-19 19:34	Add order processing and shipment services
2026-10-19 22:07	Add review moderation and management reports
2026-10-20 09:12	Port multimodal search from assignment 06
2026-10-20 11:03	Add review insight analyser and recommender
2026-10-20 14:22	Add composition root and seeded October history
2026-10-20 16:48	Add web controllers and router
2026-10-20 20:31	Add HTML views and stylesheet
2026-10-20 22:15	Add main entry point with end-to-end demo
2026-10-21 08:47	Add model, checkout and operation tests
2026-10-21 10:12	Add AI, web and architecture tests
2026-10-21 11:39	Add evaluation script and labelled reviews
2026-10-21 14:05	Add Visual Paradigm project and exported diagrams
2026-10-21 16:26	Add demo results and web screenshots
2026-10-21 20:44	Add essay report
2026-10-21 22:31	Update README with run instructions
2026-10-21 22:52	Relayout diagrams with orthogonal connectors and split use cases by package

5.13. Limitations and Future Work

- **Scope.** Screens exist for the transaction path; profile editing (UC03), category and customer management (UC15, UC17) are implemented in services but not as pages.
- **Providers.** Payment and carrier are simulated behind PaymentGateway and ShippingGateway; a real integration needs webhooks over HTTPS and a reconciliation job for Payment Pending orders.
- **AI.** Speech is simulated, the image encoder only sees colour and shape, and the review analyser is a lexicon; Section 3.12 lists the production replacements behind the same interfaces.
- **Non-functional requirements.** NFR01-03 and NFR12 (performance, availability, load) were not measured; the prototype runs on one process with SQLite.
- **Data.** 16 products and synthetic images; the AI numbers do not predict accuracy on a real catalogue.

5.14. Chapter Summary

The design of Chapter 4 runs as 3581 lines of Python in the same six packages, with a web interface, a SQLite database and the three AI components. The use case flows of Chapter 1 appear as comments and tests, the state machine and the integrity rules of Chapter 2 as code and constraints, and the package diagram as an architecture test. All 40 tests pass, and the demo reproduces every number quoted in the essay.

CONCLUSION

This essay followed ABC Online Shop from its business problem to a running program. Requirement determination turned fragmented and delayed information into 7 problems, 14 needs, 24 functional and 12 non-functional requirements and 32 use cases, plus 9 requirements for AI extensions. Analysis refined them with activity, data-flow, sequence, class, state and data models that agree with each other. The AI chapter treated multimodal search, review insights and recommendation as ordinary requirements with data, risks, fallbacks and measurements. The design applied the four transformation steps to obtain a layered MVC architecture with services and data access objects, and the code implements it with 40 passing tests.

The main lesson is about the joints between the activities. The rules that survived all five chapters were the ones written precisely at the start: status from recorded events, unique references for every external exchange, stock that can never become negative, customers who only see their own orders. Each of them is a sentence in Chapter 1, a guard or constraint in Chapter 2, a method or a unique key in Chapter 4 and a test in Chapter 5. Where a rule was vague, as with the definition of a purchase for recommendations, the vagueness came back as a failing test. AI did not change this lesson; it confirmed it, because an AI component is only as good as the operational data and the rules around it.

Natural next steps are a real payment and carrier integration with reconciliation, measurement of the performance requirements, and replacing the prototype AI components with Whisper, CLIP and a fine-tuned PhoBERT behind the interfaces that are already in place.

Table 58. Submitted files

File / folder	Content
tieuluan_V1_04_049_KHANHBQ.pdf	This essay
TieuLuan_KHANHBQ.vpp	Visual Paradigm project with the 27 diagrams of the essay
diagrams/	PNG export of every diagram
abc_shop/	Source code, data, tests, README
demo_results/	Demo, evaluation and test output; web screenshots

Project repository: https://github.com/qkhanhbe/ABC-Online-Shop-Information-System

REFERENCES

[1] Tran Dinh Que, *Information System Analysis and Design*, lecture slides and assignment briefs 01-06, Posts and Telecommunications Institute of Technology, 2026.

[2] Tran Dinh Que, *Integrating AI in E-Commerce: Analysis Phase*, course material, PTIT, 2026.

[3] J. W. Satzinger, R. B. Jackson and S. D. Burd, *Systems Analysis and Design in a Changing World*, 7th ed., Cengage Learning, 2016.

[4] A. Dennis, B. H. Wixom and D. Tegarden, *Systems Analysis and Design: An Object-Oriented Approach with UML*, 5th ed., Wiley, 2015.

[5] K. C. Laudon and J. P. Laudon, *Management Information Systems: Managing the Digital Firm*, 17th ed., Pearson, 2022.

[6] M. Fowler, *Patterns of Enterprise Application Architecture*, Addison-Wesley, 2002.

[7] Oracle, *Core J2EE Patterns: Data Access Object*, 2002.

[8] A. Radford et al., "Learning Transferable Visual Models From Natural Language Supervision (CLIP)", ICML, 2021.

[9] A. Radford et al., "Robust Speech Recognition via Large-Scale Weak Supervision (Whisper)", 2022.

[10] D. Q. Nguyen and A. T. Nguyen, "PhoBERT: Pre-trained language models for Vietnamese", Findings of EMNLP, 2020.

[11] M. Pontiki et al., "SemEval-2014 Task 4: Aspect Based Sentiment Analysis", SemEval, 2014.

[12] Visual Paradigm, *Visual Paradigm Open API (Plug-in) Developer's Guide*, version 18.

[13] Be Quoc Khanh, Assignments 01, 02, 03, 06 and Test 01 of this course, 2026.