

CS2110 Fall 2015

Homework 6

This assignment is due by:

Day: September 30, 2015

Time: 11:54:59pm

Rules and Regulations

Academic Misconduct

Academic misconduct is taken very seriously in this class. Homework assignments are collaborative. However, each of these assignments should be coded by you and only you. This means you may not copy code from your peers, someone who has already taken this course, or from the Internet. You may work with others **who are enrolled in the course**, but each student should be turning in their own version of the assignment. Be very careful when supplying your work to a classmate that promises just to look at it. If he/she turns it in as his own you will both be charged.

We will be using automated code analysis and comparison tools to enforce these rules. **If you are caught you will receive a zero and will be reported to Dean of Students.**

Submission Guidelines

1. You are responsible for turning in assignments on time. This includes allowing for unforeseen circumstances. If you have an emergency let us know **IN ADVANCE** of the due time supplying documentation (i.e. note from the dean, doctor's note, etc). Extensions will only be granted to those who contact us in advance of the deadline and no extensions will be made after the due date.
2. You are also responsible for ensuring that what you turned in is what you meant to turn in. After submitting you should be sure to download your submission into a brand new

folder and test if it works. No excuses if you submit the wrong files, what you turn in is what we grade. In addition, your assignment must be turned in via T-Square. When you submit the assignment you should get an email from T-Square telling you that you submitted the assignment. If you do not get this email that means that you did not complete the submission process correctly. Under no circumstances whatsoever we will accept any email submission of an assignment. Note: if you were granted an extension you will still turn in the assignment over T-Square.

3. There is a 6-hour grace period added to all assignments. You may submit your assignment without penalty up until 11:55PM, or with 25% penalty up until 5:55AM. So *what you should take from this is not to start assignments on the last day and plan to submit right at 11:54AM*. You alone are responsible for submitting your homework before the grace period begins or ends; neither T-Square, nor your flaky internet are to blame if you are unable to submit because you banked on your computer working up until 11:54PM. The penalty for submitting during the grace period (25%) or after (no credit) is non-negotiable.

General Rules

1. Starting with the assembly homeworks, Any code you write (if any) must be clearly commented and the comments must be meaningful. You should comment your code in terms of the algorithm you are implementing we all know what the line of code does.
2. Although you may ask TAs for clarification, you are ultimately responsible for what you submit. This means that (in the case of demos) you should come prepared to explain to the TA how any piece of code you submitted works, even if you copied it from the book or read about it on the internet.
3. Please read the assignment in its entirety before asking questions.
4. Please start assignments early, and ask for help early. Do not email us the night the assignment is due with questions.
5. If you find any problems with the assignment it would be greatly appreciated if you reported them to the author (which can be found at the top of the assignment). Announcements will be posted if the assignment changes.

Submission Conventions

1. All files you submit for assignments in this course should have your name at the top of the file as a comment for any source code file, and somewhere in the file, near the top, for other files unless otherwise noted.
2. When preparing your submission you may either submit the files individually to T-Square or you may submit an archive (zip or tar.gz only please) of the files (preferred). You can create an archive by right clicking on files and selecting the appropriate compress option on your system.
3. If you choose to submit an archive please don't zip up a folder with the files, only submit an archive of the files we want. (See **Deliverables**).

4. Do not submit compiled files that is .class files for Java code and .o files for C code. Only submit the files we ask for in the assignment.
5. Do not submit links to files. We will not grade assignments submitted this way as it is easy to change the files after the submission period ends.

Syllabus Excerpt on Academic Misconduct

Academic misconduct is taken very seriously in this class.

Quizzes, timed labs and the final examination are individual work.

Homework assignments are collaborative, In addition many if not all homework assignments will be evaluated via demo or code review. During this evaluation, you will be expected to be able to explain every aspect of your submission. Homework assignments will also be examined using electronic computer programs to find evidence of unauthorized collaboration.

What is unauthorized collaboration? Each individual programming assignment should be coded by you. You may work with others, but each student should be turning in their own version of the assignment. Submissions that are essentially identical will receive a zero and will be sent to the Dean of Students' Office of Academic Integrity. Submissions that are copies that have been superficially modified to conceal that they are copies are also considered unauthorized collaboration.

You are expressly forbidden to supply a copy of your homework to another student via electronic means. If you supply an electronic copy of your homework to another student and they are charged with copying you will also be charged. This includes storing your code on any site which would allow other parties to obtain your code such as but not limited to public repositories, etc.

Objectives

The goal of this assignment is to help you become comfortable coding in the LC-3 assembly language. This will involve the creating small programs, reading input from the keyboard, printing to the console, and converting from high-level code to assembly.

Overview

A Few Requirements

1. Your code must assemble with NO WARNINGS OR ERRORS. To assemble your program, open the file with complx. It will complain if there are any issues. **If your code does not assemble you WILL get a zero for that file.**
2. Comment your code! This is especially important in assembly, because it's much harder to interpret what is happening later, and you'll be glad left notes to let you know sections of code or certain instructions are contributing to the code. Comment things like what registers are being used for and what not so intuitive lines of code are actually doing. To comment code in LC-3 assembly just type a semi-colon (;), and the rest of that line will be a comment. Avoid stating the obvious in your comments, it doesn't help in understanding what the code is doing.

Good Comment

```
ADD R3, R3, -1      ;counter--  
BRp LOOP           ;if counter == 0 don't loop again
```

Bad Comment

```
ADD R3, R3, 1       ;Decrement R3  
BRp LOOP           ;Branch to LOOP if positive
```

3. **DO NOT assume that ANYTHING in the LC-3 is already zero.** Treat the machine as if your program was loaded into a machine with random values stored in the memory and register file.
4. Following from 3. You can randomize memory by using the menu option State → Randomize. And then load your program by saying File → Load Over
5. You may NOT use the instructions JMP, JSR, or JSRR. Do not write any TRAPs.
6. Do NOT execute any data as if it were an instruction (meaning you should put .fills after halt).
7. Do not add any comments beginning with @plugin or change any comments of this kind.
8. Test your assembly. Don't just assume it works and turn it in.

Assembly Overview

For this assignment, you will be writing 4 assembly programs. The purpose of this assignment is to get you familiar and more comfortable with writing low-level assembly code. For each part of this homework, we will supply you with pseudo-code, and you must write the equivalent assembly program. Please make your code as similar to the pseudo-code as you can! You've been given framework files for this assignment, but I'll tell you a little bit about how the assembly files in this class look.

```
.orig x3000
    LEA R0, HW      ;Load the address of the string
    PUTS            ;Output the string
    HALT            ;Stop Running
    HW .stringz "Hello World.\n"
.end
```

This is a simple assembly program that prints "Hello World." and a new line to the console.

`;` denotes a comment. You don't need a semi-colon after every line, only before comments.

`.orig` is a pseudo-op. Pseudo-ops are special instructions for the assembler that are not actually assembly instructions. `.orig x3000` tells the assembler to place this block of code at x3000, which is where the LC-3 starts code execution. Therefore "LEA R0, HW" is at address x3000, "PUTS" is at address x3001, etc.

Next is your assembly program. You've seen this before. PUTS is just a pseudonym for a TRAP that prints a string whose address is stored in R0, and HALT is a TRAP that stops the LC-3.

`.stringz` is another pseudo-op that stores the following string at that set of memory locations, followed by a zero (That's what the 'z' is for). For example, 'H' is stored at x3003, 'e' is stored at x3004, etc.

`.end` tells the assembler where to stop reading code for the current code block. Every `.orig` statement must have a corresponding `.end` statement.

Other pseudo-ops you should know are:

`.fill [value]` - put the given value at that memory location (`.fill x6000`, `.fill 7`, etc).

`.blkw [n]` - reserve the next n memory locations.

After writing your assembly code, you can test it using Complx. Complx is a full featured LC-3 simulator, and we recommend running your code in the following fashion:

1. Go to the “State” menu and click on “Randomize”. This randomly assigns values to every memory location and register, and prevents you from assuming values will be initialized to 0.
2. Go to the “File” menu, select “Load Over” and browse for your assembly file. This will load your code over the randomized memory. You will see your code load in the main window.
3. From here, you can run your code. Click the “Run” button to run your code automatically until a HALT instruction or breakpoint is hit. Click “Step” to execute one instruction at a time. Click “Next Line” to fast-forward through subroutines. Notice you can also step back.

One more thing, it is very important that you use Appendix A in the book to your advantage. Make sure you know what the instruction before you use it. Think about how you can set a register with a specific number, how can you load a value from a label, how can you compare if two numbers are equal, and so on.

Take a look at this instruction: **LD R2, 5**

What exactly is this instruction doing? Is it loading the number 5 into R2? Remember that the bits preceding the destination register are based on the PCOFFSET9, this is not an immediate value, you are merely loading data from an address location.

Part 1 – deMorgan's Law (demorgans.asm)

In LC-3 assembly you will notice that there is no OR operation. But that can easily be fixed by using deMorgan's Law. Your task is to store the value $A \mid B$ in your assembly program.

deMorgan's law: $\sim(\sim A \ \& \ \sim B) == (A \mid B)$. **Make sure you test your solution with different values.**

Here's the pseudo-code:

```
/* A and B are the parameters, answer is the return  
A = !A;  
B = !B;  
answer = A & B;  
answer = !answer;  
return answer;
```

A and B are labels for a .fill in the template file. You will need to load the values A and B into a register.

ANSWER is a label for another .fill in the template file. You will need to store the value you get for answer at the address labeled ANSWER.

A and B will be any integer in the range -32767 to 32767, inclusive.

Part 2 – Array Sum(sum.asm)

Write a program that sums up the array, you should then check if your sum is negative. If your result is negative then return the absolute value of it. So if your sum happens to be -42, you should return 42. If your sum is 42 then return that.

Here's the pseudo-code:

```
/* length and array are parameters, answer is the return value */

int sum = 0;
for(int k = 0; k < length; k++)
{
    sum += array[k];
}
if(sum < 0)
    return -sum;
else
    return sum;
```

Again, length and array are supplied as .fill'd values, and you must store your answer in ANSWER.

ARRAY is any valid address, LENGTH is in the range 0 to 100, and numbers in the array will be within the range of -256 to 255.

Part 3 – Christmas(christmas.asm)

We here in CS 2110 love all holidays, especially Christmas. So much so, that it's on our minds even in the summer time! For this part, we're going to sing a little carol. Write a program that prints out lines of the Twelve Days of Christmas to the Complx console according to the DAY value. **You are only supposed to print out 1 verse, not the whole carol.** Here is the pseudo-code:

```
void christmas(int day)
{
    printf("On the ");
    printf(grammar_arr[day - 1]);
    printf(" of Christmas my true love gave to me:\n");
    while(day > 0)
    {
        day--;
        printf(message_arr[day]);
    }
    return;
}
```

Here, GRAMMAR ARR and MESSAGE ARR are arrays with pointers to different .stringz values. GRAMMAR ARR contains the pointers to the written day strings (e.g. first, second, third) and MESSAGE ARR contains pointers to the corresponding verses. These values are all supplied with the template file.

For example, if the value of DAY is 1 then the output should be:

*On the first day of Christmas my true love gave to me:
A partridge in a pear tree*

The higher the day, the more verses of the carol are printed. DAY is a number between 1 and 12, inclusive.

Hint: Because GRAMMAR ARR and MESSAGE ARR are arrays containing pointers to strings, you cannot simply offset the array index by the day and print what is there (since what is there is a pointer). It's a step in the right direction though.

Part 4 – Sorting (sort.asm)

Write a program that sorts an array location at address ARRAY of length LENGTH in **ascending order**.

You may use whichever sorting method you prefer, but here is pseudocode for bubble sort which is recommended that you go by.

Here's the pseudo-code:

```
for (int k = 0; k < LENGTH; k++) {  
    int isSorted = 1;  
    for (int i = 1; i < LENGTH - k; i++) {  
        if (array[i] < array[i - 1]) {  
            int temp = array[i];  
            array[i] = array[i - 1];  
            array[i - 1] = temp;  
            isSorted = 0;  
        }  
    }  
    if (isSorted) break;  
}
```

Here, ARRAY and LENGTH are supplied as .fill'd values. The actual array will be defined in another .orig / .end block, as seen in the template file. You should change the array to test your code.

Helpful hint: press ctrl+v to open up a new view, then ctrl+g to go to x6000. Now you can watch your array change as you debug your instructions!

ARRAY is any valid address and LENGTH is in the range 0 to 100, numbers in the array will be within the range of -256 to 255.

Deliverables

Remember to put your name at the top of EACH file you submit.

The files should be named exactly as given.

demorgans.asm
sum.asm
christmas.asm
sort.asm

