

## LEARNING AND REASONING WITH CONSTRAINTS



*Marco Gori*  
University of Siena (Italy)

MSc DSAI 2021

## OUTLINE

- Environment, machines, and constraints
- Bridging logic and real-valued constraints
- Constraint consistency and parsimony
- Data structure, constraints, and GNN
- Learning of constraints

MSc DSAI 2021


## ENVIRONMENTS, MACHINES, AND CONSTRAINTS



MSc DSAI 2021

## Supervised Learning

architectural and environmental constraints



architectural constraints


"hard"

$$x_{\kappa 3} - \sigma(w_{31}x_{\kappa 1} + w_{32}x_{\kappa 2} + b_3) = 0$$
$$x_{\kappa 4} - \sigma(w_{41}x_{\kappa 1} + w_{42}x_{\kappa 2} + b_4) = 0 \quad \kappa = 1, 2, 3, 4$$
$$x_{\kappa 5} - \sigma(w_{53}x_{\kappa 3} + w_{54}x_{\kappa 4} + b_5) = 0$$

MSc DSAI 2021

## Enforcing Consistencies


$f_{\omega h} : \mathcal{W} \rightarrow \mathcal{H} : h \mapsto \omega(h),$   
 $f_{ah} : \mathcal{W} \rightarrow \mathcal{A} : h \mapsto a(h),$   
 $f_{\omega a} : \mathcal{A} \rightarrow \mathcal{W} : a \mapsto \omega(a),$



This functional equation is imposing the circulation of coherence. Since the functions are linear, this constraint can be converted to  $w_{\omega h}h + b_{\omega h} = w_{\omega a}w_{ah}h + (w_{ah}b_{ah} + b_{\omega a})$ . The equivalence  $\forall h \in \mathbb{R}^+$  yields

$$w_{\omega a}w_{ah} - w_{\omega h} = 0,$$
$$w_{ah}b_{ah} + b_{\omega a} - b_{\omega h} = 0.$$

## Patterns, Labels, and Individuals



What about learning and inference with individuals?

## Inference in Formal Logic

only labels are involved!

```
Domain(label="People")
Individual(label="Marco", "People")
Individual(label="Giuseppe", "People")
Individual(label="Michelangelo", "People")
Individual(label="Francesco", "People")
Individual(label="Franco", "People")
Individual(label="Andrea", "People")
```

```
Predicate(label="fatherOf", ("People", "People"))
Predicate(label="grandFatherOf", ("People", "People"))
Predicate(label="eq", ("People", "People"), function=eq)
```

```
Constraint("fatherOf(Marco, Giuseppe)")
Constraint("fatherOf(Giuseppe, Michelangelo)")
Constraint("fatherOf(Giuseppe, Francesco)")
Constraint("fatherOf(Franco, Andrea)")
```

```
Constraint("forall x: not fatherOf(x,x)")
Constraint("forall x: not grandFatherOf(x,x)")
```

MSc DSAI 2021

## Inference in Formal Logic

```
Constraint("forall x: forall y: fatherOf(x,y) -> not fatherOf(y,x)")
Constraint("forall x: forall y: grandFatherOf(x,y)
-> not grandFatherOf(y,x)")
Constraint("forall x: forall y: fatherOf(x,y) -> not grandFatherOf(x,y)")
Constraint("forall x: forall y: grandFatherOf(x,y) -> not fatherOf(x,y)")
```

```
Constraint("forall x: forall y: forall z: fatherOf(x,z) and fatherOf(z,y) ->
grandFatherOf(x,y)")
Constraint("forall x: forall y: forall z: (fatherOf(x,y) and not eq(x,z)) ->
not fatherOf(z,y)")
```

MSc DSAI 2021

## Inference in Formal Logic

```
grandFatherOf("Marco", "Michelangelo")
grandFatherOf("Marco", "Francesco")

Constraint("forall x: forall y: forall z: grandFatherOf(x,z) and
fatherOf(y,z) -> fatherOf(x,y)")
```

MSc DSAI 2021

## Full Inference on Individuals $(X, x)$

from formal logic  
from neural nets  
consistency constraints


$(age_x, weight_x, height_x, age_y, weight_y, height_y)$

Complexity issues: the inference in the environment avoids massive exploration of the Boolean hypercube

MSc DSAI 2021



## BRIDGING LOGIC AND REAL-VALUED CONSTRAINTS



"There are finer fish in the sea that have ever been caught," Irish proverb

### Logic by Real Numbers

$$\forall x \quad a(x) \wedge b(x) \Rightarrow c(x)$$

$$\neg(a(x) \wedge b(x)) \vee c(x)$$

$$\neg\neg(\neg(a(x) \wedge b(x)) \wedge c(x))$$

$$\neg(a(x) \wedge b(x) \wedge \neg c(x))$$

$$\text{p-norm}$$

$$1 - [f_a(x) \cdot f_b(x) \cdot (1 - f_c(x))] = 1$$

$$f_a(x)f_b(x)(1 - f_c(x)) = 0$$

$$\text{general form } \forall x \quad \Phi(f(x)) = 0 \longrightarrow \Phi(x, f(x)) = 0$$

MSc DSAI 2021

## Logic by Real Numbers (con't)

$$\forall x \ a(x) \wedge b(x) \Rightarrow c(x)$$

$$\neg(a(x) \wedge b(x) \wedge \neg c(x))$$

*Gödel T-norm*

$$1 - \min \{f_a(x), f_b(x), 1 - f_c(x)\} = 1$$
$$\min \{f_a(x), f_b(x), 1 - f_c(x)\} = 0$$

MSc DSAI 2021

## CONSTRAINT CONSISTENCY AND PARSIMONY

“the simplest solution” compatible  
with the constraints



We use the Lagrangian  
optimization framework

MSc DSAI 2021

## Constraint-Based Learning

$$\phi(f(x)) = 0$$

given      task to be learned

everything revolves around this compositional structure  
Gori et al, Neural Computation 2015

## A New Communication Protocol

data + constraints

$\forall x \Phi(x, f(x)) = 0$  from constraints to  
consistency check


$$\sum_{\kappa \in U} \phi^2(x_\kappa, f(x_\kappa)) \text{ loss functions}$$

unsupervised data!

## A New Communication Protocol

data + constraints

- Supervised
- Unsupervised
- Semi-supervised




## Learning Under Constraint Consistency

$\text{hair}(x) \Rightarrow \text{mammal}(x)$   
 $\text{mammal}(x) \wedge \text{hoofs}(x) \Rightarrow \text{ungulate}(x)$   
 $\text{ungulate}(x) \wedge \text{white}(x) \wedge \text{blackstripes}(x) \Rightarrow \text{zebra}(x)$ .

$f_{\text{hair}}(x)(1 - f_{\text{mammal}}(x)) = 0$   
 $f_{\text{mammal}}(x)f_{\text{hoofs}}(x)(1 - f_{\text{ungulate}}(x)) = 0$   
 $f_{\text{ungulate}}(x)f_{\text{white}}(x)f_{\text{blackstripes}}(x)(1 - f_{\text{zebra}}(x)) = 0$ .

penalty functions  
perceptual space  
 $x$



## The Marriage of Parsimony Principle and Constraints

Constraints turn out to be loss functions

keep these loss functions as small as possible

$$f_{\text{hair}}(x)(1 - f_{\text{mammal}}(x)) = 0$$
$$f_{\text{mammal}}(x)f_{\text{hoofs}}(x)(1 - f_{\text{ungulate}}(x)) = 0$$
$$f_{\text{ungulate}}(x)f_{\text{white}}(x)f_{\text{blackstripes}}(x)(1 - f_{\text{zebra}}(x)) = 0.$$

penalty functions

perceptual space

$x$

Parsimony Principle

$$\|f\|$$

$$f_{\text{hair}}$$

$$f_{\text{hoofs}}$$

$$f_{\text{mammal}}$$

$$f_{\text{ungulate}}$$

$$f_{\text{white}}$$

$$f_{\text{blackstripes}}$$

$$f_{\text{zebra}}$$


## How to Represent the Tasks?

$$f_?$$

Primal space



Dual Space




...

## Parsimony Principle

smoothness of the tasks

$$\|f\|^2 := b_0 \int_{\mathcal{X}} f^2(x) dx + b_1 \int_{\mathcal{X}} \left( \frac{df}{dx} \right)^2 dx$$



## Semi-norm in Sobolev Spaces

$$P = \sum_{|\alpha| < m} a_\alpha D_x^\alpha = \sum_{|\alpha| < m} a_\alpha \left( \frac{\partial}{\partial x_1} + \dots + \frac{\partial}{\partial x_d} \right)^\alpha$$

$\infty$        $a_\alpha \in C^\infty$

under proper boundary conditions ...

$$P = \sum_{h=0}^m a_h \sum_{|\alpha|=h} \frac{h!}{\alpha!} \left( \frac{\partial}{\partial x} \right)^\alpha$$

$$P^* = \sum_{h=0}^m (-1)^h a_h \sum_{|\alpha|=h} \frac{h!}{\alpha!} \left( \frac{\partial}{\partial x} \right)^\alpha$$

Given  $P$  and  $\gamma_i > 0, \dots, i = 1, \dots, n$

$$E(f) = \|f\|_{P,\gamma} = \sum_{j=1}^n \gamma_j \langle P f_j, P f_j \rangle = \sum_{j=1}^n \gamma_j \langle f_j, P^* P f_j \rangle = \sum_{j=1}^n \gamma_j \langle f_j, L f_j \rangle$$

## Parsimony Principle

$\mathcal{F}_\phi$  admissible w.r.t the collection of constraints  $\mathcal{C}_\phi$

$f^* = \operatorname{argmin}_{f \in \mathcal{F}_\phi} \|f\|_{P,\gamma}$

strictly (hard)

partially (soft)

inference in the environment!

check of a “new” constraint

$$\forall x \quad \phi(x, f^*(x), Df^*(x)) = 0 ?$$

MSc DSAI 2021

## Representation of the Solution

hard constraints

$$\forall x \in \mathcal{X}_i \subset X : \phi_i(x, f(x)) = 0, i \in \mathbb{N}_m \quad \frac{D(\phi_1, \dots, \phi_m)}{D(f_1, \dots, f_m)} \neq 0$$

$$\mathcal{L}(f) = \|f\|_{P,\gamma}^2 + \sum_{i=1}^m \int_{\mathcal{X}} \lambda_i(x) \cdot \phi_i(x, f(x)) dx \quad \text{Lagrangian approach}$$

$$Lf(x) + \sum_{i=1}^m \lambda_i(x) \cdot \nabla_f \phi_i(x, f(x)) = 0 \quad \text{Euler-Lagrange equations}$$

$$Lg = \delta \quad \text{Green function}$$

$$\omega_i(\cdot) = -\lambda_i(\cdot) \nabla_f \phi_i(\cdot, f^*(\cdot)) \quad \text{reaction of the constraint}$$

support constraints

$$f^*(\cdot) = \sum_{i=1}^m g(\cdot) \otimes \omega_i(f^*(\cdot))$$

Fredholm eq. (II kind)  
“merging of two ideas ...”

MSc DSAI 2021

## Lagrange Multipliers and Probability Density

hard constraints

$$\forall x \in \mathcal{X} \subset X : \phi_i(x, f(x)) = 0, i \in \mathbb{N}_m$$

$$\mathcal{L}(f) = \|f\|_{P,\gamma}^2 + \sum_{i=1}^m \int_{\mathcal{X}} \lambda_i(x) \phi_i(x, f(x)) dx$$

soft constraints

$$\mathcal{L}(f) = \|f\|_{P,\gamma}^2 + C \sum_{i=1}^m \int_{\mathcal{X}} p_i(x) \phi_i(x, f(x)) dx$$

## Case studies

- Supervised learning
- Unsupervised, semi-supervised learning
- Learning and inference in the environment
- Full inference (formal + environment+based)
- Pattern generation
- ...

## Supervised learning: Lagrangian formulation

$$\begin{aligned}
 & \text{minimize} && \frac{1}{2} \sum_{i \in O} \sum_{j \in H_o} w_{ij}^2 + \sum_{\kappa=1}^{\ell} \sum_{j \in H} \mu_{\kappa j} |x_{\kappa j}| \\
 & \text{subject to} && x_{\kappa i} - \sigma \left( \sum_{j \in \text{pa}(i)} w_{ij} x_{\kappa j} \right) = 0, \quad i \in H \cup O, \quad \kappa = 1, \dots, \ell, \\
 & && 1 - x_{\kappa i} y_{\kappa i} \leq 0 \quad i \in O, \quad \kappa = 1, \dots, \ell
 \end{aligned}$$

$$\begin{aligned}
 L(w, x, \alpha, \beta) = & \frac{1}{2} \sum_{i \in O} \sum_{j \in H_o} w_{ij}^2 + \sum_{\kappa=1}^{\ell} \sum_m \left( \lambda_{\kappa m} |x_{\kappa m}| [m \in H] \right. \\
 & + \alpha_{\kappa m} \left( x_{\kappa m} - \sigma \left( \sum_{r \in \text{pa}(m)} w_{mr} x_{\kappa r} \right) \right) [m \in H \cup O] \\
 & \left. + \sum_{i \in O} \beta_{\kappa i} (1 - x_{\kappa i} y_{\kappa i})_+ \right),
 \end{aligned}$$

MSc DSAI 2021

architectural constraints

## “Saddle moves”: gradient descent/ascent

A more biologically plausible solution than Backpropagation

saddle points of the Lagrangian

$$\begin{aligned}
 w_{ij} &\leftarrow w_{ij} - \eta_w \partial_{w_{ij}} L && \text{learning (gradient descent)} \\
 x_{\kappa i} &\leftarrow x_{\kappa i} - \eta_x \partial_{x_{\kappa i}} L \\
 \lambda_{\kappa i} &\leftarrow \lambda_{\kappa i} + \eta_\lambda \partial_{\lambda_{\kappa i}} L && \text{focus of attention (gradient ascent)}
 \end{aligned}$$

related to BP delta error!

$$g_{\kappa i} = x_{\kappa i} - \sigma \left( \sum_{j \in \text{pa}(i)} w_{ij} x_{\kappa j} \right) = 0$$

saddle points of the Lagrangian

Lagrangian multipliers, straw and support neurons!

Network growing and constraint selection ...

MSc DSAI 2021

## Learning and Inference in the Environment

$$A = \{(x_1, x_2) \in R^2 : 0 \leq x_1 < 2, 0 \leq x_2 \leq 1\}$$

$$B = \{(x_1, x_2) \in R^2 : 1 \leq x_1 < 3, 0 \leq x_2 \leq 1\}$$

$$C = \{(x_1, x_2) \in R^2 : 1 \leq x_1 < 2, 0 \leq x_2 \leq 2\}$$


$$D = C \cup \{(x_1, x_2) \in R^2 : 0 \leq x_1 \leq 1, 1 \leq x_2 \leq 2\}$$

**“Knowledge Base”**

$$a_1(x) \wedge a_2(x) \Rightarrow a_3(x)$$

$$a_3(x) \Rightarrow a_4(x)$$

$$a_1(x) \vee a_2(x) \vee a_3(x)$$




What can I deduce?  
How can data help deduction?

$$\mathcal{C} \models \phi$$


MSc DSAI 2021

## Checking (Logic) Constraints




MSc DSAI 2021

## Checking (Logic) Constraints



MSc DSAI 2021


$$a_1(x) \rightsquigarrow f_1(x)$$




MSc DSAI 2021

$$a_2(x) \rightsquigarrow f_2(x)$$

points only




points and “logic rules”




MSc DSAI 2021

$$a_3(x) \rightsquigarrow f_3(x)$$

points only




points and “logic rules”




MSc DSAI 2021

$$a_4(x) \rightsquigarrow f_4(x)$$

points only




points and “logic rules”



MSc DSAI 2021

## Checking Constraints


FOL clause	Category	Average Truth Value
$a_1(x) \wedge a_2(x) \Rightarrow a_3(x)$	KB	98.26% (1.778)
$a_3(x) \Rightarrow a_4(x)$	KB	98.11% (2.11)
$a_1(x) \vee a_2(x) \vee a_3(x)$	KB	96.2% (3.34)
$a_1(x) \wedge a_2(x) \Rightarrow a_4(x)$	LD	96.48% (3.76)
$a_1(x) \wedge a_3(x) \Rightarrow a_2(x)$	ENV	91.32% (5.67)
$a_3(x) \wedge a_2(x) \Rightarrow a_1(x)$	ENV	91.7% (4.57)
$a_2(x) \wedge a_3(x) \Rightarrow a_4(x)$	LD	96.58% (4.13)
$a_3(x) \Rightarrow a_1(x) \vee a_2(x) \vee a_4(x)$	LD	99.7% (0.54)
$a_1(x) \wedge a_4(x)$	ENV	45.26% (5.2)
$a_2(x) \vee a_3(x)$	ENV	78.26% (6.13)
$a_1(x) \vee a_2(x) \Rightarrow a_3(x)$	ENV	68.28% (5.86)
$a_1(x) \wedge a_2(x) \Rightarrow \neg a_4(x)$	ENV	3.51% (3.76)
$a_1(x) \wedge \neg a_2(x) \Rightarrow a_3(x)$	ENV	27.74% (18.96)
$a_2(x) \wedge \neg a_3(x) \Rightarrow a_1(x)$	ENV	5.71% (5.76)



Search reduced to manifolds instead of the Boolean hypercube!


MSc DSAI 2021

## Checking Constraints in the Environment



MSc DSAI 2021

## Full Inference (formal+environment-based)



What about learning and inference with individuals?

MSc DSAI 2021

## Inference in Formal Logic

only labels are involved!

```
Domain(label="People")
Individual(label="Marco", "People")
Individual(label="Giuseppe", "People")
Individual(label="Michelangelo", "People")
Individual(label="Francesco", "People")
Individual(label="Franco", "People")
Individual(label="Andrea", "People")

Predicate(label="fatherOf", ("People", "People"))
Predicate(label="grandFatherOf", ("People", "People"))
Predicate(label="eq", ("People", "People"), function=eq)

Constraint("fatherOf(Marco, Giuseppe)")
Constraint("fatherOf(Giuseppe, Michelangelo)")
Constraint("fatherOf(Giuseppe, Francesco)")
Constraint("fatherOf(Franco, Andrea)")

Constraint("forall x: not fatherOf(x,x)")
Constraint("forall x: not grandFatherOf(x,x)")
```

MSc DSAI 2021

## Inference in Formal Logic

```
Constraint("forall x: forall y: fatherOf(x,y) -> not fatherOf(y,x)")
Constraint("forall x: forall y: grandFatherOf(x,y)
-> not grandfatherOf(y,x)")
Constraint("forall x: forall y: fatherOf(x,y) -> not grandFatherOf(x,y)")
Constraint("forall x: forall y: grandFatherOf(x,y) -> not fatherOf(x,y)")

Constraint("forall x: forall y: forall z: fatherOf(x,z) and fatherOf(z,y) ->
grandFatherOf(x,y)")
Constraint("forall x: forall y: forall z: (fatherOf(x,y) and not eq(x,z)) ->
not fatherOf(z,y)")
```

MSc DSAI 2021

## Inference in Formal Logic

```
grandFatherOf("Marco", "Michelangelo")
grandFatherOf("Marco", "Francesco")

Constraint("forall x: forall y: forall z: grandFatherOf(x,z) and
fatherOf(y,z) -> fatherOf(x,y)")
```

MSc DSAI 2021

## How does it work?

grounded pair	father	grandfather
(Marco, Giuseppe)	$w^f(\text{Mar}, \text{Giu})$	$w^{gf}(\text{Mar}, \text{Giu})$
(Marco, Francesco)	$w^f(\text{Mar}, \text{Fra})$	$w^{gf}(\text{Mar}, \text{Fra})$
...		

$$w^f(\text{Mar}, \text{Giu}) = 1 \quad w^f(\text{Giu}, \text{Mic}) = 1 \quad w^f(\text{Giu}, \text{Fra}) = 1 \quad w^f(\text{Fra}, \text{And}) = 1$$

learnable

MSc DSAI 2021

## How does it work?

Łukasiewicz logic

$$T(x, y) = \max\{0, x + y - 1\}$$

$$\Rightarrow \min\{1, 1 - x + y\}$$

$$w^f(\textit{Mar}, \textit{Giu}) = 1 \quad w^f(\textit{Giu}, \textit{Mic}) = 1 \quad w^f(\textit{Giu}, \textit{Fra}) = 1 \quad w^f(\textit{Fra}, \textit{And}) = 1$$

```
Constraint("forall x: forall y: forall z: fatherOf(x,z) and fatherOf(z,y) -> grandFatherOf(x,y)")
```

$$\sum_{X,Y,Z} \min\{1 - \max\{w^f(X, Z) + w^f(Z, Y) - 1, 0\} + w^{gf}(X, Y), 1\}$$

MSc DSAI 2021

## Full Inference on Individuals ( $X, x$ )

The diagram illustrates the integration of formal logic and neural networks for consistency constraints. It features two horizontal rows of formulas. The top row contains  $w^f(X, Y), w^{gf}(X, Y)$  on the left and 'from formal logic' on the right. The bottom row contains  $\omega^f(x, y), \omega^{gf}(x, y)$  on the left and 'from neural nets' on the right. A blue curved arrow originates from the text 'consistency constraints' in the middle and points to the bottom row. A vertical dotted arrow points downwards from the bottom row towards the bottom formula.

Complexity issues: the inference in the environment avoids massive exploration of the Boolean hypercube

MSc DSAI 2021


## Pattern Generation

Provide a constrained-based description  
of what you want to generate

MSc DSAI 2021

## Generating the next/previous char

$\forall x \text{ IsZero}(x) \Rightarrow \text{zero}(x)$   
 $\forall x \text{ IsOne}(x) \Rightarrow \text{one}(x)$   
 $\forall x \text{ IsTwo}(x) \Rightarrow \text{two}(x)$



$\forall x \text{ IsZero}(x) \Rightarrow \text{one}(\text{next}(x)) \wedge \text{two}(\text{previous}(x))$   
 $\forall x \text{ IsOne}(x) \Rightarrow \text{two}(\text{next}(x)) \wedge \text{zero}(\text{previous}(x))$   
 $\forall x \text{ IsTwo}(x) \Rightarrow \text{zero}(\text{next}(x)) \wedge \text{one}(\text{previous}(x))$

$$\begin{aligned} \forall x \text{ next}(\text{previous}(x)) &= x \\ \forall x \text{ previous}(\text{next}(x)) &= x \end{aligned}$$

MSc DSAI 2021

## Generating the next char (con't)

```
Domain("Images", data=X)
Predicate("zero", ("Images"), function=Slice(NN, 0))
Predicate("one", ("Images"), function=Slice(NN, 1))
Predicate("two", ("Images"), function=Slice(NN, 2))
PointwiseConstraint(NN, y, X)


Predicate("eq", ("Images", "Images"), function=eq)
Function("next", ("Images"), function=NN_next)
Function("previous", ("Images"), function=NN_prev)

Constraint("forall x: zero(x) -> one(next(x))")
Constraint("forall x: one(x) -> two(next(x))")
Constraint("forall x: two(x) -> zero(next(x))")
Constraint("forall x: zero(x) -> two(previous(x))")
Constraint("forall x: one(x) -> zero(previous(x))")
Constraint("forall x: two(x) -> one(previous(x))")

Constraint("forall x: eq(previous(next(x)),x)")
Constraint("forall x: eq(next(previous(x)),x)")
```

MSc DSAI 2021

## Generating the next char ... (con't)





MSc DSAI 2021

DATA STRUCTURES, CONSTRAINTS  
AND GRAPHIC NEURAL NETWORKS



MSc DSAI 2021


physicochemical behavior      Protein Interaction Network



What are the features? The atoms, the bonds?


## Graph Neural Networks

(Gori et al, TNN 2009)



## Constrained-based expression of data structures

$$\mathcal{G}(x) = \max(||x||_1 - \epsilon, 0)$$



$$\forall v \in V, \mathcal{G}(x_v - f_a(x_{ne[v]}, l_{ne[v]}, l_{(v, ch[v])}, l_{(pa[v], v)}, x_v, l_v | \theta_{f_a})) = 0$$

$v \in S \subseteq V$  auxiliary variable

$$\min_{\theta_{f_a}, \theta_{f_r}, X} \sum_{v \in S} L(f_r(x_v | \theta_{f_r}), y_v) \text{ any constraint can be incorporated on the vertexes}$$

$$\text{subject to } \mathcal{G}(x_v - f_a(x_{ne[v]}, l_{ne[v]}, l_{(v, ch[v])}, l_{(pa[v], v)}, x_v, l_v | \theta_{f_a})) = 0, \quad \forall v \in V$$


... data diffusion

## LEARNING OF CONSTRAINTS



MSc DSAI 2021


## Learning of constraints?



MSc DSAI 2021

## Formulation of Learning

$$f : \mathcal{X} \subset \mathbf{R}^d \rightarrow \mathcal{Y} \subset \mathbf{R}^n \text{ and } \phi : \mathcal{Y} \subset \mathbf{R}^n \rightarrow \mathcal{Z} \subset \mathbf{R}^m$$



$$\forall x \in \mathcal{X} : \bar{\phi}(f(x)) = \prod_{i=1}^m \phi_i(f(x)) = 0$$

$$\forall x \in \mathcal{X}_i : \phi_i(f(x)) = 0, \quad i = 1, \dots, \bar{m}$$


$$1 \leq \bar{m} \leq m \quad \mathcal{Q}_x = \{\mathcal{X}_i, \quad i = 1, \dots, \bar{m} \leq m\}$$

quantization over all the perceptual space

MSc DSAI 2021

## “Rules” and constraints

$$P_{R=i|X=x}(\phi \circ f) = \frac{e^{-\phi_i(f(x))}}{\sum_{j=1}^m e^{-\phi_j(f(x))}}$$



probabilistic normalization

$$\sum_{i=1}^m \int_{\mathcal{X}} dx p_X(x) P_{R=i|X=x}(\phi \circ f) = \int_{\mathcal{X}} dx \left( \sum_{i=1}^m \frac{e^{-\phi_i(f(x))}}{\sum_{j=1}^m e^{-\phi_j(f(x))}} \right) p_X(x) = 1$$

MSc DSAI 2021

## Maximum Mutual Information Principle

$$f^*(\bar{\phi}^*) = \arg \min_{(f,\phi) \in \mathcal{C}_{\mathcal{X}}(f, \bar{\phi}^*)} \alpha \|f\| \quad \text{parsimony}$$
$$\bar{\phi}^*(f^*) = \arg \min_{(f,\phi) \in \mathcal{C}_{\mathcal{X}}(f^*, \bar{\phi})} (\beta \|\bar{\phi}^*\| - I_{X,R}(\bar{\phi}^* \circ f))$$

↑  
information-based index

MSc DSAI 2021

## MMI Stage-based learning

$$\begin{aligned}\phi_0, & [f_0^*(\bar{\phi}_0), \phi_1^*(f_0^*)], \\ & [f_1^*(\bar{\phi}_1^*), \phi_2^*(f_1^*)], \\ & [f_2^*(\bar{\phi}_2^*), \phi_3^*(f_2^*)], \\ & \dots \\ & [f_{\kappa-1}^*(\bar{\phi}_{\kappa-1}^*), \phi_\kappa^*(f_{\kappa-1}^*)], \\ & [f_\kappa^*(\bar{\phi}_\kappa^*), \phi_{\kappa+1}^*(f_\kappa^*)].\end{aligned}$$

$$\begin{aligned}f^* &= \lim_{\kappa \rightarrow \infty} f_\kappa^*(\bar{\phi}_\kappa^*) \\ \phi^* &= \lim_{\kappa \rightarrow \infty} \phi_\kappa^*(f_{\kappa-1}^*)\end{aligned}$$

MSc DSAI 2021

## Developmental function

$$D(f, \phi) = \|(f, \phi)\| - I_{X,R}(\phi \circ f)$$

$$\begin{pmatrix} f^* \\ \phi^* \end{pmatrix} = \arg \min_{(f, \phi) \in \mathcal{C}_X} D(f, \phi)$$


$$\bar{\phi}(f(x)) = \bar{\phi}_s(f(x)) \cdot \bar{\phi}_l(f(x))$$

given constraints learned constraints

Lagrangian approach by using neural nets


MSc DSAI 2021

## Neural-Based Solution



DeepMind, 28 May 2019

Looking for explanations ...



## Conclusions

- Probability distributions and Lagrange multipliers, reactions of constraints ... links with Backprop
- Bridging symbols and sub-symbols (logic representations & learning )
- Inference in the environment, full inference (searching in manifolds instead of the Boolean hypercube)
- GNN as a special case
- Learning of constraints and explanation
- Time and developmental issues (topics in Developmental Psychology), biological plausibility