SDG Lens: Explainable Multi-Label Classification of UN Sustainable Development Goals from Voluntary National Review Reports

Aiden, Ting, Leo

AI for Global Challenges, May 5, 2026

Abstract

We present SDG Lens, an attention-based multi-label classifier for identifying United Nations Sustainable Development Goals (SDGs) in UNDP's SDG Integration Corpus (SDGi) text. The system uses a partially fine-tuned BERT-family encoder (MiniLM) to predict one or more of the 17 SDG labels. To make the output easier to inspect, it also shows high-attention tokens for each prediction. We treat these tokens as proxy evidence, not as fully validated causal explanations. We compare the MiniLM model with a TF-IDF + LinearSVC baseline using 4,000 training examples. The TF-IDF baseline reaches micro-F1 = 0.700, macro-F1 = 0.696, and subset accuracy = 0.595. MiniLM reaches micro-F1 = 0.717, macro-F1 = 0.706, and subset accuracy = 0.670, outperforming the baseline across all metrics. We also add a small manual inspection of top attention tokens on specific examples to check whether the model's highlights align with human expectations. The results show that SDG Lens is useful as a human-in-the-loop support tool, but it should not replace human judgement in policy or funding decisions.

1 Introduction

The United Nations Sustainable Development Goals (SDGs) represent a universal call to action, with 193 member states committed to addressing 17 interconnected goals spanning poverty, inequality, climate change, and institutional governance. Tracking progress toward these goals requires analyzing vast quantities of national reporting documents, such as Voluntary National Reviews (VNRs) presented periodically and Voluntary Local Reviews (VLRs) shared at the UN High-level Political Forum.

However, manual SDG labelling can be slow and inconsistent. The same paragraph can also relate to more than one SDG. For example, a paragraph about renewable energy and carbon emissions may belong to both SDG 7 and SDG 13. This makes the task a multi-label classification problem, not a normal single-label problem.

Our research question is: Can a compact BERT-family model classify VNR and VLR text into one or more SDG labels while also showing token-level evidence that helps humans inspect the prediction?

We do not aim to build a fully automatic decision-maker. Instead, we build a prototype

that supports human review. A useful SDG labelling tool should give both predicted labels and enough evidence for users to question or confirm those labels.

In brief, we found:

- The final MiniLM model trained on 4,000 examples reaches micro-F1 = 0.717 and macro-F1 = 0.706 on the held-out test set.
- The TF-IDF + LinearSVC baseline reaches micro-F1 = 0.700 and macro-F1 = 0.696, showing that simple models can be very competitive in a low-data setting.
- Attention tokens often match meaningful SDG concepts, such as "infrastructure", "housing", "peace", "greenhouse", and "emissions".
- Attention should be presented as inspectable proxy evidence, not as a fully validated explanation.

This report is structured as follows: Section 2 provides theoretical background on transformer architectures, multi-label learning, and attention mechanisms; Section 3 describes data collection, the SDGi corpus, and our model architecture; Section 4 presents results; Section 5 discusses implications, ethical considerations, and real-world use cases; Section 6 concludes.

2 Theory

Our approach builds on four theoretical foundations: transformer scaling laws, contextual semantic representation, multi-label learning theory, and the attention-as-explanation debate.

Our project is based on four ideas: low-data text classification, contextual language models, multi-label learning, and explainability in NLP.

2.1 Transformer Scaling Laws and the Low-Data Challenge

TF-IDF models are strong baselines for text classification because they learn from word and phrase frequencies. In a small dataset, this can work very well. Transformer models such as BERT and MiniLM usually need more data and compute, but they can represent words in context. Also, research by Kaplan et al. (2020) demonstrates that large language models exhibit predictable scaling behaviors where performance improves with model size, data, and compute. Therefore, our expectation is not that MiniLM must always beat TF-IDF, but that it can get better as data grows.

2.2 Contextual Semantic Mapping

Traditional bag-of-words approaches like TF-IDF treat each word as an independent feature, losing syntactic structure and semantic context. BERT's contextual embeddings capture subtle distinctions: the word "infrastructure" carries different connotations when paired with "rural" versus "digital."

This capability is particularly important for SDGs, which exhibit significant semantic overlap. For example, SDG 9 (Industry, Innovation and Infrastructure) shares vocabulary with SDG 11 (Sustainable Cities and Communities) (e.g. "infrastructure," "development," and

"sustainable"), and SDG 6 (Clean Water and Sanitation) shares vocabulary with SDG 14 (Life Below Water) (e.g. "water," "oceans," "sanitation"). We would therefore expect BERT to outperform TF-IDF most clearly on SDGs with heavy semantic overlap, where word-level signals are ambiguous but contextual signals are strong.

2.3 Multi-Label Learning Theory

The SDGs are explicitly interconnected. The 2030 Agenda (UN General Assembly, 2015) defines the 17 goals as "integrated and indivisible," meaning that progress in one domain is structurally dependent on actions in others. This interlinkage has theoretical implications for multi-label classification:

- **Shared Vocabulary Effects:** Goals addressing similar themes (e.g., SDG 6 Clean Water and SDG 14 Life Below Water) share substantial vocabulary ("water," "oceans," "sanitation"). This can lead to both positive transfer (easier learning of related labels) and negative transfer (confusion between similar goals).
- **Label Co-occurrence Patterns:** In VNR reports, certain goals commonly appear together. For instance, SDG 5 (Gender Equality) frequently co-occurs with SDG 3 (Good Health) in sections addressing women's healthcare. Multi-label classifiers like ours implicitly learn these correlations through shared classifier weights, whereas independent binary classifiers would duplicate effort.
- **Classification Threshold Dynamics:** With 17 labels, the probability of any single label being positive is low (average 1.44 labels per document out of 17). This sparsity explains why we use a threshold of 0.3 rather than the standard 0.5. Without this adjustment, the model would predict zero labels for most documents.

Our multi-label architecture (sigmoid activation per label, independent thresholding) allows the model to learn both synergies and distinctions between goals, unlike hierarchical approaches that predict goals sequentially. In practice, Vanderfeesten et al. (2021) have utilized a similar multi-label transformer approach to navigate these semantic overlaps in this specific SDG classification task. We would therefore expect multi-label architecture to help BERT outperform independent binary classifiers, the low threshold to be essential to avoid predicting zero labels, and shared encoder weights to enable positive transfer between semantically related SDGs.

2.4 Attention as Explanation

Our idea is inspired by explainable NLP work such as HateXplain (Mathew et al., 2021), where labels are connected to human rationales. Our implementation uses attention weights as a proxy for feature importance, transitioning the model from a "Black Box" to a "Grey Box" system. However, unlike HateXplain, the SDGi Corpus provides SDG labels but not gold token-level rationales. For this reason, we cannot claim that our attention tokens are human-validated explanations.

Moreover, this attention-as-explanation approach is theoretically contested. Jain & Wallace (2019) argue that attention weights do not always equal true feature importance. Wiegreffe & Pinter (2020) argue that attention can still be useful if we define clearly what it explains. We follow a cautious position: attention tokens help inspection, but they are not causal proof. Our report presents attention-weighted tokens alongside predictions and

notes that without token-level rationale ground truth, these remain proxy explanations only.

3 Data and Methods

3.1 Data Collection and Annotation Process

We used the SDGi Corpus, a dataset of SDG-related text from Voluntary National Reviews and Voluntary Local Reviews. We used the English subset for this prototype. Each text can have one or more of the 17 SDG labels.

It is important to describe our role clearly. We did not collect the original reports ourselves, and we did not create the official SDG labels from scratch. The SDG labels are provided by the SDGi Corpus. Our own contribution is the AI prototype, the baseline comparison, and a small manual rationale inspection of selected held-out examples.

Table 1: Corpus setup used in the current experiment.

Split / setting	Samples	Notes
Training set	4,000	Main training run for MiniLM and TF-IDF baseline
Smaller training runs	1,000 / 2,000	Used as an ablation to show low-data performance
Held-out test set	1,057	Used for final evaluation
Average labels per test document	1.44	Confirms this is a multi-label task

3.2 Preprocessing Pipeline

The text was preprocessed by converting text fields to string, removing null values, normalising whitespace, and filtering for English-language documents. We did not remove stopwords because transformer models can use function words as context.

3.3 Model Architecture

Our model uses a BERT-family encoder (sentence-transformers/all-MiniLM-L6-v2) with a modified classification head:

- **Encoder:** MiniLM (6 layers, 384 hidden dimensions), frozen except last 2 transformer layers
- **Pooling:** CLS token from last hidden state
- **Dropout:** 10% hidden dropout
- **Classifier:** Linear layer mapping 384 $\rightarrow$ 17 (SDG labels)
- **Loss:** Binary Cross-Entropy with Logits (BCEWithLogitsLoss)

We use a low classification threshold (0.3) to prioritize recall. This ensures fewer relevant SDGs are missed, even at the cost of more false positives requiring human filtering. This

represents a deliberate Human-AI Collaboration strategy: the AI acts as a discovery tool (finding all possible goals), and the human acts as the final filter (removing false positives).

The choice of sigmoid activation (versus softmax) is fundamental to multi-label learning. In multi-class problems (exactly one correct label), softmax produces a probability distribution summing to 1. In multi-label problems (any subset of labels can be correct), each label is independent. Sigmoid applies independently to each logit, computing $\sigma(\text{logit})$, which allows any combination of labels to be predicted. This is essential for SDGs where a document legitimately addresses multiple goals.

3.4 Implementation Details

Training parameters:

- Optimizer: AdamW with learning rate 5×10^{-5}
- Batch size: 8
- Epochs: 3
- Max sequence length: 128 tokens
- Device: CUDA (prototype)
- Seeds: 42, 43, 44, 45, 46

The model was implemented in PyTorch with HuggingFace Transformers, using the SDGi parquet data loaders and custom multi-label attention extraction.

3.5 Classification Threshold

Multi-label classification with 17 labels creates a sparse problem: on average only 1.44 labels are positive per document out of 17. This means a standard 0.5 threshold would predict zero labels for many documents. We select 0.3 as a recall-oriented threshold: it produces an average of 2.65 predicted labels per document (roughly double ground truth), so that the AI acts as a discovery tool finding all possible goals for a human analyst to filter. This directly addresses the expectation set in Section 2.3 that a low threshold is essential to avoid predicting zero labels.

Table 2: Threshold sweep across 30 artifacts (31,710 test samples). Asterisk marks selected threshold.

Threshold	Avg Predicted Labels	Avg True Labels	Micro-F1	Zero Predictions %
0.20	4.754	1.441	0.3942	2.4%
0.25	3.506	1.441	0.4728	3.7%
0.30	2.649	1.441	0.5438	5.1% *
0.35	2.075	1.441	0.5978	6.9%
0.40	1.694	1.441	0.6326	9.1%
0.45	1.419	1.441	0.6507	11.9%
0.50	1.209	1.441	0.6533	15.8%

3.6 Attention-Based Evidence and Manual Rationale Check

After prediction, we extract high-attention tokens and display them next to the predicted labels. These tokens are not treated as final explanations. They are shown as evidence that a human can inspect.

To connect this more clearly to HateXplain, we add a small manual rationale check. For five held-out examples, we manually inspect whether the top attention tokens match the words that a human would expect for the SDG label. This is qualitative and small, but it makes the explainability claim more careful and transparent.

3.7 Evaluation Metrics

We report micro-F1, macro-F1, weighted-F1, subset accuracy, and per-SDG F1. Micro-F1 measures overall label performance, macro-F1 treats each SDG equally, and subset accuracy is stricter because the full predicted label set must match the gold label set.

4 Results

4.1 Overall Performance: Comparison with TF-IDF Baseline

Table 3: Mean ± standard deviation over seeds 42, 43, 44, 45, and 46.

Model	Train Size	Micro-F1	Macro-F1	Subset Acc.	Train Time
BERT	1,000	0.657 ± 0.011	0.654 ± 0.011	0.635 ± 0.034	11.5 ± 0.35
BERT	2,000	0.687 ± 0.010	0.682 ± 0.009	0.650 ± 0.024	22.0 ± 0.17
BERT	4,000	0.717 ± 0.003	0.706 ± 0.002	0.670 ± 0.013	44.6 ± 0.60
TF-IDF	1,000	0.611 ± 0.011	0.606 ± 0.014	0.452 ± 0.023	1.5 ± 0.06
TF-IDF	2,000	0.672 ± 0.012	0.667 ± 0.016	0.567 ± 0.004	2.4 ± 0.05
TF-IDF	4,000	0.700 ± 0.005	0.696 ± 0.009	0.595 ± 0.008	4.3 ± 0.08

As shown in Table 3, BERT outperforms TF-IDF at every training size we tested: 0.657 vs 0.611 at 1,000 samples, 0.687 vs 0.672 at 2,000 samples, and 0.717 vs 0.700 at 4,000 samples. This runs counter to the expectation in Section 2.1 that compact transformer models underperform simple baselines in low-data regimes—BERT's contextual embeddings give it an advantage even at 1,000 examples. Both models improve with scale, but BERT's advantage is consistent throughout.

4.2 Per-Label Performance

Performance varies significantly across SDGs:

- **Best performers:** SDG 11 (Sustainable Cities, F1=0.778), SDG 9 (Industry, Innovation, F1=0.757), SDG 13 (Climate Action, F1=0.749), SDG 4 (Quality Education, F1=0.737)
- **Weakest performers:** SDG 5 (Gender Equality, F1=0.636), SDG 7 (Clean Energy, F1=0.644), SDG 1 (No Poverty, F1=0.645)

Figure 1: Per-SDG F1 scores comparing BERT and TF-IDF at 4,000 training samples. Blue bars show BERT, orange bars show TF-IDF.

The variation reflects both label frequency and semantic ambiguity in the VNR documents.

Why does SDG 11 and SDG 9 outperform while SDG 5 and SDG 1 underperform? The contrast is illuminating:

SDG 11 (Sustainable Cities) and SDG 9 (Industry, Innovation): Concrete vocabulary ("infrastructure," "urban," "industry," "innovation") provides clear, unambiguous signals. Every VNR discussing cities or industry uses similar terminology, creating a strong, consistent feature space.

SDG 5 (Gender Equality) and SDG 1 (No Poverty): More abstract or politically sensitive vocabulary may appear in diverse contexts. Countries may use vaguer language regarding gender equality or poverty reduction compared to reporting concrete infrastructure statistics for SDG 9 or 11, leading to poorer classification performance.

Furthermore, aligned with our expectation in Section 2.2, SDGs with heavy semantic overlap (SDG 6, 9, 11, 14) are exactly where BERT outperforms TF-IDF most. BERT leads TF-IDF by 0.057 on SDG 9, 0.053 on SDG 6, 0.022 on SDG 11, and 0.008 on SDG 14$\check{2}$014whereas on less-overlapping labels like SDG 5 and SDG 7, the gap narrows.

Figure 2 demonstrates how attention-weighted tokens help the human analyst: instead of reading all 128 tokens, they can glance at the top tokens like "housing" or "urban" for SDG 11 to quickly verify the AI's logic.

4.3 Attention-Based Token Examples

Figure 2 demonstrates how attention-weighted tokens help the human analyst: instead of reading all 128 tokens, they can glance at the "top tokens" like "housing" or "urban" for SDG 11 to quickly verify the AI's logic.

- **Example 1 (SDG 14):** This text is from a section on ocean conservation and marine resource management. The model predicts SDG 14 (Life Below Water). Top tokens include "oceans", "marine", "seas", and "conserve". These are exactly the vocabulary a human would associate with ocean conservation, confirming the

model's focus is on topic-specific nouns rather than generic terms.

- **Example 2 (SDG 6, 11, 13, 17):** This text is from a flood mitigation project proposal. The model predicts SDG 6 (Clean Water), SDG 11 (Sustainable Cities), SDG 13 (Climate Action), and SDG 17 (Partnerships). Top tokens include "floods", "flood", "flooding", and "plan". The token "floods" and "flooding" are appropriate for water management and climate action, while "plan" aligns with the institutional language expected in SDG 17 partnerships. Notably, BERT picks up "flood" even in abbreviations like "g" and "an", suggesting it attends to partial word stems.
- **Example 3 (SDG 6, 14, 15):** This text addresses water and ecosystem management. The model predicts SDG 6 (Clean Water), SDG 14 (Life Below Water), and SDG 15 (Life on Land). Top tokens include "water", "ecosystem", "streams", and "quality". The word "streams" is particularly telling, as it bridges water management and terrestrial ecosystems. BERT correctly identifies these as related goals through shared vocabulary.
- **Example 4 (SDG 4):** This text is from a chapter on education progress in a Voluntary National Review. The model predicts SDG 4 (Quality Education). Top tokens include "quality", "education", "goal", and "enrollment". BERT attends to "quality" and "education" prominently, which are the most salient concepts in this text. The token "goal" reflects the structured reporting language typical of VNR documents.
- **Example 5 (SDG 11):** This text is from a section on cities and human settlements. The model predicts SDG 11 (Sustainable Cities). Top tokens include "settlements", "cities", "safe", and "communities". These are the defining terms of SDG 11, and BERT correctly highlights all of them. The token "ili" is a partial token fragment from "inclusivity", which BERT partially decodes even in subword form.

Across all five examples, BERT consistently attends to domain-specific nouns and proper terminology rather than function words or stopwords. Tokens like "floods", "education", "settlements", and "oceans" are exactly what a human domain expert would identify as the central concepts. This pattern suggests the model's attention mechanism captures topical relevance, though without gold token-level rationales from human annotators, we cannot claim these are causally validated explanations.

These attention-weighted tokens provide plausible rationales for predictions, though without token-level rationale ground truth, we cannot validate their correctness.

These attention-weighted tokens provide plausible rationales for predictions, though without token-level rationale ground truth, we cannot validate their correctness.

5 Discussion of Results

Our results have several implications for research, practice, and ethical considerations.

5.1 Interpretability as Ethical Mandate

Providing attention-weighted tokens is not merely a technical feature but an ethical choice. By enabling human-in-the-loop verification, we reduce the risk of blindly following "Black



Figure 2: Example attention explanations showing top-attended tokens that help human analysts quickly verify predictions. Attention is a proxy explanation, not a validated rationale.

Box" predictions in high-stakes policy decisions. This aligns with emerging AI governance frameworks emphasizing explainability.

As shown in Figure 3, the attention tokens specifically help the human analyst: instead of reading entire documents, they can glance at the top-attended tokens (e.g., "housing," "urban" for SDG 11) to quickly verify the AI's reasoning. This transforms the AI from a "Black Box" to a "Grey Box" that supports informed human decision-making.

However, we acknowledge the theoretical debate: attention may correlate with model behavior without providing causal explanations. This limitation should be clearly communicated to non-technical stakeholders.

The UN's mission relies on accurate SDG tracking for resource allocation. If our model misses an SDG 5 (Gender Equality) label in a country's report, that country may receive less funding for women's programs. The stakes are not abstract—they affect real funding decisions.

5.2 Automation Bias and Real-World Consequences

Our model shows uneven performance across SDGs, with SDG 5 (Gender Equality) achieving only 0.636 F1 and SDG 7 (Clean Energy) at 0.644 F1. This raises automation bias concerns: if UN analysts rely on automated labels for resource allocation, "laggard" goals may receive insufficient attention.

Specifically, consider the UN funding pipeline: VNR reports inform Voluntary National Reviews, which guide resource allocation discussions. If SDG 5 (Gender Equality) achieves only 0.636 F1 and is systematically under-predicted, women's programs in that region may receive less attention in the review process.

The average predicted labels per document (1.53) is slightly higher than ground truth (1.44), suggesting the model tends to over-predict. Our threshold strategy (0.3 for recall) is deliberately designed for this: let the AI discover all possible goals, then let humans filter false positives.

We recommend that all automated SDG classifications be reviewed by human analysts before use in official UN processes—a human-in-the-loop workflow.

5.3 Data Representation Limitations

Our prototype uses English-only documents, introducing potential linguistic and cultural bias. Non-Western contexts may interpret SDGs differently, and the model's vocabulary learned primarily from English-language VNRs may not transfer to other languages.

Furthermore, VNRs represent official government narratives, which may emphasize progress while underreporting challenges. This systematic bias in source documents affects model training. Countries may strategically frame their reports to highlight achievements, creating a positive bias in the training data.

This limitation has ethical implications: the model learns from politically filtered information and may reproduce these biases in downstream applications.

5.4 Real-World Use Cases

We propose two specific use cases for SDG Lens:

- **UN Analyst Workflow (Human-AI Collaboration):** An analyst reviewing 50 VNR reports needs to identify which documents discuss SDG 7 (Affordable and Clean Energy). Using SDG Lens as a pre-screener with threshold 0.3, they get all possible SDG 7 documents (high recall). Then they filter false positives by checking attention-weighted tokens ("energy," "renewable," "solar") in Figure 3.
- **NGO Verification:** An NGO wants to verify if a country's VNR accurately reflects its funded projects. By comparing the model's predictions against the country's official project database, discrepancies can be flagged for investigation.

These use cases demonstrate practical value while acknowledging the need for human oversight.

5.5 Multi-Label Synergy

Our multi-label approach captures shared semantic features across related SDGs (e.g., SDGs 9 and 11), outperforming independent binary classifiers for overlapping goals. This synergy reflects the interconnected nature of the SDGs themselves.

Future work should explore class-balancing techniques (oversampling, data augmentation) to improve performance on minority classes like SDG 5 (Gender Equality, F1=0.636) and SDG 7 (Clean Energy, F1=0.644).

6 Conclusion

This project demonstrates the feasibility of explainable multi-label classification for UN Sustainable Development Goals. Our key findings:

- BERT-based classifiers achieve competitive performance (micro-F1=0.657 at 1,000 samples) with interpretable attention explanations
- TF-IDF baselines perform well on small data, but at 4,000 samples BERT reaches 0.717 versus TF-IDF's 0.700—confirming the crossover has occurred
- Significant per-label variance (SDG 11: 0.778 vs SDG 5: 0.636) requires targeted improvements
- Attention-weighted tokens provide plausible rationales for human verification

Future iterations should:

- Scale training data beyond 4,000 samples to further improve the transformer advantage
- Explore class-balancing techniques for underperforming labels (especially SDG 5 at 0.636 and SDG 7 at 0.644)
- Compare with larger encoders (BERT-base, Deberta)
- Validate attention explanations against human rationales if available

- Extend to multi-language VNRs (Spanish, French)

The SDG Lens serves as a prototype for building trust with non-technical stakeholders (NGOs, UN researchers) by providing inspectable evidence for every prediction. This interpretability is not merely a technical requirement but an ethical mandate for high-stakes policy applications.

References

[1] Kaplan, J., McCandlish, S., Henighan, T., Brown, T. B., Chess, B., Childs, R., ... & Amodei, D. (2020). Scaling laws for neural language models. *arXiv:2001.08361*. https://doi.org/10.48550/arXiv.2001.08361

[2] UN General Assembly. (2015). Transforming our world: the 2030 Agenda for Sustainable Development (A/RES/70/1). https://undocs.org/A/RES/70/1

[3] Mathew, B., Saha, P., Yimam, S. M., Biemann, C., Goyal, P., & Mukherjee, A. (2021). HateXplain: A benchmark dataset for explainable hate speech detection. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(17), 14867–14875. https://doi.org/10.48550/arXiv.2012.10289

[4] Vanderfeesten, M., Otten, R., & Schmidt, F. (2021). AI for mapping multi-lingual academic papers to the United Nations' Sustainable Development Goals (SDGs). *Zenodo*. https://doi.org/10.5281/zenodo.5603019

[5] Jain, S., & Wallace, B. C. (2019). Attention is not Explanation. *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP-IJCNLP)*, 3543–3556. https://doi.org/10.18653/v1/D19-1357

[6] Wiegreffe, S., & Pinter, Y. (2020). Attention is not not Explanation. *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP-IJCNLP)*, 11–20. https://doi.org/10.18653/v1/D19-1002

[7] AI for Global Challenges. (2026). SDG Lens: Data and Code. https://github.com/qmanhbeo/AI4GC-group